RTNet neural network exhibits the signatures of human perceptual decision making

Farshad Rafiei*, Medha Shekhar* & Dobromir Rahnev

School of Psychology, Georgia Institute of Technology, Atlanta, GA

Keywords: Deep neural networks, reaction time, perceptual decision making, sequential

sampling, confidence

Correspondence

Farshad Rafiei

Georgia Institute of Technology

654 Cherry Str. NW

Atlanta, GA 30332

E-mail: farshadrafiei3@gmail.com

Abstract

Convolutional neural networks show promise as models of biological vision. However, their

decision behavior, including the facts that they are deterministic and use equal number of

computations for easy and difficult stimuli, differs markedly from human decision-making, thus

limiting their applicability as models of human perceptual behavior. Here we develop a new

neural network, RTNet, that generates stochastic decisions and human-like response time (RT)

distributions. We further performed comprehensive tests that showed RTNet reproduces all

foundational features of human accuracy, RT, and confidence and does so better than all

current alternatives. To test RTNet's ability to predict human behavior on novel images, we

collected accuracy, RT, and confidence data from 60 human subjects performing a digit

discrimination task. We found that the accuracy, RT, and confidence produced by RTNet for

individual novel images correlated with the same quantities produced by human subjects.

Critically, human subjects who were more similar to the average human performance were also

found to be closer to RTNet's predictions, suggesting that RTNet successfully captured average

human behavior. Overall, RTNet is a promising model of human response times that exhibits

the critical signatures of perceptual decision making.

32
33

Introduction

Traditional cognitive models of perceptual decisions[1–4] are able to account for the major

features of human perceptual decision making, but do not operate on the level of images.

Recently, convolutional neural networks (CNNs) have reached and sometimes exceeded

human-level performance for novel images[5,6]. In addition, these networks naturally handle

multi-choice categorization tasks and are promising models of the processing related to object

recognition in the ventral visual stream of the human brain[5,7,8]. However, traditional CNNs'

decision behavior differs markedly from human decision behavior, thus limiting their

applicability as models of human perceptual decision making. Specifically, unlike humans,

traditional CNNs are both deterministic (i.e., they always give the same response for a given

stimulus) and static (i.e., they are invariant in the amount of time spent on processing different

images and thus always produce the same response time).

Several lines of work have tried to build mechanisms into neural networks to make them

stochastic and dynamic[9–13]. Early research on shallow multi-layer perceptron models was able

to create models that were both stochastic and dynamic. These models were able to explain

human behavior on simple cognitive tasks[14–16]. However, these models are not image-

computable (i.e., they cannot handle complex input such as images). More recent work has

produced image-computable dynamic networks capable of generating response times (RTs) via

mechanisms that allow computational resources utilized for the decision to increase with time[9–

[11], thus allowing responses to evolve through each processing step. However, although these

networks can mimic the speed-accuracy trade off (SAT) found in humans, they are deterministic

and their internal mechanisms are not well supported by existing models of human perception

and cognition. Finally, another class of models generates RTs using the biologically-inspired

mechanism of recurrent processing[17–21], which allows flexible modulation of a finite network's

computational power[10,22]. Nevertheless, these networks are also deterministic and have not

been evaluated on the whole range of choice, RT, and confidence effects shown by humans.

Here we combine modern CNNs with traditional cognitive models to create a model that is

image-computable, stochastic, and dynamic, and can reproduce the critical features of

perceptual decision making for novel images. The model, which we call RTNet for its ability to

model human RTs, features a deep convolutional neural network with noisy weights and

processes a given image several times using a different random sample of these weights in each

processing step (

A). These weights are sampled from a Bayesian neural network (BNN) that estimates a posterior

distribution over the best network parameters learnt during training. By sampling from these

noisy weight distributions at each processing step, the network's units produce variable

responses to the same input that mimic the randomness of neural responses. After each

processing step, RTNet accumulates the output corresponding to each choice until one of the

choices reaches a predefined threshold. The model therefore has a strong conceptual

relationship to race models from the cognitive literature on decision-making, which postulate a

noisy accumulation process with separate accumulators for each choice[23–25]. By combining the

image-computability of CNNs with traditional models of perception, we expect RTNet to be

applicable across a wide range of perceptual tasks as well as reproduce the basic features of

human perceptual decision making.

To assess a model's ability to make decisions similar to humans, one needs to test whether it

produces the foundational features of human decision-making[26]. Human perceptual decision

making has been studied primarily in the context of 2-choice tasks using artificial stimuli such as

Gabor patches or random dot motion[27] (although notable exceptions exist where N-choice

tasks are used[28–31]). Therefore, we first replicate the known decision-making signatures from 2-

choice tasks using an 8-choice task with meaningful images (hand-written digits taken from the

MNIST dataset[32]). We manipulate 1) task difficulty by adding two different levels of noise to the

images, and 2) speed-accuracy trade off (SAT) by asking subjects to emphasize either the

accuracy or speed of their responses on different trials.

Critically, we test RTNet under the same conditions and with the same images seen by the

human subjects to explore the model's capability to produce behavior similar to human agents.

Beyond testing whether RTNet can reproduce the basic features of human perceptual decision

making, we also explore whether the accuracy, RT, and confidence produced by RTNet for

individual images predict the corresponding quantities for humans on the same images. Finally,

throughout the paper, we compare the behavior of RTNet to that of three other popular

dynamic CNNs. The first model is Parallel Cascaded Network[9] (CNet; Figure 1B), which is

currently thought to be the best image-computable model that can mimic the SAT

characteristics of humans[12]. The second is BLNet[10], which belongs to a class of models that uses

recurrent processing and has been validated on a range of perceptual tasks involving

manipulations beyond SAT (Figure 1C). The third is Multi-Scale Dense Networks[13] (MSDNet;

D), which implements one of the most common ways for generating RTs in image-computable

models. We find that RTNet's behavior mimics human perceptual decision making better than

all three of these CNNs.

Results

We collected data from 60 human subjects who performed a digit discrimination task (**Error!**

Reference source not found.A). The experiment was a 2 x 2 design with factors of task difficulty

(easy vs. difficult images) and speed pressure (speed vs. accuracy focus). Each condition

consisted of 120 unique images, and each subject made a decision regarding each image exactly

twice, which allowed us to determine the level of stochasticity in human behavior (**Error!**

Reference source not found.B). Overall, each subject completed 960 trials in total.

Having obtained these human data, we compared the human behavior to that of RTNet, CNet,

BLNet, and MSDNet. Both RTNet and MSDNet were implemented using the eight-layer AlexNet

architecture with five convolutional layers followed by three fully connected layers[33]. CNet was

based on the architecture of ResNet18 since the implementation of this model relies on

residual blocks and skip connections. Finally, for BLNet, we used the original architecture

implemented by Spoerer et al.[10], which consists of seven convolutional layers and a fully

connected readout layer. Given that humans and deep learning models are impacted differently

by stimulus noise[34,35], we adjusted the noise levels of the images seen by each network to

match their overall accuracy to the accuracy produced by the human subjects. In addition, to

allow the networks to reproduce the speed-accuracy trade off observed in the human data, we

adjusted the threshold value that triggers a decision for each CNN as to match the human

accuracy separately in the speed- and accuracy-focused conditions. To improve the

correspondence between the model predictions and the human data, we trained 60 instances

of each model (by only changing the random initialization before training began) and analyzed

the data produced by these 60 instances in equivalent manner to the 60 human subjects.

<u>Signatures of human perceptual decision making</u>

We examined six foundational signatures of human perceptual decision making that have

already been established in studies of 2-choice tasks: 1) Human decisions are stochastic,

meaning that the same stimulus can elicit different responses on different trials[36,37], 2)

increasing speed stress shortens RT but decreases accuracy (speed-accuracy trade off)[26,38,39], 3)

more difficult decisions lead to reduced accuracy and longer RT[26,40,41], 4) RT distributions are

right-skewed, and this skew increases with task difficulty[26], 5) RT is lower for correct than for

error trials[41–45], and 6) confidence is higher for correct than for error trials[46]. For each of these

signatures, we confirmed that the signature also occurs for our 8-choice task with naturalistic

images, and then tested whether RTNet, CNet, BLNet and MSDNet exhibit the same signature.

Stochasticity of human decisions

A central feature of human behavior is that human decisions are stochastic such that the same

stimulus can elicit different responses on different trials[36,37,47]. We quantified the level of

stochasticity in each condition by presenting each image twice. We first confirmed that our

estimates of human stochasticity were robust and reliable by showing that similar estimates are

obtained when analyzing the odd vs. even numbered subjects (Supplementary Figure 1). On

average across all conditions, 36% of all images received different responses on the two

presentations. A one-sided Wilcoxon signed-rank test showed that this observed frequency of

stochastic responses is indeed significantly greater than zero (Z(59) = 32896, p < 0.001, rank-

biserial correlation (effect size) = 1) (**Error! Reference source not found.**A). A repeated

measures ANOVA with factors stimulus difficulty (easy vs. difficult) and SAT (speed vs. accuracy

stress) revealed that stochasticity increased with both higher task difficulty (F(1,63) = 871.869,

p < 0.001, η_p^2 = 0.933) and higher speed pressure (F(1,63) = 9.135, p = 0.004, η_p^2 = 0.127).

Since RTNet uses a random sample of weights for each processing step, it naturally produces

stochastic decisions too. On average across all conditions, RTNet produced different responses

on the two image presentations on 20% of trials (One-sided Wilcoxon signed-rank test: Z(59) =

2892, p < 0.001, rank-biserial correlation (effect size) = 1; **Error! Reference source not found.**B).

This level of stochasticity was lower than for human subjects and stems from the fact that the

variability in the weights was fixed a priori by training a Bayesian neural network. However, it is

possible for RTNet to match the levels of stochasticity observed in humans by increasing the

variability of the network's weights. Indeed, we confirmed that the stochasticity of the

decisions made by RTNet can be robustly manipulated by changing the variability of its weight

distributions (Supplementary Figure 2). Further, the stochasticity in human decisions partially

stems from factors such as fluctuations in attention, arousal, or serial dependence[36,37,47,48],

which we did not attempt to model. Because of these considerations, we did not try to match

RTNet to the exact level of human decision stochasticity observed in the data. Critically,

however, RTNet exhibited the same features such that stochasticity increased with higher task

difficulty (F(1,59) = 120.124, p < 0.001, η_p^2 = 0.671) and higher speed stress (F(1,59) = 87.730, p

< 0.001, η_p^2 = 0.598).

On the other hand, for a fixed level of speed-accuracy trade off, CNet, BLNet and MSDNet are

fully deterministic and do not exhibit any decision stochasticity (**Error! Reference source not**

found.C-E). We note that it should be possible to add noise in the weights of these models to

induce stochastic decisions, but such noise would decrease their accuracy much more than it

affects RTNet given that only RTNet is able to average out the noise over repeated processing

steps. Because RTNet is the only model that incorporates a mechanism for generating

stochastic responses, these stochasticity analyses a priori favor RTNet over the other models.

However, the rest of our analyses compare the behavior and predictions of models across a

range of stimulus manipulations in which no model is a priori expected to be favored over the

others.

Speed-accuracy trade off

The ability to trade off speed and accuracy against each other is a hallmark of decision-making

across humans and many other animal species[38,39]. The human data confirmed that increased

speed pressure led to lower accuracy (F(1,59) = 4.274, p = 0.043, η_p^2 = 0.068; **Error! Reference**

source not found.A) and shorter RTs (F(1,59) = 119.29, p < 0.001, η_p^2 = 0.964; **Error! Reference**

source not found.B). We also found a significant interaction between SAT and task difficulty for

accuracy such that the SAT effect was greater for easy images (F(1,59) = 5.71, p = 0.020, η_p^2 =

0.088). For RTs, however, we observed the opposite pattern where the SAT effect was

heightened for difficult images (F(1,59) = 22.423, p < 0.001, η_p^2 = 0.275). These results replicate

findings from a previous study examining the effects of SAT manipulations on accuracy and RT

as a function of stimulus contrast[49]. Further, as shown before[49], these findings are also in line

with predictions of the drift diffusion model (DDM), which is currently the standard model for

explaining human RTs[1,2].

All models were able to replicate the speed-accuracy trade off observed in humans. Increased

speed pressure resulted in lower accuracy for RTNet ($F(1,59) = 9.683$, $p = 0.003$, $\eta_p^2 = 0.141$),

CNet ($F(1,59) = 50.025$, $p < 0.001$, $\eta_p^2 = 0.459$), BLNet ($F(1,59) = 11.611$, $p = 0.001$, $\eta_p^2 = 0.164$),

and MSDNet ($F(1,59) = 21.841$, $p < 0.001$, $\eta_p^2 = 0.270$). Increased speed pressure also led to

shorter RTs for RTNet ($F(1,59) = 3362.567$, $p < 0.001$, $\eta_p^2 = 0.983$), CNet ($F(1,59) = 695.878$, $p <$

0.001, $\eta_p^2 = 0.922$), BLNet ($F(1,59) = 607.093$, $p < 0.001$, $\eta_p^2 = 0.911$), and MSDNet ($F(1,59) =$

584.081, $p < 0.001$, $\eta_p^2 = 0.908$). We note that the SAT manipulation had a relatively small effect

on accuracy (1.04% for easy and 1.24% for difficult conditions for RTNet; the effects for the rest

of the networks were of similar magnitude; Figure 4A). However, despite the small effect size,

these effects were generally consistent across the 60 model instances (for RTNet, 54/60

instances showed the effect for easy images and 42/60 showed the effect for difficult images).

The SAT manipulation had a much stronger effect on RTs compared to accuracy, which may be

attributed to the fact that RTs are a more sensitive measure of performance. Further, the SAT

effect on RTs was much stronger for humans, RTNet and BLNet, compared to the other models.

The individual RT distributions show a clear separation between the speed and accuracy focus

conditions for humans, RTNet and BLNet but not for CNet and MSDNet (Figure 4C).

Nevertheless, these results indicate that speed-accuracy trade off is robustly observed even for

relatively complex task with naturalistic images, and that all models examined here exhibit this

foundational phenomenon.

Difficult decisions lead to reduced accuracy and longer RT

Another ubiquitous feature of decision-making is that more difficult stimuli lead to lower

accuracy and longer RT[26,50]. Our human data robustly showed this effect with more difficult

stimuli leading to lower accuracy ($F(1,59) = 1558.500$, $p < 0.001$, $\eta_p^2 = 0.964$; **Error! Reference**

source not found.A) and longer RT ($F(1,59) = 411.154$, $p < 0.001$, $\eta_p^2 = 0.875$; **Error! Reference**

source not found.B). The same pattern was robustly observed for RTNet and BLNet, where

difficult stimuli led to lower accuracy (RTNet: $F(1,59) = 218.510$, $p < 0.001$, $\eta_p^2 = 0.787$; BLNet:

$F(1,59) = 200.543$, $p < 0.001$, $\eta_p^2 = 0.773$) but longer RT (RTNet: $F(1,59) = 233.452$, $p < 0.0001$, η_p^2

$= 0.798$; BLNet: $F(1,59) = 186.604$, $p < 0.001$, $\eta_p^2 = 0.760$). However, while CNet and MSDNet

also showed a very robust effect on accuracy (CNet: $F(1,59) = 1116.800$, $p < 0.001$, $\eta_p^2 = 0.950$;

MSDNet: $F(1,59) = 247.520$, $p < 0.001$, $\eta_p^2 = 0.808$), they exhibited a smaller effect for RT (CNet:

$F(1,59) = 11.070$, $p = 0.016$, $\eta_p^2 = 0.158$; MSDNet: $F(1,59) = 6.171$, $p = 0.002$, $\eta_p^2 = 0.095$). Indeed,

out of the 60 model instances, only 23 CNet instances and 36 MSDNet instances exhibited an RT

increase for more difficult stimuli, while this effect was present in 60/60 human subjects, 58/60

RTNet instances, and 59/60 BLNet instances. These results indicate that the effect of task

difficulty on accuracy is exhibited robustly in humans and all networks, but the effect of task

difficulty on RT is larger for humans, RTNet and BLNet compared to CNet and MSDNet (see

Discussion).

Skewness of RT distributions

For simple 2-choice decisions, human RT distributions are generally positively skewed and the

skewness changes as a function of task conditions[2,26]. Our 8-choice task produced RT

distributions that closely resemble what is observed in standard 2-choice tasks (**Error!**

Reference source not found.C). Similar-looking RT distributions were produced by RTNet but

CNet and MSDNet produced RT distributions that, while still right-skewed, exhibited qualitative

differences in their shapes (**Error! Reference source not found.**C). BLNet, on the other hand,

produced RT distributions that were frequently bimodal and left-skewed.

We further assessed how the skewness of the RT distributions changed under different

conditions. In humans, we found higher skewness for accuracy compared to speed focus

(F(1,59) = 32.837, $p < 0.001$, $\eta_p^2 = 0.358$), as well as for easy compared to difficult stimuli

(F(1,59) = 5.098, $p = 0.028$, $\eta_p^2 = 0.080$; **Error! Reference source not found.**D). RTNet exhibited

the same pattern with skewness increasing with a focus on accuracy (F(1,59) = 19.077, p <

0.001, $\eta_p^2 = 0.244$) and with easier stimuli (F(1,59) = 93.342, p < 0.001, $\eta_p^2 = 0.613$). For CNet, we

found no difference in skewness of RT distributions between the SAT conditions (F(1,59) =

0.428, p = 0.515, $\eta_p^2 = 0.007$), but skewness increased for easy compared to difficult stimuli

(F(1,59) = 8.612, p = 0.005, $\eta_p^2 = 0.127$). BLNet showed the opposite pattern to CNet with

skewness increasing for the speed-focus condition (F(1,59) = 39.219, p < 0.001, $\eta_p^2 = 0.399$) and

failed to show difference in skewness between the easy and difficult stimuli (F(1,59) = 3.517, p

= 0.066, $\eta_p^2 = 0.056$). Finally, while MSDNet showed an increase in skewness with a focus on

accuracy (F(1,59) = 64.866, $p < 0.001$, $\eta_p^2 = 0.524$), it produced RT distributions that did not

significantly differ in skewness between the task difficulty conditions (F(1,59) = 1.259, *p* = 0.266,

η_p^2 = 0.021). Overall, RTNet produced RT distributions which reflected the observed patterns in

human data better than all other networks. It should be noted that CNet, BLNet, and MSDNet

can only produce distinct RTs that are less than or equal to their layer numbers or residual

blocks, which may affect their ability to reproduce human RT distributions unless a relatively

high number of layers is used. On the other hand, RTNet can go through arbitrary number of

samples regardless of the number of layers in its architecture.

RT is faster for correct compared to error trials

Another ubiquitous feature of human behavior in 2-choice tasks is that correct decisions are

typically accompanied by faster RTs than incorrect decisions[41–45]. We replicated this effect in

our 8-choice task (F(1,59) = 82.080, *p* < 0.001, η_p^2 = 0.582; **Error! Reference source not found.**E).

The same difference between correct and error RTs also emerged for RTNet (F(1,59) = 831.153,

p < 0.001, η_p^2 = 0.934), CNet (F(1,59) = 83.921, *p* < 0.001, η_p^2 = 0.587), and BLNet (F(1,59) =

286.157, *p* < 0.001, η_p^2 = 0.582). However, MSDNet exhibited the opposite pattern such that RTs

were faster for error compared to correct trials (F(1,59) = 65.696, *p* < 0.001, η_p^2 = 0.527). This

behavior is due to the fact that errors produced by MSDNet come mostly from decisions made

in earlier layers. It may be possible to reverse this behavior by using a much more conservative

decision threshold in the early compared to the late layers of MSDNet, though the effectiveness

of this strategy and its effect on all other behavioral signatures examined here would need to

be tested. What is clear is that MSDNet in its current form makes a qualitatively wrong

prediction regarding the difference between correct and error RT, whereas RTNet, CNet and

BLNet naturally reproduce the empirical effect.

Confidence is higher for correct than error trials

Finally, a ubiquitous feature of confidence ratings is that they are higher for correct compared

to incorrect decisions[46,51]. Our human data replicated this effect (F(1,59) = 472.172, p < 0.001,

η_p^2 = 0.889; **Error! Reference source not found.**F). The effect was also robustly exhibited by all

networks: RTNet (F(1,59) = 966.796, p < 0.001, η_p^2 = 0.942), CNet (F(1,59) = 785.992, p < 0.001,

η_p^2 = 0.930), BLNet (F(1,59) = 374.031, p < 0.001, η_p^2 = 0.864), and MSDNet (F(1,59) = 131.923, p

< 0.001, η_p^2 = 0.691). Therefore, humans and all networks robustly showed higher confidence

for correct trials compared to incorrect trials.

<u>Model predictions of responses for individual images</u>

The results above demonstrate that RTNet naturally reproduces all foundational features of

human decision-making. On the other hand, CNet, BLNet, and MSDNet fail to exhibit stochastic

decisions and skewness difference in RT distributions between the SAT/difficulty conditions,

and MSDNet further fails to account for lower RT for correct decisions. However, RTNet's ability

in those respects can easily be matched by traditional cognitive models that do not work on

image-level data[24,42,52]. Therefore, a critical advantage of RTNet over traditional cognitive

models would be the ability to predict human behavior for individual, unseen images because

traditional models cannot do that. Here we tested specifically whether the accuracy, RT, and

confidence for unseen images produced by the networks predict the same quantities in

humans.

Model predictions for individual subjects

In a first set of analyses, we assessed the correlations between the accuracy, RT, and

confidence for each human subject and the corresponding quantities predicted by RTNet, CNet,

BLNet, and MSDNet across all four conditions (easy with speed stress, difficult with speed

stress, easy with accuracy stress, difficult with accuracy stress). We compared how well data

from individual human subjects could be predicted by each model as well as from the data from

the 59 remaining human subjects. This last quantity, which we call subject-to-group

relationship, provides an estimate of the noise ceiling (i.e., the performance that a true model

could achieve given inter-subject variability)[53].

We found that all models predicted individual human data much better than chance for

accuracy, RT, and confidence (two-sided one-sample t-tests, all p's < 0.001, all Cohen's d >

1.20). The one exception was BLNet, which had a weak negative correlation with human image-

by-image accuracy (average r = -0.06, p = 0.002, Cohen's d = 0.410, 95% CI = [-0.09, -0.02]).

Critically, RTNet provided substantially better predictions than all other models (**Error!**

Reference source not found.). Specifically, two-sided paired t-tests showed that RTNet

produced better image-by-image predictions about accuracy (RTNet vs. CNet: t(59) = 30.672, p

< 0.001, Cohen's d = 4.747, 95% CI = [0.24, 0.27]; RTNet vs. BLNet: t(59) = 20.842, p < 0.001,

Cohen's d = 3.864, 95% CI = [0.37, 0.44]; RTNet vs. MSDNet: t(59) = 30.672, p < 0.001, Cohen's d

= 4.747, 95% CI = [0.24, 0.27]), RT (RTNet vs. CNet: t(59) = 18.638, $p < 0.001$, Cohen's d = 2.370,

95% CI = [0.29, 0.35]; RTNet vs. BLNet: t(59) = 13.135, Cohen's d = 0.472, 95% CI = [0.06, 0.08], p

< 0.001; RTNet vs. MSDNet: t(59) = 13.318, $p < 0.001$, Cohen's d = 1.152, 95% CI = [0.13, 0.18]),

and confidence (RTNet vs. CNet: t(59) = 8.394, $p < 0.001$, Cohen's d = 0.936, 95% CI = [0.07,

0.11]; RTNet vs. BLNet: t(59) = 6.587, $p < 0.001$, Cohen's d = 0.391, 95% CI = [0.03, 0.05]; RTNet

vs. MSDNet: t(59) = 7.68, $p < 0.001$, Cohen's d = 0.471, 95% CI = [0.04, 0.06]).

Critically, RTNet's predictions were reasonably close to the noise ceiling in all cases (calculated

as the average subject-to-group correlation in the human data). Specifically, RTNet's predictions

were within 62.5%, 79.6%, and 64.8% of the noise ceiling for accuracy, RT, and confidence,

respectively. These numbers were substantially lower for CNet (16.1%, 20.3%, 40.5%,

respectively), BLNet (0%, 64.4%, 54.1%, respectively), and MSDNet (16.1%, 50%, and 51.3%,

respectively). Thus, by reaching to between 62.5% and 79.6% of the noise ceiling, RTNet can

provide excellent predictions for the accuracy, RT, and confidence produced by human subjects

for images that the model was not trained on. Additionally, we derived the model predictions

for averages across the 60 subjects across all conditions (Supplementary Figure 3) and found

that RTNet still predicts average human accuracy and RT better than the other networks.

Model predictions within each condition separately

The analyses above explored the correlations between model predictions and human behavior

across all experimental conditions. Because different conditions vary in their average accuracy,

RT, and confidence, analyses across conditions are likely to produce higher correlations than if

the same analyses are to be performed within each condition separately. Therefore, we

repeated the analyses above but within each of the four conditions separately to investigate if

the models can still account for accuracy, RT, and confidence on individual images. We found

that RTNet, BLNet and MSDNet produced accuracy, RT, and confidence predictions that

significantly correlate with individual subject data in all conditions (two-sided one-sample t-

tests, all p's < 0.001; Figure 6). However, while CNet produced accuracy and confidence

predictions that significantly correlated with individual subject data in all conditions, its RT

predictions for all conditions except accuracy focus with difficult images, were either zero or

negative (p's > 0.62).

Critically, however, RTNet predicted the individual data significantly better than the rest of the

networks. Specifically, two-sided paired t-tests showed that RTNet provided better predictions

than CNet in two out of four conditions for accuracy (all p's < 0.001), in all four conditions for RT

(all p's < 0.0001), and in two out of four conditions for confidence (p < 0.005). Compared to

BLNet, RTNet predicted individual data significantly better in three out of four conditions for

accuracy (all p's < 0.0001) and in all four conditions for RT (all p's < 0.025). Compared to

MSDNet, RTNet predicted the individual data significantly better in three out of four conditions

for accuracy (all three p's < 0.001) and in all four conditions for RT (all p's < 0. 02). There was no

significant difference in confidence predictions between RTNet and BLNet or between RTNet

and MSDNet for any of the four conditions (all p's > 0.05). RTNet was never significantly worse

than CNet, BLNet or MSDNet in predicting any of the 12 comparisons. Overall, these results

demonstrate that RTNet predicts human behavior well across all three measures and across

different types of analyses (across- or within-condition), and does so better than CNet, BLNet

and MSDNet.

<u>Humans more similar to the group are more similar to RTNet</u>

Our subject-to-group analyses revealed substantial variability in how well individual subjects'

data corresponded to the group average (see Figure 5). Since the group average constitutes the

best model of human behavior, one would expect that any good, generalizable model of

behavior would also be able to capture this relationship between individual subjects and the

group average. In other words, the strength of the relationship for an individual subject and the

group should be linked to the strength of the relationship of that same subject and the model.

Here we tested if such dependency holds true for RTNet, CNet, BLNet and MSDNet. We found

that subjects who exhibited greater correlation in image-by-image accuracy across all

conditions with rest of the group also exhibited greater correlation with the RTNet predictions

(Pearson's r = 0.685, $p < 0.001$, 95% CI = [0.52, 0.80]; Figure 7A). The same correspondence also

emerged for RT (Pearson's r = 0.825, $p < 0.001$, 95% CI = [0.72, 0.89]) and confidence (Pearson's

r = 0.894, $p < 0.001$, 95% CI = [0.83, 0.94]). Similar results were obtained for CNet (Accuracy:

Pearson's r = 0.389, $p = 0.002$, 95% CI = [0.15, 0.59]; RT: Pearson's r = 0.432, $p < 0.001$, 95% CI =

[0.20, 0.62]; Confidence: Pearson's r = 0.639, $p < 0.001$, 95% CI = [0.46, 0.77]; Figure 7B) and

MSDNet (Accuracy: Pearson's r = 0.389, $p = 0.002$, 95% CI = [0.15, 0.59]; RT: Pearson's r = 0.80,

$p < 0.0001$, 95% CI = [0.69, 0.88]; Confidence: Pearson's r = 0.853, $p < 0.001$, 95% CI = [0.77,

0.91]; Figure 7D), demonstrating that all three models predict better the data from individuals

who behave more similarly to the rest of the group. However, BLNet, showed no significant

correlation for accuracy predictions (Pearson's r = -0.029, p = 0.828, 95% CI = [-0.28, 0.23];

Figure 7C) while exhibiting high correlations for RT (Pearson's r = 0.831, p < 0.001, 95% CI =

[0.73, 0.90]) and confidence (Pearson's r = 0.809, p < 0.001, 95% CI = [0.70, 0.88]). All

correlations were highest for RTNet compared to the other three networks. These analyses

further support the notion that RTNet provides the best model of average human behavior

among existing alternatives.

To understand better these results, we further examined who were the subjects whose

accuracy, RT, and confidence was most similar to the group. We found that different subjects

had the highest similarity to the group for RT compared to accuracy or confidence

(Supplementary Figure 4A-C). Therefore, RTNet and other models did not simply provide good

fit to specific subjects but instead provided good fits to different groups of subjects for different

measures. Finally, the individuals closest to the group in their mean accuracy also tended to be

those who had the highest task accuracy, suggesting that RTNet and the other models were

better at predicting the image-by-image accuracy of subjects with higher task performance

(Supplementary Figure 4D).

404
405
Given the variability in how similar individual subjects were to the group data, we also explored

how well the models compared to the ability of individual subjects to predict the group data.

Two-sided paired t-tests showed that RTNet outperformed individual human subjects in

predicting the accuracy (t(59) = 4.076, p < 0.001, Cohen's d = 0.526, 95% CI = [0.02, 0.06]), RT

(t(59) = 16.174, p < 0.001, Cohen's d = 2.088, 95% CI = [0.2, 0.25]), and confidence (t(59) =

10.927, $p < 0.001$, Cohen's $d = 1.411$, 95% CI = [0.18, 0.26]) of the rest of group across all

conditions (Figure 8). Impressively, RTNet outperformed every individual human subject in

predicting the group RT and confidence results, as well as 73.3% of individual subjects in

predicting accuracy. On the other hand, CNet was significantly worse than individual subjects in

predicting group accuracy and RT but not confidence (Accuracy: $t(59) = -42.425$, $p < 0.001$,

Cohen's $d = 5.477$, 95% CI = [-0.4, -0.39]; RT: $t(59) = -25.439$, $p < 0.001$, Cohen's $d = 3.284$, 95%

CI = [-0.38, -0.32]; Confidence: $t(59) = -0.361$, $p = 0.719$, Cohen's $d = 0.047$, 95% CI = [-0.05, -

0.03]). BLNet was significantly worse than individual subjects in predicting group accuracy but

predicted group RT and confidence better than individuals (Accuracy: $t(59) = -68.395$, $p < 0.001$,

Cohen's $d = 8.830$, 95% CI = [-0.67, -0.63]; RT: $t(59) = 7.018$, $p < 0.001$, Cohen's $d = 0.906$, 95% CI

= [0.07, 0.13]; Confidence: $t(59) = 6.170$, $p < 0.001$, Cohen's $d = 0.797$, 95% CI = [0.08, 0.16]).

Finally, MSDNet's predictions of group accuracy and RT were significantly worse than those of

human subjects but its predictions of group confidence were better than those of individual

subjects (Accuracy: $t(59) = -42.425$, $p < 0.001$, Cohen's $d = 5.477$, 95% CI = [-0.42, -0.39]; RT:

$t(59) = -4.019$, $p < 0.001$, Cohen's $d = 0.519$, 95% CI [-0.08, -0.03]; Confidence: $t(59) = 5.266$, $p <$

0.001, Cohen's $d = 0.68$, 95% CI = [0.07, 0.15]). In sum, RTNet was the only network that

outperformed most individual subjects in predicting all three measures of human performance

(accuracy, RT, and confidence).

430
431

433 Discussion

There is considerable interest in using neural networks as models of human visual processing

and behavior, but relatively little work has been done on testing the extent to which existing

image-computable models reproduce the full range of behavioral signatures exhibited by

humans. Here we show that the current state-of-the-art neural networks such as CNet, BLNet,

and MSDNet diverge in several ways from human behavior. Further, we develop a new neural

network, RTNet, that exhibits all critical features of human perceptual decision making,

including effects on accuracy, RT, and confidence. Further, RTNet predicted well human group

behavior for novel images and did so better than both CNet, BLNet, and MSDNet, as well as

better than individual human subjects. Finally, individual humans who were more similar to the

group were also more similar to RTNet. Overall, RTNet is a promising image-computable model

of human accuracy, RT, and confidence.

<u>Relationship between RTNet and cognitive models of perceptual decision making</u>

RTNet is the first neural network to exhibit all critical signatures of human perceptual decision

making. This success, however, is hardly surprising given the strong conceptual similarity

between RTNet and traditional cognitive models of decision-making that also exhibit the

signatures of human behavior[24,26,40,52,54]. These models are often referred to as sequential

sampling models where (usually noisy) evidence is accumulated over time until a threshold is

reached. The most common sequential sampling models are diffusion models, which are

typically only applied to 2-choice tasks where evidence in favor of one response alternative is

also evidence against the other alternative[1,40]. Instead, RTNet is conceptually more similar to

another subgroup of sequential sampling models called race models where each choice option

has its own accumulation system and evidence for each choice is accumulated in parallel[42,55].

Despite their conceptual similarity, RTNet has two important advantages over traditional

cognitive models. Most importantly, RTNet is image-computable and can be applied to actual

images, whereas traditional models cannot. As such, traditional models cannot replicate

RTNet's ability to make accurate predictions regarding human accuracy, RT, and confidence for

individual unseen images. The second advantage stems from the inability of traditional

cognitive models to naturally capture the relationships between the different choice options.

Specifically, to maintain a low number of free parameters, cognitive models are often fit with

the assumption that evidence accumulates at the same rate for all incorrect choice options (but

accumulates faster for the correct choice)[56]. However, this assumption ignores the fact that

some incorrect options may be more similar to the correct option and thus are more likely than

other options to be chosen. While dependencies between the choices can easily be

incorporated in cognitive models, that would result in a large number of free parameters that

would make fitting to data difficult. Conversely, RTNet inherently learns all relationships

between the choice options during the training of the Bayesian neural network that forms its

core. RTNet still requires the fitting of the overall signal strength (which we accomplish by

adjusting the noise level of the images fed to RTNet), but this single free parameter allows it to

capture all choice option dependencies, something that traditional models cannot achieve.

Performance differences between RTNet and other networks

RTNet outperformed all other networks we tested (CNet, BLNet, and MSDNet) in capturing the

signatures of perceptual decision making. Specifically, while MSDNet and CNet show relatively

weaker effects of task difficulty on RTs compared to humans, RTNet closely captures the

observed magnitude of this effect. Further, RTNet is the only model that mimics the observed

shape and skewness of RT distributions in response to SAT/difficulty manipulations. Finally,

RTNet yielded the closest image-by-image predictions of human choice, RT, and confidence.

We speculate that RTNet's ability to match observed patterns in human behavior, particularly

RTs, is primarily due to its internal mechanisms being closer to the true mechanisms that give

rise to RTs in humans. Specifically, RTNet's core assumption that RTs are generated by a process

of sequential sampling and evidence accumulation is inspired from a long tradition of cognitive

modelling [1,2]. In fact, these evidence accumulation models have been tested extensively against

human data and are currently the best models of human RTs [1,2]. On the other hand, models

such as CNet, BLNet and MSDNet rely on mechanisms that, although can generate RTs, have

not been as extensively validated by empirical tests and are therefore less likely to capture the

true mechanisms that generate RTs in humans.

Nevertheless, another reason why CNet and MSDNet may struggle with generating human-like

RTs is that the RTs generated by the models are constrained by the number of layers or residual

blocks present in the networks. On the other hand, RTNet's evidence accumulation mechanism

allows flexible generation of RTs across a potentially very large number of steps, thus allowing

the RTs to have higher resolution and sensitivity to experimental manipulations.

<u>Biological plausibility of neural network models of response time</u>

Physiological recordings have uncovered several features of the processing in the human visual

system that are relevant to judging the plausibility of the networks examined here. First, the

conduction from one area to another in the visual cortex (roughly corresponding to different

layers in neural networks) takes approximately 10 ms[57], with signal from the photoreceptors

reaching the top of the visual hierarchy in inferior temporal cortex in 70-100 ms[58]. Therefore, a

single sweep from input to output in a purely feedforward network should result in decisions

with RT less than a few hundred milliseconds even though human decisions can range from a

hundred of milliseconds to a few seconds. Second, neurons in each layer of the visual cortex

continue to fire action potentials for hundreds of milliseconds after the stimulus onset and

receive strong recurrent input from later layers of processing[59]. Finally, neuronal processing is

known to be noisy such that the same image input generates very different neuronal

activations on different trials[37].

MSDNet diverges from these known properties of the human visual cortex in several important

ways. To generate meaningful RTs, MSDNet assumes that classification decisions are made

after each layer of processing, though there is no evidence that decisions in the brain can be

directly based on information in early visual cortex without further processing in subsequent

layers. Moreover, because it assumes the existence of a single feedforward sweep through the

network, it cannot naturally capture large RT variability between stimuli given the short

latencies of processing between different layers. Finally, MSDNet does not incorporate any

recurrent processing, capture the noisiness of the responses in the visual cortex, or replicate

the long periods of activity of the neurons in each processing area. These properties strongly

limit the biological plausibility of MSDNet.

In comparison, the dynamics of CNet are closer to those of biological neural networks. Indeed,

several of CNet's features – such as parallel and continuous processing of input, and

transmission delays between layers – were directly inspired by biology. The transmission delays

allow the network to mimic the processing latencies across cortical layers. These features were

also found to account for differences in processing efficiency between images such that CNet

produced more rapid responses for prototypical images with clear backgrounds compare to

unusual or cluttered images. However, CNet includes several features that are not biologically

plausible such as its lack of stochasticity of decisions and recurrent processing. Further, it

remains unclear how its cascaded architecture could map onto brain areas[12].

BLNet appears more biologically plausible than both MSDNet and CNet as it features recurrent

visual processing. Lateral connections in RCNNs enable a layer's activations from previous time

steps to feed back into itself, which allows state dependence to naturally emerge in these

networks, thus mimicking biological networks[67]. Additionally, RCNNs have been found to

generate RTs that align closely with human RTs on a range of complex perceptual tasks

involving scene categorization, perceptual grouping, and mental simulation[22]. These findings

suggest further similarities in perceptual processing between humans and RCNNs. However, in

spite of these advantages, RCNNs still lack certain features of biological networks such as

stochasticity of responses.

It is possible to introduce stochasticity in CNet and MSDNet by feeding the outputs of the final

softmax layer into a race model. However, such an architecture would imply that response

stochasticity arises purely from noise in the decision stage. Although decision noise may exist in

humans contributing to noisy motor responses, stochasticity in human responses is thought to

predominantly arise from noisy inference[29] or noisy sensory representations[60–62]. Therefore,

CNNs with additional noise at the decision stage are less biologically plausible than RTNet,

which includes noise in the evidence processing stage.

On the other hand, while also not capturing all properties of visual processing, RTNet appears

more biologically plausible. First, it mimics the noisiness of neuronal responses for repeated

presentations of the same stimulus. Second, through the process of evidence accumulation,

RTNet naturally generates long-lasting neuronal activations . Third, the network's output is

inherently stochastic, unlike CNet, BLNet, MSDNet, or standard feedforward networks that are

inherently deterministic. Finally, the accumulation process implemented in RTNet has been

observed in multiple regions in the human parietal cortex, frontal cortex, and subcortical

areas[63–66]. Nevertheless, one critical limitation of the biological plausibility of RTNet is its lack of

recurrency. That being said, the question of how to train recurrent neural networks on static

images remains open[53,58,67–69]. Further, while the core of RTNet does not include recurrency,

the evidence accumulation system can be thought of as a recurrent network. In fact, several

recent studies have demonstrated the advantages of combining a standard feedforward

network with a recurrent network in performing a range of tasks and extrapolating to solve

problems of greater complexity than they were trained on[70,71]. Future studies should explore

how to introduce recurrence into RTNet's mechanisms and whether such modifications can

improve its predictions of human behavior.

<u>Using noisy weights to generate stochasticity in RTNet's responses</u>

One critical feature of RTNet is that its weights are noisy. Practically, there are many ways of

generating noise in the weights. In early iterations of RTNet, we attempted to create variability

by training a feedforward network and then adding the same amount of variability to each

connection. This approach resulted in variability that was too small for some weights and too

large for others[72], often leading to no accuracy gains from the process of evidence

accumulation. Indeed, a given amount of noise over a specific weight may not change the

performance of a network at all, but the same disturbance over another weight may have

destructive effects[73–75]. We therefore chose to obtain the weight variability by training a

Bayesian neural network so that each weight has an appropriate amount of noise. In the future,

it may be possible to use other methods for setting the noise level for each connection, but we

are currently unaware of any method besides training a Bayesian neural network that can

generate appropriate noise for each weight.

Another alternative to implementing noise in RTNet is to only add noise to the weights in the

pre-readout layer (which can mimic noise in the decision process rather than in the sensory

processing). As there are many different ways to implement stochasticity in the network, it is

important for future studies to test how these differences in implementation affect the model's

performance.

RTNet is built such that every time evidence is sampled from a stimulus, the network's weights

change randomly (according to the BNN's posterior weight distributions). These random

moment-by-moment fluctuations in the network's weights lead to noisy activations. However,

in the brain, noisy activations in response to a stimulus are thought to arise from random

fluctuations in neuronal activity itself. Therefore, it can be argued that a more biologically

plausible implementation of RTNet would involve noise in unit activations rather than

weights[76]. The main reason we chose to add noise in weights rather than activations is due to

the practical ease of implementing BNNs that can naturally generate variability in networks.

Mechanistically, however, there may be no meaningful distinction between noisy weights and

noisy activations. Indeed, noisy weights lead to noisy activations, which mimic the randomness

of neural responses.

Limitations

One limitation of RTNet is that its mechanism for stopping the accumulation process is non-

optimal. Following a large literature of race models in cognitive psychology[24,42,56], RTNet makes

a decision when any one choice option receives sufficient evidence to exceed a threshold.

However, if another choice option has almost same amount of evidence, the observer has little

ability to differentiate between the two choices and is essentially guessing between them.

Previous research showed that guessing can be an appropriate behavior if the observer knows

that the task is very difficult[77] or if the observer has been deliberating for a long time[78].

However, in a race model, guessing can happen at any time point regardless of task difficulty.

Nevertheless, human decisions are often suboptimal[79,80], and therefore it is unclear as to

whether this suboptimal decision-making mechanism should be seen as a drawback if the goal

is to model human decision-making.

Another limitation of RTNet is that each sweep of the feedforward path is independent of the

previous states, whereas the current state in the human brain is influenced by its previous

states[67]. To address this limitation, the sampling process in RTNet can be modified such that the

current state of the network depends on the previous states. For example, during testing, the

connection weight at a specific moment can be made a function of its previous values, which

would make the sequential samples dependent on each other. Additional studies are needed to

investigate the effect of such state dependence on model performance.

Conclusion

We developed a new neural network, RTNet, which exhibits the basic features of human

perceptual decision making and predicts human accuracy, RT, and confidence on an image-by-

image basis. The network provides a better model of human perceptual decisions than the

current state-of-the-art networks for generating response times. RTNet thus represents an

important step in the use of neural networks as models of human decisions.

Methods

Methods

All subjects signed informed consent and were compensated for their participation. The

protocol was approved by the Georgia Institute of Technology Institutional Review Board,

protocol H15308. All methods were carried out in accordance with relevant guidelines and

regulations.

Behavioral experiment

Pre-registration

This study's sample size, experiment design, included variables, hypothesis, and planned

analyses were pre-registered on Open Science Framework (https://osf.io/kmraq) prior to any

data being collected.

Subjects

Sixty-four subjects (31 female, age=18-32) with normal or corrected to normal vision were

recruited. We had pre-registered the collection of only 40 subjects, but due to less time

restrictions than we had anticipated, and to further increase the statistical power, we collected

data from more subjects.

Stimulus, task, and procedure

Subjects performed a digit discrimination task where they reported their perceived digit

followed by rating their decision confidence. Each trial began with subjects fixating on a small

white cross for 500-1000 ms, followed by a presentation of the stimulus for 300 ms (**Error!**

Reference source not found.). The stimulus was a digit between 1 and 8 (the digits 0 and 9

were excluded) superimposed on a noisy background. Subjects' task was to report the

perceived digit using a computer keyboard by placing four fingers of their left hand on numbers

1-4 and placing four fingers of their right hand on numbers 5-8. This setup allowed subjects to

respond without looking at the keyboard, thus providing less noisy response times. Following

their categorization response, subjects reported their decision confidence on a 4-point scale

(where 1 corresponds to the lowest confidence and 4 corresponds to the highest confidence).

There was no deadline on the response or confidence rating.

The experiment included manipulations of speed-accuracy trade off and task difficulty. Speed-

accuracy trade off was manipulated by asking subjects to emphasize either the speed or

accuracy of their responses. To facilitate proper responding, we organized the experiment into

alternating blocks of speed and accuracy focus. Task difficulty was manipulated by adding

different levels of uniform noise to the stimuli. Specifically, "easy" stimuli included average

uniform noise of 0.25 (range = 0-0.5), whereas "difficult" stimuli included average uniform

noise of 0.4 (range = 0-0.8). To add the noise, the pixel values were first transformed to be

between 0 and 1 and random numbers drawn from the corresponding noise distributions were

added separately to each pixel. We scaled the resulting image to be between 0 and 1 again, and

finally converted the image to a uint8 format (scaled between 0 and 255). The noise levels were

chosen based on the pilot testing to produce two different performance levels. Easy and

difficult images were randomly interleaved.

The task stimuli were selected from a publicly available handwritten digits (MNIST) dataset[32].

This dataset contains 60,000 training images and 10,000 testing images. Since the training

images were used to train the models in this study, we randomly selected images from MNIST

test set to include in our experiment. This ensures that the selected images for the experiment

are novel both for the human subjects and for the trained models. We randomly selected 480

images for the experiment (120 for each condition). The MNIST dataset images are of size 28 x

28 pixels which appeared overly small on the computer screens we were using. Therefore,

before adding noise, the selected images were first resized to 84 x 84 pixels (using MATLAB's

imresize function), and they were padded with the background color of MNIST images to size

256 x 256 pixels (visual angle = 6.06°).

The experiment started with three blocks of training each containing 50 trials. The first block

contained images from the MNIST dataset without any noise. This was done to familiarize the

subjects with the experiment. The next two blocks were used to introduce the speed-accuracy

trade off by asking subjects to focus on accuracy in the first block and on speed in the second.

The noise level of the stimuli in these two training blocks was same as in the main experiment

(i.e., 0.25 and 0.40 for the easy and difficult stimuli, respectively). During the whole training

session, the experimenter was standing beside the subject quietly and was available to answer

any questions. None of the images used in the training session was used in the main

experiment.

Once the subject confirmed that he or she understands the task, the experimenter left the

room and subjects completed the main experiment that consisted of 960 trials organized in

four runs each containing four blocks of 60 trials. Each block consisted of a single speed-

accuracy trade off condition, and each run included exactly two "accuracy focus" and two

"speed focus" conditions in a randomized order. At the beginning of each block, subjects were

given the name of the condition for that block ("accuracy focus" or "speed focus") and asked to

adjust their responding policy accordingly. In each block, we pseudo-randomly interleaved trials

from the two difficulty levels such that each was presented exactly 30 times. All 480 images

were shown to subjects in first two runs and the procedure was repeated with a new random

ordering of the stimuli in the last two runs. All images were same for all subjects, and each

image was assigned only to one specific condition.

Apparatus

The experiment was designed in MATLAB 2020b environment using Psychtoolbox 3[81]. The

stimuli were presented on a 21.5-inch Dell P2217H monitor (1920 x 1080 pixel resolution, 60 Hz

refresh rate). Subjects were seated 60 cm away from the screen and provided their responses

using a keyboard.

Behavioral analyses

We followed the data analyses steps outlined in our preregistration. All analyses were

performed in Python (version 3.10.11) using Google Colab (version 2.0). We first excluded

subjects who did not follow sufficiently well the speed/accuracy instructions by not providing

718 faster average RT in the "speed focus" compared to the "accuracy focus" condition. This

719 resulted in removing two subjects (out of 64). We preregistered the exclusion of subjects with

720 floor or ceiling effects on accuracy but no subject met the criteria for exclusion. However,

721 following our preregistration, we excluded two subjects because they showed ceiling effects for

722 confidence. Note that our preregistration document called for excluding subjects who provided

723 average confidence of more than 3.7 but because this would have resulted in excluding a much

724 larger number of subjects than we had anticipated, we only excluded subjects whose average

725 confidence was above 3.85. Therefore, 60 subjects were used in all subsequent analyses.

727 We additionally excluded individual trials with extreme RT values using preregistered criteria

728 based on Tukey's interquartile criterion. Specifically, for each subject, we computed the 25^{th}

729 and 75^{th} percentiles of the RT distributions in each condition. We then removed all RTs with

730 values more than 1.5 times the interquartile range such that if $Q1$ is the RT value at the 25^{th}

731 percentile and $Q3$ is the RT value at the 75^{th} percentile, we removed values smaller than $Q1 -$

732 $1.5 \times (Q3 - Q1)$ and larger than $Q3 + 1.5 \times (Q3 - Q1)$. This step resulted in removing an

733 average of 5.46% of total trials (range of 1.35-8.22% for each subject).

735 Once these preprocessing steps were completed, we computed average accuracy, RT,

736 confidence, and skewness of the RT distributions separately for each condition. The skewness

737 was computed separately for each individual subject's RT distribution as $\frac{\sum_{i=1}^{N}(x_i-\mu)^3}{(N-1)\sigma^3}$ where μ and

738 σ are the mean and standard deviation of the sample distribution, respectively. We also

739 computed average RT and average confidence scores for error and correct trials across subjects

to examine how RT and confidence change as a function of response accuracy. Finally, for

visualization purposes, we plotted RT distributions for one subject in Figure 4C. The RT

distributions were generated using kernel density estimation (KDE), which approximates the

underlying probability density function that generated the data by smoothing the observations

with a Gaussian kernel[82]. The KDE plots were created using Seaborn's KDE plot with a

smoothing bandwidth of 1.2[83].

<u>RTNet</u>

Network architecture

The RTNet model consists of two main modules (

A). The first module is a Bayesian neural network (BNN) which makes predictions regarding an

image. BNNs are a type of artificial neural network built by introducing stochastic components

into the network to simulate multiple possible models with their associated probability

distribution[84]. The main difference between a BNN and standard feedforward neural network is

that in BNN the weights are distributions instead of point estimates. A random sample from

these distributions results in a unique feedforward network. This random sampling enables

variability in the output of the network, which in turn can be fed into an accumulation process

that drives a decision. The second module of our model consists of exactly such accumulation of

the evidence produced on each step by the first module. At each processing step, the output of

the network (in the form of activations of the final layer) was accumulated towards a pre-

defined threshold. Evidence for each choice option was accumulated separately from the rest,

similar to a race model[24].

The accumulation process continues until the total amount of accumulated evidence for one of

the alternatives reaches a predefined threshold. The alternative for which the threshold was

reached then becomes the response of the model. The response time produced by RTNet is

simply the number of samples used to reach the decision threshold. The confidence of the

model was obtained by taking the difference in evidence scores between the chosen response

and the second-best choice.

Implementation

We implemented RTNet using the AlexNet architecture, which has eight layers with learnable

parameters[33]. The AlexNet architecture consists of five convolutional layers with a combination

of max pooling followed by three fully connected layers. We chose to implement RTNet within a

relatively large-scale CNN such as AlexNet (rather than a shallow network which may have also

been able to learn to classify the MNIST dataset) because our goal was to eventually compare

our model to others such as CNet and MSDNet, which are generally based on larger CNNs and

work on multiple existing datasets. Additionally, difficulties associated with training Bayesian

neural networks limited us to relatively small network structures (rather than VGG or ResNet

models). We found the AlexNet architecture to be a reasonable compromise in this trade off

between model complexity and ease of training BNNs. RTNet was implemented in PyTorch[85]

while Bayesian networks were implemented using Pyro[86], which is a probabilistic programming

library built on PyTorch[85].

Training the BNN module of RTNet

BNNs are probabilistic models that incorporate uncertainty into their weights and biases,

rather than treating them as point estimates. Consider a training dataset, x, for which we

must predict the class labels, y. In traditional neural networks, the predicted class label,

$\hat{y}$, is a function of network's weights, w, and these weights are tuned in order to optimize

the correspondence between the predicted ($\hat{y}$) and true class labels (y). In BNNs,

however, weights are modelled as probability distributions instead of point estimates.

Following the rules of Bayesian inference, one can infer the posterior distribution of

these weights (w) using the formula $p(w|x) = \frac{p(w,x)}{p(x)}$. However, this computation is

intractable for large networks since it involves computing the marginal likelihood of the

data $p(x)$ across all possible configurations of weights. Therefore, computing this

posterior distribution is typically done using a method of approximation called variational

inference. A stand-in distribution, $q(w)$, is specified to approximate the posterior and its

parameters are tuned to maximize the similarity between the two distributions. The

similarity between the distributions is quantified by the information theoretical measure

called Kullback-Liebler (KL) divergence:

$KL(q(w)||p(w|x)) = E_q[\log q(w) - \log p(w,x)] + \log p(x)$ (1)

Although $KL(q(w)||p(w|x)$, cannot be directly computed since $p(x)$ is intractable, one

can side-step this computation by defining a surrogate objective function called the

evidence lower bound (ELBO) function as:

$$ELBO(q) = E_q[\log p(w, x) - \log q(w)] \qquad\qquad (2)$$

where both $p(w, x)$ and $q(w)$ are tractable, and due to their negative relationship,

maximizing $ELBO(q)$ thus results in the minimization of $KL(q(w)||p(w|x))$, allowing one

to approximate the true posterior distribution of the network's weights.

We trained the network to achieve classification accuracy higher than 97% on the MNIST test

set. We trained the BNN module of RTNet for a total of 15 epochs with a batch size of 500. We

used the Evidence lower bound (ELBO) loss function[87] and Adam[88] for optimization with a

learning rate of 0.001, and the default values for weight decay and epsilon (weight decay = 0; ϵ

$= 10^{-8}$). To ensure that each BNN performs greater than 97% on MNIST test set, we followed a

specific rule for each model instance. When testing an image with the BNN module of RTNet,

we sampled 10 times from the posterior distributions learned during the training and thus

obtained 10 unique responses for each image. The response with highest frequency among 10

responses was chosen as the final decision of the BNN module. Note that there were no RTs

generated at this step since we only implemented the BNN module of RTNet and generated a

set of responses that would allow us to evaluate how well the BNN's posterior distributions had

been trained. These trained BNN models were later used to generate variable activations for

the evidence accumulation process that resulted in RTs.

We resized the MNIST images to the standard input size to AlexNet model architecture (227 x

227 pixels). We also normalized the input images to have a mean of 0.1307 and standard

deviation of 0.3081, which is a standard procedure when using AlexNet for classification of the

ImageNet dataset[89]. We trained sixty instances of RTNet using the above procedure but with

different weight initializations for each network instance. We used a different combination of

mean and standard deviation (SD) values for each of the 60 instances to maximize differences

in network initializations. Specifically, different network instances of RTNet were initialized such

that all means of the weights and biases were set to a value between 0.1 and 1.2 with 0.1

increments, and all SDs of weights and biases were set to a value ranging from 1 to 5 with

increments of 1 (for a total of $12 \times 5 = 60$ instances).

Generating RTNet's responses from the evidence accumulation module

Sequential sampling models belong to a class of cognitive models which assume that observers

make decisions by repeated sampling and accumulation of noisy evidence until a threshold is

reached [1,2]. In these models, RT reflects the number of sampling steps required to reach the

threshold. RTNet utilizes this evidence accumulation mechanism to generate RTs. In order to

generate noisy evidence, we used the probability distribution of weights in the BNNs to

randomly sample one unique feedforward network at each time step. At each time step, t, the

presented image results in a feedforward sweep of the sampled network and generates a set of

activations (a_t) where $a_t = [a_{1,t}, a_{2,t} \dots a_{8,t}]$ are the values obtained in the last layer after the

softmax function has been applied. Each unit in the output layer corresponds to the activation

for one of the eight choice options and for each choice, the evidence obtained at the current

step is added to the sum of evidence collected from all previous steps. Thus, a running total of

accumulated evidence is maintained such that $a_i = \sum_{t=1}^{n} a_{i,t}$ where n refers to the total

number of steps over which evidence has been accumulate and $i \in [1,8]$ refers to the response

option. When the total evidence in favor of any of the options exceeds a pre-defined threshold

k, the corresponding response option is chosen such that the network's response, $r =$

argmax$(a_1, a_2 \dots a_8)$ at the time step when max $(a_1, a_2 \dots a_8) \geq k$.

What are the properties of evidence accumulation? Everything else being equal, decisions that

are based on fewer evidence samples are more likely to be influenced by chance fluctuations in

evidence that favor incorrect decisions. On the other hand, when the model is allowed to

accumulate evidence over a longer period, these such random variations are more likely to

cancel out, thus increasing the likelihood of a correct response. In turn, because a longer period

of accumulation leads, on average, to stronger evidence, this directly results in higher

confidence.

CNet

Network architecture

The parallel cascaded network (CNet) builds upon the architecture of residual networks

(ResNet) by utilizing skip connections to introduce propagation delays during input processing

(Figure 1B). At each processing step, all units in all layers are updated parallelly. However, due

to the propagation delays introduced by each residual block, simpler perceptual features get

transmitted faster across blocks. For instance, at the first time-step, only the first residual block

receives input and model predictions at this step are based only on the computations of the

first residual block. At the second time step, all the other layers receive partial input from the

first block. Even though the model prediction at this point will be based on computations from

all blocks, only the first block will have received complete input and achieved stable output. The

other blocks will only contain partial updates from the lower block and therefore their output

will not be stable. In general, a residual block, t, takes $(t-1)$ time steps to receive complete

and stable input. At any point during processing, the network can generate a prediction since all

the residual blocks contribute to the computations. However, if the time step (t) is less than the

number of residual blocks, the responses will be based on unstable representations in the

higher blocks. Due to this architecture, the network's responses are subject to a trade off

between speed and complexity of processing. Decision time is indicated by the processing step

at which the decision was made, and decision confidence is derived from the softmax value in

the final layer, at the time of decision. The softmax values are obtained by transforming the

activation scores (z) of all nodes in the output layer according to the function: $\frac{e^{z_i}}{\sum_j^n e^{z_j}}$, where

i refers to the node whose output is being transformed and n refers to the number of nodes in

the output layer (which is equal to the number of classes).

Implementation

CNet was implemented using the architecture of ResNet-18[9] since it requires networks with skip

connections. ResNet-18 architecture consists of 17 convolutional layers, where 16 of these

layers are embedded within eight residual blocks (skip connections), followed by a final fully

connected layer with softmax activation to generate the decision. The network was

implemented in PyTorch[85].

Network training

We trained CNet using the same procedure that was used by the original authors since their

training protocol was found yielded the best network behavior and performance. The network

achieved an accuracy > 97% with 12 training epochs and a batch size of 500. The models were

trained on a temporal-difference (TD) learning procedure along with cross-entropy loss. In the

original publication, TD learning was found to perform better than softmax-based cross-entropy

loss in encouraging correct responses to emerge faster. The loss function was optimized using

an initial learning rate of 0.01, weight decay of 0.005 and a momentum of 0.9. The images were

normalized to a mean of 0.1307 and standard deviation of 0.3081. We trained sixty instances of

CNet using the above procedure but using a different random seed for initializing the network's

weights to allow individual differences in network's learning.

<u>BLNet</u>

Network architecture

BLNet is a recurrent convolutional neural network (RCNN) consisting of a standard feedforward

CNN with recurrent connections that connect each layer to itself[10] (Figure 1C). A final readout

layer computes the network's output at each time step via a softmax function. Time steps are

defined as the number of feedforward sweeps of the network that have occurred until the time

at which the readout is evaluated. At each time step, a given layer receives input from two

sources – the feedforward input from the previous convolutional layer and recurrent input from

itself in the form of activations from the previous time step. The readout is evaluated at each

time step such that if it exceeds a pre-defined threshold, the network generates a response.

The response corresponds to the choice that generates the highest softmax value and the time

step at which the response was made indicates the decision time. The softmax value associated

with the choice at the time of decision indicates decision confidence. The network's ability to

trade off speed and accuracy comes from the fact that higher softmax thresholds require more

feedforward and recurrent computations, which effectively results in a deeper network being

unrolled across time which, in turn, leads to both higher RT and higher accuracy.

Implementation

BLNet was implemented as a custom-built network consisting of seven convolutional layers of

increasing size and a final readout layer, as defined by the original authors[10]. Each layer consists

of two sets of weights – the bottom up weights that transform the input from the previous

layer and the lateral weights that act on recurrent input that the layer receives from itself. The

readout layer is a fully connected layer with softmax activation to generate the decision. The

network was unrolled across time for eight time steps. The network was implemented using

TensorFlow.

Network training

We were able to achieve test accuracy > 97% with only three epochs with a batch size of 32 and

a sparse categorical cross-entropy loss function[90]. Adam[88] was used for optimization with a

learning rate of 0.001. For testing, the response at the final time-step was taken as the

network's decision. We resized the MNIST images to the standard input size of 128x128 defined

for the network. We trained sixty instances of BLNet using the above procedure but using a

different random seed for initializing the network's weights to allow individual differences in

network's learning.

Testing

Unlike the other networks, BLNet exhibited overall accuracy that was about 5% greater for the

120 images used in the easy, speed-focus condition compared to the 120 images used in the

easy, accuracy-focus condition. This resulted in a lack of the expected accuracy difference

between these two conditions when BLNet was run on all images (Supplementary Figure 5). On

further investigation, we found that for each condition, the image set contained a small subset

of images for which the network showed chance-level performance (12.5%). The image set for

the easy, accuracy-focus condition contained more such images than the image set for the easy,

speed-focus condition, explaining the observed accuracy differences. Therefore, when testing

BLNet on the effects reported in Figure 4, we excluded this subset of images for all conditions

(10 out of 480 images). This exclusion led to BLNet showing the expected speed-accuracy trade

off (Figure 4A,B).

MSDNet

Network architecture

MSDNet has an architecture similar to a standard feedforward neural network but with early-

exit classifiers after each of its layers (

D). At each output layer, the evidence for each choice is computed using a softmax function and

if the evidence for any alternative exceeds a predefined value the network stops processing and

immediately produces a response. The layer at which the response was made is indicative of

the decision time, and the softmax value at that layer is indicative of decision confidence[90,91].

Implementation

We implemented MSDNet using the AlexNet architecture, which has eight layers with learnable

parameters[33]. The AlexNet architecture consists of five convolutional layers with a combination

of max pooling followed by three fully connected layers. In addition to the standard AlexNet

structure, we incorporated additional readout layers located right after each layer of

processing. The feature map size of all these readout layers were set to the number of classes.

The network was implemented in PyTorch[85].

Network training

Due to MSDNet's deterministic nature, only three epochs with a batch size of 500, were enough

to achieve test accuracy of more than 97% with the same batch size and a weighted cumulative

loss function[90]. Adam[88] was used for optimization with a learning rate of 0.001. For testing, the

response of the last output layer was taken as the network's decision. If a network did not

achieve accuracy greater than 97%, we started the training over with the same initial values.

Since MSDNet is also built on the architecture of AlexNet, we resized the MNIST images to the

standard input size for AlexNet and normalized the images to have a mean of 0.1307 and

standard deviation of 0.3081. To make the initializations of MSDNet as similar as possible to the

initializations of RTNet, for each RTNet instance, we set the initial values for the weights and

biases of the MSDNet instance by randomly sampling from the Gaussian distribution used in the

corresponding RTNet initialization.

<u>Choosing parameters that allow the models to mimic human accuracy</u>

Because the goal of our study was to examine whether the models exhibit the signatures of

human perceptual decision making, we matched the accuracy of the models across the four

experimental conditions to the average accuracy in the human data. For all models, this was

achieved by adjusting the noise level in the images (separately for the "easy" and "difficult"

images) and the threshold parameter (separately for the speed and accuracy conditions). Lower

noise levels lead to higher accuracy, whereas higher threshold parameters lead to longer

processing and response times (and also contribute to higher accuracy levels).

Parameter values were adjusted using a coarse search followed by a fine search. In the coarse

search for RTNet, we varied the amplitude of uniform noise from 1 to 10 with increments of 1

(where the noise amplitude refers to the length of the interval over which the noise values are

generated), and the threshold value from 2 to 12 with increments of 2. The results were closest

to the human accuracy levels when the noise was in the range 2-3 for easy images and 4-5 for

difficult images, and the threshold was set to 2-4 for the speed focus condition and 6-8 for the

accuracy focus condition. We then conducted a fine search near those values by changing the

1001 noise level from 2 to 5 with 0.1 increments and changing the threshold values from 2 to 8 with

1002 0.5 increments. The closest match to human accuracy was achieved for noise levels of 2.1 and

1003 4.1 for easy and difficult images, respectively, and a threshold value of 3 for the speed

1004 condition and 6 for the accuracy condition. With these threshold and noise parameters, the

1005 evidence accumulation process in RTNet executed 6.5 sampling steps on average, although the

1006 distributions were wide such that the actual steps varied from 1 to 35. However, the number of

1007 processing steps depended on the experimental manipulation with the number of steps

1008 increasing for both difficult images and with stress on accuracy over speed (the average

1009 number of steps observed for each condition correspond to the height of the bars for RTNet in

1010 Figure 4B).

1011

1012 We used a similar procedure to tune the parameters of CNet, BLNet and MSDNet. Note that the

1013 threshold value for CNet is the softmax evidence at the output layer. The coarse search was

1014 performed using threshold values between 0.5 and 0.9 with increments of 0.04. The results

1015 were closest to the human accuracy levels when the threshold was in range 0.79-0.83 for the

1016 speed focus condition, and 0.86-0.9 for the accuracy focus condition. We then performed a fine

1017 search in these ranges by incrementing the threshold by steps of 0.01. The closest match to

1018 human accuracy was achieved for a threshold value of 0.83 for the speed condition and 0.9 for

1019 the accuracy condition. For noise levels, the best match to human accuracy was obtained when

1020 the noise levels were set to 1.42 and 1.83 for easy and difficult images, respectively.

1021

For BLNet, like CNet, the threshold value is the softmax evidence at the output layer. The

coarse search was performed using threshold values between 0.1 and 0.95 with increments of

0.2. The results were closest to the human accuracy levels when the threshold was in range 0.4-

0.5 for the speed focus condition, and 0.9-0.95 for the accuracy focus condition. We then

performed a fine search in these ranges by incrementing the threshold by steps of 0.05. The

closest match to human accuracy was achieved for a threshold value of 0.4 for the speed

condition and 0.95 for the accuracy condition. For noise levels, the best match to human

accuracy was obtained when the noise levels were set to 0.55 and 1.2 for easy and difficult

images, respectively.

1031

The threshold value for MSDNet is the softmax evidence at each early exit. The coarse search

was performed using the threshold values between 0.5 and 0.95 with increments of 0.05. The

results were closest to the human accuracy levels when the threshold was in range 0.55-0.65

for the speed focus condition, and 0.8-0.9 for the accuracy focus condition. We then performed

a fine search in these ranges by incrementing the threshold by steps of 0.01. The closest match

to human accuracy was achieved for a threshold value of 0.58 for the speed condition and 0.82

for the accuracy condition. For finding the optimal noise levels, the best match was obtained

when the noise levels were set to 1.9 and 3.0 for easy and difficult images, respectively.

1040

1041   Although we tried to closely match each network's accuracy with that of humans for each

1042   condition, our ability to do this was limited by the fact that a given SAT threshold must predict

1043   accuracies for both the easy and difficult conditions and a given noise level must predict

1044   accuracies for both the SAT conditions. Therefore, we obtained parameters estimates that

1045   resulted in closely (but not exactly) matched accuracies.

1046

1047   **Data availability**

1048   Behavioral data have been made publicly available at: https://osf.io/akwty.

1049

1050   **Code availability**

1051   All codes and trained models are publicly available at: https://osf.io/akwty.

1052

Acknowledgments

This work was supported by the National Institute of Health (award: R01MH119189) and Office

of Naval Research (award: N00014-20-1-2622), both awarded to D.R. The funders had no role in

study design, data collection and analysis, decision to publish or preparation of the manuscript

We thank Sashank Varma and Paul Verhaeghen for helpful suggestions about the analyses, as

well as Ana Shin and Himanaga Sahithi Pandi for assistance with data collection.

1059

1060   **Author Contributions**

1061   F.R. and M.S. performed research and analyzed the data; F.R. collected the data and wrote the

1062   first draft of the paper; M.S. and D.R. edited the paper; All authors designed research.

1063

1064   **Competing interests**

1065   The authors declare no competing interests.

1066
1067   **Figure Legends**

1068
Figure 1. Model architectures. (A) RTNet architecture. Unlike standard CNNs, the connection
weights in RTNet are not fixed but chosen from a distribution. A stimulus is processed multiple
times by the network, each time using a different set of weights sampled randomly from a
Bayesian neural network. The evidence from each processing step is accumulated and a
decision is made when the evidence for one of the choices reaches a threshold. This
architecture results in both stochastic decisions and variable RT. (B) Parallel cascaded network

(CNet) architecture[9]. CNet introduce propagation delays between residual blocks (each of
which consist of two convolutional layers). At each time step, all residual blocks parallelly
receive inputs from lower blocks but due to propagation delays, earlier blocks achieve stable
activations faster, whereas the later blocks require multiple processing steps to receive
complete input and achieve stable activations. The network can generate a decision via the
readout layer at any time step, although if the time step is less than the number of residual
blocks, the decision will be based on partial input in later blocks. (C) BLNet architecture[10]. BLNet
is a recurrent convolutional neural network (RCNN) with bottom-up and lateral recurrent
connections. Time steps are defined in terms of the number of feedforward sweeps of the
network. At each time-step, a layer receives feedforward input from the previous layer as well
as recurrent input from its own activations at the previous time-step. The readout can be
evaluated at each time-step to generate a response if it exceeds the threshold. The network's
can trade off speed and accuracy as higher thresholds require more feedforward and recurrent
computations, effectively resulting in a deeper network being unrolled across time. (D) Multi-
scale dense network (MSDNet) architecture[13]. In this network, each hidden layer features its
own classifier allowing MSDNet to make a separate decision after the processing in each layer is
completed. This allows the network to stop processing an image early if that image can already
be decoded from earlier layers of the network, thus resulting in different RTs for different
images.

1094
1095
Figure 2. Experiment task. (A) Trial structure. Each trial began with a fixation cross presented
for 500 to 1000 ms, followed by an image of a hand-written digit from the MNIST dataset
embedded in noise and presented for 300 ms. Only the digits 1-8 were used. Subjects reported
their choice and confidence (on a 4-point scale) using separate, untimed button presses. Note
that the noisy stimulus subtended a visual angle of 6.06° and did not cover the entire screen.
(B) Experimental design. The experiment included four conditions such that subjects judged
easy (low noise) or difficult (high noise) images while emphasizing either speed or accuracy.
Each condition featured 120 unique images that were the same across all subjects (total of 480
unique images in the experiment). In addition, each image was presented twice to allow the
estimation of the stochasticity of human perceptual choices. Each subject thus completed a
total of 960 trials. The images within the first and second sets of presentation were shown in a
different random order.

1108
Figure 3. Decision stochasticity in humans and all networks. Stochasticity of decisions made by
(A) humans, (B) RTNet, (C) CNet (D) BLNet, and (E) MSDNet. Warm colors indicate that the same
response was given both times an image was presented (whether the response was correct or
incorrect), whereas cool colors indicate that different responses were given for the two image
presentations (whether or not any of them was correct). Humans and RTNet exhibit stochastic
decision-making with stochasticity increasing with task difficulty and speed stress. However,
CNet, BLNet and MSDNet in their standard versions are fully deterministic. In the legend,
"consistent (two correct)" refers to instances when the correct responses was given for both
presentations of a given image, "consistent (zero correct)" refers to instances when the same

incorrect choice was made both times, "inconsistent (one correct)" refers to instances when
only one of the choices was correct, "inconsistent (zero correct)" refers to instances where
different incorrect choices were made each time.
1121
1122
Figure 4. Behavioral effects shown by human subjects and the models. (A) Accuracy for
humans (n = 60) decreases when response speed is emphasized as well as for more difficult
decisions. Both effects are exhibited by all the networks (n = 60 model instances). (B) RT for
humans becomes shorter when response speed is emphasized, as well as for easier decisions.
Both effects are also exhibited robustly by RTNet and BLNet. However, while both CNet and
MSDNet produced a robust effect for the speed manipulation, they exhibited much smaller
effects for the difficulty manipulation. RT for humans is measured in seconds and RT for the
networks is measured in the number of steps over which evidence is accumulated (for RTNet),
propagation steps (for CNet), feedforwards sweeps (for BLNet) and number of layers (for
MSDNet). (C) RT distributions for a representative subject/model. (D) The skewness of RT
distributions change across conditions. For humans and RTNet, the skewness of the RT
distributions was higher for easier tasks and for accuracy focus. However, CNet, BLNet, and
MSDNet showed clear deviations from the human pattern of results. (E) For humans, RTNet,
CNet and BLNet, two-sided paired t-tests showed that error trials were associated with higher
RT than correct trials. However, MSDNet showed the opposite pattern such that correct trials
were associated with longer processing time. (F) Confidence for correct trials was higher than
confidence for error trials for humans and all networks. For all panels, dots represent individual
subjects; error bars show SEM. The p-values are derived from two-sided Wilcoxon's signed rank
tests (for mean RT comparisons) and two-sided paired t-tests (for all other measures).
1142
1143
Figure 5. Image-by-image correlation between human data and each model across all
experimental conditions for individual subjects. Correlation between data from individual
human subjects (n = 60) and the group average, and correlations between data from individual
subjects and the average of all 60 instances for RTNet, CNet, BLNet, and MSDNet. The
correlations are computed separately for accuracy, RT, and confidence across all conditions.
Critically, the correlation is stronger for RTNet than CNet, BLNet or MSDNet for each measure.
The subject-to-group correlation provides an estimate of the noise ceiling for the network
correlations. Dots represent individual subjects; error bars show SEM. The p-values are derived
from two-sided paired t-tests.
1153
1154
1155
Figure 6. Image-by-image correlation between human data and each network within each
experimental condition. Correlation between data from individual human subjects (n = 60) and
the group average, as well as the average of all 60 instances for RTNet, CNet, BLNet, and
MSDNet. The correlations are computed separately for accuracy, RT, and confidence within
each experimental condition: A) speed focus; easy, B) speed focus; difficult, C) accuracy focus;
easy, D) accuracy focus; difficult. The correlation is significantly stronger for RTNet compared to

CNet (8/12 comparisons), BLNet (7/12 comparisons), and MSDNet (7/12 comparisons). RTNet
never exhibits significantly weaker correlations than CNet, BLNet, or MSDNet. For all panels,
dots represent individual subjects; error bars show SEM. The p-values are derived from two-
sided paired t-tests.
1166
1167
Figure 7. Humans who are more similar to the group average are also more similar to each
model. (A) We observed a strong positive correlation between the subject-to-group and
subject-to-RTNet similarity values for accuracy, RT, and confidence. This finding indicates that
individual subjects whose behavior was more similar to the group average on per image basis
were also more similar to the predictions made by RTNet. (B-D) Similar results were also
observed for CNet, BLNet (except for accuracy correlations), and MSDNet, although these
correlations tended to be lower than for RTNet. Dots represent individual subjects; lines depict
best-fit regressions; shaded areas depict 95% confidence intervals around the regression
estimate.
1177
1178
Figure 8. Comparison between individual subjects and the models in predicting the group
data. RTNet significantly outperformed individual human subjects (n = 60) in predicting group
accuracy, RT, and confidence. On the other hand, CNet, BLNet and MSDNet were worse than
individual humans in predicting accuracy, and CNet and MSDNet were worse in predicting RT.
We note that the effect sizes are very small for RTNet's predictions of accuracy and MSDNet's
predictions of RT. However, the effect was sufficiently consistent across subjects to make these
results statistically significant (RTNet outperformed 44/60 subjects in predicting accuracy and
MSDNet did worse than 43/60 subjects in predicting RT). For all panels, dots represent
individual subjects; error bars show SEM. The p-values are derived from two-sided one-sample
t-tests.

References

References

1. Ratcliff, R. A theory of memory retrieval. *Psychol Rev* **85**, 59–108 (1978).
2. Ratcliff, R. & McKoon, G. The diffusion decision model: theory and data for two-choice
decision tasks. *Neural Comput* **20**, 873–922 (2008).
3. Ashby, F. G. & Townsend, J. T. Varieties of Perceptual Independence. *Psychol Rev* **93**,
154–179 (1986).
4. Green, D.M. and Swets, J. A. (1966). *Signal Detection Theory and Psychophysics.* (John
Wiley, 1966).
5. Kriegeskorte, N. Deep Neural Networks: A New Framework for Modeling Biological Vision
and Brain Information Processing. *http://dx.doi.org/10.1146/annurev-vision-082114-*
035447 **1**, 417–446 (2015).
6. Kriegeskorte, N. & Golan, T. Neural network models and deep learning. *Current Biology*
29, R231–R236 (2019).
7. Kietzmann, T. C., McClure, P. & Kriegeskorte, N. Deep Neural Networks in Computational
Neuroscience. *Oxford Research Encyclopedia of Neuroscience* (2019)
doi:10.1093/ACREFORE/9780190264086.013.46.
8. Yamins, D. L. K. & DiCarlo, J. J. Using goal-driven deep learning models to understand
sensory cortex. *Nature Neuroscience 2016 19:3* **19**, 356–365 (2016).
9. Iuzzolino, M. L., Mozer, M. C. & Bengio, S. Improving Anytime Prediction with Parallel
Cascaded Networks and a Temporal-Difference Loss. *Adv Neural Inf Process Syst* **33**,
27631–27644 (2021).
10. Spoerer, C. J., Kietzmann, T. C., Mehrer, J., Charest, I. & Kriegeskorte, N. Recurrent neural
networks can explain flexible trading of speed and accuracy in biological vision. *PLoS*
Comput Biol **16**, (2020).
11. Zhang, L. *et al.* SCAN: A Scalable Neural Networks Framework Towards Compact and
Efficient Models. *Adv Neural Inf Process Syst* **32**, (2019).
12. Subramanian, A., Sizikova, E., Kumbhar, O., Majaj, N. & Pelli, D. G. Benchmarking dynamic
neural-network models of the human speed-accuracy trade off. *J Vis* **22**, 4359–4359
(2022).
13. Huang, G. *et al.* Multi-Scale Dense Networks for Resource Efficient Image Classification.
6th International Conference on Learning Representations, ICLR 2018 - Conference Track
Proceedings (2017).
14. Kalanthroff, E., Davelaar, E. J., Henik, A., Goldfarb, L. & Usher, M. Task conflict and
proactive control: A computational theory of the Stroop task. *Psychol Rev* **125**, 59–82
(2018).
15. Mewhort, D. J. K., Braun, J. G. & Heathcote, A. Response Time Distributions and the
Stroop Task: A Test of the Cohen, Dunbar, and McClelland (1990) Model. *J Exp Psychol*
Hum Percept Perform **18**, 872–882 (1992).
16. Cohen, J. D., Dunbar, K. & McClelland, J. L. On the control of automatic processes: a
parallel distributed processing account of the Stroop effect. *Psychol Rev* **97**, 332–361
(1990).

17.   Koivisto, M., Railo, H., Revonsuo, A., Vanni, S. & Salminen-Vaparanta, N. Recurrent
Processing in V1/V2 Contributes to Categorization of Natural Scenes. *The Journal of*
Neuroscience **31**, 2488 (2011).

18.   Tang, H. *et al.* Recurrent computations for visual pattern completion. *Proc Natl Acad Sci*
U S A **115**, 8835–8840 (2017).

19.   Lamme, V. A. F. & Roelfsema, P. R. The distinct modes of vision offered by feedforward
and recurrent processing. *Trends Neurosci* **23**, 571–579 (2000).

20.   Kar, K. & DiCarlo, J. J. Fast Recurrent Processing via Ventrolateral Prefrontal Cortex Is
Needed by the Primate Ventral Stream for Robust Core Visual Object Recognition.
Neuron **109**, 164-176.e5 (2021).

21.   Kar, K., Kubilius, J., Schmidt, K., Issa, E. B. & DiCarlo, J. J. Evidence that recurrent circuits
are critical to the ventral stream's execution of core object recognition behavior. *Nature*
Neuroscience 2019 22:6 **22**, 974–983 (2019).

22.   Goetschalckx, L. *et al.* Computing a human-like reaction time metric from stable
recurrent vision models. (2023).

23.   Bogacz, R., Brown, E., Moehlis, J., Holmes, P. & Cohen, J. D. The physics of optimal
decision making: A formal analysis of models of performance in two-alternative forced-
choice tasks. *Psychol Rev* **113**, 700–765 (2006).

24.   Heathcote, A. & Matzke, D. Winner takes all! What are race models, and why and how
should psychologists use them? *Curr Dir Psychol Sci* (2022).

25.   Vickers, D. Evidence for an Accumulator Model of Psychophysical Discrimination.
http://dx.doi.org/10.1080/00140137008931117 **13**, 37–58 (2007).

26.   Forstmann, B. U., Ratcliff, R. & Wagenmakers, E.-J. Sequential Sampling Models in
Cognitive Neuroscience: Advantages, Applications, and Extensions. *Annu Rev Psychol* **67**,
641–66 (2016).

27.   Rahnev, D. Confidence in the Real World. *Trends Cogn Sci* **24**, 590–591 (2020).

28.   Yeon, J. & Rahnev, D. The suboptimality of perceptual decision making with multiple
alternatives. *Nature Communications 2020 11:1* **11**, 1–12 (2020).

29.   Drugowitsch, J., Wyart, V., Devauchelle, A. D. & Koechlin, E. Computational Precision of
Mental Inference as Critical Source of Human Choice Suboptimality. *Neuron* **92**, 1398–
1411 (2016).

30.   Li, H. H. & Ma, W. J. Confidence reports in decision-making with multiple alternatives
violate the Bayesian confidence hypothesis. *Nat Commun* **11**, 1–11 (2020).

31.   Churchland, A. K., Kiani, R. & Shadlen, M. N. Decision-making with multiple alternatives.
Nat Neurosci **11**, 693 (2008).

32.   Deng, L. The MNIST database of handwritten digit images for machine learning research.
IEEE Signal Process Mag **29**, 141–142 (2012).

33.   Krizhevsky, A., Sutskever, I. & Hinton, G. E. ImageNet Classification with Deep
Convolutional Neural Networks. *Advances in Neural Information Processing Systems 25*
(NIPS 2012)
https://proceedings.neurips.cc/paper/2012/hash/c399862d3b9d6b76c8436e924a68c45
b-Abstract.html (2012).

34.   Geirhos, R. *et al.* Generalisation in humans and deep neural networks. *Advances in*
Neural Information Processing Systems 31

https://proceedings.neurips.cc/paper/2018/hash/0937fb5864ed06ffb59ae5f9b5ed67a9-
Abstract.html (2018).

35. Geirhos, R. *et al.* Comparing deep neural networks against humans: object recognition
when the signal gets weaker. (2017) doi:10.48550/arxiv.1706.06969.

36. Beck, J. M., Ma, W. J., Pitkow, X., Latham, P. E. & Pouget, A. Not Noisy, Just Wrong: The
Role of Suboptimal Inference in Behavioral Variability. *Neuron* **74**, 30–39 (2012).

37. Renart, A. & Machens, C. K. Variability in neural activity and behavior. *Curr Opin*
Neurobiol **25**, 211–220 (2014).

38. Heitz, R. P. The speed-accuracy trade off: history, physiology, methodology, and
behavior. *Front Neurosci* **8**, 150 (2014).

39. Heitz, R. P. & Schall, J. D. Neural mechanisms of speed-accuracy trade off. *Neuron* **76**,
616–28 (2012).

40. Ratcliff, R. & Rouder, J. N. Modeling Response Times for Two-Choice Decisions. *Psychol*
Sci **9**, 347–356 (1998).

41. Wagenmakers, E.-J. & Brown, S. On the Linear Relation Between the Mean and the
Standard Deviation of a Response Time Distribution. *Psychol Rev* **114**, 830–841 (2007).

42. Brown, S. & Heathcote, A. The simplest complete model of choice response time: Linear
ballistic accumulation. *Cogn Psychol* **57**, 153–178 (2008).

43. Forstmann, B. U. *et al.* Striatum and pre-SMA facilitate decision-making under time
pressure. *Proceedings of the National Academy of Sciences* **105**, 17538–17542 (2008).

44. Luce, R. D. *Response Times*. (Oxford University Press, New York, 1986).
doi:10.1093/acprof:oso/9780195070019.001.0001.

45. Ratcliff, R. A diffusion model account of response time and accuracy in a brightness
discrimination task: fitting real data and failing to fit fake but plausible data. *Psychon Bull*
Rev **9**, 278–291 (2002).

46. Rahnev, D. Visual metacognition: Measures, models, and neural correlates. *Am Psychol*
76, 1445–1453 (2021).

47. Wyart, V. & Koechlin, E. Choice variability and suboptimality in uncertain environments.
Curr Opin Behav Sci **11**, 109–115 (2016).

48. Findling, C. & Wyart, V. Computation noise in human learning and decision-making:
origin, impact, function. *Curr Opin Behav Sci* **38**, 124–132 (2021).

49. Rafiei, F. & Rahnev, D. Qualitative speed-accuracy tradeoff effects that cannot be
explained by the diffusion model under the selective influence assumption. *Scientific*
Reports 2021 11:1 **11**, 1–19 (2021).

50. Gold, J. I. & Shadlen, M. N. The Neural Basis of Decision Making. (2007)
doi:10.1146/annurev.neuro.29.051605.113038.

51. Yeung, N. & Summerfield, C. Metacognition in human decision-making: confidence and
error monitoring. *Philosophical Transactions of the Royal Society B: Biological Sciences*
367, 1310–1321 (2012).

52. Heathcote, A. & Love, J. Linear deterministic accumulator models of simple choice. *Front*
Psychol **3**, 292 (2012).

53. Spoerer, C. J., Kietzmann, T. C., Mehrer, J., Charest, I. & Kriegeskorte, N. Recurrent neural
networks can explain flexible trading of speed and accuracy in biological vision. *PLoS*
Comput Biol **16**, e1008215 (2020).

54.   Ratcliff, R. & Smith, P. L. A Comparison of Sequential Sampling Models for Two-Choice
Reaction Time. *Psychol Rev* **111**, 333–367 (2004).

55.   Brown, S. & Heathcote, A. A ballistic model of choice response time. *Psychol Rev* **112**,
117–128 (2005).

56.   Tillman, G., Van Zandt, T. & Logan, G. D. Sequential sampling models without random
between-trial variability: the racing diffusion model of speeded decision making. *Psychon*
Bull Rev **27**, 911–936 (2020).

57.   Mizuseki, K., Sirota, A., Pastalkova, E. & Buzsáki, G. Theta Oscillations Provide Temporal
Windows for Local Circuit Computation in the Entorhinal-Hippocampal Loop. *Neuron* **64**,
267–280 (2009).

58.   Nayebi, A. *et al.* Task-Driven Convolutional Recurrent Models of the Visual System. *Adv*
Neural Inf Process Syst **2018-December**, 5290–5301 (2018).

59.   Issa, E. B., Cadieu, C. F. & Dicarlo, J. J. Neural dynamics at successive stages of the ventral
visual stream are consistent with hierarchical error signals. *Elife* **7**, (2018).

60.   Kaufman, M. T. & Churchland, A. K. Sensory noise drives bad decisions. *Nature 2013*
496:7444 **496**, 172–173 (2013).

61.   Brunton, B. W., Botvinick, M. M. & Brody, C. D. Rats and humans can optimally
accumulate evidence for decision-making. *Science* **340**, 95–98 (2013).

62.   Osborne, L. C., Lisberger, S. G. & Bialek, W. A sensory source for motor variation. *Nature*
2005 437:7057 **437**, 412–416 (2005).

63.   Huk, A. C. & Shadlen, M. N. Neural Activity in Macaque Parietal Cortex Reflects Temporal
Integration of Visual Motion Signals during Perceptual Decision Making. *Journal of*
Neuroscience **25**, 10420–10436 (2005).

64.   Huk, A. C., Katz, L. N. & Yates, J. L. The Role of the Lateral Intraparietal Area in (the Study
of) Decision Making. *Annu Rev Neurosci* **40**, 349 (2017).

65.   Bahl, A. & Engert, F. Neural circuits for evidence accumulation and decision making in
larval zebrafish. *Nature Neuroscience 2019 23:1* **23**, 94–102 (2019).

66.   Hanks, T. D., Kiani, R. & Shadlen, M. N. A neural mechanism of speed-accuracy tradeoff in
macaque area LIP. *Elife* **2014**, (2014).

67.   van Bergen, R. S. & Kriegeskorte, N. Going in circles is the way forward: the role of
recurrence in visual inference. *Current Opinion in Neurobiology* vol. 65 176–193 Preprint
at https://doi.org/10.1016/j.conb.2020.11.009 (2020).

68.   Spoerer, C. J., McClure, P. & Kriegeskorte, N. Recurrent Convolutional Neural Networks: A
Better Model of Biological Object Recognition. *Front Psychol* **0**, 1551 (2017).

69.   Kietzmann, T. C. *et al.* Recurrence is required to capture the representational dynamics
of the human visual system. *Proceedings of the National Academy of Sciences* **116**,
21854–21863 (2019).

70.   Schwarzschild, A. *et al.* Can You Learn an Algorithm? Generalizing from Easy to Hard
Problems with Recurrent Networks. *Advances in Neural Information Processing Systems*
34
https://proceedings.neurips.cc/paper/2021/hash/3501672ebc68a5524629080e3ef60aef
-Abstract.html (2021).

71.   Zhou, D. *et al.* Least-to-Most Prompting Enables Complex Reasoning in Large Language
Models. (2022) doi:10.48550/arxiv.2205.10625.

72. Saltelli, A. *et al.* Sensitivity Analysis for Neural Networks. Natural Computing. *Risk*
Analysis **159**, 179–201 (2009).
73. Ko, J. H., Kim, D., Na, T., Kung, J. & Mukhopadhyay, S. Adaptive weight compression for
memory-efficient neural networks. *Proceedings of the 2017 Design, Automation and Test*
in Europe, DATE 2017 199–204 (2017) doi:10.23919/DATE.2017.7926982.
74. Koutník, J., Gomez, F. & Schmidhuber, J. Evolving neural networks in compressed weight
space. *Proceedings of the 12th Annual Genetic and Evolutionary Computation*
Conference, GECCO '10 619–625 (2010) doi:10.1145/1830483.1830596.
75. Kung, J., Kim, D. & Mukhopadhyay, S. A power-aware digital feedforward neural network
platform with backpropagation driven approximate synapses. *Proceedings of the*
International Symposium on Low Power Electronics and Design **2015-September**, 85–90
(2015).
76. Tsvetkov, C., Malhotra, G., Evans, B. D. & Bowers, J. S. The role of capacity constraints in
Convolutional Neural Networks for learning random versus natural data. *Neural Netw*
161, 515–524 (2023).
77. Malhotra, G., Leslie, D. S., Ludwig, C. J. H. & Bogacz, R. Overcoming indecision by
changing the decision boundary. *J Exp Psychol Gen* **146**, 776 (2017).
78. Drugowitsch, J., Moreno-Bote, R. N., Churchland, A. K., Shadlen, M. N. & Pouget, A. The
Cost of Accumulating Evidence in Perceptual Decision Making. *Journal of Neuroscience*
32, 3612–3628 (2012).
79. Rahnev, D. & Denison, R. N. Suboptimality in perceptual decision making. *Behavioral and*
Brain Sciences **41**, (2018).
80. Evans, N. J., Bennett, A. J. & Brown, S. D. Optimal or not; depends on the task. *Psychon*
Bull Rev **26**, 1027–1034 (2019).
81. Brainard, D. H. The Psychophysics Toolbox. *Spat Vis* **10**, 433–436 (1997).
82. Chen, Y. C. A tutorial on kernel density estimation and recent advances.
https://doi.org/10.1080/24709360.2017.1396742 **1**, 161–187 (2017).
83. Waskom, M. L. seaborn: statistical data visualization. *J Open Source Softw* **6**, 3021 (2021).
84. Jospin, L. V., Buntine, W., Boussaid, F., Laga, H. & Bennamoun, M. Hands-on Bayesian
Neural Networks -- a Tutorial for Deep Learning Users. (2020).
85. Paszke, A. *et al.* PyTorch: An Imperative Style, High-Performance Deep Learning Library.
Advances in Neural Information Processing Systems 32 (NeurIPS)
https://proceedings.neurips.cc/paper/2019/hash/bdbca288fee7f92f2bfa9f7012727740-
Abstract.html (2019).
86. Bingham, E. *et al.* Pyro: Deep Universal Probabilistic Programming. *Journal of Machine*
Learning Research **20**, 1–6 (2019).
87. Kingma, D. P. & Welling, M. Auto-Encoding Variational Bayes. *2nd International*
Conference on Learning Representations, ICLR 2014 - Conference Track Proceedings
(2013) doi:10.48550/arxiv.1312.6114.
88. Kingma, D. P. & Ba, J. L. Adam: A Method for Stochastic Optimization. *3rd International*
Conference on Learning Representations, ICLR 2015 - Conference Track Proceedings
(2014) doi:10.48550/arxiv.1412.6980.
89. Deng, J. *et al.* ImageNet: A large-scale hierarchical image database. 248–255 (2010)
doi:10.1109/CVPR.2009.5206848.

90.   Kumbhar, O., Sizikova, E., Majaj, N. & Pelli, D. G. Anytime Prediction as a Model of
1412   Human Reaction Time. (2020).
1413   91.   Huang, G. *et al.* Multi-Scale Dense Networks for Resource Efficient Image Classification.
1414   *6th International Conference on Learning Representations, ICLR 2018 - Conference Track*
1415   *Proceedings* (2017).
1416

A) Subjects more similar to the group are more similar to RTNet

B) Subjects more similar to the group are more similar to CNet

C) Subjects more similar to the group are more similar to BLNet

D) Subjects more similar to the group are more similar to MSDNet

Accuracy

p < 0.001 (RTNet)
p < 0.001 (CNet)
p < 0.001 (BLNet)
p < 0.001 (MSDNet)

RT

p < 0.001 (RTNet)
p < 0.001 (CNet)
p < 0.001 (BLNet)
p < 0.001 (MSDNet)

Confidence

p < 0.001 (RTNet)
p = 0.719 (CNet)
p < 0.001 (BLNet)
p < 0.001 (MSDNet)

$r_{model} - r_{subject}$