Data Fusion by Matrix Completion for Exposome Target Interaction Prediction

Kai Wang[1], Nicole Kim[1], Maryam Bagherian[1,2], Kai Li[1], Elysia Chou[1], Justin A. Colacino[3,4], Dana C. Dolinoy[3,4], Maureen A. Sartor[1,5,*]

[1]Department of Computational Medicine and Bioinformatics, School of Medicine, University of Michigan, Ann Arbor, MI 48109, USA

[2]Michigan Institute for Data Science (MIDAS), University of Michigan, Ann Arbor, MI 48109, USA

[3]Department of Environmental Health Sciences, School of Public Health, University of Michigan, Ann Arbor, MI 48109, USA

[4]Department of Nutritional Sciences, School of Public Health, University of Michigan, Ann Arbor, MI 48109, USA

[5]Department of Biostatistics, School of Public Health, University of Michigan, Ann Arbor, MI 48109, USA

*Correspondence:
Maureen A Sartor
sartorma@umich.edu
Room 2017, Palmer Commons
100 Washtenaw Avenue
Ann Arbor, MI 48109-2218

Conflicts of Interest
The authors declare they have nothing to disclose.

Abstract

Background: Exposure to toxic chemicals presents a huge health burden and disease risk. Key to
understanding which chemicals cause specific toxic effects is determining the molecular target(s) of these
chemicals. Given that over a thousand new chemicals are produced annually, it is infeasible to perform a
comprehensive safety assessment for all novel chemicals due to limited resources. Thus, a robust
computational method for discovering targets of environmental exposures, which can then be used to
prioritize chemicals for further study, is a promising direction for public health research.
Objectives: We implemented a novel matrix completion algorithm named coupled matrix-matrix
completion (CMMC) for predicting exposome-target interactions.
Methods: The low rank matrix completion problem can be described as predicting missing values of an
incomplete un-observed/under-observed or partially observed matrix. Different from previous matrix
completion algorithms based on matrix factorization, the CMMC algorithm incorporates two coupled
matrices in form of auxiliary information to help better optimize the distance metric and maintains a fast
runtime. The present data fusion model has the potential to automatically reveal shared and unshared
components through modeling constraints. The two coupled matrices represent the relationships among
the chemical exposures and gene targets, respectively, and help jointly analyze incomplete data sets. We
collected and processed relevant data from the Comparative Toxicogenomics Database (CTD) as a
benchmark dataset for implementing and testing our method and comparing it to alternative prediction
methods.
Results: Our method achieved an AUC of 0.89 on the benchmark dataset generated in this study.
Compared to other state-of-the-art methods, CMMC achieved the best performance for predicting
environmental chemical-gene target interactions. The case study shows that CMMC can be used to
discover potential molecular targets of novel chemicals without any prior bioactivity knowledge.
Discussion: Our CMMC approach is a powerful method for predicting the target genes of environmental
exposures.

Introduction

Phenotype can be defined as all observable characteristics of an organism, which are influenced by
genotype and the environment. Genomic studies have provided extraordinary genetic knowledge
corresponding to different phenotypes, including generating revolutionary knowledge used to investigate
the genetic origin of diseases. However, these studies also revealed that genetic variation only partially
contributes to the origin of diseases[1]. A great portion of human disease is not caused by genetic variation
but by environmental factors, however the effects of environmental factors on phenotypes are not as well
studied due to the complexity of environmental exposures[2]. In 2005, as a complement to the genome, the
"exposome" was conceived by C. P. Wild[3], defined as the totality of exposures to which the public comes
in contact and the corresponding biological responses.

Environmental exposures include but are not limited to environmental chemicals that can enter the human
body through routes of exposure including inhalation, ingestion, or dermal. The Global Burden of Disease
project[4] estimates that 9 million deaths per year are caused by air, water, and soil pollution alone. This
number is likely to be an underestimate due to the fact that many new chemical compounds with
uncharacterized toxicological profiles are created and released into our environment annually. In
PubChem[5,6], the number of registered chemical compounds increased from 10 million in 2008 to 100
million in 2021. To perform comprehensive toxicity screenings of all these chemicals and study their
links to health effects represent a great challenge due to limited time and funds[7]. Traditional animal-based
in vivo toxicity testing is an expensive and time-consuming task. In addition, the power of using animal
models to predict human response to chemicals is limited due to often poor correlation with human

findings[8]. Compared to *in vivo* studies, *in vitro* studies that assess the toxic effects of chemicals on
cultured bacteria or mammalian cells can greatly accelerate toxicity testing and reduce animal usage[9].
However, *in vivo* physiological environments cannot be easily mimicked in the *in vitro* setting[10].
Therefore, *in vivo* and *in vitro* methods in toxicity testing can be integrated to perform a comprehensive
safety assessment, but unfortunately, performing these safety assessments over millions of chemicals is
resource intensive and thus impractical.

Computational methods are widely used in toxicology research to organize and analyze different types of
data[11]. Corresponding methods have also been developed and applied to predict chemical toxicity.
Previously developed toxicity prediction methods include structure-activity relationship (SAR)[12,13], read-
across[14,15], and quantitative structure-activity relationship (QSAR)[16–18]. These methods usually focus on
using chemical features to predict a binary label for chemicals, such as whether a chemical is a carcinogen
or not, or whether the chemical activates certain marker genes or related biological pathways. Thus, the
overall corresponding biological responses caused by a chemical cannot be described through the
aforementioned methods. Furthermore, these methods do not exploit the vast amount of data accumulated
to date for similar chemicals and molecular targets. Therefore, a method that takes advantage of both
chemical features and biological knowledge, as well as the known complex relationships among them,
could radically improve and expand the scope of chemical toxicity predictions.

Similar to exposure-target predictions, many computational methods were developed and applied to find
drug-target interactions (DTI) in pharmaceutical studies, such as deep learning methods, tree-based
methods, network-based methods, etc. Matrix completion is a task to find the missing values in a partially
observed matrix. Corresponding algorithms and applications have been widely used in DTI prediction.
Compared to other types of methods, a benefit of matrix completion algorithms is they can easily handle
big datasets with high sparsity without overfitting[19]. In DTI predictions, a binary value (i.e., 1 or 0) is
usually used to indicate the interaction between a chemical drug and its molecular targets, because drugs
are typically designed with specific molecular targets in mind. Different from DTI, chemical exposures
were not designed to interact with any specific gene targets, they often gave broader ranging effects, and
thus a continuous value approach is more appropriate than the typical binary approach used for DTI.

In this study, we take an important step towards this goal by implementing a new matrix completion
algorithm[20] called coupled matrix-matrix completion (CMMC) to predict the target genes of
environmental chemicals on a broad scale. CMMC algorithm falls under the youngest branch of data
fusion that is intermediate/partial integration, i.e., it does not necessarily fuse the input data, nor does it
develop separate models for each source. Instead, it preserves the structure of the data sources and merges
them at the level of a predictive model[21,22], here CMMC. To our knowledge, this is the first time such a
large-scale prediction effort has been attempted for exposure-target interactions. CMMC differs from
previous matrix completion algorithms based on matrix factorizations and is subject to a Distance Metric
Learning (DML) constraint, i.e., it directly utilizes supporting information (i.e., coupled matrices about
similarities among chemicals and genes) in the main iteration to learn an optimal metric for imputing
missing values. The method benefits from strong results in group action and representation theory and
guarantees a unique solution for the optimization problem. A different implementation of CMMC using a
binary matrix was shown to outperform alternative approaches in the related task of predicting drug target
interactions[20]. In this study compared with previously published methods, CMMC achieved better
performance on the benchmark datasets. To further test our approach, the representative endocrine
disrupting chemical, bisphenol A (BPA) and three of structurally related replacements, i.e., bisphenol B
(BPB), Bis (4-hydroxyphenyl) methane (BPF), and 4,4'-Sulfonyldiphenol (BPS), were utilized in a case
study. Compared to the bioactivity data from the CompTox database[23], over half of the active genes of

these four chemicals in CompTox were predicted in the top 1000 interactive genes in our results. In
summary, CMMC is a powerful tool to discover potential chemical-gene interactions and provide vital
information for prioritizing further toxicology research.

Methods and Materials

CMMC Algorithm

119 A low-rank matrix completion for an incomplete unobserved/under-observed matrix $\mathbf{X}$ can be formulated
120 as:

$$\min_{\mathbf{M}} \|\mathbf{M}\|_{\mu}, \text{ s. t. } \mathbf{X}_{\Omega} = \mathbf{M}_{\Omega} \quad (1)$$

where Ω denotes an index set and μ is a proper metric to be determined. In other words, given an
incomplete unobserved/under-observed matrix $\mathbf{X}$, the goal is to find matrix $\mathbf{M}$ whose rank is minimum,
and it has all the known entries in $\mathbf{X}$. Most methods for matrix (also tensor) completion rely upon the
choice of a fixed metric, for instance the *Euclidean* or *nuclear* norm. If there is a high correlation between
the rows/columns in a matrix, then a different metric given by the data itself could be adopted. This is part
of a well-known branch in machine learning known as Distance Metric Learning that aims to learn
distances from the data[24]. When working with problems including data points in *n*-dimensional space, $\Box^n$,
Mahalanobis distance, as the inverse of covariance matrix of the data, learns a metric induced by the data
points itself. As proposed in Bagherian M, et al[20], CMMC method development is heavily based on
algebraic property of symmetric matrices which can be thought of elements of *General Linear Group* (GL)
and *Special Linear Group* (SL). These linear groups belong to a class of groups, called *reductive* groups[25].
Norm minimization problems when put in the form of reductive groups (with a proper group action) can
in fact obtain a unique minimum (up to an orbit) using the algebraic results given in *Kempf-Ness*
theorem[25]. *Mahalanobis distance* is equivalent to *Euclidean distance* after a linear change of coordinate
and normalization with respect to covariance matrix. The *Kempf-Ness theorem* shows that there is
essentially a *unique* change of coordinates that is optimal in a certain sense.

Let data matrix $\mathbf{X} \in \Box^{n \times m}$ be given, where to any of its modes, n and m, auxiliary information in form of
symmetric matrices is present, i.e., adjacent to the mode *n*, there exists an $n \times n$ square symmetric matrix,
called $\mathbf{M}_{nn}$ and the same for the mode m and matrix $\mathbf{M}_{mm}$. These two coupled/auxiliary matrices can be
thought of regularization terms of the matrix completion problem.

The goal is to find completed observed matrix, $\mathbf{Y} \in \Box^{n \times m}$ such that the known entries of $\mathbf{X}$ and $\mathbf{Y}$ match.
To this end, through the following optimization problem, we first learn two matrices $\mathbf{S}_{nn}$ and $\mathbf{S}_{mm}$ using the
given side information, $\mathbf{M}_{nn}$ and $\mathbf{M}_{mm}$, and use them to learn the low rank completed version of $\mathbf{X}$, i.e., $\mathbf{Y}$.
Therefore, the optimization problem to be minimized can be outlined as:

$$\min_{\Gamma} \|\mathbf{S}_{nn} \mathbf{Y} \mathbf{S}_{mm}^{T}\|_{F}^{2} + \lambda_n \, \mathrm{T}_r(\mathbf{S}_{nn} \mathbf{M}_{nn} \mathbf{S}_{nn}^{T}) + \lambda_m \, \mathrm{T}_r(\mathbf{S}_{mm} \mathbf{M}_{mm} \mathbf{S}_{mm}^{T}), \quad (2)$$

$$\text{s. t. } \Omega_{nm}(\mathbf{Y}) = v_{nm}$$

145 over the optimization set $\Gamma = \{\mathbf{S}_{nn} \in \text{SL}_n, \mathbf{S}_{mm} \in \text{SL}_m, \mathbf{Y} \in \Box^{n \times m}\}$ and for some regularization parameters λ_n,
146 λ_m. The optimization problem given in Eq. 2 is subject to a vector constraint v_{nm}. If the known entries of $\mathbf{X}$
147 (or $\mathbf{Y}$ since the known entries match) are at positions

$$\Omega_{nm} = ((i_1, j_1), (i_2, j_2), \dots, (i_k, j_k)) \quad (3)$$

148 this constraint can be written as

$$\Omega_{nm}(\mathbf{Y}) = v_{nm} \quad (4)$$

149 where $v_{nm} \in \square^k$ is some fixed vector consisting of only known then fixed entries. If it happens that the
150 auxiliary matrices $\mathbf{M}_{nn}$ and $\mathbf{M}_{mm}$ are under-observed, the vector constraint may be imposed over these two
151 matrices as a *pre-processing* step. The additional constraints may be written as:

$$\Omega_{nn}(\mathbf{M}_{nn}) = v_{nn} \ \& \ \Omega_{mm}(\mathbf{M}_{mm}) = v_{mm} \quad (5)$$

It is noteworthy that without loss of generality one may perform an extra normalization step with respect
to the non-zero determinant of a given symmetric matrix in order for it to belong to the special linear
group, SL. Additional constraint, such as positive-definite constraint, or other convex regularization term
may also be integrated to the main objective function given in Eq. 2, should they be required.

CMMC was originally implemented in MATLAB for a binary interaction matrix in DTI predictions. To
reduce the run time, we re-implemented the CMMC algorithm in C++ (GCC 9.2.0) using Armadillo[26]
(v10.1.2) with a OpenBLAS backend and tested the algorithm with nonbinary interaction matrices.

Chemical-gene Interaction Dataset and Normalization

We downloaded chemical-gene interaction data from the Comparative Toxicogenomics Database (CTD
v16202)[27]. Human-related interactions were extracted and preprocessed for this study. In total, the CTD
reported 871,112 chemical-gene interactions documented in humans, classified into 132 categories. Since
this study is focused on environmental exposure chemicals, any drugs listed in the CTD were excluded.
Data from Therapeutic Target Database[28] (TTD) and DrugBank[29] were used to filter out any drugs from
the human CTD dataset by mapping chemicals to PubChem Compound IDs[6] (CIDs) (Supplementary
Figure 1). After the drug filtering, 4,864 chemicals and 22,606 genes with 201,375 known interactions
from human studies were included for further data normalization, resulting in a sparsity level of 99.8% for
the total chemical-gene matrix. For this study, we calculated an *a priori* interaction value for each known
chemical-gene pair and normalized these values in two ways without considering the different interaction
categories. The first normalization method (N1) uses the number of occurrences of a chemical-gene pair
in the dataset. The second method (N2) uses the number of unique PubMed IDs[30] listed for a chemical-
gene pair (same chemical-gene pairs could be reported in different publications). Since approximately 78%
of the chemical-gene pairs had only one interaction record in the dataset, the resulting distribution was
highly skewed towards zero. A log transformation was therefore applied to both N1 and N2 interaction
values to reduce the skewness of their respective distributions. Thus, for a specific chemical-gene pair,
there were two values to represent the interactions. Finally, interaction values were scaled to be in the
range of 0 to 1 (Supplementary Table 1).

Chemical-chemical Similarities

Two widely used chemical fingerprints[31] were applied to calculate the chemical-chemical similarities, i.e.,
Morgan fingerprints and Topological Torsion fingerprints. The SMILES[32] (simplified molecular-input
line-entry system) string was used for the aforementioned two fingerprint calculations. The CIRpy (v1.0.2)
and pubchempy (v1.0.4) Python packages were used to extract the SMILES strings for all chemicals in
our dataset from the PubChem database. Chemical-chemical similarities were calculated using the RDKit
Python package[33] (v2020.09.1).

Gene-gene Similarities

There are many ways to calculate gene-gene similarities. Pair-wise sequence alignment algorithms are
widely used for calculating gene similarities based on either DNA/RNA sequences or protein sequences
of genes. However, these methods cannot precisely reflect the biological similarities among genes. Thus,
instead of using a sequence alignment-based method for calculating the gene-gene similarities, we used a

Gene Ontology[34] (GO) based method called GOSemSim[35] to measure the gene-gene similarities. Since
there are three domains of GO annotation, i.e., cellular component (CC), molecular function (MF), and
biological process (BP), three gene similarity matrices were generated for this study.

Generation of Benchmark Datasets

To comprehensively test CMMC on environmental chemical-gene interaction datasets, we generated three
different sizes of input matrices with corresponding coupled matrices. The three different sizes are 200
chemicals by 400 genes (200×400), 400 chemicals by 600 genes (400×600), and 600 chemicals by 800
genes (600×800). To make our nonbinary interaction datasets comparable to previously published
methods used for binary interaction predictions, we manually created two gold standard datasets to use as
true positive and true negative sets for performance testing. As described above, for each chemical-gene
pair, two different interaction values, N1 and N2, were calculated. For the true positive dataset, only the
most confident chemical-gene pairs, i.e., those that have more than 20 interaction records (not unique
PubMed IDs) were selected, which resulted in 462 chemical-gene pairs in the true positive dataset. To
generate the true negative dataset, chemicals were sorted by the number genes they interact with to select
for the most well-studied chemicals. Then, the top 20 chemicals with the greatest number of interacting
genes were selected as chemicals for the negative dataset. In this manner, we generated a chemical-gene
pair list with the 20 chemicals and the genes having no interaction evidence with these 20 chemicals as a
true negative dataset.

To perform robust performance testing, for all three different sizes of input matrices, 10 different sets of
randomly selected chemical-gene pairs from the positive and negative datasets were used to generate 10
different input interaction matrices separately for a 10-fold cross validation. The number of chemical-
gene pairs for each fold took up 0.25% of the total size of the input interaction matrix. For instance, 0.25%
of a 200×400 interaction matrix equals 200. Thus, 100 chemical-gene pairs were randomly selected from
both the positive and negative data sets separately to form a total 200 chemical-gene pairs for one-fold.
Since there are only 462 chemical-gene pairs in the positive dataset, all of these interactions were used in
each of the ten folds of the 600×800 datasets. However, the 600 chemical-gene pairs in the true negative
set were different in each fold for testing. Both types of normalized interaction values (i.e., N1 and N2)
were used to generate the benchmark datasets, separately.

Other State-of-the-Art Methods

Similar matrix completion methods are broadly used in the related problem of DTI predictions. Thus, we
compared our method to other widely used matrix completion methods to test the performance with
respect to the area under the ROC curve (AUC). These methods are CMF[36] (Collaborative Matrix
Factorization), GRMF[37] (Graph-Regularized Matrix Factorization), and WGRMF[37,38] (Weighted Graph-
Regularized Matrix Factorization). These methods were selected for performance comparison because
they also require supporting information to impute missing values in the interaction matrix. WKNKN[37]
(Weighted K Nearest Knows Neighbors) is a preprocessing method that can be used to estimate the
interaction likelihoods for missing values in an interaction matrix. With and without WKNKN, our
method was compared to other six methods, i.e., CMF, CMF+WKNKN, GRMF, GRMF+WKNKN,
WGRMF, and WGRMF+WKNKN. The same testing datasets were used for performance comparison
testing. Since the aforementioned three methods were developed for imputing missing values in a binary
interaction matrix, our nonbinary interaction matrices were converted to binary matrices for these
methods by applying three cutoff values separately, i.e., 0.05, 0.1, and 0.2. Any interaction values larger
than the cutoff were replaced by 1 while those smaller than the cutoff were replaced by 0. Then, the area
under the ROC curve (AUC) values were calculated for performance comparison.

Generation of Case-study Datasets

The ultimate goal of this study is to predict potential gene targets of novel chemicals without any prior
knowledge of biological effects. Thus, to test our method on a real-life scenario, we generated a series of
datasets for BPA, and three of its structurally related replacements: BPB, BPF, and BPS. To perform a
comprehensive case study, we generated 200 different datasets, each with 299 randomly selected
chemicals (300 chemicals in total when including the case chemical) and 500 genes from a total 5000
chemicals and 10,000 genes for each case-study chemical, respectively. Since there are 4,864 chemicals
after filtering drugs from the CTD dataset, chemicals from US EPA's Toxic Substances Control Act
Chemical Substance Inventory (TSCA Inventory) were used to form a chemical list with 5000 chemicals
for this case study. To mimic a real-life scenario with missing information, rather than only use a small
handful of genes, we used a substantial portion of all genes (10,000) randomly selected from the total
22,606 genes without specifically including all interactive genes of these four chemicals. The complete
gene list and chemical list can be found in Supplementary Table 2. In this way, interactions between each
case-study chemical and 10,000 genes were imputed 10 times, and the resulting prediction averaged. In
all 200 chemical-gene interaction matrices for each case-study chemical, all known interaction values
were removed to mimic a real-life scenario. Bioactivity data of BPA, BPB, BPF, and BPS were
downloaded from the CompTox Chemical Dashboard for validating our prediction results. The DAVID[39]
(Database for Annotation, Visualization and Integrated Discovery) web service was used to identify
related GO terms using the genes predicted from CMMC and genes from CTD of the four chemicals in
case study, respectively. GO term sets containing more than 500 genes were filtered out for further
analysis. An FDR less than 0.05 was used for selecting significant GO terms. The R Bioconductor
package org.Hs.eg.db[40] (v3.14.0) was used for corresponding GO annotations.

Results

Overview of the CMMC Method

Matrix completion is an ideal approach for our goal due to the great deal of information already
accumulated and available in databases about the genes affected by chemical exposures. CMMC, in
particular, is attractive because it not only takes advantage of the known chemical-gene interactions, but
also the hidden feature relationships among chemicals and among genes. CMMC was originally
developed for predicting DTI with a binary input. As opposed to other coupled matrix completion
methods, which use a fixed distance metric, such as Euclidean, CMMC uses DML in order to learn the
metric from data itself. The metric is in fact *Mahalanobis* distance for a normalized set of data with mean
zero[20]. Thus, while other algorithms make use of coupled matrices, main advantage of CMMC is the
theoretical guarantee a unique minimum using the reductive group properties. Learning matrices S_{nn} an
S_{mm}, as given in Eq (2) helps update the coupled matrices with each iteration rather than them being static.
In this study, we re-implemented and applied the CMMC algorithm to predict exposome target
interactions with continuous input. The inputs of this method are three matrices: matrix M_{EG} represents
the chemical-gene interactions, and the two symmetric matrices M_{EE} and M_{GG} represent the chemical
similarities and gene similarities, respectively (Figure 1). Given the objective function in Eq. (2), M_{EG}
corresponds to the matrix, **Y,** which itself is formed by known values only of initial matrix of gene-
chemical interaction. Square symmetric matrices M_{EE} and M_{GG} correspond to $\mathbf{M}_{nn}$ and $\mathbf{M}_{mm}$, respectively.
The goal is to learn matrices $\mathbf{S}_{nn}$ and $\mathbf{S}_{mm}$, using DML, through which the missing values of M_{EG} are
predicted. It should be noted that M_{EG} is a sparse, partially observed matrix. In M_{EG}, each row represents
an environmental chemical while each column represents a gene. The *a priori* interaction values were
calculated based on data from the CTD (see *methods* section). M_{EE} and M_{GG} can be thought of as
regularization matrices, and two regularization hyperparameters (λ_X and λ_Y as λ_n and λ_m in Eq (2)) are

applied to scale and add weights to the diagonal for preprocessing M_{EE} and M_{GG}, respectively. The
preprocessed coupled matrices are M'_{EE} and M'_{GG} (Figure 1). Observed items (i.e., known chemical-gene
interactions) in M_{EG} are used as constraints when minimizing the objective function. Two output matrices
(B_1 and B_2) are initialized as identity matrices that are the same size as the two coupled input matrices.
The preprocessed coupled matrices are directly used in the main loop to find an optimal solution. The
comprehensive mathematical description of CMMC can be found in Bagherian M, et al[20].

Datasets Used in This Study

As described above, the data used in this study is from the Comparative Toxicogenomics Database (CTD),
a comprehensive, well-maintained publicly available database containing a vast amount of information
pertaining to how environmental exposures affects human health, including chemical-gene/protein
interactions. Human-related chemical-gene interaction pairs were normalized and adjusted in two ways,
first based on the number of occurrences of each chemical-target pair (N1) and the second method is
based on the number of unique PubMed IDs listed for each chemical-target pair (N2) (Supplementary
Table 1). Two different measurements of chemical similarities and three measurements of gene
similarities were calculated and used in this study. For gene similarities, values were calculated from
Gene Ontology (GO) cellular components (CC) and molecular functions (MF), which have similar
distributions, and from biological processes (BP), whose distribution differed significantly from that of
the other two similarity measures. Many gene pairs were assigned a similarity value of 1 based on GOCC
and GOMF, while GOBP gene similarities were skewed towards to zero with a peak around 0.2
(Supplementary Figure 2A-C and Supplementary Table 3). Chemical similarity values calculated based
on Morgan fingerprints are highly skewed towards zero and there is a clear peak around 0.1, while
chemical similarity values calculated using Topological Torsion fingerprints were also skewed towards
zero, but with a data peak around 0.02 with a small kurtosis (Supplementary Figure 2D, E and
Supplementary Table 3).

To test our method and compare its performance with other state-of-the-art methods used for DTI
prediction, we generated three different sizes of input datasets, 200×400, 400×600, and 600×800, and
visualized the distribution of gene-gene and chemical-chemical similarities (Figure 2 shows the 200×400
distribution, the others are shown in Supplementary Figure 3). The interaction values from the normalized
and adjusted values based on the number of occurrences of each exposure-target pair (N1) are illustrated
in Figure 2D. The distributions of the other datasets are similar. Chemicals and genes were randomly
selected to generate these three different datasets (see *Methods*). The sparsity of the interaction matrix
(M_{EG}) is very high, i.e., 93.44% for the 200×400 dataset, 97.11% for the 400×600 dataset, and 98.23% for
the 600×800 dataset (Figure 2D and Supplementary Figure 3). All coupled matrices were also sparse
matrices (all over 50% sparsity).

Implementation of CMMC to Chemical Exposure-Gene Target Prediction

To optimize the two regularization hyperparameters for CMMC on chemical exposure-target prediction,
the benchmark datasets were used for hyperparameter tuning (see *Methods and Materials*). The previous
application[20] of CMMC for DTI prediction (with binary interaction matrix) suggested smaller parameters
perform better. A small test on the 200×400 dataset found that the performance of CMMC was not greatly
impacted by different iteration numbers (i.e., 1, 2, and 3) with hyperparameters larger than 1 (data not
shown). Thus, a grid search with five values (i.e., 0.05, 0.1, 0.3, 0.5, and 0.9) was used to find an optimal
hyperparameter pair for the following analysis in this study. To reduce the run time of CMMC on
parameter selection, the iteration number was set to 1 for all calculations in this section. Because we
generated two different types of chemical similarities, three types of gene similarities, and two different

types of chemical-gene interaction values for this study, there were a total of 12 different scenarios for
which we tuned the hyperparameters. In addition, for each of the three sizes of input matrix and
corresponding coupled matrices, 10 different testing datasets were generated for a 10-fold cross validation
(see *Methods*). Thus, for each size of input dataset with one pair of hyperparameters, AUCs were
calculated and averaged from 120 runs ($2\times3\times2\times10$). The average AUC values increased with large
parameters in all three sizes of input data (Supplementary Figure 4). Based on these results, 0.9 was
selected for both hyperparameters and used in the following analyses.

After selecting the optimal hyperparameters, we sought to obtain an optimal iteration number for CMMC
on exposome target predictions. When applying this algorithm to a binary DTI matrix, this algorithm
converged in less than 5 iterations. In this study, the benchmark dataset was used to search for an optimal
iteration number from 1 to 6. The average AUC values were calculated using the same procedure
described in the previous section. Here, the hyperparameters were set to 0.9. We found that different
iteration numbers had minimal impact on the average AUCs (Supplementary Figure 5). Thus, to
guarantee a fast calculation, 2 iterations were used in the following analyses.

Performance Comparison

CMMC was compared with CMF[36], GRMF[37], and WGRMF[37,38] with and without WKNKN[37] using the
same benchmark datasets for performance testing (see *Other State-of-the-Art Methods*). The two
hyperparameters were set to 0.9 and the iteration number was set to 2 in CMMC for this performance
comparison. For all other methods, parameters were selected as follows: $k = 100$, $\lambda_l = 2$, $\lambda_d = 0.125$, $\lambda_t =$
0.125, and $K = 5$ if WKNKN is used, where k is the number of latent features, λ_l, λ_d, and λ_t are
regularization parameters, and K is the number of nearest neighbors. These parameters were optimized
through a test run on our benchmark datasets (200×400) using the built-in function of the GRMF package.

The average AUCs calculated based on the N1 interaction values shows CMMC achieved the highest
AUCs for all three sizes of input datasets with a maximum average AUC of 0.893 ± 0.012 using the
400×600 dataset (Figure 3A). However, the AUC values for the different sized matrices were not
significantly different. In the following results, 0.1 was used as the cutoff for converting the interaction
matrix into a binary matrix. The average AUCs across different combinations of coupled matrices with
the 10 different testing datasets for all three sizes of input matrix improved from CMF to GRMF to
WGRMF. WKNKN further improved the AUC values for these three methods (Figure 3A and 3B).
Results with other binary conversion cutoffs confirmed that CMMC maintained its superior performance
in all cases tested (Table 1). It also shows that a small binary conversion cutoff has better performances
for CMF, GRMF, and WGRMF. Surprisingly, all other methods besides CMMC showed a consistent
decrease in performance moving from smaller to larger input matrices, whereas CMMC demonstrated the
most consistent performance. It is possible this result could be explained by the higher sparsity level in
the larger matrices. Comparing the results between N1 and N2 for CMMC, N1 resulted in better
performance across all three different sizes of input data, with average AUCs near 0.89 compared to 0.84
for N2. Based on these results, the following case studies were performed using CMMC with N1.

Case study

We selected the very well-studied endocrine disrupting chemical BPA and its closely related but lesser
studied analogs BPB, BPF, and BPS, for our case study. These were chosen due to the fact that BPB, BPF,
and BPS are often used as alternatives for BPA in manufacturing now that BPA has been banned in many
products and in some countries[41]. However, given the similarity in BPA's chemical structure compared to
the analogs and based on preliminary toxicology and epidemiology studies in the analogs, negative health
effects could also be caused by exposure to the alternatives. For each of the four chemicals, we generated

200 different datasets containing randomly selected 299 chemicals and 500 genes from the total 5000
chemicals and 10,000 genes used for this study, respectively. All previously known interactions of the
case study chemical in the 200 different datasets were removed from the main matrix (M_{EG}) to mimic a
realistic scenario where one does not have any prior bioactivity knowledge of a new chemical. After
imputing all 200 datasets for a chemical, the average imputed interaction values across all six runs (two
chemical-chemical similarities by three gene-gene similarities) and 200 datasets were calculated and used
for further analysis. Bioactivity data for BPA, BPB, BPF, and BPS from CompTox Chemical Dashboard
and the corresponding GO terms from CTD were used to validate the predicted genes for each chemical
(Supplementary Table 4 and 5). Genes not included in this study were removed from further analysis. A
large, imputed interaction value in our results indicates a strong, high-confident interaction. Thus, for
each chemical, genes were ordered by the imputed interaction values in descending order. Genes with
active bioactivity responses ("active genes") of the four chemicals from the CompTox Chemical
Dashboard were compared to our results (Figure 4). For BPA, 20 active genes from CompTox were
predicted in the top 100 interactive genes in our results. While for BPB, BPF, and BPS, there are 23, 10,
and 7 active genes predicted in the top 100 interactive genes, respectively (Figure 4A). Among these
genes, four genes were identified as common target genes across these four chemicals, i.e., *ESR1*, *ESR2*,
AR, and *NR1I2*. Furthermore, around 50% of the active genes of BPA and BPB and 80% active genes of
BPF and BPS are predicted in the top 1,000 genes, respectively (Supplementary Table 4). In the
CompTox Chemical Dashboard, seven genes were identified as active genes for all four of these
chemicals (*ESR1*, *ESR2*, *AR*, *NR1I2*, *PGR*, *PPARG*, and *PPARD*). Among these genes, all six of them
used in our study, i.e., *ESR1*, *ESR2*, *AR*, *NR1I2*, *PGR*, *PPARG*, were predicted to be in the top 1,000
interacting genes for all four chemicals in our results (Figure 4B). Since the 10,000 gene list was
randomly selected, PPARD was not included in the total gene list.

To further investigate our results, the top 1,000 interacting genes of each tested chemical were used to
identify the related GO terms through gene set enrichment testing. After removing GO terms containing
more than 500 genes and filtering out GO terms with an FDR larger than 0.05, we found 401, 394, 343,
and 396 significant GO terms for BPA, BPB, BPF, and BPS, respectively (Supplementary Table 5).
Strikingly, *Response to Estradiol* (GO:0032355), *Positive regulation of ERK1 and ERK2 cascade*
(GO:0070374), and *Cellular response to tumor necrosis factor* (GO:0071356) were ranked in the top 5
significant GO terms for all four chemicals. Since BPA is an endocrine-disrupting chemical[42], hormone
related GO terms were extracted from the significant GO term lists (Figure 5A). Most hormone-related
GO terms were significantly enriched for all four chemicals, including *Response to Estradiol* (GO:
0032355), *Response to Estrogen* (GO: 0043627), *Estrogen Metabolic Process* (GO: 0008210), and
Estrogen Receptor Binding (GO:0030331). However, *Insulin receptor signaling pathway* (GO:0008286)
and *Estrogen 16-Alpha-Hydroxylase Activity* (GO:0101020) were only significantly enriched for BPB
while *Insulin-like growth factor I binding* (GO:0031994) and *Positive Regulation Of Insulin−Like*
Growth Factor Receptor Signaling Pathway (GO:0043568) were only significantly enriched for BPA.

For comparison, genes known to interact with these four chemicals were downloaded from CTD and gene
set enrichment testing was used to find the significant hormone-related GO terms. Because there are more
than 5,000 interacting genes in CTD for BPA and BPS, only the top 1,000 interacting genes were used.
For BPB and BPF, all genes in CTD (115 genes for BPB and 144 genes for BPF) were used for gene set
enrichment testing. For BPA, 54 hormone related GO terms were significantly enriched from the CTD
genes while 23 hormone related GO terms were significantly enriched from genes predicted by CMMC
(Supplementary Figure 6). 87% (20/23) of these hormone related GO terms from CMMC results were
also enriched in GO terms from CTD genes. This number is 39% (9/23), 65% (13/20), and 59% (13/22)
for BPB, BPF, and BPS, respectively (Figure 5B and Supplementary Figure 7-9). Among the significantly

enriched GO terms using genes from CTD and CMMC, six of them were enriched for all four chemicals
(Figure 5B).

We visualized the distribution of gene similarities with each of the four chemicals, both for the top 1,000
genes and non-top 1,000 genes of CompTox interacting genes (Supplementary Figure 10). For BPA and
BPB, the gene similarities show clear differences in GOCC. For BPF, all three types of gene similarities
are different between the top 1,000 genes and non-top 1,000 genes. Because there were only two non-top
1,000 genes for BPS, the non-top 1,000 gene is not shown. This is consistent with our expectation that the
supporting information can be utilized by our method to predict potential target genes of a novel chemical.

Runtime aof CMMC

Since our implementation of CMMC is in C++ and the other methods are implemented in MATLAB, we
felt it would be unfair to compare the run times. However, the elapsed real time of CMMC (excluding any
data preparation steps) on the benchmark datasets were very reasonable (Supplementary Figure 11). The
average run time for a 200×400 interaction matrix is 3.4 ± 1.7 seconds, for a 400×600 input matrix it is
5.8 ± 3.0 seconds, and for a 600×800 input matrix it is 10.1 ± 5.4 seconds. We executed CMMC on a Red
Hat Enterprise Linux Server (release 7.9) with an Intel(R) Xeon(R) Gold 6150 CPU (2.70GHz). No
parallel programming was used in the implementation.

Discussion

Data fusion by representing data from multiple sources as a collection of matrices is indeed an effective
way to jointly analyze the data together with data in the context or additional constraints. Matrix
completion, as an approach in data fusion, is a prediction method designed for finding missing values
from a partially observed matrix, where the input is usually a highly sparse matrix. In general, missing
values are imputed by using the low-rank matrix of the known values. However, it is extremely difficult
to predict the missing values of a new row or column item when there is no relevant prior knowledge.
Therefore, matrix completion methods that incorporate supporting information in the form of coupled
matrices represent a significant step forward, and have gained traction by showing improved performance
in recent years[43,44].

In this study, we created and tested a new implementation of the recently developed CMMC for
predicting environmental chemical-gene interactions. The inputs of this algorithm are three matrices, i.e.,
the main matrix represents the interactions between chemicals and genes, and two coupled symmetric
matrices represent the similarities among chemicals and genes, respectively. CMMC was previously
applied to predict DTI with a binary interaction matrix, but it was not designed to be limited to binary
matrices. In this study, we applied CMMC with a nonbinary interaction a matrix. The environmental
chemical-gene pairs used in this study were downloaded from the CTD, and two approaches were used to
calculate *a priori* interaction values. Our results show that the total number of interaction values achieved
better performance than the number of unique publications reporting an interaction. However, in future
studies additional normalization approaches should be tested due to the sensitivity of the performance to
the specific pre-processing and normalization used.

We compared the performance of our CMMC implementation for predicting environmental chemical-
gene interactions, with three related, published methods (i.e., CMF, GRMF, and WGRMF). Additionally,
WKNKN, a preprocessing method for estimating the interaction likelihoods of unknown interactions
based on known neighbors, was utilized for the three aforementioned methods in the performance
comparison. We chose these three methods because they also permit the use of two coupled supporting
matrices as input for prediction. These three methods were originally developed for predicting DTI with a

binary interaction matrix, so we used three different cutoffs (i.e., 0.05, 0.1, and 0.2) to convert the
interaction values into binary values for input for other methods. Our original plan was to use three
additional cutoffs: 0.3, 0.4, and 0.5. However, because the interaction data is highly skewed towards the
left, using 0.3, 0.4, or 0.5 as the binary conversion cutoff, resulted in too few "known neighbors" for
WKNKN to estimate the likelihood of unknown interactions which caused an internal error. Thus, we
only used the three cutoffs for performance comparisons. The performance of these three methods
gradually improved from CMF to WGRMF. Furthermore, WKNKN additionally improved the
performance of these three methods. This result is consistent with the previous study that CMF obtained
the worst performance[37]. Considering the fact that our nonbinary interaction values are highly skewed
towards the left, it is not surprising to see improved performance with smaller binary conversion cutoffs.

BPA and three of its structurally related replacements were selected to perform a case study, namely BPB,
BPF, and BPS. We chose BPA because it is a well-studied chemical with abundant bioactivity records for
validating our results. BPB, BPF, and BPS are chemicals with similar structures and are used as
substitutes of BPA in industrial production. These four chemicals have similar chemical structures which
are two phenol groups connected through a linking group. Considering the chemical similarities among
these four chemicals (Supplementary Figure 12), we expected similar but not identical prediction results.
More than half of the interacting genes of these four chemicals from the CompTox database are identified
in our results as top interacting genes. Since CompTox is a data source independent of CTD, our results
are independently validated. All known interaction values were removed in the case study for each
chemical in the imputation, so this result suggests that our method can be used to effectively find potential
target genes for a novel chemical. BPA belongs to the endocrine disrupting class of chemicals, and low
dose BPA can impact reproduction, the immune system, and is related to hormone-dependent cancers[42].
Previous studies have shown that some nuclear receptors are target genes of BPA, such as androgen
receptor[45] (*AR*), estrogen receptor 1 (*ESR1*), estrogen receptor 2[46] (*ESR2*), and aryl hydrocarbon receptor[47]
(*AHR*). In our results, all of the aforementioned four genes were predicted as top 100 interactive genes for
BPA. Except for *AHR*, other three genes were also predicted by CMMC as top interactive genes for BPB,
BPF, and BPS (Supplementary Table 4). This indicates that the three substitutes chemicals may have
similar adverse biological effects as BPA[48]. Furthermore, estrogen and other hormone-related GO terms
identified from our gene lists of these four chemicals are very similar to each other and are consistent with
the fact that these chemicals are endocrine disruptors and are able to mimic estrogen[49]. The relationship
between BPA and type 2 diabetes has been well studied in the last decade[50,51]. A recent longitudinal study
provide new evidence that not only the BPA but also BPS are associated with type 2 diabetes[52,53]. In our
results, several insulin related GO terms are significantly enriched from our gene list of all four chemicals.
Thus, the CMMC results prioritize the biological effects of BPF and BPB on type 2 diabetes for future
examination.

The supporting information in the two coupled similarity matrices is critical for any prediction method to
find chemical-gene interactions for a novel chemical without any prior knowledge. The input information
is very flexible, thus it will be interesting to test alternative similarity metrics, such as gene-gene sequence
similarities instead of or in combination with gene-gene similarity based on GO term membership. Using
this coupled matrix information with an optimized rather than fixed similarity measure represents a
significant strength of CMMC. Furthermore, CMMC is not a black box method. By comparing the
similarities of the chemicals being predicted with other known chemicals, the similarities of the known
predicted genes for the most similar chemicals with the genes predicted for the new chemicals, and the
similarities among the top-ranked genes, we can gain direct insight into the causes for each prediction.
For example, G protein-coupled estrogen receptor 1 (*GPER1*) was only predicted in the top 100 target
genes of BPB by CMMC in our case study. This is consistent with a previous study that BPB and BPAF

(Bisphenol AF) have an approximate 9-fold higher binding affinity to *GPER1* than BPA[54]. BPAF is an
analogue of BPA in which the two methyl groups are replaced with trifluoromethyl groups. Although all
of these five chemicals are very similar, BPB and BPAF are more similar to each other in which
adding/replacing chemical groups to the linking group of BPA. This can partially explain why only BPB
among the four chemicals was predicted to target *GPER1*, that is, it learned from the similarity with
BPAF. This information is very useful for post-hoc analyses and follow-up studies and would not be so
easily determined with a deep learning approach.

This study has multiple limitations. Currently, we did not differentiate the chemical-gene interaction
categories that are provided in the CTD. Although most interactions are labeled as changes in RNA
expression changes (52.6%), there are 132 different interaction categories listed. Appropriately
incorporating chemical-gene interaction categories into the prediction could be advantageous for future
studies. Additionally, only human data were used in this study. Future research is required to apply our
method on other species or tissue-specific data for more precise predictions. Identifying the target genes
of a novel chemical is key but is just one step in understanding the potential health effects from an
environmental exposure. Knowing the target tissues, considering the dosage level, and linking the
molecular response to diseases are all downstream steps that are not considered in this paper. However,
CMMC combined with our data normalization strategy has great potential to form a prioritization pipeline
for discovering potential molecular targets of novel chemicals without any priori bioactivity knowledge.
Future studies could potentially incorporate tissue information, dose information, and/or interaction
category information as an additional dimension in the interaction matrix to form a partially observed
tensor, thus expanding the CMMC to CMTC (coupled matrix-tensor completion) for missing value
imputation.

Acknowledgments

525 We thank Dr. Kayvan Najarian and Dr. Renaid Kim for their professional help of this study, and we also
526 thank the three anonymous reviewers for reviewing this manuscript. Support for this research was
527 provided by NIH/NIEHS grants P30ES017885, R35ES031686, and R01ES028802.

Data Sharing

529 All data and code are publicly available at https://github.com/sartorlab/CMMC-on-Exposome-Prediction.

References

1. Collins FS, Morgan M, Patrinos A. The Human Genome Project: lessons from large-scale biology. *Science*. 2003;300(5617):286-290.

2. Vermeulen R, Schymanski EL, Barabási AL, Miller GW. The exposome and health: Where chemistry meets biology. *Science*. 2020;367(6476):392-396.

3. Wild CP. The exposome: from concept to utility. *International journal of epidemiology*. 2012;41(1):24-32.

4. Murray CJ, Lopez AD, Mathers CD, Stein C. The Global Burden of Disease 2000 project: aims, methods and data sources. *Geneva: World Health Organization*. 2001;36:1-57.

5. Wang Y, Xiao J, Suzek TO, Zhang J, Wang J, Bryant SH. PubChem: a public information system for analyzing bioactivities of small molecules. *Nucleic acids research*. 2009;37(suppl_2):W623-W633.

6. Kim S, Chen J, Cheng T, et al. PubChem in 2021: new data content and improved web interfaces. *Nucleic acids research*. 2021;49(D1):D1388-D1395.

7. Kavlock RJ, Bahadori T, Barton-Maclaren TS, Gwinn MR, Rasenberg M, Thomas RS. Accelerating the pace of chemical risk assessment. *Chemical research in toxicology*. 2018;31(5):287-290.

8. Van Norman GA. Limitations of animal studies for predicting toxicity in clinical trials: is it time to rethink our current approach? *JACC: Basic to Translational Science*. 2019;4(7):845-854.

9. Jain AK, Singh D, Dubey K, Maurya R, Mittal S, Pandey AK. Models and methods for in vitro toxicity. In: *In Vitro Toxicology*. Elsevier; 2018:45-65.

10. Blaauboer BJ. The contribution of in vitro toxicity data in hazard and risk assessment: current limitations and future perspectives. *Toxicology letters*. 2008;180(2):81-84.

11. Zhang Q, Li J, Middleton A, Bhattacharya S, Conolly RB. Bridging the data gap from in vitro toxicity testing to chemical safety assessment through computational modeling. *Frontiers in public health*. 2018;6:261.

12. Lipnick RL. Structure-activity relationships. In: *Fundamentals of Aquatic Toxicology*. CRC Press; 2020:609-655.

13. Tong W, Welsh WJ, Shi L, Fang H, Perkins R. Structure-activity relationship approaches and applications. *Environmental Toxicology and Chemistry: An International Journal*. 2003;22(8):1680-1695.

14. Wang NCY, Zhao QJ, Wesselkamper SC, Lambert JC, Petersen D, Hess-Wilson JK. Application of computational toxicological approaches in human health risk assessment. I. A tiered surrogate approach. *Regulatory Toxicology and Pharmacology*. 2012;63(1):10-19.

15. Patlewicz G, Ball N, Becker RA, et al. Food for thought: read-across approaches–misconceptions, promises and challenges ahead. *Alternatives to Animal Experimentation: ALTEX*. 2014;31(4):387-396.

16. Cherkasov A, Muratov EN, Fourches D, et al. QSAR modeling: where have you been? Where are
you going to? *Journal of medicinal chemistry*. 2014;57(12):4977-5010.

17. Muratov EN, Bajorath J, Sheridan RP, et al. QSAR without borders. *Chemical Society Reviews*.
2020;49(11):3525-3564.

18. Neves BJ, Braga RC, Melo-Filho CC, Moreira-Filho JT, Muratov EN, Andrade CH. QSAR-based
virtual screening: advances and applications in drug discovery. *Frontiers in pharmacology*.
2018;9:1275.

19. Bagherian M, Sabeti E, Wang K, Sartor MA, Nikolovska-Coleska Z, Najarian K. Machine learning
approaches and databases for prediction of drug–target interaction: a survey paper. *Briefings in
bioinformatics*. 2021;22(1):247-269.

20. Bagherian M, Kim RB, Jiang C, Sartor MA, Derksen H, Najarian K. Coupled matrix–matrix and
coupled tensor–matrix completion methods for predicting drug–target interactions. *Briefings in
bioinformatics*. 2021;22(2):2161-2171.

21. Žitnik M, Zupan B. Data fusion by matrix factorization. *IEEE transactions on pattern analysis and
machine intelligence*. 2014;37(1):41-53.

22. Pavlidis P, Weston J, Cai J, Noble WS. Learning gene functional classifications from multiple data
types. *Journal of computational biology*. 2002;9(2):401-411.

23. Williams AJ, Grulke CM, Edwards J, et al. The CompTox Chemistry Dashboard: a community data
resource for environmental chemistry. *Journal of cheminformatics*. 2017;9(1):1-27.

24. Suárez JL, García S, Herrera F. A tutorial on distance metric learning: Mathematical foundations,
algorithms, experimental analysis, prospects and challenges. *Neurocomputing*. 2021;425:300-322.

25. Jantzen JC. *Representations of Algebraic Groups*. Vol 107. American Mathematical Soc.; 2003.

26. Sanderson C, Curtin R. Armadillo: a template-based C++ library for linear algebra. *Journal of Open
Source Software*. 2016;1(2):26.

27. Davis AP, Grondin CJ, Johnson RJ, et al. Comparative toxicogenomics database (CTD): update 2021.
Nucleic acids research. 2021;49(D1):D1138-D1143.

28. Wang Y, Zhang S, Li F, et al. Therapeutic target database 2020: enriched resource for facilitating
research and early development of targeted therapeutics. *Nucleic acids research*.
2020;48(D1):D1031-D1041.

29. Wishart DS, Feunang YD, Guo AC, et al. DrugBank 5.0: a major update to the DrugBank database
for 2018. *Nucleic acids research*. 2018;46(D1):D1074-D1082.

30. Canese K, Weis S. PubMed: the bibliographic database. *The NCBI handbook*. 2013;2(1).

31. Pattanaik L, Coley CW. Molecular representation: going long on fingerprints. *Chem*. 2020;6(6):1204-
1207.

32. Weininger D. SMILES, a chemical language and information system. 1. Introduction to methodology
and encoding rules. *Journal of chemical information and computer sciences*. 1988;28(1):31-36.

33. Landrum G. *RDKit: A Software Suite for Cheminformatics, Computational Chemistry, and Predictive*
Modeling. Academic Press; 2013.

34. Ashburner M, Ball CA, Blake JA, et al. Gene ontology: tool for the unification of biology. *Nature*
genetics. 2000;25(1):25-29.

35. Yu G, Li F, Qin Y, Bo X, Wu Y, Wang S. GOSemSim: an R package for measuring semantic
similarity among GO terms and gene products. *Bioinformatics*. 2010;26(7):976-978.

36. Zheng X, Ding H, Mamitsuka H, Zhu S. Collaborative matrix factorization with multiple similarities
for predicting drug-target interactions. In: *Proceedings of the 19th ACM SIGKDD International*
Conference on Knowledge Discovery and Data Mining. ; 2013:1025-1033.

37. Ezzat A, Zhao P, Wu M, Li XL, Kwoh CK. Drug-target interaction prediction with graph regularized
matrix factorization. *IEEE/ACM transactions on computational biology and bioinformatics*.
2016;14(3):646-656.

38. Guan NN, Zhao Y, Wang CC, Li JQ, Chen X, Piao X. Anticancer drug response prediction in cell
lines using weighted graph regularized matrix factorization. *Molecular therapy-nucleic acids*.
2019;17:164-174.

39. Dennis G, Sherman BT, Hosack DA, et al. DAVID: database for annotation, visualization, and
integrated discovery. *Genome biology*. 2003;4(9):1-11.

40. Carlson M, Falcon S, Pages H, Li N. org. Hs. eg. db: Genome wide annotation for Human. *R package*
version. 2019;3(2):3.

41. Kadasala NR, Narayanan B, Liu Y. International trade regulations on BPA: Global health and
economic implications. *Asian Development Policy Review*. 2016;4(4):134-142.

42. Cimmino I, Fiory F, Perruolo G, et al. Potential mechanisms of bisphenol A (BPA) contributing to
human disease. *International journal of molecular sciences*. 2020;21(16):5761.

43. Chen Z, Wang S. A review on matrix completion for recommender systems. *Knowledge and*
Information Systems. Published online 2022:1-34.

44. Nguyen LT, Kim J, Shim B. Low-rank matrix completion: A contemporary survey. *IEEE Access*.
2019;7:94215-94237.

45. Teng C, Goodwin B, Shockley K, et al. Bisphenol A affects androgen receptor function via multiple
mechanisms. *Chemico-biological interactions*. 2013;203(3):556-564.

46. Fischer C, Mamillapalli R, Goetz TG, Jorgenson E, Ilagan Y, Taylor HS. Bisphenol A (BPA)
exposure in utero leads to immunoregulatory cytokine dysregulation in the mouse mammary gland: a
potential mechanism programming breast cancer risk. *Discover Oncology*. 2016;7(4):241-251.

47. Donini CF, El Helou M, Wierinckx A, et al. Long-term exposure of early-transformed human
mammary cells to low doses of benzo [a] pyrene and/or bisphenol A enhances their cancerous
phenotype via an AhR/GPR30 interplay. *Frontiers in oncology*. 2020;10:712.

48. Park C, Song H, Choi J, et al. The mixture effects of bisphenol derivatives on estrogen receptor and
androgen receptor. *Environmental Pollution*. 2020;260:114036.

49. Moon MK. Concern about the safety of bisphenol A substitutes. *Diabetes & metabolism journal*.
2019;43(1):46-48.

50. Alonso-Magdalena P, Quesada I, Nadal A. Endocrine disruptors in the etiology of type 2 diabetes
mellitus. *Nature Reviews Endocrinology*. 2011;7(6):346-353.

51. Duan Y, Yao Y, Wang B, et al. Association of urinary concentrations of bisphenols with type 2
diabetes mellitus: a case-control study. *Environmental pollution*. 2018;243:1719-1726.

52. Seltenrich N. Bisphenol Exposure and Type 2 Diabetes: New Evidence for a Potential Risk Factor.
Environmental Health Perspectives. 2020;128(7):074006.

53. Rancière F, Botton J, Slama R, et al. Exposure to bisphenol A and bisphenol S and incident type 2
diabetes: a case–cohort study in the French cohort DESIR. *Environmental health perspectives*.
2019;127(10):107013.

54. Cao LY, Ren XM, Li CH, et al. Bisphenol AF and bisphenol B exert higher estrogenic effects than
bisphenol A via G protein-coupled estrogen receptor pathway. *Environmental Science & Technology*.
2017;51(19):11423-11430.

Figure 1. Illustration of the coupled matrix-matrix completion algorithm. Three input matrices are M_{EE},
M_{GG}, and M_{EG}. M'_{EE} and M'_{GG} are the preprocessed coupled matrices with the two hyperparameters.

Figure 2. Data distributions for each input matrix for the 200×400 dataset. The sparsity of each matrix is
labeled at the right top corner of each histogram. (A-C) gene-gene similarity matrices based on Gene
Ontology, (D) the *a priori* known environmental chemical-gene interactions, and (E-F) chemical-
chemical similarity matrices based on Morgan and Topological fingerprints, respectively.

Figure 3. Performance comparison of CMMC with alternative methods. (A) Average AUCs of the
methods using the N1 interaction values (see Methods). Binary conversion cutoff is 0.1 for CMF, GRMF,
and WGRMF. (B) ROC curves of different datasets (with and without WKNKN for the alternative
methods).

Figure 4. Results validation with CompTox bioactivity data. (A) Percentage of CompTox interacting
genes detected by CMMC. (B) Venn diagram of the top 1000 genes corresponding to (A). All six of the
seven interactive genes for all four chemicals from CompTox that were used in the case study were also
detected as interactive genes in our results.

Figure 5. (A) Hormone-related significantly enriched GO terms from gene set enrichment test (Top 1000
interactive genes from the CMMC results used as input gene list). Arrows point to the GO terms that
differ by chemical. (B) Overlap between GO terms detected by genes from CMMC prediction and genes
directly from the CTD.

Table 1. Performance comparisons on benchmark datasets with different binary conversion cutoffs.

		CMMC	WKNKN(-)			WKNKN(+)			Binary Conversion Cutoff
			CMF	GRMF	WGRMF	CMF	GRMF	WGRMF	
N1	200x400	**0.885±0.020**	0.832±0.025	0.844±0.018	0.845±0.021	0.843±0.025	0.854±0.019	0.856±0.021	0.05
			0.814±0.026	0.823±0.027	0.828±0.025	0.831±0.028	0.846±0.027	0.848±0.026	0.1
			0.806±0.036	0.796±0.035	0.800±0.036	0.816±0.035	0.833±0.034	0.834±0.036	0.2
	400x600	**0.893±0.012**	0.824±0.014	0.836±0.017	0.843±0.014	0.842±0.014	0.849±0.016	0.856±0.014	0.05
			0.817±0.011	0.806±0.016	0.816±0.013	0.834±0.009	0.833±0.012	0.839±0.011	0.1
			0.803±0.014	0.766±0.020	0.778±0.015	0.818±0.013	0.812±0.016	0.818±0.015	0.2
	600x800	**0.884±0.004**	0.761±0.006	0.806±0.015	0.820±0.005	0.778±0.005	0.818±0.012	0.828±0.005	0.05
			0.718±0.006	0.781±0.023	0.803±0.007	0.781±0.005	0.803±0.013	0.814±0.006	0.1
			0.599±0.006	0.660±0.020	0.679±0.004	0.732±0.006	0.746±0.015	0.760±0.006	0.2
N2	200x400	0.842±0.028	0.815±0.036	0.824±0.031	0.827±0.031	0.824±0.034	0.842±0.031	**0.845±0.032**	0.05
			0.802±0.035	0.807±0.023	0.814±0.023	0.822±0.036	0.836±0.033	0.840±0.032	0.1
			0.785±0.040	0.775±0.026	0.779±0.024	0.799±0.039	0.816±0.032	0.818±0.032	0.2
	400x600	**0.838±0.012**	0.798±0.018	0.809±0.019	0.815±0.018	0.818±0.014	0.825±0.015	0.832±0.013	0.05
			0.792±0.016	0.781±0.016	0.793±0.010	0.815±0.014	0.818±0.013	0.826±0.009	0.1
			0.762±0.014	0.753±0.023	0.767±0.016	0.785±0.013	0.784±0.013	0.791±0.011	0.2
	600x800	**0.819±0.004**	0.738±0.006	0.777±0.012	0.787±0.004	0.768±0.006	0.791±0.012	0.801±0.004	0.05
			0.672±0.005	0.749±0.021	0.769±0.005	0.773±0.006	0.783±0.015	0.796±0.004	0.1
			0.588±0.008	0.680±0.026	0.705±0.005	0.678±0.006	0.722±0.015	0.736±0.005	0.2

Figure 1

Figure 2

Figure 3

Figure 4

A — Percentage of Genes Detected from CMMC

BPA, BPB, BPF, BPS

B

BPB, BPF, BPA, BPS

ESR1, ESR2, AR, NR1l2, PGR, PPARG, PPARD

Six of the seven interactive genes for all four chemicals from CompTox used in the case study were detected as interactive genes by CMMC.

Figure 5