1   **Input variability taps on invariant representations to enable generalization in visual perceptual**

2   **learning**

3   Giorgio L. Manenti[1,2,3], Aslan Sitary Dizaji[1], Caspar M. Schwiedrzik[1,2*†]

[1]Neural Circuits and Cognition Lab, European Neuroscience Institute Göttingen – A Joint Initiative of the University Medical Center Göttingen and the Max Planck Society, Grisebachstraße 5, 37077 Göttingen, Germany; [2]Perception and Plasticity Group, German Primate Center – Leibniz Institute for Primate Research, Kellnerweg 4, 37077 Göttingen, Germany; [3]Systems Neuroscience Program; Graduate School for Neurosciences, Biophysics and Molecular Biosciences (GGNB), Göttingen, Germany

*Correspondence: c.schwiedrzik@eni-g.de

Summary

Stimulus and location specificity are long considered hallmarks of visual perceptual learning. This
renders visual perceptual learning distinct from other forms of learning, where generalization can be
more easily attained, and unsuitable for practical applications, where generalization is key. Based on
hypotheses derived from the structure of the visual system, we test here whether stimulus variability
can unlock generalization in perceptual learning. We train subjects in orientation discrimination, while
we vary the amount of variability in a task-irrelevant feature, spatial frequency. We find that
independently of task difficulty, this manipulation enables generalization of learning to new stimuli
and locations, while not negatively affecting the overall amount of learning on the task. We then use
deep neural networks which recapitulate our findings in humans to investigate how variability unlocks
generalization. We find that networks develop invariance to the task-irrelevant feature when trained
with variable inputs. The degree of learned invariance strongly predicts generalization. A reliance on
invariant representations can explain variability-induced generalization in visual perceptual learning,
suggests new targets for understanding the neural basis of perceptual learning in high-order visual
cortex, and presents an easy to implement modification of common training paradigms that may
benefit practical applications.

Keywords: visual perceptual learning, orientation discrimination, generalization, deep neural
networks

Introduction

A fundamental problem for perception is to extract reliable information from a highly variable signal [1]. It is widely accepted that the visual system achieves this by learning what is consistent in its inputs, a process called *perceptual learning* (PL). However, how the enormous variability in the environment [2] impacts PL *itself* is not well understood. Here, we ask how the visual system solves the challenge of variability for learning.

Variability poses both a problem and an opportunity for PL. Varying stimuli are problematic because they entail reduced predictability [3], weaker memory traces [4], uncertain reward assignment [5], and non-linear decision rules [6]. They can thus slow down or impair learning. Consequently, state-of-the-art research and commonly employed PL protocols aim to maximize PL using highly unnatural conditions where variability is minimized, e.g., when learning one stimulus alternative at a time. However, what is often overlooked is that variability can be a great asset for learning as it facilitates *generalization* (i.e., applying learned behavior to new stimuli): variability may foster the extraction of core features across stimuli through abstraction, concept learning, and rule derivation. In many learning domains, variability acts as a catalyst for generalization [7]. In fact, theoretical studies suggest that the degree of variability during learning determines whether the system specializes on specific stimuli by memorizing them or instead learns generalizable rules [8]. Although generalization is often considered the ultimate goal of learning [9], the current mainstream view on PL disregards variability and generalization. Instead, PL is thought not to generalize [10, 11]. This renders visual PL an outlier amongst many learning phenomena.

Alternative strategies for perceptual learning with variability

Figure 1: Alternative strategies for visual perceptual learning with variability. A. Generalization strategy: if
input varies from trial to trial, learning could rely on neurons invariant to task-irrelevant features of the stimuli.
These neurons deal with variability by subsuming it in their broad tuning and can accommodate generalization
to new stimuli. However, their tuning to the task-relevant feature may not be very precise. **B**. Specialization
strategy: alternatively, the system could implement learning with neurons narrowly tuned to task-relevant and
task-irrelevant features. These neurons can provide high precision information for the task at hand. However,
more neurons need to undergo plasticity than in A if inputs vary. Moreover, a specialization strategy does not
lead to generalization, as new, untrained neurons are needed to accommodate new inputs.

Yet, the structure of the visual system suggests (at least) two ways to solve the challenge of variability
during PL: the system could *generalize* by relying on invariant representations or *specialize* on both
task-relevant and -irrelevant aspects of the stimuli, using highly precise neurons narrowly tuned to
both dimensions. If the visual system employs any of these strategies is currently unknown.

A generalization strategy based on invariant representations, e.g., in ventral temporal cortex (VTC),
deals with variability by subsuming it: invariant representations provide information about visual
stimuli in an abstract form, irrespective of task-irrelevant variability in low-level details of the input
(Fig. 1A). Thus, even if stimuli differ in appearance from trial to trial, invariant neurons still

systematically provide relevant information, and can serve as a substrate for PL despite variability.

However, these neurons are often not very precise: e.g., they signal which orientation is presented,

but cannot distinguish orientations as accurately as neurons in early visual areas [12].

Alternatively, the visual system could specialize on both task-relevant and -irrelevant aspects of the

stimuli, using highly precise neurons narrowly tuned to both dimensions (Fig. 1B). This strategy is

optimal when there is little variability because PL can be concentrated on the most informative

neurons. When facing high variability, this strategy implies that separate neurons need to be recruited

for each stimulus alternative during training. E.g., if oriented stimuli vary in spatial frequency (SF)

during orientation discrimination PL, each orientation-SF band combination needs to be learned

separately. This strategy readily assures that task performance relies on the most precise orientation

information available. Yet, by relying on narrowly tuned neurons, this strategy comes at a cost,

because these neurons cannot, by themselves, support generalization to other stimuli or locations in

the visual field.

Here, we test how the visual system deals with the challenge of variability while achieving high

performance in PL. We chose two features which are known to entail highly specific PL effects,

orientation and SF [13]. During training, we systematically vary the required precision of the

orientation discrimination task; in addition, subjects are trained with different degrees of variability

in a task-irrelevant dimension, SF. We find that task-irrelevant SF variability indeed leads to better

generalization of orientation discrimination performance to new SFs that were never shown during

training, even in difficult tasks. Furthermore, subjects trained with variable stimuli can generalize

better to new, untrained locations. Together, this suggests that they rely on SF-invariant neurons with

large receptive fields. We then perform the same experiments in a deep neural network (DNN) that

recapitulates several known PL phenomena [14]. We find a similar pattern of results, suggesting that

variability-induced catalysis of generalization holds in vivo as much as in silico. We go on to show that

SF variability during training leads to the recruitment (or emergence) of SF-invariant representations

– and not to an increase of SF-specialized units – highlighting the benefits of invariant representations

for generalization.

Results

We trained four groups of subjects (*n*=28) in an orientation discrimination task for several days, in

which they had to determine whether a grating was tilted clockwise or counterclockwise from a

reference on every trial. Two groups learned a high precision version of the task, with orientation

differences between 0.5 and 2.75 deg, while two other groups learned a low precision version of the

task, with orientation differences between 3 and 5.25 deg. One group from each precision level was trained with a single SF (1.70 cpd), referred to as 'low variability' from here on, while the other group received training with three pseudo-randomly interleaved SFs (0.53, 1.70 and 2.76 cpd), referred to as 'high variability'.

All four groups showed statistically significant increases in orientation discrimination performance as a function of training: expressed in units of "Learning Index" (LI) [15], which quantifies learning relative to the baseline performance level, the average improvement was LI=0.13 (Fig. 2A). In fact, there were no significant difference in the performance levels reached after training (precision main effect $F(1, 24)=0.32$, $p=0.574$, partial $\eta^2=0.01$; variability main effect $F(1, 24)=0.03$, $p=0.863$, partial $\eta^2=0.02$; interaction effect $F(1, 24)=0.05$, $p=0.830$, partial $\eta^2=0$). This suggests that variability did not negatively affect the amount of PL of the trained task.

New spatial frequency

New location

Figure 2: Learning and generalization in human subjects. A. Learning in orientation discrimination, quantified as Learning Index (LI), was significant in all groups (high precision groups; low variability mean LI=0.14, permutation test, p=0.008, Hedges' g=2.31; high variability mean LI=0.12, permutation test, p=0.008, Hedges' g=2.23; low precision groups; low variability mean LI=0.13, permutation test, p=0.008, Hedges' g=1.66; high variability mean LI=0.11, permutation test, p=0.008, Hedges' g=3.06). Task-irrelevant variability did not negatively affect the amount of learning (high precision groups mean difference in LI=0.017, exact permutation test, p=0.702, Hedges' g=0.22; low precision groups mean difference in LI=0.022, exact permutation test, p=0.615, Hedges' g=0.27). **B**. To test the specificity of learning, a new SF was presented to the subjects after the last training session. After high precision training, learning was specific for the group trained with low variability (mean SI=0.35, permutation test, p=0.031, Hedges' g=1.81). In contrast, subjects that were trained on the same

high precision task but with varying SFs fully generalized to the new SF (mean SI=-0.56, permutation test, *p*=0.047, Hedges' *g*=-1.38). Accordingly, there was a statistically significant difference between low and high variability training within the high precision group (mean difference in SI=0.91, exact permutation test, *p*=0.004, Hedges' *g*=2.16). Both low precision groups showed generalization (low variability mean SI=-0.06, permutation test, *p*=0.969, Hedges' *g*=-0.15; high variability mean SI=-0.35, permutation test, *p*=0.078, Hedges' *g*=-1.10), with no difference between them (mean difference in SI=0.29, permutation test, *p*=0.317, Hedges' *g*=0.58). **C**. We also tested whether subjects could perform the transfer task at a new location. Here, training variability shaped specificity and generalizability of learning similarly in the high and low precision regimes (low variability mean difference in SI=0.92, exact permutation test, *p*=0.033, Hedges' *g*=1.14; high variability mean difference in SI=0.81, permutation test, *p*<0.0001, Hedges' *g*=1.65): low variability groups both show specificity (mean SI 0.72 and 0.50, respectively; permutation test, *p*=0.016, Hedges' *g*=2.12, and *p*=0.016, Hedges' *g*=1.84). In contrast, training with high variability led to generalization (mean SI -0.20 and -0.31, respectively; permutation test, *p*=0.703, Hedges' *g*=-0.25, and *p*=0.203, Hedges' *g*=-0.69). In all panels, *** stand for *p*<0.001, ** for *p*<0.01, and * for *p*<0.05. Error bars reflect the standard error of the mean.

We then tested generalization of PL in the four groups. For analyses, we computed the "Specificity Index" (SI, [16]), which quantifies how much of the learning improvement can be carried over to previously untrained conditions. Positive SI values indicate that learning is specific, i.e., does not transfer to new conditions, whereas SI values smaller than or equal to 0 indicate generalization.

We first challenged subjects with a new, untrained SF that was chosen to fall into a previously untapped SF channel 1.4 octaves away from the closest trained SF in the high variability group. A 2 × 2 analysis of variance (ANOVA) of the four SIs revealed a statistically significant interaction between the factors precision and variability (Fig. 2B, $F(1, 24)$=4.52, *p*=0.044, partial η^2=0.11): PL in the high precision, low variability group was highly specific to the trained SF (Fig. 2B left, mean SI=0.35, permutation test, *p*=0.031, Hedges' *g*=1.81), as would be expected from a classical PL training paradigm with only a single SF. In contrast, subjects that were trained on the same high precision task but with varying SFs fully generalized to the new SF and in fact showed negative SI (mean SI=-0.56, permutation test, *p*=0.047, Hedges' *g*=-1.38), implying that they even continued to improve their performance in the transfer task. The results from high precision training thus suggest that task-irrelevant variability indeed enables generalization in PL.

In the low precision group, a different picture emerged (Fig. 2B right). Here, both low and high variability training led to good generalization with SIs not significantly different from 0 (low variability mean SI=-0.06, permutation test, *p*=0.969, Hedges' *g*=-0.15; high variability mean SI=-0.35, permutation test, *p*=0.078, Hedges' *g*=-1.10), and no statistically significant difference between both

training regimes (mean SI difference=0.29, exact permutation test, p=0.317, Hedges' g=0.58). This is

in accordance with previous PL studies showing that easy tasks generalize well [16].

The results from the SF transfer condition suggest that high variability and low precision both enable

generalization. Given that subjects trained with high precision or low variability could perform the task

in a SF band that lay outside the trained SF range is indicative of a strategy involving SF-invariant

neurons. These neurons are more prevalent in higher order visual cortex, where neurons also have

larger receptive fields [17]. We thus hypothesized that if subjects relied on invariant neurons (and not

many narrowly tuned neurons which are more prevalent in early visual areas), they should also show

transfer to new spatial locations. This is because trained and untrained locations would be covered by

the same receptive fields. We thus moved the stimuli to a new, iso-eccentric location 8 dva from the

original training location and repeated the transfer task there.

Here, we find that all groups trained with only one SF cannot transfer their learning gains to the new

location, irrespective of the required precision in the orientation discrimination task (mean SI 0.72 and

0.50, respectively; permutation test, p=0.016, Hedges' g=2.12, and p=0.016, Hedges' g=1.84). In

contrast, both groups that were trained with variable SFs were able to generalize (mean SI -0.20 and

-0.31, respectively; permutation test, p=0.703, Hedges' g=-0.25, and p=0.203, Hedges' g=-0.69). This

was also evident in terms of a main effect of variability in the ANOVA (Fig. 2C, F(1,24)=23.08, p<0.0001,

partial η^2=0.32; all other p>0.27, partial η^2<0.02). These results suggest that learning with variability

indeed taps on SF-invariant neurons with larger receptive fields than classical PL with only a single SF

band.

To gain further insight into the computations underlying generalization after high variability training,

we repeated the same experiments in a DNN purpose built for PL [14]. This network, which is derived

from the general AlexNet architecture [18], recapitulates several known PL effects, e.g., the

sharpening of tuning curves as a result of training that has originally been observed in the primary

visual cortex of non-human primates [19].

New Spatial Frequency

Figure 3: Learning and generalization in deep neural networks. A. We found significant learning effects across

all four training regimes with high learning levels (mean LI of 1, 0.85, 1 and 0.98 respectively, all *p*<0.0001,

t(24)>14.01). Input variability led to lower LIs than training without variability (high precision groups mean

difference in LI=0.152, *t*(48)=12.97, *p*<0.0001, Hedges' *g*=3.61; low precision groups mean difference in LI=0.013,

t(48)=2.44, *p*=0.006, Hedges' *g*=0.69) **B**. When the networks were fed with stimuli at a new untrained SF, we

found specificity in all four groups (mean SI 0.81, 0.42, 0.85, and 0.22, respectively, all *p*<0.0001, *t*(24)>3.96).

Importantly, the difference in learning specificity was strongly affected by training variability (high precision

groups mean difference in SI=0.39, *t*(48)=16.03, *p*<0.0001, Hedges' *g*=4.46; low precision groups mean

difference in SI=0.64, *t*(48)=55.29, *p*<0.0001, Hedges' *g*=15.39). In all panels, *** stand for *p*<0.001, ** for

p<0.01, and * for *p*<0.05. Error bars reflect the standard error of the mean.

We trained this network with our four training paradigms, crossing the factors precision and

variability, as in our human subjects. Each condition was simulated 25 times over 360 training steps.

When considering the final performance on the trained task, we again find statistically significant

learning effects in all four groups (Fig. 3A; mean LI 1, 0.85, 1, and 0.98, respectively, all *p*<0.0001, all

$t(24)>72.36$, all Hedges' $g>14.01$). As in human subjects, there is a significant interaction between

variability and precision in LIs ($F(1,96)=115.17$, $p<0.0001$, partial $\eta^2=0.54$), with a larger difference

between high and low variability training in the high precision than the low precision simulations

(mean difference in LI=0.138, $p<0.0001$, Hedges' $g=2.99$). Critically, when we challenge the network

with a new, untrained SF, we observe a differential pattern of generalization performance that

resembles what we found in human observers: networks trained with variable SFs show better

transfer to a new SF than networks trained with only a single SF at both precision levels (Fig. 3B; high

precision mean difference in SI=0.39, $t(48)=16.03$, $p<0.0001$, Hedges' $g=4.46$; low precision mean

difference in SI=0.64, $t(48)=55.29$, $p<0.0001$, Hedges' $g=15.39$); variability explained most between-

group variance (variability main effect $F(1, 96)=1457.58$, $p<0.0001$, partial $\eta^2=0.94$, compared to

precision main effect $F(1, 96)=32.18$, $p<0.0001$, partial $\eta^2=0.25$, and interaction $F(1, 96)=85.01$,

$p<0.0001$, partial $\eta^2=0.47$). Hence, while training leads to overall more specific learning effects in DNNs

than in humans, the overall pattern of results holds both in vivo and in silico.

Given the overall similarity between human and machine generalization performance, we then made

use of the opportunity to investigate how representations in the DNN changed as a function of

training. Since the amount of training involved in the network simulations cannot easily be related to

the number of trials seen by human observers, we correlated the pattern of results that we obtained

with humans to the pattern of transfer results after 2, 5, 15, 35, 45, 50, 100, and 360 training steps of

the networks. We find the highest correspondence between in vivo and in silico experiments after 100

training steps (correlation of SI between human subjects and DNNs, $r=0.81$, $p<0.0001$). We used the

simulation results from this training step for all subsequent analyses. To dissociate a generalization

strategy relying on SF-invariant orientation representations from a specialization strategy relying on

units narrowly tuned to SF and orientation, we computed the number of units tuned to the trained SF

and a SF-invariant orientation tuning index (SIOI) and for each of the 5 layers of the DNN (see

Methods).

Figure 4: Effects of learning on the number of SF-tuned units. A. The number of SF-tuned units decreases significantly across all layers and all groups (all *p*<0.003). Error bars reflect the standard error of the mean. *** stand for *p*<0.001, ** for *p*<0.01, and * for *p*<0.05. **B**. The effect size for comparing the change in the number of SF-tuned units between low and high variability groups (expressed as Hedges' *g*) varies in size and direction across layers and training regimes (0.24 and 0.32 for layer 1; 0.88 and 0.77 for layer 2; -0.94 and 0.37 for layer 3; -0.56 and -0.36 for layer 4 and 1.44 and -0.49 for layer 5). Error bars reflect the 95% confidence interval of the effect size. **C**. The change in the number of SF-tuned units is predictive of learning specificity in layer 1 (*r*=0.85,

p<0.0001, R^2=0.72), layer 4 (r=0.73, p<0.0001, R^2=0.53), and layer 5 (r=0.62, p<0.0001, R^2=0.38) in high precision training (all other layers magnitude r<0.02, p>0.210, R^2<0.03), and in all layers in low precision training (all r>0.59, p<0.0001, R^2>0.34). Dotted lines reflect 95% confidence intervals.

We find that instead of increasing, learning significantly decreases the number of SF-tuned across all layers (Fig. 4A and Table S1). Hence, a specialization strategy is unlikely to explain our results. The decrease in the number of SF-tuned neurons differentiated high from low variability training in several layers (Fig. 4B and Table S1) and was predictive of learning specificity (Fig. 4C) in layer 1 (r=0.85, p<0.0001, R^2=0.72), layer 4 (r=0.73, p<0.0001, R^2=0.53), and layer 5 (r=0.62, p<0.0001, R^2=0.38) in high precision training (all other layers magnitude r<0.02, p>0.210, R^2<0.03), and in all layers in low precision training (all r>0.59, p<0.0001, R^2>0.34). This provides a first hint at a generalization strategy. We thus turned to SIOI to further investigate the relationship between invariance and generalization. Indeed, we find that SF-invariant orientation tuning as quantified by SIOI increases as a function of training, especially in the high variability groups, with the largest effects in the top layer of the DNN (see Fig. 5A, B and Table S2). Furthermore, from layer 1 onwards, SIOI predicts generalization on the transfer task (Fig. 5C) in high precision training (layer 1 r=-0.30, p=0.035, R^2=0.09; layer 2 r=-0.88, p<0.0001, R^2=0.77; layer 3 r=-0.85, p<0.0001, R^2=0.72; layer 4 r=-0.86, p<0.0001, R^2=0.74; layer 5 r=-0.89, p<0.0001, R^2=0.78) and low precision training (layer 1 r=-0.78, p<0.0001, R^2=0.61; layer 2 r=-0.95, p<0.0001, R^2=0.90; layer 3 r=-0.98, p<0.0001, R^2=0.96; layer 4 r=-0.98, p<0.0001, R^2=0.96; layer 5 r=-0.97, p<0.0001, R^2=0.97). This suggests that variability-induced generalization in PL could indeed rely on a recruitment (or emergence) of invariant representations that provide orientation information irrespective of SF.

SF-Invariant Orientation Tuning Index

Figure 5: Effects of learning on SF-invariant orientation tuning. A. With low precision training, SIOI increases significantly (all $p<0.0001$) over training in all layers (with the exception of layer 3, where there is no change in SIOI for low variability training, $p=0.994$). This general trend is conserved for high precision, high variability training (all $p<0.0001$), while the low variability group shows significant SIOI decreases in layers 2, 3 and 4 (all $p<0.0001$). Error bars reflect the standard error of the mean. *** stand for $p<0.001$, ** for $p<0.01$, and * for $p<0.05$. **B.** The effect size for comparing the change in SIOI between low and high variability groups (expressed as Hedges' g) differentiates high from low variability training in all layers for high and low precision and increases across layers (-0.48 and -2.60 for layer 1; -8.33 and -6.00 for layer 2; -6.34 and -10.91 for layer 3; -6.83 and -9.70 for layer 4 and -6.37 and -10.68 for layer 5). Error bars reflect the 95% confidence interval of the effect size. **C.**

A strong negative correlation between SIOI and SI is found from layer 1 onwards (all *p*<0.035) and increases over

layers. Dotted lines reflect 95% confidence intervals.

Discussion

We find that variability enables generalization in PL, beyond the generalization benefits that have been

reported in low precision tasks. Variability-induced generalization outside the trained SF band and far

from the trained location overcomes two of the hallmarks of PL, namely stimulus and location

specificity. Our results in human subjects align with the known tuning properties of SF-invariant

neurons in the primate visual system. A role of these neurons in generalization is further suggested by

our in silico results, which show that networks trained with variable stimuli evolve SF-invariant

representations of orientation with training.

Traditionally, PL protocols have not involved variability, training with a minimal number of stimuli

instead. This has led to many important insights, but mostly on extremely specific PL effects. E.g.,

simply showing stimuli to a different eye after monocular training can completely abolish learning

effects [20]. By eliminating variability and presenting the same stimuli over and over, traditional PL

paradigms may have unwittingly promoted 'memorization' or 'overfitting' of specific stimuli instead

of generalization [11]. Variability during training endows the visual system with more robustness

towards changes in the stimulus material. This also makes PL less "strange": the high specificity of PL

has not been observed in other domains of training – instead, variability has been shown to benefit

transfer in domains as disparate as baseball and soccer practice [21, 22], language learning [23], and

mathematics and problem solving [24]. Hence, variability as a catalyst or enabler of generalization can

be considered a principle of leaning across domains.

Our data suggest that instead of memorizing a small number of specific stimuli, the visual system uses

invariant representations that provide orientation information irrespective of SF. Invariance is thought

to arise from systematic pooling over feature-specific representations. When there is variability in the

inputs, this entails more frequent weight updates for invariant than for feature-specific

representations, because only the former participate in the task on every trial. Furthermore, relying

on invariant representations suggests that fewer neurons need to undergo plasticity than in a

specialization strategy, hence reducing overall metabolic cost. Invariant representations for

orientation exist, e.g., in VTC, where neurons represent the orientation of simple stimuli like gratings

independently of other stimulus properties such as color or spatial frequency [25, 26]. Although not

as frequently studied as orientation representations, e.g., in the primary visual cortex, these higher

order visual neurons have been shown to be causally relevant for orientation discrimination [27]. It

has also been shown electrophysiologically that orientation tuning of neurons in higher order visual cortex is less accurate than in early visual areas [12]. This is one of the bases of the Reverse Hierarchy Theory (RHT) [16] that has previously put forward that easier tasks are learned on the basis of neurons in higher order visual cortex, whereas difficult tasks require high precision information available in early visual areas. Our results are in line with RHT, as subjects trained in the low precision task showed generalization to new SFs even if originally trained only with a single SF. However, variability during training led to overall lower SIs and extended generalization to new locations, even when the task was difficult. Hence, variability needs to be considered as an additional relevant dimension beyond task difficulty in enabling generalization of PL.

Our results highlight (at least) three objectives for future studies: First, they suggest new targets for electrophysiological recordings investigating PL in non-human primates, namely higher order visual areas in VTC. Neurons in these areas code for orientation, are invariant to low-level features, and have large spatial receptive fields, and could thus support the generalization of PL we observed. Yet, studies investigating PL in these areas are, by and large, inexistent. Second, our results suggest that stimulus variability-induced generalization is a robust principle of learning across many learning domains, including vision, that may be strategically used in machine learning to achieve out of sample generalization. Replacing ad hoc data augmentation strategies by biologically inspired principles may lead to more robust models that may also align better with human perception. Finally, in terms of application of VPL [28], where generalization is key, it may prove beneficial to counteract overtraining by varying stimuli in task-irrelevant dimensions.

Acknowledgements

This project has received funding from the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (Grant agreement No. 802482, to CMS). CMS is supported by the German Research Foundation Emmy Noether Program (SCHW1683/2-1).

CRediT author statement

G.M., Methodology, Investigation, Formal Analysis, Visualization, Data curation, Writing – original draft preparation; A.S.D., Software; C.M.S., Conceptualization, Methodology, Writing – original draft preparation, Supervision, Project administration, Funding acquisition.

Declaration of interests

The funders had no role in study design, data collection and interpretation, decision to publish, or
preparation of the manuscript. The authors declare no competing financial interests.

Methods

Participants

A total of 37 healthy human volunteers (20 female, 6 left-handed, mean age 28 yrs, SD 7.2 yrs)
participated in this study. All subjects had normal or corrected-to-normal vision, no neurological or
psychiatric disease, and gave written informed consent before participation in accordance with the
Declaration of Helsinki. Sample size was selected based on previous studies. Subjects were randomly
assigned to one of four training groups (crossing the factors precision (high/low) and variability
(high/low), see below). All procedures were approved by the Ethics Committee of the University
Medical Center Göttingen (protocol number 29/8/17).

Stimuli and procedure

<u>General setup</u>

All subjects were trained on a two alternative forced choice (2AFC) orientation discrimination task
with oriented gratings. Training lasted 2 to 5 days with one training session per day. Transfer tasks
were conducted one and two days later, respectively. Total training and transfer time was thus 4 to 7
days. Stimuli were presented on an LCD monitor (ViewPixx EEG, refresh rate 120 Hz, resolution 1920
× 1080 pixel, viewing distance 65 cm) in a darkened, sound-attenuating booth (Desone Modular
Acoustics). Subjects viewed the screen through an elliptical aperture that covered the screen edges.
Stimulus delivery and response collection were controlled using Psychtoolbox [29] running in Matlab
(The Mathworks, Inc.). Auditory feedback was delivered via headphones (Sennheiser HDA 280). During
all experiments, we continuously acquired pupil and gaze measurements using a high-speed, video-
based eye tracker (SR Research Eyelink 1000+). Data were sampled at 1000 Hz from both eyes.
Subjects were paid €8 per hour. To assure constant motivation over the training sessions, subjects
received a bonus of €2 if they improved by 10% from the previous training session.

<u>Stimuli and task</u>

On each trial, subjects had to decide whether a monopolar, monochromatic Gabor grating (size 3.1 dva, luminance 43.4 cd/m^2) was tilted clockwise or counterclockwise with respect to a reference stimulus. The reference stimulus was a monopolar, monochromatic Gabor grating with identical size and constant spatial frequency (SF, 2.56 cpd) which was randomly tilted per subject, avoiding meridians and diagonals. The task stimuli were presented in ten linearly spaced difficulty levels clockwise and counterclockwise from the reference, respectively. Each condition was presented 20 times. In addition, we presented the reference orientation 20 times, amounting to a total of 441 trials per session evenly distributed among four blocks. In the high precision training groups, difficulty levels ranged from 0.5 to 2.75 deg, while in the low precision groups, orientation differences ranged from 3 to 5.25 deg. In the low variability groups, all stimuli were presented at a single SF (1.70 cpd). In the high variability groups, we used three SFs (0.53, 1.70 and 2.76 cpd). All SFs were spaced 1.4 octaves, ensuring that each SF would rely on a different SF channel [30, 31]. In all groups, stimuli were presented in pseudo-random order at 12.4° eccentricity against a grey background (39.5 cd/m^2). Phase varied randomly between 0° and 360° from trial to trial.

On each trial, we first presented the reference stimulus for 2000 ms. This was followed by a 1000 ms fixation period. Then, two grey saccade placeholders (luminance 23.54 cd/m^2) appeared for 1500 ms, followed by the stimulus for 250 ms. After a random delay of 500-3000 ms, the choice phase started, which was indicated by a color change of the placeholders. To respond, subjects had to direct their gaze from the fixation point (size 0.31 dva, luminance 0.28 cd/m^2) at the center of the screen to a red target (luminance 23.53 cd/m^2) if the stimulus was rotated counterclockwise or to an isoluminant green target if it was rotated clockwise. The assignment of colors to the placeholder locations was pseudo-randomized. Subjects had to reach the target at 12 dva distance within 1000 ms. Subjects were instructed to respond as accurately as possible. Feedback on accuracy was provided by playing a low pitch sound (incorrect) or a high pitch sound (correct) for 500 ms. The next trial started between 300 and 2000 ms later. If subjects did not respond in time or if they broke fixation (fixation window size 4.5 dva), the low pitch sound was played, and the trial was repeated later during the block. To keep subjects motivated, the high pitch sound increased in loudness after the first 2 and 3 sequential correct trials. Loudness was reset to the original level at the first incorrect trial.

Subjects were free to take breaks between blocks. There were additional breaks in the middle of each block to display feedback about performance. As a reminder, the reference was shown for 2000 ms at the center of the screen before and in the middle of each block (in total 8 times per session). Before each training session, subjects performed 16 warm-up trials.

Transfer conditions

Subjects had to reach at least 0.05 Learning Index (see below) improvement and show stable performance compared to the end of the preceding training session before we transitioned to the first transfer session. Subjects generally required between 2 and 5 days to reach this criterion, and there were no statistically significant differences in the amount of training days to reach criterion between the groups (main effect precision, $F(1,24)=2.25$, $p=0.147$, partial $\eta^2=0.09$; main effect variability, $F(1,24)=0.24$, $p=0.622$, partial $\eta^2=0.01$; interaction, $F(1,24)=4$, $p=0.057$, partial $\eta^2=0.14$). For the first transfer test, we asked all subjects to perform the same task as during training, but we changed the SF of the task stimuli to a new, unseen SF (0.96 cpd). This SF was chosen to lie in a previous untrained SF channel 1.4 octaves away from the closest trained SF. Pilot experiments showed that baseline performance in this SF did not differ from baseline performance in the SFs used for training (see supplemental Figure S1). Subjects performed 441 trials within a single transfer session. The SF of the reference remained identical. For the second transfer test, we changed the location of the transfer stimuli to a new, iso-eccentric position 8 deg away from the original training location. Subjects again performed 441 trials within a single session.

Deep Neural Network Simulations

The deep learning model used in this paper was adopted from [14]. The model was implemented in PyTorch (version 1.10.0) and consists of two parallel streams, each one encompassing the first five convolutional layers of AlexNet [18] plus one fully connected layer which gives out a single scalar value. One stream accepts one fixed reference stimulus and the other stream accepts one varying target stimulus. The target stimulus is then compared to the reference stimulus. After the fully connected layers, the outputs of the two parallel streams – two scaler values - are entered to a softmax layer to give out one binary value which indicates the relative orientation (clockwise or counter-clockwise) of the target stimulus relative to the reference stimulus. We used the same feature maps and kernel size as the original paper. Each stimulus had 32×32 pixel size and was centered inside a 256×256 pixel image which was cropped to 224×224 pixel shape to make it consistent with the input size of AlexNet. All stimuli had homogenous gray background. The reference stimulus had a fixed orientation of 236° and a SF of 2.56 cpd. While keeping the same orientation and spatial frequency combination as for human subjects, we simulated four different training regimes, crossing the factors variability and precision. Each regime was independently trained 25 times. We initialized the five convolutional layers with pretrained ImageNet weights of AlexNet to mimic a (pretrained) adult brain. The last fully connected layer was initialized by zero. As for human subjects, we randomized stimulus phase for training. The training samples per group were set to batch sizes of 20 and 60 stimuli, for low

variability groups and high variability groups, respectively. This ensures that each batch provides all

20 orientations and all SFs but random stimulus phases. By randomizing stimulus phase, we created

7200 and 21600 unique stimuli for the low variability groups and for high variability groups,

respectively. Training parameters were set as follow: learning rate = 0.00001, momentum = 0.9,

weight decay = 0.0001. The cross-entropy loss function was used as an objective function and

optimized via stochastic gradient descent.

Analyses

All data analyses were carried out in Matlab (The Mathworks, Inc.) and R (version 4.2.1, R Core Team,

https://www.R-project.org).

<u>Human behavior</u>

Human behavioral data were analyzed using (exact) permutation *t*-tests (two-sided for comparisons

between groups, and one-sample tests against 0) and analyses of variance (ANOVA). Before fitting

ANOVAs, data were aligned and rank-transformed [32, 33] using the ARTool package (version 0.11.1,

https://github.com/mjskay/ARTool) to satisfy distributional assumptions. For *t*-tests and ANOVAs, we

computed Hedges' *g* and partial η^2, respectively, as effect sizes. From the original sample of 37

subjects, 7 subjects had to be excluded from data analysis because lack of significant learning and 2

subjects because they did not complete the experiments (final *n*=28, 15 female, 5 left-handed, mean

age 28 yrs, SD 7.6 yrs). Accuracy was defined as the average per session. We excluded all trials with

outliers in the reaction times per subject using the estimator *Sn* [34] at a threshold of 8.5. To quantify

learning, we computed the Learning Index (LI) [15], as follows:

442
$$LI = \frac{Accuracy_{last\ trained} - Accuracy_{baseline}}{Accuracy_{baseline}}$$

443   where baseline accuracy was obtained by averaging the performance of the first session. Because LI

444   could not be lower than 0, we used one-sided (exact) permutation *t*-tests for comparisons against 0.

445   To quantify transfer, a Specificity Index (SI) [16] was calculated, as follows:

446
$$SI = \frac{Accuracy_{last\ trained} - Accuracy_{transfer}}{Accuracy_{last\ trained} - Accuracy_{baseline}}$$

447   <u>Deep Neural Networks</u>

448   For each simulation, learning and transfer performances were quantified by computing LI and SI as

449   specified above. Baseline accuracy was obtained after the first training session. To investigate how the

different training conditions affected stimulus representations in the network, the trained networks were evaluated with a set of stimuli covering all 20 orientations and all three SFs spatial frequencies. We then computed dissimilarities between the average channel activities across all pairwise stimulus combinations using abs(1-Pearson correlation) for each channel pre and post training, respectively. Channels were identified as SF-sensitive if the sum of the lower triangular matrix was bigger than zero. Furthermore, we used the average channel activity to generate a representational similarity matrix (RSM) for each of the five AlexNet layers. To quantify SF-invariant orientation tuning, we computed the SF-invariant orientation tuning index (SIOI) [35, 36] by dividing the mean correlation along the off-diagonals of this RSM by the mean correlation of all other elements (but the main diagonal). All statistical analyses were carried out using parametric *t*-tests (one-sided for LI and changes in SIOI, two sided for all others), ANOVA, and Pearson correlation.

Data and code availability

All human behavioral data are available for download on Figshare (after journal acceptance). The deep neural network is available from the original authors on Github (https://github.com/kevin-w-li/DNN_for_VPL).

References

1.	Gold, J.I., and Stocker, A.A. (2017). Visual decision-making in an uncertain and dynamic world. Annual review of vision science *3*, 227-250.

2.	Herault, J., Guyader, N., and Guerin-Dugue, A. (2009). Scene variability and perception constancy in the visual system: a model of pre-processing before data analysis and learning. In IEEE International Workshop on Machine Learning for Signal Processing. (Grenoble, FR: IEEE).

3.	Adini, Y., Wilkonsky, A., Haspel, R., Tsodyks, M., and Sagi, D. (2004). Perceptual learning in contrast discrimination: the effect of contrast uncertainty. Journal of vision *4*, 993-1005.

4.	Yu, C., Klein, S.A., and Levi, D.M. (2004). Perceptual learning in contrast discrimination and the (minimal) role of context. Journal of vision *4*, 169-182.

5.	Herzog, M.H., Aberg, K.C., Fremaux, N., Gerstner, W., and Sprekeler, H. (2012). Perceptual learning, roving and the unsupervised bias. Vision research *61*, 95-99.

6.	Zhaoping, L., Herzog, M.H., and Dayan, P. (2003). Nonlinear ideal observation and recurrent preprocessing in perceptual learning. Network *14*, 233-247.

7.   Raviv, L., Lupyan, G., and Green, S.C. (2022). How variability shapes learning and
generalization. Trends in cognitive sciences *26*, 462-483.

8.   Patarnello, S., and Carnevali, P. (1987). Learning networks of neurons with boolean logic.
Europhysics letters *4*, 503-508.

9.   Shepard, R.N. (1987). Toward a universal law of generalization for psychological science.
Science *237*, 1317-1323.

10. Fahle, M., and Poggio, T. eds. (2002). Perceptual learning (Cambridge, MA: MIT Press).

11. Sagi, D. (2011). Perceptual learning in vision research. Vision research *51*, 1552-1566.

12. Vogels, R., and Orban, G.A. (1994). Activity of inferior temporal neurons during orientation
discrimination with successively presented gratings. Journal of neurophysiology *71*, 1428-
1451.

13. Fiorentini, A., and Berardi, N. (1980). Perceptual learning specific for orientation and spatial
frequency. Nature *287*, 43-44.

14. Wenliang, L.K., and Seitz, A.R. (2018). Deep neural networks for modeling visual perceptual
learning. Journal of neuroscience *38*, 6028-6044.

15. Petrov, A.A., Van Horn, N.M., and Ratcliff, R. (2011). Dissociable perceptual-learning
mechanisms revealed by diffusion-model analysis. Psychonomic Bulletin & Review *18*, 490-
497.

16. Ahissar, M., and Hochstein, S. (1997). Task difficulty and the specificity of perceptual learning.
Nature *387*, 401-406.

17. Tanaka, K. (1996). Inferotemporal cortex and object vision. Annual review of neuroscience *19*,
109-139.

18. Krizhevsky, A., Sutskever, I., and Hinton, G.E. (2012). Imagenet classification with deep
convolutional neural networks. Advances in neural information processing systems *25*.

19. Schoups, A.A., Vogels, R., Qian, N., and Orban, G.A. (2001). Practising orientation identification
improves orientation coding in V1 neurons. Nature *412*, 549-553.

20. Karni, A., and Sagi, D. (1991). Where practice makes perfect in texture discrimination:
evidence for primary visual cortex plasticity. Proceedings of the national academy of sciences
of the united states of america *88*, 4966-4970.

21. Hall, K.G., Domingues, D.A., and Cavazos, R. (1994). Contextual interference effects with
skilled baseball players. Perceptual and motor skills *78*, 835-841.

22. Zetou, E., Papadakis, L., Vernadakis, N., Derri, V., Bebetsos, E., and Filippou, F. (2014). The
effect of variable and stable practice on performance and learning the header skill of young
athletes in soccer. Procedia social and behavioral sciences *152*, 824-829.

23.   Clopper, C.G., and Pisoni, D.B. (2004). Effects of talker variability on perceptual learning of
517   dialects. Language and speech *47*, 207-239.

518   24.   Van Merrienboer, J.J.G., and Kirschner, P.A. (2007). Ten steps to complex learning, (Mahwah,
519   NJ: Taylor & Francis).

520   25.   Desimone, R., Schein, S.J., Moran, J., and Ungerleider, L.G. (1985). Contour, color and shape
521   analysis beyond the striate cortex. Vision research *25*, 441-452.

522   26.   Sary, G., Vogels, R., and Orban, G.A. (1993). Cue-invariant shape selectivity of macaque inferior
523   temporal neurons. Science *260*, 995-997.

524   27.   Adab, H.Z., and Vogels, R. (2016). Perturbation of posterior inferior temporal cortical activity
525   impairs coarse orientation discrimination. Cerebral cortex *26*, 3814-3827.

526   28.   Deveau, J., and Seitz, A.R. (2014). Applying perceptual learning to achieve practical changes in
527   vision. Frontiers in psychology *5*, 1166.

528   29.   Brainard, D.H. (1997). The Psychophysics Toolbox. Spatial vision *10*, 433-436.

529   30.   Georgeson, M.A., and Harris, M.G. (1984). Spatial selectivity of contrast adaptation: models
530   and data. Vision research *24*, 729-741.

531   31.   Nemes, V.A., Whitaker, D., Heron, J., and McKeefry, D.J. (2011). Multiple spatial frequency
532   channels in human visual perceptual memory. Vision research *51*, 2331-2339.

533   32.   Higgins, J.J., and Tashtoush, S. (1994). An aligned rank transform test for interaction. Nonlinear
534   World *1*, 201-211.

535   33.   Wobbrock, J.O., Findlater, L., Gergle, D., and Higgins, J.J. (2011). The Aligned Rank Transform
536   for Nonparametric Factorial Analyses Using Only Anova Procedures. Proceedings of the SIGCHI
537   Conference on Human Factors in Computing Systems, 143–146.

538   34.   Rousseeuw, P.J., and Croux, C. (1993). Alternatives to the median absolute deviation. Journal
539   of the American Statistical Association *88*, 1273-1283.

540   35.   Freiwald, W.A., and Tsao, D.Y. (2010). Functional compartmentalization and viewpoint
541   generalization within the macaque face-processing system. Science *330*, 845-851.

542   36.   Farzmahdi, A., Rajaei, K., Ghodrati, M., Ebrahimpour, R., and Khaligh-Razavi, S.M. (2016). A
543   specialized face-processing model inspired by the organization of monkey face patches
544   explains several face-specific phenomena observed in humans. Scientific reports *6*, 25025.

545