Tracking subjects' strategies in behavioural choice experiments at trial resolution

Silvia Maggi[1], **Rebecca M. Hock**[1], **Martin O'Neill**[1,2], **Mark J. Buckley**[3], **Paula M. Moran**[1,4], **Tobias Bast**[1,4], **Musa Sami**[5], **Mark D Humphries**[1]

*For correspondence:
mark.humphries@nottingham.ac.uk (MDH)

[1]School of Psychology, University of Nottingham, UK.; [2]Dept of Health & Nutritional Sciences, Atlantic Technological University, Sligo, Ireland; [3]Department of Experimental Psychology, University of Oxford, Oxford, UK.; [4]Neuroscience@Nottingham, University of Nottingham, UK.; [5]Institute of Mental Health, University of Nottingham, UK

Abstract Investigating how, when, and what subjects learn during decision-making tasks requires tracking their choice strategies on a trial-by-trial basis. Here we present a simple but effective probabilistic approach to tracking choice strategies at trial resolution using Bayesian evidence accumulation. We show this approach identifies both successful learning and the exploratory strategies used in decision tasks performed by humans, non-human primates, rats, and synthetic agents. Both when subjects learn and when rules change the exploratory strategies of win-stay and lose-shift, often considered complementary, are consistently used independently. Indeed, we find the use of lose-shift is strong evidence that subjects have latently learnt the salient features of a new rewarded rule. Our approach can be extended to any discrete choice strategy, and its low computational cost is ideally suited for real-time analysis and closed-loop control.

Introduction

Experiments on decision making typically take the form of discrete trials in which a subject is required to make a choice between two or more alternatives (*Packard and McGaugh, 1996*; *Yin and Knowlton, 2004*; *Behrens et al., 2007*; *Churchland et al., 2008*; *Buckley et al., 2009*; *Hanks and Summerfield, 2017*; *Izquierdo et al., 2017*; *Juavinett et al., 2017*). The subject's goal is to learn by trial and error the target rule leading to the correct choice (*Mansouri et al., 2020*), guided by feedback alone (reward and/or error signals; *Ito et al.* (*2015*); *Amarante et al.* (*2017*)) or with additional predictive stimuli (such as texture or odour; *van Wingerden et al.* (*2010*); *Wang et al.* (*2019*); *Banerjee et al.* (*2020*)). Such experimental designs can be equally applied whether the subject is primate (*Rudebeck et al., 2008*; *Buckley et al., 2009*; *Leeson et al., 2009*; *Shiner et al., 2015*), rodent (*Raposo et al., 2012*; *Brady and Floresco, 2015*; *Tait et al., 2018*; *Campagner et al., 2019*; *Harris et al., 2021*), or insect (*Giurfa and Sandoz, 2012*).

Whatever the species, neuroscience is increasingly looking to fine-grained analyses of decision-making behaviour (*Krakauer et al., 2017*; *Pereira et al., 2020*), seeking to characterise not just the variation between subjects but also a subject's variability across trials (*Smith et al., 2004*; *Roy et al., 2021*; *Ashwood et al., 2022*). When analysing the behaviour of each subject in a choice task, we ideally want to know not only when the subject has learnt the correct rule but also what the subject tried while learning. Rules correspond to particular choice strategies, like "turn right" or

"press the cued lever"; exploratory decisions made while learning are also typically characterised as choice strategies, like "win-stay". Fully characterising the variation within and between individuals on choice tasks requires that we can ask of any trial: what choice strategy are they using now?

Classic approaches to analysing performance on decision-making tasks, like psychometric curves, are computed post-hoc and implicitly assume a fixed strategy throughout (*Kim and Shadlen, 1999*; *Carandini and Churchland, 2013*). Choice behaviour is though inherently non-stationary: learning, by definition, requires changes to behaviour, humans and other animals switch strategies as they explore tasks, and experimenters switch target rules, introducing new rules or switching previous reward contingencies (*Birrell and Brown, 2000*; *Genovesio et al., 2005*; *Rich and Shapiro, 2007*; *Leeson et al., 2009*; *Donoso et al., 2014*; *Brady and Floresco, 2015*; *Jang et al., 2015*; *Powell and Redish, 2016*; *Bartolo and Averbeck, 2020*; *Russo et al., 2021*). Some algorithms can detect changes in choice behaviour that correspond to learning (*Smith et al., 2004*; *Suzuki and Brown, 2005*), but they lack information on what strategies subjects use to learn or whether the subject's learnt strategy matches the target rule.

We introduce a simple but effective Bayesian approach to inferring the probability of different choice strategies at trial resolution. This can be used both for inferring when subjects learn, by tracking the probability of the strategy matching the target rule, and for inferring subjects' use of exploratory strategies during learning. We show that our inference algorithm successfully tracks strategies used by synthetic agents, and then show how our approach can infer both successful learning and exploratory strategies across decision-making tasks performed by rats, non-human primates, and humans. The analysis provides general insights about learning: that win-stay and lose-shift, commonly discussed as though yoked together (e.g. *Izquierdo et al., 2017*; *Miller et al., 2017*; *International Brain Laboratory et al., 2021*; *Roy et al., 2021*), are dissociable strategies; and that subjects' lose-shift choices show latent learning of new rules. Our approach is computationally efficient, could be used in real-time for triggering changes to task parameters or neural stimulation, and is easily extended to more complex decision-making tasks: to aid this we provide an open source toolbox in MATLAB (https://github.com/Humphries-Lab/Bayesian_Strategy_Analysis_MATLAB) and Python (https://github.com/Humphries-Lab/Bayesian_Strategy_Analysis_Python).

Results

Given a subject performing a decision-making task with two or more choices, and the subject's observed history of choices up to and including trial t, our goal is to compute the probability $P(\text{strategy}_i(t)|\text{choices}(1:t))$ that a particular strategy i has been used on current trial t.

With this probability, we ask two questions about choice strategies:

1. What have the subjects learnt? By defining strategy i as one of the available rules in the task, high values for $P(\text{strategy}_i(t)|\text{choices}(1:t))$ are evidence of successfully learning that rule. This approach can be equally applied to naive subjects during training or to well-trained subjects across rule switches (for example, to see which other rules they switch between).

2. What strategies are being tried in order to learn the rule? Subjects use choice strategies to explore the structure of the environment. For example, animals often show some combination of win-stay or lose-shift behaviour at the start of learning (*Jang et al., 2015*; *Akrami et al., 2018*; *Constantinople et al., 2019*). Potential exploratory strategies include random guessing, history-dependence, and information-seeking. By choosing strategy i to be one of these exploratory strategies, we can track its occurrence.

Computing strategy probabilities at trial resolution

We compute $P(\text{strategy}_i(t)|\text{choices}(1:t))$ using Bayes theorem to provide an estimate of each probability and the uncertainty of that estimate, given the available evidence up to trial t:

$$\underbrace{P(\text{strategy}_i(t)|\text{choices}(1:t))}_{\text{posterior}} \propto \underbrace{P(\text{choices}(1:t)|\text{strategy}_i(t))}_{\text{likelihood}} \times \underbrace{P(\text{strategy}_i(t))}_{\text{prior}}, \tag{1}$$

 where the posterior is the observer's estimate of the probability of strategy i being executed, which
we want to obtain; the likelihood is the consistency of the subject's choices with the strategy we
are assessing; and the prior is the initial estimate of the probability that the subject uses strategy
i. We now define each of the likelihood, prior, and posterior distributions.

On each trial there are two observable outcomes for a given strategy i: the subject's choice is
either consistent with that strategy (a success, $x = 1$) or it is not (a failure, $x = 0$). The sequence
of successes or failures to execute the strategy is then the history of choices [$\text{choices}(1 : t)$]. As
each trial in the sequence has two outcomes the likelihood $P(\text{choices}(1 : t)|\text{strategy}_i(t))$ is a binomial
distribution.

Setting the prior as the Beta distribution $B(\alpha_i, \beta_i)$, defined in the range $[0, 1]$, allows us to treat
the unknown probability of strategy i as a random variable. The Beta distribution is the so-called
conjugate prior for the binomial distribution, meaning that the posterior is also a Beta distribution,
dramatically simplifying the calculations in Equation 1.

Indeed, so simple that updating the posterior distribution $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ on trial t be-
comes, in practice, elementary arithmetic (Methods): given the parameters of the Beta distribution
$(\alpha_i(t-1), \beta_i(t-1))$ for strategy i on the previous trial, and that the choice on trial t is either consistent
$(x = 1)$ or not $(x = 0)$ with strategy i, then update $\alpha_i(t) \leftarrow \alpha_i(t-1) + x$ and $\beta_i(t) \leftarrow \beta_i(t-1) + (1-x)$. The
initial prior is defined by the values set for $\alpha(0)$ and $\beta(0)$. This, then, uses the accumulated evidence
up to trial t to provide a full trial-by-trial estimate of the posterior probability of strategy i, in the
Beta distribution $B(\alpha_i(t), \beta_i(t))$.

Using Bayes theorem in this way assumes that the parameter being estimated – here $P(\text{strategy}_i(t)|\text{choices}(1 :$
$t))$ – is stationary. But choice behaviour is often non-stationary, as when a subject switches ex-
ploratory strategies while learning, or when an experimenter changes the target rule after learning,
forcing a subject to switch away from the learnt strategy. As we show further below, naive use of
the Bayesian approach will fail to track these changes.

We solve the non-stationarity problem by weighting the evidence entered into the Bayesian
update by its recency. We keep a running total of past successes to execute strategy i up to trial t,
exponentially weighted by how far in the past each success occurred: $s_i^*(t) = \sum_{\tau=1}^{t} \gamma^{t-\tau} x(\tau)$, where
$\gamma \in (0, 1]$ is the rate of evidence decay. Similarly, we keep a running total of past failures to execute
strategy i: $f_i^*(t) = \sum_{\tau=1}^{t} \gamma^{t-\tau}(1 - x(\tau))$. We then obtain the following algorithm for trial t (Methods):

- Observe whether the choice on trial t was consistent $(x(t) = 1)$ or not $(x(t) = 0)$ with the
  execution of strategy i;
- Update the running totals of evidence, decaying the prior evidence: $s_i^*(t) = \gamma s_i^*(t - 1) + x(t)$;
  and $f_i^*(t) = \gamma f_i^*(t - 1) + (1 - x(t))$;
- Update the parameters for the posterior distribution: $\alpha_i(t) \leftarrow \alpha_i(0) + s_i^*(t)$ and $\beta_i(t) \leftarrow \beta_i(0) + f_i^*(t)$.

The posterior distribution for $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ on trial t is then the Beta distribution
$B(\alpha_i(t), \beta_i(t))$. With $\gamma = 1$ we recover standard Bayesian inference; the lower γ, the stronger re-
cent history is weighted. Throughout we use $\gamma = 0.9$ unless otherwise noted; we show below how
the choice of γ affects strategy inference.

Figure 1 demonstrates the algorithm using example data from a naive rat performing consec-
utive sessions on a Y-maze task. In every trial, the rat had to choose either the left or right arm
(*Figure 1*a), and received reward based on four rules that were applied in sequence: right arm, cued
arm, left arm, uncued arm. These rules switched after 10 consecutive correct trials or 11 correct
out of 12 trials. *Figure 1*b plots the variables needed to infer the rat's strategy: its choices, rewards,
and the cue location. We used these to compute $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ for the strategies cor-
responding to the first three rules, 'go right', 'go cued', and 'go left'. *Figure 1*c plots the resulting
posterior distributions for those three strategies across three sequential trials during the learning
of the 'go left' rule. These show how the rat consistently choosing the left arm updates (α, β) for
$P(\text{go left})$ to shift its posterior distribution rightward, while the rat choosing not to go down the
right arm when it is cued updates (α, β) for $P(\text{go cued})$ to shift its posterior distribution leftward; as

Figure 1. A Bayesian approach to tracking strategies.
(**a**) Schematic of the Y-maze task. The rat receives a reward at the arm end if it chose the correct arm according to the currently enforced rule. A light cue is randomly switched on at the end of one of the two arms on each trial. Rules were in the sequence 'go right', 'go cue', 'go left', 'go uncued', and switched after ten consecutive correct trials or 11 out of 12.

(**b**) Example rat performance on the Y-maze task. We plot performance across 14 consecutive sessions: vertical grey dashed lines indicate session separation, while coloured bars at the top give the target rule in each trial. Performance is quantified by the cumulative distributions of obtained reward (grey) and arm choice (black). We also plot the cumulative cue location (brown), to show it is randomised effectively. Choice and cue distributions increase by +1 for right and decrease by -1 for left. Small black arrow indicates the trial *t* shown in panel c.

(**c**) Example posterior distributions of three rule strategies for three sequential trials. Trial *t* is trial 250 in panel b. Vertical dashed coloured lines identify the *maximum a posteriori* (MAP) probability estimate for each strategy.

(**d**) Time-series of MAP probabilities on each trial for the three main rule strategies, for the same subject in panel b. Horizontal grey dashed line indicates chance. We omit 'go uncued' for clarity: as it is the complementary strategy of 'go cue' (P(go uncued) = 1-P(go cued)), so it is below chance for almost all trials.

(**e**) Precision (1/variance) for each trial and each of the tested strategies in panel d; note the precisions of mutually exclusive strategies (e.g. go left and go right) are identical by definition.

(**f**) Time-series of MAP probabilities for three exploratory strategies. Staying or shifting is defined with respect to the choice of arm ('Spatial') or the state of the light in the chosen arm ('Cued') – for example if the rat initially chose the unlit arm and was unrewarded, then chose the lit arm on the next trial, this would be a successful occurrence of 'Lose-Shift-Cued'.

Figure 1–Figure supplement 1. A stationary Bayesian approach fails to track behavioural changes

Figure 1–Figure supplement 2. Robustness of the Bayesian approach to changes in the initial prior

137 a consequence, 'go left' becomes the most probable strategy.

138 To track changes in $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ across all trials we take the best estimate of the
139 probability that strategy i is being executed as the *maximum a posteriori* (MAP) value of $B(\alpha(t), \beta(t))$
140 (*Figure 1*c). Plotting the MAP probabilities for each trial in *Figure 1*d shows how they capture three
141 key dynamics of choice behaviour: first, learning when the probability the subject is using the tar-
142 get rule's strategy becomes large and dominant; second, perseverance, as when learnt strategies
143 persist after the target rule has been changed – for example, 'go right' persists as the dominant
144 strategy for over a hundred trials after the reinforced rule has switched to 'go cued' around trial
145 25; and, third, switching, as when the rat switches from 'go right' to 'go cued' in the session begin-
146 ning at trial 152, emphasising that choice strategy is non-stationary. Indeed, in these example data,
147 a Bayesian approach without the decay of evidence cannot track rule learning or strategy switching
148 (*Figure 1–Figure Supplement 1*). With the decay of evidence, the estimated MAP probabilities, and
149 hence inferred changes in strategy, are robust to the choice of prior distribution (*Figure 1–Figure*
150 *Supplement 2*).

151 We can also summarise the amount of evidence we have for our MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1 :$
152 $t))$ by computing the precision – the inverse of the variance – of the full probability distribution: the
153 higher the precision, the more concentrated the Beta distribution is around the MAP estimate of
154 the probability of strategy i (*Figure 1*e).

155 The choice of scalar summaries (MAP and precision) here was made to facilitate ease of plot-
156 ting (*Figure 1* onwards), quantifying (*Figure 2* onwards), and combining across subjects (*Figure 3*
157 onwards) the changes to the posteriors $P(\text{strategy}_i(t)|\text{choices}(1 : t))$. As we show below, these scalar
158 summaries were sufficient to reveal striking behavioural changes during learning and exploration;
159 but we emphasise that the full posterior is calculated for each trial, offering rich potential for fur-
160 ther applications of this algorithm.

161 The above focused on strategies corresponding to the target rules to learn. We can equally
162 define models for strategies that are explorative, to track the strategies the subject engages while
163 learning the rule. For example, a subject's strategy of win-stay based on their previous choice
164 would be: count a success if trial $t − 1$ was correct and the subject made the same choice on trial t;
165 count a failure if trial $t − 1$ was correct and the subject made a different choice on trial t. In *Figure 1*f,
166 we plot MAP probabilities for three such explorative strategies, win-stay and lose-shift for the prior
167 choice of left or right arm, and lose-shift based on the prior cue position. This demonstrates when
168 exploratory strategies are used to guide behaviour; for example, of these strategies, lose-shift in
169 response to the choice of arm begins to dominate from around trial 50 to 150 (see *Figure 1*d).

170 Throughout we distinguish rule strategies, which correspond to one of the reinforced rules
171 available in the task, from exploratory strategies, which are all other possible choice strategies
172 given task information. The choice of strategies is down to the user (Methods).

Robust tracking of strategies in synthetic data

174 We turn now to three questions about the algorithm and its use: first, why do we need to decay evi-
175 dence? Second, how does the choice of decay rate γ affect our inferences of $P(\text{strategy}_i(t)|\text{choices}(1 :$
176 $t))$? And, third, what happens if our chosen strategies do not include a true strategy? We show that
177 decaying evidence is necessary to track strategy changes; that there is a range of γ over which per-
178 formance is robust; and that the absence of a true strategy sets upper bounds on the algorithm's
179 estimate of $P(\text{strategy}_i(t)|\text{choices}(1 : t))$.

180 First, to demonstrate the need to decay evidence, we simulated an agent doing a two-alternative
181 forced choice task. The agent was rewarded when it chose the randomly cued option (brown curve
182 in *Figure 2*a). The agent switched its strategy every 100 trials, across five strategies, with only the
183 fourth strategy corresponding to the rewarded rule (*Figure 2*a). This set of implanted strategies
184 included a range of options examined in behavioural studies, often individually, and we used many
185 consecutive trials with the same strategy to explore the full effects of the decay rate γ. We inferred
186 $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ for eight strategies in total, including the five implanted ones, using the

187 agent's choice data. *Figure 2* shows how the algorithm's MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$

188 (panel b) and its precision (panel c) tracked these strategy switches when using a decay rate of

189 $\gamma = 0.9$. *Figure 2–Figure Supplement 1* plots every strategy's MAP estimates at all tested decay

190 rates.

191   We used a simple decision rule to quantify how the decay rate γ affected the algorithm's tracking

192 of strategies (*Figure 2*d). This rule selected the most likely strategy being executed at trial t by

193 choosing strategy i with the highest MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$, resolving ties by

194 choosing the strategy with the maximum precision (*Figure 2*d).

195   *Figure 2*e plots the trials on which the algorithm was correct using this decision rule. We see

196 standard Bayesian inference ($\gamma = 1$) could not detect any switches in strategy. But with $\gamma \approx 0.9$

197 or less, the algorithm detected switches in ten trials or fewer, and tracked the correct strategy in

198 more than 88% of trials (grey shading in *Figure 2*e).

199   We then used extensive simulations to quantify how the number of trials T for which a first strat-

200 egy is used affects the algorithm's ability to track an abrupt switch to a second strategy (Methods).

201 Standard Bayesian inference scaled linearly, taking another T trials to detect the switch (*Figure 2*f,

202 $\gamma = 1$). Using evidence decay, our algorithm detects abrupt switches orders-of-magnitude faster,

203 and at a rate that rapidly plateaued with increasing T (*Figure 2*f). Decaying evidence thus ensures

204 that how long a first strategy was used little impacts the algorithm's ability to track a switch to

205 a new strategy. And while stronger evidence decay (smaller γ) increased the speed at which the

206 abrupt switch was detected, even for $\gamma = 0.9$ the worst-case performance was ten trials (*Figure 2*f).

207 Collectively, these results show how decaying evidence is necessary to detect switches in strategy,

208 and that the algorithm can rapidly track abrupt switches in strategy for a wide range of γ.

209   We could then turn to our second question: If the decay of evidence is essential, how rapid

210 should it be? Choosing $\gamma < 1$ defines asymptotic limits on the posterior distribution because it

211 limits the values that α and β can take when there is a long run of successes or failures to execute

212 a strategy (Methods, Equations (15) and (16)). These limits do not stop the algorithm correctly

213 estimating the MAP value of $P(\text{strategy}_i(t)|\text{choices}(1:t))$; for example, for a long run of successes,

214 the MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ will always be 1 (*Figure 2*g). But these limits do

215 mean that, in contrast to standard Bayesian inference, rapid decay $\gamma \ll 1$ places bounds on how

216 concentrated the posterior distribution of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ can get around its maximum

217 value (*Figure 2*g-i).

218   The main consequence of these bounds is that slower decay of evidence makes the algorithm

219 more robust to noise. We see this robustness in two crucial uses of the algorithm, tracking gradual

220 switches between two strategies and tracking the stochastic use of a strategy. In *Figure 2–Figure*

221 *Supplement 2*, we show that for gradual switches slowly decaying evidence ($\gamma \sim 0.9$) correctly iden-

222 tifies when the new strategy has become dominant, and consistently tracks its use thereafter; by

223 contrast, rapidly decaying evidence ($\gamma \ll 1$) prematurely identifies when the new strategy has be-

224 come dominant and inconsistently tracks it use thereafter. In *Figure 2–Figure Supplement 3*, we

225 show that for the stochastic use of a strategy i with some probability $p(use)$, the average MAP es-

226 timate $P(\text{strategy}_i(t)|\text{choices}(1:t))$ will converge to $p(use)$; but we also show that the more rapidly

227 evidence is decayed the greater the trial-to-trial variation in $P(\text{strategy}_i(t)|\text{choices}(1:t))$. Choosing

228 the decay rate γ is thus a trade-off between the speed (*Figure 2*f) of tracking changes in strategy

229 and the accuracy of that tracking (*Figure 2*g, *Figure 2–Figure Supplement 2*, *Figure 2–Figure Sup-*

230 *plement 3*). Our use of $\gamma = 0.9$ here is thus motivated by favouring robust yet still rapid tracking.

231   Tracking exploratory strategies presents a further challenge, our third question above: The set

232 of exploratory strategies we test may not include a true strategy used by a subject. Exploratory

233 strategies come in two forms: like rule strategies they can be unconditional, available for use at

234 every decision, such as repeating a previous choice; but unlike rule strategies they can be condi-

235 tional, only available for use when their condition or conditions or met, such as win-stay. We first

236 confirmed that our algorithm could rapidly track the use of conditional strategies (*Figure 2–Figure*

237 *Supplement 4*). We then sought to place bounds on how the inference algorithm behaves if a true

Figure 2. Robust tracking of strategies in synthetic data.
(**a**) Cumulative distribution of raw behavioural data for the synthetic agent, performing a two-alternative task of choosing the randomly-cued option. Curves are as in *Figure 1*a. Vertical dashed lines indicate strategy switches by the agent.
(**b**) MAP values of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for the five implanted strategies across trials, for $\gamma = 0.9$. Chance is 0.5.
(**c**) Precision for the five implanted strategies.
(**d**) A decision rule to quantify the effect of γ. For every tested strategy, listed on the left, we plot for each trial the strategies with the maximum MAP probability (black dots) and maximum precision (grey circles) across all strategies, and the agent's actual strategy (orange bars). Maximising both the MAP probability and precision uniquely identifies one tested strategy, which matches the agent's strategy.
(**e**) Algorithm performance across evidence decay rates. Left: successful inference (black) of the agent's strategy using the decision rule. Right: proportion of trials with the correct detected strategy; grey shading shows γ values within the top 5%. Standard Bayesian inference is $\gamma = 1$.
(**f**) Number of trials until a strategy switch is detected, as a function of the number of trials using the first strategy. One line per decay rate (γ). Detection was the first trial for which the algorithm's MAP probability estimate of the new strategy was greater than the MAP probability estimate of the first strategy.
(**g**) The decay rate (γ) sets an asymptotic limit on the posterior distribution of $P(\text{strategy}_i(t)|\text{choices}(1:t))$. We plot the posterior distribution here for an infinite run of successes in performing strategy i at a range of $\gamma \in [0.5, 0.95]$.
(**h**) The asymptotic limits on the precision of the posterior distributions set by the choice of decay rate (γ).
(**i**) The asymptotic limits on the probability that $P(\text{strategy}_i(t)|\text{choices}(1:t))$ exceeds chance (p=0.5) in a two-choice task.

Figure 2–Figure supplement 1. MAP probabilities for agent strategies across changes in decay rate

Figure 2–Figure supplement 2. Slower evidence decay tracks gradual switches in strategy more accurately and robustly.

Figure 2–Figure supplement 3. Slower evidence decay gives lower variability when tracking stochastic use of a strategy

Figure 2–Figure supplement 4. Algorithm performance for tracking a new conditional strategy

Figure 2–Figure supplement 5. Limits on the probability of the tested strategy matching a true strategy used by an agent during exploration

238 exploratory strategy is missing.

239 What then would the algorithm's MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ be for any kind of
240 strategy i that is not the true exploratory strategy? The general answer to this is the probability
241 $p(\text{match})$ that the choice made under strategy i matches the choice made under the true strategy.
242 By definition $p(\text{match}) < 1$, otherwise strategy i and the true strategy are indistinguishable to the
243 observer. What we are interested in is how close $p(\text{match})$ could grow to 1, and thus how hard it
244 would be to tell when we do not have the true strategy. Exhaustively enumerating the possible
245 values of $p(\text{match})$ for a task with n choices revealed three bounds (we derived these from the last
246 column in *Figure 2–Figure Supplement 5*; see Methods for details of enumeration). First, if the
247 algorithm estimates the MAP probability of all tested exploratory strategies to be $\leq 1 - 1/n$ then the
248 true strategy or strategies are missing. Second, a MAP probability $> 1 - 1/n$ for a tested exploratory
249 strategy is evidence for at least a partial match to the true strategy (for example, in *Figure 2*b, when
250 the true strategy adopted by the agent was "lose-shift-spatial" the tested strategy of "alternate" had
251 a MAP probability of around 0.75, because both strategies will change choice on the trial after a
252 loss, thus matching on all post-loss trials but not all post-reward trials). Indeed, our preferred way
253 of interpreting exploratory strategies is that they provide evidence about what task features, such
254 as obtaining reward (or not), and the subject's response to them, such as staying or shifting, are
255 driving exploration; the algorithm's estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ is thus a read-out of the
256 evidence. Third, we find that a MAP probability approaching 1 is strong evidence that the tested
257 strategy is, or is equivalent to, the true strategy.

258 Collectively these results show that our approach, combining Bayesian inference with a rate of
259 forgetting evidence used in that inference, can track non-stationary probabilities of strategy use at
260 trial resolution. While the forgetting rate is essential (*Figure 2*a-f), the effects it has on the behaviour
261 of the posterior distribution (*Figure 2*g-i) and on the ability to correctly track switches in strategy
262 (*Figure 2–Figure Supplement 2* and *Figure 2–Figure Supplement 3*), give us a principled range of
263 forgetting rates to consider, and over which the algorithm's performance is robust. With these
264 insights to hand, we now apply our inference algorithm to uncover the choice strategies used in
265 tasks performed by rats, humans, and monkeys.

266 ## Trial resolution inference reveals evidence of earlier learning

267 Classic approaches to detecting learning depend on arbitrary criteria based on counts of correct
268 trials (e.g. *Birrell and Brown, 2000*; *Boulougouris et al., 2007*; *Floresco et al., 2008*; *Leeson et al.,*
269 *2009*; *Peyrache et al., 2009*; *Brady and Floresco, 2015*). Such criteria are typically conservative,
270 requiring long sequences or high percentages of correct trials to give unambiguous evidence of
271 learning. We thus asked whether our trial-resolution algorithm could provide a more principled
272 approach to detecting learning.

273 To investigate this question, we used data from rats learning cross-modal rule-switch tasks.
274 We compared data from two conceptually similar tasks, the first involving the choice of one of two
275 arms in a Y-maze (*Figure 1*a, data from *Peyrache et al. 2009*) and the other the choice of one of
276 two levers in an operant box (*Figure 3*d; task design from *Brady and Floresco 2015*). In both tasks,
277 the rat had to learn at least one spatial rule based on the position of the choice option (arm or
278 lever) and at least one cue-driven rule, based on the position of a randomly-illuminated cue light.
279 As noted above, the Y-maze task contained a sequence of up to four rules, two spatial (left/right)
280 and two cue-driven. In the data available to us, three rats experienced all four rules and one rat
281 experienced the first two rules, giving a total of seven switches from spatial to cue-driven rules and
282 three switches from cue-driven to spatial rules. In the lever-press task, rats were trained on one
283 spatial and one cue-driven rule: 16 rats experienced a switch from a spatial to a cue-driven rule,
284 and 12 experienced the switch from a cue-driven to a spatial rule (Methods).

285 Classic definitions of learning the target rule were originally used for both tasks. For the Y-maze
286 study, learning was defined post-hoc by three consecutive correct trials followed by 80% correct
287 until the end of the session, with the first of the three trials then labelled as the learning trial

Figure 3. Detecting learning

(**a**) Schematic of Y-maze task, from *Figure 1*a.

(**b**) MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for the correct strategy for the spatial (left panel) and cued (right panel) rules on the Y-maze, aligned to the learning trial for each subject (trial 0, vertical dashed line). Learning trials are defined by the experimenters' original criterion (grey) or by our strategy criterion (orange). Curves represent means (bold line) $\pm$ SEM (shading) for N sessions meeting each criterion across the 4 rats (Spatial rule: original criterion $N = 5$, strategy criterion $N = 7$; Cued rules: original criterion $N = 5$, strategy criterion $N = 5$). Horizontal dashed line is chance.

(**c**) Comparison between learning trials in the Y-maze task identified using the original criterion or our strategy criterion. Left: the identified learning trials for each rule. Trial zero was the first trial with that rule enforced, and rules are labelled in the order they were presented to the rats. Right: number of identified learning trials per rat.

(**d**) Schematic of the lever-press task. Rats experienced both spatial (e.g. choose left lever) and cued (e.g. choose lit lever) rules.

(**e**) As for panel b, for the lever-press task. $N = 28$ rats.

(**f**) Comparing the learning trials identified in the lever press task by the original criterion or our strategy criterion for the first (left) and second (right) rule learnt by each rat. Solid symbols show mean and SEM; open symbols show individuals' learning trials. P-values are from a Wilcoxon signed rank test between the learning trials identified by the original and by the strategy criterion ($N = 28$ rats). For the first rule, the learning trials based on the original and strategy criterion are 88.9 ± 12.3 and 59 ± 11.3 (mean$\pm$SEM), respectively. For the second rule, the learning trials based on the original and strategy criterion are 224.3 ± 33 and 272 ± 33 (mean$\pm$SEM), respectively. Note the second rule's y-axis scale is a factor of 2 larger than for the first rule, because of the time taken to learn the cued rule second.

Figure 3–Figure supplement 1. Performance of further learning criteria.

₂₈₈ (*Peyrache et al., 2009*). For the lever-press task, learning was defined on-line as ten consecutive
₂₈₉ correct trials, after which the session ended (*Brady and Floresco, 2015*) – the first of these ten
₂₉₀ we label as the learning trial. To assess how conservative these criteria were, we computed the
₂₉₁ probability $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for the strategy i corresponding to the target rule and found
₂₉₂ it was consistently above chance before these classically-defined learning trials for both the Y-maze
₂₉₃ (*Figure 3*b, 'Criterion') and lever-press tasks (*Figure 3*e, 'Criterion'). This suggests rules were learnt
₂₉₄ notably earlier than detected.

₂₉₅ We thus tested a sequence-based criterion using $P(\text{strategy}_i(t)|\text{choices}(1:t))$ to identify the learn-
₂₉₆ ing trial: we found the first trial at which the MAP probability for the target-rule's strategy remained
₂₉₇ above chance (0.5) until the end of the session (Methods). Using this criterion, the change in prob-
₂₉₈ ability around the learning trial showed clearer steps from chance to above-chance performance
₂₉₉ in both tasks (*Figure 3*b,e, 'Strategy').

₃₀₀ In the Y-maze task, this strategy-based criterion identified that learning occurred 12 times across
₃₀₁ the four rats, compared to 10 times using the original criterion (*Figure 3*c). In particular, unlike the

original criterion, the strategy criterion suggested that all three rats which experienced the 'go left' rule learnt it, and one rat learnt the 'go uncued' rule.

For the lever-press task, we could compare the learning trials identified by both approaches because every rat was trained to the original criterion. The strategy criterion robustly identified learning earlier, on average 30 ± 5.8 trials earlier, during learning of the first target rule (*Figure 3*f, left). By contrast, both criteria identified similar learning trials during the second target rule each rat experienced (*Figure 3*f, right). They thus both agreed that learning the cued rule after a spatial rule took longer than learning a spatial rule after the cued rule (*Figure 3*f; a 2-factor ANOVA on the strategy criterion showing significant effects of rule-type [F=74.73, $p < 0.001$], rule order [F=45.36, $p < 0.001$] and their interaction [F=54.74, $p < 0.001$]).

The strategy-based criterion was analogous to classical criteria for learning as it used only a scalar estimate of performance. We thus explored two other criteria for learning (Methods) that also incorporated the uncertainty in the estimate of $P(\text{strategy}_i(t)|\text{choices}(1 : t))$. The first extended the sequence-based definition to also require that the precision of the target-rule's strategy was greater than all other tested rule strategies, indicating greater evidence for that strategy. The second defined the learning trial as the first at which the probability the posterior distribution $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ did not contain chance was above some high threshold (here 0.95) until the end of the session. We found, as expected, that learning took longer to detect with these increasingly stringent criteria for the level of uncertainty (*Figure 3–Figure Supplement 1*). Indeed, the full posterior criterion seemed to identify expert performance in both tasks (*Figure 3–Figure Supplement 1*a,c), so could itself be a useful criterion for making rule switches. Consequently, for the lever-press task, both these more stringent criteria did not identify learning markedly earlier than classic sequence criterion (*Figure 3–Figure Supplement 1*d). Nonetheless, these more stringent criterion still showed that animals were significantly slower to learn when switching from a spatial to a cued rule than vice versa (*Figure 3–Figure Supplement 1*d).

Flexibility in responses to rule changes depends on rule type

Learning a target rule is one of two key events in decision-making tasks. The other is responding to a change in the target rule. Changes in behaviour around rule switches are useful to understand the flexibility of behaviour, and the relative dominance of one mode of responding (e.g. spatial) over another (e.g. cue-driven) (*Birrell and Brown, 2000*; *Floresco et al., 2008*; *Buckley et al., 2009*; *Wang et al., 2019*). To show how our approach can quantify behavioural flexibility, we thus used our inference algorithm to examine trial resolution changes in choice strategy around rule-switches in the same Y-maze and lever-press tasks.

In both tasks, rats which had been training on a spatial rule continued to have a high probability of executing a spatial strategy on each trial long after the rule had switched to a cue-based target rule (*Figure 4*a,b left panels). Thus, rats showed little behavioural response during switches from spatial to cued rules.

The switch from a cued to a spatial rule in both tasks evoked a considerably faster change in strategy. Over the same time window as the spatial→cued switch, while the probability of selecting the cued strategy declined slowly, the probability of selecting the now-correct spatial strategy increased above chance within 20 trials of the rule switch (*Figure 4*a,b right panels).

To demonstrate the fine-grained analysis possible with our Bayesian algorithm, we also quantified the variability in rule-switch responses across rats by calculating for each rat the proportion of trials in which each rule strategy was above chance after the switch (*Figure 4*c,d). Individual rats sustained their use of the now-incorrect strategy after both spatial→cued and cued→spatial rule switches (*Figure 4*c,d). The reduction in use of a cued strategy after cued→spatial rule switches was also evidenced by that strategy reverting to chance for a few trials so that the proportion of trials above chance was less than one (*Figure 4*d, right). Rats in both tasks also showed considerable variation in how often a spatial strategy was above chance after the switch to the spatial rule (*Figure 4*c,d, right), suggesting varying rates of adapting to the rule switch.

Figure 4. Detecting responses to task changes
(**a**) Responses to rule switches in the Y-maze task. The left panel plots the MAP estimates of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for the target spatial and cue strategies aligned to the switch from a spatial to a cued rule (N=7 sessions, from 4 rats). The right panel plots the MAP estimates aligned to the switch from a cued to a spatial rule (N=3 sessions, from 3 rats). For both panels, curves plot means ± SEM (shading) across sessions, aligned to the rule switch trial (vertical dashed line). The horizontal dashed line indicates chance.
(**b**) Same as panel a, but for the lever-press task. $N = 16$ rats for spatial→cued; $N = 12$ cued→spatial.
(**c**) Response to each rule-switch in the Y-maze task. Each dot shows the proportion of trials after a rule-switch in which the labelled strategy was above chance. Proportions calculated for a window of 30 trials after the rule switch. Lines join data-points from the same switch occurrence.
(**d**) Same as panel c, for the lever-press task. Proportions calculated for a window of 60 trials after the rule switch, to take advantage of the longer sessions in this task.

Our trial resolution algorithm has thus provided evidence from both learning (Fig 3f) and responding to rule switches (Fig 4) that the spatial→cued rule switch is harder for rats to detect than the cued→spatial switch, across two different tasks. Moreover, the behavioural response to the cued→spatial rule switch (*Figure 4*a,b, right panels) shows that, as both were above chance, the newly correct strategy ('go spatial') can be acquired even while the now incorrect strategy ('go cued') is still actively used.

Independent changes in lose-shift and win-stay around learning and rule switches

Having used the changes in rule strategies to characterise both learning and the response to rule switches, we then sought to understand the exploratory strategies that were driving these changes.

To probe this, we computed $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for four exploratory strategies based on the task features pertinent to the target rules. For the spatial rules, these were win-stay and lose-shift based on the choice of arm or lever; for example, repeating the choice of left arm or lever after being rewarded for it on the previous trial would be a spatial win-stay. For the cued rules, these were win-stay and lose-shift based on the cue position; for example, repeating the choice of the cued arm or lever after being rewarded for it on the previous trial would be a cued win-stay.

We found strong evidence that rule-learning was preceded by a high probability of animals using lose-shift in response to the corresponding feature of the target rule (*Figure 5*a,d, top pair of panels). This elevated use of lose-shift to the target rule's feature was consistent for both classical and strategy definitions of learning trials and across both the Y-maze (*Figure 5*a) and lever-press (*Figure 5*d) tasks. The sustained probability of using lose-shift was not due to the lack of opportunity to update that strategy: before the identified learning trial animals had not yet reached ceiling performance with the rule, so were still incurring losses (*Figure 5*a,d, bottom panels). This use of lose-shift is consistent with latent learning of the relevant feature of the target rule.

Lose-shift exploration rapidly altered at rule changes too. Immediately after a rule switch, lose-shift in response to the old rule's target feature declined rapidly as animals now persevered in

Figure 5. Lose-shift and win-stay independently change around learning and rule switches

(**a**) Changes in the probability of win-stay and lose-shift strategies around learning. In the top pair of panels we plot probabilities for choice-driven (left) and cue-driven (right) forms of win-stay and lose-shift aligned to the identified learning trial (trial 0). Learning trials identified by either the original study's criterion (top) or our rule-strategy criterion (middle). The bottom panel plots the proportion of correct choices across animals on each trial. Lines and shading show means ± SEM (*N* given in *Figure 3*b).

(**b**) Rule-switch aligned changes in probability for choice-based win-stay and lose-shift strategies (*N* given in *Figure 4*a).

(**c**) Rule-switch aligned changes in probability for cue-based win-stay and lose-shift strategies.

(**d**-f) Same as panels a-c, but for the lever-press task. Panel d: *N* = 28 rats per curve. Panel e-f: *N* = 16 rats spatial→cued; *N* = 12 cued→spatial.

377   applying the old rule, so frequently re-chose the same option after losing (*Figure 5*b-c,e-f). In the
378   lever-press task, there was a rapid increase of lose-shift in response to the new rule's feature for

379 both switches from spatial to cued rules (*Figure 5*e, right) and vice-versa (*Figure 5*f, left), again
380 consistent with latent awareness that the original rule had changed.

381   For both learning and rule changes, win-stay exploration did not change with lose-shift. During
382 learning, win-stay changed at or around the learning trial in both the Y-maze (*Figure 5*a) and lever-
383 press (*Figure 5*d) tasks. At a rule change, win-stay for the old rule's feature changed faster for
384 the cued→spatial (*Figure 5*c,f, right panels) than the spatial→cued rule switches (*Figure 5*b,e, left
385 panels), underpinning the faster response to the cued→spatial switch (*Figure 4*). We ruled out that
386 this independence of win-stay from lose-shift was because one of those strategies could not be
387 updated, as the rate of correct trials was neither at floor nor ceiling before learning and after rule
388 switches (*Figure 5*: bottom panels in a,c,d,f). Lose-shift and win-stay were thus independently used
389 and changed during exploration around learning and rule changes.

390 **Latent exploratory strategies disguise the absence of learning in humans**

391 We now turn to demonstrating insights from the inference algorithm on a wider range of tasks.
392 Here we analyse human performance on a simple stimulus-choice task, with no rule switches, to
393 illustrate how the algorithm performs with only a few trials; in the next section we consider non-
394 human primate performance on a stimulus-action task with stochastic reward.

395   Human participants performed a two-choice task, similar to that of *Pessiglione et al.* (*2006*),
396 in which they had to choose between two stimuli that appeared above and below a central fix-
397 ation point (*Figure 6*a). The top or bottom position of each pair of stimuli was randomised on
398 each trial, and three pairs of stimuli corresponded to three interleaved trial types. In 'gain' trials,
399 one stimulus increased total reward with a probability of 0.8, the other nothing; in 'loss' trials, one
400 stimulus reduced total reward with a probability of 0.8, the other nothing; and in 'look' trials, par-
401 ticipants randomly chose one of the two stimuli, with no associated outcome. Their implicit goal
402 was thus to maximise reward by learning to select the gain stimulus and avoid the loss stimulus.
403 As participants only experienced 30 of each trial type, these data could present strong challenges
404 to classical approaches of identifying if and when participants learnt to correctly choose the gain
405 stimulus or avoid the loss stimulus, and what strategies they adopted during learning. By contrast,
406 our Bayesian approach can track changes in strategies within a few trials (*Figure 2*).

407   To identify learning, we separately computed $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ for the strategies of
408 selecting the gain stimulus and of avoiding the loss stimulus (*Figure 6*b). Despite the few trials
409 involved, these estimates were not sensitive to the choice of prior (*Figure 6*b and *Figure 6–Figure*
410 *Supplement 1*). Across all participants, the MAP estimates of $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ showed
411 evident learning of choosing the gain stimulus, but not of avoiding the loss stimulus (*Figure 6*c).
412 Applying the same learning criterion as above, of the MAP probability being above 0.5 until the
413 end of the session, our inference algorithm suggests most participants learnt to choose the gain
414 stimulus (13/20), but not to avoid the loss stimulus (5/20) (*Figure 6*d). Even then, the few who did
415 putatively learn to avoid the loss stimulus did so only towards the end of the 30 trials (*Figure 6*e).
416 Our trial resolution probabilities have thus shown both strong evidence of which participants learnt
417 the gain trials, and that there is weak evidence at best of any participant learning to avoid the loss
418 stimulus.

419   To further examine this issue, we asked if the apparent learning to avoid loss could be explained
420 by an exploratory strategy. For the participants who putatively learnt either the gain or loss rule
421 strategies we computed $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ for a range of exploratory strategies that cap-
422 tured either responding to the previously chosen stimulus or to the previous location of the chosen
423 stimulus. We found stimulus-driven win-stay and lose-shift were both used for learning gain trials,
424 but not for loss trials (*Figure 6*f). By contrast, only location-driven exploration was consistently,
425 albeit weakly, above chance for loss trials (*Figure 6*f). Because this suggested participants could
426 be sensitive to the location of the stimuli, we then also examined location-dependent strategies in
427 the 'look' trials, and found participants were strongly biased towards choosing one location over
428 the other; however, this bias did not correlate with the participants' use of the avoid-loss strategy

Figure 6. Human learning and exploration on a gain/loss task

(**a**) Gain/loss task. Gain, loss, and look trials each used a different pair of stimuli and were interleaved. A pair of stimuli were randomly assigned to the top or bottom position on each trial. Numbers above Outcome panels refer to the probabilities of those outcomes in the gain and loss trial types.

(**b**) For an example participant, the MAP estimate of $P(\mathrm{strategy}_i(t)|\mathrm{choices}(1:t))$ for the target rule strategy during gain (left panel) and loss (right panel) trials. We plot two estimates, initialized with our default uniform prior (solid) or Jeffrey's prior (dotted). Horizontal dashed lines indicate chance level. Black arrows indicate the learning trial based on our strategy criterion.

(**c**) The MAP estimate of $P(\mathrm{strategy}_i(t)|\mathrm{choices}(1:t))$ for the target rule strategies across all participants. Curves plot mean $\pm$ SEM (shading) across 20 participants. The dashed line is chance.

(**d**) Proportion of participants that learnt the target strategy for gain or loss trials. Learning was identified by the first trial at which the MAP estimate of $P(\mathrm{strategy}_i(t)|\mathrm{choices}(1:t))$ was consistently above chance until the end of the task (black arrows in panel b). Vertical bar indicates the 95% Clopper-Pearson confidence intervals for binomial estimates.

(**e**) Distributions of learning trials for gain and loss trials, for the participants meeting the learning criterion. Each dot is a subject. Boxplots show the median, and the 25^{th} and 75^{th} percentiles. The whiskers extend to the extreme values.

(**f**) Probabilities of exploratory strategies for the learning participants (N=13 for gain, N=5 for loss). Curves plot mean $\pm$ SEM (shaded area) MAP probabilities.

Figure 6–Figure supplement 1. Human strategies are robust to priors and do not correlate with bias in preferred target locations

---

₄₂₉ (*Figure 6–Figure Supplement 1*). Together, these results suggest that no participant learnt avoid-
₄₃₀ loss, and those who appeared to were instead executing a location-driven exploratory strategy that
₄₃₁ happened to coincide with avoid-loss for the final few trials.

Choice strategy driven by reward probability not magnitude in a stochastic decision task

₄₃₄ More complex decision-making tasks use probabilistic and variable-size rewards for all choices.
₄₃₅ These present further challenges for the analysis of choice behaviour, not least because the varia-
₄₃₆ tion of both probability and size of reward increases the number of features upon which subjects
₄₃₇ may base their choice strategies. To examine these challenges, we used our inference algorithm
₄₃₈ to analyse a session of data from a rhesus macaque performing a stimulus-primed two-choice task
₄₃₉ (*Figure 7*a).

Figure 7. Probabilistic reward

(**a**) Schematic of the stimulus-to-action reward task. Left: The monkey initiated a trial by touching a key after the red dot appeared on-screen. A stimulus appeared, predicting which side of the upcoming choice would have the higher probability of obtaining the large reward. Touching the stimulus and then the key brought up the choice options on-screen. The monkey indicated its decision by touching the appropriate circle on-screen. Right: probabilities of obtaining the large reward for each of the six stimuli.

(**b**) MAP probability for the strategy of choosing the side with the highest probability of reward ('go high-probability side'). We also plot the MAP probabilities for the choice of side (left or right). Green and blue dots at the top and bottom indicate the side with the higher probability of receiving the large reward; probabilities switched (vertical dashed lines) after the subject chose the high probability option on 80% of trials in a moving window of 20 trials.

(**c**) MAP probabilities in panel b aligned to the transition between blocks (trial 0). Average (bold lines; n=5 blocks) ± SEM (shaded areas).

(**d**) MAP probabilities along the session for exploratory strategies based on repeating the previous choice after either receiving the large reward or choosing the option with the higher probability of the large reward.

(**e**) Proportion of trials in which the two repeating-choice strategies had the largest MAP probability. Vertical bars are 95% Clopper-Pearson confidence intervals.

(**f**) As panel d, for exploratory strategies based on switching from the previous choice after either receiving the low reward or choosing the option with the lower probability of high reward.

(**g**) As panel e, for the switching strategies in panel f.

In this task, the monkey was presented with a stimulus that predicted the probability of obtain-
ing the larger of two rewards if it subsequently chose either the left or right option on a touchscreen
(*Figure 7*a, left). Six stimuli were associated with a different pair of probabilities for obtaining the
larger reward for the left or right choice (*Figure 7*a, right); whatever the monkey chose, the small re-
ward was delivered if the probability check for the large reward failed. The stimulus and associated
pair probabilities switched once the monkey chose the highest-probability option in 80% of trials.
With our trial-resolved approach we can immediately ask two questions: did this criterion give suf-
ficient evidence for learning, and was the monkey's choice based on the probability of obtaining
the large reward or something else?

To test the switching criterion, we computed $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for the strategy of choos-
ing the side with the highest probability of reward (*Figure 7*b). This confirmed the monkey showed
good evidence of learning by the time the criterion was reached, as $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for
the highest-probability option became dominant at least 10 trials before the switch of reward prob-
abilities (orange line *Figure 7*c). Our analysis also suggests that in at least one block (trials 25 to
160 in *Figure 7*b), the monkey had learnt to choose the appropriate option long before the block
switch.

As the choice of either option in this task could result in the large reward, the monkey may have
been basing its exploration not on the probability of the large reward, but simply on the value of
the obtained reward. To examine this, we computed $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for two sets of
exploratory strategies that used different features of the monkey's choice history: one set looked
at whether repeating the same option choice was driven by the value or the probability of reward
on the previous trial (*Figure 7*d); and the other looked at whether switching the option choice was
driven by the value or the probability of reward on the previous trial (*Figure 7*f). The monkey's use
of exploratory strategies that repeated or switched choices evolved over the blocks (*Figure 7*d,f).
Independent of this evolution, both repeating and switching strategies were dominated by the
probability of reward rather than the reward obtained (*Figure 7*e,g), evidence that the monkey
was basing its decisions more on reward probability than immediate value. Because each session
had new arbitrary stimuli for the six pairs of probabilities, the monkey was here re-learning the
mapping between stimuli and probabilities, and so was not trivially choosing from an already-learnt
association. Rather, these results suggest that, through its prior training, the monkey had learnt
the structure of the probabilities, and so was able to use that abstract knowledge to guide its
exploratory choices.

Discussion

Subjects may adopt a range of choice strategies during decision-making tasks, which change during
training as they learn a target rule, and as the rule is changed. Uncovering how subjects learn to
make decisions is essential for understanding what information drives behaviour and for linking
neural activity to behaviour. Classical approaches to characterising decision making, such as trials-
to-criterion measures (*Birrell and Brown, 2000*; *Peyrache et al., 2009*; *Brady and Floresco, 2015*),
psychometric functions (*Britten et al., 1992*; *Palmer et al., 2005*; *Churchland et al., 2008*) or reward
curves (*Gallistel et al., 2004*), cannot track changes over time; algorithms for detecting learning
points (*Smith et al., 2004*; *Suzuki and Brown, 2005*) and behavioural change-points (*Durstewitz
et al., 2010*; *Jang et al., 2015*) are useful, but do not show what strategies were used during learning
or around rule changes. To address these issues, we have introduced an approach to decision-
making tasks that fully characterises the probability of choice strategies at trial resolution. Our
inference algorithm allows tracking both learning, by defining strategies matching target rules, and
how subjects learn, by defining exploratory strategies that may or may not depend on features of
the task. We have applied our algorithm to a variety of two-choice tasks, across a range of species,
including Y-maze and lever-press tasks in rats, a stimulus-outcome mapping task in humans and
a stochastic stimulus-action task in non-human primates.

Across the tasks we analysed, our algorithm showed that lose-shift and win-stay are independent exploratory strategies, because a change in the probability of one being executed is not mirrored by a change in the probability of the other. This challenges views that win-stay and lose-shift are complementary strategies, often yoked together (*Miller et al., 2017*; *Izquierdo et al., 2017*; *International Brain Laboratory et al., 2021*; *Roy et al., 2021*).

Emphasising this independence, our analysis shows that changes to lose-shift are evidence of latent learning. Rats adopted a lose-shift strategy matching the target rule before the learning of that rule was identified by overt choice behaviour (*Figure 5*a,d). Conversely, after a switch in rewarded rules in the lever-press task, rats rapidly started using a lose-shift strategy that matched the new rule while still using a win-stay strategy based on the old rule (*Figure 5*b-c,e-f). These data are consistent with ideas that negative and positive feedback can independently drive changes in decision making. Indeed they support the idea that learning what not to do is easier than learning what to do.

We derived three potential criteria for learning from the algorithm's estimate of a subject's probability of using the correct strategy. The most sensitive criterion showed in both the Y-maze and lever-press tasks that learning occurred earlier and more often than detected in traditional approaches based on counting successful trials in some fixed window. All three criteria showed that switching from a spatial to a cue-based rule is harder than the reverse switch. This is consistent with prior work suggesting rats learn spatial rules more easily than visually-cued rules (*Mackintosh, 1969*). Prior work on the same lever press task had shown some evidence of the opposite, that re-learning is faster after switching from a spatial to a cued rule than switching from a cued to a spatial rule (*Floresco et al., 2008*). Our results suggest that the choice of learning criterion do not underpin this discrepancy.

There has been considerable recent advocacy for studying the variety of behaviour within and between individuals (*Krakauer et al., 2017*; *Honegger and de Bivort, 2018*; *Pereira et al., 2020*; *Roy et al., 2021*; *Ashwood et al., 2022*), both to more richly characterise the diversity of behavioural solutions adopted by humans or other animals facing a task, and as a basis for understanding the link between neural activity and behaviour. As it provides trial-resolution probabilities for each subject, our algorithm quantifies the behavioural diversity in a given task. We illustrated that potential here by defining learning points for each subject in the Y-maze (*Figure 3*c), lever-press (*Figure 3*f), and human gain/loss tasks (*Figure 6*d,e), and by showing the distribution of exploratory behaviours around rule switches (*Figure 4*c,d). Further work here could use the trial-resolution probabilities to characterise an individual's repertoire of strategies and when they deployed each strategy.

Reflecting this urgent need for fine-grained behavioural insights into how subjects make decisions, recent work by Pillow and colleagues introduced two innovative solutions to the problem of tracking a subject's behaviour (*Roy et al., 2021*; *Ashwood et al., 2022*). One solution (PsyTrack: *Roy et al., 2021*) continuously infers the parameters of a psychometric function to track the relative influence of different task features on choice in two-alternative forced-choice tasks; the other (*Ashwood et al., 2022*) infers the hidden states underlying decision-making behaviour and the transitions between them, by modelling psychometric functions in each state. Their elegant work applies to well-learnt behaviour, using computationally-intensive models fit to all available data post-hoc, but lacks the ability to infer when learning occurs. By contrast, our approach focuses on behavioural strategies adopted during learning and rule switches, accumulates evidence up to trial t so can be used on-line, and is able to infer strategies in a few tens of trials (Figures 2 and 6), but lacks a model of the transitions between strategies or the parameters which influence the current strategy. An interesting future avenue for our work would be to use the changing probability of different strategies to infer the transition probabilities between them. Our approach and that of Pillow and colleagues are thus complementary, collectively providing a richer toolbox for understanding a subject's behaviour on choice tasks.

The probabilities computed by our algorithm are a description of the observer: what we can tell about the behaviour on trial t from the evidence so far. This Bayesian analysis of behaviour

does not imply the animal is behaving in any optimal, Bayesian way, nor that its brain is computing or using probabilities (*Knill and Pouget, 2004*; *Fiser et al., 2010*; *Pouget et al., 2013*; *Sohn et al., 2019*). Nonetheless, using a Bayesian strategy analysis could let us then formulate those questions of optimality in behaviour and look for neural correlates of probabilistic representations. More generally, such a trial-by-trial analysis of a strategy could then let us look for neural correlates, more accurately tracking the changes in neural activity that precede or align with changes in behavioural strategy (*Rich and Shapiro, 2009*; *Durstewitz et al., 2010*; *Karlsson et al., 2012*; *Powell and Redish, 2016*; *Guise and Shapiro, 2017*).

One issue we faced is that Bayesian inference assumes the parameter being estimated is stationary, but choice strategies are not, so any estimate of their probability must also change. Here we solve that problem by weighting the evidence entering the Bayesian update by its recency. This allows tracking the probabilities of strategies as they change, and is robust to the exact weighting used (*Figure 2*; *Figure 2–Figure Supplement 2* to *Figure 2–Figure Supplement 4*).

The choice of how much to decay the influence of past evidence can determine how quickly a change in strategy is detected (*Figure 2*; *Figure 2–Figure Supplement 2* to *Figure 2–Figure Supplement 4*), suggesting other solutions to this non-stationary problem are worth pursuing. For example, having a principled way of varying the weighting γ of evidence over time could be useful, potentially so that evidence is rapidly decayed around a switch in strategies and less rapidly during stable execution of a strategy. This would require defining γ as a function of some observable parameter of behaviour. It could also potentially find different evidence decay rates γ between different strategies.

Introducing γ may seem to create a free parameter for the analysis. However, all frequentist approaches to analysing the strategies of subjects also have at least one free parameter, namely the length of the time window over which to compute the probability they are using. This is true both for computing the probability of a particular strategy being used as the proportion of trials it occurs on (*Singh et al., 2019*; *Harris et al., 2021*; *Trepka et al., 2021*) and for classic learning criterion of subjects performing sequential, or a proportion of, successful trials in some time window (e.g. *Birrell and Brown, 2000*; *Boulougouris et al., 2007*; *Floresco et al., 2008*; *Leeson et al., 2009*; *Peyrache et al., 2009*; *Brady and Floresco, 2015*). Sometimes this time window is explicitly chosen (*Singh et al., 2019*); sometimes the choice is implicit, as the probabilities are computed over trial blocks (*Trepka et al., 2021*) or phases of the experiment (*Harris et al., 2021*). Either way, rarely is the influence of that time window considered. Thus, rather than γ introducing a further free parameter, it instead makes the inevitable free parameter of time explicit and bounded: we have placed strong bounds on the values of γ by showing the trade-off between the speed of detecting a new strategy and the stability of detecting it.

Our algorithm provides rich information about choice behaviour by computing a full posterior distribution for each modelled strategy, for every trial. How that information is then used to further our understanding of choice behaviour offers a wealth of potential. Here we tackled the question of when subjects learnt by computing three criteria from the posterior distribution of the target rule's strategy and the question of how they explored by tracking a point estimate of the probability of each exploratory strategy from their posterior distribution. A third question, which we did not address here, is: which strategy is the subject most likely to be using now? In our simulations, the simple decision rule of choosing the strategy with the highest MAP estimate and highest precision worked well; further work could explore solutions that make fuller use of the posterior distribution, for example computing the probability (*Cinotti and Humphries, 2022*) that a strategy is dominant over the others. Whether this is a good question to ask depends upon our model for how a subject is using strategies: seeking the dominant strategy implies a model where subjects switch between strategies discretely; by contrast, a model where subjects sample from a repertoire of strategies on each trial means our estimated $P(\text{strategy}_i(t)|\text{choices}(1:t))$ is tracking the probability of sampling each strategy. Disentangling these models would give deeper insight into how subjects explore while learning.

The richness of the information depends in part on the choice of strategies examined, which is down to the end-user and what questions they wish to ask of their data. We here distinguished rule strategies and exploratory strategies: while the former should be examined to understand learning, the latter can include a wider range of options than we examined here. We focused predominantly on variants of win-stay and lose-shift strategies as these are widely studied (*Miller et al., 2017*; *Constantinople et al., 2019*; *International Brain Laboratory et al., 2021*; *Roy et al., 2021*; *Ashwood et al., 2022*), contrasting the different features of a task – subject's spatial choice or the task cues – that define the stay or shift response. But the range of strategy models usable with our inference algorithm is broad enough to cover many potential questions about decision-making: all the algorithm needs is the success or failure to execute a given strategy on trial t. As such, our approach is highly extensible. It can be used with more complex models of choice-history strategies than those considered here: for example, where classic win-stay and lose-shift consider only the previous trial, n-back history strategies (*Lau and Glimcher, 2005*; *Akrami et al., 2018*) could capture the effect of choices or outcomes $t - n$ trials ago on the decision at trial t. It could also be used with economic games, tracking the probability of each player using specific response strategies to others' decisions, like Tit-for-Tat (*Axelrod and Hamilton, 1981*; *Axelrod and Dion, 1988*; *Nowak and Sigmund, 1993*; *Ohtsuki et al., 2006*). Pilot or bias tests could be used to estimate the prior distribution's parameters for each subject. And while all tasks here had two choices, the algorithm can just as easily compute probabilities of choice strategies in tasks with three or more choices. Despite this extensibility, the computational cost per trial is extremely low, as elementary arithmetic alone is needed for computing the update to the posterior distribution. Consequently, the inference algorithm we introduce here can assess the probabilities of an extensive, flexible range of choice strategies, and could do so in real-time, allowing detailed interrogation and potentially closed-loop control of animal and human behaviour during decision-making tasks.

Acknowledgements

This work was supported by the Medical Research Council [grant numbers MR/J008648/1, MR/P005659/1 and MR/S025944/1] to M.D.H. and [grant number MR/K005480/1] to M.J.B, and the Biotechnology and Biological Sciences Research Council [grant number BB/T00598X/1] to M.J.B. and M.D.H. S.M. was supported by an Anne McLaren Fellowship from the University of Nottingham. M.S. was supported by a Medical Research Council fellowship and a grant from the Dowager Countess Eleanor Peel Trust. Collection of the data on the rat lever-press task was supported by the Biotechnology and Biological Sciences Research Council (BBSRC) Doctoral Training Programme (DTP) at the University of Nottingham [grant number BB/M008770/1, project 1644954], and we are grateful to Stan Floresco for providing MedAssociates programmes to run the lever-press task. We thank Hazem Toutounji for comments on the manuscript, Nathan Lepora for discussions, and Lowri Powell for contributing to the Python port of the toolbox.

Author contributions

Silvia Maggi: Formal Analysis, Software, Writing – Original Draft Preparation, Visualization, Validation, Data Curation.

Rebecca M Hock: Investigation, Writing – Review and Editing.

Martin O'Neill: Investigation, Writing – Review and Editing.

Mark J Buckley: Supervision, Funding Acquisition, Writing – Review and Editing, Investigation.

Paula Moran: Supervision, Writing – Review and Editing.

Tobias Bast: Supervision, Writing – Review and Editing

Musa Sami: Investigation, Writing – Review and Editing

Mark Humphries: Conceptualization, Methodology, Software, Formal Analysis, Writing - Original Draft Preparation, Visualization, Supervision, Project Administration, Funding Acquisition.

Materials and methods

Code availability

Code toolboxes implementing the algorithm and strategy models are available for MATLAB (https://github.com/Humphries-Lab/Bayesian_Strategy_Analysis_MATLAB and Python (https://github.com/Humphries-Lab/Bayesian_Strategy_Analysis_Python). These toolboxes will be updated with future improvements to the algorithm.

All code used to produce the figures in this paper is available at https://github.com/Humphries-Lab/Bayesian_strategy_analysis_Paper. This repository also includes all data in the paper that we are able to share (see Data Availability Statement below).

Bayesian inference of strategy probability

Here we give the full algorithm as used throughout the paper.

1. Choose a set of N strategy models to test.
2. Each $P(\text{strategy}_i(t)|\text{choices}(1:t))$ is parameterised by a Beta distribution, with parameters $\alpha_i(t), \beta_i(t)$, for $i = 1, 2, \ldots, N$.
3. The prior is defined by the choice of $\alpha_i(0), \beta_i(0)$. We use the uniform prior $\alpha_i(0) = \beta_i(0) = 1$ by default; we use the Jeffrey's prior $\alpha_i(0) = \beta_i(0) = 1/2$ where noted.
4. Initialise the running counts of successful (s_i^*) and failed (f_i^*) trials to use strategy i as $s_i^*(0) = f_i^*(0) = 0$.
5. On every trial t:
   (a) label it for strategy i as either a:
   Success trial choice made on trial t is consistent with strategy i: $x_i(t) = 1$;
   Failure trial choice made on trial t is inconsistent with strategy i: $x_i(t) = 0$,
   Null trial strategy i could not be assessed on trial t.
   (b) For success and failure trials, we update the parameters $\alpha_i(t), \beta_i(t)$:
      i. decay the event totals, and add the new event: $s_i^*(t) = \gamma s_i^*(t-1) + x(t)$; and $f_i^*(t) = \gamma f_i^*(t-1) + (1 - x(t))$;
      ii. update the Beta distribution parameters: $\alpha_i(t) \leftarrow \alpha_i(0) + s_i^*(t)$ and $\beta_i(t) \leftarrow \beta_i(0) + f_i^*(t)$.
   with a decay rate $\gamma \in (0, 1]$.
   (c) For null trials, we assign the previous trial's parameter value: $\alpha_i(t) \leftarrow \alpha_i(t-1)$, $\beta_i(t) \leftarrow \beta_i(t-1)$.
6. Output: time-series of $\alpha_i(t)$ and $\beta_i(t)$ for each strategy i, which define a Beta distribution for each trial.

Null trials occur when a strategy depends on conditions that could not be met in that trial. In our current implementation we interpolate the previous values for α, β for a null trial, to define the probability at which that strategy could have occurred. Future extensions to our work could usefully explore alternative solutions to the handling of null trials.

Task descriptions

Data availability statement

Source data from the rat Y-maze task data are available from crcns.org at http://dx.doi.org/10.6080/K0KH0KH5. Source data from the rat lever-press task (32 rats), the human gain/loss task (20 participants) and the primate stimulus-to-action task (one session) are available from the Nottingham Research Data Management Service at http://doi.org/10.17639/nott.7274. Processed data and analysis code to replicate all figures are available in our GitHub repository https://github.com/Humphries-Lab/Bayesian_strategy_analysis_Paper. Our copies of the source data for the Y-maze task, lever-press task, gain/loss task, and stimulus-to-action task are also freely available from the same repository.

Y-maze – rats

Rat behavioural data on the Y-maze task data came from the study of *Peyrache et al.* (*2009*). This dataset includes 50 sessions of four male Long-Evans rats performing a cross-modal rule switch task. Rats were trained to self-initiate the trial by running up the central stem of the maze and choosing one of the two arms. The rats had to learn in sequence one of four rules: 'go right','go cued', 'go left', 'go un-cued'. The cue was a light stimulus randomly switched at the end of one of the two arms. The rule was changed within session after performing 10 consecutive trials or 11 out of 12 correct trials. In the original study, learning was defined as the first of three consecutive trials followed by a performance of $\geq 80\%$ until the end of the session. For each trial, we used the choice location (right or left), the cue location (right or left) and the reward (yes or no) as input data for the Bayesian model.

Lever-press – rats

All experimental procedures were conducted in accordance with the requirements of the United Kingdom (UK) Animals (Scientific Procedures) Act 1986, approved by the University of Nottingham's Animal Welfare and Ethical Review Board (AWERB) and run under the authority of Home Office project license 30/3357.

Rat behavioural data for the lever-press task was taken from 32 male Lister Hooded rats (aged 11 weeks at the start of testing and food-restricted throughout behavioural training), which served as control groups in two micro-infusion studies (each $N = 16$) targeting prelimbic medial prefrontal cortex. These rats had infusion guide cannulae implanted in the medial prefrontal cortex and received saline infusions in the medial prefrontal cortex (for surgery and infusion procedures, see *Pezze et al. 2014*) at various task stages, including before the sessions during which the data presented in this paper were collected. The task was run in standard 2-lever operant boxes with cue lights above the levers and a food well between them (Med Associates, US) based on a previously published training protocol (*Brady and Floresco, 2015*).

Rats were pre-trained to press the levers for sucrose rewards. The rats then had to learn an initial rule to receive one reward per correct response: either a spatial rule or a visual cue-based rule. The spatial rule required the rat to select the left or right lever, one of which was designated as the correct response and associated with reward. The visual cue-based rule required the rat to select the lever indicated by a cue light, which appeared above one of the two levers and was always associated with reward irrespective of which lever it appeared above. Each trial ended either when a response was made on a lever or when the 10-s time window for responses had elapsed without a response (defined as an omission). After reaching the criterion of 10 consecutive correct trials, the rats had to learn to switch their responses to the second rule: rats which had learnt the spatial rule first were tested on the cue-based rule, and vice versa.

Half the rats ($N = 16$) experienced the spatial rule first: all reached criterion on it and on the subsequent cued rule. Half ($N = 16$) experienced the cued rule first: 12 reached criterion so were switched to the spatial rule, which all 12 reached criterion on as well. Our strategy-based definition of learning (see below) found the same number of learners in each condition, so we have $N = 28$ rats throughout for analysis of learning (*Figure 3*) and strategy flexibility (*Figure 4*).

Gain/loss task – humans

The study was approved by Research Ethics Committee (Stanmore London REC 17/LO/0577). Human participants ($n = 20$, 10 male, 10 female) read a participation information leaflet and undertook informed consent. Participants performed a two choice task, similar to that of *Pessiglione et al.* (*2006*), in which they had to choose between two arbitrary stimuli that appeared above and below a central fixation point (*Figure 6*a), across three pairs of stimuli corresponding to three interleaved trial types. The top or bottom position of each pair of stimuli was randomised on each trial. In 'gain' trials, one stimulus increased total reward by £1 with a probability of 0.8, the other nothing; in 'loss' trials, one stimulus reduced total reward by £1 with a probability of 0.8, the other nothing;

and in 'look' trials, participants randomly chose one of the two stimuli, with no associated outcome. 30 trials of each type were presented, randomly interleaved. All participants were informed that the amount they received would be dependent upon their performance, but all received the same amount (£20) at the end of the task.

Stimulus-action task – non-human primates

Rhesus macaques were trained to touch a key in front of a touchscreen monitor when a red dot appeared on the screen (*Figure 7*a). A visual stimulus then appeared above the dot. After a delay the dot disappeared and the animal had to touch the monitor where the stimulus was present. The dot then reappeared instructing the animal to touch the key again. Two white circles then appeared simultaneously to the left and right of the dot. After a delay the dot disappeared, and the animal chose to select the left or right circle. A large (0.9 ml) or small (0.3 ml) reward of banana smoothie was delivered after every trial. The rewards were probabilistic and asymmetric to either side (*Figure 7*a, right panel). There were six reward probability pairings associated with six visual stimuli per session. For example, one visual stimulus predicted the large reward with p = 0.5 following a left action and p = 0.1 following a right action (denoted '0.5:0.1' in *Figure 7*a). If the probability check for the large reward failed, the small reward was delivered instead. Each of the six stimuli were presented in a blocked design with the stimulus change and block transition occurring after 80% choices (16/20 trials) of the side with the highest probability of the large reward. We analysed here a single session from one monkey.

In the full study from which this session was taken, behavioural data were recorded in two young adult male rhesus macaque monkeys (Macaca mulatta, one aged 8 years, weight 10-13 kg; the other aged 9 years, weight 11-15 kg). All animals in the Buckley lab are socially housed (or socially housed for as long as possible if later precluded, for example, by repeated fighting with cage-mates despite multiple regrouping attempts) and all are housed in enriched environments (e.g. swings and ropes and objects, all within large pens with multiple wooden ledges at many levels) with a 12hr light/dark cycle. The NHPs always had ad libitum water access 7 days/week. Most of their daily food ration of wet mash and fruit and nuts and other treats were delivered in the automated testing/lunch-box at the end of each behavioral session (this provided 'jack-pot' motivation for quickly completing successful session performance; supplemented by the trial-by-trial rewards for correct choices in the form of drops of smoothie delivered via a sipping tube) and this was supplemented with fruit and foraging mix in the home enclosure. For the study the animal was prepared for parallel neurophysiological investigation, and so was head-fixated during the task using a standard titanium head-post (and also had recording implants); implantation adopted standard aseptic surgical methods used in the non-human primate laboratory that are not directly relevant for this behavioural study but are described in detail elsewhere (*Wu et al., 2021*). All animal training and experimental procedures were performed in accordance with the guidelines of the UK Animals (Scientific Procedures) Act of 1986, licensed by the UK Home Office, and approved by Oxford's Committee on Animal Care and Ethical Review.

Strategy models for each task

The strategy models we use for the analysis of the Y-maze and lever-press task data are defined in Tables 1 and 2. In Figures 3-5 we group the analyses of either 'go left' or 'go right' as 'spatial rules', and the analyses of either 'go cued' or 'go uncued' as 'cued' rules.

Analyses of the human gain/loss task used the same set of exploratory strategies, with the replacement of "spatial" by "location", and "cued" by "stimulus". The two rule strategies were defined as: "go gain" – success if the subject chose the potentially rewarded stimulus; "avoid loss" – success if the subject did not choose the potentially reward-decreasing stimulus.

Analyses of the non-human primate stimulus-action task examined three rule strategies, 'go left', 'go right', and 'go high-probability', the latter defined as a success if the subject selected the option with the higher probability of the large reward. Table 3 defines the exploratory strategy

Table 1. Rule strategy models for rat tasks. Columns give the conditions to define trial t as a success, failure, or null for each strategy corresponding to a target rule. The rule strategies we consider here do not have null conditions.

	Success	Failure	Null
Go left	chose left option	didn't choose left option	n/a
Go right	chose the right-hand option	didn't choose the right-hand option	n/a
Go cued	chose cued option (e.g. the lit lever)	didn't choose the cued option	n/a
Go uncued	chose the uncued option (e.g. the unlit lever)	didn't choose the uncued option	n/a

Table 2. Exploratory strategy models for rat tasks. Columns give the conditions to define trial t as a success, failure, or null for each exploratory strategy.

	Success	Failure	Null
Win-stay-spatial	Rewarded on trial $t-1$ AND chose the same spatial option (e.g. the left lever) on trial t	Rewarded on trial $t-1$ AND NOT chosen the same spatial option on trial t	Unrewarded on trial $t-1$
Lose-shift-spatial	Unrewarded on trial $t-1$ AND chose a different spatial option (e.g. the left lever) on trial t	Unrewarded on trial $t-1$ AND NOT chosen a different spatial option on trial t	Rewarded on trial $t-1$
Win-stay-cue	Rewarded on trial $t-1$ AND chose the same cued option on trial t (e.g. chose the lit lever on trials $t-1$ and t; or the unlit lever on trials $t-1$ and t)	Rewarded on trial $t-1$ AND NOT chosen the same cued option on trial t	Unrewarded on trial $t-1$
Lose-shift-cue	Unrewarded on trial $t-1$ AND chose a different cued option on trial t from the choice on trial t (e.g. chose the lit lever on trial $t-1$ and the unlit lever on trial t; or the unlit lever on trial $t-1$ and the lit lever on trial t)	Unrewarded on trial $t-1$ AND NOT chosen a different cued option on trial t	Rewarded on trial $t-1$
Alternate	Chose another spatial option compared to the previous trial	Chose the same spatial option as the previous trial	n/a
Sticky	Chose the same spatial option as the previous trial	Chose another spatial option compared to the previous trial	n/a

Table 3. Exploratory strategy models for the non-human primate stimulus-to-action task. Columns give the conditions to define trial t as a success, failure, or null for each exploratory strategy.

	Success	Failure	Null
Repeat-Large-Reward	Obtained the large reward on trial $t-1$ AND chose the same option on trial t	Obtained the large reward on trial $t-1$ AND NOT chosen the same option on trial t	Obtained the small reward on trial $t-1$
Repeat-High-Prob	Chose the higher probability of large reward option on trial $t-1$ AND chose the same option on trial t	Chose the higher probability of large reward option on trial $t-1$ AND NOT chosen the same option on trial t	Chose the lower probability of large reward option on trial $t-1$
Switch-After-Small-Reward	Obtained the small reward on trial $t-1$ AND NOT chosen the same option on trial t	Obtained the small reward on trial $t-1$ AND chosen the same option on trial t	Obtained the large reward on trial $t-1$
Switch-To-High-Prob	Chose the lower probability of large reward option on trial $t-1$ AND NOT chosen the same option on trial t	Chose the lower probability of large reward option on trial $t-1$ AND chose the same option on trial t	Chose the higher probability of large reward option on trial $t-1$.

781 models we used for this task.

Interpreting the posterior distributions

The full posterior distribution $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ is a Beta distribution with parameters
$\alpha_i(t), \beta_i(t)$. In this paper we extract two scalar estimates from that posterior distribution in order to
visualise changes in strategies and compare strategies.

First, the best point estimate of probability of $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ is its mode, also called
its *maximum a posteriori* (MAP) value. We find the MAP value by numerically evaluating the Beta
distribution's probability density function, and finding the value of p that corresponds to the peak
of the density function.

Second, as a summary of evidence for that MAP probability estimate we compute the precision
of the posterior distribution, which is the inverse of the variance of the Beta distribution:

$$\text{Precision} = \left(\frac{\alpha\beta}{(\alpha + \beta)^2(\alpha + \beta + 1)} \right)^{-1}. \tag{2}$$

Learning criteria
We tested three different criteria for defining learning based on the posterior distribution of $P(\text{strategy}_i(t)|\text{choi}$
$t)$) for the target rule.

1. Sequence criterion the first trial at which the MAP probability estimate for the target-rule's
strategy remained above chance until the end of the session. If the first trial of a session
met this criterion, so all trials were above chance, we chose the trial with the minimum MAP
probability estimate, to identify the trial at which the strategy probability increased thereafter.

2. Sequence and precision criteria an extension of the sequence criterion to account for the ev-
idence for each strategy: the trial at which both the MAP probability estimate for the target-
rule's strategy remained above chance until the end of the session and the precision of the
target-rule's strategy was greater than for all strategies for the other tested rules.

804 **3. Expert criteria** the first trial at which the probability that the posterior distribution $P(\text{strategy}_i(t)|\text{choices}(1:$
805 $t))$ contained chance fell below some threshold θ, and remained so until the end of the ses-
806 sion. We use $\theta = 0.05$ here.

Performance simulations

807

Synthetic agent on a 2AFC task

808

809 To illustrate the Bayesian algorithm, we generated synthetic data that simulated an agent working
810 on a two-alternative forced-choice task, described in *Figure 2*. The task structure was similar to
811 the tasks described in Figures 1 and 3. The agent could choose between two options (e.g. a right
812 or left lever), and a random cue was alternated between the two options. A reward was delivered
813 only when the agent's choice matched the cue. We generated 500 trials divided into blocks of 100
814 trials, in which the agent's choice followed a specific strategy ('Go right', 'Alternate','Lose-Shift-Cued',
815 'Go cued' and 'Lose-Shift-Choice'). We first defined the vector of cue locations as a random binary
816 vector with p=0.5; then we defined the vector of choices. For 'Go right' and 'Alternate' the agent's
817 choice was consistently right or alternating, respectively. For 'Lose-Shift' strategies, we generated
818 a random vector of binary choices; then, for every trial t corresponding to a loss (i.e. not matching
819 the cue), we changed the choice in trial $t+1$ in order to match the cue ('Lose-Shift-Cued') or choice
820 location ('Lose-Shift-Choice'). The 'Go cued' block consisted of choices matching the cue location.
821 To select the most likely strategy being executed at trial t, we chose strategy i with the highest
822 MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ resolving ties by choosing the strategy with the maxi-
823 mum precision.

Switching simulations

824

To explore the performance of the Bayesian algorithm, we ran extensive simulations of the algo-
rithm detecting the switch between two arbitrary strategies. The general model for the switch
between the two strategies generated a time-series of the success ($x_i(t) = 1$) or failure ($x_i(t) = 0$)
to execute strategy $i \in \{1, 2\}$ on each trial. Strategy 1 was executed on trials 1 to T with proba-
bility $p_1 = a$, and strategy 2 was executed on trials 1 to T with probability $p_2 = b$. From trial T the
probabilities then reversed linearly:

$$p_1 = \begin{cases} a - m \times j & \text{if } j < (a-b)/m \\ b & \text{otherwise} \end{cases}$$

$$p_2 = \begin{cases} b + m \times j & \text{if } j < (a-b)/m \\ a & \text{otherwise} \end{cases}$$

825 where j is the number of trials elapsed since T, and m is the rate of change in probability per trial.
826 *Figure 2*g illustrates the model for the case of $a = 1$ and $b = 0$. Note that the probabilities crossover
827 at $j = (a-b)/2m$; we use this in our definitions of detecting the switch below. From this general
828 model we could explore qualitatively different types of strategy switch: whether the switch was
829 abrupt (m is infinity) or gradual ($m < a - b$).
830 Given some choice of $\{a,b,T,m\}$, we generated the time-series of x_1 and x_2 for strategies 1 and 2.
831 On every trial t we applied our algorithm to update the two posterior distributions for strategies 1
832 and 2, and their corresponding MAP estimates $\hat{p}(\text{strategy}_1)$ and $\hat{p}(\text{strategy}_2)$. We defined the detection
833 of the switch as the first trial for which $\hat{p}(\text{strategy}_2) \geq \hat{p}(\text{strategy}_1)$. For abrupt-switching models this
834 was counted from trial T; for gradual-switching models this was counted from the "crossover" trial
835 at which p_2 first exceeded p_1. Stability of detection was defined as the proportion of the next w
836 trials for which this detection criterion remained true; results are presented for $w = 50$.
837 As shown in *Figure 2*f, using $\gamma < 1$ causes the detection time to plateau with increasing T, be-
838 cause evidence decay means past history has no effect on detection time. For further simulations
839 (*Figure 2–Figure Supplement 2*) we thus fixed $T = 500$, to get worst-case performance for detection.

For the detection of a new conditional strategy, we defined a probability per trial $p(\text{condition met}) \in$
$(0, 1]$ that its condition would be met and simulated a model where its probability of execution
$p_{\text{new}}(t)$ increased linearly from 0 to 1 at a rate of m per trial. We then created time-series of $x_{\text{new}}(t)$,
by first checking if its condition was met, setting $x_{\text{new}}(t) = \text{null}$ if not; if it was met, we then checked
if the strategy was executed ($x_{\text{new}}(t) = 1$) or not ($x_{\text{new}}(t) = 0$). We used our algorithm to find the
corresponding MAP estimate $\hat{p}(\text{strategy}_{\text{new}})$ from the time-series, and defined detection as the MAP
estimate being greater than 0.5. Results are plotted in *Figure 2–Figure Supplement 4*.

Effects of missing the true exploratory strategy

A set of tested exploratory strategies may not contain the true exploratory strategy or strategies
used by a subject. To examine how the algorithm performs in this case, we determined the propor-
tion of trials on which a given tested strategy would be expected to make the same choice as a true
strategy. Formally, this is the conditional probability $p(x_{\text{test}} = 1|\text{true strategy})$ that the tested strategy
is a success on any trial given that the true strategy is being used, which we call $p(\text{match})$ in the
main text. The algorithm's MAP probability for the tested strategy is an estimate of this conditional
probability.

To compute $p(x_{\text{test}} = 1|\text{true strategy})$, we decomposed this conditional probability into two main
terms, one for trials where the true strategy can be executed, and one for trials where it cannot:

$$p(x_{\text{test}} = 1|\text{true strategy}) = p(x_{\text{test}} = 1|x_{\text{true}} = 1)p(x_{\text{true}} = 1) + p(x_{\text{test}} = 1|x_{\text{true}} = \text{null})p(x_{\text{true}} = \text{null}), \quad (3)$$

with $p(x_{\text{true}} = 1) + p(x_{\text{true}} = \text{null}) = 1$. To understand what happens if the true strategy is missing,
we enumerated the possible values of Equation 3 for four cases: both true and tested strategies
were unconditional; one was unconditional and the other conditional (giving two cases); and both
were conditional. We explain the enumerations for these cases below, and plot the results in *Fig-*
ure 2–Figure Supplement 5.

We first considered the case where the true and tested exploratory strategies were uncondi-
tional. In this case $p(x_{\text{true}} = 1) = 1$, and so we needed only to consider the possible values of
$p(x_{\text{test}} = 1|x_{\text{true}} = 1)$. For a task with n choices these are $\{0, 1/n, 1 - 1/n, 1\}$: 0, if the tested and true
strategy are mutually exclusive (e.g. one repeats the previous choice and one makes a different
choice to the previous one); $1/n$, if the true and tested strategy make a single choice; $1 - 1/n$ if the
true and tested strategy make anything other than a single choice (e.g. the shift to any other choice
than the previous one); 1, if the tested and true strategy are equivalent. The latter implies the true
strategy is not missing, so we omitted it; consequently, for the case where both true and test strate-
gies are unconditional, Equation 3 gives just three solutions $p(x_{\text{test}} = 1|\text{true strategy}) = \{0, 1/n, 1-1/n\}$;
we plot these three solution as a cumulative distribution in *Figure 2–Figure Supplement 5*, panel a.
The maximum MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ is thus $1 - 1/n$ for this case.

For the case where the true strategy is unconditional and the tested strategy is conditional, we
first decomposed the probability $p(x_{\text{test}} = 1|x_{\text{true}} = 1)$ into a the probability that the condition for the
test strategy is met $p(\text{test condition met})$ and the probability that the test strategy's choice, if made,
matches the true strategy $p(\text{test match true}|\text{condition met})$:

$$p(x_{\text{test}} = 1|x_{\text{true}} = 1) = p(\text{test match true | condition met})p(\text{test condition met}). \quad (4)$$

To evaluate Equation 3 using Equation 4, we tested $p(\text{test condition met}) \in [0.1, 1)$, and used $p(\text{test match true | con}$
$\{0, 1/n, 1 - 1/n, 1\}$ as argued for the unconditional case, above. We then evaluated Equation 3 for
all combinations of these values in Equation 4, and plot the full set of enumerated probabilities in
Figure 2–Figure Supplement 5 panel b, as a cumulative distribution, omitting the case where the
tested and true strategies were entirely equivalent (i.e. $p(x_{\text{test}} = 1|x_{\text{true}} = 1) = 1$). Note that we al-
lowed the possibility of the tested strategy being logically equivalent to the true strategy when the
tested strategy's condition was met, by including $p(\text{test match true| condition met}) = 1$; if we do not al-
low this possibility, we get the set of enumerated probabilities plotted in purple in *Figure 2–Figure*
Supplement 5, panel b.

For the case where the true strategy is conditional and the tested strategy is unconditional, we set $p(\text{true} = 1) \in [0.1, 1)$ to model the frequency at which the true strategy's condition was met. We noted that $p(x_{\text{test}} = 1 | x_{\text{true}} = 1)$ and $p(x_{\text{test}} = 1 | x_{\text{true}} = \text{null})$ were independent and can each take any value in $\{0, 1/n, 1 - 1/n, 1\}$, except both could not be equal to 1 as this would mean the tested and true strategy were logically equivalent. We then evaluated Equation 3 using all combinations of these values for $p(\text{true} = 1)$, $p(x_{\text{test}} = 1 | x_{\text{true}} = 1)$, and $p(x_{\text{test}} = 1 | x_{\text{true}} = \text{null})$, and plot the enumerated probabilities in *Figure 2–Figure Supplement 5*, panel d.

For the case where both the tested and true strategy are conditional, we again used Equation 4 to model the conditional test strategy. We then evaluated Equation 3 using all combinations of values for $p(\text{true} = 1)$ and $p(x_{\text{test}} = 1 | x_{\text{true}} = \text{null})$ specified in the preceding paragraph, and for $p(x_{\text{test}} = 1 | x_{\text{true}} = 1)$ specified under Equation 4. The resulting enumerated probabilities are plotted in *Figure 2–Figure Supplement 5*, panel e.

In reality we only get to specify the type of test strategy and do not know the type (conditional or unconditional) of true strategy adopted by the subject. Thus, to put bounds on what we can infer from the observed MAP probabilities for a given type of test strategy, we combined the enumerated probabilities for the unconditional and conditional true strategies. The resulting distributions are plotted in the last column of *Figure 2–Figure Supplement 5*, and from these we derive the three bounds discussed in the main text.

Derivation of the iterative update and evidence decay

We first rehearse the standard Bayesian approach to estimating a binomial probability p as a random variable when that probability is stationary. We then introduce the decay of evidence to track non-stationary probabilities, and obtain the iterative update rules given in the main text.

Our data are a sequence of Bernoulli trials $\tau = 1, 2, \ldots t$, each of which is either a success $x(\tau) = 1$ or a failure $x(\tau) = 0$ of an event. A running total of the successful events is $s(t) = \sum_{\tau=1}^{t} x(\tau)$. The posterior distribution $\pi(p|s)$ for estimating the probability of that number of successful events is then given by Bayes theorem

$$\pi(p|s) = \frac{P(s|p)\pi(p)}{\int_0^1 P(s|p)\pi(p)dp}, \tag{5}$$

where the denominator is the normalisation constant to obtain a probability distribution function. (Note we write $\pi(p|s)$ as $P(\text{strategy}_i | \text{choices}(1:t))$ in the main text when applied to our specific problem of estimating the probability of strategy i).

As noted in the main text, the likelihood $P(s|p)$ is the binomial distribution and we chose the prior $\pi(p)$ to be the Beta distribution with parameters α, β. Using those in Equation (5) gives

$$\pi(p|s) = \frac{1}{Z} \underbrace{\left[\binom{t}{s} p^s (1-p)^{t-s} \right]}_{\text{likelihood}} \underbrace{\left[\frac{\Gamma(\alpha+\beta)}{\Gamma(\alpha)\Gamma(\beta)} p^{\alpha-1}(1-p)^{\beta-1} \right]}_{\text{prior}}, \tag{6}$$

where Γ is the gamma function and Z is the denominator in Equation 5.

The solution of Equation (6) is another Beta distribution:

$$\pi(p|s) = \frac{\Gamma(\alpha+\beta)}{\Gamma(\alpha)\Gamma(\beta)} p^{\alpha+s-1}(1-p)^{\beta+t-s-1} \tag{7}$$

which is equivalent to simply updating the Beta distribution parameters as $(\alpha(0) + s, \beta(0) + t - s)$ given some starting values of $\alpha(0), \beta(0)$, which define the prior distribution.

Rather than updating after t trials have elapsed, we can instead update every trial by using the posterior of the previous trial $\pi(p|s(t-1))$ as the prior for the update on the current trial t. To see this, we can rewrite Equation (5) to update on every trial t by substituting the Bernoulli distribution $p^x(1-p)^{(1-x)}$ for the binomial distribution, and obtain the iterative equivalent of Equation (7):

$$\pi(p|s(t)) = Bp^{\alpha(t-1)+x-1}(1-p)^{\beta(t-1)-x}, \tag{8}$$

where B is the constant $\frac{\Gamma(\alpha(t-1)+\beta(t-1))}{\Gamma(\alpha(t-1))\Gamma(\beta(t-1))}$.

Equation (8) is equivalent to updating the parameters of the Beta distribution on every trial t as $(\alpha(t-1)+x(t), \beta(t-1)+(1-x(t)))$, given some prior values for $\alpha(0), \beta(0)$:

$$
\begin{aligned}
\text{Trial 1} \quad &\alpha(1) = \alpha(0) + x(1), \quad &\beta(1) = \beta(0) + (1 - x(1)) \\
\text{Trial 2} \quad &\alpha(2) = \alpha(1) + x(2), \quad &\beta(2) = \beta(1) + (1 - x(2)) \\
&\quad\vdots &\vdots \\
\text{Trial } t \quad &\alpha(t) = \alpha(t-1) + x(t), \quad &\beta(t) = \beta(t-1) + (1 - x(t)).
\end{aligned}
\tag{9}
$$

It is this iterative form that allows computationally efficient real-time updates of the probability of each strategy.

We now turn to our solution to the problem that p is not stationary when estimating the use of strategies. Our idea is to decay the evidence entering the posterior update in Equation (5). Consider the following models for the exponential decay of the Bernoulli trial outcomes up to trial t, for the successes

$$
s^*(t) = \sum_{\tau=1}^{t} \gamma^{t-\tau} x(\tau),
\tag{10}
$$

and the failures

$$
f^*(t) = \sum_{\tau=1}^{t} \gamma^{t-\tau} (1 - x(\tau)),
\tag{11}
$$

where $\gamma \in (0, 1]$ is the rate of evidence decay.

We can substitute s^* for s and f^* for $t - s$ in Equation (6) and obtain the posterior distribution

$$
\pi(p|s^*(t), f^*(t)) = B p^{\alpha+s^*(t)-1}(1 - p)^{\beta+f^*(t)-1},
\tag{12}
$$

for the estimate of p on trial t given the decayed evidence up to that trial. Again, this is equivalent to updating the Beta distribution parameters as $(\alpha(0) + s^*(t), \beta(0) + f^*(t))$.

To obtain the trial-by-trial update equivalent to Equation (12), we note that the iterative forms of Equations (10) and (11) are

$$
\begin{aligned}
s^*(t) &= \gamma s^*(t-1) + x(t), \\
f^*(t) &= \gamma f^*(t-1) + (1 - x(t)),
\end{aligned}
\tag{13}
$$

starting from $s^*(0) = f^*(0) = 0$.

With these the update of the Beta distribution parameters on trial t becomes

$$
\begin{aligned}
\alpha(t) &= \alpha(0) + \gamma s^*(t-1) + x(t) \\
\beta(t) &= \beta(0) + \gamma f^*(t-1) + (1 - x(t)).
\end{aligned}
\tag{14}
$$

Together, Equations (13) and Equations (14) form the algorithm we use here.

Limits on the posterior distribution

Any operation altering the evidence entering the likelihood function in Equation 6 could limit the changes to the resulting posterior distribution compared to the standard Bayesian update. Our decay models (Equations (10) and (11)) have the advantage that we can define these limits exactly.

Equations (10) and (11) are geometric series with asymptotic limits for the total successes $s^*(t)$ and failures $f^*(t)$. They thus also set asymptotic limits for α and β (Equation (12). For a long run of successes where $x(t) = 1$ as $t \to \infty$ these are

$$
\alpha \to \alpha(0) + \frac{1}{1 - \gamma}, \quad \beta \to \beta(0).
\tag{15}
$$

Similarly, for a long run of failures where $x(t) = 0$ as $t \to \infty$ these are

$$
\alpha \to \alpha(0), \quad \beta \to \beta(0) + \frac{1}{1 - \gamma}.
\tag{16}
$$

Consequently, setting the decay parameter $\gamma < 1$ creates asymptotic limits for the values of α and β that could limit how much the posterior $P(\text{strategy}_i|\text{choices}(1 : t))$ changes from the prior.

We checked the potential limits on the posterior by calculating it at the asymptotic values of α and β for long-run successes (Equation (15)) across the full range of $\gamma \in (0, 1]$. We then calculated the MAP, precision, and the proportion of the posterior that exceeds chance for two options (i.e. $p = 0.5$). These showed that while the asymptotic limits do not affect the MAP estimate of $P(\text{strategy}_i|\text{choices}(1 : t))$, as expected, they do limit how concentrated the posterior becomes around that MAP estimate, which we plot in Figure 2.

References

Akrami A, Kopec CD, Diamond ME, Brody CD. Posterior parietal cortex represents sensory history and mediates its effects on behaviour. Nature. 2018 Feb; 554:368–372. doi: 10.1038/nature25510.

Amarante LM, Caetano MS, Laubach M. Medial Frontal Theta Is Entrained to Rewarded Actions. J Neurosci. 2017 Nov; 37:10757–10769. doi: 10.1523/JNEUROSCI.1965-17.2017.

Ashwood ZC, Roy NA, Stone IR, Laboratory IB, Urai AE, Churchland AK, Pouget A, Pillow JW. Mice alternate between discrete strategies during perceptual decision-making. Nat Neurosci. 2022 Feb; 25:201–212. doi: 10.1038/s41593-021-01007-z.

Axelrod R, Dion D. The further evolution of cooperation. Science (New York, NY). 1988 Dec; 242:1385–1390. doi: 10.1126/science.242.4884.1385.

Axelrod R, Hamilton WD. The evolution of cooperation. Science (New York, NY). 1981 Mar; 211:1390–1396. doi: 10.1126/science.7466396.

Banerjee A, Parente G, Teutsch J, Lewis C, Voigt FF, Helmchen F. Value-guided remapping of sensory cortex by lateral orbitofrontal cortex. Nature. 2020 Sep; 585:245–250. doi: 10.1038/s41586-020-2704-z.

Bartolo R, Averbeck BB. Prefrontal Cortex Predicts State Switches during Reversal Learning. Neuron. 2020 Jun; 106:1044–1054.e4. doi: 10.1016/j.neuron.2020.03.024.

Behrens TEJ, Woolrich MW, Walton ME, Rushworth MFS. Learning the value of information in an uncertain world. Nat Neurosci. 2007 Sep; 10:1214–1221. doi: 10.1038/nn1954.

Birrell JM, Brown VJ. Medial frontal cortex mediates perceptual attentional set shifting in the rat. J Neurosci. 2000 Jun; 20:4320–4324.

Boulougouris V, Dalley JW, Robbins TW. Effects of orbitofrontal, infralimbic and prelimbic cortical lesions on serial spatial reversal learning in the rat. Behavioural brain research. 2007 May; 179:219–228. doi: 10.1016/j.bbr.2007.02.005.

Brady AM, Floresco SB. Operant procedures for assessing behavioral flexibility in rats. Journal of visualized experiments : JoVE. 2015 Feb; p. e52387. doi: 10.3791/52387.

Britten KH, Shadlen MN, Newsome WT, Movshon JA. The analysis of visual motion: a comparison of neuronal and psychophysical performance. J Neurosci. 1992; 12(12):4745–4765.

Buckley MJ, Mansouri FA, Hoda H, Mahboubi M, Browning PGF, Kwok SC, Phillips A, Tanaka K. Dissociable components of rule-guided behavior depend on distinct medial and prefrontal regions. Science. 2009 Jul; 325:52–58. doi: 10.1126/science.1172377.

Campagner D, Evans MH, Chlebikova K, Colins-Rodriguez A, Loft MSE, Fox S, Pettifer D, Humphries MD, Svoboda K, Petersen RS. Prediction of Choice from Competing Mechanosensory and Choice-Memory Cues during Active Tactile Decision Making. J Neurosci. 2019 May; 39:3921–3933. doi: 10.1523/JNEUROSCI.2217-18.2019.

Carandini M, Churchland AK. Probing perceptual decisions in rodents. Nature neuroscience. 2013 Jul; 16:824–831. doi: 10.1038/nn.3410.

Churchland AK, Kiani R, Shadlen MN. Decision-making with multiple alternatives. Nature neuroscience. 2008 Jun; 11:693–702. doi: 10.1038/nn.2123.

Cinotti F, Humphries MD. Bayesian Mapping of the Striatal Microcircuit Reveals Robust Asymmetries in the Probabilities and Distances of Connections. J Neurosci. 2022 Feb; 42:1417–1435. doi: 10.1523/JNEUROSCI.1487-21.2021.

Constantinople CM, Piet AT, Bibawi P, Akrami A, Kopec C, Brody CD. Lateral orbitofrontal cortex promotes trial-by-trial learning of risky, but not spatial, biases. eLife. 2019 Nov; 8. doi: 10.7554/eLife.49744.

Donoso M, Collins AGE, Koechlin E. Foundations of human reasoning in the prefrontal cortex. Science. 2014 Jun; 344:1481–1486. doi: 10.1126/science.1252254.

Durstewitz D, Vittoz NM, Floresco SB, Seamans JK. Abrupt transitions between prefrontal neural ensemble states accompany behavioral transitions during rule learning. Neuron. 2010 May; 66:438–448. doi: 10.1016/j.neuron.2010.03.029.

Fiser J, Berkes P, Orbán G, Lengyel M. Statistically optimal perception and learning: from behavior to neural representations. Trends Cogn Sci. 2010 Mar; 14(3):119–130. http://dx.doi.org/10.1016/j.tics.2010.01.003, doi: 10.1016/j.tics.2010.01.003.

Floresco SB, Block AE, Tse MTL. Inactivation of the medial prefrontal cortex of the rat impairs strategy set-shifting, but not reversal learning, using a novel, automated procedure. Behav Brain Res. 2008 Jun; 190:85–96. doi: 10.1016/j.bbr.2008.02.008.

Gallistel CR, Fairhurst S, Balsam P. The learning curve: implications of a quantitative analysis. Proc Natl Acad Sci U S A. 2004 Sep; 101(36):13124–13131. http://dx.doi.org/10.1073/pnas.0404965101, doi: 10.1073/pnas.0404965101.

Genovesio A, Brasted PJ, Mitz AR, Wise SP. Prefrontal cortex activity related to abstract response strategies. Neuron. 2005 Jul; 47:307–320. doi: 10.1016/j.neuron.2005.06.006.

Giurfa M, Sandoz JC. Invertebrate learning and memory: Fifty years of olfactory conditioning of the proboscis extension response in honeybees. Learning & Memory. 2012 Feb; 19:54–66. doi: 10.1101/lm.024711.111.

Guise KG, Shapiro ML. Medial Prefrontal Cortex Reduces Memory Interference by Modifying Hippocampal Encoding. Neuron. 2017 Apr; 94:183–192.e8. doi: 10.1016/j.neuron.2017.03.011.

Hanks TD, Summerfield C. Perceptual Decision Making in Rodents, Monkeys, and Humans. Neuron. 2017; 93:15–31. doi: 10.1016/j.neuron.2016.12.003.

Harris C, Aguirre C, Kolli S, Das K, Izquierdo A, Soltani A. Unique features of stimulus-based probabilistic reversal learning. Behavioral neuroscience. 2021 Aug; 135:550–570. doi: 10.1037/bne0000474.

Honegger K, de Bivort B. Stochasticity, individuality and behavior. Curr Biol. 2018 Jan; 28:R8–R12. doi: 10.1016/j.cub.2017.11.058.

International Brain Laboratory, Aguillon-Rodriguez V, Angelaki D, Bayer H, Bonacchi N, Carandini M, Cazettes F, Chapuis G, Churchland AK, Dan Y, Dewitt E, Faulkner M, Forrest H, Haetzel L, Häusser M, Hofer SB, Hu F, Khanal A, Krasniak C, Laranjeira I, et al. Standardized and reproducible measurement of decision-making in mice. eLife. 2021 May; 10. doi: 10.7554/eLife.63711.

Ito HT, Zhang SJ, Witter MP, Moser EI, Moser MB. A prefrontal-thalamo-hippocampal circuit for goal-directed spatial navigation. Nature. 2015 Jun; 522:50–55. doi: 10.1038/nature14396.

Izquierdo A, Brigman JL, Radke AK, Rudebeck PH, Holmes A. The neural basis of reversal learning: An updated perspective. Neuroscience. 2017 Mar; 345:12–26. doi: 10.1016/j.neuroscience.2016.03.021.

Jang AI, Costa VD, Rudebeck PH, Chudasama Y, Murray EA, Averbeck BB. The Role of Frontal Cortical and Medial-Temporal Lobe Brain Areas in Learning a Bayesian Prior Belief on Reversals. J Neurosci. 2015 Aug; 35:11751–11760. doi: 10.1523/JNEUROSCI.1594-15.2015.

Juavinett AL, Erlich JC, Churchland AK. Decision-making behaviors: weighing ethology, complexity, and sensorimotor compatibility. Curr Opin Neurobiol. 2017 Nov; 49:42–50. doi: 10.1016/j.conb.2017.11.001.

Karlsson MP, Tervo DGR, Karpova AY. Network resets in medial prefrontal cortex mark the onset of behavioral uncertainty. Science. 2012 Oct; 338:135–139. doi: 10.1126/science.1226518.

Kim JN, Shadlen MN. Neural correlates of a decision in the dorsolateral prefrontal cortex of the macaque. Nature Neuroscience. 1999 feb; 2(2):176–185. doi: 10.1038/5739.

Knill DC, Pouget A. The Bayesian brain: the role of uncertainty in neural coding and computation. Trends Neurosci. 2004 Dec; 27(12):712–719. http://dx.doi.org/10.1016/j.tins.2004.10.007, doi: 10.1016/j.tins.2004.10.007.

Krakauer JW, Ghazanfar AA, Gomez-Marin A, MacIver MA, Poeppel D. Neuroscience Needs Behavior: Correcting a Reductionist Bias. Neuron. 2017 Feb; 93:480–490. doi: 10.1016/j.neuron.2016.12.041.

Lau B, Glimcher PW. Dynamic response-by-response models of matching behavior in rhesus monkeys. Journal of the experimental analysis of behavior. 2005 Nov; 84:555–579. doi: 10.1901/jeab.2005.110-04.

Leeson VC, Robbins TW, Matheson E, Hutton SB, Ron MA, Barnes TRE, Joyce EM. Discrimination learning, reversal, and set-shifting in first-episode schizophrenia: stability over six years and specific associations with medication type and disorganization syndrome. Biol Psychiatry. 2009 Sep; 66:586–593. doi: 10.1016/j.biopsych.2009.05.016.

Mackintosh NJ. Further analysis of the overtraining reversal effect. Journal of Comparative and Physiological Psychology. 1969 Feb; 67(2, Pt.2):1–18. doi: 10.1037/h0026784.

Mansouri FA, Freedman DJ, Buckley MJ. Emergence of abstract rules in the primate brain. Nat Rev Neurosci. 2020 Nov; 21:595–610. doi: 10.1038/s41583-020-0364-5.

Miller KJ, Botvinick MM, Brody CD. Dorsal hippocampus contributes to model-based planning. Nature neuroscience. 2017 Sep; 20:1269–1276. doi: 10.1038/nn.4613.

Nowak M, Sigmund K. A strategy of win-stay, lose-shift that outperforms tit-for-tat in the Prisoner's Dilemma game. Nature. 1993 Jul; 364:56–58. doi: 10.1038/364056a0.

Ohtsuki H, Hauert C, Lieberman E, Nowak MA. A simple rule for the evolution of cooperation on graphs and social networks. Nature. 2006 May; 441:502–505. doi: 10.1038/nature04605.

Packard MG, McGaugh JL. Inactivation of hippocampus or caudate nucleus with lidocaine differentially affects expression of place and response learning. Neurobiology of learning and memory. 1996 Jan; 65:65–72. doi: 10.1006/nlme.1996.0007.

Palmer J, Huk AC, Shadlen MN. The effect of stimulus strength on the speed and accuracy of a perceptual decision. J Vis. 2005; 5(5):376–404.

Pereira TD, Shaevitz JW, Murthy M. Quantifying behavior to understand the brain. Nature Neurosci. 2020; 23:1537–1549. doi: 10.1038/s41593-020-00734-z.

Pessiglione M, Seymour B, Flandin G, Dolan RJ, Frith CD. Dopamine-dependent prediction errors underpin reward-seeking behaviour in humans. Nature. 2006; 442:1042–1045. doi: 10.1038/nature05051.

Peyrache A, Khamassi M, Benchenane K, Wiener SI, Battaglia FP. Replay of rule-learning related neural patterns in the prefrontal cortex during sleep. Nature Neuroscience. 2009; 12:919–926.

Pezze M, McGarrity S, Mason R, Fone KC, Bast T. Too little and too much: hypoactivation and disinhibition of medial prefrontal cortex cause attentional deficits. J Neurosci. 2014 Jun; 34:7931–7946. doi: 10.1523/JNEUROSCI.3450-13.2014.

Pouget A, Beck JM, Ma WJ, Latham PE. Probabilistic brains: knowns and unknowns. Nat Neurosci. 2013 Sep; 16(9):1170–1178. http://dx.doi.org/10.1038/nn.3495, doi: 10.1038/nn.3495.

Powell NJ, Redish AD. Representational changes of latent strategies in rat medial prefrontal cortex precede changes in behaviour. Nature communications. 2016 Sep; 7:12830. doi: 10.1038/ncomms12830.

Raposo D, Sheppard JP, Schrater PR, Churchland AK. Multisensory decision-making in rats and humans. J Neurosci. 2012 Mar; 32:3726–3735. doi: 10.1523/JNEUROSCI.4998-11.2012.

Rich EL, Shapiro M. Rat prefrontal cortical neurons selectively code strategy switches. J Neurosci. 2009 Jun; 29(22):7208–7219. http://dx.doi.org/10.1523/JNEUROSCI.6068-08.2009, doi: 10.1523/JNEUROSCI.6068-08.2009.

Rich EL, Shapiro ML. Prelimbic/infralimbic inactivation impairs memory for multiple task switches, but not flexible selection of familiar tasks. J Neurosci. 2007 Apr; 27(17):4747–4755. http://dx.doi.org/10.1523/JNEUROSCI.0369-07.2007, doi: 10.1523/JNEUROSCI.0369-07.2007.

Roy NA, Bak JH, Laboratory IB, Akrami A, Brody CD, Pillow JW. Extracting the dynamics of behavior in sensory decision-making experiments. Neuron. 2021 Feb; 109:597–610.e6. doi: 10.1016/j.neuron.2020.12.004.

Rudebeck PH, Behrens TE, Kennerley SW, Baxter MG, Buckley MJ, Walton ME, Rushworth MFS. Frontal cortex subregions play distinct roles in choices between actions and stimuli. J Neurosci. 2008 Dec; 28:13775–13785. doi: 10.1523/JNEUROSCI.3541-08.2008.

Russo E, Ma T, Spanagel R, Durstewitz D, Toutounji H, Köhr G. Coordinated Prefrontal State Transition Leads Extinction of Reward-Seeking Behaviors. J Neurosci. 2021 Mar; 41:2406–2419. doi: 10.1523/JNEUROSCI.2588-20.2021.

Shiner T, Symmonds M, Guitart-Masip M, Fleming SM, Friston KJ, Dolan RJ. Dopamine, Salience, and Response Set Shifting in Prefrontal Cortex. Cerebral Cortex. 2015 Oct; 25:3629–3639. doi: 10.1093/cercor/bhu210.

Singh A, Peyrache A, Humphries MD. Medial prefrontal cortex population activity is plastic irrespective of learning. J Neurosci. 2019; 39:3470–3483. doi: 10.1523/JNEUROSCI.1370-17.2019.

Smith AC, Frank LM, Wirth S, Yanike M, Hu D, Kubota Y, Graybiel AM, Suzuki WA, Brown EN. Dynamic analysis of learning in behavioral experiments. J Neurosci. 2004 Jan; 24(2):447–461. http://dx.doi.org/10.1523/JNEUROSCI.2908-03.2004, doi: 10.1523/JNEUROSCI.2908-03.2004.

Sohn H, Narain D, Meirhaeghe N, Jazayeri M. Bayesian Computation through Cortical Latent Dynamics. Neuron. 2019 Sep; 103:934–947.e5. doi: 10.1016/j.neuron.2019.06.012.

Suzuki WA, Brown EN. Behavioral and neurophysiological analyses of dynamic learning processes. Behavioral and cognitive neuroscience reviews. 2005 Jun; 4:67–95. doi: 10.1177/1534582305280030.

Tait DS, Bowman EM, Neuwirth LS, Brown VJ. Assessment of intradimensional/extradimensional attentional set-shifting in rats. Neuroscience and biobehavioral reviews. 2018 Jun; 89:72–84. doi: 10.1016/j.neubiorev.2018.02.013.

Trepka E, Spitmaan M, Bari BA, Costa VD, Cohen JY, Soltani A. Entropy-based metrics for predicting choice behavior based on local response to reward. Nature communications. 2021 Nov; 12:6567. doi: 10.1038/s41467-021-26784-w.

Wang J, Tait DS, Brown VJ, Bowman EM. Exacerbation of the credit assignment problem in rats with lesions of the medial prefrontal cortex is revealed by Bayesian analysis of behavior in the pre-solution period of learning. Behavioural brain research. 2019 Oct; 372:112037. doi: 10.1016/j.bbr.2019.112037.

van Wingerden M, Vinck M, Lankelma J, Pennartz CMA. Theta-band phase locking of orbitofrontal neurons during reward expectancy. J Neurosci. 2010 May; 30:7078–7087. doi: 10.1523/JNEUROSCI.3860-09.2010.

Wu Z, Kavanova M, Hickman L, Boschin EA, Galeazzi JM, Verhagen L, Ainsworth M, Pedreira C, Buckley MJ. Low-beta repetitive transcranial magnetic stimulation to human dorsolateral prefrontal cortex during object recognition memory sample presentation, at a task-related frequency observed in local field potentials in homologous macaque cortex, impairs subsequent recollection but not familiarity. Eur J Neurosci. 2021 Dec; 54:7918–7945. doi: 10.1111/ejn.15535.

Yin HH, Knowlton BJ. Contributions of striatal subregions to place and response learning. Learn Mem. 2004; 11(4):459–463. http://dx.doi.org/10.1101/lm.81004, doi: 10.1101/lm.81004.

1129

Figure 1–Figure supplement 1. A stationary Bayesian approach fails to track behavioural changes.

(**a**) Same as **Figure 1**b. Example rat performance on the Y-maze task. Each curve show the cumulative distribution of reward (grey), choice (black) and cue location (brown). Vertical grey dashed lines indicate sessions. Colours at the top indicate the target rule.

(**b**) MAP probabilities for three strategies across the 14 sessions for the example animal in panel a, when using Bayesian estimation without evidence decay. Note how the estimated probability of 'go right' remains the highest through both the switches to the 'go cued' and 'go left' rules, despite the animal clearly altering its behaviour, as it required ten consecutive trials (or 11 out of 12) of the correct choice to switch the rule. Horizontal grey dashed line indicates chance level.

Figure 1–Figure supplement 2. Robustness of the Bayesian approach to changes in the initial prior.

(**a**) Example of uniform and Jeffrey's distributions used as the prior probability for the Bayesian algorithm.

(**b**) Similar to **Figure 1**d, MAP probabilities over trials for the example rat in **Figure 1**b. The model is initialized with the Jeffrey's prior.

(**c**) Difference between the MAP probabilities for each strategy when initialized with either the uniform or the Jeffrey's prior.

1130

Figure 2–Figure supplement 1. MAP probabilities for agent strategies across changes in decay rate.

For the synthetic agent performing the five blocks of strategies, each panel plots the MAP values for one strategy, across each trial and each value of the decay rate between 0.5 and 1, in steps of 0.01. Vertical black dashed lines indicate block switches. Horizontal arrows are $\gamma = 0.9$.

Figure 2–Figure supplement 2. Slower evidence decay tracks gradual switches in strategy more accurately and robustly.

(**a**) Model for the gradual switch between two strategies after trial T. The probabilities of executing the two strategies change linearly at some rate m. Trial T is 500 in panels b and c, so that past-history effects have plateaued, giving worst-case performance for detection. Detection of the switch is measured from when the probabilities cross over: when the probability of executing strategy 2 exceeds that of executing strategy 1.

(**b**) Accuracy of tracking gradual strategy switches increases with slower evidence decay. We plot the number of trials after the crossover trial until detection as a function of m, the rate of change in the execution probabilities. Negative values indicate detection before the crossover of probabilities; these false positive detections were due to a chance run of trials using the new strategy 2. Plots show means and SD over 50 repeats; $\gamma = 1$ omitted as detection scales with T when there is no evidence decay.

(**c**) Stability of the detected switch increases with slower evidence decay: the proportion of trials after the detection for which the algorithm reported the new strategy (strategy 2) was dominant. Plots show means and SD over 50 repeats.

Figure 2–Figure supplement 3. Slower evidence decay gives lower variability when tracking stochastic use of a strategy.

(**a**) Estimating the stochastic probability of using a strategy. For three different probabilities of using a strategy ($p(\text{use})$), we plot the mean and standard deviation (S.D.) of the algorithm's MAP estimate of that test strategy, over 50 simulations of 50 trials. Results shown for $\gamma = 0.5$.

(**b**) As for (a), for $\gamma = 0.9$.

(**c**) Variation in the MAP estimates of $p(\text{use})$ decreases with slower rates of evidence decay (higher γ). S.D. taken from trial 50 of 50 simulations similar to those in panels a and b.

Figure 2–Figure supplement 4. Algorithm performance for tracking a new conditional strategy.

Each panel plots the number of trials needed to track $P(\text{strategy}_i(t)|\text{choices}(1 : t))$ above chance (0.5) after the appearance of a new conditional strategy whose condition occurs with probability $p(\text{meet condition})$. The probability of executing the new conditional strategy when its condition is met linearly increases from 0 to 1 with rate m. The right-most panel is the abrupt case ($m = \infty$) where the strategy's probability is immediately 1.

Figure 2–Figure supplement 5. Limits on the probability of the tested strategy matching a true strategy used by an agent during exploration.
(**a**) The cumulative distribution of $p(\text{match})$ between the tested strategy and a true strategy when both are unconditional. For a task with n options $p(\text{match})$ can take one of three values: 0 (tested and true are mutually exclusive); $1/n$ (tested strategy chooses one option); $1 - 1/n$ (the tested strategy chooses any but one option).
(**b**) The distribution of $p(\text{match})$ when the tested strategy is unconditional, but one true strategy is conditional (blue: "All"). We evaluated $p(\text{match})$ using probabilities between 0.1 and 1 that this true strategy's condition is met; and we allowed that the tested strategy could exactly match this true strategy either when the condition is met or when it is not. Not allowing this exact matching gives the distribution in purple, with a maximum at $1 - 1/n$.
(**c**) The full distribution of $p(\text{match})$ for when the tested strategy is unconditional, given by the combination of the relevant distributions in panels (a) and (b). Because we know the type of tested strategy, but not the type of true strategy used by a subject, these distributions place bounds on what we can infer from the MAP probability of a tested unconditional strategy.
(**d**)–(**f**) As for (a)-(c), for when the tested strategy is conditional.
(**g**)–(**l**) As for (a)-(f), for a task with n=3 options. Note the maximum $p(\text{match})$ at $1 - 1/n$ (vertical dashed grey line) when the logical equivalence between tested and true strategies is omitted.

1135

Figure 3–Figure supplement 1. Performance of further learning criteria.
"Criterion" and "Strategy" criteria are those shown in **Figure 3** for classic trial-counting and MAP estimates contiguously above chance, respectively. We compare those here to two more stringent criteria: "Strategy 2": the first trial at which the MAP estimate for the rule strategy is above chance and the precision of the posterior distribution is greater than all others; "Strategy 3": the first trial at which the probability of the posterior distribution $P(\text{strategy}_i(t)|\text{choices}(1:t))$ containing chance fell below some threshold $\theta = 0.05$.

a For the Y-maze task, the MAP estimate of $P(\text{strategy}_i(t)|\text{choices}(1:t))$ for the target-rule strategy around learning defined by the four tested learning criteria. Lines represent means over sessions; shading shows SEM.

b The number of learning trials per animal identified by each criterion.

c As for panel a, for the lever-press task.

d The identified learning trials in the lever press task according to each criterion. The task had equal numbers of animals learn an egocentric or cued lever press rule first, then switched to the other rule; the plots group animals by their experienced rule sequence. A 3-factor ANOVA on criterion, rule-type, and rule-order confirmed a significant effect on learning trials of the choice of learning criterion (F = 8.91, $p < 0.001$); it confirmed that learning trials depended on rule type (F = 297.18, $p < 0.001$) and rule order (F = 270.12, $p < 0.001$); and it confirmed that the sequence of rules affected the speed of learning for all tested criteria, with cued rules taking substantially longer to learn after first learning a spatial rule (the interaction of rule order × rule type, F = 250.05, $p < 0.001$).

Figure 6–Figure supplement 1. Human strategies are robust to priors and do not correlate with bias in preferred target locations.

(**a**) Difference between MAP probability of 'go gain' and 'avoid loss' strategies initialized with uniform prior and Jeffrey's prior for the example participant in **Figure 6**b.

(**b**) MAP probability profiles for 'go gain' and 'avoid loss' strategies along the session during gain and loss trials, respectively. Mean (solid curve) ± SEM (shaded area) across participants (N=20). Horizontal dashed line indicates chance level. These strategies were initialized with Jeffrey's prior.

(**c**) Similar to panel a, the difference between the MAP probability of 'go gain' and 'avoid loss' strategies initialized with uniform and Jeffrey's prior for every participant (one line per participant).

(**d**) The distribution of biased trials during Look trials, defined as the proportion of trials in which the MAP probability for using a direction strategy towards one of the two stimulus locations was consistently above chance. No bias corresponds to 0.5, whereas 1 is when the participant chose the same location on every Look trial. Each dot is a participant. White dot is median and grey bars show the 25^{th} and 75^{th} percentiles.

(**e**) The proportion of trials in which 'go gain' (left panel) and 'avoid loss' (right panel) were the winning strategy for each subject as function of their look bias. Each dot is a participant. r is the Pearson correlation coefficient. Solid line plots the linear fit to the data.