Kmer-Node2Vec: a Fast and Efficient Method for Kmer Embedding from the Kmer Co-occurrence Graph, with Applications to DNA Sequences

Zhaochong Yu, Zihang Yang, Qingyang Lan, Yuchuan Wang, Feijuan Huang, Yuanzhe Cai

Abstract—**Learning low-dimensional continuous vector representation for short k-mers divided from long DNA sequences is key to DNA sequence modeling that can be utilized in many bioinformatics investigations, such as DNA sequence classification and retrieval. DNA2Vec is the most widely used method for DNA sequence embedding. However, it poorly scales to large data sets due to its extremely long training time in kmer embedding. In this paper, we propose a novel efficient graph-based kmer embedding method, named Kmer-Node2Vec, to tackle this concern. Our method converts the large DNA corpus into one kmer co-occurrence graph and extracts kmer relation on the graph by random walks to learn fast and high-quality kmer embedding. Extensive experiments show that our method is faster than DNA2Vec by 29 times for training on a 4GB data set, and on par with DNA2Vec in terms of task-specific accuracy of sequence retrieval and classification.**

I. INTRODUCTION

DNA/RNA sequence embedding technique has been used in many fields, such as pathogen detection [1], species traceability [2], microbiome analysis [3], etc. Recent DNA/RNA sequence embedding works [4], [5] first divide the long DNA sequence into kmer components, applies the skip-gram [6] to gain the kmer embedding for these kmer components, and then aggregates the kmer embedding to present the DNA sequence. Nevertheless, these methods scale poorly to large-scale data sets because they suffer huge time from training the kmer embedding. For example, DNA2Vec [4] needs **4.5 days** to train on 4GB DNA sequence data set. To tackle this concern, we propose a novel approach, Kmer-Node2Vec, which needs 3.7 hours (**29** times faster than DNA2Vec) with the better accuracy on the same data set.

Our idea comes from De Bruijn graph [7] (see Fig. 1(A)), which is applied for the genome assembly. In traditional sequencing algorithms [8] (e.g., Sanger sequencing or Next generation sequencing), reads (3mers) are represented as nodes in a graph, and edges represent alignments between the reads. Walking along a Hamiltonian cycle by following the edges in numerical order allows one to reconstruct the genome by combining alignments between successive reads. De Bruijn graph with applications to genetic sequences indicates that *graph structure* can be applied to represent genetic sequences well. Inspired by De Bruijn graph, we propose **the kmer co-occurrence graph** (see Fig. 1(B)) to

Zhaochong Yu, Zihang Yang, Qingyang Lan, Yuanzhe Cai are with the Department of Big Data and Internet, Shenzhen Technology University, Shenzhen, China.

Feijuan Huang is with Shenzhen Institute of Translational Medicine, Shenzhen Second People's Hospital, Shenzhen, China.

Yuchuan Wang is with North China University of Science and Technology, Tangshan, China.

Fig. 1. De Bruijn Graph vs. the Kmer Co-occurrence Graph. Fig. 1(A) describes De Bruijn graph for gene assembly. In traditional Sanger sequencing algorithms, reads (*3mers*) are represented as nodes in a graph, and edges represent alignments between reads. Travelling along a Hamiltonian cycle by following the edges in numerical order allows one to reconstruct the genome sequence by combining alignments between successive reads. Fig. 1(B) describes the 3mer co-occurrence graph. This 3mer co-occurrence graph is built from the DNA sequence "GAACTTCGAAGTGCCGTGAAGC". An edge is directed from 3mer node *v* to node *x* if they overlap by two continuous nucleotides with node *v*'s suffix being the node *x*'s prefix, i.e., from "GAA" (the red node in genome) to "AAG" (the green node), and "AA" as their overlap. The pair of "GAA" to "AAG" occurs *twice* in the sequence, so that the weight of the graph edge from "GAA" to "AAG" is 2. The dashed line with an arrow describes a path of a random walk with "TGC" as the starting node and "AGC" as the ending node.

describe the genetic sequences. Similar to De Bruijn graph, the kmers in a sequence (*3mers* in Fig. 1(B)) are represented as nodes in a kmer co-occurrence graph, and edges represent kmer co-occurrence relationship (alignments) between nodes, with edge direction as the kmer order. For example, the edge from GAA to AAG denotes that "AA" is the *co-occurrence 2mer* between G**AA** and **AA**G. However, different from De Bruijn graph, the number of co-occurrences of two kmers in the genetic sequence is used as the edge weight, and the kmer frequency in the sequence is used as the node weight, on the kmer co-occurrences graph.

Our method, Kmer-Node2Vec[1], samples kmers by random walk traveling on the kmer co-occurrence graph, and learns kmer embedding from these kmers. First, Kmer-Node2Vec uses kmer co-occurrence information in DNA sequences to construct a kmer co-occurrence graph. Second, it performs fast and efficient random walk traveling on the graph to sample kmer sequences. Third, Skip-Gram [6], a language embedding model, is applied to these sampled kmer sequences to learn the kmer embedding. We argue that training the kmer embedding on a kmer co-occurrence graph is effective and efficient for the following reasons.

(i) Effectiveness. With random travelling on the kmer co-

occurrence graph, our method is able to capture both **local** (in a local sliding window) and **global** (among different sequences) kmer co-occurrence information together, and use this information to embed kmers under the assumption that highly co-occurring kmers should have similar meaning [4].

(ii) Efficiency. Two points motivate the improvement of our method's efficiency. First, DNA2Vec requires a long period to train the kmer embedding, since **its** training corpus of kmers is huge. DNA molecule in the nucleoid of Take an Escherichia coli, whose DNA sequence is 4.7 million bp, as an example. This bacterial genome will be fragmented into 4.7 million kmers in kmer representation, which indicates that even a E coli's data size is equivalent to a 4.7 million words long novel (one kmer corresponds one word in word2vec [6]). That is equal to **four** times of total words in "Gone with the Wind". Second, another interesting observation on DNA sequences is that there are a large number of **same** genetic segments among various species. For example, comprehensive analysis of chimpanzee and human chromosomes reveals average DNA similarity of 70% [9]. Meanwhile, SARS-CoV-2 shares 79% genome sequence identity with SARS-CoV and 50% with MERS-CoV [10]. DNA2Vec wastes too much computation by sliding a window on these same genetic segments. Based on this observation, we emphasize that the kmer co-occurrence graph, which has already captured all the **statistics** of genetic sequences, is a better model to analyze the genetic sequences. The number of nodes in the kmer co-occurrence graph is not large since the maximum number of graph nodes is 4^k (e.g., 8-mer graph contains 4^8 (65536) nodes), and the kmer co-occurrence graph is highly sparse because the maximum edges for each node are four as there are only four kinds of base-pair (A, T, C, G) (e.g., in 8mer co-occurrence graph, the density is no more than 0.01%, $\frac{65536 \times 4}{65536 \times (65536-1)/2}$). Meanwhile, these above-mentioned same DNA segments only change the edge weights of the kmer co-occurrence graph, but the size of nodes and graph density do not have any alteration. Thus, it does not affect the Kmer-Node2Vec's performance.

II. KMER-NODE2VEC ALGORITHM

Fig. 2 clearly shows our Kmer-Node2Vec's framework, which includes constructing the kmer co-occurrence graph, randomly travelling on the graph, learning kmer embedding by Skip-Gram [9], calculating the sequence embedding, and applying sequence embedding for bioinformatics tasks.

1) The Kmer Co-occurrence Graph Construction: We map *numerous* DNA sequences to a kmer co-occurrence graph that corresponds to a weighted directed graph whose nodes represent unique kmers, whose edges represent co-occurrences between kmers with edge direction denoting the order of kmers. To simply illustrate, we use only one DNA sequence to construct the graph. Let a sequence be *GAACTTCGAAGTGCCGTGAAGC* and $k = 3$, the sequence is represented as a series of *3mers = {GAA, AAC, ACT, CTT, TTC, TCG, CGA, GAA, AAG, AGT, GTG, TGC, GCC, CCG, CGT, GTG, TGA, GAA, AAG, AGC}*. Then we take each unique 3mer as a node of the graph. An edge is

drawn between a kmer and its following kmer. Fig. 1(B) corresponds to the graph that we construct.

Weight on edges. The co-occurrence number of two kmers in the sequences is used as their edge weight. A weighted adjacency matrix W is used to store the edge weights, and W_{vx} is the edge weight from node v to node x.

$$W_{vx} = \sum co\text{-}occurrence(v,x) \qquad (1)$$

where $co\text{-}occurrence(v,x)$ is the number of times that the kmer v, x appear together from left to right. For instance, the number of occurrences of $GGA \Rightarrow GAA$ is 2, thus $W_{GGA,GAA}$ is set as 2 (see Fig. 1(B)).

Weight on nodes. The node weight is used to determine the sampling times of random walks. We take probability PW_v to indicate how kmer v *important* is in the DNA corpus, that is, the node weight in the graph. Intuitively, the kmer frequency can be applied to measure the importance score.

$$PW_v = \frac{n_v}{\sum_k n_k} \qquad (2)$$

where PW_v is the important score for kmer v, n_v denotes the occurrence number of the kmer v, and $\sum_k n_k$ represents the occurrence number of all kmers. Taking Fig. 1(B) as an example, **GGA** appears 3 times and the occurrence number of total kmers is 20, therefore $PW_{GGA} = \frac{3}{20} = 0.15$.

2) Kmer Node Sampling: This random walk sampling process [12] iteratively explores the local structure of the kmer co-occurrence graph to estimate the **proximity** between kmer nodes. Generate a random walk from the current node, and select the random neighbors of the current node as a candidate based on the transition probability on the kmer co-occurrence graph. Take a hypothetical case in Fig. 1(B) as an example to explain how we use our sampling strategy to sample a sequence (nodes) from the kmer co-occurrence graph. We select TGC as the starting node to execute a random walk of walk-length 8; the random walk starts from TGC, passes through GCC, CCG, ..., and finally arrives at AGC. The sample of the sequence (nodes) obtained by this random walk is exactly $TGCCGTGAAGC = TGC \rightarrow GCC \rightarrow CCG \rightarrow CGT \rightarrow GTG \rightarrow TGA \rightarrow GAA \rightarrow AAG \rightarrow AGC$. We iterate over all the graph nodes to execute numerous random walks to sample kmer sequences. To *better estimate* the kmer proximity, we carefully design the random walk procedure with the following *three* characteristics.

First, the transition probability is affected by directed edge weights. This forces random walks to preserve the kmer co-occurrence information as much as possible. The probability of traversing from node v to its neighbour node x is W_{vx} (see Eq. 1) divided by the sum of all neighbouring *directed* weights. As shown in Fig. 1, probability to traverse from node **GAA** to node **AAG** is $\frac{1}{1+2}$ (0.66).

Second, each starting node should execute sufficient random walks to obtain a qualified sample for kmer embedding training. A node's number of walks should be in line with its role in the graph, as important nodes should enjoy more random walks than others. We assign each node with a node weight (see Eq. 2) that reflects a node's importance. The

Fig. 2. The overall framework of Kmer-Node2Vec algorithm for kmer embedding. In step 1, Kmer-Node2Vec takes DNA sequences as input and constructs a kmer co-occurrence graph based on them. In step 2, Kmer-Node2Vec uses random walks to extract kmer relation sequences. In step 3, Kmer-Node2Vec feeds these sequences to Skip-Gram [6] and produces a kmer vector for each kmer (kmer embedding). In step 4, these kmer vectors can be used to compute the DNA sequence embedding using AVG, TF-IDF, Doc2Vec [11]. In step 5, we apply the sequence embedding for bioinformatics tasks, such as sequence classification, sequence retrieval and so on.

number of random walks rooted at node v is computed using Eq. 3:

$$number\_walks(v) = \lfloor total\_walks \times PW_v \rfloor \qquad (3)$$

where $total\_walks$ is the total number of random walks set by the user. For example, in Fig. 1(B), let $total\_walk = 200$, $number\_walks(GAA)$ should be $200 \times 0.15 = 30$. That means there are 30 sampled sequences that start from node GAA.

Third, to capture both homophily and structural proximity between kmer nodes of the graph, we employ Node2Vec [12] second-order sampling strategy in Kmer-Node2Vec. In addition, Pecanpy [13], which offers a parallelized and accelerated Node2Vec in python, is applied in our experiments.

3) Training Kmer Embedding with Skip-Gram: We use Skip-Gram to train the kmer embedding on the sampling corpus. The sampling corpus is composed of numerous random walks, which can be thought of kmer node sequences. Skip-Gram maximizes the *co-occurrence probability* among the kmers that appear within a local context in a kmer node sequence. In that way, Skip-Gram will produce very similar vector representations for two kmers if they are *frequently* within a local context of sampled kmer node sequences. With our sampling strategy, there is a **high** likelihood that such two kmers are also *frequently* within a local context in DNA sequences, and thus have similar meaning [4].

4) Theoretical Analysis on Performance: We pay attention to the runtime gap between Kmer-Node2Vec and DNA2Vec. Denoting N as the total corpus size and V as the unique-kmers vocabulary count, DNA2Vec has a high time complexity in training kmer embedding with Skip-Gram, which is $O(Nlog(V))$. N will be very big on genetic data sets (e.g., $N \approx 1.1e9$ on 1GB data set, and $\approx 4.5e9$ on 4GB data set). However, in Kmer-Node2Vec, the training corpus for Skip-Gram is our sampling corpus whose size is nl, where n is the number of random walks and l is the walk length. The time complexity is reduced to $O(nllog(V))$, since nl is smaller than N ($nl \approx 1.9e8$ for both 1GB and 4GB data set). On large-scale data sets, V is the fixed value, and nl is also set by the user so that our method's training time is relative **stable** for various-size data sets.

III. EXPERIMENT

A. Experimental Settings

We use various data sets in our experiments (see Table I), and set kmer size as 8 to train the model.

TABLE I
THE STATISTIC OF DATA SETS

Data set	Total size	Total sequence number	Average sequence length
Fungi	142MB	2,007	71,670 bp
Virus	380MB	13,274	29,563 bp
Bacteria	706MB	28,115	25,858 bp
1G data set	1GB	43,145	26,644 bp
2G data set	2GB	65,614	28,947 bp
3G data set	3GB	95,991	30,599 bp
4G data set	4GB	129,999	34,247 bp

(a) Runtimes   (b) Memory usage

Fig. 3. Runtimes and Memory usage on four data sets (1G-4G). Note that the ordinate scale is arranged in logarithmic base 10.

B. Efficiency of Kmer-Node2Vec algorithm:

Fig. 3(a) and Fig. 3(b) summarize the runtime and memory usage for DNA2Vec [4]. The empirical results show that: (i) Kmer-Node2Vec is much faster than DNA2Vec in training speed on **all** data sets, with the former 27 times faster than the latter, on average; (ii) As training DNA data grows, Kmer-Node2Vec's runtime increases slower than DNA2Vec's, indicating that larger data will see a greater runtime gap between them. For example, from 1G data set to 4G data set, Kmer-Node2Vec's runtime increases slightly from 80min to 230min, whereas DNA2Vec's runtime rises from 1,780min to 6,600min; (iii) Kmer-Node2Vec consumes more memory usage than DNA2Vec, because the kmer co-occurrence graph needs more memory to storage. Fortunately, the memory usage of our method intends to remain unchanged once reaching the peak (10GB), since the size of the kmer co-occurrence graph and sampled sequences can be viewed as constant.

C. Accuracy Evaluation

1) Retrieval Task: This task is to evaluate the accuracy with a baseline approach, **BLAST+** [14]. The DNA sequence

retrieval system using either our method or DNA2Vec is described here: (i) DNA sequences in *three* data sets of Fungi, Virus and Bacteria (see Table I) are split into non-overlapping segments of 150bp, denoted as S_{150bp}; (ii) these segments are transformed to vectors to load into Faiss [15] system. HNSW [16] index is built for vector retrieval in the Faiss system; (iii) given a query sequence, we use its sequence vector (an average of learned kmer vectors) to search in the Faiss to find Top-K segment vectors that are highly similar to the query sequence vector. All parameters for BLAST+ and Faiss in the experiments are adjusted to achieve the best performance.

Specifically, we randomly extract 1,000 DNA segment sequences (15bp-75bp) from S_{150bp} as query sequences and take the corresponding labels as the ground-truth. We feed each query sequence into the retrieval system and Top-K similar DNA sequence segments, denoted as S_K, are returned. Top-K accuracy is used to measure the proportion of the correct label is within the Top-K sequences returned by the retrieval system, denoted as $accuracy(K) = \frac{\sum_{i=1}^{u} |s_i \in S_K|}{u}$, where K denotes the number of query's nearest neighbors to be found, u represents the number of queries, and s_i is the correct segment label as the ground-truth of the query.

Overall, in Fig 4, Top-K accuracy of Faiss is slightly lower than BLAST+, but Faiss takes a much shorter retrieval time than BLAST+. For example, Faiss is about **1.4 times** and **3.3 times** faster than BLAST+ using the minimum data set (Fungi) and the maximum one (Bacteria), respectively. Meanwhile, Kmer-Node2Vec's Top-K accuracy is higher than DNA2Vec's, since our method can capture both local and global co-occurrences between kmers. Because Faiss with Kmer-Node2Vec typically achieves high search accuracy of **99.5%** at the Top-20 level, it is adequate to satisfy the real application.

(a) Fungi accuracy   (b) Virus accuracy

(c) Bacteria accuracy   (d) Retrieval time

Fig. 4. Fig 4(a), (b), (c) compare the sequence retrieval accuracy. Fig 4(d) shows the retrieval time.

2) Classification Task: This task first randomly chooses 18,000 DNA sequences of three species (6,000 for fungi,

virus and bacteria, respectively). We apply either our method or DNA2Vec to calculate the sequence embedding (an average of learned kmer vectors), and build the random forest classifier with the sequence embedding as features to classify these sequences into their corresponding species (fungi, viral, bacteria). Precision, Recall and F1-score [17] computed using 10-fold cross-validation are used to test the performance of classification. Experimental results show that the precision, recall and F1-score for our method and DNA2Vec are (0.942, 0.860, 0.896) and (0.936, 0.849, 0.887), respectively, indicating that our method outperforms DNA2Vec (**1.01%** improvement for F1-score) on the classification task.

REFERENCES

[1] C.-M. Leung, D. Li, Y. Xin, W.-C. Law, Y. Zhang, H.-F. Ting, R. Luo, and T.-W. Lam, "Megapath: sensitive and rapid pathogen detection using metagenomic ngs data," *BMC genomics*, vol. 21, no. 6, pp. 1–9, 2020. I

[2] S. Bowler, G. Papoutsoglou, A. Karanikas, I. Tsamardinos, M. J. Corley, and L. C. Ndhlovu, "A machine learning approach utilizing dna methylation as an accurate classifier of covid-19 disease severity," *Scientific Reports*, vol. 12, no. 1, p. 17480, 2022. I

[3] J. S. Johnson, D. J. Spakowicz, B.-Y. Hong, L. M. Petersen, P. Demkowicz, L. Chen, S. R. Leopold, B. M. Hanson, H. O. Agresta, M. Gerstein *et al.*, "Evaluation of 16s rrna gene sequencing for species and strain-level microbiome analysis," *Nature communications*, vol. 10, no. 1, pp. 1–11, 2019. I

[4] P. Ng, "dna2vec: Consistent vector representations of variable-length k-mers," *arXiv preprint arXiv:1701.06279*, 2017. I, I, II-.3, III-B

[5] B. K. Sarkar, A. R. Sharma, M. Bhattacharya, G. Sharma, S.-S. Lee, and C. Chakraborty, "Determination of k-mer density in a dna sequence and subsequent cluster formation algorithm based on the application of electronic filter," *Scientific reports*, vol. 11, no. 1, pp. 1–12, 2021. I

[6] T. Mikolov, K. Chen, G. Corrado, and J. Dean, "Efficient estimation of word representations in vector space," *arXiv preprint arXiv:1301.3781*, 2013. I, I, 2

[7] P. E. Compeau, P. A. Pevzner, and G. Tesler, "How to apply de bruijn graphs to genome assembly," *Nature biotechnology*, vol. 29, no. 11, pp. 987–991, 2011. I

[8] R. Stark, M. Grzelak, and J. Hadfield, "Rna sequencing: the teenage years," *Nature Reviews Genetics*, vol. 20, pp. 631–656, 2019. I

[9] J. Tomkins, "Comprehensive analysis of chimpanzee and human chromosomes reveals average dna similarity of 70%," *Answers Research Journal*, vol. 6, no. 2013, pp. 63–69, 2013. I, II

[10] B. Hu, H. Guo, P. Zhou, and Z.-L. Shi, "Characteristics of sars-cov-2 and covid-19," *Nature Reviews Microbiology*, vol. 19, no. 3, pp. 141–154, 2021. I

[11] S. Lauly, Y. Zheng, A. Allauzen, and H. Larochelle, "Document neural autoregressive distribution estimation," *Journal of Machine Learning Research*, vol. 18, 2016. 2

[12] A. Grover and J. Leskovec, "node2vec: Scalable feature learning for networks," in *Proceedings of the 22nd ACM SIGKDD international conference on Knowledge discovery and data mining*, 2016, pp. 855–864. II-.2, II-.2

[13] R. Liu and A. Krishnan, "Pecanpy: a fast, efficient and parallelized python implementation of node2vec," *Bioinformatics*, vol. 37, no. 19, pp. 3377–3379, 2021. II-.2

[14] C. Camacho, G. Coulouris, V. Avagyan, N. Ma, J. Papadopoulos, K. Bealer, and T. L. Madden, "Blast+: architecture and applications," *BMC bioinformatics*, vol. 10, no. 1, pp. 1–9, 2009. III-C.1

[15] J. Johnson, M. Douze, and H. Jégou, "Billion-scale similarity search with GPUs," *IEEE Transactions on Big Data*, vol. 7, no. 3, pp. 535–547, 2019. III-C.1

[16] Y. A. Malkov and D. A. Yashunin, "Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs," *IEEE transactions on pattern analysis and machine intelligence*, vol. 42, no. 4, pp. 824–836, 2018. III-C.1

[17] M. Littmann, M. Heinzinger, C. Dallago, K. Weissenow, and B. Rost, "Protein embeddings and deep learning predict binding residues for various ligand classes," *Scientific Reports*, vol. 11, no. 1, pp. 1–15, 2021. III-C.2