Physics-based inverse design of lipid packing defect sensing peptides; distinguishing sensors from binders

Niek van Hilten[1], Jeroen Methorst[1], Nino Verwei[1] and Herre Jelger Risselada[1,2,3*]

[1]Leiden Institute of Chemistry, Leiden University, Einsteinweg 55, Leiden, 2333 CC, The Netherlands.
[2]Department of Physics, Technical University Dortmund, Otto-Hahn-Strasse 4, Dortmund, 44227, Germany.
[3]Institute of Theoretical Physics, Georg-August-University Göttingen, Friedrich-Hund-Platz 1, Göttingen, 37077, Germany.

*Corresponding author(s). E-mail(s):
jelger.risselada@tu-dortmund.de;
Contributing authors: n.van.hilten@lic.leidenuniv.nl;

Abstract

Proteins can sense hydrophobic lipid packing defects on positively curved membranes. The chemical diversity among such 'sensors' challenges our understanding of how they differ from 'binders', that bind membranes without curvature selectivity. Here, we combine an evolutionary algorithm with coarse-grained molecular dynamics (Evo-MD) to inverse design curvature sensing peptides. The resolved optimum illustrates that curvature sensing is driven by hydrophobic interactions. With the data obtained in the design process, we trained a neural network (NN) that can predict sensing free energy from a peptide sequence only. We applied this NN to experimentally classified sensors and binders and illustrate *why* sensing and binding are phenomena on the same thermodynamic continuum, with only subtle differences in membrane binding free energy. The here-developed physics-based inverse design approach introduces a quantum leap in the computational design of peptide drugs that recognise (inter)facial characteristics of membranes in viruses, bacteria and cancer cells.

Keywords: Curvature sensing, protein-membrane binding, peptides, physics-based inverse design, evolutionary algorithm, Evo-MD

1 How peptides recognise curved membranes

The recognition of curved regions of lipid bilayer membranes by proteins plays a key role in many biological processes, such as vesicular transport, fusion, and fission. This preferred binding to curved membranes is called curvature sensing and is driven by the outer leaflet of the curved bilayer membrane being stretched, which causes defects in the packing of the polar lipid head groups. Apolar amino acids of proteins can complement the now exposed hydrophobic tails within these lipid packing defects, negating their energetic penalty and resulting in a thermodynamic driving force (Fig. 1A).

Many natural lipid packing sensing proteins that bind to the surface of curved membranes feature an amphipathic helix (AH). AHs have a polar face that interacts with the solvent and the lipid head groups and an apolar face that interacts with the hydrophobic lipid tails. Beyond this shared structural amphipathicity, the chemical composition of AHs is highly diverse. For example, the contrasting compositions of the amphipathic lipid packing sensing (ALPS) motif of the ArfGAP1 protein [1] and the AH of α-synuclein [2] (Fig. 1B-C) suggest that curvature sensing results from a delicate balance between the amino acid content on the apolar and polar sides of the helices [3, 4]. Morover, and important to note, some AHs (like α-synuclein) have a positive net charge, providing additional selectivity for anionic liposomes specifically [5]. Taken together, the structural diversity among curvature sensors complicates reliable prediction of a given peptide's sensing ability simply from sequence-based physicochemical descriptors, like mean hydrophobicity $\langle H \rangle$, hydrophobic moment μ_H [6], and net charge z.

Molecular dynamics (MD) simulations are a valuable asset in expanding our understanding of lipid packing defect sensing, since they can access the necessary molecular resolution that many experimental methods lack [7–9]. To reduce system size and, consequently, reduce the computational cost, curved membranes are often represented as stretched flat membranes in MD simulations [10, 11] (Fig. 1A), such that the lipid packing defects on the surface are similar and the consequent relative binding free energies correlate [12]. This approximation is valid since biologically relevant bilayer curvatures are negligible on the length scale of peptides ($\approx$5 nm).

Recently, we developed a highly efficient method that can quantify the relative free energy ($\Delta\Delta F$) of lipid packing defect sensing (i.e. the preference for curved/stretched membranes) by surface peptides [12]. By redefining $\Delta\Delta F$ as a mechanical property, we realised that differential binding can be reinterpreted as the reduction of work required to stretch a membrane leaflet when

Fig. 1 A) A peptide (in black) can have an enhanced affinity (thicker arrows) toward a curved or stretched membrane (in red) as apposed to a flat tensionless membrane (in green), due to hydrophobic lipid packing defects between the lipid head groups. **B-C)** Helical wheel representations [13] of ALPS1 from ArfGAP1 [1] and α-synuclein [2].

the peptide is bound to it. In other words: a peptide that senses leaflet tension/curvature will also tend to induce leaflet tension/curvature and, therefore, those properties are two sides of the same coin. In line with this notion, many AHs have been shown to bind to flat membranes and then actively generate positive membrane curvature (e.g. Epsin [14] and the N-BAR domain [15]).

A still unresolved key question is what physical characteristics differentiate AHs that specifically bind to curved membranes ('sensors') from AHs that bind without curvature specificity ('binders'). To date, this question has mostly been addressed by making strategically chosen point mutations in specific example cases [2, 4, 16–18], but a fundamental understanding on how to distinguish 'sensors' from 'binders' among multiple chemically diverse classes of AHs is – to the best of our knowledge – still lacking.

2 Optimising lipid packing defect sensing

Evolutionary molecular dynamics (Evo-MD) is a physics-based inverse design method that embeds molecular dynamics (MD) simulations in a genetic algorithm (GA) framework [19]. GAs are inspired by Darwinian evolution and can serve as a powerful tool for optimisation problems in large discrete search spaces, like the 20^L possible peptide sequences (for 20 natural amino acids and peptide length L). Starting from a, in our case random, initial subset ('population'), a GA iteratively (1) evaluates the desired property ('fitness') of the candidate solutions in the population, (2) selects the best candidates as the 'parents' for the next generation, and then (3) performs genetic operations, like cross-over recombination and random point mutations to (4) generate the next population (Fig. 2A). While evolution proceeds, the population's average fitness will increase until it converges to an optimum. To date, GAs have mainly been applied to peptide optimisation problems that involve protein-peptide interactions and use fitness functions based on physicochemical descriptors or information from databases [13, 20–22]. In contrast, the fitness calculation in Evo-MD is based on ensemble averaging from (coarse-grained) MD

simulation trajectories and is therefore completely data-independent. In this
physics-based approach, experimental data contributes to solving the optimi-
sation problem via the parametrisation of the force-field that is used in the
simulations, the Martini model [23] in this study.
For the optimisation of lipid packing defect sensing peptides, we used the
aforementioned mechanical free-energy method [12] to quantify sensing. The
fitness function is given by the resulting $\Delta\Delta F$ value, scaled by a factor c that
equals 1 when located on the membrane surface and goes to 0 for transmem-
brane or soluble configurations (see SI). We emphasise that $\Delta\Delta F$ characterises
the relative affinity for lipid packing defects or equivalently positive leaflet cur-
vature, analogous to the curvature-dependent binding constants (free energy of
partitioning) measured in experimental model liposome assays [4, 16–18, 24–
28] as well as measured differences in the concentration of peripheral membrane
proteins due to curvature-driven sorting in micropipette aspiration assays
[29, 30].
Since membrane-surface peptides are in most cases α-helical and the Mar-
tini force-field is unable to model protein folding events, we assume and fix
helical secondary structure when generating the starting conformations for our
peptides. To this end, and to reduce the search space, we excluded 10 amino
acids with low α-helical propensities [31] (P, G, D, R, C, T, N, H, V, and I),
whilst ensuring that every chemical subtype is represented in our final subset
(comprising A, L, M, K, Q, E, W, S, Y, and F). We chose a fixed peptide
length of 24 residues, which is in the typical range for lipid packing sensing
peptides. Consequently, our search space contains 10^{24} peptide sequences.
In the three independent Evo-MD runs we performed (see SI for method-
ological details), we observed convergence within 25 iterations with the best
candidates having a $\Delta\Delta F$ of around -32 kJ mol^{-1} (Fig. 2B). The consen-
sus sequence logos [33] of the final generations show a strong enrichment of
bulky hydrophobic residues, mainly F and W (Fig. 2C-E and supplementary
movies). We can understand this result by returning to our earlier state-
ment that "a peptide that senses tension/curvature will also tend to induce
tension/curvature".
Such induction of tension and concomitant membrane curvature in a mem-
brane leaflet occurs via shallow insertions within the hydrophobic interior of
the lipid membrane, i.e. the region directly below the head groups. Indeed,
we observe that the optimal sequences – the point of maximum leaflet ten-
sion generation with respect to the helix' central axis – is characterised by an
insertion of 1.69 ± 0.05 nm from the bilayer center in a tensionless membrane
(d_{mem} in Fig. 2I), or alternatively 0.24 ± 0.05 nm below the average position of
the phosphate groups (d_{PO4} in Fig. 2I). This is in quantitative agreement with
predictions from membrane elastic theory, which suggests an optimal inser-
tion of about 1.7 nm from the membrane center plane [34]. Furthermore, the
bulkier the peptide is, and thus the larger its excluded volume and effective
helical radius, the more pronounced the induced leaflet tension will be.
183
184

Fig. 2 A) Schematic representation of the Evo-MD process. Figure adapted from previous work [12]. **B)** Three independent replica Evo-MD runs show convergence within 25 iterations, as evident by the population best (solid lines) and population average (dashed lines). For comparison, the $\Delta\Delta F$ values for two known curvature sensing motifs (ALPS1 of ArfGAP1 [1] and α-synuclein [2]) are shown in green. **C-E)** Consensus sequence logos [32] for the best 36 sequences of the final population. **F-H)** The respective helical wheel representations [13] of the consensus sequences shown in C-E. **I)** Simulation snapshot of a consensus peptide (Fig. 2C, F) bound to a tensionless POPC membrane. Hydrophobic residues (F, W, L) are shown in yellow; E is shown in red. Phosphate (PO_4) and choline (NC_3) beads are shown in orange and blue, respectively. d_{mem} is the z-component of the center-of-mass distance between the membrane and the peptide. d_{PO4} is the z-component of the center-of-mass distance between the PO_4 groups and the peptide.

Besides the abundant hydrophobic residues, we observed that the solutions of all three Evo-MD runs feature two charged residues (E or K, see Fig. 2C-E). This numerical conservation of two charged amino acids suggests that this is the bare minimum of polar content that is necessary to maintain a surface orientation for such hydrophobic peptides (i.e. scaling factor $c \to 1$). The sign of the charge appears to be irrelevant for the zwitterionic POPC membranes we used here. Also, the exact position of these residues seems arbitrary, as long as the two charged residues end up on the same side of the helix in the folded conformation (Fig. 2F-H).

The fact that all three randomly initiated Evo-MD runs produced peptide sequences with identical physical characteristics within the same number of iterations strongly suggests that this is indeed the global and not a local optimum. To probe the effect of only using the 10 most helix-prone amino acids, we performed an additional Evo-MD run with all 20 natural residues included.

This, again, yielded peptides with the same physical characteristics, but showing slower convergence (40 iterations) and higher diversity due to the vastly increased search space (see SI).

What this simulated evolution shows is that the GA has successfully selected a key aspect in curvature sensing, insertion of hydrophobic residues [16, 28], which is then maximally amplified and exploited until the fitness converges. To such extent even, that the optimal 'sensor' is so hydrophobic that it would likely stick to any membrane, regardless of curvature, thus being classified as a 'binder' instead. What is immediately clear is that our optimised peptides strongly differ from the naturally evolved optima (e.g. the ALPS motif and α-synuclein), both in terms of $\Delta\Delta F$ (Fig. 2B) and in their chemical compositions (Fig. 1B-C and Fig. 2F-H). Thus, our physics-based inverse design indicates that the distinction between curvature sensors and membrane binders can be considered as a continuum with a soft, subtle threshold at a relative binding free energy that is much lower than the theoretical optimum.

Biologically, the differences between the simulated optimum and naturally evolved peptides can be explained by considering the many boundary conditions imposed by the complex environment of *in vivo* systems. One of the most obvious and fundamental requirements is that proteins should be soluble in physiological buffer. The extremely hydrophobic GA-generated optima clearly fail this criterion and will readily aggregate and precipitate out of the solution. Also, since lipid packing defect sensing implies tension generation, peptides with a high $\Delta\Delta F$ could harm the integrity of the membranes they adhere to. Therefore, an evolutionary pressure to limit this potency must exist.

3 A neural network model for sensing ability predictions

As a valuable byproduct of the iterative optimisation process by Evo-MD, we obtained a large database of $\approx$54,000 unique sequences (all 24 residues long) and their respective sensing free energies ($\Delta\Delta F$) as calculated by MD simulations. With this wealth of data, we set out to train a convolutional neural network (CNN) that is able to predict lipid packing sensing ability from peptide sequence information only.

To enable the model to handle peptides shorter than 24 amino acids as well, we split the sequences in the original data set at a random position, such that the resulting two fragments were at least 7 residues long. Next, since $\Delta\Delta F$ depends linearly on length (see SI), we interpolated the $\Delta\Delta F$ values to the split sequences, hereby tripling the data set to $\approx$138,000 sequences (after discarding duplicate fragments). We refrained from extrapolating to sequences longer than 24 residues, since this would require additional assumptions on amino acid composition and – potentially – involve more complex tertiary structures that are inaccurately modeled by the Martini force-field. A detailed description of the final training data is included in the SI.

As described previously in the context of activity prediction of helical antimicrobial peptides [35], we used one-hot encoded and zero-padded representations for the input sequences. These are then fed to two consecutive convolutional layers with max pooling, followed by a fully connected layer and a single output neuron to translate the connection weights into a float value: the predicted $\Delta\Delta F$ (Fig. 3A, see SI for details on the optimisation of the architecture and hyperparameters).

Fig. 3 **A)** Architecture of the CNN model. **B-C)** Correlation between the CNN-predicted and MD-calculated $\Delta\Delta F$ values for the validation set after the final training (B) and for a random test set (C).

During the CNN training, minimisation of the mean squared error (MSE) converged after 18 epochs (see SI) to a MSE of 1.84 for the validation set (25% random sample from the full data). For this validation set, we achieved excellent correlation ($R^2 = 0.97$) between the predicted and MD-calculated $\Delta\Delta F$'s (Fig. 3B). However, because sequences from the late iterations of the same Evo-MD run can be highly similar, the validation and training sets are arguably not fully independent. Therefore, to ultimately test our model, we predicted the $\Delta\Delta F$ for 1,000 randomly generated sequences (between 7 and 24 residues long) that were not part of the training data and obtained a MSE of 2.92 and an R^2-value of 0.66 when comparing the predicted values to the $\Delta\Delta F$ calculated by MD simulations (Fig. 3C).

The trained neural network and all data sets are accessible at
github.com/nvanhilten/CNN_lipid_packing_defect_sensing. Please note
that the model should only be used for sequences between 7 and 24 amino
acids long, and that it assumes α-helical folding (as we did in the training
data). Based on the performance of our model on the randomly generated test
set, the root-mean-square error (RMSE) of its predictions is $\sqrt{MSE} = 1.71$
kJ mol^{-1}, which is comparable to the typical errors obtained when calculating
$\Delta\Delta F$ by MD simulation (e.g. compare the error bars of Fig. 4A and 4B).

4 Distinguishing sensing from binding

Now, with the MD quantification and CNN tools in hand, we can return to
the key question posed in the first section of this paper, namely: which, if
any, characteristics can help us distinguish curvature sensors from binders, and
what can relative binding free energies, like $\Delta\Delta F$, teach us in this regard? To
address this question, we composed a set of natural curvature sensing peptides
(see SI), also including mutated variants that were empirically categorised as
'non-binders' (i.e. no affinity for any membrane) or 'binders' (i.e. binding to
membranes without curvature specificity). We should acknowledge the expert
help of Prof. Bruno Antonny and Dr. Romain Gautier in composing this list.
To fairly compare the sequences, we propose two correction factors to
obtain an adjusted relative binding free energy $\Delta\Delta F_{adj}$. First, we linearly
extrapolate the $\Delta\Delta F$ values of shorter peptides to their corresponding free
energies if they were 24 residues long ($\Delta\Delta F_{L=24}$, see SI). Second, we realised
that many of the peptides are cationic to improve interaction with (curved)
anionic membranes that are abundant in nature. Since our MD simulations
were performed with neutral POPC membranes, we hypothesised that the rel-
ative binding free energies would in these cases be underestimated and thus
require a correction term $c_z z$ to account for this:

$$\Delta\Delta F_{adj} = \Delta\Delta F_{L=24} + c_z z \tag{1}$$

To determine the magnitude of c_z (the relative free energy contribution per
unit charge z), we performed additional MD simulations with anionic mem-
branes (75% POPC, 25% POPG) and indeed found elevated relative binding
free energies, especially for the cationic peptides (see SI). From the average dif-
ference between the $\Delta\Delta F$'s calculated on the different membranes, we obtained
$c_z = -0.93 \pm 0.89$ kJ mol^{-1} per unit charge.
We calculated this $\Delta\Delta F_{adj}$ for our peptides of interest with the CNN model
(Fig. 4A) and MD simulations (Fig. 4B). When ranking the peptides accord-
ingly, we find that we can roughly reproduce the empirical qualification of
'non-binders' at the lower end and 'binders' at the higher end of the ranking,
and 'sensors' in the middle. Notably, the differences between the values for
subsequently ranked peptides are rather small, often below 1 kJ mol^{-1}. These
findings are in line with our hypothesis that the thermodynamics of binding
and sensing are subtle energetic transitions on a continuous scale.

Interestingly, we find that the CNN-predicted ranking is in better agreement with the experimental trends than the results from MD simulations (Fig. 4A-B). We speculate that this is likely due to a smoothening effect, i.e. predictions of the MD simulations for individual peptide sequences are fully independent whereas the CNN introduces effective correlations between sequences. Because the CNN is trained on the ensemble averaged values from many thousands of independent MD trajectories for different peptide sequences, we argue that disturbances ('noise') in chemical space (point mutations) and in the molecular dynamics itself (limited sampling) are therefore smoothened out to such extent that the experimental trends are more robustly reproduced. Hence, we use the CNN-predicted $\Delta\Delta F_{adj}$ values for the remainder of this paper.

5 Thermodynamic model of the sensing→binding transition

Along the lines of our current definitions, every peptide undergoing hydrophobically driven membrane binding is able to sense positive membrane curvature due the increase in surface hydrophobicity upon bending. In other words, positive curvature enhances hydrophobically driven membrane binding. Empirically, however, a peptide is only classified as a curvature sensor if it *only* significantly binds to membranes characterised by a high positive curvature. In this section, we will argue that the empirical classification of sensors versus binders can be intuitively understood from the population statistics of a two-state partition function.

Herein, we define the following two states; (i) state m: the peptide is bound to the membrane, (ii) state s: the peptide is in solution. We define the partitioning free energy difference between the two states as ΔF_{sm}: the free energy of membrane binding minus the free energy of solvation with respect to the peptide in the gas phase. We calculated ΔF_{sm} by thermodynamic integration (see SI) for a non-binder, a sensor, a binder, and the consensus sequence (Fig. 2D, F) produced by Evo-MD, and found that it linearly relates to $\Delta\Delta F_{adj}$ (Fig. 4C).

Furthermore, the number of membrane binding realisations is proportional to the (normalised) membrane area A_m, and equivalently the number of realisations in solution is proportional to the (normalised) volume of accessible solvent V_s. At thermal equilibrium, the relative probability for a peptide to bind to the membrane P_m is Boltzmann distributed. Consequently, P_m is given by:

$$P_m = \frac{1}{1 + \frac{V_s}{A_m}e^{\Delta F_{sm}}} \tag{2}$$

Eq. 2 resembles the so-called Fermi-Dirac function. If $\frac{V_s}{A_m} = 1$, this function features a sharp but continuous transition at $\Delta F_{sm} = 0$ (dashed curve in Fig. 4E), i.e. the point where membrane binding and peptide solubility

are precisely in balance ($P_m = 0.5$). However, the number of realisations in
solution is expected to be much larger than the number of realisations asso-
ciated with membrane binding, $\frac{V_s}{A_m} \gg 1$. Consequently, the transition point
shifts to the right, i.e. peptide-membrane binding is significantly favoured
over peptide solvation at the transition point $P_m = 0.5$. The steep nature
of this 'switch function' strikingly explains *how* empirically classified sensing
behaviour switches to binding behaviour based on only subtle differences in
(relative) membrane binding free energy, like we observed in this work (Fig.
4A).

Fig. 4 A-B) Length- and charge-adjusted relative binding free energy ($\Delta\Delta F_{adj}$, see eq.
1) for 19 curvature sensors or derivatives (see SI) predicted with the CNN model (A) and
calculated from MD simulations (B). **C)** Linear correlation between CNN-predicted $\Delta\Delta F_{adj}$
and the membrane binding free energy (ΔF_{sm}). Circles indicate peptides for which ΔF_{sm}
was calculated by thermodynamic integration (see SI). The consensus peptide (black) is the
sequence in Fig. 2D. For the remaining peptides (crosses), ΔF_{sm} was derived from the linear
correlation. **D)** Highlighted CNN-predicted $\Delta\Delta F_{adj}$ values for ALPS GMAP-210 variants.
E) The probability of a peptide to bind a membrane P_m as a function of the partitioning
free energy ΔF_{sm} (eq. 2). The dashed curve is for $\frac{V_s}{A_m} = 1$, which is shifted to the solid
curve for $\frac{V_s}{A_m} = 2.6 \cdot 10^3$, as derived in the main text. In C-E, the green area indicates the
likely regime ($0.05 \leq P_m \leq 0.95$) where peptides are empirically classified as sensors.

To finalise our model, we estimate the prefactor $\frac{V_s}{A_m}$. The accessible mem-
brane area in one liter of solution is $A = \frac{1}{2}cN_{av}A_{lip}$, with c being the lipid

concentration, N_{av} the Avogadro constant, and A_{lip} the area per lipid. The
characteristic surface area of a helical peptide is roughly $A_p = 5 \times 1$ nm^2 and
equivalently its volume in solution is $V_p = 5 \times 1 \times 1$ nm^3. Taking $c = 2$ mM
(a typical value in the middle of the concentration range used in experiments
[4, 16–18, 24–28]) and $A_{lip} = 0.64$ nm^2 we obtain $\frac{V_s}{A_m} = \frac{V/V_p}{A/A_p} = 2.6 \cdot 10^3$.

When we plug this number into eq. 2, we find that free energy of membrane
binding outperforms the free energy of solvation by -19.5 kJ mol^{-1} at the tran-
sition point $P_m = 0.5$ (Fig. 4E), i.e. the transition point is associated with
favourable but relatively weak membrane binding. Because of the sharp tran-
sition behaviour 'sensors' are envisioned as peptides with a ΔF_{sm} value near
the transition point ($0.05 \leq P_m \leq 0.95$, the green area in Fig. 4E). According
to our model, a peptide with $P_m < 0.05$ would be classified as a 'non-binder',
and a peptide with $P_m > 0.95$ would be deemed a 'binder'. When overlaying
the values for the 19 example peptides we introduced earlier (vertical lines in
Fig. 4E, see SI), we find that 3/3 non-binders, 7/11 sensors, and 3/4 binders
are classified correctly, i.e. in agreement with the original experiments. Such
categorisation would have been impossible with crude physicochemical descrip-
tors like mean hydrophobicity $\langle H \rangle$ or hydrophobic moment μ_H despite them
(weakly) correlating with ΔF_{sm} (see SI).

We defined the sensing regime rather generously ($0.05 \leq P_m \leq 0.95$) to
accommodate for the fact that both the empirical classification and the posi-
tioning of the Fermi-Dirac curve are sensitive to the lipid concentration c,
which can differ significantly between experiments. Moreover, differing lipid
compositions, cell systems, and read-out types can complicate the direct com-
parison between empirical classifications. In terms of partitioning free energy
ΔF_{sm}, the lower and upper boundaries of sensing ($0.05 \leq P_m \leq 0.95$) corre-
spond to -12.2 and -26.8 kJ mol^{-1}, respectively (green area in Fig. 4C, E).
In other words, when the work required to pull a peptide from a membrane is
between those values, it can be classified as a sensor. In terms of the length-
and charge-adjusted relative binding free energy ($\Delta\Delta F_{adj}$), i.e. the preference
for highly curved membranes (≈ 25 nm vesicles [12]), sensors fall between -6.4
and -10.2 kJ mol^{-1} (green area in Fig. 4C-D).

As an example, we highlighted four variants of ALPS GMAP-210 [17, 18]
for which the relative differences in experimental sensing/binding behaviour
were correctly captured (Fig. 4D). This is a striking example because the
sequences are so similar: the only difference between the original sensor ALPS
GMAP-210 and the non-binding variant ALPS GMAP-210 (L12D) is a sin-
gle point mutation (L $\rightarrow$ D) that disturbs the peptide's hydrophobic face.
As can be expected, and in line with the experimental findings, the inverse
sequence ALPS GMAP-210 (inv) scores the same as the original peptide and
is thus categorised as a sensor as well. Finally, the condensed version ALPS
GMAP-210 (cond) was correctly identified as a binder. With this highlighted
example, we demonstrate that our method and thermodynamic model can
pick out these features and the resulting subtle differences in relative free

energy and correctly categorise the consequent sensing behaviour.

When starting this project, we set out to optimise lipid packing defect
(curvature) sensing by resolving the sequence that maximises the *relative* affin-
ity for lipid packing defects. Instead, we ended up with the optimal 'binder'.
This finding led to the important realisation that curvature sensing and mem-
brane binding are phenomena that lie on the same thermodynamic continuum
(Fig. 4D). Naturally evolved curvature sensors, such as the ALPS motif and
α-synuclein, are chemically diverse but turn out to be remarkably similar in
terms of partitioning free energies, which explains their functional similar-
ities. In this paper, we – for the first time – describe the thermodynamic
regime that defines the curvature sensing behaviour of peptides. Efficient free-
energy calculations and (especially) the here-described neural network model
enable high-throughput evaluation of peptide sequences, which allows for the
navigation, optimisation and convergence of vast search spaces, as we have
demonstrated via the effective sampling of a search space comprising 20^{24}
peptide sequences. We postulate that restriction of the search space to the
here-resolved sensing regime may facilitate the discovery of novel curvature
sensing motifs in natural proteins, as well as their *de novo* generation. Addi-
tionally, we envision an important potential application in the inverse design
of peptide drugs that target membranes with aberrant characteristics such as
high positive curvature (e.g. viruses) and/or membrane lipid composition (e.g.
bacteria and cancer cells), particularly when realising that the simultaneous
encoding of selective membrane binding plus an active drug mode such as the
induction of membrane lysis is realistic. After all, since (selective) membrane
binding results in the generation of leaflet tension, membrane binding peptides
have an inherent propensity to form toroidal pores in addition to favourable
binding, thereby stabilising the highly curved pore interface. Therefore, encod-
ing a differential binding affinity within the here-illustrated weak binding or
sensing regime (i.e., membrane binding selectivity) may be a key design strat-
egy for the development of potent membrane active peptide drugs with a low
overall toxicity (drug selectivity).

Supplementary information.   Methodological details and additional anal-
yses are included in the supplementary information (SI). We also provide the
evolution of consensus sequences as supplementary movies.

Acknowledgments.   We thank Prof. Bruno Antonny and Dr. Romain Gau-
tier for insightful discussions and their expert help in selecting relevant
curvature sensors, non-binders, and binders to test our theory and methods.
The Dutch Research Organisation NWO (Snellius@Surfsara) and the HLRN
Göttingen/Berlin are acknowledged for the provided computational resources.
This work was funded by the Deutsche Forschungsgemeinschaft (DFG, Ger-
man Research Foundation) under Germany's Excellence Strategy - EXC 2033
- 390677874 - RESOLV. We thank the NWO Vidi scheme (project number
723.016.005), and the DFG (grant number RI2791/2-1) for funding.

Author contributions. N.v.H. and H.J.R. designed the research. J.M. wrote the Evo-MD code. N.v.H implemented Evo-MD modules specific to the lipid packing defect sensing problem. N.v.H. and N.V. developed, trained, and optimised the neural network model. N.v.H. and H.J.R. wrote the manuscript.

Data avalability. The Evo-MD code and all related files are available at github.com/nvanhilten/Evo-MD_lipid_packing_defect_sensing.
   The data sets, trained CNN model, and related scripts are available at github.com/nvanhilten/CNN_lipid_packing_defect_sensing.

References

[1] Bigay, J., Casella, J.F., Drin, G., Mesmin, B., Antonny, B.: ArfGAP1 responds to membrane curvature through the folding of a lipid packing sensor motif. EMBO J. **24**(13), 2244–2253 (2005)

[2] Jensen, M.B., Bhatia, V.K., Jao, C.C., Rasmussen, J.E., Pedersen, S.L., Jensen, K.J., Langen, R., Stamou, D.: Membrane curvature sensing by amphipathic helices. J. Biol. Chem. **286**(49), 42603–42614 (2011)

[3] Drin, G., Antonny, B.: Amphipathic helices and membrane curvature. FEBS Lett. **584**(9), 1840–1847 (2010)

[4] Pranke, I.M., Morello, V., Bigay, J., Gibson, K., Verbavatz, J.-M., Antonny, B., Jackson, C.L.: α-synuclein and alps motifs are membrane curvature sensors whose contrasting chemistry mediates selective vesicle binding. J. Cell Biol. **194**(1), 89–103 (2011)

[5] Davidson, W.S., Jonas, A., Clayton, D.F., George, J.M.: Stabilization of α-synuclein secondary structure upon binding to synthetic membranes. J. Biol. Chem. **273**(16), 9443–9449 (1998)

[6] Eisenberg, D., Weiss, R.M., Terwilliger, T.C.: The helical hydrophobic moment: a measure of the amphiphilicity of a helix. Nature **299**(5881), 371–374 (1982)

[7] González-Rubio, P., Gautierd, R., Etchebest, C., Fuchs, P.F.J.: Amphipathic-lipid-packing-sensor interactions with lipids assessed by atomistic molecular dynamics. Biochim. Biophys. Acta Biomembr. **1808**(9), 2119–2127 (2011)

[8] Vanni, S., Hirose, H., Barelli, H., Antonny, B., Gautier, R.: A sub-nanometre view of how membrane curvature and composition modulate lipid packing and protein recruitment. Nature Comm. **5**, 4916 (2014)

[9] Stroh, K.S., Risselada, H.J.: Quantifying membrane curvature sensing of peripheral proteins by simulated buckling and umbrella sampling. J. Chem. Theory Comput. **17**(8), 5276–5286 (2021)

[10] van Hilten, N., Stroh, K.S., Risselada, H.J.: Membrane Thinning Induces Sorting of Lipids and the Amphipathic Lipid Packing Sensor (ALPS) Protein Motif. Front. Physiol. **11**, 250 (2020)

[11] Chng, C.-P., Cho, N.-J., Hsia, K.J., Huang, C.: Role of membrane stretch in adsorption of antiviral peptides onto lipid membranes and membrane pore formation. Langmuir (2021)

[12] van Hilten, N., Stroh, K.S., Risselada, H.J.: Efficient quantification of lipid packing defect sensing by amphipathic peptides: Comparing martini 2 and 3 with CHARMM36. J. Chem. Theory Comput. (2022)

[13] Gautier, R., Douguet, D., Antonny, B., Drin, G.: HELIQUEST: a web server to screen sequences with specific α-helical properties. Bioinformatics **24**(18), 2101–2102 (2008)

[14] Ford, M.G., Mills, I.G., Peter, B.J., Vallis, Y., Praefcke, G.J., Evans, P.R., McMahon, H.T.: Curvature of clathrin-coated pits driven by epsin. Nature **419**(6905), 361–366 (2002)

[15] Löw, C., Weininger, U., Lee, H., Schweimer, K., Neundorf, I., Beck-Sickinger, A.G., Pastor, R.W., Balbach, J.: Structure and dynamics of helix-0 of the n-bar domain in lipid micelles and bilayers. Biophys. J. **95**(9), 4315–4323 (2008)

[16] Drin, G., Casella, J.F., Gautier, R., Boehmer, T., Schwartz, T.U., Antonny, B.: A general amphipathic alpha-helical motif for sensing membrane curvature. Nat. Struct. Mol. Biol. **14**(2), 138–146 (2007)

[17] Drin, G., Morello, V., Casella, J.-F., Gounon, P., Antonny, B.: Asymmetric tethering of flat and curved lipid membranes by a golgin. Science **320**(5876), 670–673 (2008)

[18] Magdeleine, M., Gautier, R., Gounon, P., Barelli, H., Vanni, S., Antonny, B.: A filter at the entrance of the golgi that selects vesicles according to size and bulk lipid composition. eLife **5**, 16988 (2016)

[19] Methorst, J., van Hilten, N., Risselada, H.J.: Inverse design of cholesterol attracting transmembrane helices reveals a paradoxical role of hydrophobic length. bioRxiv (2021)

[20] Belda, I., Llorà, X., Giralt, E.: Evolutionary algorithms and de novo peptide design. Soft Comput. **10**(4), 295–304 (2006)

[21] Knapp, B., Giczi, V., Ribarics, R., Schreiner, W.: PeptX: using genetic algorithms to optimize peptides for MHC binding. BMC Bioinformatics **12**(1), 241 (2011)

[22] Barigye, S.J., García de la Vega, J.M., Perez-Castillo, Y., Castillo-Garit, J.A.: Evolutionary algorithm-based generation of optimum peptide sequences with dengue virus inhibitory activity. Future Med. Chem. **13**(11), 993–1000 (2021)

[23] Souza, P.C.T., Alessandri, R., Barnoud, J., Thallmair, S., Faustino, I.,

Grünewald, F., Patmanidis, I., Abdizadeh, H., Bruininks, B.M.H., Wasse­naar, T.A., Kroon, P.C., Melcr, J., Nieto, V., Corradi, V., Khan, H.M., Domański, J., Javanainen, M., Martinez-Seara, H., Reuter, N., Best, R.B., Vattulainen, I., Monticelli, L., Periole, X., Tieleman, D.P., de Vries, A.H., Marrink, S.J.: Martini 3: a general purpose force field for coarse-grained molecular dynamics. Nature Methods **18**(4), 382–388 (2021)

[24] Mesmin, B., Drin, G., Levi, S., Rawet, M., Cassel, D., Bigay, J., Antonny, B.: Two lipid-packing sensor motifs contribute to the sensitivity of ArfGAP1 to membrane curvature. Biochemistry **46**(7), 1779–1790 (2007)

[25] Fan, W., Nassiri, A., Zhong, Q.: Autophagosome targeting and membrane curvature sensing by barkor/atg14(l). Proc. Natl. Acad. Sci. **108**(19), 7769–7774 (2011)

[26] Cabrera, M., Langemeyer, L., Mari, M., Rethmeier, R., Orban, I., Perz, A., Bröcker, C., Griffith, J., Klose, D., Steinhoff, H.-J., Reggiori, F., Engelbrecht-Vandré, S., Ungermann, C.: Phosphorylation of a membrane curvature–sensing motif switches function of the HOPS subunit vps41 in membrane tethering. J. Cell Biol. **191**(4), 845–859 (2010)

[27] Karanasios, E., Han, G.-S., Xu, Z., Carman, G.M., Siniossoglou, S.: A phosphorylation-regulated amphipathic helix controls the membrane translocation and function of the yeast phosphatidate phosphatase. Proc. Natl. Acad. Sci. **107**(41), 17539–17544 (2010)

[28] Vanni, S., Vamparys, L., Gautier, R., Drin, G., Etchebest, C., Fuchs, P.F., Antonny, B.: Amphipathic lipid packing sensor motifs: probing bilayer defects with hydrophobic residues. Biophys. J. **104**(3), 575–584 (2013)

[29] Tian, A., Baumgart, T.: Sorting of lipids and proteins in membrane curvature gradients. Biophys. J. **96**(7), 2676–2688 (2009)

[30] Sorre, B., Callan-Jones, A., Manneville, J.B., Nassoy, P., Joanny, J.F., Prost, J., Goud, B., Bassereau, P.: Curvature-driven lipid sorting needs proximity to a demixing point and is aided by proteins. Proc. Natl. Acad. Sci. U.S.A. **106**(14), 5622–5626 (2009)

[31] Pace, C.N., Scholtz, J.M.: A helix propensity scale based on experimental studies of peptides and proteins. Biophys. J. **75**(1), 422–427 (1998)

[32] Tareen, A., Kinney, J.B.: Logomaker: beautiful sequence logos in Python. Bioinformatics **36**(7), 2272–2274 (2019)

[33] Schneider, T.D., Stephens, R.M.: Sequence logos: a new way to display consensus sequences. Nucleic Acids Res. **18**(20), 6097–6100 (1990)

[34] Campelo, F., McMahon, H.T., Kozlov, M.M.: The hydrophobic insertion mechanism of membrane curvature generation by proteins. Biophys. J. **95**(5), 2325–2339 (2008)

[35] Witten, J., Witten, Z.: Deep learning regression model for antimicrobial peptide design. bioRxiv (2019)

782