Machine learning identification of *Pseudomonas aeruginosa* strains from colony image data

Jennifer B. Rattray[1,2], Ryan J. Lowhorn[1,2], Ryan Walden[3], Pedro Márquez-Zacarías[4], Evgeniya Molotkova[1,2], Gabriel Perron[5,6], Claudia Solis-Lemus[7,8], Daniel Pimentel Alarcon[8,9], Sam P. Brown[1,2,*]

[1] School of Biological Sciences, Georgia Institute of Technology, Atlanta, GA 30332, USA
[2] Center for Microbial Dynamics and Infection, Georgia Institute of Technology, Atlanta, GA 30332, USA
[3] Rosenblatt, LLC
[4] Santa Fe Institute, Santa Fe, NM 87501, USA
[5] Department of Biology, Bard College, Annandale-On-Hudson, NY 12504, USA
[6] Center for Systems Biology and Genomics, New York University, New York, NY, 10003, USA
[7] Department of Plant Pathology, University of Wisconsin-Madison, Madison, WI 53706, USA
[8] Wisconsin Institute for Discovery, University of Wisconsin-Madison, Madison, WI 53706, USA
[9] Department of Biostatistics and Medical Informatics, University of Wisconsin-Madison, Madison, WI 53706, USA

*corresponding author, email Sam.brown@biology.gatech.edu

Abstract

When grown on agar surfaces, microbes can produce distinct multicellular spatial structures called colonies, which contain characteristic sizes, shapes, edges, textures, and degrees of opacity and color. For over one hundred years, researchers have used these morphology cues to classify bacteria and guide more targeted treatment of pathogens. Advances in genome sequencing technology have revolutionized our ability to classify bacterial isolates and while genomic methods are in the ascendancy, morphological characterization of bacterial species has made a resurgence due to increased computing capacities and widespread application of machine learning tools. In this paper, we revisit the topic of colony morphotype on the within-species scale and apply concepts from image processing, computer vision, and deep learning to a dataset of 69 environmental and clinical *Pseudomonas aeruginosa* strains. We find that colony morphology and complexity under common laboratory conditions is a robust, repeatable

phenotype on the level of individual strains, and therefore forms a potential basis for strain classification. We then use a deep convolutional neural network approach with a combination of data augmentation and transfer learning to overcome the typical data starvation problem in biological applications of deep learning. Using a train/validation/test split, our results achieve an average validation accuracy of 92.9% and an average test accuracy of 90.7% for the classification of individual strains. These results indicate that bacterial strains have characteristic visual 'fingerprints' that can serve as the basis of classification on a sub-species level. Our work illustrates the potential of image-based classification of bacterial pathogens and highlights the potential to use similar approaches to predict medically relevant strain characteristics like antibiotic resistance and virulence from colony data.

Author Summary

Since the birth of microbiology, scientists have looked at the patterns of bacterial growth on agar (colony morphology) as a key tool for identifying bacterial species. We return to this traditional approach with modern tools of computer vision and deep learning and show that we can achieve high levels of classification accuracy on a within-species scale, despite what is considered a 'data-starved' dataset. Our results show that strains of the environmental generalist and opportunistic pathogen *Pseudomonas aeruginosa* have a characteristic morphological 'fingerprint' that enables accurate strain classification via a custom deep convolutional neural network. Our work points to extensions towards predicting phenotypes of interest (e.g. antibiotic resistance, virulence), and suggests that sample size limitations may be less restrictive than previously thought for deep learning applications in biology, given appropriate use of data augmentation and transfer-learning tools.

Introduction

Since Semmelweis, Lister, and Koch began studying pure cultures of microorganisms, scientists have tried to organize the immense diversity of bacteria into orderly categories to understand their behavior, including pathogenesis. In particular, Koch pioneered the method of determining how specific microorganisms cause distinct diseases and highlighted the importance of laboratory culture for the identification and targeted treatment of pathogenic bacteria (1). By identifying the specific bacterial cause of disease, we can better manage and eradicate the infection. When a sample from an environment or clinical source is plated on solid media at sufficient dilution, individual colonies can be observed, where each colony grows from a single founding bacterial cell (Figure 1A). These clonal groups have characteristic sizes, shapes, edges, textures, and degrees of opacity and color (Figure 1B) (2). These characteristics describe the morphology of a single colony and formed the basis for the earliest attempts at categorization. In modern clinical laboratories, morphological tests play a role but are increasingly replaced by biochemical and genomic methods of classification (3).

Figure 1. Bacterial colony morphology varies across and within species. A) Morphological identification of bacterial species from a mixed culture plated on Chocolate Agar: *Rothia mucilaginosa* (smallest white circles), *Neisseria subflava* (larger tan round circles), and *Streptococcus mitis* (large bullseye circles). B) A common example of 2D colony morphology features include the appearance of the colony edges. C) Morphological identification of bacterial strains, in this case called "smooth", "wrinkly spreader", and "fuzzy spreader"(4), from a culture containing only *Pseudomonas fluorescens* plated on King's Medium B Agar.

While initial classification was morphology based, advances in genome sequencing technology have revolutionized our ability to classify bacterial isolates. Widespread use of 16S rRNA amplicon sequencing not only allows for robust taxon identification to the genus scale (5,6), but also fosters phylogenetic organization of bacterial taxa (7,8). Marker gene or whole genome sequencing provides finer scale strain identification and allows specific focus on markers of pathogenicity (via identification of virulence factors), drug resistance or other characteristics of interest. Transcriptomic sequencing provides a more direct window into the behavior of

pathogens, to assay for example whether virulence factor or drug resistance genes are actually

being expressed (9).

While genomic methods are in the ascendancy, morphological characterization of bacterial

species has made a resurgence. How a population of bacteria grow is a direct result of the

interplay between their genotype, phenotype, and environment (10) and *a priori* contains critical

phenotypic information on the behavior of individual microbes. For example, colony

morphotype can indicate specific mutations in a bacteria, e.g. small colony variants and cyclic

di-GMP regulation (11) or rugosity and phenazine production (12). Morphological

characterization and data science have collided to provide insights into image-based prediction of

microbial taxa (13–18). The earliest attempts introduced light-scattering for presence-absence

detection of microorganisms on surfaces (19,20), which paved the way for image-based

identification of *Listeria* species from light scattering patterns of *Listeria* colonies (13). This

developed into an automated light scattering sensor called BARDOT (BActerial Rapid Detection

using Optical scattering Technology) that produced scatter patterns sensitive enough to

distinguish between *Escherichia coli* serotypes (14), virulence mutants (15), and industrial

Staphylococcus contaminants (16). At the same time, imaged-based prediction diversified to use

more accessible standard light microscopes instead of specialized equipment, putting the focus

on new analysis methods like colony morphology ontology (18) and deep learning (17,21) .

Deep learning algorithms have gained popularity (17,21,22) as machine learning becomes

ubiquitous across fields. Several supervised deep learning models have demonstrated near human

accuracy in classification of various image datasets (23) and in the case of bacterial biofilms,

deep learning has outperformed human characterization of single and mixed species biofilms

(24). Zielinksi et al. (17) investigate several models for colony classification utilizing a deep

convolutional neural network (D-CNN) on a rich dataset pre-trained on the ImageNet (25)

dataset, achieving a very high validation accuracy of ~ 97%. However, existing work using a D-

CNN approach has focused on classification across species, not across strains within a species.

Additionally, a ubiquitous challenge in many biology applications (including the one in this

paper) is the limited number of samples. For example, the hallmark ImageNet image-based

dataset (26–28) contains more than 14 million images across 1000 classes. Outside a colloquial

'rule of thumb' that you need at least 1000 samples per class, there is no absolute way to

determine a 'minimum' sample size (29).

We focus on within species classification of *Pseudomonas aeruginosa*, a gram-negative

bacterium capable of causing severe chronic illness and a major cause of acute hospital-acquired

infections (30–33). While it is widely viewed as a generalist and can be isolated from a wide

number of environments including water and soil, it is frequently found in human/animal-

impacted environments (30). *P. aeruginosa* has large variety of mechanisms that allow it to

respond to its environment (34–36). There are frequently differences in behavior across strains,

like type and production of secreted products (37,38), which can result in observable

morphological diversity when cultured on agar surfaces (39–43). Classic examples of

morphological variation in P. *aeruginosa* caused by underlying genetic differences include small

colony variants related to cyclic di-GMP regulation (11), rugosity related to phenazine

production (12), and mucoidy related to secreted polymer production (44).

In this paper, we use a collection of 69 clinical and environmental *P. aeruginosa* isolates which

present a range of phenotypic features (e.g. exopolysaccharide production, virulence gene

expression, and antibiotic resistance profiles) that have been previously described in (45–47).

From these 69 isolates we generate a library of 266 *P. aeruginosa* colony images in a training /

validation dataset, plus a separately generated 69-image test dataset. As expected, we document a

high level of variation in the physical appearance of colonies across strains. Additionally, we see

that strain morphology in *P. aeruginosa* is consistent across replicates. We then use a D-CNN

approach and a combination of data augmentation (48,49) and transfer learning (50) to classify

strains of *P. aeruginosa* and achieve an average validation accuracy of 92.9% and an average test

accuracy of 90.7%.

Results

Morphological variation across strains and replicates

Individual isolates from our 69-strain collection were spotted onto Luria-Bertani (LB) agar plates

supplemented with Congo Red, a dye commonly used in microbiology to stain the biofilm matrix

and extracellular polysaccharides (Figure 2). This was done in quadruplicate and generated a

training and validation library of 266 colonies after quality control (10 colonies were removed

due to debris or writing obscuring part of the image). Colonies were grown for 72 hours, which

was determined during the pilot experiment to be enough time to reveal major morphological

differences while minimizing outward expansion. This resulted in an imaged library of image

colonies that ranged in size from 12M (approximately 0.74cm x 0.74cm) to 183M pixels

(approximately 2.8cm x 2.8cm).

Figure 2. Random sample of the *P. aeruginosa* train/validation strain colony dataset. 10 strains (in four-fold replication) were selected randomly without replacement from a complete list of 69 strains via the native sample() command in R. From top to bottom: (left) strain 25, strain, 38, strain 52, strain 113, strain 1; (right) strain 127, strain 316, strain 298, strain 121, strain 174. Colony size has been adjusted for viewing purposes.

In our first approach to characterizing morphological diversity, we use 8 simple descriptive metrics (Figure 3A). Classic morphological descriptive variables include area, radius, perimeter, centroid (the point in which the three medians of the triangle imposed within the image intersect), eccentricity (the ratio of the distance between the foci of the ellipse and its major axis length), circularity (deviation of the perimeter from a superimposed perfect circle), bounding disk center (center of mass of the brightest pixels), and caliper diameter (the caliper dimension obtained by averaging over all orientations).

Figure 3. Diversity of *P. aeruginosa* strains in both classic morphological descriptive variables and derived complexity descriptive variables across 69 strains and 266 colonies. Histograms are built from all replicates of all strains. A) classic metrics used to describe colony appearance. B) Derived metrics from image processing and computer vision to describe colony complexity including compression ratio (relative reduction in size of data) and 6 descriptive statistics derived from the Sobel–Feldman operator.

To expand on these classic descriptive variables, we next introduce complexity metrics (Figure 3B) used in image processing and computer vision (51,52). Compression ratio is a single variable that describes how repetitive an image is, i.e. how repetitive are certain patterns in the pixel distribution and how many times do they occur? Specifically, it is a measurement of the reduction in size of pixel data produced by, in our case, the traditional JPEG compression algorithm. An alternate approach to quantifying image complexity is using the Sobel–Feldman operator, a popular method to detect edges in images due to its ability to detect gradients. At

every pixel in an image, it calculates the pixel intensity of the vertical and horizontal adjacent

pixels and expresses the results as vectors. You can then plot these gradient vectors creating a

unique profile for every colony. These profiles can then be summarized by describing their

distribution (mean, median, standard deviation, skew, root mean square, and kurtosis).

Unsurprisingly, we find that many of these metrics are highly correlated (Supplemental Figure

S1).

Figure 3 summarizes variation in our metrics across both strains and replicates. In Figure 4, we

assess the extent of variation using coefficients of variation (CV = mean / standard deviation),

across replicates (black bars) and across strains (grey bars). With the exception of the

eccentricity and circularity metrics, we see coefficients of variation across replicates are low

(standard deviation << mean), and less than the coefficient of variation across strains. This

pattern of variation indicates that colony morphology under common laboratory conditions is a

robust, repeatable phenotype on the level of individual strains, and therefore forms a potential

basis for strain classification.

Figure 4. Morphological metrics are generally stable across replicates. Coefficient of variation (mean / standard deviation) across replicates (black) and across strains (grey). With the exception of the eccentricity and circularity metrics, coefficients of variation across replicates are low (standard deviation << mean), and less than the coefficient of variation across strains.

Classifying strain identity from image data

Considering our initial results indicating robust morphological traits for each strain, we reasoned that morphological data could be used to classify colonies via a deep learning approach. Deep convolutional neural networks (D-CNNs) typically require larger datasets than those found in biology- usually a minimum of thousands of examples to train properly (53). To address this issue, we applied various transfer learning (50) and data augmentation techniques (48,49) (see methods for details). This initial dataset was split into 90% training and 10% validation sets.

High performance on our validation dataset provides some confidence that the CNN approach

can successfully classify previously unseen strain images. Yet validation results merit caution, as

the validation images were all generated on the same agar plate, imaged on the same day and

from the same overnight culture. These shared features raise the risk that a CNN is detecting

technical batch effects of the experimental environment (e.g. variations in the lighting

conditions) rather than strain-specific features of interest. To address this concern we generated a

separate 69-image test dataset (1 image per strain) using distinct overnight cultures and produced

by a different experimenter on a different day (following the same protocol).

In a first round of computational experiments, we sought to compare the performance of four

transfer learning models (Figure 5, Table S1), using our standard data preprocessing and

augmentation choices (normalized pixel intensities; shear / zoom / flip / rotation / brightness /

scaling data augmentation – see methods). To determine the best approach for our dataset, our

performance metrics are accuracy (the number of correct predictions divided by the total number

of predictions x100) and loss (a summation of the errors, calculated via cross-entropy, made for

each sample). We chose to use cross-entropy for loss instead of negative log-likelihood since it

automatically transforms the raw outputs of the neural network into probabilities (via a softmax

activation).

Figure 5: Performance comparison of transfer learning methods. The performance of four trained transfer learning models (ResNet-50, VGG-19, MobileNetV2 and Xception, see methods) were evaluated on both validation (blue circles) and test (orange triangles) datasets. Each computational experiment was replicated five-fold (five separate training runs for each model), allowing statistical comparison of approaches. (A) Accuracy scores (the number of correct predictions divided by the total number of predictions x100). (B) Loss scores (a summation of the errors made for each sample). Statistical comparisons are summarized in Table S1.

Figure 5 illustrates that model performance varies significantly between transfer learning models (e.g. for test accuracy: ANOVA, F = 124.2, df = 3, p < 0.05. See Table S1B).

MobileNetV2 performs significantly worse than the other transfer learning models on both

accuracy and loss metrics (Tukey HSD, $p < 0.05$ on all comparisons, see Table S1C-F), while

VGG-19 performs significantly worse than ResNet and Xception on test loss (Table S1D).

ResNet and Xception do not show significantly different performance in posthoc tests (Table

S1C-F). In terms of best individual model run performance, both the top accuracy and top loss

was achieved by the ResNet model (Figure 5), so we use this as our baseline in our subsequent

analyses.

In a second round of experiments, we take the best-performing model from Figure 5 (Resnet-50),

and assess the contribution of data pre-processing, augmentation and training steps in generating

the high levels of performance illustrated in Figure 5. Table 1 illustrates that removing each

component of data augmentation leads to a significant drop in model accuracy (Tukey HSD, $p <$

0.05 on all comparisons, see Table S2B-E), and the loss of all augmentation leads to a substantial

drop in performance (38.4 +/- 7.4% validation accuracy, 34.7 +/- 7.4% test accuracy). The

removal of pre-trained weights results in a similar drop in performance.

Table 1. Performance contribution of data pre-processing, augmentation, and training. To

assess contributions, we took the trained ResNet-50 model (Figure 5) as a baseline method and

assessed the impact of removing components of our methods pipeline. Each computational

experiment was replicated five-fold (five separate training runs for each model), allowing

statistical comparison of approaches. Across replicates we report average (+/- standard deviation)

accuracy (the number of correct predictions divided by the total number of predictions x100) and

loss (a summation of the errors made for each sample). Statistical comparisons are summarized

in Table S2.

Modification to baseline (ResNet)	Validation accuracy	Validation loss	Test accuracy	Test loss
Remove rotation augmentation	76.83 ± 7.061	0.667 ± 0.368	72.12 ± 7.061	0.707 ± 0.408
Remove brightness augmentation	78.33 ± 6.982	0.618 ± 0.346	52.17 ± 7.038	1.622 ± 0.456
Remove shift augmentation	69.27 ± 7.716	0.789 ± 0.429	65.13 ± 7.716	0.829 ± 0.469
Remove shear augmentation	70.84 ± 7.431	0.761 ± 0.416	66.25 ± 7.431	0.801 ± 0.456
Remove horizontal flip augmentation	72.58 ± 7.287	0.735 ± 0.403	67.85 ± 7.287	0.775 ± 0.443
Remove zoom augmentation	71.92 ± 7.415	0.754 ± 0.413	67.08 ± 7.415	0.794 ± 0.453
Remove all augmentation	38.42 ± 7.360	2.302 ± 0.468	34.75 ± 7.360	2.372 ± 0.508
No pre-trained weights	32.81 ± 6.822	2.302 ± 0.368	29.08 ± 7.234	2.742 ± 0.541
Remove image normalization	73.52 ± 7.534	0.722 ± 0.397	68.39 ± 7.534	0.762 ± 0.437

The performance of our best performing ResNet-50 model (Figure 5) indicates that while most

classification calls are accurate, there remain a number of mistaken calls in our validation tests.

To look more closely at these errors, we present in Figure 6 a reduced confusion matrix showing

all classification errors across our five replicate runs of the ResNet-50 model. Of the 69 strains

considered in this study, only 5 were not classified with perfect precision. Strains 2 and 84 were

the most challenging for our model, attaining the lowest test accuracies of 40% and 20%

respectively. In contrast, 64 out 69 strains were classified with perfect accuracy across 5

independent model runs.

Figure 6. Reduced confusion matrix, aggregating all test data errors across five iterations of the ResNet-50 model. Of the 69 strains in this study, only 5 strains were not classified with 100% precision (the 5 rows). For brevity, this matrix includes only the strains that were misclassified by our model instead of the whole 69 x 69 confusion matrix.

Our results in Tables 1 and 2 show that D-CNN models are capable of effective bacterial colony classification down to the sub-species (strain) level, and that performance is dependent on details of data pre-processing and augmentation. This success does not rule out that other simpler models can also effectively classify strains. To establish simple model benchmarks, we next

evaluate the performance of 'shallow learning' classification models (support vector machines,

SVMs), trained on our colony metric features (Figures 3, 4), or on features extracted by our deep

learning ResNet 50 model (Table 2). These benchmarking results highlight that SVM tools

cannot match the performance of our D-CNN models (Figure 5), whether they are trained on *a*

priori identified colony metric features (Figures 3,4) or on features extracted from our successful

D-CNN models.

Table 2. Performance comparison with shallow learning (SVM) models. We contrast

validation and test accuracy for our trained ResNet model (see also Figure 5, Table S1) with

accuracy metrics for radial basis function (RBF) SVMs trained on colony metric data (Figure

3,4) and on features extracted from the trained ResNet model. See methods for details of SVM

models and feature extraction. Statistical comparisons are summarized in Table S3.

model	Validation accuracy (%)	Test accuracy (%)
ResNet 50	92.93 ± 4.831	90.73 ± 5.073
Colony metric data, RBF SVM	46.73 ± 7.532	33.43 ± 6.341
ResNet 50 feature extraction and RBF SVM	65.29 ± 1.754	62.75 ± 1.931

Discussion

Our results show that *P. aeruginosa* strains have a characteristic morphological 'fingerprint'

(Figures 2-4) that enables accurate strain classification via a custom deep convolutional neural

network (Figure 5). When trained on morphological data, our most successful model can

classify strain identity with a test accuracy that exceeds 90% despite what is considered a "data

starved" dataset. Our work points to extensions towards predicting phenotypes of interest (e.g.

antibiotic resistance, virulence), and suggests that sample size limitations may be less restrictive

than previously thought for deep learning applications in biology. In the following paragraphs we

will review these implications, while addressing caveats and next steps for this research.

The existence of a morphological 'fingerprint' that can be classified via machine learning

architecture opens the potential to relate strain identity to key phenotypes of interest, such as

antimicrobial resistance (AMR) or virulence. While species differ in their levels and types of

virulence (54), there are also significant differences in virulence between strains of the same

species (55,56). In so far as AMR or virulence is a stable and repeatable property of a strain, our

classification model could simply "look up" the recorded values in a dataset based on the strain

prediction. Yet this "look up" approach is vulnerable to variation within strains due for instance

to gain or loss in virulence factor and AMR genes, or mutations in the regulatory control of these

genes.

To address the challenge of predicting phenotypes such as virulence or AMR, a future direction

would be to extend our deep learning approach to directly predict phenotypes of interest, either

through a classification (qualitative trait) or regression (quantitative trait) framework. Our

current analysis shows that morphological 'fingerprints' are sufficient to identify individual

strains, but this does not directly imply that we can use image data to successfully predict disease

traits (analogously, human fingerprints are sufficient to identify individuals, but are not

considered predictive of human disease traits). We speculate that colony 'fingerprints' are likely

to allow for trait prediction, due to paths of common causality from bacterial modes of growth to

colony morphology and disease phenotypes. Given the established connection between biofilm

growth and antibiotic tolerance (57), it is possible that our default growth settings (Figure 2) will

reveal differences in patterning that correlate with differences in antibiotic resistance (and/or

tolerance). We further anticipate that our approach would become more discriminatory if

imaging data was also collected in the presence/absence of relevant stressors of interest (e.g.

antibiotics or immune effectors).

Deep learning methods are commonly described as 'black box' methodologies (58), presenting

challenges for model interrogation and mathematical justification for sample size requirements.

Even when classification through deep learning has a monotonically increasing prediction

accuracy, the nature of the image collection process in biological research will limit the total size

of the dataset. This is a contrast to machine learning applications in other fields that have

continually and often exponentially increasing datasets (e.g., spending habits and surveillance

cameras). Considering these challenges, arguably our best alternatives for increasing the size of

biological datasets for image-based prediction in microbiology are data augmentation and

transfer learning, which we combined in this study. Our algorithm transfers learning from the

canonical ImageNet dataset while also using standard data augmentation techniques (rotations,

shifts, zooms, shears, flips, reflections, brightness.). Future tests to explore the amount of data

needed for accurate classification could be run by reducing the size of the dataset by decreasing

the amount of data augmentation performed or by reducing the number of replicate colonies

used. Moving forward, generative adversarial networks, a class of machine learning frameworks

that learns to generate new data by competing two neural networks, is promising technique that

could supplement current data augmentation efforts (59,60).

Prior to our data augmentation, we downsampled the original dataset in order to match the image

dimensions of the ImageNet dataset which we pretrained on and to minimize computational time.

The original dataset contains colony images of 12 million to 183 million pixels (depending on

colony size) while our downsized colony images each contained a standardized 60 thousand

pixels. The success of strain classification based on these heavily down-sampled images suggests

that classification is possible based only on more 'macro' scale morphological features that are

still discriminable at this resolution. Yet this down-sampling is essentially throwing away a rich

array of more micro-scale image features (Figure 7), and so opens the possibility for future

analyses to explore these features. The inset panels in Figure 7 illustrate striking local and finer-

scale features that are present across strains. These panels suggest an additional data

augmentation option, where each colony image is processed into multiple 60K chunks, sampling

at different locations within the image and at different spatial scales. Comparing model

performance using 60K images taken at different spatial scales could provide valuable

information on what are the most diagnostic spatial scales.

Figure 7. Avenues for finer scale image segmentation and augmentation. Insets reveal finer-

scale features at smaller spatial scales.

Our analysis to date implicitly assumes that our image data represent independent samples of *P.*

aeruginosa morphology, which due to phylogenetic relationships among these strains is not the

case. A simple null expectation given these phylogenetic relationships is that strains that are

most morphologically similar (i.e., similar morphological metrics, Figure 3; and more commonly

confused in classification, Figure 6) will tend to have a shorter phylogenetic distance. Under this

phylogenetic null model, strains with minimal phylogenetic differences will have overlapping

morphological metrics and will not provide dependable classification results. We do not expect

this pattern to hold uniformly, as we know that single-gene changes can generate large-scale

changes to colony morphology (11,12,44). Future work can systematically explore the impacts of

single gene mutations through automated screening of transposon mutagenesis libraries (61),

potentially aiding in the discovery of previously unrecognized genes involved in colony / biofilm

formation. We also encourage future work applying our general methodology to sets of strains in

other species, as we expect our approach will generalize beyond the model organism *P.*

aeruginosa. In summary, the level of classification accuracy achieved in this work illustrates the

potential of image-based prediction tools, deep learning, transfer learning, and data augmentation

in the characterization of bacterial strains.

Methods

Strain Culturing

This study uses a collection of 69 clinical and environmental *P. aeruginosa* isolates (45–47),

each grown and imaged in quadruplicate. We used Luria-Bertani (LB) agar (1.5%) plates

supplemented with 0.08% Congo Red, a dye commonly used to characterize biofilm formation

which binds to compounds in the extracellular biofilm matrix. In an effort to minimize variation

in plate preparation and the age of the plates, 20ml volume plates were made 24 hours before

each experiment with a large, motorized pipette and kept in a sealed plastic sleeve at 4C. Strains

were inoculated into LB broth and incubated shaking overnight at 37C. The day of the

experiment, each plate was then sliced into 4 sections using a sterilized razor and tweezers,

which both limited colony outgrowth and prevented the diffusion of small molecules between

colonies. 5µl of the overnight culture was then spotted onto pre-prepared, sectioned LB agar

Congo Red plates. After the spots dried, plates were parafilmed to retain moisture and placed in a

37C static incubator. All strains were incubated at 37C for 72 hours, which was determined

during the pilot experiment to be enough time to reveal major morphological differences while

minimizing outward expansion.

Colony Imaging.

After 72 hours, strains were imaged on a Nikon Eclipse Ti inverted microscope at 4X using the

DS-Fi2 colored camera. This results in a pixel-to-size ratio is 2.07uM per pixel. Large, stitched

images were required to scan an entire colony and were generated with Nikon's built-in

software. Some replicate colonies had to be excluded from analysis due to error (strains 13, 47,

78, 86, 122, 124, 132, 210 have 3 replicates and strain 329 has 2 replicates). This resulted in a

dataset of 266 *P. aeruginosa* colony images that ranged in size from 12,644,652 pixels

(approximately 0.74cm x 0.74cm) to 183,329,280 pixels (approximately 2.8cm x 2.8cm).

Morphological and Complexity Metrics

For the morphological and complexity measurements, colony images were analyzed in

Mathematica. Images were scaled down by a factor of four, to make computations timelier, and

the backgrounds were cropped out by using a watershed transformation, binarization, and

selection of the contiguous non-zero area surrounding the colony. The morphological metrics

(Area, EquivalentDiskRadius, PerimeterLength, MeanCentroidDistance, Eccentricity,

Circularity, BoundingDiskCenter, and MeanCaliperDiameter) were all calculated using the

native Mathematica commands. For the complexity metrics, CompRatio was calculated by

comparing the number of bytes in the uncompressed and compressed (using the native

Mathematica command) colony images. A Sobel-Freidman operator was applied in both x and y

dimensions and Sobel histograms were generated. MeanSobel, MedianSobel, SDSobel,

RootMSSobel, SkewSobel, and KurtosisSobel were all then calculated using the native

Mathematica commands.

Data pre-processing for machine learning

Our experimental pipeline is an integration of several steps: preprocessing, transfer learning, and

data augmentation techniques, all aimed at maximizing the predictive performance of our deep

learning model. In the preprocessing phase, all images are first downsampled to a uniform size of

224x224 pixels, consistent with the image dimensions used in the pretrained ImageNet database.

To preserve the original aspect ratio and minimize distortions during the resizing process, we

employed inter-area interpolation.

In addition to resizing, another important step in our preprocessing is image normalization. This

includes two primary aspects. The first is the correction of image backgrounds: the algorithm

iterates over the images and replaces any black pixels with white ones. This process aids in

standardizing the image backgrounds across our dataset, ensuring that the model does not get

biased by variations in the background and thus enhancing its robustness to different imaging

conditions.

The second aspect of image normalization involves rescaling the pixel intensities. Raw images

are composed of pixels with intensity values that usually fall within a range of 0 to 255. These

large values may slow down the learning process and make the model more susceptible to

suboptimal solutions. To mitigate this, we applied a transformation to rescale the pixel values to

a 0-1 range. This process, often termed pixel normalization, can help improve the efficiency of

the learning process by preventing large input values from causing numerical instability and by

ensuring that the input features have a similar data distribution, thus assisting the optimization

algorithm to converge more quickly (62).

Overall, these preprocessing steps serve as an integral part of the pipeline, shaping the data into a

more suitable form for the model to learn effectively and efficiently, while ensuring robustness

to potential sources of variation.

Data augmentation

In order to further optimize our model's performance and ensure its robustness, we utilized

various data augmentation techniques. This approach, known to improve the generalization

capability of deep learning models by artificially expanding the training dataset (63), involves

making stochastic transformations to the training images, thereby mimicking variations likely to

be seen in the real-world application of the model. One such transformation was brightness

augmentation, where the brightness of the image is varied randomly within a range. Specifically,

the brightness was altered by factors between 0.2 and 0.8, effectively simulating various lighting

conditions that the images might be subjected to in real-world scenarios (64). This rescaling

process not only aids in normalizing the data but also helps in mitigating the risk of gradient

explosion, a phenomenon that can hinder the learning process (65). Random rotations within a

range of -20 to 20 degrees and random shifts in image width and height by up to 20% of the

original size are also used. These techniques simulate changes in the object's orientation and

position within the frame, thus allowing our model to learn invariance to such alterations (66).

The application of shear transformations and zoom operations, both by up to 20%, mimic the

effects of perspective distortion and changes in the object-camera distance respectively. These

techniques enhance the model's ability to recognize the subject regardless of variations in the

camera perspective or object scale (49). Finally, we also incorporated horizontal flipping of

images, a transformation especially useful for our dataset since it does not possess any inherent

left-right bias. This method doubles the size of the dataset and helps the model generalize better

by learning symmetrical features (67).

Train/validation/test split

Images from the initial 4 replicate imaging experiment were divided (following augmentation)

into a 90-10 train/validation split. The imaging protocol was repeated by a separate experimenter

to generate an independent test sample.

Transfer learning models

In our study, we employed four deep learning models to classify bacterial strains, leveraging the

advantages of both transfer learning and architectural diversity. Each model used was pre-trained

on the ImageNet dataset and further fine-tuned to our specific task. This section details the deep

learning models used, the modifications we made, and our rationale for these choices.

Before the training of any models, the topmost layer of each pre-trained model was removed, and

replaced by a new flatten layer. This was followed by two pairs of dense and dropout layers, and

finally, a softmax dense output layer. The dense layers were designed using Rectified Linear

Unit (ReLU) activations (68), while the final dense layer employs a softmax activation function.

This transforms the output into a probability distribution across 69 neurons, each corresponding

to a unique strain identification within our dataset. The resulting confidence vector is obtained

when the output layer is activated.

The decision to downsize the new dense layers from the original size (e.g., from 2048 to 1024 in

ResNet-50) was influenced by the size of our dataset in contrast to ImageNet. Dropout layers

were also incorporated to prevent overfitting, following the transfer learning research conducted

by (69).

ResNet-50

ResNet-50 (70) is known for its residual blocks, which mitigate the vanishing and exploding

gradient issues common in deep learning models. In our application, the weights of the pre-

existing layers were frozen, and only the newly added dense layers were trained - a method

known as 'feature extraction.' This method exploits the pre-trained model's ability to extract

generalized features, while the added layers learn to make predictions based on these features.

The use of ResNet-50 in bacterial strain identification tasks is well-documented. A study (71)

employed a ResNet-based approach to classify three species of gram-positive bacteria, achieving

an accuracy of 81%. Another study (72) compared the performance of various deep learning

models, including ResNet, for bacilli detection, demonstrating the efficacy of these architectures

in bacterial identification tasks. These previous successful uses of ResNet-50 provide a robust

motivation for its selection in our study.

MobileNetV2

We employed the MobileNetV2 model for its compactness and efficiency, making it suitable for

mobile and embedded vision applications (73). Similar to ResNet-50, we used the feature

extraction approach with this model.

VGG-19

The VGG-19 model (53) was also utilized in our study due to its proven efficacy in various

classification tasks. We implemented the feature extraction strategy, leveraging the learned

features from the model and fine-tuning our custom layers for our specific task.

Xception

The Xception model was incorporated due to its unique architecture, designed to recognize

nuanced patterns (74). For Xception, we adopted a 'fine-tuning' strategy, training all layers of the

network with a smaller learning rate. This allowed the model to adjust the learned weights more

accurately to our problem.

Benchmark Models

For comparison, two 'shallow learning' methods were used as benchmarks. First, a Radial Basis

Function (RBF) Support Vector Machine (SVM) was employed for strain classification using

colony metric data (Figure 3), following the successful application demonstrated by Chen et al.

(75) in bacterial classification.

Additionally, a hybrid approach was adopted to exploit the strengths of both deep and shallow

learning. Here, we extracted feature vectors from our top-performing deep learning model,

ResNet-50, which were then used as input for a RBF SVM. This process of feature extraction

involves using ResNet-50's pre-trained weights to generate a representative vector of the input

image. These vectors essentially encapsulate the critical visual patterns recognized by the model,

thus serving as robust predictors in the SVM. This hybrid approach involves loading the pre-

trained ResNet-50 model with weights trained on the ImageNet dataset and setting the

'include_top' parameter to False. This configuration returns a model that does not include the

final dense layer, making it suitable for feature extraction. An image is loaded and preprocessed

to match the input requirements of ResNet-50, and the model's 'predict' function is then used to

generate the feature vector. This feature vector is then used as input to the SVM for

classification. This transfer learning strategy has been successfully applied in numerous studies,

including Rahmayuna et al. (76), who achieved a remarkable classification accuracy of 90.33%.

Acknowledgements

We thank Jennifer Farrell for culturing the mixed community in Figure 1 and members of

the Center for Microbial Dynamics and Infection (CMDI), in particular Dr. Peter Yunker,

Dr. Conan Zhao, and Dr. Yifei Wang, for valuable comments and discussion on this work.

This research was supported by the National Science Foundation Graduate Research

Fellowship Program under grant no. DGE-1650044, the Foundation for the National

Institutes of Health grant no. 1R21AI143296, and the Foundation for the National

Institutes of Health grant no. 1R21AI156817.

References

1.   Koch R. Ueber den augenblicklichen Stand der bakteriologischen Choleradiagnose.

Zeitschrift für Hygiene und Infektionskrankheiten 1983 14:1 [Internet]. 1893 Dec [cited

2022   Jul   19];14(1):319–38.   Available   from:

https://link.springer.com/article/10.1007/BF02284324

2.   Madigan MT, Brock TD. Brock biology of microorganisms. 12th editi. Biology of
Microorganisms. San Francisco, CA: Pearson/Benjamin Cummings; 2009.

3.   Bergey D, Krieg NR, Holt JG. Bergey's manual of systematic bacteriology. Baltimore,
MD: Williams & Wilkins; 1984.

4.   Rainey PB, Travisano M. Adaptive radiation in a heterogeneous environment. Nature
1998 394:6688 [Internet]. 1998 Jul 1 [cited 2022 Jul 18];394(6688):69–72. Available
from: https://www.nature.com/articles/27900

5.   Woo PCY, Lau SKP, Teng JLL, Tse H, Yuen KY. Then and now: use of 16S rDNA gene
sequencing for bacterial identification and discovery of novel bacteria in clinical
microbiology laboratories. Clin Microbiol Infect [Internet]. 2008 [cited 2022 Jul
19];14(10):908–34. Available from: https://pubmed.ncbi.nlm.nih.gov/18828852/

6.   Yarza P, Yilmaz P, Pruesse E, Glöckner FO, Ludwig W, Schleifer KH, et al. Uniting the
classification of cultured and uncultured bacteria and archaea using 16S rRNA gene
sequences. Nat Rev Microbiol [Internet]. 2014 [cited 2022 Jul 19];12(9):635–45.
Available from: https://pubmed.ncbi.nlm.nih.gov/25118885/

7.   Woese CR. Bacterial evolution. Microbiol Rev [Internet]. 1987 Jun [cited 2022 Jul
19];51(2):221. Available from: https://www.ncbi.nlm.nih.gov/pmc/articles/PMC373105/

8.   Woese C. The universal ancestor. Proceedings of the National Academy of Sciences
[Internet]. 1998 Jun 9 [cited 2022 Jul 19];95(12):6854–9. Available from:
https://www.pnas.org/doi/abs/10.1073/pnas.95.12.6854

9.   Güell M, Yus E, Lluch-Senar M, Serrano L. Bacterial transcriptomics: what is beyond the

RNA horiz-ome? Nature Reviews Microbiology 2011 9:9 [Internet]. 2011 Aug 12 [cited

2022 Jul 19];9(9):658–69. Available from: https://www.nature.com/articles/nrmicro2620

10.   Kalziqi A, Yanni D, Thomas J, Ng SL, Vivek S, Hammer BK, et al. Immotile Active

Matter: Activity from Death and Reproduction. Phys Rev Lett [Internet]. 2018 Jan 5 [cited

2022   Jul   17];120(1):018101.   Available   from:

https://journals.aps.org/prl/abstract/10.1103/PhysRevLett.120.018101

11.   Starkey M, Hickman JH, Ma L, Zhang N, de Long S, Hinz A, et al. Pseudomonas

aeruginosa rugose small-colony variants have adaptations that likely promote persistence

in the cystic fibrosis lung. J Bacteriol [Internet]. 2009 Jun [cited 2016 May

18];191(11):3492–503. Available from: http://www.ncbi.nlm.nih.gov/pubmed/19329647

12.   Recinos DA, Sekedat MD, Hernandez A, Cohen TS, Sakhtah H, Prince AS, et al.

Redundant phenazine operons in Pseudomonas aeruginosa exhibit environment-dependent

expression and differential roles in pathogenicity. Proc Natl Acad Sci U S A [Internet].

2012   Nov   20   [cited   2022   Jul   3];109(47):19420–5.   Available   from:

www.pnas.org/cgi/doi/10.1073/pnas.1213901109

13.   Banada PP, Guo S, Bayraktar B, Bae E, Rajwa B, Robinson JP, et al. Optical forward-

scattering for detection of Listeria monocytogenes and other Listeria species. Biosens

Bioelectron. 2007 Mar 15;22(8):1664–71.

14.   Tang Y, Kim H, Singh AK, Aroonnual A, Bae E, Rajwa B, et al. Light Scattering Sensor

for Direct Identification of Colonies of Escherichia coli Serogroups O26, O45, O103,

612   O111, O121, O145 and O157. PLoS One [Internet]. 2014 Aug 19 [cited 2022 Jul 17];9(8).

613   Available from: /pmc/articles/PMC4138183/

614 15. Singh AK, Sun X, Bai X, Kim H, Abdalhaseib MU, Bae E, et al. Label-free, non-invasive

615   light scattering sensor for rapid screening of Bacillus colonies. J Microbiol Methods. 2015

616   Feb 1;109:56–66.

617 16. Alsulami TS, Zhu X, Abdelhaseib MU, Singh AK, Bhunia AK. Rapid detection and

618   differentiation of Staphylococcus colonies using an optical scattering technology. Anal

619   Bioanal Chem [Internet]. 2018 Sep 1 [cited 2022 Jul 17];410(22):5445–54. Available

620   from: https://pubmed.ncbi.nlm.nih.gov/29796901/

621 17. Zieliński B, Plichta A, Misztal K, Spurek P, Brzychczy-Włoch M, Ochońska D. Deep

622   learning approach to bacterial colony classification. PLoS One [Internet]. 2017 Sep 1

623   [cited 2022 Jul 17];12(9):e0184554. Available from:

624   https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0184554

625 18. Sousa AM, Pereira MO, Lourenço A. MorphoCol: An ontology-based knowledgebase for

626   the characterisation of clinically significant bacterial colony morphologies. J Biomed

627   Inform [Internet]. 2015 Jun 1 [cited 2022 Jul 17];55:55–63. Available from:

628   https://pubmed.ncbi.nlm.nih.gov/25817920/

629 19. Fratamico PM, Strobaugh TR, Medina MB, Gehring AG. Detection of Escherichia coli

630   0157:H7 using a surface plasmon resonance biosensor. Biotechnology Techniques 1998

631   12:7 [Internet]. 1998 [cited 2022 Aug 23];12(7):571–6. Available from:

632   https://link.springer.com/article/10.1023/A:1008872002336

633 20. Perkins EA, Squirrell DJ. Development of instrumentation to allow the detection of microorganisms using light scattering in combination with surface plasmon resonance. Biosens Bioelectron [Internet]. 2000 Jan [cited 2022 Aug 23];14(10–11):853–9. Available from: https://pubmed.ncbi.nlm.nih.gov/10945460/

637 21. Turra G, Arrigoni S, Signoroni A. CNN-Based Identification of Hyperspectral Bacterial Signatures for Digital Microbiology. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) [Internet]. 2017 [cited 2022 Jul 17];10485 LNCS:500–10. Available from: https://link.springer.com/chapter/10.1007/978-3-319-68548-9_46

642 22. Andreini P, Bonechi S, Bianchini M, Mecocci A, Scarselli F. A deep learning approach to bacterial colony segmentation. Lecture Notes in Computer Science (including subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics) [Internet]. 2018 [cited 2022 Jul 17];11141 LNCS:522–33. Available from: https://link.springer.com/chapter/10.1007/978-3-030-01424-7_51

647 23. Geirhos R, Janssen DHJ, Schütt HH, Rauber J, Bethge M, Wichmann FA. Comparing deep neural networks against humans: object recognition when the signal gets weaker. 2017 Jun 21 [cited 2022 Jul 17]; Available from: https://arxiv.org/abs/1706.06969v2

650 24. Buetti-Dinh A, Galli V, Bellenberg S, Ilie O, Herold M, Christel S, et al. Deep neural networks outperform human expert's capacity in characterizing bioleaching bacterial biofilm composition. Biotechnology Reports. 2019 Jun 1;22:e00321.

653   25.   Russakovsky O, Deng J, Su H, Krause J, Satheesh S, Ma S, et al. ImageNet Large Scale

654   Visual Recognition Challenge. Int J Comput Vis [Internet]. 2014 Sep 1 [cited 2022 Jul

655   17];115(3):211–52. Available from: https://arxiv.org/abs/1409.0575v3

656   26.   Deng J, Berg AC, Li K, Fei-Fei L. What Does Classifying More than 10,000 Image

657   Categories Tell Us? In: Proceedings of the 11th European Conference on Computer

658   Vision: Part V. Berlin, Heidelberg: Springer-Verlag; 2010. p. 71–84. (ECCV'10).

659   27.   Russakovsky O, Fei-Fei L. Attribute learning in large-scale datasets. Lecture Notes in

660   Computer Science (including subseries Lecture Notes in Artificial Intelligence and

661   Lecture Notes in Bioinformatics) [Internet]. 2012 [cited 2022 Jul 18];6553 LNCS(PART

662   1):1–14.   Available   from: https://collaborate.princeton.edu/en/publications/attribute-

663   learning-in-large-scale-datasets

664   28.   Russakovsky O, Deng J, Huang Z, Berg AC, Fei-Fei L. Detecting avocados to Zucchinis:

665   What have we done, and where are we going? Proceedings of the IEEE International

666   Conference on Computer Vision [Internet]. 2013 [cited 2022 Jul 18];2064–71. Available

667   from: https://collaborate.princeton.edu/en/publications/detecting-avocados-to-zucchinis-

668   what-have-we-done-and-where-are-w

669   29.   Balki I, Amirabadi A, Levman J, Martel AL, Emersic Z, Meden B, et al. Sample-Size

670   Determination Methodologies for Machine Learning in Medical Imaging Research: A

671   Systematic Review. Canadian Association of Radiologists Journal [Internet]. 2019 Nov 1

672   [cited   2022   Jul   17];70(4):344–53.   Available   from:

673   https://journals.sagepub.com/doi/10.1016/j.carj.2019.06.002?url_ver=Z39.88-

674   2003&rfr_id=ori%3Arid%3Acrossref.org&rfr_dat=cr_pub++0pubmed

30.   Diggle SP, Whiteley M. Microbe profile: Pseudomonas aeruginosa: Opportunistic

pathogen and lab rat. Microbiology (United Kingdom) [Internet]. 2020 Oct 10 [cited 2022

Jul 17];166(1):30–3. Available from:

https://www.microbiologyresearch.org/content/journal/micro/10.1099/mic.0.000860

31.   Moradali MF, Ghods S, Rehm BHA. Pseudomonas aeruginosa Lifestyle: A Paradigm for

Adaptation, Survival, and Persistence. Front Cell Infect Microbiol [Internet]. 2017 Feb 15

[cited 2022 Jul 17];7(FEB):39. Available from: /pmc/articles/PMC5310132/

32.   Nathwani D, Raman G, Sulham K, Gavaghan M, Menon V. Clinical and economic

consequences of hospital-acquired resistant and multidrug-resistant Pseudomonas

aeruginosa infections: A systematic review and meta-analysis. Antimicrob Resist Infect

Control [Internet]. 2014 Oct 20 [cited 2022 Jul 17];3(1):1–16. Available from:

https://aricjournal.biomedcentral.com/articles/10.1186/2047-2994-3-32

33.   Elborn JS. Cystic fibrosis. The Lancet. 2016 Nov 19;388(10059):2519–31.

34.   Pohl S, Klockgether J, Eckweiler D, Khaledi A, Schniederjans M, Chouvarine P, et al.

The extensive set of accessory Pseudomonas aeruginosa genomic components. FEMS

Microbiol Lett [Internet]. 2014 Jul 1 [cited 2022 Jul 18];356(2):235–41. Available from:

https://academic.oup.com/femsle/article/356/2/235/542446

35.   Freschi L, Vincent AT, Jeukens J, Emond-Rheault JG, Kukavica-Ibrulj I, Dupont MJ, et

al. The Pseudomonas aeruginosa Pan-Genome Provides New Insights on Its Population

Structure, Horizontal Gene Transfer, and Pathogenicity. Genome Biol Evol [Internet].

2019 Jan 1 [cited 2022 Jul 17];11(1):109–20. Available from:

https://pubmed.ncbi.nlm.nih.gov/30496396/

36.   Poulsen BE, Yang R, Clatworthy AE, White T, Osmulski SJ, Li L, et al. Defining the core

essential genome of Pseudomonas aeruginosa. Proc Natl Acad Sci U S A [Internet]. 2019

May 14 [cited 2022 Jul 17];116(20):10072–80. Available from:

/pmc/articles/PMC6525520/

37.   Lebreton F, Snesrud E, Hall L, Mills E, Galac M, Stam J, et al. A panel of diverse

Pseudomonas aeruginosa clinical isolates for research and development. JAC Antimicrob

Resist [Internet]. 2021 Sep 30 [cited 2022 Jul 18];3(4). Available from:

https://academic.oup.com/jacamr/article/3/4/dlab179/6458700

38.   Kiyaga S, Kyany'a C, Muraya AW, Smith HJ, Mills EG, Kibet C, et al. Genetic Diversity,

Distribution, and Genomic Characterization of Antibiotic Resistance and Virulence of

Clinical Pseudomonas aeruginosa Strains in Kenya. Front Microbiol. 2022 Mar 14;13:699.

39.   Kirisits MJ, Prost L, Starkey M, Parsek MR. Characterization of Colony Morphology

Variants Isolated from Pseudomonas aeruginosa Biofilms. Appl Environ Microbiol

[Internet]. 2005 Aug [cited 2022 Jul 17];71(8):4809. Available from:

/pmc/articles/PMC1183349/

40.   Ikeno T, Fukuda K, Ogawa M, Honda M, Tanabe T, Taniguchi H. Small and rough colony

pseudomonas aeruginosa with elevated biofilm formation ability isolated in hospitalized

patients. Microbiol Immunol [Internet]. 2007 [cited 2022 Jul 17];51(10):929–38.

Available from: https://pubmed.ncbi.nlm.nih.gov/17951982/

41.   Rakhimova E, Munder A, Wiehlmann L, Bredenbruch F, Tümmler B. Fitness of Isogenic

717   Colony Morphology Variants of Pseudomonas aeruginosa in Murine Airway Infection.

718   PLoS One [Internet]. 2008 Feb 27 [cited 2022 Jul 17];3(2):1685. Available from:

719   /pmc/articles/PMC2246019/

720   42.   Azimi S, Roberts AEL, Peng S, Weitz JS, McNally A, Brown SP, et al. Allelic

721   polymorphism shapes community function in evolving Pseudomonas aeruginosa

722   populations. The ISME Journal 2020 14:8 [Internet]. 2020 Apr 27 [cited 2022 Jul

723   17];14(8):1929–42. Available from: https://www.nature.com/articles/s41396-020-0652-0

724   43.   Vanderwoude J, Fleming D, Azimi S, Trivedi U, Rumbaugh KP, Diggle SP. The

725   evolution of virulence in Pseudomonas aeruginosa during chronic wound infection.

726   Proceedings of the Royal Society B [Internet]. 2020 Oct 28 [cited 2022 Jul

727   17];287(1937):20202272.   Available   from:

728   https://royalsocietypublishing.org/doi/10.1098/rspb.2020.2272

729   44.   Boucher JC, Yu H, Mudd MH, Deretic V. Mucoid Pseudomonas aeruginosa in cystic

730   fibrosis: characterization of muc mutations in clinical isolates and analysis of clearance in

731   a mouse model of respiratory infection. Infect Immun [Internet]. 1997 [cited 2022 Jul

732   20];65(9):3838–46. Available from: https://pubmed.ncbi.nlm.nih.gov/9284161/

733   45.   Pirnay JP, Bilocq F, Pot B, Cornelis P, Zizi M, van Eldere J, et al. Pseudomonas

734   aeruginosa Population Structure Revisited. PLoS One [Internet]. 2009 Nov 13 [cited 2022

735   Jul   17];4(11):e7740.   Available   from:

736   https://journals.plos.org/plosone/article?id=10.1371/journal.pone.0007740

46. Dettman JR, Rodrigue N, Aaron SD, Kassen R. Evolutionary genomics of epidemic and

nonepidemic strains of Pseudomonas aeruginosa. Proc Natl Acad Sci U S A [Internet].

2013 Dec 24 [cited 2022 Jul 17];110(52):21065–70. Available from:

www.pnas.org/cgi/doi/10.1073/pnas.1307862110

47. Shrestha SD, Guttman DS, Perron GG. Draft Genome Sequences of 10 Environmental

Pseudomonas aeruginosa Strains Isolated from Soils, Sediments, and Waters. Genome

Announc [Internet]. 2017 [cited 2022 Jul 17];5(34). Available from:

https://journals.asm.org/doi/10.1128/genomeA.00804-17

48. Mikołajczyk A, Grochowski M. Data augmentation for improving deep learning in image

classification problem. 2018 International Interdisciplinary PhD Workshop, IIPhDW

2018. 2018 Jun 18;117–22.

49. Wong SC, Gatt A, Stamatescu V, McDonnell MD. Understanding Data Augmentation for

Classification: When to Warp? 2016 International Conference on Digital Image

Computing: Techniques and Applications, DICTA 2016. 2016 Dec 22;

50. Pratt LY. Discriminability-Based Transfer between Neural Networks. In: Hanson S,

Cowan J, Giles C, editors. Advances in Neural Information Processing Systems [Internet].

Morgan-Kaufmann; 1992. Available from:

https://proceedings.neurips.cc/paper/1992/file/67e103b0761e60683e83c559be18d40c-

Paper.pdf

51.   Yu H, Winkler S. Image complexity and spatial information. 2013 5th International

757   Workshop on Quality of Multimedia Experience, QoMEX 2013 - Proceedings. 2013;12–

758   7.

759   52.   Danielsen J, Nordenfelt P. Computer vision-based image analysis of bacteria. Methods in

760   Molecular Biology [Internet]. 2017 [cited 2022 Oct 11];1535:161–72. Available from:

761   https://link.springer.com/protocol/10.1007/978-1-4939-6673-8_10

762   53.   Simonyan K, Zisserman A. Very Deep Convolutional Networks for Large-Scale Image

763   Recognition. 3rd International Conference on Learning Representations, ICLR 2015 -

764   Conference Track Proceedings [Internet]. 2014 Sep 4 [cited 2022 Jul 17]; Available from:

765   https://arxiv.org/abs/1409.1556v6

766   54.   Shaw LP, Wang AD, Dylus D, Meier M, Pogacnik G, Dessimoz C, et al. The phylogenetic

767   range of bacterial and viral pathogens of vertebrates. Mol Ecol [Internet]. 2020 Sep 1

768   [cited   2022   Jul   17];29(17):3361–79.   Available   from:

769   https://onlinelibrary.wiley.com/doi/full/10.1111/mec.15463

770   55.   Subedi D, Vijay AK, Kohli GS, Rice SA, Willcox M. Comparative genomics of clinical

771   strains of Pseudomonas aeruginosa strains isolated from different geographic sites.

772   Scientific Reports 2018 8:1 [Internet]. 2018 Oct 23 [cited 2022 Jul 17];8(1):1–14.

773   Available from: https://www.nature.com/articles/s41598-018-34020-7

774   56.   Medina-Rojas M, Stribling W, Snesrud E, Garry BI, Li Y, Gann PM, et al. Comparison of

775   Pseudomonas aeruginosa strains reveals that Exolysin A toxin plays an additive role in

virulence. Pathog Dis [Internet]. 2020 Feb 1 [cited 2022 Jul 17];78(1):10. Available from:

https://academic.oup.com/femspd/article/78/1/ftaa010/5804881

57.   Sharma D, Misba L, Khan AU. Antibiotics versus biofilm: an emerging battleground in

microbial communities. Antimicrobial Resistance & Infection Control 2019 8:1 [Internet].

2019 May 16 [cited 2022 Jul 25];8(1):1–10. Available from:

https://aricjournal.biomedcentral.com/articles/10.1186/s13756-019-0533-3

58.   Rudin C. Stop explaining black box machine learning models for high stakes decisions

and use interpretable models instead. Nature Machine Intelligence 2019 1:5 [Internet].

2019 May 13 [cited 2022 Jul 20];1(5):206–15. Available from:

https://www.nature.com/articles/s42256-019-0048-x

59.   Tolstikhin I, Bousquet O, Schölkopf B, Thierbach K, Bazin PL, de Back W, et al.

Generative Adversarial Networks. Lecture Notes in Computer Science (including

subseries Lecture Notes in Artificial Intelligence and Lecture Notes in Bioinformatics)

[Internet]. 2014 Jun 10 [cited 2022 Jul 17];11046 LNCS(NeurIPS):1–9. Available from:

https://arxiv.org/abs/1406.2661v1

60.   Radford A, Metz L, Chintala S. Unsupervised Representation Learning with Deep

Convolutional Generative Adversarial Networks. 4th International Conference on

Learning Representations, ICLR 2016 - Conference Track Proceedings [Internet]. 2015

Nov 19 [cited 2022 Jul 17]; Available from: https://arxiv.org/abs/1511.06434v2

61.   Cabeen MT, Leiman SA, Losick R. Colony-morphology screening uncovers a role for the

Pseudomonas aeruginosa nitrogen-related phosphotransferase system in biofilm

formation. Mol Microbiol [Internet]. 2016 Feb 1 [cited 2022 Jul 17];99(3):557. Available

from: /pmc/articles/PMC5130288/

62.   LeCun Y, Bottou L, Bengio Y, Haffner P. Gradient-based learning applied to document

recognition. Proceedings of the IEEE. 1998;86(11):2278–323.

63.   Perez L, Wang J. The Effectiveness of Data Augmentation in Image Classification using

Deep   Learning.   2017   Dec   13   [cited   2023   Jul   11];   Available   from:

https://arxiv.org/abs/1712.04621v1

64.   Alomar K, Aysel HI, Cai X. Data Augmentation in Classification and Segmentation: A

Survey and New Strategies. Journal of Imaging 2023, Vol 9, Page 46 [Internet]. 2023 Feb

17   [cited   2023   Jul   11];9(2):46.   Available   from: https://www.mdpi.com/2313-

433X/9/2/46/htm

65.   Ioffe S, Szegedy C. Batch Normalization: Accelerating Deep Network Training by

Reducing Internal Covariate Shift. CoRR [Internet]. 2015;abs/1502.0. Available from:

http://arxiv.org/abs/1502.03167

66.   Shorten C, Khoshgoftaar TM. A survey on Image Data Augmentation for Deep Learning.

J Big Data [Internet]. 2019 Dec 1 [cited 2023 Jul 11];6(1):1–48. Available from:

https://journalofbigdata.springeropen.com/articles/10.1186/s40537-019-0197-0

67.   Cubuk ED, Zoph B, Mané D, Vasudevan V, Le Q V. AutoAugment: Learning

Augmentation Policies from Data. CoRR [Internet]. 2018;abs/1805.0. Available from:

http://arxiv.org/abs/1805.09501

68.   Nair V, Hinton GE. Rectified Linear Units Improve Restricted Boltzmann Machines. In:

818   International Conference on Machine Learning. 2010.

819   69.   Yosinski J, Clune J, Bengio Y, Lipson H. How transferable are features in deep neural

820   networks?   CoRR   [Internet].   2014;abs/1411.1.   Available   from:

821   http://arxiv.org/abs/1411.1792

822   70.   He K, Zhang X, Ren S, Sun J. Deep Residual Learning for Image Recognition. CoRR

823   [Internet]. 2015;abs/1512.0. Available from: http://arxiv.org/abs/1512.03385

824   71.   Alhammad S, Zhao K, Jennings A, Hobson P, Smith DF, Baker B, et al. Efficient DNN-

825   Based Classification of Whole Slide Gram Stain Images for Microbiology. In: 2021

826   Digital Image Computing: Techniques and Applications (DICTA). 2021. p. 1–8.

827   72.   Shwetha V, Prasad K, Mukhopadhyay C, Banerjee B, Chakrabarti A. Automatic Detection

828   of Bacilli Bacteria from Ziehl-Neelsen Sputum Smear Images. In: 2021 2nd International

829   Conference on Communication, Computing and Industry 40 (C2I4). 2021. p. 1–5.

830   73.   Sandler M, Howard AG, Zhu M, Zhmoginov A, Chen LC. Inverted Residuals and Linear

831   Bottlenecks: Mobile Networks for Classification, Detection and Segmentation. CoRR

832   [Internet]. 2018;abs/1801.0. Available from: http://arxiv.org/abs/1801.04381

833   74.   Chollet F. Xception: Deep Learning with Depthwise Separable Convolutions. CoRR

834   [Internet]. 2016;abs/1610.0. Available from: http://arxiv.org/abs/1610.02357

835   75.   Chen Y, Yu G, Long Y, Teng J, You X, Liao BQ, et al. Application of radial basis

836   function artificial neural network to quantify interfacial energies related to membrane

fouling in a membrane bioreactor. Bioresour Technol [Internet]. 2019;293:122103.

Available from: https://www.sciencedirect.com/science/article/pii/S0960852419313331

76.   Rahmayuna N, Rahardwika D, Sari A, Setiadi DRIM, Rachmawanto E. Pathogenic

Bacteria Genus Classification using Support Vector Machine. In 2018. p. 23–7.

Supporting Information

Supplemental Figure S1. Correlation matrix for all morphological and complexity metrics.

Morphological (green) and complexity (orange) metrics.

Supplemental Table S1. Statistical comparisons of transfer learning methods (Figure 5).

The performance of four trained transfer learning models (ResNet-50, VGG-19, MobileNetV2

and Xception, see methods) were evaluated on both validation and test datasets. Each

computational experiment was replicated five-fold (five separate training runs for each model),

allowing statistical comparison of approaches.

Table S1A. Summary statistics. Across replicates we report average (+/- standard deviation)

accuracy (the **number of correct predictions divided by the total number of predictions**

x100) and loss (a summation of the errors made for each sample).

Transfer learning Method	Validation accuracy (%)	Validation loss	Test accuracy (%)	Test loss
ResNet 50	92.93 ± 4.831	0.251 ± 0.174	90.73 ± 5.073	0.278 ± 0.183
VGG-19	86.96 ± 4.033	0.448 ± 0.130	83.92 ± 4.232	0.510 ± 0.137
MobileNetV2	54.40 ± 6.252	1.853 ± 0.303	53.39 ± 6.563	2.043 ± 0.318
Xception	90.25 ± 4.561	0.300 ± 0.201	88.36 ± 4.788	0.330 ± 0.210

859　**Table S1B. ANOVA table.**

ANOVA		df	F	P-value
Validation Accuracy	4700.077255	3.0	119.531973	3.627413e-11
Test Accuracy	4571.131895	3.0	124.245285	2.698834e-11
Validation Loss	8.867851	3.0	269.70656	6.616010e-14
Test Loss	10.635474	3.0	942.817267	3.337569e-18

861　**Tables S1C-F. Post-hoc pairwise tests** (Tukey HSD with alpha = 0.05).

Supplementary Table S1C: Post Hoc Analysis for Validation Loss						
group1	group2	meandiff	p-adj	lower	upper	reject
MobileNetV2	ResNet-50 (Baseline)	-1.6076	0.0	-1.797	-1.4182	True
MobileNetV2	VGG-19	-1.4158	0.0	-1.6052	-1.2264	True
MobileNetV2	Xception	-1.5636	0.0	-1.753	-1.3742	True
ResNet-50 (Baseline)	VGG-19	0.1918	0.0467	0.0024	0.3812	True
ResNet-50 (Baseline)	Xception	0.044	0.9088	-0.1454	0.2334	False

VGG-19	Xception	-0.1478	0.1567	-0.3372	0.0416	False

Supplementary Table 1D: Post Hoc Analysis for Test Loss

group1	group2	meandiff	p-adj	lower	upper	reject
MobileNetV2	ResNet-50 (Baseline)	-1.7704	0.0	-1.8814	-1.6594	True
MobileNetV2	VGG-19	-1.5342	0.0	-1.6452	-1.4232	True
MobileNetV2	Xception	-1.7116	0.0	-1.8226	-1.6006	True
ResNet-50 (Baseline)	VGG-19	0.2362	0.0001	0.1252	0.3472	True
ResNet-50 (Baseline)	Xception	0.0588	0.4513	-0.0522	0.1698	False
VGG-19	Xception	-0.1774	0.0016	-0.2884	-0.0664	True

Supplementary Table 1E: Post Hoc Analysis for Validation Accuracy

group1	group2	meandiff	p-adj	lower	upper	reject
MobileNetV2	ResNet-50 (Baseline)	37.688	0	31.1371	44.2389	True
MobileNetV2	VGG-19	32.128	0	25.5771	38.6789	True
MobileNetV2	Xception	35.502	0	28.9511	42.0529	True
ResNet-50 (Baseline)	VGG-19	-5.56	0.1115	-12.1109	0.9909	False
ResNet-50 (Baseline)	Xception	-2.186	0.7763	-8.7369	4.3649	False
VGG-19	Xception	3.374	0.4751	-3.1769	9.9249	False

Supplementary Table 1F: Post Hoc Analysis for Test Accuracy

group1	group2	meandiff	p-adj	lower	upper	reject
MobileNetV2	ResNet-50 (Baseline)	37.13	0	30.7933	43.4667	True
MobileNetV2	VGG-19	31.206	0	24.8693	37.5427	True
MobileNetV2	Xception	35.342	0	29.0053	41.6787	True
ResNet-50 (Baseline)	VGG-19	-5.924	0.0711	-12.2607	0.4127	False
ResNet-50 (Baseline)	Xception	-1.788	0.8501	-8.1247	4.5487	False
VGG-19	Xception	4.136	0.2801	-2.2007	10.4727	False

Supplemental Table S2. Performance contribution of data pre-processing, augmentation and training. To assess contributions we took the trained ResNet-50 model (Figure 5, Table S1A) as a baseline method, and assessed the impact of removing components of our methods pipeline. Five-fold replicated results are summarized in Table 1.

Supplemental Table S2A. ANOVA table of data in table 1.

869
870

ANOVA	sum_sq	df	F	P-value
Validation Accuracy	14795.48945	9.0	278.010813	3.655742e-33
Test Accuracy	14972.050258	3.0	241.435997	5.808255e-32
Validation Loss	30.322865	3.0	782.2722	4.790182e-42
Test Loss	40.431932	3.0	977.413531	5.719771e-44

Supplemental Table S2B-E. Post-hoc pairwise tests (Tukey HSD with alpha = 0.05).
874

Table S2B. Post Hoc Analysis for Validation Loss						
Group 1	Group 2	Meandiff	p-adj	Lower	Upper	Reject
No pre-trained weights	Resnet-50	-2.0578	0	-2.1968	-1.9188	TRUE
Remove all augmentation	Resnet-50	-0.457	0	-0.596	-0.318	TRUE
Remove brightness augmentation	Resnet-50	-0.3572	0	-0.4962	-0.2182	TRUE
Remove horizontal flip augmentation	Resnet-50	-2.0254	0	-2.1644	-1.8864	TRUE
Remove image normalization	Resnet-50	-0.457	0	-0.596	-0.318	TRUE
Remove rotation augmentation	Resnet-50	-0.3844	0	-0.5234	-0.2454	TRUE

Group 1	Group 2	Meandiff	p-adj	Lower	Upper	Reject
Remove shear augmentation	Resnet-50	-0.4578	0	-0.5968	-0.3188	TRUE
Remove shift augmentation	Resnet-50	-0.5098	0	-0.6488	-0.3708	TRUE
Remove zoom augmentation	Resnet-50	-2.0628	0	-2.2018	-1.9238	TRUE

Table S2C. Post Hoc Analysis for Test Loss

Group 1	Group 2	Meandiff	p-adj	Lower	Upper	Reject
No pre-trained weights	Resnet-50	-2.5482	0	-2.6917	-2.4047	TRUE
Remove all augmentation	Resnet-50	-0.532	0	-0.6755	-0.3885	TRUE
Remove brightness augmentation	Resnet-50	-1.3998	0	-1.5433	-1.2563	TRUE
Remove horizontal flip augmentation	Resnet-50	-2.082	0	-2.2255	-1.9385	TRUE
Remove image normalization	Resnet-50	-0.532	0	-0.6755	-0.3885	TRUE
Remove rotation augmentation	Resnet-50	-0.4308	0	-0.5743	-0.2873	TRUE
Remove shear augmentation	Resnet-50	-0.5532	0	-0.6967	-0.4097	TRUE
Remove shift augmentation	Resnet-50	-0.609	0	-0.7525	-0.4655	TRUE
Remove zoom augmentation	Resnet-50	-2.5482	0	-2.6917	-2.4047	TRUE

Table S2C. Post Hoc Analysis for Validation Accuracy

Group 1	Group 2	Meandiff	p-adj	Lower	Upper	Reject
No pre-trained weights	Resnet-50	59.004	0	53.8552	64.1528	TRUE
Remove all augmentation	Resnet-50	52.004	0	46.8552	57.1528	TRUE
Remove brightness augmentation	Resnet-50	12.416	0	7.2672	17.5648	TRUE
Remove horizontal flip augmentation	Resnet-50	17.94	0	12.7912	23.0888	TRUE
Remove image normalization	Resnet-50	16.888	0	11.7392	22.0368	TRUE
Remove rotation augmentation	Resnet-50	13.704	0	8.5552	18.8528	TRUE
Remove shear augmentation	Resnet-50	19.738	0	14.5892	24.8868	TRUE
Remove shift augmentation	Resnet-50	21.358	0	16.2092	26.5068	TRUE
Remove zoom augmentation	Resnet-50	18.738	0	13.5892	23.8868	TRUE

Table S2E. Post Hoc Analysis for Test Accuracy

Group 1	Group 2	Meandiff	p-adj	Lower	Upper	Reject
No pre-trained weights	Resnet-50	62.322	0	56.7641	67.8799	TRUE
Remove all augmentation	Resnet-50	55.274	0	49.7161	60.8319	TRUE
Remove brightness augmentation	Resnet-50	38.774	0	33.2161	44.3319	TRUE
Remove horizontal flip augmentation	Resnet-50	22.868	0	17.3101	28.4259	TRUE
Remove image normalization	Resnet-50	21.726	0	16.1681	27.2839	TRUE
Remove rotation augmentation	Resnet-50	18.506	0	12.9481	24.0639	TRUE
Remove shear augmentation	Resnet-50	24.6	0	19.0421	30.1579	TRUE
Remove shift augmentation	Resnet-50	26.584	0	21.0261	32.1419	TRUE
Remove zoom augmentation	Resnet-50	23.264	0	17.7061	28.8219	TRUE

Supplemental Table S3. Performance comparison with shallow learning (SVM) models.

We contrast validation and test accuracy for our trained ResNet model (see also Table 1) with

accuracy metrics for radial basis function (RBF) SVMs trained on colony metric data (Figure

3,4) and on features extracted from the trained ResNet model. See methods for details of SVM

models and feature extraction.

Supplemental Table S3A: ANOVA of Table 2.

ANOVA	sum_sq	df	F	P-value
Validation Accuracy	5268.1030	9.0	324.059336	3.608738e-11
Test Accuracy	7869.885293	3.0	909.536437	7.922344e-14

884 **Supplemental Table S3B-E. Post-hoc pairwise tests (Tukey HSD with alpha = 0.05).**

Table S3B. Post Hoc Analysis for Validation Accuracy:

Group 1	Group 2	Mean Difference	p-adj	Lower	Upper	Reject
Colony metric data, RBF SVM	ResNet-50	45.73	0	40.9195	50.5405	TRUE
Colony metric data, RBF SVM	ResNet 50 feature extraction and RBF SVM	19.4	0	14.5895	24.2105	TRUE
ResNet 50 feature extraction and RBF SVM	ResNet-50	26.33	0	21.5195	31.1405	TRUE
Table S3C. Post Hoc Analysis for Test Accuracy:						
Group 1	Group 2	Mean Difference	p-adj	Lower	Upper	Reject
Colony metric data, RBF SVM	ResNet-50	56.094	0	52.5844	59.6036	TRUE
Colony metric data, RBF SVM	ResNet 50 feature extraction and RBF SVM	29.078	0	25.5684	32.5876	TRUE
ResNet 50 feature extraction and RBF SVM	ResNet-50	27.016	0	23.5064	30.52	TRUE

885