Localizing post-admixture adaptive variants with object detection on ancestry-painted chromosomes

Iman Hamid[1], Katharine L. Korunes[1], Daniel R. Schrider[2], Amy Goldberg[1],*

[1]Department of Evolutionary Anthropology, Duke University, Durham, North Carolina, USA
[2]Department of Genetics, University of North Carolina, Chapel Hill, North Carolina, USA
*Correspondence: amy.goldberg@duke.edu

Abstract: Gene flow between previously isolated populations during the founding of an admixed or hybrid population has the potential to introduce adaptive alleles into the new population. If the adaptive allele is common in one source population, but not the other, then as the adaptive allele rises in frequency in the admixed population, genetic ancestry from the source containing the adaptive allele will increase nearby as well. Patterns of genetic ancestry have therefore been used to identify post-admixture positive selection in humans and other animals, including examples in immunity, metabolism, and animal coloration. A common method identifies regions of the genome that have local ancestry 'outliers' compared to the distribution across the rest of the genome, considering each locus independently. However, we lack theoretical models for expected distributions of ancestry under various demographic scenarios, resulting in potential false positives and false negatives in ancestry outlier approaches. Further, ancestry patterns between distant sites are often not independent. As a result, current methods tend to infer wide genomic regions containing many genes as under selection, limiting biological interpretation. Instead, we develop a deep learning object detection method applied to images generated from local ancestry-painted genomes. This approach preserves information from the surrounding genomic context and avoids potential pitfalls of user-defined summary statistics. We find the method is robust to a variety of demographic misspecifications using simulated data. Applied to human genotype data from the admixed population of Cabo Verde, we localize a known adaptive locus to a single narrow region compared to multiple or long windows obtained using two other ancestry-based methods.

Introduction

Genetic exchange between previously separated populations is ubiquitous across species (Moran et al., 2021; Payseur & Rieseberg 2016), often referred to as 'admixture' or 'hybridization' when moderate- to large-scale movements of individuals create new populations with ancestors from multiple source populations. In admixed populations, genetic ancestry varies between individuals and along the chromosome within individuals (Aguillon et al., 2022; Gopalan et al., 2022; Hellenthal et al., 2014). Across the tree of life, variation in genetic ancestry shapes genetic and phenotypic variation, such as differences in disease risk between populations. Small amounts of gene flow or larger admixture may introduce advantageous alleles which then undergo positive selection. Such cases have been identified in diverse taxa, often termed adaptive introgression (Aguillon et al., 2022; Edelman & Mallet 2021; Hedrick, 2013; Hsieh et al., 2019; Huerta-Sánchez et al., 2014; Moran et al., 2021; Norris et al., 2015; Oziolor et al., 2019; Racimo et al., 2015; Whitney et al., 2006) or, in humans, post-admixture positive selection (Cuadros-Espinoza et al., 2022; Gopalan et al., 2022; Tang et al., 2007).

Despite the ubiquity and biological importance of admixture, understanding evolutionary processes in admixed populations remains challenging (Gopalan et al., 2022; Moran et al., 2021). Classical methods to detect selection may pick up signatures of pre-admixture selection, and are often confounded by the process of admixture, which can increase linkage disequilibrium (LD) and change the distribution of allele frequencies (Cuadros-Espinoza et al., 2022; Lohmueller et al., 2010, 2011; Yelman et al., 2021). Yet, because admixture can introduce advantageous alleles at intermediate frequencies, post-admixture selection provides an opportunity for particularly rapid adaptation on the scale of tens or hundreds of generations (Hellenthal et al., 2016; Hamid et al., 2021). Thus, methods tailored to the genetic signatures of admixed populations are important to investigate the extent and impact of post-admixture adaptation across many organisms.

Recent methods have advanced our ability to identify regions of admixed genomes containing haplotypes under positive selection by using patterns of genetic ancestry. When one source population provides a beneficial allele, we expect that, as the beneficial allele increases in frequency, linked alleles from the source population will hitchhike along with it, and thereby the proportion of admixed individuals with ancestry from that source population at the selected locus (i.e. the local ancestry proportion) increases too. This logic has been leveraged to detect selection in recently admixed populations by identifying outliers in local ancestry proportion compared to a genome-wide average. Applied to human populations, variations on ancestry outlier detection have identified genomic regions associated with a range of phenotypic traits potentially underlying adaptation, including response to high altitude, diet, pigmentation, immunity, and disease susceptibility (Bryc et al., 2010; Bryc et al., 2015; Busby et al., 2016; Busby et al., 2017; Cuadros-Espinoza et al., 2022; Fernandes et al., 2019; Hamid et al., 2021; Isshiki et al., 2021; Jeong et al., 2014; Jin et al., 2012; Laso-Jadart et al., 2017; Lopez et al., 2019; Norris et al., 2020; Patin et al., 2017; Pierron et al., 2018; Rishishwar et al., 2015; Tang et al., 2007; Triska et al., 2015; Vicuña et al., 2020; Zhou et al., 2016).

This ancestry outlier detection approach is useful for identifying regions that may be under selection, but it can yield false positives due to long-range LD from the source populations or allele frequencies drifting as a result of serial founder effects, and the criteria for determining outliers is difficult (Bhatia et al., 2014; Buby et al., 2017; Price et al., 2008); false negatives may also occur if the number of true adaptive events is greater than the number of outliers retained. Importantly, the ancestry outlier approach discards the wealth of information from the surrounding genomic context. Along-genome spatial patterns of ancestry, such as the distribution of ancestry tract lengths containing a selected locus, may be informative about selection on this timescale in admixed populations. The length of ancestry tracts is influenced by the timing and strength of selection, analogous to the increase in LD in around selective sweeps in homogeneous populations (Kelley

1997; Kim & Nielsen, 2004; Sabeti et al., 2002; Voight et al., 2006). Similarly, strong selection can influence ancestry patterns along long stretches of the genome, often in complex patterns depending on the evolutionary scenario (Hamid et al., 2021; Shchur et al., 2020). However, information about the complex patterns of ancestry around a selected locus is lost when relying on summary statistics, and there is a bias inherent in the user's choice of quantitative summaries to include during inference. More generally, we lack theoretical expectations for patterns of ancestry expected under post-admixture selection, especially under a range of selective and demographic histories.

To overcome the loss of spatial information along the genome and the simplifying assumptions of classical summary statistics, deep learning techniques have been increasingly used in population genetics. Deep learning algorithms are multi-layered networks trained on example datasets with known response variables with the goal of learning a relationship between the input data and output variable(s) (applications to population genetics reviewed in Schrider & Kern (2018). Deep learning techniques are flexible with respect to data type and the specific task at hand, and have been shown to be effective for inferring demographic histories (Flagel et al., 2019; Sanchez et al., 2021; Sheehan & Song, 2016; Wang et al., 2021), recombination rates (Adrion et al., 2020; Chan et al., 2018; Flagel et al., 2019), and natural selection (Gower et al., 2021; Kern & Schrider, 2018; Sheehan & Song, 2016). Among the branches of deep learning, computer vision methods are a family of techniques originally developed to recognize images by using convolutional neural networks (CNNs) (Krizhevsky et al., 2012; LeCun et al., 2015; Lecun & Bengio, 1995). CNNs learn from complex spatial patterns in large datasets through a series of filtering and down sampling operations that compress the data into features that are informative for inference. CNNs have recently been applied to images of genotype matrices for population genetic inference with great success (Battey et al., 2020; Battey et al., 2021; Blischak et al., 2021; Chan et al., 2018; Flagel et al., 2019; Gower et al., 2021; Isildak et al., 2021; Sanchez et al., 2021; Torada et al., 2019). In doing so, researchers can circumvent the loss of information and bias from using user-defined population genetic summary statistics and make inferences for study systems and questions for which we lack theoretical expectations.

Here, we build on recent successes in deep learning applications to population genetics problems and develop a deep learning object detection strategy that localizes genomic regions under selection from images of chromosomes 'painted' by ancestry (Figure 1) (Lawson et al., 2012; Maples et al., 2012). In using local ancestry rather than the genotypes directly, we focus on post-admixture processes and are potentially well-suited to low coverage or sparse SNP data common in non-model systems (Schaefer et al., 2016; Schaefer et al., 2017; Schumer et al., 2020; Wall et al., 2016). Using this approach, we demonstrate that complex ancestry patterns beyond single-locus summary statistics are informative about selection in recently admixed populations. We take advantage of existing deep learning object detection frameworks, illustrating the ease of use and accessibility of deep learning applications for population genetic researchers without experience in machine learning techniques. In simulated as well as human SNP data, we show that our method is able to localize regions under positive selection post admixture, and remains effective at identifying selection under a range of demographic misspecifications. We focus on scenarios with moderate to high admixture contributions occurring in the last tens to hundreds of generations; multiple other methods have recently been developed focused on older admixture scenarios at low admixture contribution rates, often termed adaptive introgression (Gower et al., 2021; Racimo et al., 2017; Setter et al., 2020; Svedberg et al., 2021).

Figure 1. Schematic of our baseline simulation scenario. Image input for the object detection model is generated by sampling 200 ancestry-painted chromosomes from a simulated admixed population. Rows represent individuals, with chromosome position along columns. Training samples have a known "target" bounding box (yellow box), spanning an 11-pixel window centered on the position of the known beneficial variant. Using training examples, the object detection model learns the complex patterns of ancestry indicative of positive selection post-admixture and uses this information to localize a beneficial variant to a small genomic region. The trained object detection model is then expected to output bounding boxes that contain variants under selection.

Results

Baseline Model Performance

We first describe the object detection method's performance in a baseline simulated scenario, before exploring the effects of model misspecification and finally comparing the method to other approaches. Full details on simulations, image generation, model training, and performance metrics are in Materials and Methods. Briefly, in the baseline scenario, we simulated a single-pulse admixture event between two isolated source populations. One source population was fixed for a beneficial variant randomly placed along the 50 Mb chromosome tract, with positive selection strength post admixture drawn from a uniform distribution $s \sim U(0, 0.5)$. For each simulation, we generated two images representing two types of genetic data that a user may be analyzing: one with full local ancestry (the "whole genome" scenario) representing whole-genome, high-density SNP, or similar data, and the second scenario with only 100 ancestry informative markers (AIMs, the "low resolution" scenario) in the 50 Mb. We then trained and validated the method for each of these two sets of images. Performance metrics included precision and recall (P-R), the proportion of inferred bounding boxes that contain the true selected variant, the average width of the inferred bounding boxes, and the average number of inferred bounding boxes per image.

Overall, the locus simulated to be under positive selection was contained within the inferred bounding box ~95% of the time in both the whole genome and low resolution scenarios (Table 1 & Figure 2). As expected, the whole genome ancestry scenario had higher precision and recall across the range of detection thresholds (Figure 2), though both had P-R curves well above a no-skill (random) classifier.

Figure 2. Precision-Recall curves for high (full) and low (AIMs) ancestry resolution images across a range of detection thresholds. Area under the curve (AUC) is calculated for the two scenarios, with the no-skill classifier indicated by the dashed black line.

Table 1. Performance of object detection method on images with high and low ancestry resolution.

ancestry resolution	proportion of variants detected	average width	average number of bounding boxes	precision	recall	AUC
high (whole genome)	0.950	10.830	1.027	0.886	0.897	0.871
low (100 AIMs)	0.946	10.829	0.998	0.871	0.861	0.800

Model Misspecification

Often, we do not know the full model and parameters of a population's history. We tested the robustness of our method to several demographic model misspecifications, performing inference based on images generated from simulations that differed in model and/or parameter from the ones used to generate training images. Generally, we followed the "whole genome" ancestry baseline scenario described above and in the Materials and Methods, and altered one aspect of the admixed population's history for each scenario. We separately altered parameters for the admixture proportion, the number of generations since admixture occurred, as well as different models of the population size trajectory (bottleneck with a return to original size, expansion, or contraction). We also considered a scenario in which both source populations have the beneficial mutation segregating at a frequency of 0.5 at the time of admixture (i.e. $F_{ST} = 0$ between the source populations at this allele) (see also Gopalan et al., 2022 for post-admixture positive selection simulations under different F_{ST} values between sources at the adaptive locus)

That is, we trained the model once under the baseline scenario, and then conducted inference on simulated versions that represent empirical data under different evolutionary scenarios. We then evaluated performance using the same set of metrics as described above for the baseline model, presented in Table 2 & Figure S1. Under these demographic misspecifications, the model was still able to detect 80-98% of variants under selection, except in two scenarios where the impact of selection on patterns of local ancestry is expected to be very weak or entirely absent (Table 2).

First, the model underperforms when contributing ancestry proportions was varied such that we inferred from images generated under an admixture scenario with 90% ancestral contribution from the source population providing the beneficial allele ($m = 0.9$). In this scenario the method has difficulty detecting regions under selection resulting in a high rate of false negatives (Figure S1A) because, even in regions unaffected by selection, the image is primarily one color by the end of 50 generations. We do not see this effect in the opposite scenario involving 10% ancestral contribution from the source population providing the beneficial allele ($m = 0.1$). In this scenario, the beneficial allele increasing in frequency results in the "minor" image color increasing specifically around that region.

Second, the model also underperforms when the two source populations carry the beneficial allele at the same frequency ($F_{ST} = 0$). The performance of the model under this misspecification follows the no-skill classifier (Figure S1D), suggesting the model is randomly assigning bounding boxes. In this case, the model is unable to detect any ancestry-based patterns of selection because both ancestries are being equally selected. We have previously suggested and demonstrated this same result with other ancestry-based signatures of selection (Gopalan et al., 2022; Hamid et al., 2021).

Table 2. Performance of object detection method on images generated from demographic misspecifications. Further details of models in Materials and Methods. The two scenarios that perform poorly are marked (*).

misspecification	proportion of variants detected	average width	average number of bounding boxes	precision	recall	AUC
none (baseline)	0.950	10.830	1.027	0.886	0.897	0.871
m = 0.1	0.796	10.780	0.815	0.944	0.760	0.766
m = 0.25	0.885	10.869	0.947	0.912	0.846	0.859
m = 0.75	0.827	10.852	0.862	0.876	0.753	0.713
m = 0.9*	0.109	10.845	0.248	0.376	0.093	0.057
gen = 25	0.859	10.827	1.007	0.794	0.783	0.750
gen = 100	0.978	10.816	1.014	0.915	0.916	0.881
Fst = 0*	0.047	10.838	1.293	0.059	0.063	0.015
bottleneck (50%)	0.951	10.767	1.024	0.885	0.893	0.861
bottleneck (10%)	0.941	10.824	1.023	0.869	0.878	0.845
expansion	0.952	10.860	1.030	0.880	0.896	0.860
contraction	0.943	10.819	1.032	0.873	0.886	0.861

Comparison ancestry outlier detection

We next sought to evaluate whether our method constitutes an improvement on the most commonly used method for detecting regions under selection for admixed populations. The 'local ancestry outlier' approach identifies regions that deviate from the genome-wide average ancestry proportion, which are hypothesized to be enriched for regions under selection (Bryc et al., 2010; Gopalan et al., 2022; Tang et al., 2007). We compared performance between ancestry outlier detection and our method by calculating precision and recall, including over a range of selection coefficients (Table 3 & Figure 3B-E). For each genomic window, we additionally calculated the proportion of simulations that were classified as being "under selection" at that region as a measure of localization ability (Figure 3A). The local ancestry approach has much lower precision resulting from increased false positives, even in scenarios with greater selection strength (Table 3 & Figure 3B&C). This is further visualized in Figure 3A, where the object detection method detects a narrower region under selection (~3 Mb) compared to the local ancestry outlier approach (~8 Mb). The width of the inferred region in object detection is highly determined by the bbox size in training data, as well as window length and input image size so it is likely possible to narrow the inferred region further.

Table 3. Performance of object detection and local ancestry outlier methods.

method	proportion of variants detected	average width	average number of bboxes	precision	recall
object detection	0.948	10.990	1.037	0.875	0.890
local ancestry outlier	-	-	-	0.542	0.901

Figure 3. Comparison of local ancestry outlier approach and object detection method. A) Heatmap showing, for each genomic window, the proportion of simulations that had that region classified as "under selection" by either the object detection (top) or local ancestry outlier (bottom) methods. The position of the true selected variant is indicated by the vertical dashed red line. Precision across a range of selection coefficients (s) for the B) local ancestry outlier approach and C) the object detection method. Recall across a range of selection coefficients (s) for the D) local ancestry outlier approach and E) object detection method.

Application to human genotype data from Cabo Verde

We next tested the object detection method on human genotype data from the admixed population of Santiago, Cabo Verde using genotype data from 172 individuals at ~800k SNPs genome-wide (Beleza et al., 2013). We previously showed multiple lines of evidence for adaptation in this dataset at the Duffy-null that is protective against *P. vivax* malaria, including ancestry outlier detection and a statistic that incorporates the length of tracts as well as their frequency, *iDAT*; this allele is common in African ancestry and rare in Portuguese ancestry (Hamid et al., 2021). This locus has been a candidate for post-admixture positive selection in multiple other populations as well (Busby et al., 2017; Fernandes et al., 2019; Hodgson et al., 2014; Laso-Jadart et al., 2017; Pierron et al., 2018; Triska et al., 2015).

Figure 4 shows that all three methods detect an adaptive locus in the nearby region; the object detection approach is highly specific, returning a single bbox approximately centered on the adaptive locus (center is ~130 kb from truth), whereas the ancestry-outlier approach returns multiple nearby hits across ~48 Mb (outliers sum to ~6 Mb). iDAT finds one region as an outlier spanning ~12 Mb and not centered on the locus under selection. The nearby centromere may be extending the window that ancestry outlier detection identifies as under selection by repressing recombination. We generated the image of ancestry on Santiago using genetic distances so the object detection approach is less sensitive to recombination variation without needing to explicitly model recombination variation in the training data.

Notably, inference was conducted using the pre-trained baseline model whose demographic and genomic scenario differs from that in Cabo Verde. Specifically, the training model included 50% ancestry contributions from each source 50 generations ago; Santiago is estimated to have a 73% African ancestry contribution about 22 generations ago (Hamid et al., 2021; Korunes et al., 2022). We also trained on a 50 Mb window and applied the method to the whole ~250 Mb chromosome 1. Despite these substantial differences, the method performs well, suggesting it can be used widely for populations without well-studied demographic histories. Further, leveraging the general applicability of the baseline model, we made the pre-trained baseline model available online at
https://huggingface.co/spaces/imanhamid/ObjectDetection_AdmixtureSelection_Space (see Data and Code Availability). Users can upload an image of painted chromosomes and quickly use the pre-trained set to get inferred adaptation under our method.

Figure 4. Identification of a known adaptive allele in a human population using multiple ancestry-based methods. We compare multiple methods to detect a well-known example of post-admixture positive selection in the admixed human populations from Santiago, Cabo Verde on the Duffy-null allele protective against *P. vivax* malaria (Hamid et al., 2021). (A) *iDAT* from Hamid et al., 2021, (B) ancestry outlier detection using a 3 standard deviation cutoff, and (C) the object detection approach developed in this paper. African ancestry in black and European ancestry in white. The image represents the entirety of chromosome 1 for 172 individuals. The dashed line indicates the position of the adaptive allele. The inferred bbox using object detection (C) is in yellow, closely matching the true bbox centered on the adaptive allele (red) in size and location. The other two methods infer multiple and/or longer regions as potentially under selection.

Discussion

We developed a deep learning object detection strategy to detect and localize within the genome post-admixture positive selection based on images of chromosomes painted by local genetic ancestry. Our results demonstrate the power gained when including spatial patterns of ancestry beyond single locus summary statistics, and emphasize the need for further development of methods tailored to populations that do not fit the expectations of classical population genetics methods.

Our object detection approach can leverage complex local ancestry patterns without discarding information about the surrounding genomic context or requiring user choice of statistics. Using simulated and empirical human genetic data from Cabo Verde, we show that our framework better localizes the adaptive locus to a narrower genomic window and is less prone to false positives compared to common ancestry outlier approaches (Figures 3, 4). We expect many empirical examples to actually perform better than this case study because admixture is so recent (~22 generations) and strong ($s = 0.08$ from Hamid et al., 2021) with ~73% admixture contributions from the source with the adaptive allele, which together produce extremely long stretches of African ancestry often spanning the entirety of chromosome 1 reminiscent of the poor performance observed in Table 2 for $m = 0.9$. In both simulated data and our empirical example, the object detection approach remains generally effective at identifying selection even when we misspecify aspects of demographic history such as admixture proportion, admixture timing, and population size trajectory. That is, we expect strong performance on empirical data even without knowing the full details of an admixed population's history. The size of the window that our method identifies will depend on the chromosome size, input image size, and choice of bbox size used in training. It may indeed be possible to identify a narrower window for a small chromosome, a larger image, or if we train with smaller target boxes. The midpoint of the bbox is a reasonable metric for a point estimate for the location of the adaptive locus.

Despite the overall strong performance of the method, we note several potential pitfalls and areas where future work could make this type of approach more generalizable. A primary barrier to effective implementation is the availability and accuracy of local ancestry calls. As with all ancestry-based approaches, such as ancestry outlier scans, local ancestry calling is a necessary prerequisite for this method. Many tools exist to infer local ancestry along admixed chromosomes, including recent developments for samples in which it is difficult to confidently call genotypes because of low or sparse coverage (Schaefer et al., 2016; Schaefer et al., 2017; Schumer et al., 2020; Wall et al., 2016). Still, local ancestry calling remains potentially challenging, especially in nonmodel systems, and the quality of local ancestry estimates often depends on reference dataset availability and the degree of differentiation between source populations. Notably, we tested our object detection strategy using phased ancestry haplotypes, and further work is needed to address the effects of phase errors. Phasing accuracy can be sensitive to factors such as the availability of reference panels, the number of unrelated individuals present in the sample, and the choice of phasing method (Browning & Browning, 2011). We recommend that researchers hoping to take ancestry-based approaches to detecting selection first confirm the validity of their local ancestry calls, for example by first simulating admixed haplotypes from genomes representing proxies for source populations and testing local ancestry assignment accuracy (Schumer et al., 2020; Williams, 2016). Though local ancestry calling is necessary, the similar performance of the object detection method in the whole genome and low resolution ancestry scenarios demonstrates the utility of our method for a variety of organisms or situations where a limited set of markers are available for assigning local ancestry.

Ancestry-based methods such as the one presented here that leverage long stretches of higher than expected frequency are well-suited to detect selection on short timescales; we focus on history within a couple hundred generations after admixture and selection onset. For admixture more than a few hundred generations

old, the length of ancestry tracts will decay due to recombination over time. As local ancestry at distant sites is decoupled over generations, detectable signatures of long ancestry tracts or high ancestry proportion in a large genomic region surrounding a variant under selection are less likely. Therefore, ancestry-based approaches are better suited for detecting post-admixture selection on the scale of tens to hundreds of generations since admixture.

Our use of out-of-the box object detection frameworks demonstrates that population genetics researchers can apply deep learning applications without prior experience with machine learning techniques. We required only ~1.5 hours to train the object detection method on 8000 images. To train on 800 images, it only took ~15 minutes with comparably high performance (~90% of selected variants detected vs ~95% with more training examples), making optimization and troubleshooting on small training sets possible in a reasonable timeframe before scaling up to a larger final dataset. Additionally, with the availability of free GPU access via platforms such as Google Colab, deep learning methodology is accessible to researchers without the means or desire to buy their own GPU or pay for access to a remote server. The same training set can be used for multiple regions of the genome and for multiple populations given the limited impact of model misspecification. More generally, the success of our approach suggests that researchers should consider object detection methods for other problems in detecting selection and population genetics.

Materials and Methods

Simulations

      Simulated data were generated with the forward simulator SLiM 3, combined with tree-sequence recording to track and assign local ancestry (Haller et al., 2019; Haller & Messer, 2019). For our baseline scenario, we considered a single-pulse admixture event between two source populations (Figure 1). One source population was fixed for a beneficial mutation randomly placed along a 50 Mb chromosome, with selection strength drawn from a uniform distribution ranging from 0 to 0.5. The newly admixed population had a population size N of 10000, with 50% ancestral contribution from each source. That is, the range of Ns is in [0,5000]. Tree sequence files were output after 50 generations.

Ancestry Image Generation

      For each simulation, we used *tskit* to read the tree sequence files and extract local ancestry information for 200 sampled chromosomes from 100 diploid individuals from the admixed population (Haller et al., 2019; Kelleher et al., 2016, 2018). We then used R to generate a black and white 200x200 pixel image of the entire set of sampled chromosomes for each simulation (y-axis representing sampled chromosomes, x-axis representing genomic position), with each position colored by local ancestry for that individual chromosome. In these images, "black" represented ancestry from the source population that was fixed for the beneficial mutation, and "white" represented the other source population.

      For our whole genome, or "full ancestry" images, we used true local ancestry at every position. For our low-resolution ancestry images, we used the same simulations but instead only assigned local ancestry at 100 randomly dispersed markers to generate images. We used the same internally consistent markers across all simulations from the same demographic model. This approach to assigning local ancestry allowed us to test the model performance for scenarios where we have only a few Ancestry Informative Markers (AIMs) for population(s) of interest.

Object detection model architecture and training

      We implemented an object detection model using the IceVision computer vision framework (v0.5.2; https://airctic.com/0.5.2/). Specifically, we trained a FasterRCNN model (Ren et al., 2016) (https://airctic.com/0.5.2/model_faster_rcnn/) with the FastAI deep learning framework (built on PyTorch; https://docs.fast.ai/). We used a resnet18 backbone and pretrained model weights from ImageNet (https://image-net.org/).

      For the sets of high and low resolution ancestry images described above, we generated 8000 images for training and 2000 images for validation from the same demographic model. In object detection models, the goal is to predict a bounding box around an object of interest. Under the IceVision framework, the bounding box is set as [x-min, y-min, x-max, y-max]. In our case, our goal is to detect the position of the selected variant (if there is one). Thus, for each image in our training and validation sets, we defined the target bounding box as an 11-pixel-wide window centered on the selected variant. For example, if the selected variant is in x-axis position 155, the bounding box was defined as [150, 0, 161, 200].

      We trained each model for 30 epochs using the *learn.fine_tune* function, freezing the pretrained layers for one epoch. We used a base learning rate of 3×10^{-3} and a weight decay of 1×10^{-2}.

      The whole genome and low resolution ancestry models were both trained on an NVIDIA GeForce RTX 2080 Ti GPU. The time to train one model was approximately 1.5 hours.

Validation

We evaluated performance on the validation sets using several metrics. We first calculated precision and recall by defining each x-axis pixel position as an independent test. If a position is within the x-min and x-max of the predicted bounding box, it was classified as a "region under selection" (i.e. a positive classification). X-axis positions outside the predicted bounding box were classified as a "region not under selection" (i.e. a negative classification). That is, pixels within the true bbox are all labeled as positive and pixels outside the true bbox are labeled as negative. In this way, we were able to calculate true and false positives and negatives.

We also defined several other metrics to assist in evaluating object detection performance across different demographic scenarios. First, we calculated the proportion of predicted bounding boxes that contain the true selected variant. A value close to 1 indicates high sensitivity, or that the method is consistently able to detect a region under selection. We also calculated the average width of the predicted bounding boxes. If the average width is much wider than the 11-pixels we used in training, this may indicate we have low specificity to detect a region under selection. Finally, we calculated the average number of predicted bounding boxes per image. Since we are only simulating one variant under selection, the model should predict 1 bounding box per image. These metrics combined with the more universal precision and recall statistics allowed us to compare performance of our model across different scenarios and between different methods.

Model Misspecifications

We tested the performance of our baseline whole genome ancestry model under several demographic model misspecifications (Results & Table 2). For each misspecification scenario, we generated 1000 whole genome ancestry images (i.e. incorporating full local ancestry information), ran inference using our trained baseline model, and calculated performance metrics detailed in the previous section.

For these simulations, we followed the baseline scenario described previously while changing one feature of the admixture or population history. We tested inference on images generated from different admixture contributions than what we trained on (10%, 25%, 75% or 90% contribution from the source population providing the beneficial mutation), number of generations since admixture began (25 and 100 generations), population size histories (expansion, contraction, and moderate (50%) and severe (10%) bottlenecks), and a scenario where the selected variant is present in both sources at a frequency of 0.5 (i.e. F_{ST} of 0 between the sources).

For the population size misspecifications, the expansion (200%) or contraction (50%) events occurred at 25 generations (halfway through the simulation). The bottlenecks occurred at 25 generations and lasted for 10 generations before expanding to the original population size of 10000. All scenarios start with N=10000.

Comparison to local ancestry outlier approach

We generated 1000 'genome-wide' simulations of 5 independently segregating chromosomes of 50 Mb each. For each simulation, the beneficial allele was fixed at the center of the first chromosome. The rest of the simulation followed exactly the admixture scenario for our baseline model described previously. After sampling 200 haplotypes from the population, we binned the first chromosome into 200 equally-sized windows (to be analogous with the 200x200 pixel images for comparison). Any window with an average local ancestry proportion greater than 3 standard deviations from the genome-wide mean was classified as "under selection" by this outlier approach. We generated ancestry-painted images from the same simulated chromosomes and classified regions under selection using our object detection method trained on the baseline high resolution ancestry scenario.

Application to human SNP data from Cabo Verde

We used local ancestry calls for ~800k genome-wide SNPs from a previous study of post-admixture selection in Cabo Verde, which included 172 individuals from the island of Santiago (Beleza et al., 2013;

Hamid et al., 2021). We focused on Santiago because we had previously detected evidence of strong positive selection in this population for the Duffy-null allele at the *DARC* (also known as *ACKR1*) gene. We generated a 200x200 pixel image of West African and European ancestry tracts on Chromosome 1 for these 172 individuals (344 haplotypes). The length of ancestry tracts can be influenced by the recombination landscape along the chromosome (e.g. long ancestry tracts are often found close to the centromere). To account for this effect, we used genetic map distances rather than physical positions to calculate ancestry tract lengths, and suggest this approach for others using our method if a genetic map is available. We then identified regions under selection on Chromosome 1 using our pre-trained high resolution object detection method for the baseline ancestry scenario (Figure 4).

To compare our results to the local ancestry outlier approach, we identified sites where the proportion of individuals with West African ancestry was more than 3 standard deviations from the mean genome-wide ancestry proportion (~0.73).

We also compared our results to the calculated *iDAT* values from Hamid et al. 2021 (the full genome-wide *iDAT* scores can also be downloaded from Hamid et al.'s associated github repository). This data consists of *iDAT* values for 10,000 randomly sampled SNPs across the genome. *iDAT* is a summary statistic designed to detect ancestry-specific post-admixture selection by calculating the difference in the rate of tract length decay between two ancestries at a site of interest, similar to how *iHS* compares the decay in homozygosity between haplotypes bearing the ancestral and derived alleles at a focal site (Voight et al., 2006). Duffy-null was previously shown to be in a genomic window with extreme values of *iDAT* in Santiago, indicative of the strong recent positive selection at the locus. For our purposes, we first standardized *iDAT* by the genome-wide background. Then, we identified standardized *iDAT* values on Chromosome 1 that were more than 3 standard deviations from the mean genome-wide standardized *iDAT*.

Acknowledgements: This work was supported by National Institutes of Health R35GM133481 to AG, R35GM138286 to DRS, and F32GM139313 to KLK. We thank Alejandro Ochoa for valuable feedback. We thank Hua Tang and Greg Barsh for generating genetic data used in this study, and the individuals from Cabo Verde for their participation. Inferred local ancestry information for the individuals from Cabo Verde can be found at https://doi.org/10.5281/zenodo.4021277, originally published by Hamid et al. 2021 from genotype data published in Beleza et al. 2013.

Data and Code Availability: Code for this study is available at https://github.com/agoldberglab/ObjectDetection_AdmixtureSelection. The pretrained high resolution baseline model that was used for most analyses in this study is uploaded and deployed at https://huggingface.co/spaces/imanhamid/ObjectDetection_AdmixtureSelection_Space. Here, users can input a 200x200 pixel, black and white, ancestry-painted image and the model will return vertices and scores for bboxes centered on predicted regions under selection (if there are any). We recommend that users follow the example code in our github for generating ancestry images to ensure that files are in the correct format. We emphasize that this model is trained under a simple single-locus selection scenario, so users should use discretion when deciding if this is an appropriate method for their data.

References

Adrion, J. R., Galloway, J. G., & Kern, A. D. (2020). Predicting the landscape of recombination using deep learning. Molecular biology and evolution, 37(6), 1790-1808.

Aguillon, S. M., Dodge, T. O., Preising, G. A., & Schumer, M. (2022). Introgression. Current Biology, 32(16), R865-R868.

Battey, C. J., Ralph, P. L., & Kern, A. D. (2020). Predicting geographic location from genetic variation with deep neural networks. eLife, 9, e54507.

Battey, C. J., Coffing, G. C., & Kern, A. D. (2021). Visualizing population structure with variational autoencoders. G3, 11(1), jkaa036.

Beleza, S., Johnson, N. A., Candille, S. I., Absher, D. M., Coram, M. A., Lopes, J., et al. (2013). Genetic architecture of skin and eye color in an African-European admixed population. PLoS genetics, 9(3), e1003372.

Bhatia, G., Tandon, A., Patterson, N., Aldrich, M. C., Ambrosone, C. B., Amos, C., Bandera, E. V., Berndt, S. I., Bernstein, L., Blot, W. J., Bock, C. H., Caporaso, N., Casey, G., Deming, S. L., Diver, W. R., Gapstur, S. M., Gillanders, E. M., Harris, C. C., Henderson, B. E., et al. (2014). Genome-wide Scan of 29,141 African Americans Finds No Evidence of Directional Selection since Admixture. The American Journal of Human Genetics, 95(4), 437–444. https://doi.org/10.1016/j.ajhg.2014.08.011

Blischak, P. D., Barker, M. S., & Gutenkunst, R. N. (2021). Chromosome-scale inference of hybrid speciation and admixture with convolutional neural networks. Molecular Ecology Resources, 21(8), 2676–2688. https://doi.org/10.1111/1755-0998.13355

Browning, S. R., & Browning, B. L. (2011). Haplotype phasing: Existing methods and new developments. Nature Reviews Genetics, 12(10), 703–714. https://doi.org/10.1038/nrg3054

Bryc, K., Auton, A., Nelson, M. R., Oksenberg, J. R., Hauser, S. L., Williams, S., Froment, A., Bodo, J.-M., Wambebe, C., Tishkoff, S. A., & Bustamante, C. D. (2010). Genome-wide patterns of population structure and admixture in West Africans and African Americans. Proceedings of the National Academy of Sciences, 107(2), 786–791. https://doi.org/10.1073/pnas.0909559107

Bryc, K., Durand, E. Y., Macpherson, J. M., Reich, D., & Mountain, J. L. (2015). The Genetic Ancestry of African Americans, Latinos, and European Americans across the United States. The American Journal of Human Genetics, 96(1), 37–53. https://doi.org/10.1016/j.ajhg.2014.11.010

Busby, G. B., Band, G., Si Le, Q., Jallow, M., Bougama, E., Mangano, V. D., Amenga-Etego, L. N., Enimil, A., Apinjoh, T., Ndila, C. M., Manjurano, A., Nyirongo, V., Doumba, O., Rockett, K. A., Kwiatkowski, D. P., Spencer, C. C., & Malaria Genomic Epidemiology Network. (2016). Admixture into and within sub-Saharan Africa. ELife, 5, e15266. https://doi.org/10.7554/eLife.15266

Busby, G., Christ, R., Band, G., Leffler, E., Le, Q. S., Rockett, K., Kwiatkowski, D., & Spencer, C. (2017). Inferring adaptive gene-flow in recent African history. BioRxiv, 205252. https://doi.org/10.1101/205252

Chan, J., Perrone, V., Spence, J. P., Jenkins, P. A., Mathieson, S., & Song, Y. S. (2018). A Likelihood-Free Inference Framework for Population Genetic Data using Exchangeable Neural Networks. Advances in Neural Information Processing Systems, 31, 8594–8605.

Cuadros-Espinoza, S., Laval, G., Quintana-Murci, L., & Patin, E. (2022). The genomic signatures of natural selection in admixed human populations. The American Journal of Human Genetics, 109(4), 710-726.

Edelman, N. B., & Mallet, J. (2021). Prevalence and adaptive impact of introgression. Annual Review of Genetics, 55, 265-283.

Fernandes, V., Brucato, N., Ferreira, J. C., Pedro, N., Cavadas, B., Ricaut, F.-X., Alshamali, F., & Pereira, L. (2019). Genome-Wide Characterization of Arabian Peninsula Populations: Shedding Light on the History of a Fundamental Bridge between Continents. Molecular Biology and Evolution, 36(3), 575–586. https://doi.org/10.1093/molbev/msz005

Flagel, L., Brandvain, Y., & Schrider, D. R. (2019). The Unreasonable Effectiveness of Convolutional Neural Networks in Population Genetic Inference. Molecular Biology and Evolution, 36(2), 220–238. https://doi.org/10.1093/molbev/msy224

Gopalan, S., Smith, S. P., Korunes, K., Hamid, I., Ramachandran, S., & Goldberg, A. (2022). Human genetic admixture through the lens of population genomics. Philosophical Transactions of the Royal Society B, 377(1852), 20200410.

Gower, G., Picazo, P. I., Fumagalli, M., & Racimo, F. (2021). Detecting adaptive introgression in human evolution using convolutional neural networks. ELife, 10, e64669. https://doi.org/10.7554/eLife.64669

Gravel, S., Stephens, M., & Pritchard, J. K. (2012). Population genetics models of local ancestry. Genetics, 191(2), 607–619. https://doi.org/10.1534/genetics.112.139808

Haller, B. C., Galloway, J., Kelleher, J., Messer, P. W., & Ralph, P. L. (2019). Tree-sequence recording in SLiM opens new horizons for forward-time simulation of whole genomes. Molecular Ecology Resources, 19(2), 552–566. https://doi.org/10.1111/1755-0998.12968

Haller, B. C., & Messer, P. W. (2019). SLiM 3: Forward Genetic Simulations Beyond the Wright–Fisher Model. Molecular Biology and Evolution, 36(3), 632–637. https://doi.org/10.1093/molbev/msy228

Hamid, I., Korunes, K. L., Beleza, S., & Goldberg, A. (2021). Rapid adaptation to malaria facilitated by admixture in the human population of Cabo Verde. ELife, 10, e63177. https://doi.org/10.7554/eLife.63177

Hedrick, P. W. (2013). Adaptive introgression in animals: Examples and comparison to new mutation and standing variation as sources of adaptive variation. Molecular Ecology, 22(18), 4606–4618. https://doi.org/10.1111/mec.12415

Hellenthal, G., Busby, G. B., Band, G., Wilson, J. F., Capelli, C., Falush, D., & Myers, S. (2014). A genetic atlas of human admixture history. science, 343(6172), 747-751.

Hodgson, J. A., Pickrell, J. K., Pearson, L. N., Quillen, E. E., Prista, A., Rocha, J., et al. (2014). Natural selection for the Duffy-null allele in the recently admixed people of Madagascar. Proceedings of the Royal Society B: Biological Sciences, 281(1789), 20140930.

Hsieh, P., Vollger, M. R., Dang, V., Porubsky, D., Baker, C., Cantsilieris, S., et al. (2019). Adaptive archaic introgression of copy number variants and the discovery of previously unknown human genes. Science, 366(6463), eaax2083.

Huerta-Sánchez, E., Jin, X., Bianba, Z., Peter, B. M., Vinckenbosch, N., Liang, Y., et al. (2014). Altitude adaptation in Tibetans caused by introgression of Denisovan-like DNA. Nature, 512(7513), 194-197.

Isildak, U., Stella, A., & Fumagalli, M. (2021). Distinguishing between recent balancing selection and incomplete sweep using deep neural networks. Molecular Ecology Resources, 21(8), 2706–2718. https://doi.org/10.1111/1755-0998.13379

Isshiki, M., Naka, I., Kimura, R., Nishida, N., Furusawa, T., Natsuhara, K., Yamauchi, T., Nakazawa, M., Ishida, T., Inaoka, T., Matsumura, Y., Ohtsuka, R., & Ohashi, J. (2021). Admixture with indigenous people helps local adaptation: Admixture-enabled selection in Polynesians. BMC Ecology and Evolution, 21(1), 179. https://doi.org/10.1186/s12862-021-01900-y

Jeong, C., Alkorta-Aranburu, G., Basnyat, B., Neupane, M., Witonsky, D. B., Pritchard, J. K., Beall, C. M., & Rienzo, A. D. (2014). Admixture facilitates genetic adaptations to high altitude in Tibet. Nature Communications, 5(1), 1–7. https://doi.org/10.1038/ncomms4281

Jin, W., Xu, S., Wang, H., Yu, Y., Shen, Y., Wu, B., & Jin, L. (2012). Genome-wide detection of natural selection in African Americans pre- and post-admixture. Genome Research, 22(3), 519–527. https://doi.org/10.1101/gr.124784.111

Kelleher, J., Etheridge, A. M., & McVean, G. (2016). Efficient Coalescent Simulation and Genealogical Analysis for Large Sample Sizes. PLOS Computational Biology, 12(5), e1004842. https://doi.org/10.1371/journal.pcbi.1004842

Kelleher, J., Thornton, K. R., Ashander, J., & Ralph, P. L. (2018). Efficient pedigree recording for fast population genetics simulation. PLOS Computational Biology, 14(11), e1006581. https://doi.org/10.1371/journal.pcbi.1006581

Kelly, J. K. (1997). A test of neutrality based on interlocus associations. Genetics, 146(3), 1197-1206.

Kern, A. D., & Schrider, D. R. (2018). diploS/HIC: An Updated Approach to Classifying Selective Sweeps. G3: Genes, Genomes, Genetics, 8(6), 1959–1970. https://doi.org/10.1534/g3.118.200262

Kim, Y., & Nielsen, R. (2004). Linkage Disequilibrium as a Signature of Selective Sweeps. Genetics, 167(3), 1513–1524. https://doi.org/10.1534/genetics.103.025387

Korunes, K., Soares-Souza, G. B., Bobrek, K., Tang, H., Araújo, I. I., Goldberg, A., Beleza, S. (2022) Sex-biased admixture and assortative mating shape genetic variation and influence demographic inference in admixed Cabo Verdeans. G3: Genes|Genomes|Genetics, jkac183

Krizhevsky, A., Sutskever, I., & Hinton, G. E. (2012). ImageNet Classification with Deep Convolutional Neural Networks. Advances in Neural Information Processing Systems, 25.

https://papers.nips.cc/paper/2012/hash/c399862d3b9d6b76c8436e924a68c45b-Abstract.html

Laso-Jadart, R., Harmant, C., Quach, H., Zidane, N., Tyler-Smith, C., Mehdi, Q., Ayub, Q., Quintana-Murci, L., & Patin, E. (2017). The Genetic Legacy of the Indian Ocean Slave Trade: Recent Admixture and Post-admixture Selection in the Makranis of Pakistan. The American Journal of Human Genetics, 101(6), 977–984. https://doi.org/10.1016/j.ajhg.2017.09.025

Lawson, D. J., Hellenthal, G., Myers, S., & Falush, D. (2012). Inference of population structure using dense haplotype data. PLoS genetics, 8(1), e1002453.

Lecun, Y., & Bengio, Y. (1995). Convolutional networks for images, speech, and time-series. In M. A. Arbib (Ed.), The handbook of brain theory and neural networks. MIT Press.

LeCun, Y., Bengio, Y., & Hinton, G. (2015). Deep learning. Nature, 521(7553), 436–444. https://doi.org/10.1038/nature14539

Lohmueller, K. E., Bustamante, C. D., & Clark, A. G. (2010). The Effect of Recent Admixture on Inference of Ancient Human Population History. Genetics, 185(2), 611–622. https://doi.org/10.1534/genetics.109.113761

Lohmueller, K. E., Bustamante, C. D., & Clark, A. G. (2011). Detecting Directional Selection in the Presence of Recent Admixture in African-Americans. Genetics, 187(3), 823–835. https://doi.org/10.1534/genetics.110.122739

Lopez, M., Choin, J., Sikora, M., Siddle, K., Harmant, C., Costa, H. A., Silvert, M., Mouguiama-Daouda, P., Hombert, J.-M., Froment, A., Le Bomin, S., Perry, G. H., Barreiro, L. B., Bustamante, C. D., Verdu, P., Patin, E., & Quintana-Murci, L. (2019). Genomic Evidence for Local Adaptation of Hunter-Gatherers to the African Rainforest. Current Biology, 29(17), 2926-2935.e4. https://doi.org/10.1016/j.cub.2019.07.013

Maples, B. K., Gravel, S., Kenny, E. E., & Bustamante, C. D. (2013). RFMix: a discriminative modeling approach for rapid and robust local-ancestry inference. The American Journal of Human Genetics, 93(2), 278-288.

Moran, B. M., Payne, C., Langdon, Q., Powell, D. L., Brandvain, Y., & Schumer, M. (2021). The genomic consequences of hybridization. ELife, 10, e69016.

Norris, E. T., Rishishwar, L., Chande, A. T., Conley, A. B., Ye, K., Valderrama-Aguirre, A., & Jordan, I. K. (2020). Admixture-enabled selection for rapid adaptive evolution in the Americas. Genome Biology, 21(1), 29. https://doi.org/10.1186/s13059-020-1946-2

Norris, L. C., Main, B. J., Lee, Y., Collier, T. C., Fofana, A., Cornel, A. J., & Lanzaro, G. C. (2015). Adaptive introgression in an African malaria mosquito coincident with the increased usage of insecticide-treated bed nets. Proceedings of the National Academy of Sciences, 112(3), 815–820. https://doi.org/10.1073/pnas.1418892112

Oziolor, E. M., Reid, N. M., Yair, S., Lee, K. M., Guberman VerPloeg, S., Bruns, P. C., et al. (2019). Adaptive introgression enables evolutionary rescue from extreme environmental pollution. Science, 364(6439), 455-457.

Patin, E., Lopez, M., Grollemund, R., Verdu, P., Harmant, C., Quach, H., Laval, G., Perry, G. H., Barreiro, L. B., Froment, A., Heyer, E., Massougbodji, A., Fortes-Lima, C., Migot-Nabias, F., Bellis, G., Dugoujon, J.-M., Pereira, J. B., Fernandes, V., Pereira, L., et al. (2017). Dispersals and genetic adaptation of Bantu-speaking populations in Africa and North America. Science, 356(6337), 543–546. https://doi.org/10.1126/science.aal1988

Payseur, B. A., & Rieseberg, L. H. (2016). A genomic perspective on hybridization and speciation. Molecular ecology, 25(11), 2337-2360.

Pierron, D., Heiske, M., Razafindrazaka, H., Pereda-loth, V., Sanchez, J., Alva, O., Arachiche, A., Boland, A., Olaso, R., Deleuze, J.-F., Ricaut, F.-X., Rakotoarisoa, J.-A., Radimilahy, C., Stoneking, M., & Letellier, T. (2018). Strong selection during the last millennium for African ancestry in the admixed population of Madagascar. Nature Communications, 9(1), 1–9. https://doi.org/10.1038/s41467-018-03342-5

Price, A. L., Weale, M. E., Patterson, N., Myers, S. R., Need, A. C., Shianna, K. V., Ge, D., Rotter, J. I., Torres, E., Taylor, K. D., Goldstein, D. B., & Reich, D. (2008). Long-Range LD Can Confound Genome Scans in Admixed Populations. The American Journal of Human Genetics, 83(1), 132–135. https://doi.org/10.1016/j.ajhg.2008.06.005

Racimo, F., Sankararaman, S., Nielsen, R., & Huerta-Sánchez, E. (2015). Evidence for archaic adaptive introgression in humans. Nature Reviews Genetics, 16(6), 359–371. https://doi.org/10.1038/nrg3936

Racimo, F., Marnetto, D., & Huerta-Sánchez, E. (2017). Signatures of archaic adaptive introgression in present-day human populations. Molecular biology and evolution, 34(2), 296-317.

Ren, S., He, K., Girshick, R., & Sun, J. (2016). Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks. ArXiv:1506.01497 [Cs]. http://arxiv.org/abs/1506.01497

Rishishwar, L., Conley, A. B., Wigington, C. H., Wang, L., Valderrama-Aguirre, A., & Jordan, I. K. (2015). Ancestry, admixture and fitness in Colombian genomes. Scientific Reports, 5(1), 1–16. https://doi.org/10.1038/srep12376

Sabeti, P. C., Reich, D. E., Higgins, J. M., Levine, H. Z. P., Richter, D. J., Schaffner, S. F., Gabriel, S. B., Platko, J. V., Patterson, N. J., McDonald, G. J., Ackerman, H. C., Campbell, S. J., Altshuler, D., Cooper, R., Kwiatkowski, D., Ward, R., & Lander, E. S. (2002). Detecting recent positive selection in the human genome from haplotype structure. Nature, 419(6909), 832–837. https://doi.org/10.1038/nature01140

Sanchez, T., Cury, J., Charpiat, G., & Jay, F. (2021). Deep learning for population size history inference: Design, comparison and combination with approximate Bayesian computation. Molecular Ecology Resources, 21(8), 2645–2660. https://doi.org/10.1111/1755-0998.13224

Schaefer, N. K., Shapiro, B., & Green, R. E. (2016). Detecting hybridization using ancient DNA. Molecular ecology, 25(11), 2398-2412.

Schaefer, N. K., Shapiro, B., & Green, R. E. (2017). AD-LIBS: inferring ancestry across hybrid genomes using low-coverage sequence data. BMC bioinformatics, 18(1), 1-22.

Schrider, D. R., & Kern, A. D. (2018). Supervised Machine Learning for Population Genetics: A New Paradigm. Trends in Genetics, 34(4), 301–312. https://doi.org/10.1016/j.tig.2017.12.005

Schumer, M., Powell, D. L., & Corbett-Detig, R. (2020). Versatile simulations of admixture and accurate local ancestry inference with mixnmatch and ancestryinfer. Molecular Ecology Resources, 20(4), 1141–1151. https://doi.org/10.1111/1755-0998.13175

Setter, D., Mousset, S., Cheng, X., Nielsen, R., DeGiorgio, M., & Hermisson, J. (2020). VolcanoFinder: genomic scans for adaptive introgression. PLoS Genetics, 16(6), e1008867.

Shchur, V., Svedberg, J., Medina, P., Corbett-Detig, R., & Nielsen, R. (2020). On the distribution of tract lengths during adaptive introgression. G3: Genes, Genomes, Genetics, 10(10), 3663-3673.

Sheehan, S., & Song, Y. S. (2016). Deep Learning for Population Genetic Inference. PLOS Computational Biology, 12(3), e1004845. https://doi.org/10.1371/journal.pcbi.1004845

Svedberg, J., Shchur, V., Reinman, S., Nielsen, R., & Corbett-Detig, R. (2021). Inferring adaptive introgression using hidden Markov models. Molecular biology and evolution, 38(5), 2152-2165.

Tang, H., Choudhry, S., Mei, R., Morgan, M., Rodriguez-Cintron, W., Burchard, E. G., & Risch, N. J. (2007). Recent Genetic Selection in the Ancestral Admixture of Puerto Ricans. The American Journal of Human Genetics, 81(3), 626–633. https://doi.org/10.1086/520769

Torada, L., Lorenzon, L., Beddis, A., Isildak, U., Pattini, L., Mathieson, S., & Fumagalli, M. (2019). ImaGene: A convolutional neural network to quantify natural selection from genomic data. BMC Bioinformatics, 20(9), 337. https://doi.org/10.1186/s12859-019-2927-x

Triska, P., Soares, P., Patin, E., Fernandes, V., Cerny, V., & Pereira, L. (2015). Extensive Admixture and Selective Pressure Across the Sahel Belt. Genome Biology and Evolution, 7(12), 3484–3495. https://doi.org/10.1093/gbe/evv236

Vicuña, L., Klimenkova, O., Norambuena, T., Martinez, F. I., Fernandez, M. I., Shchur, V., & Eyheramendy, S. (2020). Post-Admixture Selection on Chileans Targets Haplotype Involved in Pigmentation and Immune Defense Against Pathogens. Genome Biology and Evolution. https://doi.org/10.1093/gbe/evaa136

Voight, B. F., Kudaravalli, S., Wen, X., & Pritchard, J. K. (2006). A Map of Recent Positive Selection in the Human Genome. PLOS Biology, 4(3), e72. https://doi.org/10.1371/journal.pbio.0040072

Wall, J. D., Schlebusch, S. A., Alberts, S. C., Cox, L. A., Snyder-Mackler, N., Nevonen, K. A., et al. (2016). Genomewide ancestry and divergence patterns from low-coverage sequencing data reveal a complex history of admixture in wild baboons. Molecular ecology, 25(14), 3469-3483.

Wang, Z., Wang, J., Kourakos, M., Hoang, N., Lee, H. H., Mathieson, I., & Mathieson, S. (2021). Automatic inference of demographic parameters using generative adversarial networks. Molecular Ecology Resources, 21(8), 2689–2705. https://doi.org/10.1111/1755-0998.13386

Whitney, K. D., Randell, R. A., & Rieseberg, L. H. (2006). Adaptive Introgression of Herbivore Resistance Traits in the Weedy Sunflower Helianthus annuus. The American Naturalist, 167(6), 794–807.

https://doi.org/10.1086/504606

Williams, A. (2016). admix-simu: Admix-simu: program to simulate admixture between multiple populations. Zenodo. https://doi.org/10.5281/zenodo.45517

Yelmen, B., Marnetto, D., Molinaro, L., Flores, R., Mondal, M., & Pagani, L. (2021). Improving selection detection with population branch statistic on admixed populations. Genome biology and evolution, 13(4), evab039.

Zhou, Q., Zhao, L., & Guan, Y. (2016). Strong Selection at MHC in Mexicans since Admixture. PLOS Genetics, 12(2), e1005847. https://doi.org/10.1371/journal.pgen.1005847

Supplemental Figure 1. Precision-Recall curves comparing performance under demographic model misspecifications to the baseline scenario (high (full) ancestry resolution images; solid black line in each plot). Panels show different categories of misspecification: A) founding admixture contribution from the population providing the beneficial allele, B) number of generations since admixture occurred, C) population size change since the founding of the admixed populations, and D) level of differentiation between the source populations for the variant under selection. Area under the curves (AUC) can be found in Table 2. The no-skill classifier is indicated by the dashed black lines in each plot.