Emergence of syntax and word prediction in an artificial neural circuit of the cerebellum

Keiko Ohmae[1] and Shogo Ohmae[1]

1. Neuroscience Department, Baylor College of Medicine, Houston, TX 77030, USA

Correspondence to: shogo.ohmae@bcm.edu (S.O)

ACKNOWLEDGMENTS
We thank Dr. Javier Medina for multiple rounds of brilliant advice and Dr. Mitsuo Kawato, Dr. Tatsuo Sato, Dr. Tatiana Schnur, Dr. Nuo Li, and Dr. Shigeru Kitazawa (listed in the chronological order that the comments were provided) for invaluable insights and comments that improved the manuscript. We also thank Mrs. Zoha Hassan for editing to select subtle nuances of language, Dr. Masashi Kimura (via MENTA: https://menta.work/) for continuous helpful advice on programming, and Dr. Lindsay Bremner (via NeuroEdit: https://www.neuroedit.com/) for excellent editing. This work was supported by grant to SO from the National Institutes of Health (R34 NS118445).

AUTHOR CONTRIBUTIONS
Conceptualization, S.O.; Data curation, S.O.; Formal analysis, S.O. and K.O.; Funding acquisition, S.O.; Investigation, S.O.; Methodology, S.O.; Project administration, S.O.; Resources, S.O.; Software, S.O.; Supervision, S.O.; Validation, S.O.; Visualization, S.O. and K.O.; Writing – original draft, S.O. and K.O.; Writing – review & editing, S.O. and K.O.

CONFLICT OF INTEREST
The authors declare no competing financial interests.

ABSTRACT
The cerebellum, interconnected with the cerebral neocortex, plays a vital role in human-
characteristic cognition such as language processing, but knowledge about the underlying
circuit computation of the cerebellum remains very limited. Here, to understand the computation
underlying the cerebellar language processing, we developed a biologically-constrained
cerebellar artificial neural network (cANN) model, which implemented the recently identified
cerebello-cerebellar recurrent pathway. We found that while cANN acquires prediction of future
words, another function of syntactic recognition emerges in the middle layer of the prediction
circuit. The recurrent pathway of the cANN was essential for the two language functions,
whereas cANN variants with further biological constraints preserved these functions.
Considering the uniform structure of cerebellar circuitry across all functional domains, the
single-circuit computation, which is the common basis of the two language functions, can be
generalized to fundamental cerebellar functions of prediction and grammar-like rule extraction
from sequences, that underpin a wide range of cerebellar motor and cognitive functions.
This is a pioneering study to understand the circuit computation of human-characteristic
cognition by biologically-constrained ANNs, which can lead new therapeutic interventions for
human cognitive dysfunction.
45
46 **182 words**

INTRODUCTION

Language comprehension is a vital cognitive function that supports human communication and knowledge acquisition, but the underlying mechanisms at the level of neuronal activity within specific brain circuits remain largely unexplored. Artificial neural networks (ANNs) provide an invaluable tool to examine how the brain processes language, because there are no established animal models and only limited data from invasive recordings in humans. While recent AI advancements have led to ANN models that attempt to replicate brain functionality, these models do not adequately account for biological constraints. For instance, neocortical models for language processing based on the transformer algorithm[1, 2, 3], which are widely used in language-processing AI like ChatGPT, deviate from actual brain physiology. This is because the transformer-based models lack artificial neurons and process a sentence as a single unit rather than as a sequence of individual words. Thus, creating biologically constrained ANN models is essential to elucidate the computational processes of brain circuits involved in language processing.

Language comprehension after word recognition requires cooperation between the left neocortical language area and the right lateral cerebellum (right Crus I/II)[4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16]. The cerebellum has a large capacity of plasticity, and interestingly, according to recent observations that childhood damage to the right cerebellum causes more permanent and severe language deficits than adult damage[17, 18, 19, 20] and that the right cerebellum is activated during learning of new language tasks[16, 21, 22], cerebellar language acquisition is considered to support subsequent acquisition in the neocortex[15, 17, 18]. To understand the origins of language functions in the neocortex, it is crucial to understand the language processing mechanisms in the cerebellum at the circuit computation level. Here, we examine how language functions emerge in an ANN model that is biologically-constrained by the known connectivity and inputs/outputs of the cerebellar circuit (cANN).

Sentence comprehension involves recalling the meanings of words and combining them appropriately based on grammar to compose the meaning of the sentence, and during this process, two major language functions have been linked to the right lateral cerebellum: The first is (1) next-word prediction[4, 6, 7, 8, 9, 10], which supports faster and more accurate sentence comprehension by placing input words in a predictive context (particularly in noisy environments)[1, 6, 8, 10, 23, 24, 25, 26]. Although neural activity related to this function has also been reported in neocortical language areas[1, 3, 23], stronger evidence including causality has accumulated for the cerebellum[6, 7, 8, 9]. The second function is (2) grammatical processing, especially syntactic recognition about subject–verb–object (S-V-O) information[5, 11, 12, 13, 27]. These two language functions reflect two more general cerebellar functions that support a variety of cognitive functions. One is prediction of external events[4, 5, 10, 15, 28, 29, 30, 31], and (1) next-word prediction is a language case of this general function[6, 7, 8, 10, 15, 25]. The other is rule extraction from the sequence of events[11, 13, 32], and (2) syntactic recognition is a language case of this function[11, 13, 33]. Although the two general functions underlie various cerebellar cognitive functions[4, 10, 15, 28, 31] (see Discussion), it remains unclear how these different functions are

realized in a cerebellar circuit with a uniform cytoarchitecture. To address this gap in knowledge,
elucidation of the underlying network dynamics by ANN is needed[15]. Therefore, in the context of
language processing, we tested whether a single circuit architecture can support both general
functions, thereby shedding light on the general circuit computation of the cerebellum.
Here, we found that the cANN can acquire prediction in language (i.e., next-word
prediction) through training, and simultaneously rule extraction from sequences (i.e., syntactic
recognition) can also be acquired spontaneously in the middle layer of the same circuit. This
suggests that two general functions of the cerebellum, prediction and rule extraction from
sequence, can be captured by a single circuit computation of the cerebellum. This also indicates
a new treatment for language dysfunction, in which training in word prediction leads to
improvement in syntactic comprehension.
98
RESULTS
The cerebellar ANN model as a next-word prediction circuit
We started by assessing whether the biologically-constrained cANN could learn next-word
prediction. Our cANN contains three layers—an input layer (granule cells), a middle layer
(Purkinje cells), and an output layer (nuclei neurons), and the cANN consists of a conventionally
reported feedforward pathway and a recently identified recurrent pathway (brown, blue
pathways in Fig. 1b, respectively). The recurrent pathway includes output cell-input cell pathway,
also called the nucleocortical pathway[34, 35, 36, 37, 38, 39, 40], that has been demonstrated to be
essential for prediction in the cerebellum[34, 37, 41]. The cANN circuit also incorporates the climbing
fiber pathway (gray, Fig. 1b) which delivers prediction errors to the cerebellum[6, 10, 28, 42, 43, 44].
Based on physiological observations that the prediction signal generated by Purkinje cells after
a cue event is persistent until the actual event occurs[34, 45, 46], we assumed that the prediction
signal of Purkinje cells in the cANN is persistent until the next word (see Discussion). By this
persistent prediction signal, the recurrent signal is maintained, allowing it to be integrated with
the next word. Additionally, the circuit output signal is also maintained and can be compared
with the correct answer signal of the actual next word, to compute the prediction error signal.
We designed the inputs/outputs of the cANN (Fig. 1b) according to previous proposals
for the next-word prediction circuit of the cerebellum as in Figure 1a[6, 7, 8, 10, 25]. Based on the
sparse coding theory of the input cells (i.e., granule cells), we assumed that words were
represented by sparse coding in the input cells: each of the 3000 cells was randomly assigned
to one of 3000 words and hence the input signal contained no semantic or grammatical
information at all (confirmed later, Fig. 3d). To facilitate the investigation of information
processing in this network, we assumed that the correct answer signal (correct answer = actual
next word in Fig 1b, gray) was encoded by the same 3000-dimensional sparse coding as in the
input cells, so that the correct answer signal contained no syntactic information at all (Fig. 3d).
Because the dimensionality of the output cells is theorized to be the same as that of the correct
answer signal[28, 47, 48, 49], we set the number of the output cells as 3000. Through the training of
cANN, the activity intensity of each output cell can indicate the likelihood of the corresponding

word being the next word (percentages in Fig. 1b). Solely for performance evaluation purposes,
we selected the five output cells with the strongest activity and the corresponding five words as
the prediction candidates for the next word. Additionally, to replicate the anatomical
convergence from Purkinje cells to the output cells (i.e., the number of Purkinje cells > that of
the output cells), we created and examined another cANN with this biological convergence (Fig.
5).
For learning, the correct information for the next word was delivered to the circuit word
by word and the synaptic weights were updated to reduce the prediction error, in line with the
learning rule of the cerebellum (Fig. 1b, gray)[10, 50, 51].
Training the cANN with sentences (e.g., from classic novels) produced significant
improvements in both the prediction error and the correct prediction rate (Fig. 1c,d). At the very
early stages of training, the correct prediction rate jumped from 0% to about 17% (Fig 1d, gray
arrowhead), and at this point the prediction was based on the words that appeared most
frequently in the training sentences, regardless of the identity of the immediately preceding word
(Extended Data Fig. 1a,b). Then, the correct rate slowly increased to about 40%, where it
plateaued; here, the cANN achieved correct prediction rates higher than chance regardless of
the frequency of occurrence of the target word (Extended Data Fig. 1f), and the cANN made
different next-word predictions after each of the two instances of "the" in a sentence (Fig. 1e,
gray boxes), indicating that the circuit utilized words prior to the immediately preceding word.
146

147   **Figure 1.** Local circuit model of a cANN to reconstruct cerebellar language
148   functions. **a**, Previously proposed block diagram with Inputs/outputs for next-
149   word prediction. **b**, The three-layer cerebellar circuit, consisting of a
150   feedforward pathway (brown) and a recurrent pathway (blue). The climbing
151   fiber pathway (gray arrows) delivers the prediction error signal to update the

synaptic weights on the Purkinje and output cells (gray shading). **c,d**, Learning curves for the prediction error (**c**; cross entropy; median and IQR) and percentage correct predictions (**d**) for 20 cANNs trained on next-word prediction. Inset, magnified view of the early learning period (gray interval). **e**, Predictions (five candidate words) for the two instances of "the" in a sentence by a well-trained cANN. Correct predictions are highlighted in red, and synonyms are in orange.

Figure 2. Next-word prediction and network dynamics of a representative cANN. **a,b**, Predictions after three instances of "the" (indexed) in two sentences. **c**, Visualization of the neural activity of Purkinje cells after input of each word by PCA. Words are color-coded in rainbow from the beginning of the sentence to the end, and spontaneous activity is indicated by the black dot. **d**, Predictions when the recurrent signal was blocked.

Next, to replicate the finding from human cerebellar research[7, 8], we examined whether
the cANN could predict the noun after a verb. For the sentence "The man will sail [verb] the boat
[noun]" used in the previous research, together with two similar sentences, the cANN predicted
correct next words and synonyms (Figs. 1e, 2a,b, black boxes). Predicting the noun after a verb
had a lower correct rate (median, 22.9%; interquartile range (IQR), 21.0%–23.4%) than the
overall prediction rate (38.3%; 37.8%–38.6%), possibly because verbs often have a large
number of potential noun partners (e.g. partners of "eat"). By contrast, predictions were more
accurate for other word types after a verb (for prepositions: 60.0%, 56.7–63.3; object pronouns:
56.5%, 52.2–60.9). The cANN also made proper predictions for other word types, such as
nouns after prepositions (43.0%, 42.1-45.6), and adjectives after "be" verbs (27.5%, 25.0-30.0).
From these results, we conclude that the cANN is able to function as a next-word prediction
circuit, although the correct rate varies with the word type.
To investigate the mechanism of information processing, we examined the role of the
Purkinje cells, where the feedforward signal of a newly arriving word and the recurrent signal
containing the previous word information are integrated (Fig. 1b). When we visualized the word-
by-word transition of Purkinje cells activity in the sentences using principal component analysis
(PCA), three different instances of "the" generated different activity patterns in the Purkinje cells
(Fig. 2c, the[1], the[2], the[3]). Since the Purkinje cells are the only element of the circuit upstream of
the output cells responsible for predictions, these differences are essential for generating
different predictions (Fig. 2a,b, gray and black boxes). When the recurrent input was blocked,
the activity in the Purkinje cells became identical for all three instances of "the" (Extended Data
Fig. 1c), and the impaired cANN no longer produced different predictions (Fig. 2d), indicating
that only the immediately preceding word is encoded. More generally, prediction of the noun
after a verb was dramatically degraded in the impaired cANN (correct rate, 2.1%; IQR, 1.1%–
2.1%).
192
The cANN model as a syntax-processing circuit
193
There is little-to-no evidence as to how the inputs/outputs should be designed for another cANN
dedicated to syntactic processing[15] (Fig. 1a). For the cerebellum to assist the neocortex in
language acquisition, the cerebellum must acquire language processing on its own without
information from the neocortex. Inspired by the potential of the middle layer of recurrent ANNs[52,]
[53, 54], we investigated whether subject–verb–object (S-V-O) syntactic information could emerge
within the next-word prediction circuit of the cANN, whose input signals contain no syntactic
information. Indeed, the cANN reliably predicted objective case pronouns after a verb (Extended
Data Fig. 1d,e), suggesting that the predictions reflect S-V-O information. Since the Purkinje
cells may integrate new and past words according to S-V-O structure, we visualized the activity
of the Purkinje cells by PCA (Extended Data Fig. 2a) and by linear support vector machine (Fig.
3a) and found that S words were clustered and well separated from V-O words (blue circle),
regardless of the number of words forming the subject (black trace). The separation of S words
from V-O words (96.1%; 95.7–96.6; nonlinear support vector machine), V words (96.0%; IQR,

95.7–96.5), and O words (95.8%; 95.4–96.1) was highly accurate (visualized in Extended Data
Fig. 2b). Since syntactic information is not included in the correct answer of the next word
(confirmed in Fig. 3d, right), these results indicate that the Purkinje cells in the word prediction
circuit are capable of extracting highly accurate SVO syntactic information independent of
external information. Importantly, even for the same word, the cANN can distinguish when the
word appears as a subject (e.g., "the" as a part of a subject, blue arrowhead in Fig. 3a) and
when it appears as an object ("the" as a part of object, yellow arrowheads), ensuring that it has
S-V-O recognition capability. Thus, to our surprise, syntactic processing does not require a
dedicated circuit (Fig. 3b). This may be why the conventional approach of assuming a dedicated
circuit as in Figure 1a worked well for next-word prediction, but not for syntactic processing[15].
217

218 **Figure 3.** Syntactic processing by the cANN. **a**, Visualization of neural activity
219 of Purkinje cells after inputting a subject (blue), verb (red), and object (yellow),
220 in the dimensions used for classification. The activity transition for a sentence
221 with a longer subject (three words) is highlighted (dark gray trace). **b**,
222 Inputs/outputs for syntactic processing. **c**, Similarity analysis of the

223   dimensions of S-V, V-O, and S-O separations with PCA dimensions (median).
224   **d**, Syntactic information contained in the feedforward-input, Purkinje,
225   feedforward-output cells, and correct answer signal. The chance level of
226   separation is 50% (gray horizontal line). **e**, Syntactic information when the
227   recurrent signal was blocked.

To investigate how syntactic information emerges in the cANN, we compared the
syntactic information along the feedforward pathway (Fig. 3d). We confirmed that the input cells
contain no syntactic information at all, and found that syntactic information was predominantly
extracted in the Purkinje cells and was degraded in the output cells ($p < 0.001$ for any of S, V,
and O, Wilcoxon signed-rank test; visualized by distorted distributions in Extended Data Fig. 2c),
probably because their direct task is next-word prediction. Furthermore, when the recurrent
signal was blocked, the separation of S and O dropped sharply, revealing the importance of the
recurrent signal for processing syntactic information (Fig. 3e).
Examining the extent to which S-V-O syntactic information is a primary piece of
information in Purkinje cells, we found that the dimensions used for S-V, V-O, and S-O
separation by the support vector machine were all similar to the major dimensions of PCA space
in terms of direction (Fig. 3c) and information content (Extended Data Fig. 2d,e). This indicates
that S-V-O syntactic information is the primary information represented by the activity of
Purkinje cells.

Further biologically constrained cANN variants
We developed three new cANN variants incorporating further biological constraints and
assessed their performance. In the first variant, the recurrent pathway was designed according
to the cerebellar anatomy, where connections from Purkinje cells to output cells are convergent,
and connections from output cells to input cells are divergent. We set the number of output cells
to 48 and the number of input cells to 192 in the recurrent pathway, so that Purkinje cell signals
must be compressed and decompressed through this pathway. Given that plasticity has been
reported for various connections in the cerebellum[55], we assumed plasticity in the recurrent
pathway. This cANN variant acquired the equivalent language functions to the original cANN
(median of correct prediction rates, 36.5%; median of syntactic separation accuracy, S, 93.4%,
V, 95.1%, O, 95.0%). This demonstrates that the robustness of cANN's language functions
despite cell number variations in the recurrent pathway.
The second cANN variant, with inhibitory-restricted Purkinje-output connections, also
achieved equivalent language functions (median of correct prediction rates, 36.8%; median of
syntactic separation accuracy, S, 94.8%, V, 96.2%, O, 95.5%). This demonstrates cANN's
robustness regarding sign of connection between the Purkinje cells and the output cells,
suggesting that such constraints do not hinder information processing. This aligns with the
physiological observation that, although Purkinje cells has only GABAergic connections to the

output cells, they can both inhibit and disinhibit the output cells by increasing and decreasing
their firing rates (i.e., the sign of the downstream signal is not limited).
In the original cANN, the distribution of the synaptic weights of input-Purkinje connection
resembled a normal distribution (Fig. 4a). If considering the greater-than-zero portion of the
weights (w>0; black in Fig. 4a) as the weights of parallel fiber-Purkinje cell synapses (i.e., direct
excitatory input cell-Purkinje cell connection), this distribution closely aligns with the
physiological distribution of parallel fiber-Purkinje cell synaptic weights, which can be
approximated by a half of a normal distribution[56, 57]. However, a sharp peak with zero synaptic
weight (w=0; silent synapses) was observed in the physiological data but not in the cANN.
Therefore, we created the third cANN variant combining excitatory-limited input-Purkinje
projections (imitating direct projection) and inhibitory-limited input-Purkinje projections (imitating
indirect projection via molecular layer interneurons). This cANN variant also achieved
comparable language functions (median of correct prediction rates, 37.0%; median of syntactic
separation accuracy, S, 94.5%, V, 96.6%, O, 95.5%). Interestingly, the distribution of the
excitatory-limited synapses exhibited the peak of silent synapses, closer to the physiological
observation (Fig. 4b). These findings demonstrate the robustness of the cANN functions to
stringent biological constraints, while highlighting the need for such constraints to replicate
circuit details such as synaptic weight distributions.
280

Figure 4. Distribution of synaptic weights at the input cell-Purkinje cell
connection. **a**, The original cANN's synaptic weight distribution (right) without
sign restriction at input-Purkinje synapses (left). The negative-weight
component is in gray, and the positive-weight component is in black. **b**, The
synaptic weight distributions of a cANN variant with input-Purkinje synaptic
signs restricted to either excitatory (black) or inhibitory (gray).
287

Convergent cANN with the biological Purkinje-output convergence
We examined the performance of another cerebellar cANN model with an anatomical constraint
of convergence of the Purkinje-output connection[36, 58] and a physiological constraint of
population coding of the output cells[51]. To this end, we modified the original cANN circuit (Fig.
1b) to have only 16 output cells in the feedforward pathway so that the activity pattern of the 16
output cells represents a single word by population coding. Then, the modified circuit predicts
only a single word at a time, unlike the original cANN which could probabilistically predict

multiple candidate words. To enable the output of multiple word candidates, based on the

physiological observation that the cerebellum has a modular structure which allows for

simultaneous generation of multiple outputs, we treated this modified circuit as one module and

created a new cANN model with 10 modules in a row (Fig. 5a). Since parallel fibers, projections

from the input cells to Purkinje cells, are known to pass across many modules, we assumed the

input cells are shared between the modules. This new cANN is referred to as a "convergent

cANN", while the original cANN is referred to as a "non-convergent cANN".

For learning, based on the cerebellar theory that enables multiple modules to

cooperate and achieve a complex function (MOSAIC model)[31, 48, 58, 59], after each prediction, the

prediction error signal was given solely to the module with the closest prediction to the correct

answer (= the actual next word). Based on the cerebellar theory that the output cells and the

correct answer signal should have the same dimensionality[28, 47, 48, 49], the correct answer was set

to be represented in 16 dimensions. To represent the correct answer of 3000 words in 16

dimensions, we assumed a compressed word representation in which similar words (e.g., ship

and boat) are represented by similar signal patterns, as observed in the neocortex[60], which is

the source of the correct answer signal[10, 25, 28]. To facilitate comparison with the non-convergent

cANN model, the following analysis focused on the top five modules in terms of prediction

accuracy at the final training stage (see Methods).

Figure 5. Performance of the convergent cANN.

a, Circuit design of the convergent cANN. The convergent cANN consists of 10 modules, each containing the same circuit as the original cANN in Figure 1b, except for having 16 output cells. After each prediction, the prediction error is given solely to the module that produced the closest output to the correct answer signal of the actual next word (gray solid arrows). **b**,**c**, Learning curves of 10 convergent cANNs for the prediction error (**b**; mean squared error) and percentage of correct predictions (**c**) for all the 10 modules (black) and for the top 5 modules (blue). **d**, Visualization of the neural activity of Purkinje cells of a representative convergent cANN after input of each word, by PCA. Words are color-coded in rainbow from the beginning to the end of the sentence, and spontaneous activity is indicated by the black dot. **e**, Syntactic processing by the convergent cANN. Neuronal activity of Purkinje cells in the convergent cANN after input of a subject (blue), verb (red), and object (yellow) is visualized by the dimensions of the V-O and S-O classifications of the support vector machine. The solid black trace indicates the activity dynamics for the sentence, "The beautiful birds catch fish in the river". **f**, Syntactic information contained in the feedforward-input, Purkinje, feedforward-output cells, and the correct answer signal. The chance level of separation is 50% (gray horizontal line).

Training the convergent cANNs with the training sentences (e.g., from classic novels), again, significantly improved next-word prediction (Fig. 5b,c). The correct prediction rate using top 5 modules was 26.4% (median; interquartile range (IQR), 25.7%–27.1%; Fig 5c, blue; 33.6% by 10 modules), indicating that the convergent cANNs can also acquire next-word prediction. Because learning of the modules occurs independently, one after another, each convergent cANN module had only 1/10 of the learning opportunities compared to the non-convergent cANN, which may have resulted in lower prediction accuracy. In the example sentences (Fig. 5d, top), three different instances of "the" generated different activity patterns of Purkinje cell signals (Fig. 5d, the[1], the[2], the[3]), which led different proper predictions. Specifically, after "the[1]" for "man", a representative convergent cANN predicted "general", "prince", "roll", "same", and "kind"; after "open the[2]" for "gate", it predicted "post" and "door"; and after "read the[3]" for "book", it successfully predicted "book" and "press". In total, the correct prediction rate of the noun after a verb was 16.0% (median; IQR, 14.9%–17.0%), which was slightly lower than that of the non-convergent cANNs. In contrast, the correct prediction rate of prepositions after verbs was 65.0% (median; IQR, 60.8%–66.7%), slightly higher than that of the non-convergent cANNs. These results indicate that the convergent cANN has capability to make different proper predictions according to context, although the prediction accuracy is slightly lower depending on the word type than the original non-convergent cANN.

We then examined the capability of syntactic processing in the intermediate layer of the
convergent cANN and found that signals for subject, verb, and object words were highly
clustered and well separated (Fig. 5e). Comparing syntactic information along the feedforward
pathway (Fig. 5f), we found that syntactic information was not above the chance level in the
input layer, peaked at the Purkinje layer (S, 94.9%, V, 93.8%, O, 92.6%; almost equivalent to
the non-convergent cANN), and was significantly degraded in the output layer (p < 0.01 for any
of S, V, and O, Wilcoxon signed-rank test). Although the correct answer signal contained a
small amount of syntactic information (Fig. 5f, right), the Purkinje cells in the convergent-cANN
acquired a higher level of syntactic information, indicating that the convergent cANN have the
capability to extract syntactic information beyond all external inputs. The important conclusion
here is that our cerebellar models can acquire two cerebellar language functions, regardless of
the dimensionality or the cording format of the output cells.
364
DISCUSSION
Anatomical and physiological support for the cANN
Our cANN is highly consistent with a wealth of anatomical and physiological knowledge. This
new model effectively accounts for the cerebellar language functions by incorporating the
recently identified recurrent pathway into the feedforward circuit, which is the fundamental
structure of the conventional cerebellar circuit models. Regarding the recurrent pathway,
numerous reports have demonstrated the existence of the key part of the pathway, the output
cell-input cell projection[35, 36, 37, 38, 39], and its functional significance on the cerebellar prediction[34,
[37, 41]. The recurrent pathway has been implemented in cerebellar modeling[61]. Consistent with
this growing evidence for the significance of the recurrent pathway, we found that the pathway is
essential for predicting the next word in a sentence and processing syntactic information in the
cANN. We assumed that the Purkinje cell signal which is the source signal of the recurrent
pathway is persistent until the next word arrives, based on the physiological observation that the
predictive signal in Purkinje cells persists from the cue event until the actual event targeted for
prediction occurs[34, 45, 46]. This persistent predictive signal enables the recurrent signal to last
until the next word, preparing for integration with the next word information of the feedforward
pathway. The time interval between words in natural speech and reading is approximately 300
milliseconds (200 words per minute), which aligns well with the reported time scale of predictive
signal persistence in the Purkinje cells (over 500 ms)[34, 45, 46].
Traditionally the cerebellum has been modeled as feedforward circuits[57, 62, 63, 64, 65, 66, 67],
whereas our cANN incorporates the recurrent pathway. Feedforward models, with their
limitation of predicting the next word based solely on the immediately preceding word, have
significantly reduced capabilities compared to the cANN (see Extended Data Fig. 3). Indeed,
when we remove the recurrent pathway from the cANN and trained the cANN variant (emulating
a feedforward cerebellar model), both word prediction and syntactic processing became
inaccurate (data not shown), resembling the results of blocking the pathway post-training (see
Extended Data Figure 1 and Figure 3e). Moreover, conventional feedforward cerebellar models,

based on a two-layer perceptron model with Purkinje cells as the output layer, lack the
remarkable middle-layer processing capabilities found in the cANN. In contrast, the cANN can
extract syntactic information through middle-layer processing after training the output layer to
predict the next word. For the output of the middle-layer processing, we propose candidate
output pathways that can be tested in future circuit studies (Extended Data Fig. 4a).
With respect to learning, the cANN utilizes prediction error-based learning, a method
frequently employed in ANN models of the brain. Although this type of learning is widely used,
the cerebellum is a rare region where its application is physiologically plausible[68]. The
cerebellum is clearly considered to learn based on prediction errors in both motor and cognitive
processing[10, 28, 36, 42, 69]. The cANN incorporates the inferior olive-climbing fiber pathway, which
calculates and conveys prediction errors to the cerebellum (Fig. 1b). In prediction error
calculation, there is no need for a retention mechanism for the prediction signal until the next
word arrives, since the persistent predictive signal of Purkinje cells ensures that the circuit
output persists. Also, a series of studies indicate that the cerebellum can learn more flexibly
than classical cerebellar learning rules[40, 42, 43, 55, 70, 71, 72, 73, 74, 75]. In particular, based on
experimental findings and proposals that synaptic weights of Purkinje cells and cerebellar
nucleus neurons are updated in the direction to reduce prediction error, our cANN updated
synaptic weights[10, 50, 51].
Furthermore, we created cANN variants (including the convergent cANN) with further
biological constraints, demonstrating the robustness of the two cerebellar language functions of
the cANN. Together, our cANN is multilaterally consistent with our biological and physiological
knowledge about the cerebellum and is capable of reproducing high-level cognitive functions of
the brain.
415
Significance of a common computational basis for the two functions
Because the cerebellum has a uniform cytoarchitecture[4, 15, 36, 40, 76, 77, 78], much conventional
research has been directed toward elucidating the common circuit computation underlying all
cerebellar functions. Although many descriptive ideas have been proposed, none have yet
successfully explained all the diverse functions of the cerebellum[15]. For example, in the internal-
model theory, the cerebellum is a predictive simulator of the external world. This theory can
explain next-word prediction by replacing the external world as the prediction target with
sentences and viewing the cerebellum as a sentence simulator[6, 7, 8, 10, 15, 25]. However, explaining
syntactic processing with the predictive functions of the theory is difficult and requires other
ideas such as sequence processing[11, 13, 32].
Recognizing the limited reach of descriptive ideas to the common circuit computation,
Diedrichsen, Ivry, and colleagues emphasized the need for a more abstract concept, like the
network dynamics of neurons, to explain cerebellar computation[15]. Responding to precisely this
need, we here demonstrated that the network dynamics visualized by the cANN can capture the
common circuit computation underlying two major language functions. Considering next-word
prediction as a language case of cerebellar prediction function (i.e., internal-model function of

the cerebellum) and syntactic processing as a language case of sequence-processing function,
we can conclude that a single computational concept—the computation of our cANN—can unify
both types of cerebellar general function, at least in language processing. The following general
cerebellar computational mechanisms are indicated: (1) prediction-type (i.e., internal-model-
type) circuits have inputs/outputs and error-based learning consistent with previous proposals
(i.e., the circuit receives a series of events, produces predictions for one-step future events, and
is trained by prediction errors) [6, 7, 8, 10, 24, 25, 28], (2) the recurrent signal is essential for long time-
step dependent predictions, (3) sequence-processing-type circuits, depending on all the
elements of the prediction-type circuits, spontaneously emerge, with utilizing the middle-layer
processing as the output. Predictions by internal models are essential for various functions from
motor control to cognition[4, 5, 10, 15, 28, 29, 30, 31], and sequence processing is also of broad
importance; for example, the motor sequences for tool use in humans have a hierarchical
grammar-like structure (called "action grammar")[79, 80]. Therefore, we propose that the circuit
computation of our cANN is the generalized basis of the cerebellar computation that underlies a
wide range of motor and cognitive functions.
447
Differing roles of the neocortex and cerebellum in language function
The neocortex and cerebellum are tightly interconnected and cooperate to achieve
sophisticated functions such as language processing[5, 10, 14, 15, 28, 69, 81, 82, 83, 84, 85, 86], but it remains
unclear how the functions of the two regions differ and how the roles are shared. When
combined with clinical findings about language disorders, our cANN provides insights into the
differing roles of the neocortex and cerebellum. Although the cerebellar role is limited in adults[15,
87] and so the language functions of the cerebellum are considered subordinate to those of the
neocortex, in children, cerebellar language disorders cause permanent and severe deficits[17, 18,
19, 20], including agrammatism, suggesting that the development of the neocortex requires
cerebellar support[15, 17, 18]. The ability of the cANN to extract syntactic information independently
from the neocortex suggests that syntactic information is sent from the cerebellum during
development. If the neocortex can associate S-V-O information with the words themselves to
produce information such as word class, this process gradually becomes self-sustaining,
consistent with the clinical observations. Segmenting sentences according to S-V-O information
may allow the neocortex to process sentences more efficiently[88] (hierarchical processing,
Extended Data Fig. 4b,c). Considering that the cerebellum supports the development and
maturation of other cognitive functions of the neocortex[10, 15, 89, 90], the developmental importance
of sequence processing by the cerebellum may generalize to other cognitive functions in
addition to language processing.
467
Human-characteristic Cognition Revealed by Biologically Constrained ANN Models
ANN models can be categorized according to whether they comply with biological constraints,
and if the functions they realize are human-characteristic cognitive functions, for which neuronal
data are very limited (e.g., language processing, logical thinking, or social processing). Until

now, no brain circuit model has been developed to fulfill both criteria: adhering to biological
constraints and performing sophisticated human-characteristic cognitive functions. However,
many models exist which fulfill one or the other demand.
For non-human-characteristic functions (including less complex cognitive functions),
numerous ANN models have been proposed, with some adhering to biological constraints and
others not. Biologically constrained ANNs have been developed for regions like the cerebellum
and basal ganglia, realizing various basic sensorimotor functions including decision-making[62, 63,
64, 65, 66, 67, 91, 92, 93]. ANNs that do not account for essential biological constraints, such as circuit
connectivity between cell types, have been created for the cerebral neocortex using simple
recurrent neural networks (e.g., three-layer recurrent neural network)[94, 95, 96, 97] and for the visual
cortex utilizing deep-learning circuits[98, 99].
For higher-level cognitive processing such as language, far fewer ANNs have been
proposed, and none of them are biologically constrained. Namely, models of neocortical
language processing are based on language-processing AI circuits, which deviate from actual
brain anatomy and physiology (e.g., transformer, LSTM)[1, 2, 3, 100]. In contrast, the cANN is
designed based on the cerebellar local circuit and successfully realizes language functions of
the brain area. This is the first proposal of a biologically constrained brain model capable of
human-characteristic cognitive functions.
490
Future Directions
We anticipate the creation of biologically constrained ANNs to investigate cognitive functions
that are characteristic to humans and difficult to study in animal experiments will be a prominent
trend in neuroscience. This study using cANN is a pioneer in such research.
Biologically constrained ANNs also have potential for clinical applications. The following
insights gleaned from the findings of the cANN serve as an example. According to previous
studies, when two functions share a circuit, training one function can improve the other, even in
language functions[79, 80]. Our findings predict that training in predicting the next word will improve
the ability to process sentences with complex syntax, leading to the development of training in
language processing and rehabilitation of language dysfunction.
Much remains to be elucidated about the grammatical processing performed by the
cerebellum. Exploring the cANN's capacity beyond S-V-O syntactic processing, including its
potential to word class recognition (suggested by Extended Data Figure 2a) will offer valuable
insight into cerebellar grammar processing.
Interestingly, the convergent cANN, which incorporates the further constraint of
convergence in Purkinje-output connection into the original cANN, differs substantially from
typical circuit design of language-processing AI. Typical AI designs use compressed word
representations containing semantic information for input and the sparse one-hot word
representation for output. This input format aims to boost output accuracy by providing
additional information at the input stage, while the output format is designed to facilitate listing
multiple next-word candidates and accommodate sentences with various grammatically correct

branches. Conversely, the convergent cANN employs the sparse coding for input and a
compressed word representation for output. This design can be interpreted as aiming to learn
information-rich output from information-poor input, proposing a novel brain-inspired AI circuit.
Future research is anticipated to uncover the potential of this circuit design.
516
517

518 **METHODS**
519 **Simulation environment**
520 Code was written in Python and executed with Google Colab (Pro). The source code is
521 available on github (https://github.com/cANN-NLP/NLP_codes).
522

Circuit design of cANN
The cANN was created with Google's deep learning libraries, TensorFlow and Keras. To
replicate the local circuitry of the cerebellum, the cANN comprised three layers—an input layer
(granule cells), a middle layer (Purkinje cells), and an output layer (cerebellar nuclei neurons)—
with a recurrent pathway from the output layer to the input layer (Fig. 1b; Apps and Garwicz,
2005; Houck and Person, 2014; Ankri et al., 2015; Houck and Person, 2015; Gao et al., 2016;
Raymond and Medina, 2018; Ohmae et al., 2021). In addition, the cANN implemented the
climbing fiber pathway which is known to deliver prediction errors to the cerebellum in both
motor and cognitive functions (gray, Fig. 1b) (Ito 2008, *Nat Rev*; Sokolov et al. 2017, *Trends*
Cogn; Moberget et al. 2014, *JNS*). According to cerebellar learning theory that the cerebellum
learns to align its output (prediction) very faithfully with the correct answer signal (Doya, 2000,
Curr Opin; Ito 2008, *Nat Rev*), and that the representation of cerebellar output and correct
answer signal have the same dimensions (Kawato 1999, *Curr Opin*; Kawato et al. 2011, *Curr*
Opin), the output layer and the correct answer signal were set to have the same dimensionality.
Then, the prediction error is calculated by subtracting the prediction from the correct answer
signal.
The next-word prediction circuit was designed according to previous proposals, where
words are fed sequentially into the circuit then, at each step, the circuit outputs a prediction of
the next word, and information about the correct word information is given used as a teaching
signal to improve future predictions. In addition to the circuit connectivity, this biological
constraint on the inputs given to the circuit is also critical for simulating the acquisition of
function, because, in general, the difficulty of learning is determined by the information supplied
in the input signals, including error signals.
Integration of information between the feedforward and recurrent pathways occur as
follows: When a sentence begins, the Purkinje cells receive information about the first word from
the feedforward input cells and send their activity to the recurrent pathway (and to the
feedforward output pathway). Because the Purkinje cell signal is persistent, the recurrent-input
cell signal also persists until the feedforward-input cells receive the second word. The Purkinje
cells then integrate both signals (i.e., the second word from the feedforward-input cells and the
first-word information from the recurrent input cells) and transmit their new signal to the
recurrent pathway. In this way, the Purkinje cells sequentially integrate a newly entered word
with the previous words. We assumed that the feedforward and recurrent input cells are distinct
cell populations because the cerebellum has an enormous number of granule cells in the input
layer and individual cells receive only a small number of inputs (on average, only four).

To facilitate the investigation of information processing in this network, we assumed that
word representation is coded sparsely in the input layer and the correct answer signal (each of
3000 words is represented by one of 3000 cells; e.g., one cell encodes 'I' and another cell codes
'the'). Then, the immediately preceding word, which is the input to the circuit, and the correct
next word (for prediction error) are represented by an activity state in which only one cell is 1
and the rest are 0 (known as a one-hot representation). Theoretically, this representation is
known to contain no information associated with the word, such as the syntax or meaning of the
word (confirmed in Fig. 3d; cosine similarity is 0 for all word pairs); this allowed us to study the
learning and information processing of cANNs in an environment where there is no information
supplied externally other than word information.
The 3000 words represented by the 3000 cells were the 3000 most-frequent words in
the training sentences. All the other words that appeared less frequently were grouped together
as "unknown words" and assigned to the 3001st cell. For the prediction of the next word, the
word encoded by the most active output cell denoted the first prediction candidate. Note that in
the analysis, even if a prediction of "unknown" was correct, it was not considered a correct
prediction of the next specific word so was excluded from the calculation of the correct
prediction rate. The correct prediction rate is the percentage of matches between the top five
prediction candidates and the correct next word (i.e., this selection of the five candidates was
done for analysis purpose only).
Circuit connections denoted by arrows in Figure 1b implement F(Wx+b). For connections
from N presynaptic cells to M postsynaptic cells, x is an (N x 1) vector representing the activity
of the presynaptic neurons, W is an (M x N) matrix representing the synaptic weights from the
presynaptic neurons to the postsynaptic neurons, b is an (M x 1) vector representing the
spontaneous activity of the postsynaptic neurons, and F is the function that converts the
neuron's input to its output (firing frequency) using the leaky Rectified Linear Unit (leaky ReLU;
y = x, if x >= 0, and y = α * x, if x < 0). For F from the input cells to the Purkinje cells and the
output cells to the input cells, α = 0.14, and for F from the Purkinje cells to the output cells, α =
1.0. If alpha is 0, the input/output of the neuron is highly nonlinear; if alpha is 1, the input/output
is perfectly linear (y = x). Although alpha could be modified quite flexibly to train the circuit, the
cerebellum was assumed to be quite linear with Purkinje cells and output cells having high
spontaneous firing rates (i.e., linear computing; Raymond and Medina, 2018). Since no
functionally significant learning has been reported at this time for synaptic weights from the
Purkinje cells to the recurrent output cells and from the recurrent output cells to the recurrent
input cells, synaptic weights were assumed to be for relaying information (i.e., W = the identity
matrix).
The prediction output was compared with the desired output of the true next word (i.e.,
the ground truth) to calculate the prediction error (E), using the following formula:

$$Prediction\ error\ = cross\ entropy(T, softmax(O))$$

where T is the ground truth of the next word in the one-hot representation and O is the activity of
the output cells. The softmax function normalizes the outputs so that the sum of the outputs is
one and converts them to probabilities (P), and the cross entropy is the information of the
difference between T and P:

$$P_i = softmax(O_i) = \exp(O_i) / \sum \exp(O_i) \quad , \text{ for i = 1,...,3001 (index of cells)}$$
$$E = cross\ entropy(T,P) = \sum T_i \log(P_i) = \log(P_j)$$

for $T_i = 1$ (i = j) and $T_i = 0$ (i ≠ j), where j is the index corresponding to the next word. The
prediction error was used to update synaptic weights on the input (i.e. dendritic) side of the
Purkinje cells and the output cells (Fig. 1b, gray; Aizenman et al. 1998; Sokolov et al 2017).
Encouraged by recent discoveries and proposals suggesting stochastic gradient descent of
synaptic updates (i.e., in the direction to reduce prediction error) in the cerebellum (Bouvier et al.
2018; Shadmehr 2020), we assumed a gradient-descending update:

$$W_{ij} = W_{ij} - \varepsilon \frac{\partial E}{\partial W_{ij}}$$

where W represents the synaptic weights and ε is the learning rate.
To make the recurrent pathway more powerful, the number of recurrent input cells could
be increased, but increasing the number to more than 192 did not improve the accuracy of word
prediction or classification of the syntactic information. This suggests that more sentences are
needed to train a greater number of synapses.
613
Circuit design of convergent cANN
Following the anatomical convergence of Purkinje-output connection, we designed the
convergent cANN, in which we set the number of the feed-forward output cells to 16. Based on
the cerebellar learning theory mentioned earlier that the representation of cerebellar output and
correct answer have the same dimensions, we assumed that the cANN received 16-dimensional
correct answer signal. To represent the correct answer of 3000 words in 16 dimensions, we
employed a compressed word representation, akin to that in the neocortex (Huth et al. 2016,
Nature). Concretely, we adopted the 100-dimension word representation, made by Stanford
University group's GloVe algorithm and Wikipedia text dataset (glove-wiki-gigaword-100), and
reduced the 100 dimensions to 16 using PCA. Consequently, each word was represented as a
unique 16-cell activity pattern (a point in 16-dimensional space, fixed throughout the training).
The candidate predicted by the 16 output cells was defined as the word whose activity pattern is
closest to that of the output cells (≈, in Fig 5a). Since the 16 output cells of one module can
output only one word as a prediction, 10 modules were arranged in parallel with a shared input
cell layer to replicate the modular structure of the cerebellum. For learning, based on the
cerebellar learning theory of how multiple modules cooperate to achieve a complex function
(Jacobs et al. 1991; Wolpert & Kawato, 1998; Wolpert et al. 1998, *Trends Cogn Sci*; Haruno et
al., 2001; Kawato, Ohmae, et al. 2021), we set only the module with the closest prediction to the
correct answer receives the prediction error signal (gray solid line, Fig 5a). Although only one
module learns after each prediction, with training on a large number of predictions, all modules
should have the chance to make the best prediction and receive the prediction error (due to this,

each convergent cANN module had only 1/10 of learning opportunities compared with the
original non-convergent cANN, which may had resulted in slightly lower performance of the
convergent cANN).
In the analysis, we examined the five candidate words of the convergent cANN to
compare with the original cANN. To obtain the five candidates, we opted for training the 10-
module cANN and selecting the five best-performing modules, as this design resulted in higher
prediction accuracy than training the 5-module cANN and using all five modules. This difference
in performance is attributed to the numerous grammatically correct branches in sentences (e.g.,
various adverbs and verbs can follow a subject) that five modules were inadequate to encode.
The top five modules were selected based on prediction accuracy during training (in the last 1/8
lap). The differences in prediction accuracy between modules were highly consistent between
training data and validation data.
647
Circuit training
Twenty cANNs were trained independently. To train the cANNs, we used 88711 sentences from
the Gutenberg Corpus (novels such as *Moby-Dick*, *Alice in Wonderland*, etc.) and the Brown
Corpus of the Natural Language Toolkit (NLTK). Sentences that were too short (fewer than
three words) or contained too many unknowns (four or more) were excluded. Next-word
prediction was terminated at the 16th word if the sentence was too long. 90% (79444) of the
sentences were used for training and the remaining 10% were used to evaluate the prediction
performance during training. Training was terminated when the prediction performance
plateaued (at the end of the eighth lap of the 79444 sentences).
657
Data analysis
For the 20 cANNs, the median was used as the representative statistical feature and the
interquartile range (25th and 75th percentiles) was used for the error bars, in all cases except
where noted. To analyze the performance of the cANNs at next-word prediction and syntactic
processing after training, we used relatively simple sentences from online sites
(https://sentencedict.com/; https://lengusa.com/; https://www.rong-chang.com/nse/) because the
novels in the NLTK corpus contain many sentences that are not syntactically common (e.g.,
conversational calls). We selected 190 sentences containing verbs that the cANNs could handle
(i.e., verbs included in the 3000 encoded words). We added the sentence "The man will sail the
boat," which was used by Lesage and colleagues to examine language processing in the
cerebellum (Lesage et al. 2012), and the similar sentences "The man will read the book" and
"The man will open the gate." All test sentences are available in a text file, named as
test_sentences.txt, on github (https://github.com/cANN-NLP/NLP_codes). In the training
sentences, "read" and "open" appeared more frequently than "sail" (82 occurrences of "sail", 214
of "read", and 317 of "open").
The correct rate for next-word prediction was defined as the probability that one of the
first to fifth candidate words would match the correct next word (ground truth). We selected up

to the fifth candidate because that is the standard for the Google deep learning libraries used in

this study (keras.metrics.TopKCategoricalAccuracy) and is also the standard in recent AI

language processing. To examine the contribution of the recurrent signal, the recurrent signal

was blocked by setting the synaptic weight from the recurrent-input cells to Purkinje cells to 0.

To analyze the dynamics of activity of the 192 Purkinje cells, 1328 words in the 190

sentences were fed sequentially into the cANN, and we measured the corresponding 1328

activity states in 192 dimensions of the Purkinje cells. To visualize the transition of Purkinje cell

activity in a sentence, the 192 dimensions were compressed into two or three dimensions that

maximally preserved the variance of the 1328 points, using principal component analysis (PCA;

Python's online source-code library, scikit-learn). To evaluate the accuracy of classification of S-

V-O syntactic information in the neuronal activity, we measured the percentage separation of S

vs. V/O, V vs. S/O, and O vs. S/V with a nonlinear support vector machine (radial basis function

kernel). For this, 90% of the 190 evaluation sentences were used to determine the support

vector and the remaining 10% were used to obtain the classification accuracy (%); this process

was repeated 256 times to obtain the average accuracy (%). To visualize S-V-O syntactic

information in Figure 3a, we used the dimensions of the linear support vector machine, which

are best suited for S-V, V-O, and O-S separations (coordinates of vectors orthogonal to the

hyperplane best suited for the separations, obtained by svm.coef_ of scikit-learn). In the

comparison of the optimal dimensions of the linear support vector machine with the PCA

dimensions (Fig. 3c), the similarity index was calculated as the squared dot product of the unit

vectors representing the dimensions (squared was used because the sum of the 192

dimensions is one).

REFERENCES

1. Schrimpf M*, et al.* The neural architecture of language: Integrative modeling converges on predictive processing. *Proc Natl Acad Sci U S A* **118**, (2021).

2. Caucheteux C, King JR. Brains and algorithms partially converge in natural language processing. *Commun Biol* **5**, 134 (2022).

3. Caucheteux C, Gramfort A, King JR. Evidence of a predictive coding hierarchy in the human brain listening to speech. *Nat Hum Behav* **7**, 430-441 (2023).

4. Schmahmann JD, Guell X, Stoodley CJ, Halko MA. The Theory and Neuroscience of Cerebellar Cognition. *Annual review of neuroscience* **42**, 337-364 (2019).

5. Marien P*, et al.* Consensus paper: Language and the cerebellum: an ongoing enigma. *Cerebellum (London, England)* **13**, 386-410 (2014).

6. Moberget T, Gullesen EH, Andersson S, Ivry RB, Endestad T. Generalized role for the cerebellum in encoding internal models: evidence from semantic processing. *J Neurosci* **34**, 2871-2878 (2014).

7. Lesage E, Morgan BE, Olson AC, Meyer AS, Miall RC. Cerebellar rTMS disrupts predictive language processing. *Curr Biol* **22**, R794-795 (2012).

8. Lesage E, Hansen PC, Miall RC. Right Lateral Cerebellum Represents Linguistic Predictability. *J Neurosci* **37**, 6231-6241 (2017).

9. D'Mello AM, Turkeltaub PE, Stoodley CJ. Cerebellar tDCS Modulates Neural Circuits during Semantic Prediction: A Combined tDCS-fMRI Study. *J Neurosci* **37**, 1604-1613 (2017).

10. Sokolov AA, Miall RC, Ivry RB. The Cerebellum: Adaptive Prediction for Movement and Cognition. *Trends in cognitive sciences* **21**, 313-332 (2017).

11. Leggio MG, Chiricozzi FR, Clausi S, Tedesco AM, Molinari M. The neuropsychological profile of cerebellar damage: The sequencing hypothesis. *Cortex; a journal devoted to the study of the nervous system and behavior* **47**, 137-144 (2009).

12. Argyropoulos GP. The Subcortical Foundations of Grammaticalization. In: *The Evolution of*
Language) (2008).

13. Adamaszek M, Kirkby KC. Cerebellum and Grammar Processing. In: *The Linguistic Cerebellum*)
(2016).

14. Wagner MJ, Luo L. Neocortex-Cerebellum Circuits for Cognitive Processing. *Trends Neurosci* **43**,
42-54 (2020).

15. Diedrichsen J, King M, Hernandez-Castillo C, Sereno M, Ivry RB. Universal Transform or Multiple
Functionality? Understanding the Contribution of the Human Cerebellum across Task Domains.
Neuron **102**, 918-928 (2019).

16. Raichle ME*, et al.* Practice-related changes in human brain functional anatomy during nonmotor
learning. *Cereb Cortex* **4**, 8-26 (1994).

17. Steinlin M. The cerebellum in cognitive processes: supporting studies in children. *Cerebellum*
(London, England) **6**, 237-241 (2007).

18. Steinlin M. Cerebellar disorders in childhood: cognitive problems. *Cerebellum (London, England)*
7, 607-610 (2008).

19. Riva D, Giorgi C. The cerebellum contributes to higher functions during development: evidence
from a series of children surgically treated for posterior fossa tumours. *Brain* **123 (Pt 5)**, 1051-
1061 (2000).

20. Scott RB*, et al.* Lateralized cognitive deficits in children following cerebellar lesions. *Dev Med*
Child Neurol **43**, 685-691 (2001).

21. Momo K, Sakai H, Sakai KL. Syntax in a native language still continues to develop in adults:
honorification judgment in Japanese. *Brain Lang* **107**, 81-89 (2008).

22. Umejima K, Flynn S, Sakai KL. Enhanced activations in syntax-related regions for multilinguals
while acquiring a new language. *Scientific reports* **11**, 7296 (2021).

23. Goldstein A*, et al.* Shared computational principles for language processing in humans and deep
language models. *Nature neuroscience* **25**, 369-380 (2022).

24.   Pickering MJ, Garrod S. An integrated theory of language production and comprehension. *Behav*
Brain Sci **36**, 329-347 (2013).

25.   Argyropoulos GP. The cerebellum, internal models and prediction in 'non-motor' aspects of
language: A critical review. *Brain Lang* **161**, 4-17 (2016).

26.   Kuperberg GR, Jaeger TF. What do we mean by prediction in language comprehension? *Lang*
Cogn Neurosci **31**, 32-59 (2016).

27.   Balsters JH, Whelan CD, Robertson IH, Ramnani N. Cerebellum and cognition: evidence for the
encoding of higher order rules. *Cereb Cortex* **23**, 1433-1443 (2013).

28.   Ito M. Control of mental activities by internal models in the cerebellum. *Nature reviews* **9**, 304-313
(2008).

29.   Desmond JE, Fiez JA. Neuroimaging studies of the cerebellum: language, learning and memory.
Trends in cognitive sciences **2**, 355-362 (1998).

30.   McDougle SD*, et al.* Continuous manipulation of mental representations is compromised in
cerebellar degeneration. *Brain*, (2022).

31.   Wolpert DM, Miall RC, Kawato M. Internal models in the cerebellum. *Trends Cogn Sci* **2**, 338-347
(1998).

32.   Tedesco AM*, et al.* Does the cerebellum contribute to human navigation by processing sequential
information? *Neuropsychology* **31**, 564-574 (2017).

33.   Lupo M*, et al.* Does the cerebellar sequential theory explain spoken language impairments? A
literature review. *Clin Linguist Phon* **35**, 296-309 (2021).

34.   Ohmae S, Ohmae K, Heiney S, Subramanian D, Medina JF. A recurrent circuit links antagonistic
cerebellar modules during associative motor learning. *bioRxiv preprint*, (2021).

35.   Ankri L*, et al.* A novel inhibitory nucleo-cortical circuit controls cerebellar Golgi cell activity. *eLife*
4, (2015).

36.   Apps R, Garwicz M. Anatomical and physiological foundations of cerebellar information
810   processing. *Nature reviews* **6**, 297-311 (2005).

812   37.   Gao Z*, et al.* Excitatory Cerebellar Nucleocortical Circuit Provides Internal Amplification during
813   Associative Conditioning. *Neuron* **89**, 645-657 (2016).

815   38.   Houck BD, Person AL. Cerebellar loops: a review of the nucleocortical pathway. *Cerebellum*
816   *(London, England)* **13**, 378-385 (2014).

818   39.   Houck BD, Person AL. Cerebellar Premotor Output Neurons Collateralize to Innervate the
819   Cerebellar Cortex. *J Comp Neurol* **523**, 2254-2271 (2015).

821   40.   Raymond JL, Medina JF. Computational Principles of Supervised Learning in the Cerebellum.
822   *Annual review of neuroscience* **41**, 233-253 (2018).

824   41.   Xiao N*, et al.* Positive feedback of efferent copy via pontine nucleus facilitates cerebellum-
825   mediated associative learning. *Cell Rep* **42**, 112072 (2023).

827   42.   Ohmae S, Medina JF. Climbing fibers encode a temporal-difference prediction error during
828   cerebellar learning in mice. *Nature neuroscience* **18**, 1798-1803 (2015).

830   43.   Kitazawa S, Kimura T, Yin PB. Cerebellar complex spikes encode both destinations and errors in
831   arm movements. *Nature* **392**, 494-497 (1998).

833   44.   Ito M. Error detection and representation in the olivo-cerebellar system. *Frontiers in neural circuits*
834   **7**, 1 (2013).

836   45.   Halverson HE, Khilkevich A, Mauk MD. Relating cerebellar purkinje cell activity to the timing and
837   amplitude of conditioned eyelid responses. *J Neurosci* **35**, 7813-7832 (2015).

839   46.   Johansson F, Jirenhed DA, Rasmussen A, Zucca R, Hesslow G. Memory trace and timing
840   mechanism localized to cerebellar Purkinje cells. *Proc Natl Acad Sci U S A* **111**, 14930-14934
841   (2014).

843   47.   Doya K. Complementary roles of basal ganglia and cerebellum in learning and motor control.
844   *Current opinion in neurobiology* **10**, 732-739 (2000).

48.   Kawato M. Internal models for motor control and trajectory planning. *Current opinion in*
neurobiology **9**, 718-727 (1999).

49.   Kawato M, Kuroda S, Schweighofer N. Cerebellar supervised learning revisited: biophysical
modeling and degrees-of-freedom control. *Current opinion in neurobiology* **21**, 791-800 (2011).

50.   Bouvier G*, et al.* Cerebellar learning using perturbations. *eLife* **7**, (2018).

51.   Shadmehr R. Population coding in the cerebellum: a machine learning perspective. *J*
Neurophysiol **124**, 2022-2051 (2020).

52.   Elman JL. Finding Structure in Time. *Cognitive Science* **14**, 179-211 (1990).

53.   Socher R, Lin CC-Y, Ng AY, Manning CD. Parsing natural scenes and natural language with
recursive neural networks. In: *ICML*) (2011).

54.   Chang F, Dell GS, Bock K. Becoming syntactic. *Psychological Review* **113**, 234-272 (2006).

55.   Gao Z, van Beugen BJ, De Zeeuw CI. Distributed synergistic plasticity and cerebellar learning.
Nature reviews **13**, 619-635 (2012).

56.   Isope P, Barbour B. Properties of unitary granule cell-->Purkinje cell synapses in adult rat
cerebellar slices. *J Neurosci* **22**, 9668-9678 (2002).

57.   Brunel N, Hakim V, Isope P, Nadal JP, Barbour B. Optimal information storage and the
distribution of synaptic weights: perceptron versus Purkinje cell. *Neuron* **43**, 745-757 (2004).

58.   Kawato M, Ohmae S, Hoang H, Sanger T. 50 Years Since the Marr, Ito, and Albus Models of the
Cerebellum. *Neuroscience* **462**, 151-174 (2021).

59.   Haruno M, Wolpert DM, Kawato M. Mosaic model for sensorimotor learning and control. *Neural*
Comput **13**, 2201-2220 (2001).

60.   Huth AG, de Heer WA, Griffiths TL, Theunissen FE, Gallant JL. Natural speech reveals the
semantic maps that tile human cerebral cortex. *Nature* **532**, 453-458 (2016).

61.   Khilkevich A, Canton-Josh J, DeLord E, Mauk MD. A cerebellar adaptation to uncertain inputs.
883   *Sci Adv* **4**, eaap9660 (2018).

885   62.   Albus JS. A theory of cerebellar function. *Mathematical Biosciences* **10**, 25-61 (1971).

887   63.   Marr D. A theory of cerebellar cortex. *J Physiol* **202**, 437-470 (1969).

889   64.   Buonomano DV, Mauk MD. Neural Network Model of the Cerebellum: Temporal Discrimination
890   and the Timing of Motor Responses. *Neural Computation* **6**, 38-55 (1994).

892   65.   Medina JF, Mauk MD. Computer simulation of cerebellar information processing. *Nature*
893   *neuroscience* **3 Suppl**, 1205-1211 (2000).

895   66.   Yamazaki T, Tanaka S. The cerebellum as a liquid state machine. *Neural Netw* **20**, 290-297
896   (2007).

898   67.   Narain D, Remington ED, Zeeuw CI, Jazayeri M. A cerebellar mechanism for learning prior
899   distributions of time intervals. *Nat Commun* **9**, 469 (2018).

901   68.   Doya K. What are the computations of the cerebellum, the basal ganglia and the cerebral cortex?
902   *Neural Netw* **12**, 961-974 (1999).

904   69.   Porrill J, Dean P, Stone JV. Recurrent cerebellar architecture solves the motor-error problem.
905   *Proc Biol Sci* **271**, 789-796 (2004).

907   70.   Hull C. Prediction signals in the cerebellum: beyond supervised motor learning. *eLife* **9**, (2020).

909   71.   Boyden ES, Katoh A, Raymond JL. Cerebellum-dependent learning: the role of multiple plasticity
910   mechanisms. *Annual review of neuroscience* **27**, 581-609 (2004).

912   72.   Carey M, Lisberger S. Embarrassed, but not depressed: eye opening lessons for cerebellar
913   learning. *Neuron* **35**, 223-226 (2002).

915   73.   Medina JF. The multiple roles of Purkinje cells in sensori-motor calibration: to predict, teach and
916   command. *Current opinion in neurobiology* **21**, 616-622 (2011).

918   74.   Aizenman CD, Manis PB, Linden DJ. Polarity of long-term synaptic gain change is related to
919   postsynaptic spike firing at a cerebellar inhibitory synapse. *Neuron* **21**, 827-835 (1998).
920

921   75.   Kitazawa S, Wolpert DM. Rhythmicity, randomness and synchrony in climbing fiber signals.
922   *Trends Neurosci* **28**, 611-619 (2005).
923

924   76.   Apps R, Hawkes R. Cerebellar cortical organization: a one-map hypothesis. *Nature reviews* **10**,
925   670-681 (2009).
926

927   77.   Ramnani N. The primate cortico-cerebellar system: anatomy and function. *Nature reviews* **7**, 511-
928   522 (2006).
929

930   78.   De Zeeuw CI. Bidirectional learning in upbound and downbound microzones of the cerebellum.
931   *Nat Rev Neurosci* **22**, 92-110 (2021).
932

933   79.   Thibault S*, et al.* Tool use and language share syntactic processes and neural patterns in the
934   basal ganglia. *Science (New York, NY* **374**, eabe0874 (2021).
935

936   80.   Higuchi S, Chaminade T, Imamizu H, Kawato M. Shared neural correlates for language and tool
937   use in Broca's area. *Neuroreport* **20**, 1376-1381 (2009).
938

939   81.   Li N, Mrsic-Flogel TD. Cortico-cerebellar interactions during goal-directed behavior. *Current*
940   *opinion in neurobiology* **65**, 27-37 (2020).
941

942   82.   Ohmae S, Uematsu A, Tanaka M. Temporally specific sensory signals for the detection of
943   stimulus omission in the primate deep cerebellar nuclei. *J Neurosci* **33**, 15432-15441 (2013).
944

945   83.   Bostan AC, Dum RP, Strick PL. Cerebellar networks with the cerebral cortex and basal ganglia.
946   *Trends in cognitive sciences* **17**, 241-254 (2013).
947

948   84.   Kinno R, Ohta S, Muragaki Y, Maruyama T, Sakai KL. Differential reorganization of three syntax-
949   related networks induced by a left frontal glioma. *Brain* **137**, 1193-1212 (2014).
950

951   85.   Tanaka M*, et al.* Roles of the Cerebellum in Motor Preparation and Prediction of Timing.
952   *Neuroscience* **462**, 220-234 (2021).
953

954   86.   Proville RD*, et al.* Cerebellum involvement in cortical sensorimotor circuits for the control of
955   voluntary movements. *Nature neuroscience* **17**, 1233-1239 (2014).

957   87.   Fiez JA, Raichle ME. Linguistic processing. *Int Rev Neurobiol* **41**, 233-254 (1997).

959   88.   Ding N, Melloni L, Zhang H, Tian X, Poeppel D. Cortical tracking of hierarchical linguistic
960   structures in connected speech. *Nature neuroscience* **19**, 158-164 (2016).

962   89.   Wang SS, Kloth AD, Badura A. The cerebellum, sensitive periods, and autism. *Neuron* **83**, 518-
963   532 (2014).

965   90.   Badura A*, et al.* Normal cognitive and social development require posterior cerebellar activity.
966   *eLife* **7**, (2018).

968   91.   Lo CC, Wang XJ. Cortico-basal ganglia circuit mechanism for a decision threshold in reaction
969   time tasks. *Nature neuroscience* **9**, 956-963 (2006).

971   92.   O'Reilly RC, Frank MJ. Making working memory work: a computational model of learning in the
972   prefrontal cortex and basal ganglia. *Neural Comput* **18**, 283-328 (2006).

974   93.   Chen G, Scherr F, Maass W. A data-based large-scale model for primary visual cortex enables
975   brain-like robust and versatile visual processing. *Sci Adv* **8**, eabq7592 (2022).

977   94.   Mante V, Sussillo D, Shenoy KV, Newsome WT. Context-dependent computation by recurrent
978   dynamics in prefrontal cortex. *Nature* **503**, 78-84 (2013).

980   95.   Chen G, Kang B, Lindsey J, Druckmann S, Li N. Modularity and robustness of frontal cortical
981   networks. *Cell* **184**, 3717-3730 e3724 (2021).

983   96.   Sussillo D, Abbott LF. Generating coherent patterns of activity from chaotic neural networks.
984   *Neuron* **63**, 544-557 (2009).

986   97.   Wang XJ. Decision making in recurrent neuronal circuits. *Neuron* **60**, 215-234 (2008).

988   98.   Yamins DL, DiCarlo JJ. Using goal-driven deep learning models to understand sensory cortex.
989   *Nature neuroscience* **19**, 356-365 (2016).

991   99.   Yamins DL, Hong H, Cadieu CF, Solomon EA, Seibert D, DiCarlo JJ. Performance-optimized

992   hierarchical models predict neural responses in higher visual cortex. *Proc Natl Acad Sci U S A*

993   **111**, 8619-8624 (2014).

995   100.   Costa R, Assael IA, Shillingford B, de Freitas N, Vogels T. Cortical microcircuits as gated-

996   recurrent neural networks. *Advances in neural information processing systems* **30**, (2017).