This population doesn't exist: learning the distribution of evolutionary histories with

generative adversarial networks

William W. Booker[1*], Dylan D. Ray[1], Daniel R. Schrider[1]

[1]Department of Genetics, University of North Carolina at Chapel Hill, Chapel Hill, North

Carolina, United States of America

* Corresponding author

E-mail: wbooker14@gmail.com

ABSTRACT

Numerous studies over the last decade have demonstrated the utility of machine learning methods when applied to population genetic tasks. More recent studies show the potential of deep learning methods in particular, which allow researchers to approach problems without making prior assumptions about how the data should be summarized or manipulated, instead learning their own internal representation of the data in an attempt to maximize inferential accuracy. One type of deep neural network, called Generative Adversarial Networks (GANs), can even be used to generate new data, and this approach has been used to create individual artificial human genomes free from privacy concerns. In this study, we further explore the application of GANs in population genetics by designing and training a network to learn the statistical distribution of population genetic alignments (i.e. data sets consisting of sequences from an entire population sample) under several diverse evolutionary histories—the first GAN capable of performing this task. After testing multiple different neural network architectures, we report the results of a fully differentiable Deep-Convolutional Wasserstein GAN with gradient penalty that is capable of generating artificial examples of population genetic alignments that successfully mimic key aspects of the training data, including the site frequency spectrum, differentiation between populations, and patterns of linkage disequilibrium. We demonstrate consistent training success across various evolutionary models, including models of panmictic and subdivided populations, populations at equilibrium and experiencing changes in size, and populations experiencing either no selection or positive selection of various strengths, all without the need for extensive hyperparameter tuning. Overall, our findings highlight the ability of GANs to learn and mimic population genetic data, and suggest future areas where this work can be applied in population genetics research that we discuss herein.

AUTHOR SUMMARY

The application of deep-learning to biological problems has expanded greatly over the last

decade. One type of deep neural network, called a Generative Adversarial Network (GAN),

attempts to generate artificial examples of a given type of data by learning to fool a discriminator

that is simultaneously learning to discriminate between real and artificial examples. In this study,

we design a GAN whose purpose is to generate artificial examples of genetic alignments from

biological populations of varying evolutionary histories—essentially learning the statistical

distribution of those evolutionary histories. We show that our GAN is able to mimic key aspects

of the genetic alignments relevant to population genetics, and that the GAN does not require

extensive tuning of the network parameters. Ultimately, this work demonstrates the ability of

these networks to learn and mimic population genetic data, and highlights future areas where

this work can be applied and expanded.

INTRODUCTION

Accurately capturing the properties of genetic variation to infer evolutionary processes is a

major goal of population genetics. Throughout the history of population genetic research, myriad

summary statistics have been created to accomplish this task. Ideally, the values of a given

statistic follow theoretical predictions and are robust to additional unconsidered forces. For

example, π [1], which measures the degree of nucleotide diversity in a population, is reduced by

linked directional selection in a manner that is predicted by the selection coefficient and the

recombination landscape around the selected site(s) [2–5]. However, diversity levels are also

affected by other processes such as population bottlenecks and population subdivision [6].

Although the simplicity of this univariate summary of genetic diversity makes it well-suited for

theoretical studies of the effects of various evolutionary processes on diversity, this also renders

π relatively uninformative for distinguishing among the diversity of complex evolutionary

scenarios considered in modern population genetic inference.

As a solution to this problem, researchers have turned to either creating more complex statistics

[e.g. 7,8] or using methods that rely on a number of theoretically informative summary statistics

to infer a process or evolutionary history [9,10]. Common to the latter approaches is the

leveraging of increasingly greater amounts of information or observations to make evolutionary

inferences, and this increased inferential power typically comes at the cost of reduced

interpretability. As the number of summary statistics used increases, it becomes less apparent

how any one statistic, and especially any combination of statistics, is informative about the

process in question. Ultimately, the tools we use to make meaningful inference currently lie on a

continuum between interpretability and power, and researchers must make a choice within this

continuum for the question at hand.

If simple statistics lie on one end of the interpretability-power continuum, deep-learning methods

lie on its opposite. Often described as a 'black box', deep-learning models frequently have

millions of parameters that make identifying the features responsible for a given inference a

challenging task [11–13]. However, these methods can be remarkably powerful and in some

cases have made dramatic progress in the biological domain [e.g. 14]. In population genetics,

deep-learning methods have been used for a number of purposes, such as detecting

introgression [15]—including adaptive introgression [16]; distinguishing among various modes of

natural selection as well as neutral evolution [17–20]; estimating parameters such as selection

coefficients and recombination rates [15,21], dispersal distances [22], and population sizes [23];

and visualizing population structure [24].

Although deep-learning networks are often thought of as an uninterpretable 'black box', one

argument suggests that such algorithmically generated models may in fact be well suited to

model natural phenomena that are generated by complex processes that are inherently

uninterpretable through the lens of simple statistical models [25]. Rather than reducing our data

down to some predetermined set of variables, many of these networks—such as those that use

convolutional neural networks [26,27]—are able to learn their own data representations from the

raw data itself. Because they do not rely on *a priori* assumptions of how to summarize our data,

these methods can potentially learn to extract the information needed to make accurate

inferences without requiring our data be manipulated in ways that may be biased or otherwise

omit useful information. While much of the natural world can be understood using mechanistic

models with clear causes and effects, restricting ourselves to this frame of understanding

renders biological science myopic—precluding our ability to discover more complex phenomena

with emergent properties otherwise unaccounted for. In evolutionary biology, and in particular

population genetics, progress has traditionally relied on this mechanistic framework though the

development of theoretical models that are then used to explain our observations [10]. Deep-

learning methods, however, allow us to take the opposite approach: letting observation directly

inform our understanding [28].

One limitation of this approach is that for most evolutionary processes we have few example

phenomena where the true evolutionary history with respect to the phenomenon of interest is

known with complete certainty. For example, although there are many loci where we strongly

suspect there has been recent positive selection, even for the best studied examples we often

cannot be certain of the identity of the selected site, or even gene, let alone of parameters such

as the strength of selection. Thus, typically in machine learning applications to population

genetic problems, the training observations themselves must be generated from simulations

based on reductionist models [but see 29]. However, if we leverage the usefully reductive

aspects of biology (e.g. predictable changes in allele frequencies in response to selection)

alongside the advantages of deep-learning methods to factor in the unreducible parts (i.e. the

messy nature of biological data and its collection), it may be possible to render this limitation

advantageous.

In this study, we focus on Generative Adversarial Networks (GANs), a specific class of deep-

learning network that may be particularly useful in population genetics. Variations of GANs have

been previously used to generate artificial human genomes [30] and estimate demographic

parameters of populations [31]. While the explicit function of these networks is to generate

artificial examples of some set of input data, training these networks aims to learn the statistical

distribution of the input data in a multidimensional parameter space [32]. As a result, GANs can

be useful for any task where identifying this distribution is advantageous and can be exploited,

such as data augmentation [33], classification [34], clustering [35], or the transfer of properties

from one dataset onto another [i.e. style transfer; 36]. Importantly, by learning this distribution,

any artificial examples generated by the GAN are not tied to any one input example. This

property makes GANs particularly useful for generating testing data containing sensitive

information or where privacy is a concern, such as data collected from human subjects [30,37].

Here, we complement previous work using generative models in population genetics by

designing the first fully differentiable GAN capable of generating artificial population genetic

alignments. We begin with a design based on the Wasserstein GAN [38] and test several

different architectures to find the optimal design for this task. We then simulate alignments

under a variety of evolutionary scenarios, including models of population size change,

subdivision, and natural selection, and evaluate our GAN's ability to accurately capture and

replicate alignment properties under each of these scenarios. Finally, we discuss the strengths

and weaknesses of our GAN, and propose paths forward for using GANs for population genetic

modeling and inference.

METHODS

GAN Overview

Generative Adversarial Networks (GANs) are in actuality a combination of two different

networks that compete against each other during training. As initially designed, these two

networks consist of a generator that produces some output from a latent noise vector as input,

and a discriminator that takes in both real and generated data and attempts to distinguish

between the two [39]. By training these two networks in tandem, the generator should get

progressively better at producing realistic copies while the discriminator gets better at

distinguishing those fake copies from real ones. Critically, the generator is blind to the data it is

trying to replicate, and only receives updates from the discriminator on its performance.

Architecture and Implementation

All networks were created using python version 3.9.7 along with pytorch version 1.9.1 [40] and

numpy version 1.20.3 [41]. To design our GAN, we tested several network architectures with

different combinations of layers and properties to find an architecture that performed

consistently across runs and population genetic models. Largely, the networks tested were

variations of a Deep Convolutional GAN [34] or a ResNet GAN [as implemented in 42], with the

ResNet GAN being largely a modification of the DCGAN architecture where the input to each

convolutional layer block is added to its output. These networks were initially designed to

reproduce two-dimensional images with color values on 3 channels, and this data structure is

easily translatable to population genetic alignments with biallelic polymorphisms by reducing the

network to a single color channel, analogous to a black and white image, with values that

represent ancestral (0) or derived (1) alleles. However, while this structure captures allelic

information at each site it leaves out valuable information about the position of those sites along

a sequence. To include this information, in both the generator and discriminator networks we

included two branches, one performing two-dimensional convolutions on the alignment matrix,

and the other performing one-dimensional convolutions on the vector of positions for each

polymorphism in the alignment (Fig. 1).

One difficulty with GANs as initially designed is the "vanishing gradient" problem, where the

discriminator learns too quickly and the generator is unable to keep up. To prevent this from

occurring, we used the Earth Mover's (EM) distance as our loss function as implemented in the

Wasserstein GAN [WGAN; 38], which rather than treating the discriminator and generator as

adversaries in a min-max game using the discrete prediction of real (1) or fake (0) from the

sigmoid activated output of the discriminator [as in the original GAN; ,39], attempts to minimize

the 'effort' required to transform the distribution of values output by the discriminator (or critic, in

Wasserstein GANs) when given generated examples into the distribution of real examples.

However, by using the EM distance as a loss function the network is no longer 1-Lipshitz

continuous and requires either weight clipping or other modifications to enforce the Lipshitz

constraint. To enforce this constraint, we added a gradient penalty [42] to the loss calculation:

Eq. 1

$$L = \mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_g}[D(\tilde{\boldsymbol{x}})] - \mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_r}[D(\boldsymbol{x})] + \lambda \mathop{\mathbb{E}}_{\hat{\boldsymbol{x}} \sim \mathbb{P}_{\hat{\boldsymbol{x}}}}\left[\left(\left\|\nabla_{\hat{\boldsymbol{x}}} D(\hat{\boldsymbol{x}})\right\|_2 - 1\right)^2\right]$$

Here, the first two elements of the equation $\mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_g}[D(\tilde{\boldsymbol{x}})] - \mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_r}[D(\boldsymbol{x})]$ calculate the EM distance

between the discriminator's predictions on generated (the first term) and real data (the second

term), with the second half $\lambda \mathop{\mathbb{E}}_{\hat{\boldsymbol{x}} \sim \mathbb{P}_{\hat{\boldsymbol{x}}}}\left[\left(\left\|\nabla_{\hat{\boldsymbol{x}}} D(\hat{\boldsymbol{x}})\right\|_2 - 1\right)^2\right]$ calculating a penalty on the gradient norm of

the discriminator for examples randomly sampled in between real and generated data ($\hat{x} \sim \mathbb{P}_{\hat{x}}$),

with deviations of this norm from 1 being penalized according to the penalty hyperparameter λ.

By designing our GAN this way, training should converge more easily and be more stable

across runs and hyperparameter values. Finally, we used the 'Adam' optimizer for training [43].

Within the overall architectures outlined above, we also tested a number of more subtle

variations of the network architecture to arrive at a more optimal solution. These included

various normalization layers following convolutions (batch, instance, layer), activation functions

following internal convolutions (ReLU and leaky ReLU), adding Gaussian noise between layers

in the discriminator, upsampling and transposed convolutions in the generator, and final

activation layers in the generator (sigmoid, tanh, Gumbel softmax). Regarding the final

activation, the sigmoid activation [0,1] value was interpreted as the probability of having a

derived allele for a given individual at each site, with the tanh activation [-1,1] being a similar

probability when re-scaled to [0,1]. The Gumbel softmax activation was tested in an attempt to

discretize the generated alignments fed into the discriminator with the value for a given

individual at each site representing an allele belonging to either the ancestral (0) or derived (1)

class.

In addition to these variations, we also attempted to add in additional information in the models

related to the variation and frequency of alleles. A fundamental difference between simulated

alignments and alignments generated by a GAN is that output from simulated alignments are

guaranteed to have variation at every site, whereas the GAN has no such guarantee and

variation at every site must be learned or achieved by some other means after generating the

data. To assist training in ensuring variation at every site, we tested networks that had an

additional loss term penalizing monomorphic sites added to the generator loss (Eq. 2, where l is

the number of sites and ω is some weight either fixed or tied to the gradient penalty loss) and

additional features passed as input into the discriminator including the sum, minimum,

maximum, and variance of values at each site. To ensure variation at every site in generated

alignments, a random individual at sites initially monomorphic for the ancestral allele was

chosen to have the derived allele, with this choice weighted by each individual's probabilities

from the final activation layer. The same was done for sites monomorphic for the derived allele,

except in these cases the weight used to randomly select an individual to be given the ancestral

allele was one minus the probability from the final activation later.

Eq. 2

201
$$\sum_{i=1}^{l}(1 - (max_i - min_i)) * \omega$$

Simulations and Models

We tested the ability of our GAN to broadly capture the properties of population genetic

alignments by training the GAN using several different simulated models as input. All models

were simulated using coalescent simulators: ms [44], discoal [45], or stdpopsim version 0.1.2

[46] with msprime version 1.0.2 [47,48] as the backend of stdpopsim. The most basic of models

assessed were a standard neutral model both with and without recombination. Together, these

models allow us to evaluate the GAN's ability in the simplest of cases as well as its ability to

capture information about the covariance of nearby sites when recombination is present. We

also evaluated a model of isolation with migration of two equally sized populations,

experimenting with several rates of migration. To evaluate the GAN's ability to learn to model

population structure from structure in the alignment, we trained the GAN where the input was

the direct output from the simulation (where the population 1 is the first 32 rows of the

alignment, and population 2 the remaining 32 rows) and where the input rows (individuals) were

shuffled. Additionally, we evaluated models where there was a recent population expansion or

contraction. To assess performance on a more complex demographic model, we trained the

GAN using simulations from the two- population 'Out of Africa' model from Tennessen et al.

[49].Finally, we assessed the ability of the GAN to replicate patterns of recent positive selection

by simulating models of strong and moderate selective sweeps ($2Ns$=2000 and $2Ns$=100,

respectively) where the selected site was in the middle of the alignment and the sweep had

completed upon sampling. The standard neutral and IM models were simulated with a set

number of segregating sites using the ms '-s' flag. All other models were simulated with a

variable number of sites, and 64 sites were extracted for training by taking the 64 sites

surrounding the most central position in the alignment. Note that because of this, the locus-wide

recombination rate parameter used for these simulations is greater than or equal to that of the

window of the alignment fed as input into the GAN. This also ensured that, for the simulations of

selection, the selected site was always in the center of the alignment and could be properly

captured by windowed diversity metrics. All simulation commands are available in the

supplement (Supp. Table 1).

Evaluation

We used a number of measures relevant to population genetics to evaluate the performance

and training of our GAN. Because of the nature of adversarial training, the loss of GANs does

not directly correlate to the ability of the GAN to generate realistic copies. Typically, these GANs

are evaluated by some metric calculated using a pretrained network to determine the similarity

of GAN output to the input data, such as inception scores [50], however the inception network

was designed and trained for use with 3-channel color images rather than the binary alignments

used here. To evaluate our single channel output, we evaluated our GAN using the 2D sliced

Wasserstein distance of the distribution characterized by the first two principal components

calculated from the site-frequency spectra (SFS) of the input and generated alignments

(referred hereafter as 2DSWD). This measurement is an approximation of the exact

Wasserstein (or earth mover's) distance calculated through linear slicing of the two distributions

[51].

Similar to Yelmen et al. [30], we used nearest-neighbor adversarial accuracy (here calculated

using the SFS of each alignment) to evaluate over and underfitting [see 37]. We used Eq. 3-5

(reproduced from [30]) to calculate 3 adversarial accuracy scores: AA_{truth}, AA_{syn}, and AA_{TS}.

Here, m is the number of alignments (real alignments for Eq. 3, and generated alignments for

Eq. 4), the function 1 returns 1 if its input value is true and 0 otherwise, $d_{TS}(i)$ is the distance

between the ith real alignment its nearest generated alignment, $d_{ST}(i)$ is the distance between

the ith generated alignment and its nearest real alignment, $d_{TT}(i)$ is the distance between the ith

real alignment indexed and its nearest neighboring real alignment, and $d_{SS}(i)$ is the distance

between the ith generated alignment and its nearest neighboring generated alignment. The

optimal value for all AA values is 0.5, with an AA_{TS} above and below 0.5 suggesting the

generator is underfitting or overfitting, respectively.

Eq. 3

$$AA_{truth} = 1/m * \sum_{i=1}^{m} 1(d_{TS}(i) > d_{TT}(i))$$

256   Eq. 4

$$AA_{syn} = 1/m * \sum_{i=1}^{m} 1(d_{ST}(i) > d_{SS}(i))$$

258   Eq. 5

$$AA_{truth} = 1/2 * (AA_{truth} + AA_{syn})$$

To broadly capture the similarity of the input and generated alignments, we calculated and

compared the average SFS, and joint SFS for two-population models using scikit-allel [52]. To

assess the GAN's ability to mimic recombination, we calculated the decay of gametic linkage

disequilibrium (as measured by r^2) with distance. To investigate population size histories

consistent with the observed SFS, we used the program Stairway Plot version 2.1.1 [53].

Finally, we also calculated the summary statistics Watterson's θ [54], Tajima's D [55], π [1], and

ω [56]. For each model evaluated, we used a training set of 20,000 input alignments and trained

for 10,000 epochs. Because GANs may become unstable as training goes on, we saved the

network after every 100 epochs and evaluated the performance of the saved model that

minimized the 2DSWD as calculated above.

RESULTS

Architecture

Final architecture

We experimented with several GAN architectures for generating population genetic alignments

(Methods). Of the architectures tested, our final design was a modification of the DCGAN with

Wasserstein loss and gradient penalty to enforce 1-Lipschitz continuity (Fig. 1). The final design

takes in a noise vector of samples from a 128-dimensional standard normal distribution as input.

This input is then branched into two series of convolutions to produce the alignment and

positions vector, respectively. In the generator, the initial transformation from the latent vector in

the alignment branch involves a 2D transposed convolution from the 128-channel noise vector

to 512 channels with a kernel size of 4, a stride of 1, and no padding, followed by a batch

normalization layer and leaky ReLU activation with a negative slope of 0.1. Following the initial

transformation are 3 additional transposed convolutional layers with batch normalization and

leaky ReLU, and each of these layers reduces the number of channels by half with a kernel size

of 4, stride of 2, and padding of 1. The final transposed convolution has the same kernel, stride,

and padding as previous layers and produces a 64x64 alignment on a single channel, has no

batch normalization layer, and is followed by a sigmoid activation layer producing values from 0

to 1 which we interpret as the probability of having a derived allele for each individual at each

site. For the positions branch, the same 128-channel noise vector used in the alignment branch

is passed through an initial 1D transposed convolution that reduces the number of channels by

half with a kernel size of 4, stride of 1, and no padding, followed by a batch normalization layer

and a leaky ReLU activation with negative slope 0.1. This initial transformation is followed by 3

additional 1D transposed convolutional layers that each reduce the number of channels in half

and are each followed by batch normalization and leaky ReLU activation, and that have a kernel

size of 4, stride of 2, and padding of 1. The final 1D convolution produces a 1x64 vector on a

single channel with a single convolution and is followed by a sigmoid activation layer to produce

values from 0 to 1, with the boundaries of this range indicating the beginning and end of the

chromosome, respectively.

The discriminator largely mirrors the generator in the reverse. In the alignment branch, the

64x64x1 alignment is initially transformed into 64 channels via a 2D convolution with a kernel

size of 4, stride of 2, and padding of 1, followed by a layer normalization layer and a leaky ReLU

activation with negative slope 0.1. This is followed by 3 additional 2D convolutions with the

same layer normalization and leaky ReLU activation, but instead the number of channels

doubles after each of these convolution layers. The positions branch is initially transformed

through a 1D convolution into 16 channels with a kernel size of 4, stride of 1, and no padding,

followed by layer normalization and leaky ReLU activation with negative slope 0.1. This initial

transformation is then followed by 3 additional 1D convolutions with the same layer

normalization and leaky ReLU activation, but with the number of output channels doubling after

every convolution. After all convolutions, the alignment and positions branches are both

flattened down to a single dimension, concatenated, and passed through a dense layer with a

linear activation to produce a single output.

Hyperparameter tuning of batch size, lambda value for the gradient penalty, number of critic

(discriminator) iterations per generator training step, leaky ReLU negative slope, and learning

rate produced some variation in the performance of our GAN, but largely the GAN demonstrated

stability over a wide variety of hyperparameter values (Supp. Table 1). Additionally, there was

no clear value for any hyperparameter that consistently performed better than others across

multiple hyperparameter combinations. Ultimately, we chose the hyperparameter values that

minimized the average of the last 5 saved 2DSWDs. This distance was calculated and saved

after every 100 epochs, training for 5000 epochs total with 10,000 alignments as input. The final

hyperparameter values were: batch size = 256, lambda = 10, critic iterations = 5, negative slope

= 0.1, and learning rate = 0.0002.

Additional architectures

Aside from our final GAN design, we tested several modifications of the final architecture or

alternatives that we found performed more poorly. Most surprisingly, ResNet architectures

[38,57], which show improved performance over DCGANs in generating color images,

performed worse than DCGANs for our purposes. Rarely did ResNet architectures produce

something resembling an alignment, and when it did, these alignments were poor

representations of the input alignments. Similarly, other proposed additions or variations to

improve performance including upsampling in the generator, adding Gaussian noise between

discriminator layers, smoothing allele values (subtracting or adding a small noise value drawn

from $U(0,0.05)$ to all values in the alignment), and flipping (switching 1-5% of generated and

input example labels going into the discriminator) also reduced performance. Upsampling in

particular produced output that had large, smooth blocks of similar values instead of the rigid,

blocked structure of population genetic alignments. Using normalization layers other than batch

normalization and layer normalization in the generator and discriminator, respectively, severely

reduced performance–likely in part as a result of the Wasserstein loss function used [38].

In addition to variations to the network structure, we also tried modifications to the architecture

that introduced some penalty or evaluation to coerce the GAN to produce output that was more

'alignment-like'. To attempt to ensure our alignments had variation at every site, we added a

penalty term to the loss function weighted by one minus the difference between the minimum

and maximum values at each site multiplied by some fraction of the gradient penalty (as the

gradient penalty and loss magnitude increases during training). However, this penalty was either

too weak to be effective, or when effective, produced alignments with site frequencies that

avoided singletons or nearly fixed derived alleles (Supp. Fig. 1).

Because the added penalty resulted in poor behavior during training, we tried modifications that

were implemented within the GAN itself to achieve variation at every site. Here, we added

tensor operations into the features concatenated before the discriminator's final linear activation,

including the minimum, maximum, mean, and variance at every site. We investigated the effects

of different combinations of these operations, upsampling the operations through a Multi-Layer

Perceptron (MLP), and downsampling the other features through a dense layer. While these

additions did not substantially harm performance, none produced better alignments than the

DCGAN without these extra features.

As the input alignments have values of only 0 and 1, while the generated alignments can

produce any value from 0 to 1 at any individual and site, we considered the possibility that this

difference between discrete and continuous values negatively affected training. One possible fix

for this that is fully differentiable is to have the generator produce log probabilities of belonging

to one of two classes at each individual and site (i.e. ancestral and derived) instead of ending

with a sigmoid activation, and to discretize the class affinity by sampling from the Gumbel-

Softmax distribution [58,59]. While this Gumbel-Softmax variation did not dramatically reduce

performance, we obtained better alignments when using the sigmoid-activated DCGAN,

regardless of whether the former included the now-discretized tensor operations (i.e. the

minimum, maximum, mean, and variance at every site) as input features for the discriminator as

described above.

Performance

In general, our GAN achieved the most drastic increases in similarity between input and

generated alignments early in training (Supp. Fig. 2). For most models, the minimum 2DSWD

was reached early in training (median of 4000 epochs), and continual training generally resulted

in a gradual decrease in similarity, albeit with significant fluctuations, over the rest of training.

However, some models, such as the population contraction and subdivided population with a

migration rate of 0.1, remained relatively stable over training. For both selection models, there is

an overall increase in 2DSWD after early training epochs, but with several later sharp decreases

in 2DSWD that result in values well below the early training minimum. The shuffled migration

model had the most unique training trajectory, exhibiting an overall decrease in 2DSWD over

time, but with much larger fluctuations across epochs, as well as much higher 2DSWD values,

than observed for other models.

We also assessed our models' tendency to over or underfit the training data using adversarial

accuracy measures (Methods; [30]), summarizing each simulated or generated alignment by its

SFS. For most models, AA_{TS} approached intermediate levels between 0.6 and 0.8 early in

training and remained stable (Supp. Fig. 3). No model reached an AA_{TS} below 0.5 at any time

during training, indicating a tendency of our GAN to underfit, rather than overfit, to the models

[30]. Additionally, AA_{truth} values were generally close to 0.5 indicating that our simulated input

alignments were on average roughly as similar to generated alignments as they are to other

input alignments. AA_{syn} values, however, were generally closer to 1.0, indicating most generated

alignments were closer to other generated alignments than the input alignments. In general

terms, this trend indicates that the distribution of generated alignments overlapped the majority

of the distribution of input alignments, but that a substantial fraction of the generated alignments

were outside of the input alignment distribution and/or were clustered within regions of the

distribution that had a comparatively low density of input alignments.

However, a few models show different adversarial accuracy trends than those of the general

trend. For the subdivided population model with a migration rate of 0.1, both shuffled and

unshuffled, all AA values remained tightly linked throughout most of the training run, diverging

slightly after ~4000 epochs. For the two population Out-of-Africa and moderate selection

models, although the AA_{TS} value slowly increased after reaching a minimum close to 0.5, all AA

values became more tightly linked as training went on. Finally, the strong selection model was

unique in that the AA_{syn} scores were substantially lower than AA_{truth} scores throughout the

training run, with the former closer to 0.5 and the latter closer to 1.0, while for most models we

observed the opposite pattern. This pattern would indicate that the GAN was accurate in

capturing a subset of the distribution of sweep alignments with strong selection, but not the

whole distribution, and/or that the simulated alignments are found at relatively high density in

some regions of the distribution where the generated data were at low density. We emphasize

that these adversarial accuracy measures were based on the SFS, and thus it is possible that

somewhat different patterns would emerge from an examination of other summaries of the

alignment data.

GANs can generate data mimicking a variety of population genetic models

Standard neutral model

To understand how our GAN performs in capturing the properties of the most basic models, we

first tested its performance generating alignments simulated under a standard neutral model

(i.e. a single panmictic population with no population size changes or natural selection). Overall

our GAN was able to generate alignments under our most basic neutral model that broadly have

the same properties and summary statistics of the input alignments. To visualize the similarity of

simulated and generated alignments, we performed principal component analysis (PCA) of the

site frequency spectra of these alignments. The first two principal components, shown in Fig.

2a, demonstrate that the generated alignments largely fall within the same distribution as the

input alignments, although the generated alignments are more densely packed within a

subregion of this distribution and thus do not capture the full distribution of input alignments.

Although the bulk of the distribution is captured, GANs can also suffer from mode collapse [see

60], which may be happening here as indicated by the elevated AA_{syn} values (Supp. Fig. 3). The

SFS averaged across 1000 alignments (Fig. 2b), the distribution of positions of polymorphisms

in the alignment (Fig. 2c), and nucleotide diversity distribution (Fig. 2d) are highly similar

between the simulated and generated alignments. To test the GAN's ability to implicitly model

recombination, we added a recombination parameter to our standard neutral simulation. The

amount of LD was lower in both the non-recombinant (Fig. 2e) and recombinant (Fig. 2f) neutral

models' generated alignments relative to the corresponding simulated alignments, likely due to

noise in the generated alignments; the slight excess of singleton polymorphisms in the

generated alignments is consistent with this explanation. Although the magnitude of LD was

somewhat diminished, our GAN clearly produces the expected decay of LD with increasing

distance between polymorphisms when recombination is added to the model.

Subdivided population

To test how well our GAN identifies both physical structure in the alignment and its relationship

to the underlying population structure in a two-population sample, we simulated alignments

under multiple two-population island models with varying levels of migration and trained our

GAN on those alignments. F_{ST} between the two populations was similar between the input and

generated alignments for all four migration rates examined (Fig. 3). As with LD, F_{ST} is somewhat

diminished in generated alignments, a pattern that may be attributable to additional noise in

these alignments. We saw among the smallest 2DSWD with the two-population models as

compared to other models our GAN was trained on, particularly when there was little migration

(2DSWD values of 2.26 and 0.74 for migration rates of 0.1 and 1.0, respectively, with the latter

being the lowest 2DSWD observed in our study; Supp. Fig. 2). This result is likely in part

because these models introduce an especially clear structure into the alignments themselves—

the horizontal subdivision between population one (top of the alignment) and population two

(bottom of the alignment; see Fig. 4). This structure may be somewhat analogous to having

distinct objects or edges in an image—something that convolutional networks were designed to

detect [26]. Indeed, when we shuffled the individuals in the alignment, thereby removing that

structure, our GAN was unable to recover the clear peak in the SFS at at 50% derived allele

frequency in the same manner as it does for the original image (Supp. Fig. 4a,c)—although it

produced an abundance of alleles near 50% frequency, and was able to better mimic the

density of singletons in the alignment. Interestingly, our GAN appears to recover different parts

of the alignment distribution depending on whether individuals are shuffled or not (Supp. Fig.

4b,d). This may be evidence that the GAN struggles to pick up more nuanced properties of the

alignments like low frequency variants when there is a very strong signal, such as a clear

horizontal split in the alignment as expected in a multi-population dataset, but those properties

are captured when that signal is removed. Such a result is not completely unexpected as GANs

can be weak for characterizing the tails of statistical distributions [61].

Two-epoch models of population size change

The demographic history of a population leaves a footprint in patterns of genetic variation, and

accurately detecting this signature and estimating the demographic history of a population is a

common analysis in population genetics [53,62–65]. To see if our GAN can recreate this

signature, we trained our GAN on alignments generated under models of population expansion

and contraction and used Stairway Plot [53] to compare the population size histories of

simulated and GAN-generated alignments. Both population expansion and contraction can be

mimicked by our GAN under modest population size changes (Fig. 5). Population contractions

appear to be more easily captured than expansions, particularly when the magnitude of the

expansion is substantial (Supp. Fig. 5). This may relate to the nature of the input data, where for

histories of population expansion there is an increase in the number of rare polymorphisms

(Supp. Fig. 6). Overall these alignments are more sparse and have less structure for the GAN to

pick up. Additionally, any noise introduced from the GAN would have a disproportionate effect

on such sparse alignments, and potentially reduce the number of rare/singleton polymorphisms.

A two-population model of African and European human demographic history

Modern population genetics is increasingly more interested in identifying signatures of complex

histories [46]. To test our GAN's ability to capture the properties of a more complex model, we

trained our GAN on simulated alignments under a model of the demographic history of African

and European demography [49]. This model consists of an ancient expansion followed by a

population split, two subsequent contractions of the European population, a phase of

exponential expansion of the European population, and then finally rapid exponential growth in

both populations continuing until the present. Interestingly, even though this is our most

complex demographic model, our GAN performs perhaps better on this model than any of the

other models we tested, achieving better LD estimates than neutral models (Fig. 6a) and the

2nd lowest 2DSWD of any other model (1.00 at minimum; Supp. Fig. 2). However, the 2DSWD

minimum is achieved relatively early in training and the distance between generated and input

alignments increases steadily after that point (Supp. Fig. 2). Also remarkably similar is the SFS

of input and generated alignments for this model (Fig. 6b). Because this model includes two

populations, we also investigated the joint Site-Frequency Spectrum (jSFS) produced by our

GAN. Overall, our GAN is able to accurately capture the structure and relationship of the two

populations in this model, with a fairly similar jSFS between the simulated and GAN-generated

alignments (Fig. 6c,d). However, our GAN produces a less sharp boundary delineating alleles

that are found exclusively in one population (left-most column and bottom row) or that are fixed

in the European population (right-most column and top row). Although the number of sites in

each of these categories is roughly similar between generated and input alignments, these strict

delineations appear difficult for our GAN to capture precisely when compared to the more

conspicuous delineations created by the simulations.

Selective sweeps

Because selective sweeps can leave a strong imprint on genetic diversity (i.e. the hitchhiking

effect; [4,5,66], but are challenging to characterize or identify [67,68], we were interested in

testing how well our GAN reproduces the hitchhiking effect under varying strengths of selection.

Overall, our GAN was able to replicate the properties of selective sweeps but underestimated

some signatures under models of strong selection. Both the moderate and strong selective

sweep GANs generated alignments that show reduced nucleotide diversity around the selected

site (Fig. 7) nearly identical to the pattern found in the simulated alignments. We also see a

reduction in the related statistics Tajima's D and Watterson's θ (Supp. Fig. 7, Supp. Fig. 8). Not

surprisingly, Kim and Nielsen's ω, which seeks to detect recent hitchhiking events by taking the

ratio of the amount of LD on either side of a sweep site to the amount of LD between pairs of

polymorphisms on either side of the sweep site, is somewhat lower in GAN-generated than

simulated alignments for strong sweeps (mean generated ω = 155.73, mean input ω = 445.29;

Fig. 7). As the amount of LD produced by our GANs was lower than that produced by the

corresponding simulations for each model that we examined, it is not surprising that the ω

statistic deviates from the simulated distribution as well. However, it is clear that the GAN has

learned the essence of the signature that ω is designed to detect: selective sweeps can produce

LD blocks on either side of the sweep that do not extend across the sweep site (see example

alignments, Fig. 7), and we do note that ω values produced by our GAN are similar for the

moderate selection alignments (mean generated ω = 8.58, mean input ω = 8.00) and much

larger than in the no-selection case (mean generated ω = 3.48, mean input ω = 3.23), especially

for the GAN trained to mimic strong selection.

DISCUSSION

In the present work we have demonstrated the efficacy of using GANs to generate artificial

population genetic alignments. After testing several architectures, we were able to design a

GAN that could accurately capture and replicate the properties of alignments under a variety of

evolutionary models. For many of these properties, such as nucleotide diversity and the position

of sites along the alignment, generated alignments from our GAN were largely indistinguishable

from the input alignments. For others, such as measures of LD, even though the GAN-

generated alignments produced values differing from the simulated distribution, the qualitative

dynamics of these statistics reflected those of the simulated population genetic model (e.g.

decaying LD as a function of the distance between polymorphisms for recombinant models, and

the presence of distinct LD blocks on either side of a selective sweep).

Although our GAN performed well for most models tested, it underperformed in some consistent

ways. Most notably was the addition of noise or less distinct boundaries in generated

alignments as compared to the simulated alignments. This effect predictably resulted in the

reduction of certain metrics that rely on structure between individuals or sites (e.g. LD and Fst),

something also seen in previous genetic GANs [30,31]. As well, although the number of variable

sites was close between simulated and generated alignments, we were unable to ensure

variation at every site using just the GAN architecture, and instead enforced variation by

sampling an individual in proportion to its allele probabilities at otherwise monomorphic sites.

While inaccuracy due to noise is most proximally due to inadequate GAN performance, the

ultimate cause of all of these discrepancies results from comparing an exact and specific

population genetic alignment from simulations to an alignment that is not exact by nature.

Simulators produce alignments that guarantee the presence of variation at every segregating

site, and the models that produce linkage disequilibrium and population structure do not

introduce 'noise' beyond that governed by the user-specified model parameters themselves

(e.g. a migration rate parameter that erodes population structure). Although improvements to

the architecture and the use of more sophisticated GANs may produce generated alignments

that more accurately capture these properties, unless the exact function to produce an

alignment for a given model is identified by the network GAN generated alignments will always

be an inexact approximation as compared to simulated alignments.

As presented here, our GAN provides a proof-of-concept for a population genetic GAN in the

nature of GANs as broadly implemented in the deep learning literature: unlike previously

developed population genetic GANs, ours is fully-differentiable (in terms of the density

distribution of alignments) and generates sequences for the whole population sample at once.

This design implies that, while our GAN can be useful for more traditional uses, such as data

augmentation, it perhaps more importantly provides a basis with which to explore more

advanced applications of GANs to population genetics.

One potential application with which to extend this work that may prove to be particularly useful

to population genetics is style transfer [36], where subproperties of the input are identified by the

network and can then be transferred to other data where that subproperty is absent. In a

population genetic context, the ability to transfer styles from one source to another could be

used to 'transfer' one evolutionary process, such as positive selection, to a population genetic

alignment where selection is not believed to have occurred. In this example, the positive

selection 'style' can be learned from simulated data, while the examples without sweeps can be

learned from empirical data that includes all of the challenges such data may present for

detecting selection (e.g. unknown true demographic history, low data quality, etc). Thus, this

approach presents the possibility of combining the strengths of reductionist generative models

with those of GANs, and could potentially be used to produce more accurate training data for

machine learning-based methods for detecting selective sweeps [17,19,20,69]. Alternatively,

one could take alignments from empirical data and transfer various demographic hypotheses to

those alignments to help generate the reference table for performing approximate Bayesian

computation. Similar to transferring selection 'styles', this example provides the obvious benefit

of not requiring pre-defined population parameters for generating all aspects of the desired

training data. Finally, a particularly intriguing use would involve combining work on creating an

interpretable latent space, where population parameters can be translated into different parts of

a multi-dimensional Gaussian [70], with the ability to project generated examples onto this latent

space [71]. While the latent space interpretation would allow for a simulator that is

instantaneous once trained, the combination with latent space projection would make the

network capable of inferring the demographic parameters of real data and testing evolutionary

hypotheses using the network directly.

Ultimately, this work and its potential expansions further demonstrate the potential of deep-

learning methods for population genetic research. While some may deride deep-learning as

inferior to more traditional statistical methods due to their (current) black box nature, we urge

skeptical readers to momentarily suspend this view and instead explore the ever-expanding

plethora of deep-learning networks and their applications consider how these advances could

help facilitate advances in their own systems and fields. As we have shown here, researchers

do not need to start from scratch and can repurpose existing networks for evolutionary

applications. Unsurprisingly, such repurposing has led to several creative purposes well outside

of the developer's initial intention, such as applying cycleGANs [72] to normalize single cell

RNA-seq data across datasets [73] and using natural language processing models to predict the

effect of nucleotide variants [74]. At a time when unprecedented resources are being used to

develop deep-learning technologies outside of biology, biologists from all fields should consider

the myriad ways in which these technologies can be leveraged to solve problems and answer

longstanding questions.

ACKNOWLEDGEMENTS

We would like to thank Andrew Kern for comments on the manuscript, Nick Matthew for his

work and guidance on GANs prior to the development of this project, as well as other members

of our lab: Logan Whitehouse, Amjad Dabi, Becca Love, and Anton Suvrov for their advice and

assistance. WWB was supported by NIH grant HG010774, and DRS was supported by NIH

grants HG010774 and GM138286.

DATA AVAILABILITY

Scripts and additional example images available at github.com/SchriderLab/PG-Alignments-

GAN

REFERENCES

1. Nei M, Li WH. Mathematical model for studying genetic variation in terms of restriction

endonucleases. Proc Natl Acad Sci USA. 1979;76: 5269–5273.

doi:10.1073/pnas.76.10.5269

2. Nordborg M, Charlesworth B, Charlesworth D. The effect of recombination on background

selection. Genet Res. 1996;67: 159–174. doi:10.1017/s0016672300033619

3. Hudson RR, Kaplan NL. Deleterious background selection with recombination. Genetics.

1995;141: 1605–1617.

4. Smith JM, Haigh J. The hitch-hiking effect of a favourable gene. Genet Res. 1974;23: 23–

35. doi:10.1017/S0016672300014634

5. Kaplan NL, Hudson RR, Langley CH. The "hitchhiking effect" revisited. Genetics.

1989;123: 887–899.

6. Simonsen KL, Churchill GA, Aquadro CF. Properties of statistical tests of neutrality for

DNA polymorphism data. Genetics. 1995;141: 413–429. doi:10.1093/genetics/141.1.413

7. Ferrer-Admetlla A, Liang M, Korneliussen T, Nielsen R. On detecting incomplete soft or

hard selective sweeps using haplotype structure. Mol Biol Evol. 2014;31: 1275–1291.

doi:10.1093/molbev/msu077

8. Voight BF, Kudaravalli S, Wen X, Pritchard JK. A map of recent positive selection in the

human genome. PLoS Biol. 2006;4: e72. doi:10.1371/journal.pbio.0040072

9. Beaumont MA. Approximate Bayesian Computation in Evolution and Ecology. Annu Rev

Ecol Evol Syst. 2010;41: 379–406. doi:10.1146/annurev-ecolsys-102209-144621

10. Schrider DR, Kern AD. Supervised machine learning for population genetics: A new

paradigm. Trends Genet. 2018;34: 301–312. doi:10.1016/j.tig.2017.12.005

11. Burkart N, Huber MF. A survey on the explainability of supervised machine learning. jair.
2021;70: 245–317. doi:10.1613/jair.1.12228

12. Selvaraju RR, Cogswell M, Das A, Vedantam R, Parikh D, Batra D. Grad-CAM: Visual
explanations from deep networks via gradient-based localization. Proceedings of 2017
IEEE International Conference on Computer Vision (ICCV). IEEE; 2017. pp. 618–626.
doi:10.1109/ICCV.2017.74

13. Simonyan K, Vedaldi A, Zisserman A. Deep Inside Convolutional Networks: Visualising
Image Classification Models and Saliency Maps. arXiv. 2013.
doi:10.48550/arxiv.1312.6034

14. Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, et al. Highly accurate
protein structure prediction with AlphaFold. Nature. 2021;596: 583–589.
doi:10.1038/s41586-021-03819-2

15. Flagel L, Brandvain Y, Schrider DR. The unreasonable effectiveness of convolutional
neural networks in population genetic inference. Mol Biol Evol. 2019;36: 220–238.
doi:10.1093/molbev/msy224

16. Gower G, Picazo PI, Fumagalli M, Racimo F. Detecting adaptive introgression in human
evolution using convolutional neural networks. eLife. 2021;10. doi:10.7554/eLife.64669

17. Schrider DR, Kern AD. S/HIC: robust identification of soft and hard sweeps using machine
learning. PLoS Genet. 2016;12: e1005928. doi:10.1371/journal.pgen.1005928

18. Isildak U, Stella A, Fumagalli M. Distinguishing between recent balancing selection and
incomplete sweep using deep neural networks. Mol Ecol Resour. 2021. doi:10.1111/1755-
0998.13379

19. Whitehouse LS, Schrider DR. Timesweeper: accurately identifying selective sweeps using
population genomic time series. BioRxiv. 2022. doi:10.1101/2022.07.06.499052

20.   Kern AD, Schrider DR. diploS/HIC: An Updated Approach to Classifying Selective

Sweeps. G3 (Bethesda). 2018;8: 1959–1970. doi:10.1534/g3.118.200262

21.   Adrion JR, Galloway JG, Kern AD. Predicting the landscape of recombination using deep

learning. Mol Biol Evol. 2020;37: 1790–1808. doi:10.1093/molbev/msaa038

22.   Smith CCR, Tittes S, Ralph PL, Kern AD. Dispersal inference from population genetic

variation using a convolutional neural network. BioRxiv. 2022.

doi:10.1101/2022.08.25.505329

23.   Sanchez T, Cury J, Charpiat G, Jay F. Deep learning for population size history inference:

Design, comparison and combination with approximate Bayesian computation. Mol Ecol

Resour. 2021;21: 2645–2660. doi:10.1111/1755-0998.13224

24.   Battey CJ, Coffing GC, Kern AD. Visualizing population structure with variational

autoencoders. G3 (Bethesda). 2021;11. doi:10.1093/g3journal/jkaa036

25.   Breiman L. Statistical Modeling: The Two Cultures (with comments and a rejoinder by the

author). Stat Sci. 2001;16: 199–231. doi:10.1214/ss/1009213726

26.   Lecun Y, Bottou L, Bengio Y, Haffner P. Gradient-based learning applied to document

recognition. Proc IEEE. 1998;86: 2278–2324. doi:10.1109/5.726791

27.   LeCun Y, Boser B, Denker JS, Henderson D, Howard RE, Hubbard W, et al.

Backpropagation applied to handwritten zip code recognition. Neural Comput. 1989;1:

541–551. doi:10.1162/neco.1989.1.4.541

28.   LeCun Y, Bengio Y, Hinton G. Deep learning. Nature. 2015;521: 436–444.

doi:10.1038/nature14539

29.   Schrider DR, Kern AD. Inferring Selective Constraint from Population Genomic Data

Suggests Recent Regulatory Turnover in the Human Brain. Genome Biol Evol. 2015;7:

3511–3528. doi:10.1093/gbe/evv228

30.   Yelmen B, Decelle A, Ongaro L, Marnetto D, Tallec C, Montinaro F, et al. Creating

artificial human genomes using generative neural networks. PLoS Genet. 2021;17:

e1009303. doi:10.1371/journal.pgen.1009303

31.   Wang Z, Wang J, Kourakos M, Hoang N, Lee HH, Mathieson I, et al. Automatic inference

of demographic parameters using generative adversarial networks. BioRxiv. 2020.

doi:10.1101/2020.08.05.237834

32.   Creswell A, White T, Dumoulin V, Arulkumaran K, Sengupta B, Bharath AA. Generative

adversarial networks: an overview. IEEE Signal Process Mag. 2018;35: 53–65.

doi:10.1109/MSP.2017.2765202

33.   Bousmalis K, Silberman N, Dohan D, Erhan D, Krishnan D. Unsupervised Pixel-Level

Domain Adaptation with Generative Adversarial Networks. 2017 IEEE Conference on

Computer Vision and Pattern Recognition (CVPR). IEEE; 2017. pp. 95–104.

doi:10.1109/CVPR.2017.18

34.   Radford A, Metz L, Chintala S. Unsupervised Representation Learning with Deep

Convolutional Generative Adversarial Networks. arXiv. 2015.

doi:10.48550/arxiv.1511.06434

35.   Kim Y, Ha J-W. Contrastive Fine-grained Class Clustering via Generative Adversarial

Networks. arXiv. 2021. doi:10.48550/arxiv.2112.14971

36.   Karras T, Laine S, Aila T. A Style-Based Generator Architecture for Generative

Adversarial Networks. arXiv. 2018. doi:10.48550/arxiv.1812.04948

37.   Yale A, Dash S, Dutta R, Guyon I, Pavao A, Bennett K. Privacy Preserving Synthetic

Health Data. Bruges, Belgium: hal-02160496; 2019.

38.   Arjovsky M, Chintala S, Bottou L. Wasserstein GAN. arXiv. 2017.

doi:10.48550/arxiv.1701.07875

39.   Goodfellow IJ, Pouget-Abadie J, Mirza M, Xu B, Warde-Farley D, Ozair S, et al.

Generative Adversarial Networks. arXiv. 2014. doi:10.48550/arxiv.1406.2661

40.   Paszke A, Gross S, Massa F, Lerer A, Bradbury J, Chanan G, et al. PyTorch: An

Imperative Style, High-Performance Deep Learning Library. In: Wallach H, Larochelle H,

Beygelzimer A, dAlché-Buc F, Fox E, Garnett R, editors. Advances in Neural Information

Processing Systems 32. Curran Associates, Inc.; 2019. pp. 8024–8035.

41.   Harris CR, Millman KJ, van der Walt SJ, Gommers R, Virtanen P, Cournapeau D, et al.

Array programming with NumPy. Nature. 2020;585: 357–362. doi:10.1038/s41586-020-

2649-2

42.   Gulrajani I, Ahmed F, Arjovsky M, Dumoulin V, Courville AC. Improved training of

wasserstein gans. Advances in neural information processing systems. 2017;30.

43.   Kingma DP, Ba J. Adam: A Method for Stochastic Optimization. arXiv. 2014.

doi:10.48550/arxiv.1412.6980

44.   Hudson RR. Generating samples under a Wright-Fisher neutral model of genetic

variation. Bioinformatics. 2002;18: 337–338. doi:10.1093/bioinformatics/18.2.337

45.   Kern AD, Schrider DR. Discoal: flexible coalescent simulations with selection.

Bioinformatics. 2016;32: 3839–3841. doi:10.1093/bioinformatics/btw556

46.   Adrion JR, Cole CB, Dukler N, Galloway JG, Gladstein AL, Gower G, et al. A community-

maintained standard library of population genetic models. eLife. 2020;9.

doi:10.7554/eLife.54967

47.   Baumdicker F, Bisschop G, Goldstein D, Gower G, Ragsdale AP, Tsambos G, et al.

Efficient ancestry and mutation simulation with msprime 1.0. Genetics. 2022;220.

doi:10.1093/genetics/iyab229

48.   Kelleher J, Etheridge AM, McVean G. Efficient coalescent simulation and genealogical

analysis for large sample sizes. PLoS Comput Biol. 2016;12: e1004842.

doi:10.1371/journal.pcbi.1004842

49.   Tennessen JA, Bigham AW, O'Connor TD, Fu W, Kenny EE, Gravel S, et al. Evolution

and functional impact of rare coding variation from deep sequencing of human exomes.

Science. 2012;337: 64–69. doi:10.1126/science.1219240

50.   Salimans T, Goodfellow I, Zaremba W, Cheung V, Radford A, Chen X. Improved

techniques for training gans. Advances in neural information processing systems.

2016;29.

51.   Bonneel N, Rabin J, Peyré G, Pfister H. Sliced and radon wasserstein barycenters of

measures. J Math Imaging Vis. 2015;51: 22–45. doi:10.1007/s10851-014-0506-3

52.   Miles A, Ralph P, Rae S, Pisupati R. cggh/scikit-allel: v1.3.3. London: Zenodo. 2021.

53.   Liu X, Fu Y-X. Stairway Plot 2: demographic history inference with folded SNP frequency

spectra. Genome Biol. 2020;21: 280. doi:10.1186/s13059-020-02196-9

54.   Watterson GA. On the number of segregating sites in genetical models without

recombination. Theor Popul Biol. 1975;7: 256–276. doi:10.1016/0040-5809(75)90020-9

55.   Tajima F. Statistical method for testing the neutral mutation hypothesis by DNA

polymorphism. Genetics. 1989;123: 585–595. doi:10.1093/genetics/123.3.585

56.   Kim Y, Nielsen R. Linkage disequilibrium as a signature of selective sweeps. Genetics.

2004;167: 1513–1524. doi:10.1534/genetics.103.025387

57.   He K, Zhang X, Ren S, Sun J. Deep Residual Learning for Image Recognition. arXiv.

2015. doi:10.48550/arxiv.1512.03385

58.   Maddison CJ, Mnih A, Teh YW. The Concrete Distribution: A Continuous Relaxation of

Discrete Random Variables. arXiv. 2016. doi:10.48550/arxiv.1611.00712

59.   Jang E, Gu S, Poole B. Categorical Reparameterization with Gumbel-Softmax. arXiv.

2016. doi:10.48550/arxiv.1611.01144

60.   Thanh-Tung H, Tran T. Catastrophic forgetting and mode collapse in GANs. 2020

International Joint Conference on Neural Networks (IJCNN). IEEE; 2020. pp. 1–10.

doi:10.1109/IJCNN48605.2020.9207181

61.   Abbasnejad ME, Shi Q, van den Hengel A, Liu L. A generative adversarial density

estimator. 2019 IEEE/CVF Conference on Computer Vision and Pattern Recognition

(CVPR). IEEE; 2019. pp. 10774–10783. doi:10.1109/CVPR.2019.01104

62.   Li H, Durbin R. Inference of human population history from individual whole-genome

sequences. Nature. 2011;475: 493–496. doi:10.1038/nature10231

63.   Terhorst J, Kamm JA, Song YS. Robust and scalable inference of population history from

hundreds of unphased whole genomes. Nat Genet. 2017;49: 303–309.

doi:10.1038/ng.3748

64.   Schiffels S, Durbin R. Inferring human population size and separation history from multiple

genome sequences. Nat Genet. 2014;46: 919–925. doi:10.1038/ng.3015

65.   Liu X, Fu Y-X. Exploring population size changes using SNP frequency spectra. Nat

Genet. 2015;47: 555–559. doi:10.1038/ng.3254

66.   Fay JC, Wu CI. Hitchhiking under positive Darwinian selection. Genetics. 2000;155:

1405–1413. doi:10.1093/genetics/155.3.1405

67.   Jensen JD, Kim Y, DuMont VB, Aquadro CF, Bustamante CD. Distinguishing between

selective sweeps and demography using DNA polymorphism data. Genetics. 2005;170:

1401–1410. doi:10.1534/genetics.104.038224

68.   Stephan W. Signatures of positive selection: from selective sweeps at individual loci to

subtle allele frequency changes in polygenic adaptation. Mol Ecol. 2016;25: 79–88.

794   doi:10.1111/mec.13288

795 69. Pybus M, Luisi P, Dall'Olio GM, Uzkudun M, Laayouni H, Bertranpetit J, et al. Hierarchical

796   boosting: a machine-learning framework to detect and classify hard selective sweeps in

797   human populations. Bioinformatics. 2015;31: 3946–3952.

798   doi:10.1093/bioinformatics/btv493

799 70. Liu K, Cao G, Zhou F, Liu B, Duan J, Qiu G. Towards disentangling latent space for

800   unsupervised semantic face editing. IEEE Trans on Image Process. 2022;31: 1475–1489.

801   doi:10.1109/TIP.2022.3142527

802 71. Karras T, Aittala M, Laine S, Härkönen E, Hellsten J, Lehtinen J, et al. Alias-Free

803   Generative Adversarial Networks. arXiv. 2021.

804 72. Zhu J-Y, Park T, Isola P, Efros AA. Unpaired Image-to-Image Translation using Cycle-

805   Consistent Adversarial Networks. arXiv. 2017. doi:10.48550/arxiv.1703.10593

806 73. Khan SA, Lehmann R, Martinez-de-Morentin X, Ruiz AM, Lagani V, Kiani NA, et al.

807   scAEGAN: Unification of Single-Cell Genomics Data by Adversarial Learning of Latent

808   Space Correspondences. BioRxiv. 2022. doi:10.1101/2022.04.19.488745

809 74. Benegas G, Batra SS, Song YS. DNA language models are powerful zero-shot predictors

810   of non-coding variant effects. BioRxiv. 2022. doi:10.1101/2022.08.22.504706

812 **Figures**

Figure 1. Architecture and implementation of our Generative Adversarial Network. The final

network chosen is a branched Deep Convolutional Gan (DCGAN) with Wasserstein loss

(WGAN) and a gradient penalty to enforce 1-Lipshitz continuity (DCWGAN+GP). The generator

takes in a random noise vector drawn from a multidimensional Gaussian and is branched into

independent transposed convolutional layers to produce artificial alignments along with a vector

of the positions of segregating sites. The discriminator takes in either generated or real

alignments and positions vectors and evaluates them through a branched network of

convolutions. Loss is calculated using the earth mover's distance between real and generated

alignments with an additional gradient penalty term and is used to train the discriminator which

in turn trains the generator.

Figure 2. GAN performance under a standard neutral model. Input (i.e. simulated) alignments

are shown in purple and generated alignments are shown in green. (a) PCA of the SFS of each

alignment, calculated jointly with 100 input and generated alignments each. (b) Average SFS

across 1000 simulated alignments and 1000 generated alignments. (c) Positions of

polymorphisms along 100 example simulated and generated chromosomes. (d) Density plot

showing the distribution of average per-site nucleotide diversity values across all input and

generated alignments. (e) LD as a function of distance between polymorphisms for the non-

recombinant model. (f) LD as a function of distance between polymorphisms for the

recombinant model.

Figure 3. Fixation index (F_{ST}) as a function of migration rate (shown in units of $4Nm$) in input

(purple) and generated (green) alignments. Each GAN was trained on alignments of two

populations of 32 individuals and one of four bidirectional migration rates. Box and whisker plots

of F_{ST} were generated using 1000 alignments for each migration rate.

Figure 4. Example input (left) and generated (right) alignments for each model analyzed.

Generated alignments were made using the saved network with the minimum 2DSWD. Each

alignment contains 64 individuals with 64 sites. Selective sweep models (bottom two rows)

show a blue line in the center of the alignment identifying the sweep site.

Figure 5. Effective population size (Ne) estimates as a function of time for input (purple) and

generated (green) alignments. All estimates were calculated using Stairway Plot (version 2.1.1)

with 1000 averaged site-frequency spectra and show the median and 95% CI population size

estimate at each point in time. (a) Stairway Plot estimates for 10-fold population-size expansion

input alignments, (b) 10-fold population-size expansion generated alignments, (c) 10-fold

population contraction input alignments, (d) 10-fold population contraction generated

alignments.

Figure 6. GAN results for generating alignments under the two-population out-of-Africa model

from Tennessen et al. (2012). (a) LD decay as a function of distance between polymorphisms

for input (purple) and generated (green) alignments. (b) Average site-frequency spectrum (SFS)

over 1000 input and generated alignments. (c) joint site-frequency spectrum (jSFS) of 1000

input alignments for African (AFR) and European (EUR) individuals. (c) joint site-frequency

spectrum (jSFS) of 1000 generated alignments for AFR and EUR individuals.

Figure 7. Generating selective sweeps using GANs. From top to bottom: metrics and examples

from GANs trained on alignments with no selection, a moderate selective sweep, and a strong

selective sweep, with the selected site occurring at the alignment midpoint. From left to right:

position of each of the 64 sites in the alignment along the chromosome for input (purple) and

generated (green) alignments, Average nucleotide diversity (π) across 1000 alignments in 0.05

position windows along the alignment (error bars represent standard deviations), and density

plots showing the distribution of Kim and Nielsen's ω for 1000 alignments.

874 **Supporting Information**

876 **Supplemental Table 1.** Models used for this study and their commands for simulation.

Standard neutral	ms 64 20000 -s 64
Standard neutral with recombination	ms 64 20000 -s 64 -r 13.6 1000
Subdivided	ms 64 20000 -s 64 -I 2 32 32 0.1 ms 64 20000 -s 64 -I 2 32 32 1.0 ms 64 20000 -s 64 -I 2 32 32 2.0 ms 64 20000 -s 64 -I 2 32 32 5.0
Two-epoch contraction	ms 64 20000 -t 40 -eN 0 0.5 -eG 0.00025 -10 -eN 0.01 5
Two-epoch expansion	ms 64 20000 -t 100 -eN 0 5 -eG 0.00025 10 -eN 0.01 0.5
Two-population Out-of-Africa	species = stdpopsim.get_species("HomSap") model = species.get_demographic_model("OutOfAfrica_2T12") contig = species.get_contig("chr22", length_multiplier=0.001) samples = model.get_samples(32,32) engine = stdpopsim.get_engine("msprime") ts = engine.simulate(model, contig, samples)
Selective sweep (strong)	discoal 64 20000 1000 -t 125 -ws 0 -x 0.5 -r 125 -a 2000
Selective sweep (moderate)	discoal 64 20000 1000 -t 45 -r 45 -ws 0 -x 0.5 -a 100

880 **Supplemental Table 2.** Sorted results from hyper-parameter tuning. The 2D sliced Wasserstein

881 distance (2DSWD) between the distribution of input and generated SFS PCAs was calculated

882 after every 100 epochs for 10,000 epochs and averaged across the last 5 100 epoch iterations.

883 Hypertuning results are for various hyperparameter values used to train a GAN on 10,000

884 alignments generated under a standard neutral simulation.

2DSWD	Critic Iterations	Negative Slope	Batch Size	Learning Rate	Lambda
5.87411	5	0.1	256	0.0002	10
5.93474	5	0.05	128	0.00005	7
5.94295	3	0.2	64	0.0001	7
6.00638	3	0.2	128	0.0002	7
6.04408	3	0.1	256	0.00005	10
6.05793	3	0.2	256	0.00005	7
6.10092	3	0.1	128	0.0002	7
6.10765	3	0.1	128	0.0001	7
6.17229	5	0.05	256	0.0001	10
6.1919	5	0.05	128	0.0002	10
6.19733	5	0.1	64	0.0002	10
6.19958	5	0.1	64	0.00005	10

6.20759	5	0.1	256	0.0001	10
6.229	3	0.1	64	0.00005	13
6.26189	3	0.05	64	0.0001	13
6.262	3	0.1	128	0.0001	13
6.27331	3	0.2	128	0.0001	7
6.27816	3	0.2	256	0.0001	10
6.2905	3	0.1	256	0.0002	10
6.29516	3	0.05	64	0.00005	7
6.30886	3	0.2	64	0.00005	7
6.32172	3	0.05	256	0.0002	7
6.33799	5	0.05	64	0.0002	13
6.34701	3	0.2	256	0.0002	13
6.36392	5	0.05	64	0.0002	10
6.36868	5	0.1	128	0.0001	7
6.37928	3	0.2	256	0.0001	7
6.38694	3	0.1	64	0.0002	13
6.40434	5	0.05	128	0.0002	7

6.40612	5	0.2	64	0.0001	7
6.41192	5	0.05	64	0.00005	13
6.4121	5	0.2	128	0.0001	10
6.41471	3	0.1	256	0.0002	7
6.42442	3	0.1	256	0.0002	13
6.42818	3	0.05	128	0.0002	13
6.45462	3	0.1	64	0.0002	7
6.45554	3	0.2	64	0.0002	13
6.45769	3	0.1	128	0.00005	13
6.46328	5	0.1	64	0.0001	7
6.46528	5	0.1	64	0.0001	10
6.48234	5	0.1	128	0.0002	7
6.48584	5	0.2	128	0.0002	7
6.48753	5	0.2	64	0.00005	10
6.49694	5	0.1	256	0.0002	13
6.50457	5	0.05	256	0.00005	10
6.50636	5	0.2	256	0.00005	7

6.50718	5	0.1	256	0.0001	7
6.51397	3	0.1	128	0.00005	10
6.52245	5	0.05	128	0.00005	13
6.53101	5	0.05	128	0.00005	10
6.55597	3	0.2	128	0.0001	10
6.56345	3	0.2	128	0.0002	13
6.58064	5	0.05	64	0.00005	7
6.58214	5	0.1	128	0.0001	13
6.59873	5	0.05	64	0.0001	10
6.59877	5	0.1	128	0.0002	10
6.60062	3	0.05	64	0.0001	7
6.6028	3	0.2	256	0.0002	7
6.62975	5	0.05	64	0.0002	7
6.64012	3	0.2	128	0.0001	13
6.64276	5	0.2	64	0.0001	13
6.65617	3	0.1	128	0.0002	10
6.66339	5	0.05	256	0.00005	13

6.66821	5	0.1	128	0.00005	10
6.67048	3	0.05	128	0.0002	7
6.69036	5	0.05	256	0.0001	7
6.69057	5	0.05	128	0.0001	13
6.698	3	0.2	64	0.0001	13
6.6985	3	0.2	64	0.00005	13
6.70101	5	0.2	64	0.0002	10
6.70287	3	0.1	128	0.00005	7
6.70348	5	0.05	128	0.0002	13
6.70428	5	0.2	128	0.00005	13
6.7089	3	0.1	256	0.0001	7
6.72157	5	0.05	256	0.0002	7
6.72375	3	0.05	256	0.00005	7
6.72785	5	0.2	64	0.0002	7
6.74168	3	0.05	256	0.0001	10
6.7419	5	0.05	256	0.0002	10
6.74266	3	0.1	64	0.00005	10

6.74598	5	0.2	64	0.00005	13
6.74975	3	0.05	128	0.00005	10
6.76969	5	0.05	64	0.00005	10
6.77618	5	0.1	64	0.00005	7
6.77886	3	0.05	256	0.0001	13
6.78035	5	0.1	128	0.0002	13
6.79024	3	0.05	128	0.00005	7
6.79112	3	0.1	64	0.0001	10
6.79691	3	0.1	64	0.0001	13
6.79903	5	0.2	256	0.00005	10
6.80702	3	0.1	64	0.0002	10
6.80986	3	0.2	64	0.00005	10
6.81372	3	0.1	64	0.0001	7
6.83414	3	0.2	64	0.0002	7
6.83985	5	0.2	256	0.0001	13
6.84113	3	0.2	256	0.0001	13
6.84245	5	0.1	64	0.0002	7

6.85644	3	0.1	256	0.00005	7
6.87124	3	0.2	64	0.0002	10
6.87158	5	0.2	256	0.0001	7
6.87834	5	0.2	64	0.0001	10
6.88091	5	0.2	128	0.00005	10
6.88179	5	0.2	64	0.00005	7
6.89394	5	0.1	256	0.0001	13
6.91445	3	0.05	128	0.0001	13
6.92013	3	0.05	64	0.0002	10
6.92505	5	0.2	256	0.0001	10
6.92947	3	0.05	256	0.0002	10
6.94061	3	0.1	64	0.00005	7
6.94177	3	0.05	128	0.00005	13
6.94303	5	0.1	256	0.0002	7
6.94823	5	0.1	64	0.0001	13
6.96352	3	0.1	128	0.0002	13
6.97825	5	0.2	64	0.0002	13

6.98608	5	0.1	128	0.0001	10
6.99399	3	0.05	64	0.0002	13
6.99967	3	0.05	256	0.00005	10
7.00575	5	0.1	64	0.0002	13
7.01481	5	0.05	256	0.0001	13
7.02492	3	0.2	256	0.00005	10
7.03051	5	0.2	128	0.0001	13
7.03168	3	0.2	256	0.00005	13
7.04809	5	0.2	256	0.0002	13
7.05967	5	0.05	64	0.0001	7
7.06284	3	0.05	256	0.0001	7
7.06631	3	0.2	256	0.0002	10
7.0688	3	0.05	128	0.0002	10
7.09667	3	0.05	64	0.0002	7
7.1083	5	0.05	64	0.0001	13
7.12276	3	0.05	128	0.0001	7
7.12441	5	0.1	256	0.00005	10

7.15015	3	0.2	128	0.0002	10
7.15558	3	0.1	256	0.0001	13
7.15796	5	0.2	128	0.0002	10
7.16688	5	0.05	128	0.0001	10
7.16808	3	0.2	64	0.0001	10
7.18039	3	0.2	128	0.00005	10
7.19611	5	0.2	256	0.00005	13
7.1972	3	0.05	64	0.00005	13
7.2513	3	0.05	256	0.00005	13
7.25356	3	0.05	64	0.0001	10
7.26264	3	0.1	128	0.0001	10
7.27577	5	0.2	128	0.00005	7
7.30135	5	0.1	256	0.00005	13
7.32328	5	0.05	256	0.00005	7
7.33035	5	0.1	64	0.00005	13
7.34931	3	0.1	256	0.0001	10
7.36709	3	0.2	128	0.00005	7

7.3816	5	0.1	256	0.00005	7
7.39383	5	0.05	128	0.0001	7
7.40595	5	0.2	256	0.0002	10
7.44567	5	0.2	256	0.0002	7
7.44807	5	0.2	128	0.0002	13
7.48629	5	0.1	128	0.00005	7
7.53794	3	0.2	128	0.00005	13
7.5714	5	0.2	128	0.0001	7
7.62356	3	0.05	128	0.0001	10
7.63378	3	0.05	256	0.0002	13
7.80113	3	0.1	256	0.00005	13
7.8211	5	0.05	256	0.0002	13
7.85496	5	0.1	128	0.00005	13
8.71081	3	0.05	64	0.00005	10

Supplemental Figure 1. Average site-frequency spectrum from 1000 input (left) and generated

(right) alignments using a custom loss penalty on monomorphic sites.

Supplemental Figure 2. 2D sliced Wasserstein distance (2DSWD) between the PCA values

894   calculated from input and generated site-frequency spectra throughout training. Vertical line

895   represents the 2DSWD minimum value during training used for evaluation.

Supplemental Figure 3. Nearest neighbor adversarial accuracy (AA) scores throughout

training. Vertical line represents the 2DSWD minimum value during training used for evaluation.

Supplemental Figure 4. GAN performance on unshuffled (a,b) and shuffled (c,d) structured

population alignments with a 0.1 migration rate. (a) Average SFS of 1,000 input (purple) and

GAN generated (green) alignments of an unshuffled structured population. (b) PCA of the SFS

of 200 input (purple) and GAN generated (green) alignments of an unshuffled structured

population. (c) Average SFS of 1,000 input (purple) and GAN generated (green) alignments of a

shuffled structured population. (d) PCA of the SFS of 200 input (purple) and GAN generated

(green) alignments of a shuffled structured population.

Supplemental Figure 5. Effective population size (Ne) estimates for a population experiencing

a 50-fold increase as a function of time for input (purple) and generated (green) alignments. All

estimates were calculated using Stairwayplot (version 2.1.1) and show the median and 95% CI

population size estimate. Ne is multiplied by 1e6.

Supplemental Figure 6. Input and generated site frequency spectra (SFS) averaged across

1000 samples for generated (green) and input (purple) alignments under a (a) 10-fold

population expansion and a (b) 10-fold population contraction.

Supplemental Figure 7. Windowed diversity statistics for input (purple) and generated (green)

alignments under a model of moderate selection. Error bars represent standard deviation.

Nucleotide diversity (pi), Watterson's theta, Tajima's D are calculated in non-overlapping

windows of 5% of the chromosome length. Kim and Nielsen's omega is calculated in

overlapping windows 30% of the chromosome length and sliding 10% of the chromosome for

each window.

Supplemental Figure 8. Windowed diversity statistics for input (purple) and generated (green) alignments under a model of strong selection. Error bars represent standard deviation. Nucleotide diversity (pi), Watterson's theta, Tajima's D are calculated in non-overlapping windows of 5% of the chromosome length. Kim and Nielsen's omega is calculated in overlapping windows 30% of the chromosome length and sliding 10% of the chromosome for each window.