This population does not exist: learning the distribution of evolutionary histories with
generative adversarial networks

William W. Booker[1*], Dylan D. Ray[1], Daniel R. Schrider[1*]

[1]Department of Genetics, University of North Carolina at Chapel Hill, Chapel Hill, North
Carolina, 27514-2916, United States of America

* Corresponding author

E-mail: wbooker14@gmail.com, drs@unc.edu

Keywords: deep learning, machine learning, population genetics, evolution, generative
adversarial network, neural network

10 ABSTRACT

Numerous studies over the last decade have demonstrated the utility of machine learning
methods when applied to population genetic tasks. More recent studies show the potential of
deep learning methods in particular, which allow researchers to approach problems without
making prior assumptions about how the data should be summarized or manipulated, instead
learning their own internal representation of the data in an attempt to maximize inferential
accuracy. One type of deep neural network, called Generative Adversarial Networks (GANs),
can even be used to generate new data, and this approach has been used to create individual
artificial human genomes free from privacy concerns. In this study, we further explore the
application of GANs in population genetics by designing and training a network to learn the
statistical distribution of population genetic alignments (i.e. data sets consisting of sequences
from an entire population sample) under several diverse evolutionary histories—the first GAN
capable of performing this task. After testing multiple different neural network architectures, we
report the results of a fully differentiable Deep-Convolutional Wasserstein GAN with gradient
penalty that is capable of generating artificial examples of population genetic alignments that
successfully mimic key aspects of the training data, including the site frequency spectrum,
differentiation between populations, and patterns of linkage disequilibrium. We demonstrate
consistent training success across various evolutionary models, including models of panmictic
and subdivided populations, populations at equilibrium and experiencing changes in size, and
populations experiencing either no selection or positive selection of various strengths, all without
the need for extensive hyperparameter tuning. Overall, our findings highlight the ability of GANs
to learn and mimic population genetic data and suggest future areas where this work can be
applied in population genetics research that we discuss herein.

33 INTRODUCTION

Accurately capturing the properties of genetic variation to infer evolutionary processes is a
major goal of population genetics. Throughout the history of population genetic research, myriad
summary statistics have been created to accomplish this task. Ideally, the values of a given
statistic follow theoretical predictions and are robust to additional unconsidered forces. For
example, π (Nei and Li 1979), which measures the degree of nucleotide diversity in a
population, is reduced by linked directional selection in a manner that is predicted by the
selection coefficient and the recombination landscape around the selected site(s) (Smith and
Haigh 1974; Kaplan *et al.* 1989; Hudson and Kaplan 1995; Nordborg *et al.* 1996). However,
diversity levels are also affected by other processes such as population bottlenecks and
population subdivision (Simonsen *et al.* 1995). Although the simplicity of this univariate
summary of genetic diversity makes it well-suited for theoretical studies of the effects of various
evolutionary processes on diversity, this also renders π relatively uninformative for
distinguishing among the diversity of complex evolutionary scenarios considered in modern
population genetic inference.

As a solution to this problem, researchers have turned to either creating more complex statistics
(Voight *et al.* 2006; e.g. Ferrer-Admetlla *et al.* 2014) or using methods that rely on a number of
theoretically informative summary statistics to infer a process or evolutionary history (Beaumont

2010; Schrider and Kern 2018). Common to the latter approaches is the leveraging of
increasingly greater amounts of information or observations to make evolutionary inferences,
and this increased inferential power typically comes at the cost of reduced interpretability. As
the number of summary statistics used increases, it becomes less apparent how any one
statistic, and especially any combination of statistics, is informative about the process in
question. Ultimately, the tools we use to make meaningful inference currently lie on a continuum
between interpretability and power, and researchers must make a choice within this continuum
for the question at hand.

If simple statistics lie on one end of the interpretability-power continuum, deep-learning methods
lie on its opposite. Often described as a 'black box', deep-learning models frequently have
millions of parameters that make identifying the features responsible for a given inference a
challenging task (although research is being conducted on this task, see: Simonyan et al. 2013;
Selvaraju et al. 2017; Burkart and Huber 2021). However, these methods can be remarkably
powerful and in some cases have made dramatic progress in the biological domain (e.g. Jumper
et al. 2021). In population genetics, deep-learning methods have been used for a number of
purposes, such as detecting introgression (Flagel *et al.* 2019)—including adaptive introgression
(Gower *et al.* 2021); distinguishing among various modes of natural selection as well as neutral
evolution (Schrider and Kern 2016; Kern and Schrider 2018; Isildak *et al.* 2021; Whitehouse and
Schrider 2022); estimating parameters such as selection coefficients and recombination rates
(Flagel *et al.* 2019; Adrion *et al.* 2020a), dispersal distances (Smith *et al.* 2022), and population
sizes (Sanchez *et al.* 2021); and visualizing population structure (Battey *et al.* 2021).

Although deep-learning networks are often thought of as an uninterpretable 'black box', one
argument suggests that such algorithmically generated models may in fact be well suited to
model natural phenomena that are generated by complex processes that are inherently
uninterpretable through the lens of simple statistical models (Breiman 2001). Rather than
reducing our data down to some predetermined set of variables, many of these networks—such
as those that use convolutional neural networks (LeCun et al. 1989; LeCun et al. 1998)—are
able to learn their own data representations from the raw data itself. Because they do not rely
on *a priori* assumptions of how to summarize our data, these methods can potentially learn to
extract the information needed to make accurate inferences without requiring our data be
manipulated in ways that may be biased or otherwise omit useful information. While much of the
natural world can be understood using mechanistic models with clear causes and effects,
restricting ourselves to this frame of understanding renders biological science myopic—
precluding our ability to discover more complex phenomena with emergent properties otherwise
unaccounted for. In evolutionary biology, and in particular population genetics, progress has
traditionally relied on this mechanistic framework through the development of theoretical models
that are then used to explain our observations (Schrider and Kern 2018). Deep-learning
methods, however, allow us to take the opposite approach: letting observation directly inform
our understanding (LeCun *et al.* 2015).

One limitation of this approach is that for most evolutionary processes we have few example
phenomena where the true evolutionary history with respect to the phenomenon of interest is
known with complete certainty. For example, although there are many loci where we strongly

suspect there has been recent positive selection, even for the best studied examples we often
cannot be certain of the identity of the selected site, or even gene, let alone of parameters such
as the strength of selection. Thus, typically in machine learning applications to population
genetic problems, the training observations themselves must be generated from simulations
based on reductionist models (but see Schrider and Kern 2015). However, if we leverage the
usefully reductive aspects of biology (e.g. predictable changes in allele frequencies in response
to selection) alongside the advantages of deep-learning methods to factor in the unreducible
parts (i.e. the messy nature of biological data and its collection), it may be possible to render
this limitation advantageous.

In this study, we focus on Generative Adversarial Networks (GANs), a specific class of deep-
learning network that may be particularly useful in population genetics. Variations of GANs have
been previously used to generate artificial human genomes (Yelmen *et al.* 2021) and estimate
demographic parameters of populations (Wang *et al.* 2020). While the explicit function of these
networks is to generate artificial examples of some set of input data, training these networks
aims to learn the statistical distribution of the input data in a multidimensional parameter space
(Creswell *et al.* 2018). As a result, GANs can be useful for any task where identifying this
distribution is advantageous and can be exploited, such as data augmentation (Bousmalis *et al.*
2017), classification (Radford *et al.* 2015), clustering (Kim and Ha 2021), or the transfer of
properties from one dataset onto another (i.e. style transfer; Karras *et al.* 2018).
Importantly, by learning this distribution, any artificial examples generated by the GAN are not
tied to any one input example. This property makes GANs particularly useful for generating
testing data containing sensitive information or where privacy is a concern, such as data
collected from human subjects (Yale *et al.* 2019; Yelmen *et al.* 2021).

Here, we complement previous work using generative models in population genetics by
designing the first fully differentiable GAN capable of generating artificial population genetic
alignments. Previous work has shown that GANs can learn to generate individual genomes from
a shared ancestry (Yelmen *et al.* 2021), analogous to drawing multiple individuals from a single
ancestral recombination graph (ARG). Here, we demonstrate that GANs can simultaneously
generate entire samples of genomes from the full distribution of samples that may be produced
under a given evolutionary model, analogous to drawing an entire ARG from the distribution of
ARGs produced by an evolutionary process. While qualitatively different in the data learned and
generated, the architectural differences in our GAN may also allow us to capture additional
information about the joint history of individuals in each sample. We begin with a design based
on the Wasserstein GAN (Arjovsky *et al.* 2017) and test several different architectures to find
the optimal design for this task. We then simulate alignments under a variety of evolutionary
scenarios, including models of population size change, subdivision, and natural selection, and
evaluate our GAN's ability to accurately capture and replicate alignment properties under each
of these scenarios. Finally, we discuss the strengths and weaknesses of our GAN, and propose
paths forward for using GANs for population genetic modeling and inference.

METHODS

GAN Overview

Generative Adversarial Networks (GANs) are in actuality a combination of two different
networks that compete against each other during training. As initially designed, these two
networks consist of a generator that produces some output from a latent noise vector as input,
and a discriminator that takes in both real and generated data and attempts to distinguish
between the two (Goodfellow *et al.* 2014). By training these two networks in tandem, the
generator should get progressively better at producing realistic copies while the discriminator
gets better at distinguishing those fake copies from real ones. Critically, the generator is blind to
the data it is trying to replicate, and only receives updates from the discriminator on its
performance.

Architecture and Implementation

All networks were created using python version 3.9.7 along with pytorch version 1.9.1 (Paszke
et al. 2019) and numpy version 1.20.3 (Harris *et al.* 2020). To design our GAN, we tested
several network architectures with different combinations of layers and properties to find an
architecture that performed consistently across runs and population genetic models. Largely,
the networks tested were variations of a Deep Convolutional GAN (Radford *et al.* 2015) or a
ResNet GAN (as implemented in Gulrajani *et al.* 2017), with the ResNet GAN being largely a
modification of the DCGAN architecture where the input to each convolutional layer block is
added to its output. These networks were initially designed to reproduce two-dimensional
images with color values on 3 channels, and this data structure is easily translatable to
population genetic alignments with biallelic polymorphisms by reducing the network to a single
color channel, analogous to a black and white image, with values that represent ancestral (0) or
derived (1) alleles. However, while this structure captures allelic information at each site it
leaves out valuable information about the position of those sites along a sequence. To include
this information, in both the generator and discriminator networks we included two branches,
one performing two-dimensional convolutions on the alignment matrix, and the other performing
one-dimensional convolutions on the vector of positions for each polymorphism in the alignment
(Fig. 1).

One difficulty with GANs as initially designed is the "vanishing gradient" problem, where the
discriminator learns too quickly and the generator is unable to keep up. To prevent this from
occurring, we used the Earth Mover's (EM) distance as our loss function as implemented in the
Wasserstein GAN (WGAN; Arjovsky *et al.* 2017). Rather than treating the discriminator and
generator as adversaries in a min-max game using the discrete prediction of real (1) or fake (0)
as in the original GAN (Goodfellow et al. 2014), the WGAN attempts to minimize the 'effort'
required to transform the distribution of values output by the discriminator (or critic, in
Wasserstein GANs) from generated examples into the distribution of values output by real
examples. However, by using the EM distance as a loss function the network is no longer 1-
Lipschitz continuous and requires either weight clipping or other modifications to enforce the
Lipschitz constraint. To enforce this constraint, we added a gradient penalty (Gulrajani *et al.*
2017) to the loss calculation:

Eq. 1

$$L = \mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_g} [D(\tilde{\boldsymbol{x}})] - \mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_r} [D(\boldsymbol{x})] + \lambda \mathop{\mathbb{E}}_{\hat{\boldsymbol{x}} \sim \mathbb{P}_{\hat{\boldsymbol{x}}}} \left[(\|\nabla_{\hat{\boldsymbol{x}}} D(\hat{\boldsymbol{x}})\|_2 - 1)^2 \right]$$

Here, the first two elements of the equation $\mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_g} [D(\tilde{\boldsymbol{x}})] - \mathop{\mathbb{E}}_{\boldsymbol{x} \sim \mathbb{P}_r} [D(\boldsymbol{x})]$ calculate the EM distance
between the discriminator's predictions on generated (the first term) and real data (the second
term), with the second half $\lambda \mathop{\mathbb{E}}_{\hat{\boldsymbol{x}} \sim \mathbb{P}_{\hat{\boldsymbol{x}}}} \left[(\|\nabla_{\hat{\boldsymbol{x}}} D(\hat{\boldsymbol{x}})\|_2 - 1)^2 \right]$ calculating a penalty on the gradient norm of
the discriminator for examples randomly sampled in between real and generated data ($\hat{\boldsymbol{x}} \sim \mathbb{P}_{\hat{\boldsymbol{x}}}$),
with deviations of this norm from 1 being penalized according to the penalty hyperparameter λ.
By designing our GAN this way, training should converge more easily and be more stable
across runs and hyperparameter values. Finally, we used the 'Adam' optimizer for training
(Kingma and Ba 2014).

Within the overall architectures outlined above, we also tested a number of more subtle
variations of the network architecture to arrive at a more optimal solution. These included
various normalization layers following convolutions (batch, instance, layer), activation functions
following internal convolutions (ReLU and leaky ReLU), adding Gaussian noise between layers
in the discriminator, upsampling and transposed convolutions in the generator, and final
activation layers in the generator (sigmoid, tanh, Gumbel softmax). Regarding the final
activation, the sigmoid activation [0,1] value was interpreted as the probability of having a
derived allele for a given individual at each site, with the tanh activation [-1,1] being a similar
probability when re-scaled to [0,1]. The Gumbel softmax activation was tested in an attempt to
discretize the generated alignments fed into the discriminator with the value for a given
individual at each site representing an allele belonging to either the ancestral (0) or derived (1)
class.

In addition to these variations, we also attempted to add in additional information in the models
related to the variation and frequency of alleles. A fundamental difference between simulated
alignments and alignments generated by a GAN is that output from simulated alignments are
guaranteed to have variation at every site, whereas the GAN has no such guarantee and
variation at every site must be learned or achieved by some other means after generating the
data if generating alignments with the same number of sites as the input is desired. Although
alignments don't need to have the same number of sites for comparison, early tests suggested
not requiring variation led to a reduction in singleton sites almost exclusively (Supp. Fig. 1).

To assist training in ensuring variation at every site, we tested networks that had an additional
loss term penalizing monomorphic sites added to the generator loss (Eq. 2, where i is the
number of sites and ω is some weight either fixed or tied to the gradient penalty loss) and
additional features passed as input into the discriminator including the sum, minimum,
maximum, and variance of values at each site. To ensure variation at every site in generated
alignments, a random individual at sites initially monomorphic for the ancestral allele was
chosen to have the derived allele, with this choice weighted by each individual's probabilities
from the final activation layer. The same was done for sites monomorphic for the derived allele,
except in these cases the weight used to randomly select an individual to be given the ancestral
allele was one minus the probability from the final activation later.

Eq. 2

214
$$\sum_{i=1}^{l} (1 - (max_i - min_i)) * \omega$$

Simulations and Models

We tested the ability of our GAN to broadly capture the properties of population genetic
alignments by training the GAN using several different simulated models as input. All models
were simulated using coalescent simulators: ms (Hudson 2002), discoal (Kern and Schrider
2016), or stdpopsim version 0.1.2 (Adrion *et al.* 2020b) with msprime version 1.0.2 (Kelleher *et*
al. 2016; Baumdicker *et al.* 2022) as the backend of stdpopsim. The most basic of models
assessed were a standard neutral model both with and without recombination. Together, these
models allow us to evaluate the GAN's ability in the simplest of cases as well as its ability to
capture information about the covariance of nearby sites when recombination is present. We
also evaluated a model of isolation with migration of two equally sized populations,
experimenting with several rates of migration. To evaluate the GAN's ability to learn to model
population structure from structure in the alignment, we trained the GAN where the input was
the direct output from the simulation (where the population 1 is the first 32 rows of the
alignment, and population 2 the remaining 32 rows) and where the input rows (individuals) were
shuffled. Additionally, we evaluated models where there was a recent population expansion or
contraction. To assess performance on a more complex demographic model, we trained the
GAN using simulations from the two- population 'Out of Africa' model from Tennessen et al.
(2012).Finally, we assessed the ability of the GAN to replicate patterns of recent positive
selection by simulating models of strong and moderate selective sweeps (2*Ns*=2000 and
2*Ns*=100, respectively) where the selected site was in the middle of the alignment and the
sweep had completed upon sampling. The standard neutral and IM models were simulated with
a set number of segregating sites using the ms '-s' flag. All other models were simulated with a
variable number of sites, and 64 sites were extracted for training by taking the 64 sites
surrounding the most central position in the alignment. Note that because of this, the locus-wide
recombination rate parameter used for these simulations is greater than or equal to that of the
window of the alignment fed as input into the GAN. This also ensured that, for the simulations of
selection, the selected site was always in the center of the alignment and could be properly
captured by windowed diversity metrics. All simulation commands are available in the
supplement (Supp. Table 1).

Evaluation

We used a number of measures relevant to population genetics to evaluate the performance
and training of our GAN. Because of the nature of adversarial training, the loss of GANs does
not directly correlate to the ability of the GAN to generate realistic copies. Typically, these GANs
are evaluated by some metric calculated using a pretrained network to determine the similarity
of GAN output to the input data, such as inception scores (Salimans *et al.* 2016), however the
inception network was designed and trained for use with 3-channel color images rather than the

binary alignments used here. To evaluate our single channel output, we evaluated our GAN
using the 2D sliced Wasserstein distance of the distribution characterized by the first two
principal components calculated from the site-frequency spectra (SFS) of the input and
generated alignments (referred hereafter as 2DSWD). This measurement is an approximation of
the exact Wasserstein (or earth mover's) distance calculated through linear slicing of the two
distributions (Bonneel *et al.* 2015).

Similar to Yelmen et al. (2021), we used nearest-neighbor adversarial accuracy (here calculated
using the SFS of each alignment) to evaluate over and underfitting (see Yale *et al.* 2019). We
used Eq. 3-5 (reproduced from Yelmen et al. (2021)) to calculate 3 adversarial accuracy scores:
AA_{truth}, AA_{syn}, and AA_{TS}. Here, m is the number of alignments (real alignments for Eq. 3, and
generated alignments for Eq. 4), the function 1 returns 1 if its input value is true and 0
otherwise, $d_{TS}(i)$ is the distance between the ith real alignment its nearest generated alignment,
$d_{ST}(i)$ is the distance between the ith generated alignment and its nearest real alignment, $d_{TT}(i)$
is the distance between the ith real alignment indexed and its nearest neighboring real
alignment, and $d_{SS}(i)$ is the distance between the ith generated alignment and its nearest
neighboring generated alignment. The optimal value for all AA values is 0.5, with an AA_{TS} above
and below 0.5 suggesting the generator is underfitting or overfitting, respectively.

Eq. 3

269
$$AA_{truth} = 1/m * \sum_{i=1}^{m} 1(d_{TS}(i) > d_{TT}(i))$$

270   Eq. 4

271
$$AA_{syn} = 1/m * \sum_{i=1}^{m} 1(d_{ST}(i) > d_{SS}(i))$$

272   Eq. 5

273
$$AA_{TS} = 1/2 * (AA_{truth} + AA_{syn})$$

To broadly capture the similarity of the input and generated alignments, we calculated and
compared the average SFS, and joint SFS for two-population models using scikit-allel (Miles *et*
al. 2021). To assess the GAN's ability to mimic recombination, we calculated the decay of
gametic linkage disequilibrium (as measured by r^2) with distance. To investigate population size
histories consistent with the observed SFS, we used the program Stairway Plot version 2.1.1
(Liu and Fu 2020). Finally, we also calculated the summary statistics Watterson's θ (Watterson
1975), Tajima's D (Tajima 1989), π (Nei and Li 1979), and ω (Kim and Nielsen 2004). For each
model evaluated, we used a training set of 20,000 input alignments and trained for 10,000
epochs. Because GANs may become unstable as training goes on, we saved the network after
every 100 epochs and evaluated the performance of the saved model that minimized the
2DSWD as calculated above.

RESULTS

Architecture

Final architecture

We experimented with several GAN architectures for generating population genetic alignments
(Methods). Of the architectures tested, our final design was a modification of the DCGAN with
Wasserstein loss and gradient penalty to enforce 1-Lipschitz continuity (Fig. 1). The final design
takes in a noise vector of samples from a 128-dimensional standard normal distribution as input.
This input is then branched into two series of convolutions to produce the alignment and
positions vector, respectively. In the generator, the initial transformation from the latent vector in
the alignment branch involves a 2D transposed convolution from the 128-channel noise vector
to 512 channels with a kernel size of 4, a stride of 1, and no padding, followed by a batch
normalization layer and leaky ReLU activation with a negative slope of 0.1. Following the initial
transformation are 3 additional transposed convolutional layers with batch normalization and
leaky ReLU, and each of these layers reduces the number of channels by half with a kernel size
of 4, stride of 2, and padding of 1. The final transposed convolution has the same kernel, stride,
and padding as previous layers and produces a 64x64 alignment on a single channel, has no
batch normalization layer, and is followed by a sigmoid activation layer producing values from 0
to 1 which we interpret as the probability of having a derived allele for each individual at each
site. For the positions branch, the same 128-channel noise vector used in the alignment branch
is passed through an initial 1D transposed convolution that reduces the number of channels by
half with a kernel size of 4, stride of 1, and no padding, followed by a batch normalization layer
and a leaky ReLU activation with negative slope 0.1. This initial transformation is followed by 3
additional 1D transposed convolutional layers that each reduce the number of channels in half
and are each followed by batch normalization and leaky ReLU activation, and that have a kernel
size of 4, stride of 2, and padding of 1. The final 1D convolution produces a 1x64 vector on a
single channel with a single convolution and is followed by a sigmoid activation layer to produce
values from 0 to 1, with the boundaries of this range indicating the beginning and end of the
chromosome, respectively.

The discriminator largely mirrors the generator in the reverse. In the alignment branch, the
64x64x1 alignment is initially transformed into 64 channels via a 2D convolution with a kernel
size of 4, stride of 2, and padding of 1, followed by a layer normalization layer and a leaky ReLU
activation with negative slope 0.1. This is followed by 3 additional 2D convolutions with the
same layer normalization and leaky ReLU activation, but instead the number of channels
doubles after each of these convolution layers. The positions branch is initially transformed
through a 1D convolution into 16 channels with a kernel size of 4, stride of 1, and no padding,
followed by layer normalization and leaky ReLU activation with negative slope 0.1. This initial
transformation is then followed by 3 additional 1D convolutions with the same layer
normalization and leaky ReLU activation, but with the number of output channels doubling after
every convolution. After all convolutions, the alignment and positions branches are both

flattened down to a single dimension, concatenated, and passed through a dense layer with a
linear activation to produce a single output.
329
Hyperparameter tuning produced some variation in the performance of our GAN, but largely the
GAN demonstrated stability over a wide variety of hyperparameter values (Supp. Table 2).
Additionally, there was no clear value for any hyperparameter that consistently performed better
than others across multiple hyperparameter combinations. Ultimately, we chose the
hyperparameter values that minimized the average of the last 5 saved 2DSWDs. This distance
was calculated and saved after every 100 epochs, training for 5000 epochs total with 10,000
alignments as input. The final hyperparameter values were: batch size = 256, lambda = 10, critic
iterations = 5, negative slope = 0.1, and learning rate = 0.0002.
338
339   *Additional architectures*
340
Aside from our final GAN design, we tested several modifications of the final architecture or
alternatives that we found performed more poorly. Most surprisingly, ResNet architectures (He
et al. 2015; Arjovsky *et al.* 2017), which show improved performance over DCGANs in
generating color images, performed worse than DCGANs for our purposes. Rarely did ResNet
architectures produce something resembling an alignment, and when it did, these alignments
were poor representations of the input alignments. Similarly, other proposed additions or
variations to improve performance including upsampling in the generator, adding Gaussian
noise between discriminator layers, smoothing allele values (subtracting or adding a small noise
value drawn from $U(0,0.05)$ to all values in the alignment), and flipping (switching 1-5% of
generated and input example labels going into the discriminator) also reduced performance.
Upsampling in particular produced output that had large, smooth blocks of similar values instead
of the rigid, blocked structure of population genetic alignments. Using normalization layers other
than batch normalization and layer normalization in the generator and discriminator,
respectively, severely reduced performance–likely in part as a result of the Wasserstein loss
function used (Arjovsky *et al.* 2017).
356
In addition to variations to the network structure, we also tried modifications to the architecture
that introduced some penalty or evaluation to coerce the GAN to produce output that was more
'alignment-like'. To attempt to ensure our alignments had variation at every site, we added a
penalty term to the loss function weighted by one minus the difference between the minimum
and maximum values at each site multiplied by some fraction of the gradient penalty (as the
gradient penalty and loss magnitude increases during training). However, this penalty was either
too weak to be effective, or when effective, produced alignments with site frequencies that
avoided singletons or nearly fixed derived alleles (Supp. Fig. 2).
365
Because the added penalty resulted in poor behavior during training, we tried modifications that
were implemented within the GAN itself to achieve variation at every site. Here, we added
tensor operations into the features concatenated before the discriminator's final linear activation,
including the minimum, maximum, mean, and variance at every site. We investigated the effects
of different combinations of these operations, upsampling the operations through a Multi-Layer

Perceptron (MLP), and downsampling the other features through a dense layer. While these
additions did not substantially harm performance, none produced better alignments than the
DCGAN without these extra features.

As the input alignments have values of only 0 and 1, while the generated alignments can
produce any value from 0 to 1 at any individual and site, we considered the possibility that this
difference between discrete and continuous values negatively affected training. One possible fix
for this that is fully differentiable is to have the generator produce log probabilities of belonging
to one of two classes at each individual and site (i.e. ancestral and derived) instead of ending
with a sigmoid activation, and to discretize the class affinity by sampling from the Gumbel-
Softmax distribution (Jang *et al.* 2016; Maddison *et al.* 2016). While this Gumbel-Softmax
variation did not dramatically reduce performance, we obtained better alignments when using
the sigmoid-activated DCGAN, regardless of whether the former included the now-discretized
tensor operations (i.e. the minimum, maximum, mean, and variance at every site) as input
features for the discriminator as described above.

Performance

In general, our GAN achieved the most drastic increases in similarity between input and
generated alignments early in training (Supp. Fig. 3). For most models, the minimum 2DSWD
was reached early in training (median of 4000 epochs), and continual training generally resulted
in a gradual decrease in similarity, albeit with significant fluctuations, over the rest of training.
However, some models, such as the population contraction and subdivided population with a
migration rate of 0.1, remained relatively stable over training. For both selection models, there is
an overall increase in 2DSWD after early training epochs, but with several later sharp decreases
in 2DSWD that result in values well below the early training minimum. The shuffled migration
model had the most unique training trajectory, exhibiting an overall decrease in 2DSWD over
time, but with much larger fluctuations across epochs, as well as much higher 2DSWD values,
than observed for other models.

We also assessed our models' tendency to over or underfit the training data using adversarial
accuracy measures (Methods; Yelmen et al. (2021)), summarizing each simulated or generated
alignment by its SFS. For most models, AA_{TS} approached intermediate levels between 0.6 and
0.8 early in training and remained stable (Supp. Fig. 3). No model reached an AA_{TS} below 0.5 at
any time during training, indicating a tendency of our GAN to underfit, rather than overfit, to the
models (2021). Additionally, AA_{truth} values were generally close to 0.5 indicating that our
simulated input alignments were on average roughly as similar to generated alignments as they
are to other input alignments. AA_{syn} values, however, were generally closer to 1.0, indicating
most generated alignments were closer to other generated alignments than the input
alignments. In general terms, this trend indicates that the distribution of generated alignments
overlapped the majority of the distribution of input alignments, but that a substantial fraction of
the generated alignments were outside of the input alignment distribution and/or were clustered
within regions of the distribution that had a comparatively low density of input alignments.

However, a few models show different adversarial accuracy trends than those of the general
trend. For the subdivided population model with a migration rate of 0.1, both shuffled and
unshuffled, all AA values remained tightly linked throughout most of the training run, diverging
slightly after ~4000 epochs. For the two population Out-of-Africa and moderate selection
models, although the AA_{TS} value slowly increased after reaching a minimum close to 0.5, all AA
values became more tightly linked as training went on. Finally, the strong selection model was
unique in that the AA_{syn} scores were substantially lower than AA_{truth} scores throughout the
training run, with the former closer to 0.5 and the latter closer to 1.0, while for most models we
observed the opposite pattern. This pattern would indicate that the GAN was accurate in
capturing a subset of the distribution of sweep alignments with strong selection, but not the
whole distribution, and/or that the simulated alignments are found at relatively high density in
some regions of the distribution where the generated data were at low density. We emphasize
that these adversarial accuracy measures were based on the SFS, and thus it is possible that
somewhat different patterns would emerge from an examination of other summaries of the
alignment data.
430
431 ***GANs can generate data mimicking a variety of population genetic models***
432
433 *Standard neutral model*
434
To understand how our GAN performs in capturing the properties of the most basic models, we
first tested its performance generating alignments simulated under a standard neutral model
(i.e. a single panmictic population with no population size changes or natural selection). Overall
our GAN was able to generate alignments under our most basic neutral model that broadly have
the same properties and summary statistics of the input alignments. To visualize the similarity of
simulated and generated alignments, we performed principal component analysis (PCA) of the
site frequency spectra of these alignments. The first two principal components, shown in Fig.
2a, demonstrate that the generated alignments largely fall within the same distribution as the
input alignments, although the generated alignments are more densely packed within a
subregion of this distribution and thus do not capture the full distribution of input alignments.
Although the bulk of the distribution is captured, GANs can also suffer from mode collapse (see
Thanh-Tung and Tran 2020), which may be happening here as indicated by the elevated AA_{syn}
values (Supp. Fig. 4). The SFS averaged across 1000 alignments (Fig. 2b), the distribution of
positions of polymorphisms in the alignment (Fig. 2c), and nucleotide diversity distribution (Fig.
2d) are highly similar between the simulated and generated alignments. To test the GAN's
ability to implicitly model recombination, we added a recombination parameter to our standard
neutral simulation. The amount of LD was lower in both the non-recombinant (Fig. 2e) and
recombinant (Fig. 2f) neutral models' generated alignments relative to the corresponding
simulated alignments, likely due to noise in the generated alignments; the slight excess of
singleton polymorphisms in the generated alignments is consistent with this explanation.
Although the magnitude of LD was somewhat diminished, our GAN clearly produces the
expected decay of LD with increasing distance between polymorphisms when recombination is
added to the model.
458

Subdivided population

To test how well our GAN identifies both physical structure in the alignment and its relationship

to the underlying population structure in a two-population sample, we simulated alignments

under multiple two-population island models with varying levels of migration and trained our

GAN on those alignments. F_{ST} between the two populations was similar between the input and

generated alignments for all four migration rates examined (Fig. 3). As with LD, F_{ST} is somewhat

diminished in generated alignments, a pattern that may be attributable to additional noise in

these alignments. We saw among the smallest 2DSWD with the two-population models as

compared to other models our GAN was trained on, particularly when there was little migration

(2DSWD values of 2.26 and 0.74 for migration rates of 0.1 and 1.0, respectively, with the latter

being the lowest 2DSWD observed in our study; Supp. Fig. 3). This result is likely in part

because these models introduce an especially clear structure into the alignments themselves—

the horizontal subdivision between population one (top of the alignment) and population two

(bottom of the alignment; see Fig. 4). This structure may be somewhat analogous to having

distinct objects or edges in an image—something that convolutional networks were designed to

detect (LeCun et al. 1998). Indeed, when we shuffled the individuals in the alignment, thereby

removing that structure, our GAN was unable to recover the clear peak in the SFS at 50%

derived allele frequency in the same manner as it does for the original image (Supp. Fig. 5a,c)—

although it produced an abundance of alleles near 50% frequency, and was able to better mimic

the density of singletons in the alignment. Interestingly, our GAN appears to recover different

parts of the alignment distribution depending on whether individuals are shuffled or not (Supp.

Fig. 5b,d). This may be evidence that the GAN struggles to pick up more nuanced properties of

the alignments like low frequency variants when there is a very strong signal, such as a clear

horizontal split in the alignment as expected in a multi-population dataset, but those properties

are captured when that signal is removed. Such a result is not completely unexpected as GANs

can be weak for characterizing the tails of statistical distributions (Abbasnejad *et al.* 2019).

Two-epoch models of population size change

The demographic history of a population leaves a footprint in patterns of genetic variation, and

accurately detecting this signature and estimating the demographic history of a population is a

common analysis in population genetics (Li and Durbin 2011; Schiffels and Durbin 2014; Liu

and Fu 2015, 2020; Terhorst *et al.* 2017). To see if our GAN can recreate this signature, we

trained our GAN on alignments generated under models of population expansion and

contraction and used Stairway Plot (Liu and Fu 2020) to compare the population size histories

of simulated and GAN-generated alignments. Both population expansion and contraction can be

mimicked by our GAN under modest population size changes (Fig. 5). Population contractions

appear to be more easily captured than expansions, particularly when the magnitude of the

expansion is substantial (Supp. Fig. 6). This may relate to the nature of the input data, where for

histories of population expansion there is an increase in the number of rare polymorphisms

(Supp. Fig. 7). Overall these alignments are more sparse and have less structure for the GAN to

pick up. Additionally, any noise introduced from the GAN would have a disproportionate effect

on such sparse alignments, and potentially reduce the number of rare/singleton polymorphisms.

503
504 *A two-population model of African and European human demographic history*
505
Modern population genetics is increasingly more interested in identifying signatures of complex
histories (Adrion *et al.* 2020b). To test our GAN's ability to capture the properties of a more
complex model, we trained our GAN on simulated alignments under a model of the
demographic history of African and European demography (Tennessen *et al.* 2012). This model
consists of an ancient expansion followed by a population split, two subsequent contractions of
the European population, a phase of exponential expansion of the European population, and
then finally rapid exponential growth in both populations continuing until the present.
Interestingly, even though this is our most complex demographic model, our GAN performs
perhaps better on this model than any of the other models we tested, achieving better LD
estimates than neutral models (Fig. 6a) and the 2nd lowest 2DSWD of any other model (1.00 at
minimum; Supp. Fig. 3). However, the 2DSWD minimum is achieved relatively early in training
and the distance between generated and input alignments increases steadily after that point
(Supp. Fig. 3). Also remarkably similar is the SFS of input and generated alignments for this
model (Fig. 6b). Because this model includes two populations, we also investigated the joint
Site-Frequency Spectrum (jSFS) produced by our GAN. Overall, our GAN is able to accurately
capture the structure and relationship of the two populations in this model, with a fairly similar
jSFS between the simulated and GAN-generated alignments (Fig. 6c,d). However, our GAN
produces a less sharp boundary delineating alleles that are found exclusively in one population
(left-most column and bottom row) or that are fixed in the European population (right-most
column and top row). Although the number of sites in each of these categories is roughly similar
between generated and input alignments, these strict delineations appear difficult for our GAN
to capture precisely when compared to the more conspicuous delineations created by the
simulations.
529
530 *Selective sweeps*
531
Because selective sweeps can leave a strong imprint on genetic diversity (i.e. the hitchhiking
effect; (Smith and Haigh 1974; Kaplan *et al.* 1989; Fay and Wu 2000), but are challenging to
characterize or identify (Jensen *et al.* 2005; Stephan 2016), we were interested in testing how
well our GAN reproduces the hitchhiking effect under varying strengths of selection. Overall, our
GAN was able to replicate the properties of selective sweeps but underestimated some
signatures under models of strong selection. Both the moderate and strong selective sweep
GANs generated alignments that show reduced nucleotide diversity around the selected site
(Fig. 7) nearly identical to the pattern found in the simulated alignments. We also see a
reduction in the related statistics Tajima's D and Watterson's θ (Supp. Fig. 8, Supp. Fig. 9). Not
surprisingly, Kim and Nielsen's ω, which seeks to detect recent hitchhiking events by taking the
ratio of the amount of LD on either side of a sweep site to the amount of LD between pairs of
polymorphisms on either side of the sweep site, is somewhat lower in GAN-generated than
simulated alignments for strong sweeps (mean generated ω = 155.73, mean input ω = 445.29;
Fig. 7). As the amount of LD produced by our GANs was lower than that produced by the
corresponding simulations for each model that we examined, it is not surprising that the ω

statistic deviates from the simulated distribution as well. However, it is clear that the GAN has
learned the essence of the signature that ω is designed to detect: selective sweeps can produce
LD blocks on either side of the sweep that do not extend across the sweep site (see example
alignments, Fig. 7), and we do note that ω values produced by our GAN are similar for the
moderate selection alignments (mean generated ω = 8.58, mean input ω = 8.00) and much
larger than in the no-selection case (mean generated ω = 3.48, mean input ω = 3.23), especially
for the GAN trained to mimic strong selection.
554
555 **Additional Considerations and Evaluation**
556
Throughout training and evaluation of our GAN, the potential for the GAN to generate invariant
sites and the addition of noise breaking down covariances across sites provided the most
consistent effects differentiating GAN-generated from simulated alignments. To quantify the
effect of enforcing variation at every site in the GAN-generated alignments, we calculated
several statistics to compare alignments where invariant sites were dropped from the alignment
with alignments where variation was enforced (see Architecture and Implementation Methods).
We compared these statistics under three models: the standard neutral model with
recombination (no selection), moderate positive selection, and strong positive selection.
Although simply removing invariant sites rather than enforcing variation at every site resulted in
a reduction in singletons as well as poorer overlap of the generated and simulated SFS PCA
(Supp. Fig. 1), enforcing variation did result in reduced LD for all models (Supp. Fig. 10). In the
selective sweep models, it appears that enforcing variation results in a drop in ω for the model
of strong selection, but looking at the moderate selection model, ω is actually overestimated. As
such, it is unclear if the improvement to ω as seen in the strong selection model from dropping
invariant sites is due to increased accuracy or a positive bias. Finally, there seemed to be little
effect on π but a tendency for alignments that simply drop invariant sites to overestimate
Tajima's D (Supp. Fig. 10), as expected due to the reduction of singletons compared to
alignments with variation enforced at every site. Ultimately, it appears that enforcing variation
may have a small effect on downwardly biasing LD, but results in other improvements that make
GAN generated alignments more similar to the input alignments.
577
To quantify the impact of noise introduced by the GAN on its ability to recreate the properties of
the input alignments, we compared input and GAN-generated alignments to input alignments
where a random one percent of values were flipped. We performed this experiment for the same
models examined above when testing the impact of enforcing variation. As predicted, the added
noise resulted in reduced LD across all models and lower ω for models of selection (Supp. Fig.
11). Added noise had little effect on π, but did appear to positively influence Tajima's D across
most windows for all models. Interestingly, this small percentage of added noise had a larger
effect on LD, ω, and Tajima's D for selection models, indicating that the GAN generated
alignments come remarkably close to capturing the statistics of the input alignments, but for
models with reduced diversity and stronger correlations across sites (such as in selection
models), even small amounts of noise can have noticeable effects. We also investigated the
effect of noise on F_{ST} for subdivided population models (Supp. Fig. 12). As in the selection

models, added noise reliably reduced F_{ST} between populations to levels similar to those
observed in GAN-generated alignments.
592

DISCUSSION

In the present work we have demonstrated the efficacy of using GANs to generate artificial
population genetic alignments. After testing several architectures, we were able to design a
GAN that could accurately capture and replicate the properties of alignments under a variety of
evolutionary models. For many of these properties, such as nucleotide diversity and the position
of sites along the alignment, generated alignments from our GAN were largely indistinguishable
from the input alignments. For others, such as measures of LD, even though the GAN-
generated alignments produced values differing from the simulated distribution, the qualitative
dynamics of these statistics reflected those of the simulated population genetic model (e.g.
decaying LD as a function of the distance between polymorphisms for recombinant models, and
the presence of distinct LD blocks on either side of a selective sweep).

Although our GAN performed well for most models tested, it underperformed in some consistent
ways. Most notably was the addition of noise or less distinct boundaries in generated
alignments as compared to the simulated alignments. This effect predictably resulted in the
reduction of certain metrics that rely on structure between individuals or sites (e.g. LD and F_{ST}),
something also seen in previous genetic GANs (Wang *et al.* 2020; Yelmen *et al.* 2021). As well,
although the number of variable sites was close between simulated and generated alignments,
we were unable to ensure variation at every site using just the GAN architecture, and instead
enforced variation by sampling an individual in proportion to its allele probabilities at otherwise
monomorphic sites. While inaccuracy due to noise is most proximally due to inadequate GAN
performance, the ultimate cause of all of these discrepancies results from comparing an exact
and specific population genetic alignment from simulations to an alignment that is not exact by
nature. Simulators produce alignments that guarantee the presence of variation at every
segregating site, and the models that produce linkage disequilibrium and population structure do
not introduce 'noise' beyond that governed by the user-specified model parameters themselves
(e.g. a migration rate parameter that erodes population structure). Although improvements to
the architecture and the use of more sophisticated GANs may produce generated alignments
that more accurately capture these properties, unless the exact function to produce an
alignment for a given model is identified by the network GAN generated alignments will always
be an inexact approximation as compared to simulated alignments.

As presented here, our GAN provides a proof-of-concept for a population genetic GAN in the
nature of GANs as broadly implemented in the deep learning literature: unlike previously
developed population genetic GANs, ours is fully-differentiable (in terms of the density
distribution of alignments) and generates sequences for the whole population sample at once.
This design implies that, while our GAN can be useful for more traditional uses, such as data

augmentation, it perhaps more importantly provides a basis with which to explore more
advanced applications of GANs to population genetics.
633
One potential application with which to extend this work that may prove to be particularly useful
to population genetics is style transfer (Karras *et al.* 2018), where subproperties of the input are
identified by the network and can then be transferred to other data where that subproperty is
absent. In a population genetic context, the ability to transfer styles from one source to another
could be used to 'transfer' one evolutionary process, such as positive selection, to a population
genetic alignment where selection is not believed to have occurred. In this example, the positive
selection 'style' can be learned from simulated data, while the examples without sweeps can
use empirical data that includes all of the challenges such data may present for detecting
selection (e.g. unknown true demographic history, cryptic population structure, low data quality,
etc). Thus, this approach presents the possibility of combining the strengths of reductionist
generative models with those of GANs, and could potentially be used to produce more accurate
training data for machine learning-based methods for detecting selective sweeps (Pybus *et al.*
2015; Schrider and Kern 2016; Kern and Schrider 2018; Whitehouse and Schrider 2022). Such
uses may prove to be one of the strengths of GANs for population genetic data over using
simulators alone, as they provide ability to capture and recreate subtle properties of the data
that cannot be encompassed by simple idealized models used for simulations. Similarly, one
could take alignments from empirical data and transfer various demographic hypotheses to
those alignments to help generate the reference table for performing approximate Bayesian
computation. Much like transferring selection 'styles', this example provides the obvious benefit
of not requiring pre-defined population parameters for generating all aspects of the desired
training data. Finally, a particularly intriguing use would involve combining work on creating an
interpretable latent space, where population parameters can be translated into different parts of
a multi-dimensional Gaussian (Liu *et al.* 2022), with the ability to project generated examples
onto this latent space (Karras *et al.* 2021). While the latent space interpretation would allow for a
simulator that is instantaneous once trained, the combination with latent space projection would
make the network capable of inferring the demographic parameters of real data and testing
evolutionary hypotheses using the network directly.
661
Ultimately, this work and its potential expansions further demonstrate the potential of deep-
learning methods for population genetic research. While some may deride deep-learning as
inferior to more traditional statistical methods due to their (current) black box nature, we urge
skeptical readers to momentarily suspend this view. Instead, we implore readers to explore the
continually-expanding collection of deep-learning networks alongside their applications, and
consider how these tools could be used to help facilitate advances in their own systems and
fields. As we have shown here, researchers do not need to start from scratch and can
repurpose existing networks for evolutionary applications. Unsurprisingly, such repurposing has
led to several creative purposes well outside of the developer's initial intention, such as applying
cycleGANs (Zhu *et al.* 2017) to normalize single cell RNA-seq data across datasets (Khan *et al.*
2022) and using natural language processing models to predict the effect of nucleotide variants
(Benegas *et al.* 2022). At a time when unprecedented resources are being used to develop
deep-learning technologies outside of biology, biologists from all fields should consider the

myriad ways in which these technologies can be leveraged to solve problems and answer
longstanding questions.
677

DATA AVAILABILITY

679 Scripts and additional example images available at github.com/SchriderLab/PG-Alignments-
680 GAN

ACKNOWLEDGEMENTS

682 We would like to thank Andrew Kern for comments on the manuscript, Nick Matthew for his
683 work and guidance on GANs prior to the development of this project, as well as other members
684 of our lab: Logan Whitehouse, Amjad Dabi, Becca Love, and Anton Suvrov for their advice and
685 assistance.
686

FUNDING AND COMPETING INTERESTS

688 WWB was supported by NIH grant HG010774, and DRS was supported by NIH grants
689 HG010774 and GM138286. The authors have no competing interests.
690
691

REFERENCES

Abbasnejad M. E., Q. Shi, A. van den Hengel, and L. Liu, 2019 A generative adversarial density

estimator, pp. 10774–10783 in *2019 IEEE/CVF Conference on Computer Vision and*

Pattern Recognition (CVPR), IEEE.

Adrion J. R., J. G. Galloway, and A. D. Kern, 2020a Predicting the landscape of recombination

using deep learning. Mol. Biol. Evol. 37: 1790–1808.

https://doi.org/10.1093/molbev/msaa038

Adrion J. R., C. B. Cole, N. Dukler, J. G. Galloway, A. L. Gladstein, *et al.*, 2020b A community-

maintained standard library of population genetic models. eLife 9.

https://doi.org/10.7554/eLife.54967

Arjovsky M., S. Chintala, and L. Bottou, 2017 Wasserstein GAN. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.1701.07875

Battey C. J., G. C. Coffing, and A. D. Kern, 2021 Visualizing population structure with variational

autoencoders. G3 (Bethesda) 11. https://doi.org/10.1093/g3journal/jkaa036

Baumdicker F., G. Bisschop, D. Goldstein, G. Gower, A. P. Ragsdale, *et al.*, 2022 Efficient

ancestry and mutation simulation with msprime 1.0. Genetics 220.

https://doi.org/10.1093/genetics/iyab229

Beaumont M. A., 2010 Approximate Bayesian Computation in Evolution and Ecology. Annu.

Rev. Ecol. Evol. Syst. 41: 379–406. https://doi.org/10.1146/annurev-ecolsys-102209-

144621

Benegas G., S. S. Batra, and Y. S. Song, 2022 DNA language models are powerful zero-shot

predictors of non-coding variant effects. BioRxiv. [accessed 2023 Apr 6].

https://doi.org/10.1101/2022.08.22.504706

Bonneel N., J. Rabin, G. Peyré, and H. Pfister, 2015 Sliced and radon wasserstein barycenters

of measures. J. Math. Imaging Vis. 51: 22–45. https://doi.org/10.1007/s10851-014-0506-3

Bousmalis K., N. Silberman, D. Dohan, D. Erhan, and D. Krishnan, 2017 Unsupervised Pixel-

Level Domain Adaptation with Generative Adversarial Networks, pp. 95–104 in *2017 IEEE*

Conference on Computer Vision and Pattern Recognition (CVPR), IEEE.

Breiman L., 2001 Statistical Modeling: The Two Cultures (with comments and a rejoinder by the

author). Stat. Sci. 16: 199–231. https://doi.org/10.1214/ss/1009213726

Burkart N., and M. F. Huber, 2021 A survey on the explainability of supervised machine

learning. jair 70: 245–317. https://doi.org/10.1613/jair.1.12228

Creswell A., T. White, V. Dumoulin, K. Arulkumaran, B. Sengupta, *et al.*, 2018 Generative

adversarial networks: an overview. IEEE Signal Process. Mag. 35: 53–65.

https://doi.org/10.1109/MSP.2017.2765202

Fay J. C., and C. I. Wu, 2000 Hitchhiking under positive Darwinian selection. Genetics 155:

1405–1413. https://doi.org/10.1093/genetics/155.3.1405

Ferrer-Admetlla A., M. Liang, T. Korneliussen, and R. Nielsen, 2014 On detecting incomplete

soft or hard selective sweeps using haplotype structure. Mol. Biol. Evol. 31: 1275–1291.

https://doi.org/10.1093/molbev/msu077

Flagel L., Y. Brandvain, and D. R. Schrider, 2019 The unreasonable effectiveness of

convolutional neural networks in population genetic inference. Mol. Biol. Evol. 36: 220–238.

https://doi.org/10.1093/molbev/msy224

Goodfellow I. J., J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, *et al.*, 2014 Generative

Adversarial Networks. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.1406.2661

Gower G., P. I. Picazo, M. Fumagalli, and F. Racimo, 2021 Detecting adaptive introgression in

human evolution using convolutional neural networks. eLife 10.

https://doi.org/10.7554/eLife.64669

Gulrajani I., F. Ahmed, M. Arjovsky, V. Dumoulin, and A. C. Courville, 2017 Improved training of

wasserstein gans. Advances in neural information processing systems 30.

Harris C. R., K. J. Millman, S. J. van der Walt, R. Gommers, P. Virtanen, *et al.*, 2020 Array

programming with NumPy. Nature 585: 357–362. https://doi.org/10.1038/s41586-020-2649-

2

He K., X. Zhang, S. Ren, and J. Sun, 2015 Deep Residual Learning for Image Recognition.

arXiv. [accessed 2023 Apr 6]. https://doi.org/10.48550/arxiv.1512.03385

Hudson R. R., and N. L. Kaplan, 1995 Deleterious background selection with recombination.

Genetics 141: 1605–1617.

Hudson R. R., 2002 Generating samples under a Wright-Fisher neutral model of genetic

variation. Bioinformatics 18: 337–338. https://doi.org/10.1093/bioinformatics/18.2.337

Isildak U., A. Stella, and M. Fumagalli, 2021 Distinguishing between recent balancing selection

and incomplete sweep using deep neural networks. Mol. Ecol. Resour.

https://doi.org/10.1111/1755-0998.13379

Jang E., S. Gu, and B. Poole, 2016 Categorical Reparameterization with Gumbel-Softmax.

arXiv. [accessed 2023 Apr 6]. https://doi.org/10.48550/arxiv.1611.01144

Jensen J. D., Y. Kim, V. B. DuMont, C. F. Aquadro, and C. D. Bustamante, 2005 Distinguishing

between selective sweeps and demography using DNA polymorphism data. Genetics 170:

1401–1410. https://doi.org/10.1534/genetics.104.038224

Jumper J., R. Evans, A. Pritzel, T. Green, M. Figurnov, *et al.*, 2021 Highly accurate protein

structure prediction with AlphaFold. Nature 596: 583–589. https://doi.org/10.1038/s41586-

021-03819-2

Kaplan N. L., R. R. Hudson, and C. H. Langley, 1989 The "hitchhiking effect" revisited. Genetics

123: 887–899.

Karras T., S. Laine, and T. Aila, 2018 A Style-Based Generator Architecture for Generative

Adversarial Networks. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.1812.04948

Karras T., M. Aittala, S. Laine, E. Härkönen, J. Hellsten, *et al.*, 2021 Alias-Free Generative

Adversarial Networks. Advances in Neural Information Processing Systems 34: 852-863

Kelleher J., A. M. Etheridge, and G. McVean, 2016 Efficient coalescent simulation and

genealogical analysis for large sample sizes. PLoS Comput. Biol. 12: e1004842.

https://doi.org/10.1371/journal.pcbi.1004842

Kern A. D., and D. R. Schrider, 2016 Discoal: flexible coalescent simulations with selection.

Bioinformatics 32: 3839–3841. https://doi.org/10.1093/bioinformatics/btw556

Kern A. D., and D. R. Schrider, 2018 diploS/HIC: An Updated Approach to Classifying Selective

Sweeps. G3 (Bethesda) 8: 1959–1970. https://doi.org/10.1534/g3.118.200262

Khan S. A., R. Lehmann, X. Martinez-de-Morentin, A. M. Ruiz, V. Lagani, *et al.*, 2022

scAEGAN: Unification of Single-Cell Genomics Data by Adversarial Learning of Latent

Space Correspondences. BioRxiv. https://doi.org/10.1101/2022.04.19.488745

Kim Y., and R. Nielsen, 2004 Linkage disequilibrium as a signature of selective sweeps.

Genetics 167: 1513–1524. https://doi.org/10.1534/genetics.103.025387

Kim Y., and J.-W. Ha, 2021 Contrastive Fine-grained Class Clustering via Generative

Adversarial Networks. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.2112.14971

Kingma D. P., and J. Ba, 2014 Adam: A Method for Stochastic Optimization. arXiv. [accessed

2023 Apr 6]. https://doi.org/10.48550/arxiv.1412.6980

LeCun Y., B. Boser, J. S. Denker, D. Henderson, R. E. Howard, *et al.*, 1989 Backpropagation

applied to handwritten zip code recognition. Neural Comput. 1: 541–551.

https://doi.org/10.1162/neco.1989.1.4.541

Lecun Y., L. Bottou, Y. Bengio, and P. Haffner, 1998 Gradient-based learning applied to

document recognition. Proc. IEEE 86: 2278–2324. https://doi.org/10.1109/5.726791

LeCun Y., Y. Bengio, and G. Hinton, 2015 Deep learning. Nature 521: 436–444.

https://doi.org/10.1038/nature14539

Liu X., and Y.-X. Fu, 2015 Exploring population size changes using SNP frequency spectra.

Nat. Genet. 47: 555–559. https://doi.org/10.1038/ng.3254

Liu X., and Y.-X. Fu, 2020 Stairway Plot 2: demographic history inference with folded SNP

frequency spectra. Genome Biol. 21: 280. https://doi.org/10.1186/s13059-020-02196-9

Liu K., G. Cao, F. Zhou, B. Liu, J. Duan, *et al.*, 2022 Towards disentangling latent space for

unsupervised semantic face editing. IEEE Trans. on Image Process. 31: 1475–1489.

https://doi.org/10.1109/TIP.2022.3142527

Li H., and R. Durbin, 2011 Inference of human population history from individual whole-genome

sequences. Nature 475: 493–496. https://doi.org/10.1038/nature10231

Maddison C. J., A. Mnih, and Y. W. Teh, 2016 The Concrete Distribution: A Continuous

Relaxation of Discrete Random Variables. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.1611.00712

Miles A., P. Ralph, S. Rae, and R. Pisupati, 2021 cggh/scikit-allel: v1.3.3. London: Zenodo.

Nei M., and W. H. Li, 1979 Mathematical model for studying genetic variation in terms of

restriction endonucleases. Proc Natl Acad Sci USA 76: 5269–5273.

https://doi.org/10.1073/pnas.76.10.5269

Nordborg M., B. Charlesworth, and D. Charlesworth, 1996 The effect of recombination on

background selection. Genet. Res. 67: 159–174.

https://doi.org/10.1017/s0016672300033619

Paszke A., S. Gross, F. Massa, A. Lerer, J. Bradbury, *et al.*, 2019 PyTorch: An Imperative Style,

High-Performance Deep Learning Library, pp. 8024–8035 in *Advances in Neural*

Information Processing Systems 32, edited by Wallach H., Larochelle H., Beygelzimer A.,

Buc F. dAlché-, Fox E., *et al.* Curran Associates, Inc.

Pybus M., P. Luisi, G. M. Dall'Olio, M. Uzkudun, H. Laayouni, *et al.*, 2015 Hierarchical boosting:

a machine-learning framework to detect and classify hard selective sweeps in human

populations. Bioinformatics 31: 3946–3952. https://doi.org/10.1093/bioinformatics/btv493

Radford A., L. Metz, and S. Chintala, 2015 Unsupervised Representation Learning with Deep

Convolutional Generative Adversarial Networks. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.1511.06434

Salimans T., I. Goodfellow, W. Zaremba, V. Cheung, A. Radford, *et al.*, 2016 Improved

824   techniques for training gans. Advances in neural information processing systems 29.

825 Sanchez T., J. Cury, G. Charpiat, and F. Jay, 2021 Deep learning for population size history

826   inference: Design, comparison and combination with approximate Bayesian computation.

827   Mol. Ecol. Resour. 21: 2645–2660. https://doi.org/10.1111/1755-0998.13224

828 Schiffels S., and R. Durbin, 2014 Inferring human population size and separation history from

829   multiple genome sequences. Nat. Genet. 46: 919–925. https://doi.org/10.1038/ng.3015

830 Schrider D. R., and A. D. Kern, 2015 Inferring Selective Constraint from Population Genomic

831   Data Suggests Recent Regulatory Turnover in the Human Brain. Genome Biol. Evol. 7:

832   3511–3528. https://doi.org/10.1093/gbe/evv228

833 Schrider D. R., and A. D. Kern, 2016 S/HIC: robust identification of soft and hard sweeps using

834   machine learning. PLoS Genet. 12: e1005928.

835   https://doi.org/10.1371/journal.pgen.1005928

836 Schrider D. R., and A. D. Kern, 2018 Supervised machine learning for population genetics: A

837   new paradigm. Trends Genet. 34: 301–312. https://doi.org/10.1016/j.tig.2017.12.005

838 Selvaraju R. R., M. Cogswell, A. Das, R. Vedantam, D. Parikh, *et al.*, 2017 Grad-CAM: Visual

839   explanations from deep networks via gradient-based localization, pp. 618–626 in

840   *Proceedings of 2017 IEEE International Conference on Computer Vision (ICCV)*, IEEE.

841 Simonsen K. L., G. A. Churchill, and C. F. Aquadro, 1995 Properties of statistical tests of

842   neutrality for DNA polymorphism data. Genetics 141: 413–429.

843   https://doi.org/10.1093/genetics/141.1.413

844 Simonyan K., A. Vedaldi, and A. Zisserman, 2013 Deep Inside Convolutional Networks:

845   Visualising Image Classification Models and Saliency Maps. arXiv. [accessed 2023 Apr 6].

846   https://doi.org/10.48550/arxiv.1312.6034

Smith J. M., and J. Haigh, 1974 The hitch-hiking effect of a favourable gene. Genet. Res. 23:

23–35. https://doi.org/10.1017/S0016672300014634

Smith C. C. R., S. Tittes, P. L. Ralph, and A. D. Kern, 2022 Dispersal inference from population

genetic variation using a convolutional neural network. BioRxiv. [accessed 2023 Apr 6].

https://doi.org/10.1101/2022.08.25.505329

Stephan W., 2016 Signatures of positive selection: from selective sweeps at individual loci to

subtle allele frequency changes in polygenic adaptation. Mol. Ecol. 25: 79–88.

https://doi.org/10.1111/mec.13288

Tajima F., 1989 Statistical method for testing the neutral mutation hypothesis by DNA

polymorphism. Genetics 123: 585–595. https://doi.org/10.1093/genetics/123.3.585

Tennessen J. A., A. W. Bigham, T. D. O'Connor, W. Fu, E. E. Kenny, *et al.*, 2012 Evolution and

functional impact of rare coding variation from deep sequencing of human exomes. Science

337: 64–69. https://doi.org/10.1126/science.1219240

Terhorst J., J. A. Kamm, and Y. S. Song, 2017 Robust and scalable inference of population

history from hundreds of unphased whole genomes. Nat. Genet. 49: 303–309.

https://doi.org/10.1038/ng.3748

Thanh-Tung H., and T. Tran, 2020 Catastrophic forgetting and mode collapse in GANs, pp. 1–

10 in *2020 International Joint Conference on Neural Networks (IJCNN)*, IEEE.

Voight B. F., S. Kudaravalli, X. Wen, and J. K. Pritchard, 2006 A map of recent positive

selection in the human genome. PLoS Biol. 4: e72.

https://doi.org/10.1371/journal.pbio.0040072

Wang Z., J. Wang, M. Kourakos, N. Hoang, H. H. Lee, *et al.*, 2020 Automatic inference of

demographic parameters using generative adversarial networks. BioRxiv. [accessed 2023

Apr 6]. https://doi.org/10.1101/2020.08.05.237834

Watterson G. A., 1975 On the number of segregating sites in genetical models without

recombination. Theor. Popul. Biol. 7: 256–276. https://doi.org/10.1016/0040-

5809(75)90020-9

Whitehouse L. S., and D. R. Schrider, 2022 Timesweeper: accurately identifying selective

sweeps using population genomic time series. BioRxiv. [accessed 2023 Apr 6].

https://doi.org/10.1101/2022.07.06.499052

Yale A., S. Dash, R. Dutta, I. Guyon, A. Pavao, *et al.*, 2019 Privacy Preserving Synthetic Health

Data, in hal-02160496, Bruges, Belgium.

Yelmen B., A. Decelle, L. Ongaro, D. Marnetto, C. Tallec, *et al.*, 2021 Creating artificial human

genomes using generative neural networks. PLoS Genet. 17: e1009303.

https://doi.org/10.1371/journal.pgen.1009303

Zhu J.-Y., T. Park, P. Isola, and A. A. Efros, 2017 Unpaired Image-to-Image Translation using

Cycle-Consistent Adversarial Networks. arXiv. [accessed 2023 Apr 6].

https://doi.org/10.48550/arxiv.1703.10593

<u>Figures</u>

Figure 1. Architecture and implementation of our Generative Adversarial Network. The final
network chosen is a branched Deep Convolutional Gan (DCGAN) with Wasserstein loss
(WGAN) and a gradient penalty to enforce 1-Lipschitz continuity. The generator takes in a
random noise vector drawn from a multidimensional Gaussian and is branched into independent
transposed convolutional layers to produce artificial alignments along with a vector of the
positions of segregating sites. The discriminator takes in either generated or real alignments
and positions vectors and evaluates them through a branched network of convolutions. Loss is
calculated using the earth mover's distance between real and generated alignments with an
additional gradient penalty term, and is used to train the discriminator which in turn trains the
generator.

Figure 2. GAN performance under a standard neutral model. Input (i.e. simulated) alignments are shown in purple and generated alignments are shown in green. (a) PCA of the SFS of each alignment, calculated jointly with 100 input and generated alignments each. (b) Average SFS across 1000 simulated alignments and 1000 generated alignments. (c) Positions of polymorphisms along 100 example simulated and generated chromosomes. (d) Density plot showing the distribution of average per-site nucleotide diversity values across all input and generated alignments. (e) LD as a function of distance between polymorphisms for the non-

908   recombinant model. (f) LD as a function of distance between polymorphisms for the
909   recombinant model.
910
911

912
913   **Figure 3.** Fixation index (F_{ST}) as a function of migration rate (shown in units of $4Nm$) in input
914   (purple) and generated (green) alignments. Each GAN was trained on alignments of two
915   populations of 32 individuals and one of four bidirectional migration rates. Box and whisker plots
916   of F_{ST} were generated using 1000 alignments for each migration rate.
917
918

919
920 **Figure 4.** Example input (left) and generated (right) alignments for each model analyzed.
921 Generated alignments were made using the saved network with the minimum 2DSWD. Each
922 alignment contains 64 individuals with 64 sites. Selective sweep models (bottom two rows)
923 show a blue line in the center of the alignment identifying the sweep site.
924

Figure 5. Effective population size (Ne) estimates as a function of time for input (purple) and generated (green) alignments. All estimates were calculated using Stairway Plot (version 2.1.1) with 1000 averaged site-frequency spectra and show the median and 95% CI population size estimate at each point in time. (a) Stairway Plot estimates for 10-fold population-size expansion input alignments, (b) 10-fold population-size expansion generated alignments, (c) 10-fold population contraction input alignments, (d) 10-fold population contraction generated alignments.

Figure 6. GAN results for generating alignments under the two-population out-of-Africa model from Tennessen et al. (2012). (a) LD decay as a function of distance between polymorphisms for input (purple) and generated (green) alignments. (b) Average site-frequency spectrum (SFS) over 1000 input and generated alignments. (c) joint site-frequency spectrum (jSFS) of 1000 input alignments for African (AFR) and European (EUR) individuals. (c) joint site-frequency spectrum (jSFS) of 1000 generated alignments for AFR and EUR individuals.

Figure 7. Generating selective sweeps using GANs. From top to bottom: metrics and examples from GANs trained on alignments with no selection, a moderate selective sweep, and a strong selective sweep, with the selected site occurring at the alignment midpoint. From left to right: position of each of the 64 sites in the alignment along the chromosome for input (purple) and generated (green) alignments, Average nucleotide diversity (π) across 1000 alignments in 0.05 position windows along the alignment (error bars represent standard deviations), and density plots showing the distribution of Kim and Nielsen's ω for 1000 alignments.