CysPresso: A classification model utilizing deep learning protein

representations to predict recombinant expression of cysteine-dense

peptides

Sébastien Ouellet[1], Larissa Ferguson[2], Angus Z. Lau[3,4], Tony K.Y. Lim[5,6]*

Author Information

[1] Independent Researcher, Ottawa, Ontario, Canada

[2] Neurobiology Division, MRC Laboratory of Molecular Biology, Cambridge, United Kingdom

[3] Medical Biophysics, University of Toronto, Toronto, Ontario, Canada.

[4] Physical Sciences Platform, Sunnybrook Research Institute, Toronto, Ontario, Canada.

[5] Independent Researcher, Vancouver, British Columbia, Canada

[6] Department of Pharmacology, University of Cambridge, Cambridge, United Kingdom

* Corresponding Author (tony.ky.lim@gmail.com)

ORCID: SO (0000-0002-3098-4907), LF (0000-0003-4274-8634), TKYL (0000-0003-1843-0060)

Abstract

Background: Cysteine-dense peptides (CDPs) are an attractive pharmaceutical scaffold that

display extreme biochemical properties, low immunogenicity, and the ability to bind targets with

high affinity and selectivity. While many CDPs have potential and confirmed therapeutic uses,

synthesis of CDPs is a challenge. Recent advances have made the recombinant expression of

CDPs a viable alternative to chemical synthesis. Moreover, identifying CDPs that can be

expressed in mammalian cells is crucial in predicting their compatibility with gene therapy and

mRNA therapy. Currently, we lack the ability to identify CDPs that will express recombinantly in

mammalian cells without labour intensive experimentation. To address this, we developed

CysPresso, a novel machine learning model that predicts recombinant expression of CDPs

based on primary sequence.

Results: We tested various protein representations generated by deep learning algorithms

(SeqVec, proteInfer, AlphaFold2) for their suitability in predicting CDP expression and found that

AlphaFold2 representations possessed the best predictive features. We then optimized the

model by concatenation of AlphaFold2 representations, time series transformation with random

convolutional kernels, and dataset partitioning.

Conclusion: Our novel model, CysPresso, is the first to successfully predict recombinant CDP

expression in mammalian cells and is particularly well suited for predicting recombinant

expression of knottin peptides. When preprocessing the deep learning protein representation for

supervised machine learning, we found that random convolutional kernel transformation

preserves more pertinent information relevant for predicting expressibility than embedding

averaging. Our study showcases the applicability of deep learning-based protein

representations, such as those provided by AlphaFold2, in tasks beyond structure prediction.

Keywords:

Protein representation, recombinant expression, cysteine-dense peptide, knottin, deep learning,

AlphaFold

Background

Cysteine-dense peptides (CDPs) are highly constrained by disulfide bonds, producing a

molecular structure that confers extreme stability against proteolytic, thermal, and chemical

degradation [1, 2]. As a result, there is much interest in utilizing CDPs as drug scaffolds [3].

Naturally occurring CDPs have diverse pharmacological and toxicological effects, including

activities against ion channels, G-protein coupled receptors, and enzymes, as well as cytotoxic

and anti-microbial properties [4–7]. One particular class of CDP, the inhibitor cysteine knot

peptides—also known as knottins—has received much interest due to their confirmed and

potential uses as analgesics, anthelmintics, anti-erectile dysfunction agents, neuroprotectives,

antimalarials, antimicrobials, antitumour agents, protease inhibitors, toxins, insecticides,

molecular imaging agents, and drug delivery vehicles [8–10].

Another reason that CDPs are of interest is their potential in drugging "undruggable" targets

[11]. Identifying small molecules capable of disrupting protein-protein interactions has proven to

be a challenge, leaving many protein aggregation diseases untreated. While antibodies are

capable of disrupting protein-protein interactions, their large size limits their ability to penetrate

tissues and access intracellular targets. CDPs, on the other hand, are small enough to avoid

these limitations while still being able to interfere with protein-protein interactions [12, 13].

One of the challenges of using CDPs for therapeutic purposes is that they are difficult to

synthesize and express. While the disulfide bonds are important for the stability of the molecule,

incorrect linkage can lead to misfolded non-native isomers [14–16]. Recent work using high-

throughput expression systems to express CDPs in mammalian cells has allowed the screening

of hundreds of CDPs for expression [17, 18]. Though this work has led to the identification of a

number of CDPs that can be efficiently produced through recombinant expression, our ability to

discern the expressibility of CDPs based on amino acid sequences is currently limited,

necessitating prior experimentation. The ability to determine which CDPs will express in

mammalian cells would be valuable in identifying those compatible with biologic production,

gene therapy, and mRNA therapy, and would facilitate the design and development of

recombinant CDPs for therapeutic use.

To bridge this gap, we developed CysPresso, a machine learning classifier that predicts

whether a CDP will be expressible based on its primary sequence. We tested various protein

representations to identify the ideal model to utilize with machine learning algorithms to predict

expressibility from primary sequences. We tested the performance of representations from an

ELMo language model trained on protein sequences (SeqVec) [19], a deep dilated convolutional

network trained on protein functions (ProteInfer) [20], and a neural network trained to predict

protein structure (AlphaFold2) [21], and determined that AlphaFold2 representations performed

best at predicting expressibility. The AlphaFold2 algorithm generates four protein

representations, and we found that combining the representations enhanced model

performance. Stratification of the dataset into knottin and non-knottin CDPs improved

predictions of expressibility for knottin peptides. Additionally, model performance for knottin

peptide expressibility could be further enhanced through application of a time series

classification method implementing random convolutional kernels [22]. The performance of the

final model, CysPresso, evaluated by receiver operating characteristic area under the curve

(AUC) yielded 0.798 for non-knottin CDPs and 0.852 for knottin CDPs. To our knowledge, this is

the first study to demonstrate that prediction of recombinant protein expression in mammalian

cells can be carried out successfully by supervised machine learning. This method will be useful

in identifying recombinant peptides and proteins that are expressible in mammalian cells,

enabling the prediction of proteins compatible with biologic production, gene therapy and mRNA

therapy.

Methods

Data preprocessing

This study utilized previously published data [17]. In this dataset, CDPs of 30 to 50 amino acids

in length were tested for expression using the Daedalus lentivirus production system in HEK293

cells and subsequently purified by reverse phase chromatography (RPC). Products were

deemed successfully expressed if the RPC peak demonstrated a single peak under both

oxidizing and reducing conditions, which is characteristic of a single folding state and the

absence of heterogeneity.

The original dataset contained a list of 1249 CDPs, including UniProt accession number,

primary sequence, source organism, and expressibility. Twenty two duplicate entries were

removed, leaving 1227 CDPs (Supplemental Table 1). CDPs were identified as knottins if the

keyword knottin (KW-0960) was mapped to its UniProt entry on the UniProt database [23].

Protein representations

Protein representations, or embeddings, encode proteins into a numeric format compatible with

mathematical operations used in machine learning. Representations from SeqVec were

generated using the pre-trained UniRef50 ELMo model [19], resulting in 1024 per-residue

features derived from the final hidden layer of the neural network. Averaging within-feature

yielded an embedding of 1024 features per CDP. Similarly, representations from proteInfer were

generated using the Swiss-Prot EC model [24] to yield 1100 per-residue features, which were

then averaged within-feature to yield an embedding of 1100 features per CDP.

To generate AlphaFold2 representations, AlphaFold2 [21] was run using the complete database

setting for Multiple Sequence Alignment (MSA) search on the Compute Canada supercomputer

cluster. The five models (monomer_casp14, model weights: v2.2.0 with 8x ensembling and

relaxation) that were used during the 14th community wide experiment on the Critical

Assessment of techniques for protein Structure Prediction (CASP14) were utilized to generate

representations, but only the representation from the model with the highest average predicted

Local Distance Difference Test (pLDDT) was used for downstream predictions. Embeddings

from the final hidden layer of the single (384 per-residue features), pair (128 per-residue

features after averaging the first dimension), MSA (256 per-residue features) and structure

module (384 per-residue features) representations were collected. To create the combined

AlphaFold2 representation, the single, pair, MSA and structure module features were

concatenated, producing feature vectors of 1152 dimensions. When used to train random forest

algorithms, per-residue features of the AlphaFold2 representations were averaged.

Supervised learning algorithms

As random forest classifiers perform implicit feature selection and provide a measure of feature

importance [25], they were implemented through scikit-learn [26] to allow comparisons between

the quality of protein representations for the prediction of expressibility. Hyperparameters were

left at default scikit-learn values, other than the n_estimators (number of trees) value which was

set to 300. To estimate performance between different protein models, 10-fold cross validation

was used, and the same shuffle was utilized across the different protein models. When data

stratification was carried out, shuffling the train and test folds was balanced to contain an equal

number of expressing and non-expressing non-knottins and knottins among each fold (Table 1).

When time series transformation was carried out, such as when implementing the final

CysPresso model, L2-regularized logistic regression was used for supervised learning as

described below.

Random Convolutional Kernel Transformation

Embeddings from deep learning protein representations are commonly averaged before

machine learning tasks are carried out [19, 27, 28]. We hypothesized that employing other

methodologies such as utilizing convolutional kernels may provide better feature extraction.

RandOm Convolutional KErnel Transform (ROCKET) is an approach developed for time series

classification tasks that uses random convolutional kernels to transform sequential features, and

is useful for capturing discriminating signals and patterns in ordered data with a low

computational requirement [22]. To apply ROCKET, we created a concatenation of the four

AlphaFold2 representations without any per-residue averaging. To ensure uniformity in

representation size, representations of CDPs with fewer than 50 amino acids were padded with

zeros. As a result, each CDP was represented as 50 residues x 1152 per-residue hidden layer

neural activations. Representations were then transformed by ROCKET, convolving 10,000

randomly generated kernels over the representation, producing a new representation of 20,000

features per CDP. The ROCKET representations were then classified using a L2-regularized

logistic regression model, which was chosen because linear classifiers, such as logistic

regression, are well-suited for utilizing limited information from a vast number of features, and

regularization plays a crucial role in preventing overfitting when the number of features exceeds

the number of training examples [29]. The original ROCKET methodology also promotes the

use of L2-regularized logistic regression for high classification accuracy when computational

expense does not need to be minimized [17].

Comparison of average pLDDT values

AlphaFold2 offers a confidence metric on a per-residue basis, which is referred to as pLDDT

[21]. The pLDDT values of AlphaFold2 for each CDP were averaged over the entire peptide and

then displayed using a violin plot. Comparisons of average pLDDT values were made using the

Mann Whitney test.

SHAP analysis

To investigate the impact of AlphaFold2 representation types and residue positions on the

predictions, we trained a random forest classifier on representations of size 50x1152 per CDP

and analysed individual predictions over the dataset using SHapley Additive exPlanations

(SHAP), a method developed to compute the direct contributions from each feature toward the

final class probability [22]. The absolute values of these contributions were summed and

visualized to determine which features contribute the most towards expressibility. Utilizing

SHAP values, we were able to isolate the contributions per AlphaFold2 representation type as

well as the contributions per residue position. To account for differences in sequence length,

SHAP values were normalized by the number of sequences of that length. As data

transformation (such as ROCKET) breaks direct relationships between residue positions and

feature contributions, SHAP analysis was only applied to the random forest model.

Leave-one-out cross validation

To evaluate the quality of the classification in terms of class-specific accuracies, we computed

confusion matrices for both knottin and non-knottin models using ROCKET time-series

classification with the combined AlphaFold2 representations as described above using a L2-

regularized logistic regression model with a decision threshold of 0.5. A leave-one-out cross

validation scheme was followed, training as many model instances as samples per set and

aggregating the predicted labels over all samples. We also aggregated the confidence

estimates of the models to calculate a general AUC over the entire set.

Comparisons of model performance

The models discussed in this paper (except SeqVec and UniRep-RF) were evaluated with a

permutation test over 50 random permutations of the stratified dataset, with a 90-10 split for

training and validation sets. The different models were ranked in order of AUC, and the average

rank out of 50 permutations was determined and plotted on a critical difference diagram using

previously described methods [30], with the significance level set to 0.05.

To assess CysPresso in relation to state-of-the-art models of recombinant protein expression,

we conducted a comparison to UniRep-RF, a predictive model of recombinant protein

expression in B. subtilis [27]. Utilizing the CDPs in this dataset, UniRep protein representations

were obtained [28] and UniRep-RF was implemented according to previously established

methods with hyperparameter optimization [27]. UniRep-RF was compared to CysPresso by

two-tailed permutation test on AUC values with significance level set to 0.05. AUC was

calculated by 10-fold cross validation and iterated over 10,000 random permutations.

Code

Code used to generate this work is available on github at https://github.com/Zebreu/cyspresso.

Results

Peptide expressibility database

The library used in this study characterized the expression of 1227 CDPs [17]. The lengths of

the CDPs varied between 30 to 50 amino acids and were derived from a wide range of

organisms, including mammals, arachnids, amphibians, reptiles, insects, birds, molluscs, fish,

plants, and fungi. Of these CDPs, 351 were classified as knottins according to the UniProt

database (Table 1). The data was slightly skewed, with 58.6% and 47% of the non-knottin and

knottin CDPs deemed expressible in HEK293 cells, respectively.

Table 1. Expressibility of recombinant non-knottin and knottin CDPs.

	Successful expression	Unsuccessful expression	Total
Non-knottin CDPs	513 (58.6%)	363 (41.4%)	876
Knottin CDPs	165 (47.0%)	186 (53.0%)	351
			1227

Using a high-throughput expression system in HEK293 cells, the expressibility of 1227 CDPs
was determined [17]. Entries were cross referenced with the UniProt database to distinguish
knottins from non-knottins.

Protein representation performance

Protein representations of CDPs were generated by obtaining neural embeddings from SeqVec,

proteInfer, and AlphaFold2–models that are distinct in how they generate representations. For

instance, SeqVec generates protein representations by utilizing the bi-directional language

model 'Embeddings from Language Models' to identify relationships based on sequence syntax

[19]. On the other hand, proteInfer [20] and AlphaFold2 [21] are neural network models trained

to predict protein function and structure, respectively. Embeddings from these models were

averaged and used as inputs for random forest algorithms to predict expressibility and tested

using a stratified 10-fold cross validation. AUC was used as the evaluation metric (Fig. 1A). As

random forest algorithms perform implicit feature selection, the performance of the random

forest algorithm becomes a measure of feature performance. Thus, we examined the

performance of protein representations generated from primary sequences at predicting

expressibility. Out of the different protein representations tested, SeqVec had the least

predictive power but still yielded usable models with AUC averaging 0.665. When classifiers

were trained using embeddings from proteInfer, performance was improved with classifier AUC

averaging 0.696. Interestingly, the best performance was obtained with embeddings from

AlphaFold2. By using the single representation from AlphaFold2, AUC averaged 0.781 (Fig.

1B).

AlphaFold2 uses four different types of representations for structure predictions [21]. The MSA

representation is based on the primary sequence and evolutionary relationships between

proteins. The abstract single representation is derived from a linear projection of the first row of

the MSA representation. The pair representation is a model of amino acids which are likely in

close proximity based on a structure database search. These three representations are updated

by the neural network and used as inputs to generate the structure module representation,

which is a prediction of atom coordinates and a per-residue confidence measure. As the four

AlphaFold2 representations contain different information (evolutionary relationships, abstract

features, known protein structures, and atomic positions), we examined whether any of them

provided superior model performance at predicting CDP expressibility, and found that AUC for

MSA, single, pair, and structure module representations were similar (0.789, 0.781, 0.790, and

0.788 respectively). We then examined the effect of concatenating the four representations and

observed an improvement in model performance (AUC = 0.801) (Fig. 1C).

<u>Fig 1. Random forest classifiers trained on SeqVec, proteInfer, and AlphaFold2 protein</u>
<u>representations predict recombinant CDP expressibility.</u>
Random forest classifiers were trained using protein representations generated by primary
sequences of CDPs and performance was estimated by 10-fold cross validation. AUC was used
as the performance metric. **(A)** An example showing receiver operating characteristic curves
generated using the single representation from AlphaFold2 neural embeddings. **(B)** The
performance of protein representations generated by SeqVec, proteInfer, and AlphaFold2.
AlphaFold2 protein representations had the highest predictive performance. **(C)** The predictive
performance of neural embeddings from the four representations generated by AlphaFold2 and
a concatenated combined representation. The combined representation produced classifiers
with the best performance at predicting recombinant CDP expressibility. Error bars represent
standard deviation of the mean value.

Generating a state-of-the-art classifier of recombinant non-knottin and knottin CDP expressibility

Having determined that combined AlphaFold2 protein representations provided the best

performance for predicting recombinant CDP expressibility, we then sought to optimize the

classification model. To accomplish this, we first examined whether the classifier would benefit

from partitioning the data into non-knottin CDPs and knottin CDPs. Intriguingly, when the

dataset was subset to knottins, the classifier performance was enhanced, although such an

improvement was not observed when the dataset was subset to non-knottin CDPs (Fig. 2A).

To further improve classifier performance, a time series classification method was utilized. The

neural embeddings generated by the models used in this study produce high dimensional

feature vectors describing each residue in the peptide. The features were initially averaged to

compress the sequence of amino acid residue features into a summary representation of a fixed

size per peptide that was then used to train the random forest classifiers. While averaging

preserves information from each residue, information such as order and sequential relationships

are lost. Therefore, we hypothesized that by implementing a large number of random

convolutional kernels, relevant features for expressibility may be captured. As a result, we

applied a time series transformation technique that utilizes random convolutional kernels,

named ROCKET [22], to the combined AlphaFold2 representations. Before implementing

ROCKET, classifier performance (AUC) was estimated to be 0.827 ± 0.065 (Fig. 2A). Using the

same cross validation folds, we found that employing ROCKET improved classifier performance

for knottins and resulted in an estimated AUC of 0.865 ± 0.043 (Fig. 2B). Curiously, while the

prediction of knottin expressibility was improved by the use of ROCKET, it appeared to have no

impact on the prediction of non-knottin expressibility (Fig. 2B).

The proteInfer, individual AlphaFold2, combined AlphaFold2, and ROCKET models were

compared by permutation test. Model performance was ranked according to AUC. For

predicting the expressibility of non-knottin CDPs, the top ranked model was the combined

AlphaFold2 representation without ROCKET time series transformation, though it was not

ranked significantly better than the MSA, pair or ROCKET models (Figure 2C). On the other

hand, for predicting the expressibility of knottin CDPs, the top ranked model was the combined

AlphaFold2 representation with ROCKET time series transformation, which ranked significantly

better than all of the other models (Figure 2D).

The finalized model, CysPresso, which utilizes partitioning and random convolutional kernel

transformation, was evaluated by leave-one-out-cross-validation. Using this approach, classifier

AUC was determined to be 0.798 for non-knottin CDPs (Figure 2E, Table 2) and 0.852 for

knottins (Figure 2F, Table 2). A diagram of the machine learning model architecture is shown in

Figure 3.

<u>Fig 2. Dataset partitioning and time series classification improves prediction of knottin</u>
<u>expressibility.</u>
(A) Splitting the dataset into non-knottin and knottin partitions improves prediction of knottin but
not non-knottin CDP expressibility when using random forest classifiers.
(B) Transforming AlphaFold2 protein representations with ROCKET time-series classification
further improves prediction of knottin but not non-knottin CDP expressibility. Error bars
represent standard deviation of the mean.
(C) Mean AUC rank for various models at predicting non-knottin expressibility (50
permutations). Training random forest algorithms on the combined AlphaFold2 representation
provided the best performance. Ranks that are not significantly different are connected by
horizontal lines.
(D) Mean AUC rank for various models at predicting knottin expressibility (50 permutations).
Utilizing ROCKET on the combined AlphaFold2 representation provided the best performance.
Ranks that are not significantly different are connected by horizontal lines.
(E) Confusion matrix of the final machine learning model for non-knottin CDPs evaluated by
leave-one-out cross validation.
(F) Confusion matrix of the final machine learning model for knottins evaluated by leave-one-out
cross validation.
354
355
356 <u>Table 2. Classifier performance metrics for CysPresso.</u>
357

Measure	Non-knottin CDP model	Knottin model
AUC	0.798	0.852
Sensitivity	0.853	0.764
Specificity	0.584	0.812
Precision	0.743	0.783
Accuracy	0.742	0.789
F1 Score	0.794	0.773

358 The performance of the non-knottin and knottin CysPresso models were evaluated by leave-
359 one-out cross-validation.
360

<u>Fig 3. Machine learning architecture diagram of CysPresso</u>
The primary sequence of the CDP is used to generate MSA, single, pair, and structure module
AlphaFold2 representations. The four representations are concatenated, and a time series
transformation utilizing random convolutional kernels is carried out on the concatenated
representation. The transformed representation is then used to predict expressibility using L2-
regularized logistic regression machine learning models for knottin and non-knottin CDPs.
368

Model interpretability

We then posed the question: Which features are most important for determining expressibility in

non-knottin and knottin CDPs? To answer this, we calculated random forest feature

contributions by SHAP analysis [31]. Surprisingly, this analysis revealed that the region most

important for the prediction of expressibility in non-knottins was near the C-terminus, whereas

amino acid residues closer to the N-terminus were deemed more important for predicting

expressibility in knottins (Fig. 4A). We then examined the relative importance of the different

AlphaFold2 representations in the prediction of expressibility and found that the structure

module representation was most important for predicting non-knottin expressibility, while the

abstract single representation was most important for predicting knottin expressibility (Fig. 4B).

This difference provides a strong rationale for partitioning the dataset into non-knottin and

knottin subgroups for improved model performance.

<u>Fig 4. Features important for predicting expressibility in non-knottins are different from the</u>
<u>features that are important for predicting expressibility in knottin peptides.</u>
This figure shows absolute SHAP values, which illustrate to what degree a feature affects
prediction, calculated for different AlphaFold2 features.
(A) The relative importance of amino acid position for prediction of expressibility in non-knottin
and knottin peptides. In non-knottins, a region near the C-terminus (position 42 to 47) was
identified as playing an important role in determining expressibility. In knottin peptides, the
features at amino acid position 7-9 near the N-terminus were most important for expressibility.
(B) The relative importance of the different AlphaFold2 representations for expressibility
prediction of non-knottin and knottin peptides. For non-knottins, the structure representation
module representation was most important for prediction of expressibility. On the other hand, in
knottin peptides, the abstract single representation was most important for prediction of
expressibility.
397

AlphaFold2 provides a per-residue confidence metric called pLDDT, which estimates how well

the structure prediction should agree with experimentally determined structures. To determine

whether the confidence of the AlphaFold2 structure prediction was associated with prediction

outcome, the average pLDDT in correctly predicted (true positive and true negative) and

incorrectly predicted (false positive and false negative) CDPs were plotted in Figure 5A. The

lack of a difference between the average pLDDT values of CDPs that were correctly and

incorrectly classified suggests that the confidence of the AlphaFold2 structures do not impact

expressibility prediction. This finding is further supported by the fact that the non-knottin CDPs

in this study had a higher average pLDDT than knottins (Figure 5B), despite the non-knottin

model having a lower performance than that of the knottin model.

Fig 5. CysPresso outcomes are not biased by pLDDT, a confidence metric of AlphaFold2
predictions

412
(A) AlphaFold2 average pLDDT values are not significantly different between CDPs that were
correctly predicted as expressible and CDPs that were incorrectly predicted. Mann-Whitney test,
p = 0.512. (B) The average pLDDT values of non-knottin CDPs in the dataset analyzed for this
study are significantly higher than those of knottin CDPs. Mann-Whitney test, p < 0.0001. The
median and interquartile ranges are indicated by the horizontal lines in the violin plots.
Comparison to state-of-the-art models

As far as we know, CysPresso is the first machine learning model that predicts the expressibility

of recombinant proteins in mammalian cells based on primary sequence. Due to the absence of

another model for this classification task, it is challenging to make state-of-the-art comparisons.

Recently, a classification model called UniRep-RF was developed using UniRep protein

representations obtained from primary sequence to predict recombinant protein expression in *B.*

subtilis, where it achieved an AUC of 0.64 [27]. As this model was the closest known

comparable model to CysPresso, we obtained UniRep representations [28] for the dataset

utilized in this study and evaluated the performance of UniRep-RF and CysPresso using leave-

one-out cross-validation (Table 3). Interestingly, UniRep-RF was much better at predicting

expressibility of CDPs than it was at predicting recombinant protein expression in *B. subtilis* and

achieved an AUC of 0.760. By comparison, CysPresso provided better performance at the task

of predicting CDP expressibility from primary sequence and yielded an AUC of 0.816. To test if

CysPresso and UniRep-RF were significantly different when evaluated by AUC, we then carried

out a non-parametric permutation test and found that CysPresso significantly outperformed

UniRep-RF at predicting CDP expressibility (p = 0.0059).

Table 3. Comparison of the performance of CysPresso and UniRep-RF at predicting
expressibility of CDPs from primary sequence.
439

Measure	CysPresso	UniRep-RF
AUC	0.816	0.760
Sensitivity	0.818	0.786
Specificity	0.672	0.594
Precision	0.755	0.705
Accuracy	0.753	0.700
F1 Score	0.785	0.743

440 The performance of CysPresso and UniRep-RF [27] were evaluated by leave-one-out cross-
441 validation.
442

Discussion

The expressibility of recombinant peptides in human cells can be predicted from primary

sequences using machine learning methods.

Peptide therapeutics occupy 5% of the global pharmaceutical market, and their approval rate

has steadily increased over the last few decades [32]. Presently, peptide therapeutics face two

major challenges: the poor yield of peptides from traditional solid-phase synthesis [33] and the

intrinsically short plasma half-life of peptides [34]. As a result of recent advances, recombinant

peptide production is now a cost effective, simple, and high-yield production platform for peptide

drugs [35]. Our tool helps predict which peptides are compatible with recombinant expression,

reducing the amount of time-consuming empirical experimentation required to identify

expressible CDPs by allowing laboratory efforts to focus on the candidates most likely to

express. Furthermore, CysPresso may be useful in the identification of CDPs that are

compatible with *in situ* expression technologies such as viral gene therapy and mRNA-based

therapeutics, methods that may extend the *in vivo* activity of peptide therapeutics.

To our knowledge there is currently no other model that predicts the expressibility of CDPs (or

any difficult-to-express proteins) in mammalian cells based on primary sequence. However,

numerous machine learning algorithms have been created for the prediction of heterologous

recombinant protein solubility in bacterial expression systems such as *E. coli*. In *E. coli*,

overexpression of heterologous proteins can result in protein aggregates and the formation of

insoluble inclusion bodies–a phenomenon thought to be a result of misfolding or the formation of

intermolecular oligomers. These same factors likely lead to unsuccessful recombinant CDPs

expression in mammalian cells. Therefore, prediction of protein solubility in E. coli and

predicting CDP expression in mammalian cells is not a dissimilar problem. Recent examples for

sequence-based prediction of protein solubility include SoluProt which achieves an AUC of 0.62

[36], SoDoPe which achieves an AUC of 0.71 [37], SKADE which achieves an AUC of 0.82 [38],

and DSResSol which achieves an AUC of 0.87 [39]. Our model achieved an AUC of 0.82, which

provides comparable performance and it was significantly better at predicting CDP expressibility

than UniRep-RF, a *B. subtilis* specific machine learning model for predicting protein expression

[27].

Deep learning protein representations retain information that is complementary to prediction

tasks beyond protein structure.

In this study, we tested various protein representations and evaluated their usefulness at

predicting expressibility of difficult to express peptides. We began our investigation by utilizing

neural embeddings from protein language models such as SeqVec and ProteInfer, which are

based on statistical models and generated by training large scale sequence datasets. We also

utilized AlphaFold2 neural embeddings, which include several representations based on

evolutionary, positional, structural, and simulated relationships. AlphaFold2 protein

representations provided better predictive performance than the purely language based models.

This may be due to the structural information contained within AlphaFold2 representations, as

the expressibility of a peptide is determined not only by its amino acid sequence but also by its

tertiary and quaternary structure.

While AlphaFold2 accurately predicts protein structures, the suitability of AlphaFold2 neural

embeddings for use in general functional prediction tasks is not well established. We find that

AlphaFold2 neural embeddings are indeed suitable for general purpose tasks such as the

prediction of expressibility of difficult-to-express peptides such as CDPs. Our results agree with

work from other groups that have shown that AlphaFold2 produces a general-purpose protein

representation that can be used for functional predictions [40]. Though in this study we focused

on the expressibility of CDPs, protein representations can theoretically be generated for any

class of protein or peptide, thus there is no reason why the methods utilized in this study cannot

be generalized to expression datasets of any difficult-to-expression protein. On the same note,

protein representations from deep learning protein models, such as those used in this study and

others such as RoseTTAFold [32], colabfold [41], openFold [33], proteinBERT [34] and ESMfold

[35] have no species bias. Resultantly, there is no reason why the methods in this study cannot

be generalized to the prediction of expressibility in any heterologous expression system.

Different variables determine the expressibility of non-knottin peptides and knottin peptides

Our analysis demonstrated that expressibility is determined by different protein features in

knottin and non-knottin CDPs. Knottins are characterized by six cysteine residues making up

three interwoven disulfide bridges that form a unique pseudoknot with conserved secondary

structure [3]. It is hypothesized that during folding, the C-terminus of the peptide first forms a

conserved ⍺-hairpin, allowing disulfide bridges to form between cysteines II–V and III–VI.

Folding is then completed by the N-terminal loop swinging around to create the cysteine I–IV

disulfide bridge [42]. Since our data suggests that the N-terminal region is important for the

prediction of expressibility, it is likely that the success of the final N-terminal folding step is

required for successful expression of knottin peptides.

Our results also demonstrated that the various AlphaFold2 representations hold differential

predictive value. For non-knottins, the structure representation was most important for predicting

expressibility, while for knottins, the abstract single representation was most predictive. We

speculate that this may be due to the fact that the non-knottin CDPs in this study was a

heterogeneous group that included cyclotides, hitchins, growth factor cysteine knots and non-

knotted CDPs [17], while the knottin peptides in this study were a homogenous group that all

had the conserved inhibitor cysteine knot structure characteristic of knottins. As a result,

structurally diverse non-knottin CDPs benefited more from structural information, whereas

structural information was less important at providing features that determine expressibility in

the structurally related knottins group. In this case, primary sequence relationships captured in

the abstract single representation provided more meaningful predictive value.

Random convolutional kernel time series classification improves protein representation feature

performance for prediction of knottin expressibility

The goal of time series classification is to predict the class that a new sample belongs to using

labeled ordered training data. While the data used with time series algorithms are typically

sequences of discrete-time data, any data registered with some notion of ordering is compatible

[43]. As AlphaFold2 and many other protein models such as SeqVec and ProteInfer produce

such ordered data (ie. a neural embedding for each amino acid residue), we were able to cast

our classification problem as a time series classification problem. We find that applying a time

series transformation such as ROCKET improves the capture of ordered features relevant for

the prediction of peptide expressibility when examining knottin peptides. Importantly, ROCKET

employs random convolutional kernels, which have been shown to be a simple and cost efficient

method to capture many features which previously required their own specialized techniques

[44]. Thus far, almost all studies that use protein representations for supervised machine

learning tasks generate embeddings by taking the average of the pool of activations from the

last hidden layer of the model [45]. Our results suggest that the use of time series

transformations, in particular–the use of convolutional kernels–provides a better summary of the

protein representation by capturing important features that are lost by averaging.

Study limitations

We analyzed a previously published dataset [17] that examined the expressibility of CDPs in

HEK293 cells using a high-throughput Daedalus lentivirus transduction system. In that study,

CDPs were considered successfully expressed if the peptide product was free of heterogeneity,

as determined by RPC. It is important to note that, while RPC is a rigorous tool for ensuring

chemical and conformational homogeneity, it is possible that the expressed products lack

biological activity or that heterogeneous products deemed unexpressible may in fact be

biologically functional. Additionally, the Daedalus lentiviral expression system that generated the

dataset requires proteolytic cleavage to free the peptide from a mouse Igκ peptide sequence.

Thus, it is possible our results are not generalizable to peptides expressed by other methods.

It is also important to note that the dataset used in this study is likely to be affected by selection

biases and coverage bias. For example, our dataset only included CDPs that were between 30

and 50 amino acids long. According to a 2017 analysis [17] of CDPs listed on the RSCB Protein

Data Bank [46], non-knottin CDPs ranged from 15 to 81 amino acids in length, and knottin

CDPs ranged from 20 to 70 amino acids in length. Resultantly, it is possible that CysPresso

may not generalize to CDPs outside of the 30 to 50 amino acid range. Future work should aim

to evaluate CysPresso with randomly sampled real-world data.

Conclusion

In this work, we used supervised machine learning to develop a tool to predict whether a CDP is

expressible in a mammalian cell expression system. To accomplish this, we tested the

performance of various protein representations and found that AlphaFold2 representations,

which are typically used to generate predictions of protein structures, can also be used to

predict expressibility. By combining the four AlphaFold2 representations, partitioning the model,

and utilizing time series transformation and random convolutional kernels, we further improved

the performance of the expressibility classifier to yield an approach with state-of-the-art

performance for predicting CDP expressibility in mammalian cells.

Supplemental Material

580
581 Supplemental Table 1: The CDP expressibility dataset utilized in this study.
582

583
Declarations

Ethics approval and consent to participate

Not applicable. This study does not involve human subjects, vertebrate animals, or human

embryonic stem cells.

Consent for publication

Not applicable. This study does not involve human subjects.

Availability of data and materials

The datasets generated and/or analyzed during the current study are available in the Hugging

Face Repository, https://huggingface.co/datasets/TonyKYLim/CysPresso/tree/main. The code

for CysPresso is available as a Colaboratory notebook at https://github.com/Zebreu/cyspresso.

Competing interests

The authors have no relevant financial or non-financial interests to disclose.

Funding

The authors received no financial support for the research, authorship, and/or publication of this

article.

Author Contributions

Sébastien Ouellet: Conceptualization, Methodology, Software, Validation, Formal analysis,

Investigation, Data curation, Writing - Original Draft, Writing - Review & Editing, Visualization.

Larissa Ferguson: Conceptualization, Software, Writing - Review & Editing, Visualization.

Angus Z. Lau: Investigation, Resources. **Tony K.Y. Lim:** Conceptualization, Methodology,

Validation, Formal analysis, Investigation, Writing - Original Draft, Writing - Review & Editing,

Visualization.

Acknowledgements

Not applicable.

Affiliations

Sébastien Ouellet and Tony K.Y. Lim performed this work as unaffiliated researchers. Tony K.Y.

Lim's current affiliation is the Department of Pharmacology, University of Cambridge.

References

1. Northfield SE, Wang CK, Schroeder CI, Durek T, Kan M-W, Swedberg JE, et al. Disulfide-rich
macrocyclic peptides as templates in drug design. Eur J Med Chem. 2014;77:248–57.
2. Wang CK, Craik DJ. Designing macrocyclic disulfide-rich peptides for biotechnological
applications. Nat Chem Biol. 2018;14:417–27.
3. Gracy J, Chiche L. Structure and Modeling of Knottins, a Promising Molecular Scaffold for
Drug Discovery. Current Pharmaceutical Design. 2011;17:4337–50.
4. Molesini B, Treggiari D, Dalbeni A, Minuz P, Pandolfini T. Plant cystine-knot peptides:
pharmacological perspectives. British Journal of Clinical Pharmacology. 2017;83:63–70.
5. Dongol Y, Cardoso FC, Lewis RJ. Spider Knottin Pharmacology at Voltage-Gated Sodium
Channels and Their Potential to Modulate Pain Pathways. Toxins (Basel). 2019;11:E626.
6. Scott A, Weldon S, Taggart CC. SLPI and elafin: multifunctional antiproteases of the WFDC
family. Biochem Soc Trans. 2011;39:1437–40.
7. Muratspahić E, Koehbach J, Gruber CW, Craik DJ. Harnessing cyclotides to design and
develop novel peptide GPCR ligands. RSC Chem Biol. 2020;1:177–91.
8. Gracy J, Le-Nguyen D, Gelly J-C, Kaas Q, Heitz A, Chiche L. KNOTTIN: the knottin or
inhibitor cystine knot scaffold in 2007. Nucleic Acids Res. 2008.
https://doi.org/10.1093/nar/gkm939.
9. Postic G, Gracy J, Périn C, Chiche L, Gelly J-C. KNOTTIN: the database of inhibitor cystine
knot scaffold after 10 years, toward a systematic structure modeling. Nucleic Acids Res.
2018;46 Database issue:D454–8.
10. Kintzing JR, Cochran JR. Engineered knottin peptides as diagnostics, therapeutics, and

drug delivery vehicles. Current Opinion in Chemical Biology. 2016;34:143–50.
11. Russo A, Aiello C, Grieco P, Marasco D. Targeting "Undruggable" Proteins: Design of
Synthetic Cyclopeptides. Current Medicinal Chemistry. 2016;23:748–62.
12. Visintin M, Melchionna T, Cannistraci I, Cattaneo A. In vivo selection of intrabodies
specifically targeting protein–protein interactions: A general platform for an "undruggable" class
of disease targets. Journal of Biotechnology. 2008;135:1–15.
13. de Araujo CB, Heimann AS, Remer RA, Russo LC, Colquhoun A, Forti FL, et al. Intracellular
Peptides in Cell Biology and Pharmacology. Biomolecules. 2019;9:150.
14. Reinwarth M, Glotzbach B, Tomaszowski M, Fabritz S, Avrutina O, Kolmar H. Oxidative
Folding of Peptides with Cystine-Knot Architectures: Kinetic Studies and Optimization of Folding
Conditions. ChemBioChem. 2013;14:137–46.
15. Reinwarth M, Nasu D, Kolmar H, Avrutina O. Chemical Synthesis, Backbone Cyclization
and Oxidative Folding of Cystine-knot Peptides — Promising Scaffolds for Applications in Drug
Design. Molecules. 2012;17:12533–52.
16. Rivera-de-Torre E, Rimbault C, Jenkins TP, Sørensen CV, Damsbo A, Saez NJ, et al.
Strategies for Heterologous Expression, Synthesis, and Purification of Animal Venom Toxins.
Front Bioeng Biotechnol. 2022;9:811905.
17. Correnti CE, Gewe MM, Mehlin C, Bandaranayake AD, Johnsen WA, Rupert PB, et al.
Screening, large-scale production and structure-based classification of cystine-dense peptides.
Nat Struct Mol Biol. 2018;25:270–8.
18. Crook ZR, Sevilla GP, Friend D, Brusniak M-Y, Bandaranayake AD, Clarke M, et al.
Mammalian display screening of diverse cystine-dense peptides for difficult to drug targets. Nat
Commun. 2017;8:2244.
19. Heinzinger M, Elnaggar A, Wang Y, Dallago C, Nechaev D, Matthes F, et al. Modeling
aspects of the language of life through transfer-learning protein sequences. BMC
Bioinformatics. 2019;20:723.
20. Sanderson T, Bileschi ML, Belanger D, Colwell LJ. ProteInfer: deep networks for protein
functional inference. 2021;:2021.09.20.461077.
21. Jumper J, Evans R, Pritzel A, Green T, Figurnov M, Ronneberger O, et al. Highly accurate
protein structure prediction with AlphaFold. Nature. 2021;596:583–9.
22. Dempster A, Petitjean F, Webb GI. ROCKET: exceptionally fast and accurate time series
classification using random convolutional kernels. Data Min Knowl Disc. 2020;34:1454–95.
23. The UniProt Consortium. UniProt: the universal protein knowledgebase in 2021. Nucleic
Acids Research. 2021;49:D480–9.
24. Sanderson T, Bileschi ML, Belanger D, Colwell LJ. ProteInfer, deep neural networks for
protein functional inference. eLife. 2023;12:e80942.
25. Breiman L. Random Forests. Machine Learning. 2001;45:5–32.
26. Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn:
Machine Learning in Python. Journal of Machine Learning Research. 2011;12:2825–30.
27. Martiny H-M, Armenteros JJA, Johansen AR, Salomon J, Nielsen H. Deep protein
representations enable recombinant protein expression prediction. Computational Biology and
Chemistry. 2021;95:107596.
28. Alley EC, Khimulya G, Biswas S, AlQuraishi M, Church GM. Unified rational protein
engineering with sequence-based deep representation learning. Nat Methods. 2019;16:1315–
22.
29. Goodfellow I, Bengio Y, Courville A. Deep Learning. MIT Press; 2016.
30. Demšar J. Statistical Comparisons of Classifiers over Multiple Data Sets. J Mach Learn Res.
2006;7:1–30.
31. Lundberg SM, Lee S-I. A Unified Approach to Interpreting Model Predictions. In: Advances
in Neural Information Processing Systems. Curran Associates, Inc.; 2017.
32. Muttenthaler M, King GF, Adams DJ, Alewood PF. Trends in peptide drug discovery. Nat

Rev Drug Discov. 2021;20:309–25.

33. Isidro-Llobet A, Kenworthy MN, Mukherjee S, Kopach ME, Wegner K, Gallou F, et al.
Sustainability Challenges in Peptide Synthesis and Purification: From R&D to Production. J Org
Chem. 2019;84:4615–28.

34. Kontermann RE. Strategies for extended serum half-life of protein therapeutics. Curr Opin
Biotechnol. 2011;22:868–76.

35. Ajingi YS, Rukying N, Aroonsri A, Jongruja N. Recombinant Active Peptides and their
Therapeutic Functions. Current Pharmaceutical Biotechnology. 2022;23:645–63.

36. Hon J, Marusiak M, Martinek T, Kunka A, Zendulka J, Bednar D, et al. SoluProt: prediction
of soluble protein expression in Escherichia coli. Bioinformatics. 2021;37:23–8.

37. Bhandari BK, Gardner PP, Lim CS. Solubility-Weighted Index: fast and accurate prediction
of protein solubility. Bioinformatics. 2020;36:4691–8.

38. Raimondi D, Orlando G, Fariselli P, Moreau Y. Insight into the protein solubility driving
forces with neural attention. PLoS Comput Biol. 2020;16:e1007722.

39. Madani M, Lin K, Tarakanova A. DSResSol: A Sequence-Based Solubility Predictor Created
with Dilated Squeeze Excitation Residual Networks. IJMS. 2021;22:13555.

40. Hu M, Yuan F, Yang KK, Ju F, Su J, Wang H, et al. Exploring evolution-based & -free
protein language models as protein function predictors. 2022.

41. Mirdita M, Schütze K, Moriwaki Y, Heo L, Ovchinnikov S, Steinegger M. ColabFold: making
protein folding accessible to all. Nat Methods. 2022;19:679–82.

42. McCarthy S, Robinson J, Thalassinos K, Tabor AB. A Chemical Biology Approach to
Probing the Folding Pathways of the Inhibitory Cystine Knot (ICK) Peptide ProTx-II. Frontiers in
Chemistry. 2020;8:228.

43. Gamboa JCB. Deep Learning for Time-Series Analysis. 2017.

44. Wang Z, Yan W, Oates T. Time Series Classification from Scratch with Deep Neural
Networks: A Strong Baseline. 2016.

45. Yang KK, Wu Z, Bedbrook CN, Arnold FH. Learned protein embeddings for machine
learning. Bioinformatics. 2018;34:2642–8.

46. Burley SK, Bhikadiya C, Bi C, Bittrich S, Chen L, Crichlow GV, et al. RCSB Protein Data
Bank: powerful new tools for exploring 3D structures of biological macromolecules for basic and
applied research and education in fundamental biology, biomedicine, biotechnology,
bioengineering and energy sciences. Nucleic Acids Research. 2021;49:D437–51.

A

Non-knottins

Knottins

Absolute SHAP value (normalized)

B

| MSA | Single | Pair | Structure |

Non-knottins

Knottins

Absolute SHAP value