Meta-analysis of (single-cell method) benchmarks reveals the need for extensibility and interoperability

Anthony Sonrel[1,2,*], Almut Luetge[1,2,*], Charlotte Soneson[2,3,*], Izaskun Mallona[1,2,*], Pierre-Luc Germain[1,2,4,*], Sergey Knyazev[5,6], Jeroen Gilis[7,8,9], Reto Gerber[1,2], Ruth Seurinck[7,8], Dominique Paul[1], Emanuel Sonder[1,2,4], Helena L. Crowell[1,2], Imran Fanaswala[1,2], Ahmad Al-Ajami[1,2], Elyas Heidari[1,2], Stephan Schmeing[1,2], Stefan Milosavljevic[1,2,10], Yvan Saeys[7,8], Serghei Mangul[6], Mark D. Robinson[1,2,#]

[1]Department of Molecular Life Sciences, University of Zurich, Zurich, Switzerland
[2]SIB Swiss Institute of Bioinformatics, Switzerland
[3]Friedrich Miescher Institute for Biomedical Research, Basel, Switzerland
[4]D-HEST Institute for Neuroscience, ETH Zürich, Zürich, Switzerland
[5]Department of Pathology and Laboratory Medicine, David Geffen School of Medicine, University of California, Los Angeles, Los Angeles, CA, USA
[6]Department of Clinical Pharmacy, School of Pharmacy, University of Southern California, Los Angeles, CA, USA
[7]Department of Applied Mathematics, Computer Science & Statistics, Ghent University, Belgium.
[8]Data Mining and Modeling for Biomedicine, VIB Center for Inflammation Research, Ghent, Belgium
[9]Bioinformatics Institute Ghent, Ghent University, Ghent, Belgium
[10]Department of Evolutionary Biology and Environmental Studies, University of Zurich, Zurich, Switzerland

* these authors contributed equally and reserve the right to list themselves as first author.
# corresponding author: mark.robinson@mls.uzh.ch

Abstract

Computational methods represent the lifeblood of modern molecular biology. Benchmarking is important for all methods, but with a focus here on computational methods, benchmarking is critical to dissect important steps of analysis pipelines, formally assess performance across common situations as well as edge cases, and ultimately guide users on what tools to use. Benchmarking can also be important for community building and advancing methods in a principled way. We conducted a meta-analysis of recent single-cell benchmarks to summarize the scope, extensibility, neutrality, as well as technical features and whether best practices in open data and reproducible research were followed. The results highlight that while benchmarks often make code available and are in principle reproducible, they remain difficult to extend, for example, as new methods and new ways to assess methods emerge. In addition, embracing containerization and workflow systems would enhance reusability of intermediate benchmarking results, thus also driving wider adoption.

Introduction

Given the rapid development and uptake of new technologies in biology (e.g., high-throughput DNA sequencing, single-cell assays and imaging technologies), methodologists are presented with nearly unlimited opportunities to apply or develop computational tools to process, model, and interpret large-scale datasets across a wide range of applications. Unsurprisingly, the data explosion (Schatz 2015; Svensson, da Veiga Beltrame, and Pachter 2020) is mirrored by a massive increase in the number of computational methods; for example, at time of writing, 1,318 are listed in a database of tools for the analysis of single-cell RNA-seq data (Zappia, Phipson, and Oshlack 2018; Zappia and Theis 2021) and more than 370 tools are listed for the analysis of spatial omics data (Moses and Pachter 2022). This imposes challenges for determining what tools to use for discovery. In particular, researchers often need to convince themselves that they develop or use performant tools in their research, and a typical approach is via formal benchmarks. Benchmarks can be decomposed into five steps: 1) formulating a computational task (or subtask) that will be investigated (e.g., calling differentially expressed genes); 2) collecting reference datasets by either generating (realistic) synthetic datasets or using ground truth derived from experimental data; 3) defining performance criteria (e.g., sensitivity, specificity); 4) evaluating a representative set of methods via a set of performance criteria across multiple reference datasets; and, 5) formulating conclusions and guidelines.

In terms of developing and disseminating new methods, the minimum requirement of quality is usually that the new approach provides a benefit against existing approaches. However, the current standard allows developers to be their own "judge, jury and executioner" (Norel, Rice, and Stolovitzky 2011), giving them some freedom to choose the settings and the evaluations used in the benchmark. There is a notable tension here, since methodologists that want to develop high-quality novel approaches may also be under pressure to publish (Grimes, Bauch, and Ioannidis 2018). One can argue that the risk of biases and over-optimistic evaluations of new approaches is minimised by

the standard scientific review process, however this is also known to have its challenges (Tennant and Ross-Hellauer 2020). Ultimately, it is almost a foregone conclusion that a newly proposed method will report comparatively strong performance (Buchka et al. 2021; Norel, Rice, and Stolovitzky 2011). Thus, claims from individual method development papers need to be scrutinized, preferably from a neutral (i.e., independent) standpoint (Mangul et al. 2019; Weber et al. 2019). Neutral benchmarking appears to be a popular approach, since over 60 benchmarks have been conducted for single-cell data analysis alone (see below and Additional file 1). But even if done neutrally, the community may still want a mechanism to challenge, extend or personalize the assessments (e.g., update/add reference datasets, run methods with alternative parameters, use different metrics, rank methods differently).

Neutral benchmarking shares common ground with community "challenges" for consolidating the state-of-the-art. In some subfields of computational biology, there is a long history of such challenges, such as the biannual CASP (Critical Assessment of Structure Prediction) (Kryshtafovych et al. 2021) and DREAM (Dialogue on Reverse Engineering Assessment and Methods) challenges (Stolovitzky, Monroe, and Califano 2007), where participants are invited to propose solutions to a predefined problem. The challenge model is growing in success, including leaderboards that give real-time feedback, but these can sometimes reinforce a narrow view of performance (e.g., a single measure of performance on a single dataset ("Open Problems - Multimodal Single-Cell Integration" n.d.). In addition, for a challenge to be conceptualised in the first place, the community needs to formalize and frame existing problems, have access to suitable reference datasets, gather indications that the challenge can be solved and only then assess if current technologies and methods would be able to solve it. This necessarily requires some common ground and knowledge in the field, which is often gained by neutral benchmarking studies. Although community challenges engage communities and innovation, they are typically time-gated in their scope, whereas one could also imagine benchmarking as a continuous process where challenges are integrated into the subfield's trajectory. Initiatives in this direction include OpenEBench (Capella-Gutierrez et al. 2017), which provides a computing platform and infrastructure for benchmarking events, and 'Open Problems in Single Cell Analysis', which is focused

on formalizing (single-cell data analysis) tasks to foster innovation in method development while providing infrastructure and datasets such that new methods can be tested (Lance et al. 2022; Luecken, Burkhardt, et al. 2022).

There are several obstacles related to running and using the results of benchmarks. In fast-moving subfields, benchmark results become rapidly out-of-date and in some cases, competing methods never get directly compared because they are developed simultaneously. Current benchmarks are always a snapshot in time, while tool development is continuous. There are common components of most benchmarks, such as reference datasets, a set of methods and metrics to score their performance, but there are typically no pervasive standards for the system or strategy of benchmarking in computational biology, except for those predefined by challenges. This lack of standards can, for example, lead to different rankings of the same methods for the same task (Luecken, Büttner, et al. 2022; Chazarra-Gil et al. 2021; Tran et al. 2020). Similarly, shortcomings of existing performance metrics may be discovered subsequent to earlier benchmarks (Lütge et al. 2021). Another area in which benchmarks underdeliver is the interpretation of performance results. Benchmark authors (or challenge organizers) generally get to make all the decisions about how the performance evaluation is conducted (e.g., how a ranking is determined, given multiple criteria).

Altogether, it remains an open question whether computational biology has reached a benchmarking optimum, achieving fair comparisons in a timely, independent and continuous manner, while also keeping the barrier low enough for colleagues, including those in adjacent fields, to participate. In this report, we review current benchmarking practices in a subfield of genome biology (single-cell data analysis) to get an understanding of where the current state-of-the-art is and based on our findings, we postulate what elements of benchmarking would be considered desirable for the future.

State-of-the-art in benchmarking

To understand the current state of practice in benchmarking studies in computational biology, we crowdsourced a list of single-cell method benchmarks (studies were selected by the project team from the period of 2018-2021 as exhaustively as possible

on the basis of having at least a preprint posted, and involving the comparison of computational methods for some form of single-cell data, and not a primary method publication; see Additional file 1 for the list of studies). We then designed a questionnaire to query various attributes of a benchmark study (see Additional file 2), and crowdsourced the review of these benchmarks. We focused on single-cell methods because it is an active area of methodological research, with an acute method explosion (Zappia, Phipson, and Oshlack 2018; Zappia and Theis 2021), and a large number of benchmarks have been conducted. The list of questions asked for each benchmark includes both factual (e.g., "Whether synthetic data is available") and opinion (e.g., "Degree to which authors are neutral") assessments. Overall, we queried the scope, extensibility, neutrality, open science and technical features of each benchmark. We required that at least two reviewers answer the questionnaire for each benchmark and in the case of large discrepancies between responses (disagreement in a factual question or large difference in opinion), results were consolidated manually by a third reviewer (see Additional file 3). Questions were organized into two topics: 1) overall design of the benchmark; 2) code and data availability and technical aspects.

Overall design of benchmarks

The overall design of the 62 surveyed single-cell benchmarks, including the number of datasets, methods or criteria used for the comparison or the neutrality of the authors, were assessed. The number of benchmark datasets varied greatly, with 2 benchmarks using only 1 dataset and 1 benchmark using thousands of simulated datasets (median = 8). Likewise, the number of methods evaluated varied from 2 to 88 (median = 9) for the chosen task. Finally, the number of evaluation criteria, defined here as numerical metrics to compare method results against a ground truth, varied from 1 to 18 (median = 4), showing that current benchmarks tend to include more methods and datasets than evaluation criteria (Figure 1A). The range of analysis tasks covered by the benchmarks mirrors quite well the range of tools available (Zappia, Phipson, and Oshlack 2018; Zappia and Theis 2021). A notable exception is the category of visualisation tasks, accounting for 40% of the available tools but formally benchmarked only once (Figure 1B). 72% of the manuscripts were first released as preprints and 66% tested only

default parameters (Figure 1C). We also enquired about the neutrality of the authors, defined as whether the authors of the benchmark were involved in one or several of the methods evaluated. For more than 60% of the benchmarks, the authors were completely independent of the evaluated methods (Figure 1D); neutrality is a desired attribute, although not absolutely required. More than 75% of benchmarks also assessed secondary measures (Supplementary Figure 1), such as runtime, memory usage and scalability.

Figure 1. **Overall design of 62 single-cell method benchmarks**. Overview of crowdsourced meta-analysis across surveyed benchmarks. A) numbers of entities (datasets, methods, metrics) present in each benchmark (each dot is a benchmark). Jitter is added to the X-axis; B) data analysis tasks; C) percentages of benchmarks that were first posted as preprint or whether benchmarks explored parameter space beyond default settings; D) reviewer's opinions on the neutrality (whether the benchmark authors were involved in methods evaluated). Jitter is added to the X-axis and Y-axis of the scores.

Code / data availability, reproducibility and technical aspects

Also important for the uptake of benchmarking results is the open science and reproducibility practices of the studies. Thus, the second group of questions related to the availability of data, code and results as well as technical aspects. Figure 2A gives an overview of the availability of the different levels of data for benchmarking studies, highlighting that input (often ground-truth-including) data is frequently available (97% of studies). However, intermediate results, including outputs of methods run on datasets and performance results were only sparsely available at 19% and 29%, respectively. For studies that generated simulated data, less than half (19/46 articles) made their synthetic data available. Only 10% of benchmarks provided performance results in an explorable format. On the technical side, most benchmarks reported software versions of the methods being evaluated (68%), although provenance tracking (tracking of inputs, outputs, parameters, software versions, etc.) was not explicitly used. Another aspect of reproducible practice is related to workflow tools that are used to orchestrate the datasets through methods and metrics. Although their use in computational biology is increasing (Perkel 2019), we observed that less than 25% of the surveyed benchmarks used any form of them (see Figure 2B). In a similar vein, containerization of software environments is quite mature in computational biology (Gruening et al. 2018), but is rarely utilized in benchmarking (8% of studies). Concerning the methods that are compared, R and Python remain the dominant programming languages for single-cell methods, mirroring the summaries in the scrna-tools database (Zappia and Theis 2021); see also Supplementary Figure 1.

We next scored the *degree* to which code is available on a scale of 1 to 5 (Figure 2C) where 1 means 'not at all' and 5 means 'completely'. For over 75% of the benchmarks, code was fully or partially available, such as in a GitHub repository, although there are clearly different levels of completeness and description. We also gathered opinions on how extensible the available code is (e.g., how easy it is to incorporate an additional dataset, method or evaluation criterion; see Figure 2C); amongst the 47 studies sharing code, only two studies received a high score for extensibility.

Explicit code licensing is somewhat sporadic for benchmark studies (Figure 2D); of the 47 studies that made code available, 19 (40%) did not specify a licence. This can become an important consideration when re-using (public but licensed) code for building data analysis pipelines or extending benchmarks. Of those benchmarks that specified a licence, the free software MIT and GPLv3 appeared to be the dominant ones.

Taken together, our meta-analysis shows that most benchmarks results are at least in principle reproducible, since code and data are shared. However, extending or updating benchmarks remains challenging because setting up software environments locally is challenging and intermediate results are not available; by and large, a significant amount of redundant work would be required to reestablish or extend the vast majority of surveyed benchmarks.

Figure 2. **Code / data availability, reproducibility and technical aspects of 62 single-cell method benchmarks**. A) Each column of the heatmap represents a benchmark study and each row represents a factual question; responses are represented by colours (*Yes*: blue; *Partially*: orange; *Not Applicable*: white; *No*: red). *Not Applicable* corresponds to benchmarks that did not use simulated data (*synthetic data is available* row) and to a benchmark that

evaluated secondary measures only (*performance results available* row); B) type of workflow system used (benchmarks with no workflow used or no code available are represented in red, otherwise grey); C) reviewer's opinions on the availability and extensibility of benchmarking code; D) licence specification across benchmarking studies (benchmarks without licences or no code available are represented in red, otherwise grey).

The future of benchmarking

Benchmarking of omics tools has evolved to become standard practice and remains a crucial part of the development cycle of computational methods. However, the current standard of benchmarking still leaves considerable room for improvement. For example, benchmarks can become out-of-date rapidly, especially in fast-moving subfields such as genomic data analysis. A better standard would involve updating and running benchmarking continuously as new methods emerge and importantly, as better metrics become apparent. The computational biology community has for a long time been liberal about making code available (Deshpande et al. 2021), mirroring the genomics community in making data available (Byrd et al. 2020), but the current standard in benchmarking is often not much more than a code dump, i.e., a minimal record of what was done. Ideally, methodologists get access to not only code and input data, but also full software environments as well as modular workflow systems to orchestrate the running of methods on datasets and evaluations of results against a ground truth. Ultimately, many of the components that form a benchmark (datasets, methods, evaluation metrics) could be potentially re-used (e.g., ground truth datasets re-purposed for a different computational task). What is lacking right now is a general interoperability between components. Across current benchmarks, there is (typically) no mechanism to add new methods, datasets, or metrics, which is an important consideration, since we want to update and push the state-of-the-art for developers, researchers and consumers of our methods.

Seamless and eternal extensibility or reproducibility can be challenging to establish and maintain indefinitely, especially for single research groups and because software toolchains used in computational biology are constantly in flux. The complete absence of provenance tracking also highlights that the intermediate results of a benchmark are not currently being directly reused. For example, if a developer wanted to evaluate their method within the context of an existing benchmark, they would only have access to the

bare minimum (usually just the reference datasets and some code); nonetheless, they are expected to re-run all previous methods essentially reconstructing the benchmark from scratch. This signals an opportunity to make intermediate results available in a systematic way, and use provenance tracking more broadly, whereby the results of methods run on datasets are recorded (as well as metric calculations comparing the results to the ground truth), together with the relevant parameters, such that method developers need only to re-execute relevant new components of a workflow. Reusability and extensibility of benchmarks would not only benefit users but also increase the visibility of published benchmarks, not simply a static and dated view of the field. A related point is software environments, since an ongoing challenge in computational biology is to onboard new methods across diverse computing systems, due to possibly different library requirements (e.g., Python version or Bioconductor release) of each software tool. Here, containerization (Gruening et al. 2018) represents a currently untapped opportunity to systematize this for research pipelines as well as benchmarking studies.

Another area where users (data analysts, method developers) could directly interact with the benchmark data products is in the interpretation of performance. With access to the various assessment criteria, ranking strategies could be established that are tailored to specific use cases and experimental settings, instead of that chosen in advance by the benchmarking team.

Despite the considerable time and effort required to set up a serious benchmark (e.g., collecting and standardising datasets with ground truth, installing and onboarding methods, defining and running metrics), it is still most common to build a benchmark from scratch instead of extending existing benchmarks. To put in context, the single-cell community has developed over 80 methods to infer trajectories and over 40 methods to call differentially expressed genes (Zappia and Theis 2021), but there are seemingly few systems to orchestrate (create, extend, and run) neutral benchmarks. The burden of implementing extensible and continuously updated benchmarks does not necessarily need to be on the side of the benchmarker alone, since most benchmarks employ a

similar structure (e.g. datasets, methods, metrics) and could use a general benchmarking orchestration system.

Although here we have focused on stand-alone benchmarks, every method developer is obligated to compare their approach to existing ones and also here a systematic approach has the potential to achieve considerable efficiency. Method developers could use an established (vetted) benchmark to evaluate their method, while introducing considerable time savings, avoiding some of the problems of self assessment (Buchka et al. 2021), and increasing transparency while preserving the value of benchmarks for end users.

Besides having a modern technical implementation to organize benchmarks, it will be important that the community populates the system with high-quality tests of methods and finds strategies to constantly re-monitor the suitability of such tests, in a both systematic and community-informed way. However, several questions remain, such as who is responsible for the cost of computation, how to decide on the composition of high-quality tests of methods, and how to best combine performance metrics to rank methods.

Taken together, to achieve a more transparent and impactful methods assessment ecosystem, we suggest that systematization of benchmarks through containerization, workflow tools and provenance tracking with access to the full results of a benchmark would be required. This echoes a very recent call to evaluate computational methods using a common platform (Czarnewski et al. 2022). Several initiatives are in motion here, such as 'Open Problems in Single-Cell Analysis' and OpenEBench (Lance et al. 2022; Capella-Gutierrez et al. 2017), and other tools may emerge for achieving this desired interoperability. We believe that if benchmark authors and method developers start embracing these tools, future benchmarks will have an enduring impact in guiding computational methods towards a more structured and comprehensive science.

Additional files

Additional file 1 - list of benchmarks (CSV)

Additional file 2 - review form (CSV)

Additional file 3 - consolidated survey answers (TXT)

Code and data availability statement

The code to organize, consolidate, monitor and analyze the benchmark reviews is available from https://github.com/markrobinsonuzh/sc_benchmark_metaanalysis and a snapshot is posted at zenodo (DOI: 10.5281/zenodo.7097767). The additional files mentioned above are available at zenodo (DOI: 10.5281/zenodo.7096030).

Supplementary Figure

Simulator used

What secondary measures were assessed?

For the methods benchmarked, what is/are the primary language/s they are written in?

Supplementary Figure 1. **Auxiliary summaries from the survey responses**. Simulator used, secondary measures assessed, language of tools assessed.

References

Buchka, Stefan, Alexander Hapfelmeier, Paul P. Gardner, Rory Wilson, and Anne-Laure Boulesteix. 2021. "On the Optimistic Performance Evaluation of Newly Introduced Bioinformatic Methods." https://doi.org/10.31222/osf.io/pkqdx.

Byrd, James Brian, Anna C. Greene, Deepashree Venkatesh Prasad, Xiaoqian Jiang, and Casey S. Greene. 2020. "Responsible, Practical Genomic Data Sharing That Accelerates Research." *Nature Reviews. Genetics* 21 (10): 615–29.

Capella-Gutierrez, Salvador, Diana de la Iglesia, Juergen Haas, Analia Lourenco, José María Fernández, Dmitry Repchevsky, Christophe Dessimoz, et al. 2017. "Lessons Learned: Recommendations for Establishing Critical Periodic Scientific Benchmarking." *bioRxiv*. https://doi.org/10.1101/181677.

Chazarra-Gil, Ruben, Stijn van Dongen, Vladimir Yu Kiselev, and Martin Hemberg. 2021. "Flexible Comparison of Batch Correction Methods for Single-Cell RNA-Seq Using BatchBench." *Nucleic Acids Research*, February. https://doi.org/10.1093/nar/gkab004.

Czarnewski, Paulo, Ahmed Mahfouz, Raffaele A. Calogero, Patricia M. Palagi, Laura Portell-Silva, Asier Gonzalez-Uriarte, Charlotte Soneson, et al. 2022. "Community-Driven ELIXIR Activities in Single-Cell Omics." *F1000Research* 11 (869): 869.

Deshpande, Dhrithi, Aditya Sarkar, Ruiwei Guo, Andrew Moore, Nicholas Darci-Maher, and Serghei Mangul. 2021. "A Comprehensive Analysis of Code and Data Availability in Biomedical Research." OSF Preprints. https://doi.org/10.31219/osf.io/uz7m5.

Grimes, David Robert, Chris T. Bauch, and John P. A. Ioannidis. 2018. "Modelling Science Trustworthiness under Publish or Perish Pressure." *Royal Society Open Science* 5 (1): 171511.

Gruening, Bjorn, Olivier Sallou, Pablo Moreno, Felipe da Veiga Leprevost, Hervé Ménager, Dan Søndergaard, Hannes Röst, et al. 2018. "Recommendations for the Packaging and Containerizing of Bioinformatics Software." *F1000Research* 7 (June). https://doi.org/10.12688/f1000research.15140.2.

Kryshtafovych, Andriy, Torsten Schwede, Maya Topf, Krzysztof Fidelis, and John Moult. 2021. "Critical Assessment of Methods of Protein Structure Prediction (CASP)-Round XIV." *Proteins* 89 (12): 1607–17.

Lance, Christopher, Malte D. Luecken, Daniel B. Burkhardt, Robrecht Cannoodt, Pia Rautenstrauch, Anna Laddach, Aidyn Ubingazhibov, et al. 2022. "Multimodal Single Cell Data Integration Challenge: Results and Lessons Learned." *bioRxiv*. https://doi.org/10.1101/2022.04.11.487796.

Luecken, Malte D., Daniel Bernard Burkhardt, Robrecht Cannoodt, Christopher Lance, Aditi Agrawal, Hananeh Aliee, Ann T. Chen, et al. 2022. "A Sandbox for Prediction and Integration of DNA, RNA, and Proteins in Single Cells." https://openreview.net/pdf?id=gN35BGa1Rt.

Luecken, Malte D., M. Büttner, K. Chaichoompu, A. Danese, M. Interlandi, M. F. Mueller, D. C. Strobl, et al. 2022. "Benchmarking Atlas-Level Data Integration in Single-Cell Genomics." *Nature Methods* 19 (1): 41–50.

Lütge, Almut, Joanna Zyprych-Walczak, Urszula Brykczynska Kunzmann, Helena L. Crowell, Daniela Calini, Dheeraj Malhotra, Charlotte Soneson, and Mark D. Robinson. 2021. "CellMixS: Quantifying and Visualizing Batch Effects in Single-Cell RNA-Seq Data." *Life Science Alliance* 4 (6). https://doi.org/10.26508/lsa.202001004.

Mangul, Serghei, Lana S. Martin, Brian L. Hill, Angela Ka-Mei Lam, Margaret G. Distler, Alex Zelikovsky, Eleazar Eskin, and Jonathan Flint. 2019. "Systematic Benchmarking of Omics Computational Tools." *Nature Communications* 10 (1): 1393.

Moses, Lambda, and Lior Pachter. 2022. "Museum of Spatial Transcriptomics." *Nature Methods* 19 (5): 534–46.

Norel, Raquel, John Jeremy Rice, and Gustavo Stolovitzky. 2011. "The Self-Assessment Trap: Can We All Be Better than Average?" *Molecular Systems Biology* 7 (October): 537.

"Open Problems - Multimodal Single-Cell Integration." n.d. Accessed August 26, 2022. https://www.kaggle.com/competitions/open-problems-multimodal/leaderboard.

Perkel, Jeffrey M. 2019. "Workflow Systems Turn Raw Data into Scientific Knowledge." *Nature* 573 (7772): 149–50.

Schatz, Michael C. 2015. "Biological Data Sciences in Genome Research." *Genome Research* 25 (10): 1417–22.

Stolovitzky, Gustavo, Don Monroe, and Andrea Califano. 2007. "Dialogue on Reverse-Engineering

Assessment and Methods: The DREAM of High-Throughput Pathway Inference." *Annals of the New York Academy of Sciences* 1115 (December): 1–22.

Svensson, Valentine, Eduardo da Veiga Beltrame, and Lior Pachter. 2020. "A Curated Database Reveals Trends in Single-Cell Transcriptomics." *Database: The Journal of Biological Databases and Curation* 2020 (November). https://doi.org/10.1093/database/baaa073.

Tennant, Jonathan P., and Tony Ross-Hellauer. 2020. "The Limitations to Our Understanding of Peer Review." *Research Integrity and Peer Review* 5 (April): 6.

Tran, Hoa Thi Nhu, Kok Siong Ang, Marion Chevrier, Xiaomeng Zhang, Nicole Yee Shin Lee, Michelle Goh, and Jinmiao Chen. 2020. "A Benchmark of Batch-Effect Correction Methods for Single-Cell RNA Sequencing Data." *Genome Biology* 21 (1): 12.

Weber, Lukas M., Wouter Saelens, Robrecht Cannoodt, Charlotte Soneson, Alexander Hapfelmeier, Paul P. Gardner, Anne-Laure Boulesteix, Yvan Saeys, and Mark D. Robinson. 2019. "Essential Guidelines for Computational Method Benchmarking." *Genome Biology* 20 (1): 125.

Zappia, Luke, Belinda Phipson, and Alicia Oshlack. 2018. "Exploring the Single-Cell RNA-Seq Analysis Landscape with the scRNA-Tools Database." *PLoS Computational Biology* 14 (6): e1006245.

Zappia, Luke, and Fabian J. Theis. 2021. "Over 1000 Tools Reveal Trends in the Single-Cell RNA-Seq Analysis Landscape." *Genome Biology* 22 (1): 301.