A natural history of networks: Modeling higher-order interactions in geohistorical data

Alexis Rojas[1,] Anton Holmgren[1], Magnus Neuman[1], Daniel Edler[1, 2, 3], Christopher Blöcker[1] and Martin Rosvall[1]

[1]Integrated Science Lab, Department of Physics, Umeå University, SE-901 87 Umeå, Sweden

[2]Gothenburg Global Biodiversity Centre, Box 461, SE-405 30 Gothenburg, Sweden

[3]Department of Biological and Environmental Sciences, University of Gothenburg, Box 461, SE-405 30 Gothenburg, Sweden

* Correspondence:
Corresponding Author
alexis.rojasbriceno@unibo.it

Keywords: geohistorical data, paleobiology, complex networks, higher-order interactions, Infomap, map equation.

Abstract

Paleobiologists are increasingly employing network-based methods to analyze the complex data retrieved from geohistorical records, including stratigraphic sections, sediments, and fossil collections. However, the lack of a common framework for designing, performing, evaluating, and communicating these studies, leads to issues of reproducibility and communicability. The high-dimensional geohistorical data also raises questions about the limitations of standard network approaches, which assume independent interactions between pairs of components. Higher-order network models better suited for the complex relational structure of the geohistorical data provide an opportunity to overcome these challenges. These models can represent temporal and spatial constraints inherent to the biosedimentary record and describe higher-order interactions, capturing more accurate biogeographical, biostratigraphic, and macroevolutionary patterns. Here we describe how to use the Map Equation framework for designing higher-order network models of geohistorical data, address some practical decisions involved in modeling complex dependencies, and discuss critical methodological and conceptual issues that currently make it difficult to compare results across studies in the growing body of network-based paleobiology research. We illustrate different higher-order network representations and models, including multilayers, hypergraphs, and varying Markov times models, using case studies on gradient analysis, bioregionalization, and macroevolution, and delineate future research directions for current challenges in the emerging field of network paleobiology.

1.   Introduction: Challenges and opportunities for network-based paleobiology research

Network science is transforming scientific research by enhancing our modeling capacities and helping
us understand the behavior of complex systems (Battiston et al. 2020). Many natural and social
phenomena can be described as networks, where nodes represent individual components and links
indicate their interactions. Network science studies high-dimensional, heterogeneously structured,
complex systems and their underlying processes (Barabási and Pósfai 2016). In recent years, standard
network models based on pairwise or direct interactions between individual components have been
applied to almost every area of paleontological research, including biostratigraphy (Muscente et al.
2019), biogeography (Dunhill et al. 2016; Kiel 2017; Rojas et al. 2017; Kocsis et al. 2018; Jeon et al.
2021), macroecology (Roopnarine 2010), and macroevolution (Muscente et al. 2018; Kocsis et al.
2021). However, methodological inconsistencies and conceptual issues make it challenging to
reproduce experiments and compare outcomes across studies, for instance macroevolutionary patterns
delineated using standard (Muscente et al. 2018) and higher-order network models (Rojas et al. 2021)
representing the same underlying data. The complexity of the high-dimensional and spatiotemporally
resolved data retrieved from different geohistorical records, including stratigraphic sections, sediments,
fossil collections, and ice cores (National Research Council 2005), also raises questions about the
limitations of the standard network models: How accurately do they capture environmental (e.g.,
sedimentary facies, depositional environments), spatial (e.g., geographical proximity, plate tectonic
configuration), and temporal (e.g., chronostratigraphic resolution; geohistorical time arrow)
characteristics of the local (bed sets, stratigraphic sections), regional (geological basins; continental
records), and global scale systems examined by paleobiologist?

Although network science provides methods for statistical analysis and machine learning of relational
data (Brandes et al. 2013; Lambiotte et al. 2019), paleobiologists often describe network analysis as a
tool for visualization and qualitative assessment (e.g., Huang et al. 2016; Penn-Clarke and Harper 2020;
Ye et al. 2021). This misconception emerges from the general assumption that spatial patterns observed
in network diagrams created with force-directed layout algorithms (e.g., Kamada-Kawai algorithm,
Fruchterman-Reingold algorithm, etc.) (Csárdi et al. 2024) and representing the observable entities and
their connection, properly capture the underlying network dynamics and structure. This assumption
ignores the fact that different drawing algorithms highlight different aspects of networks and may not
provide reliable insights about their structure. While network visualization techniques are powerful
tools for exploratory data analysis (Perri and Scholtes 2020), this misrepresentation reflects a need to
adapt research practices in quantitative paleobiology based on theoretical and methodological advances
of the network science. Pioneering studies using higher-order representations to explore the deep-time
fossil record (Eriksson et al. 2021; Rojas et al. 2021) suggest that the most critical conceptual issue in
the growing body of network-based paleobiology research is ignoring the extent to which the choice
of network model impacts the results. There are also methodological inconsistencies, including
inadequate descriptions of the input network, incomplete explanations of the clustering approach, and
uncritical acceptance of the network partition without validation. Overall, the lack of a common
framework obstructs interdisciplinarity, reproducibility, and communicability, highlighting the need
for standardized research practices in the emergent field of network paleobiology to guide the design,
execution, communication, and evaluation of network-based studies.

In this overview, we describe how to use the Map Equation framework (Rosvall and Bergstrom 2008;
Edler et al. 2017) to identify important patterns in geohistorical data with different higher-order
network models. Specifically, we describe the concept of higher-order interactions in network
representations of the fossil record, address some practical decisions involved in modeling the
geohistorical data, and illustrate alternative higher-order network models, including multilayer

networks, hypergraphs, and varying Markov time models. We illustrate these concepts through classic
paleontological examples such as depth gradient analysis, marine bioregionalization, and
macroevolution. Our analysis of these case studies either challenges well-established hypotheses or
enhances understanding of the underlying research questions, thereby highlighting both the need and
opportunity to introduce network models beyond pairwise interactions in paleobiology research.
Finally, we delineate major future research directions for current challenges in network paleobiology.
We have focused on the Map Equation framework and its applications in paleobiology research
because it is an increasingly popular alternative to the standard statistical approaches currently used in
paleobiology research (Kocsis et al. 2021; Rojas et al. 2021; Pilotto et al. 2022; Viglietti et al. 2022).
The associated software called Infomap for finding community structure in standard and higher-order
networks is also widely used in natural and social sciences (Law et al. 2022; Lazaridis et al. 2022;
Martins et al. 2022). Overall, our study demonstrates how the Map Equation framework for network
analysis allows researchers to integrate sedimentological, ecological, morphological, taxonomic, and
any other data retrieved from geohistorical records. This approach ultimately allows an integrated
investigation of the complex interactions between plate tectonics, climate, and the evolution of life.

2.   The Map Equation framework for network analysis

Network scientists have developed various methods for different purposes and research questions.
The unsupervised learning task known as community detection refers to the partition of a network
into essential building communities or modules. A particular assignment of the nodes into such
modules is called a network partition. Different approaches have emerged from different research
goals and motivations, leading to different perspectives on how to formulate the question of
community detection on networks (Schaub et al. 2017). The Map Equation framework is an
approach for community detection that models random walks on networks and identify the groups of
nodes that confine the random-walk flows for a relatively long time (Rosvall and Bergstrom 2008).
This dynamic approach provides an intuitive notion of flow-based modules (Smiljanić et al. 2023).
In paleobiology research, random-walk flows on networks constructed from geohistorical data
capture movement dynamics across nodes beyond the nearest neighbors, such as species moving
across their geographic ranges and through geological time. Network-based research in modern
paleobiology has largely focused on community detection in networks. Overall, network partitions
obtained via community detection with The Map Equation framework have revealed meaningful
biostratigraphic (Viglietti et al. 2022), biogeographic (Rojas et al. 2017; Kocsis et al. 2018), and
evolutionary patterns (Rojas et al. 2022) (Figure 1A-D).

The Map Equation framework consists of an objective function – the map equation – and its search
algorithm Infomap. The map equation measures the quality of a network partition through the modular
description length of the random-walk flows (Rosvall and Bergstrom 2008). Minimizing the map
equation over possible solutions with the search algorithm Infomap identifies how network flows
organize into modules. Previous research has found that the Map Equation framework performs
effectively compared with other approaches on various benchmark networks (Lancichinetti and
Fortunato 2009; Aldecoa and Marín 2013; Kheirkhahzadeh et al. 2016; Ghasemian et al. 2019).

Figure 1. Network representations of geohistorical data. **A.** The physical fossil record. These brachiopod shells aim to represent the benthic macrofauna from the R/V Pillsbury program in the Caribbean. Modified from Rojas et al. (2022, fig. 2). **B**. A network representation of the physical record. This bipartite network is an abstracted representation of the underlying data (sampling stations × taxa matrix) (Rojas et al. 2015)(Supplementary Data 1). The brachiopod *Tichosina*, the larger component of the Cenozoic brachiopod faunas in the Caribbean, is indicated. **C.** Modular structure delineated via community detection with the Map Equation framework and using a Markov Time = 2 (Kheirkhahzadeh et al. 2016) (Supplementary Data 2). Modules include sampling stations and taxa. Nodes are rearranged in the circular layout by their module affiliation. Only the two larger modules, representing 98% of the network flow (see Table 1), are displayed. **D**. Modules mapped on a Detrended Correspondence Analysis (DCA) ordination space. E. Small example showing a bipartite network (1B) partitioned into two modules.

Table 1. Glossary of terms related to the Map Equation framework in the context of network-based paleobiology research.

Geohistorical records: Individual stratigraphic sections, sediments, ice cores, fossil collections, and other natural or historical archives providing temporal, environmental, and ecological information (National Research Council, 2005; Kowalewski et al. 2023).

Geohistorical data: Data retrieved from geohistorical records, including, for instance, fossil, sedimentological, biogeochemical, and historical data (see Kowalewski et al. 2023).

Physical fossil record: Physical objects including fossil specimens observed in the field, deposited in collections, or remaining undiscovered in nature (modified from Allmon et al. 2018).

Abstracted fossil record: A simplified representation of the fossil record. It was introduced to describe the large paleontological data retrieved from the physical record (Allmon et al. 2018). We distinguish abstracted representations, including network-based representations, from the underlying data to emphasize that different representations capture different aspects of the underlying data.

Network: A collection of nodes connected by links used to represent a complex system (Newman 2003).

Physical node: An observable entity within a network that represents an actual component in the system (Boccaletti et al. 2006).

State node: A specific state that a physical node can assume in a network. In a multilayer network, different layers capture information of the different states of the same physical node (Edler et al. 2017).

Link: A connection between two nodes in a network, representing an interaction, relationship, or flow between them (Barabási and Pósfai 2016).

Link weight: The strength of the connection between two nodes in a network (Barabási, 2016).

Pairwise interaction: A direct interaction between two nodes in a network (Newman 2001)

Network flow: The movement of information or random walkers through the nodes and links of a network (Rosvall, et al 2014).

Random walk: A stochastic process where a walker moves between nodes in a network, with the probability of choosing a link to traverse based on specific rules or at random (Masuda et al. 2017)

Higer-order interaction: Complex dependencies involving more than two nodes in a network that cannot be captured by pairwise connections alone (Battiston et al. 2021). These can be represented, for instance, by hypergraphs, multilayer networks, or memory networks.

2.1. The map equation objective function

The map equation is an information-theoretic objective function designed to identify flow-based modules in networks (Rosvall and Bergstrom 2008). It applies the minimum description length principle (Rissanen 1978) to network flows, measuring how well a network partition can compress these flows by capturing their modular patterns. By default, it models network flows as a Markovian diffusion process; a random walker moves between nodes, following links proportional to their weights (Rosvall et al. 2009). For example, in a schematic network representing fossil occurrences across several samples, the random walk begins at a randomly selected sample (Figure 1E), moves to a random taxon present in that sample, and then continues to a random sample where the taxon occurs, and so on repeatedly. When a network contains communities of highly interconnected samples and taxa – representing, for instance, biofacies (Scarponi et al. 2022) or biozones (Viglietti et al. 2022) – the network flows will persist relatively long within those communities.

The map equation captures the network's modular structure through the stationary node and link visit rates, reflecting the long-term behavior of the random walk (Rosvall and Bergstrom 2008; Rosvall et al. 2009). Given a partition of nodes into modules, it specifies the theoretical lower bound on how concisely we can describe the trajectory of the random walk. An illustration with codewords exemplifies the machinery: A sender wants to convey the random walk's position after each step to a receiver. Just as Morse code assigns shorter codewords to frequently used letters for efficient communication, the sender uses shorter codewords to frequently visited nodes. For a modular description that capitalizes on the community structure, the sender assigns each node a unique codeword within its module and reuses short codewords across different modules. To ensure the code

is uniquely decodable when switching modules, the sender assigns an exit codeword to each module
codebook and uses an index codebook with codewords for entering each module.

When the random walker stays within a module, the sender must transmit only a single codeword for
the new node. However, if the walker moves between modules, the sender must transmit three
codewords: the exit codeword from the current module codebook, the enter codeword for the new
module from the index codebook, and the codeword for the new node from the new module codebook.
This modular coding scheme becomes efficient when the network partition aligns with the community
structure such that the sender can take advantage of shorter codewords within modules and module
exits are relatively rare.

The map equation quantifies this tradeoff between efficient descriptions within many small modules at
the cost of many transitions between modules and longer descriptions within a few larger modules with
rare transitions between them. While we use codewords to illustrate the machinery of the map equation,
it exploits Shannon's source coding theorem (Shannon 1948) and uses Shannon entropy terms to set
the lower bounds on the per-step codelengths for the index and module codebooks. For the distribution
of visit probabilities P, the Shannon entropy $H(P) = -\sum p_\alpha log_2 p_\alpha$ measures the per-step average
codelength in bits. The entropy term for the index codebook is $H(Q)$ with normalized enter rates q_i/q
into each module i, where $q = \sum_{i=1}^{m} q_i$ is the total rate at which the index codebook is used. The entropy
term for each module i is $H(P^i)$ with normalized visit rates for each node in the module and its exit
rate, and p_i is the rate of use for the module codebook. With the entropy terms weighted by their use,
the map equation for partition M is

179
$$L(M) = qH(Q) + \sum_{i=1}^{m} p_i\, H(P^i).$$

Sample-based geohistorical data typically form undirected networks because the relationship between
sampling units and taxa is symmetric: a random walker can move along links between samples and
taxa in both directions. In an undirected network, node α's visit rate is the total weight w_α of its links
divided by the total link weight of all N nodes in the network, $W = \sum_{\alpha=1}^{N} w_\alpha$. In the small example in
Figure 1E, we treat all fossil occurrences as equally important, resulting in an unweighted network
where all link weights are equal to 1. Therefore, node α's visit rate is its number of links divided by
two times the total number of links in the network, since each undirected link has two link-ends.
Similarly, a module's exit and enter rates are the total number of links that crosses its boundary divided
by W. In the small example network in Figure 1E, one link with weight 1 crosses each boundary such
that all enter and exit rates are $\frac{1}{18}$. With a compressed notation for the entropy, $H(w_1, w_2, \ldots, w_m) =$
$-\sum_{i=1}^{m} \frac{w_i}{w} log_2 \frac{w_i}{w}$, where $w = \sum_{i=1}^{m} w_i$, the total codelength for the two-module partition is

191
$$L_{(M)} = \frac{2}{18}H(1,1) + \frac{10}{18}H(2,2,2,3,1) + \frac{10}{18}H(2,2,2,3,1) = 2.61 \; bits.$$

This partition minimizes the map equation (Figure 2). In general, small modules where random walks
persist long compress the network flows maximally and reveal the most modular regularities for the
modeled network flows (Rosvall and Bergstrom 2008; Rosvall et al. 2009).

The map equation generalizes straightforwardly to multilevel, hierarchically nested modules (Rosvall
and Bergstrom 2011), to higher-order network models, including so-called memory networks (Rosvall
et al. 2014), multilayer networks (De Domenico et al. 2015), and hypergraphs (Eriksson et al. 2021,
2022), and to varying Markov time models (Kheirkhahzadeh et al. 2016). Recent Bayesian
generalizations of the Map Equation deal with incomplete data in sparse networks (Smiljanić et al.
2020, 2021).

A. Input network format (plain text file).

B. Onput format (plain text file).

Figure 2. Input and output formats. -The Map Equation framework understands different formats. **A.**
Input file in Pajek format. **B.** Output file. The resulting partition is written to a file with the extension
.tree (plain text file). The formats described here correspond to the small example network in Figure
1E.

2.2.   The search algorithm Infomap

Infomap is a greedy stochastic search algorithm designed to minimize the map equation over possible
node assignments and detect two-level and multilevel flow modules in networks (Rosvall and
Bergstrom 2008). Since community detection in networks is a complex optimization problem, no
search algorithm can guarantee finding the map equation's global minimum, and it is often informative
to investigate a set of good partitions (Calatayud et al 2019). For a network with n nodes assigned to
m modules, there are on the order of n^m possible partitions. Even for moderately sized networks, testing

all possible partitions to guarantee that we have found the best one is impractical. Instead, Infomap
uses multiple iterative and recursive optimization heuristics to avoid local minima and provide good
network partitions (Edler et al. 2017). The core algorithm starts by assigning each node to its own
module. Then it repeatedly loops through each node in random order and moves it to the module that
reduces the codelength the most. Infomap repeats this procedure until no move decreases the
codelength, rebuilds the network with the modules forming nodes at a coarser level, moves these nodes
into even coarser modules, and so on until no move reduces the codelength further.

To improve this two-level solution, Infomap alternates between a fine-tuning and a coarse-tuning
procedure by moving individual nodes or sub-modules between modules. To find a hierarchical
solution, Infomap starts from the two-level solution and iteratively builds super-module levels that
compress the description of movements between modules. Then it clears the structure under each of
the coarsest modules and recursively and in parallel builds sub-modules within each module until it
cannot find a finer structure that decreases the hierarchical codelength. In this way, the resulting
hierarchical structure of the network may have branches of different depths. Tests comparing various
community detection methods have consistently demonstrated that Infomap performs exceptionally
well across a range of benchmark networks and real-world case studies (Lancichinetti and Fortunato
2009; Aldecoa and Marín 2013; Kheirkhahzadeh et al. 2016; Ghasemian et al. 2019).

2.3.   The Map Equation for higher-order networks

The Map Equation framework extends to higher-order networks, offering a powerful approach for
modeling complex systems with diverse link types and memory effects (Rosvall et al. 2024, Edler et
al. 2017). When modeling network dynamics on standard networks through random walks, the nodes
simultaneously represent the physical components of the system – observable entities such as
individual species, collections, geological outcrops, or stratigraphic units of any resolution, from
individual beds to entire formations – and define the flows through pairwise links between them (Figure
3A-B). To overcome the limitations of analyzing network dynamics based solely on pairwise
interactions, the map equation for higher-order networks uses so-called state nodes to capture higher-
order dependencies and extends Markovian dynamics from first to higher orders (Smiljanić et al. 2023).
Network representations with state nodes are referred to as memory networks when these nodes retain
information from previously visited physical nodes. State nodes can also reflect various aspects of the
system, such as distinct layers in multilayer networks.

State nodes not only provide a more accurate representation of real dynamics but also enable
overlapping modules, as state nodes of the same physical node can be assigned to different modules.
Infomap applies the same iterative and recursive optimization procedures to the state nodes as to
standard nodes. However, to generalize the coding machinery to higher-order dynamics and encode
only visits to physical nodes, it aggregates the visit rates for all state nodes of the same physical node
assigned to the same module, representing them with a single codeword (Edler et al. 2017). This
approach has been used to study the Phanerozoic fossil record using a multilayer network
representation of global occurrence data, with physical nodes representing interacting taxa and grid
cells (aggregated data), and layers representing ordered geological stages. In this case, state nodes
denoted the different geological stages where a particular taxon occurs (Rojas et al. 2021). While all
intra-layer and inter-layer links can be explicitly provided, when inter-layer links are missing, as in this
example, Infomap can generate them through inter-layer relaxation (Figure 3). Since an individual
taxon exists in several geological stages, a physical node contains as many state nodes as geological
stages where the taxon occurs. As a result, Infomap can provide an optimized solution with
taxonomically overlapping communities.

Figure 3. Network representations of geohistorical data. **A.** Temporal occurrence data. **B.** Standard
bipartite network representation created by aggregating fossil occurrences (sp. 1) into arbitrary
spatiotemporally explicit units (g1 to g4). This standard network uses the same nodes to represent the
physical components of the system as well as to describe system's flows (see Table 1). A random walk
as the simplest information flow model forms paths across independent pairwise links on this network
washing out higher-order node interactions. **C.** Multilayer network representation. The Map Equation
framework for higher-order networks distinguishes physical nodes that represent the system's
components from state nodes describing the system's internal flows. This higher-order network better
captures the constraints on the information paths and thus flows tend to stay among units from each
layer.

269   **3.   Higher-order network models in paleobiology**
270
271   **3.1.   The complex relational structure of the geohistorical data**

Geohistorical records, either stratigraphic sections, boreholes, ice cores, or archaeological sites, are
inherently complex. Despite their limitations (Kidwell and Holland 2002; Kidwell and Tomasovych
2013), the high-dimensional and spatiotemporally resolved data retrieved from individual geohistorical
records allow for evaluation of past biotic responses to natural and human-induced environmental
changes at local to regional scales (Council 2005; Scarponi and Kowalewski 2007; Dietl and Flessa
2011; Durham and Dietl 2015; Kowalewski et al. 2023). Although high-precision chronological studies
of selected stratigraphic sections have improved our understanding of major biotic crises in Earth's
history (Smith et al. 2018), extensive compilations of data from individual geohistorical records are
required for studies at large spatiotemporal scales. Fossil occurrences of the benthic marine
invertebrates in the Paleobiology Database (PaleoDB)(Peters and McClennen 2016) have become the
benchmark data for network-based research on macroevolution, macroecology, and pleobiogeography
(Rojas et al. 2017, 2021; Kocsis et al. 2018; Muscente et al. 2018). In most cases, PaleoDB collections
have geographic information and are assigned to a geological stage, enabling the modeling of temporal
constraints. PaleoDB collections also have lithostratigraphic and sedimentological information and
sometimes include taphonomy and body-size data. Each fossil occurrence in PaleoDB belongs to one
collection, has a name with a specific taxonomic resolution, and is linked to an independent taxonomic
classification with associated ecological information. These complex relational data describe the
structure of the Phanerozoic life at multiple taxonomic levels, stratigraphic resolutions, and
spatiotemporal scales.

There are also numerous databases covering specific taxonomic groups, time intervals, or geographic
regions (Williams et al. 2018). For instance, The Strategic Environmental Archaeology Database
compiles high-resolution archaeological and paleontological data (Buckland and Eriksson 2014). In

most cases, the sample's age is a value taken from the original literature sources and obtained from a
range of dating methods varying in precision and accuracy (Buckland 2014). Because samples may
have an age range larger than the length of the preferred bin interval, modeling temporal constraints of
high-resolution data using multilayer networks is challenging. This question has been approached using
the Map Equation framework to investigate the recent fossil record of European beetles (Pilotto et al.
2022). Their multilayer network analysis relaxes the temporal constraints, allowing a random walker
to move toward neighboring layers without exceeding the age limits of the samples in the data. In
practice, with ordered layers representing 500-year time intervals and an accepted age range of 2000
years in the filtered samples, authors allowed a random walker to relax toward the first two layers in
each direction (i.e., *relax limit* = 2) to explore the temporal connections between species and geological
sites only within the maximum age uncertainty. This procedure can be modified to allow a variable
Relax limit that constrains the random walk movement to the given number of neighboring layers
within the age limits of the geological site where it is coming from. Overall, this approach accounts for
the age uncertainty inherent to the samples, making it possible to explore high-resolution geohistorical
data using multilayer representations.

3.2.   Higher-order networks capture the complexity of the geohistorical data

One of the major conceptual changes in modern paleobiology research has been the distinction between
the physical fossil record, consisting of *in-situ* or *ex-situ* specimens, and abstracted representations
based on data retrieved from this physical record (Sepkoski 2013; Allmon et al. 2018). We capitalize
on this idea by explicitly considering network representations of geohistorical data as abstracted
records that can be improved (Figure 4). Intuitively, a good model of the physical fossil record should
be maximally parsimonious yet sufficiently complex to capture the complex interactions of
spatiotemporally resolved and high-dimensional geohistorical data. Researchers designing network
representations of geohistorical data must recognize that their choices make various assumptions about
the spatiotemporal structure and dynamics of the fossil record, such as whether or not to describe
temporal constraints. These assumptions impact the outcome, such as whether or not the solutions
capture larger-scale patterns. In paleobiology, researchers tacitly assume that working on the same data
(e.g., global-scale records of the benthic marine invertebrates from the PaleoDB) guarantees
reproducibility, ignoring that different network representations and modeling decisions may impact the
observed patterns. Here we argue that setting benchmarks is required to improve reproducibility and
communicability in the emergent field of network paleobiology. This challenge is also an opportunity
to move beyond standard network representations, toward higher-order models (Battiston et al. 2020)
assuming biotic and abiotic components of the environment can interact in higher-order combinations,
for instance, the interactions between two species can be affected by other species (Bairey et al. 2016).
Overall, these higher-order network models allow to capture the complexity of the biosphere over
evolutionary time scales.

Figure 4. The notion of multiple fossil records in modern paleobiology research. A major conceptual change in modern paleobiology research has been the distinction between the physical fossil record, consisting of specimens, and the abstracted fossil record derived from this physical record (Allmon et al. 2018). The concept of the abstracted fossil record was first introduced to highlight the extensive data already stored in paleontological databases (Sepkoski 2013). This major shift in paleobiology research represents a transition from a specimen-based discipline to its current status as a data-driven field (Dillon et al. 2023). Here we argue that a new major conceptual change in paleobiology has emerged from the growing body of network-based studies that consider network representations of fossil data as abstracted records. From a given physical fossil record and associated data, paleobiologists can build different abstract records that capture different aspects of the underlying system.

Network representations of geohistorical data in modern paleontological literature are typically models accounting for observed interactions among pairs of taxa (e.g., Muscente et al. 2018), sampling units (e.g., Kocsis et al. 2018), or pairs comprising both taxa and sampling units (e.g., Swain et al. 2022) (Figure 3A). This standard approach models dynamical processes on these networks using only pairwise interactions, ignoring a fundamental feature of any complex system, that is the rich pattern of higher-order dependences between components (Battiston et al. 2020) (Figure 3B). In the Map Equation framework, such dependencies are modeled by equipping a random walker with memory, and letting it choose its steps based on its current node but also on the previously visited node or nodes. Whereas standard network models, which actually suffers from memory loss, use a single node type to represent the physical components of the system, including for instance taxa and sampling units, and model flows through one-step dynamics on their links, the Map Equation framework for higher-order networks introduces abstract nodes to describe the different states in which the physical nodes can be in the system, so-called state nodes (De Domenico et al. 2015) (Figure 3C). For instance, the multilayer network representation of the benchmark data on the Phanerozoic fossil record is a higher-order model in which a physical node representing a given taxon contains several state nodes carrying information on the geological stage where this taxon occurs (Rojas et al. 2021). Therefore, this higher-order representation created through the Map Equation framework is a form of sparse memory network (Edler et al. 2017). In addition to the information inherent to the species, states nodes can be used to describe the localities or any other sampling units representing physical nodes in the network, for instance, they can be used to indicate the tectonic context of the grid cells resulting from aggregating global occurrences (i.e., a given grid cell will have as many state nodes as the number of different

plates it lies on over time). Overall, first-order models of stage-level occurrence data of the Phanerozoic
benthic marine faunas without memory ignore some of the constraints inherent to the underlying
system (e.g., the law of faunal succession, geohistorical time arrow, place tectonic context, etc.) and
may obscure the macroevolutionary patterns (Figure 5). Furthermore, when comparing optimized
partitions of unipartite, bipartite, and multilayer representations of this data, the multilayer network
achieves the shortest codelength and the best compression (see below; Table 2).

Figure 5. Different network representations capture different aspects of the benchmark data on the
Phanerozoic benthic marine faunas (Peters and McClennen 2016). Bipartite and unipartite
representations ignore the temporal constraints inherent to the biosedimentary record. *Unipartite
projection obtained from the bipartite network by rescaling the Markov time (Kheirkhahzadeh et al.
2016). Alluvial diagram representing 98% of the network flow in each case (Supplementary Data 3-7).

Table 2. Comparison of the modular structure of different network representations of the benchmark
data on the Phanerozoic marine faunas. The multilayer representation achieves the shortest codelength
and the best compression. For each partition, we measure the compression by using the corresponding
one-level partition as a baseline. *Unipartite projection obtained from the bipartite network by
rescaling the Markov time (Kheirkhahzadeh et al. 2016).

Model	Physical nodes	State nodes	Levels	Top modules (99%)	Codelength (bits)	Compression (%)
Unipartite*	23203	—	2	4	11.0646	8.6009
Bipartite	23203	—	3	3	10.5169	13.1253
Multilayer	23203	64508	7	4	**6.2826**	**55.2804**

3.3 Higher-order network representations for geohistorical data

3.3.1 Multilayer networks

A multilayer network is a model used to represent a system with multitype interactions between its
components. In the Map Equation framework, multilayer networks can be used to model temporal and
non-temporal constraints in the data. Similar to the geological principle of superposition used to
determine the relative ages of layered strata, layers in multilayers can be used to capture the ordered
arrangement of rock (lithostratigraphic) and time-rock (chronostratigraphic) units (Rojas et al. 2021;
Viglietti et al. 2022), (Viglietti et al. 2022)as well as equal-interval time bins (Pilotto et al. 2022).
Interlayer dynamics in multilayer networks is often modeled based on the intralayer information

(Eriksson et al. 2022). For instance, with layers representing geological stages, the intralayer link
structure can describe species occurrences at the localities in each stage, whereas interlayer connections
are modeled linking the same species across stages. This is achieved through neighborhood flow
coupling (Aslak et al., 2018) between state nodes of the same physical node (or observable entity),
representing the same species in different layers (see Figure 3). In practice, the Map Equation
framework can generate interlayer links using a *relax rate* (*r*), with a random walker moving between
nodes within a given layer guided by intralayer links with probability 1−*r* and relaxing to other layers
guided by links between state nodes of the same physical node with a probability *r* (Edler et al. 2017).
Previous studies show that a relax rate equal to 0.25 is large enough to capture interlayer structures but
small enough to preserve intralayer information (Aslak et al. 2018). This feature is useful when
measuring interlayer links empirically is challenging. By gradually tuning the *relax rate*, it is possible
to explore the relative contribution of intra- and interlayer connections to the overall network structure
(Farage et al. 2021).

Multilayer networks can be also used to model multitype interactions from geohistorical data lacking
temporal structure o when the research design does not account for changes over time. In general,
geohistorical records, including stratigraphic sections, sediments, fossil collections, and ice cores
(National Research Council 2005), consist of multiple biotic and abiotic components and can be
conceptualized as systems with multilayered structure, where each layer describes a particular
interaction between the observable entities. For example, samples from different well sections across
a marine basin can be linked together based on their (*i*) fossil content and (*ii*) lithological
characteristics, independently. A two-layered network can be used to represent this system, with each
layer representing a different type of relationship between the samples. As a consequence, in this
particular multilayer network, each observable entity, which is represented by a unique physical node,
comprises a number of state nodes equal to the number of interactions in the system, Our first example
illustrates multilayer networks through a case study based on the marine invertebrate fossil record
(Holland and Patzkowsky 2004).

3.3.2   Varying Markov time models for higher-order networks

The fossil record does not have a unique and optimal level of description but instead multiple levels
representing different scales in the organization of life. The Markov time represents the scale of time
over which a Markov process evolves on a network. In the context of flow-based community detection
such as the Map Equation Framework, the Markov time indicates how information or a random walker
propagates through the network over different time scales. Modeling network dynamics at shorter or
longer Markov times captures the modular structure at different resolutions (Delvenne et al. 2010).
These Markov time models can be used to explore structure and dynamics in both first- and higher-
order networks (Kheirkhahzadeh et al. 2016). They are particularly useful when the modular structure
of an empirical network lacks a hierarchical organization (e.g., Penn-Clarke and Harper 2020) or when
a two-level solution (i.e., non-hierarchical) is used in the Map Equation framework. Exploring various
time scales to reveal finer or coarser partitions allows connecting time scales of the dynamics to the
structural scales in the network (Lambiotte et al. 2014). Although network analyses in paleobiology
typically assume one-step dynamics on the links, corresponding to Markov time 1, a recent study used
varying Markov time models to compare the organization of a Holocene succession with present-day
nearshore seabed of the Adriatic Sea (Scarponi et al. 2022). However, the specific relationship between
Markov time and the multiple time scales of the evolution of the Earth-Life system, recorded in the
deep-time fossil record (Rojas et al. 2021), has not been explored.

In the Map Equation framework, the discrete (Kheirkhahzadeh et al. 2016) and continuous (Schaub et
al. 2012) time evolution of a Markov process on the network is defined by the parameter Markov time.

Intuitively, when using shorter Markov times than 1, the average transition rate of a random walk is
lower than the encoding rate (see Map Equation section), the same node is encoded multiple times in
its trajectory, and smaller modules are delineated. In contrast, when using longer Markov times than 1,
the average transition rate is higher than the encoding rate, only some nodes on its trajectory are
encoded, and larger modules are delineated. In practice, by setting *markov time* = 2, we explicitly
explore the two-step dynamics on the network. Our second example illustrates varying Markov time
models through an empirical study on the mid-Devonian biogeography of the brachiopods where one-
step dynamics on the links (*markov time* = 1) in a relatively small bipartite network does not capture a
hierarchical organization.

3.3.3 Hypergraphs

Hypergraphs are network models used to study complex systems in which an arbitrary number of its
components can interact. These so-called multigroup interactions, represented through hyperedges
connecting all the nodes involved in the interaction, differ from binary contacts represented through
links in conventional network models (Carletti and Fanelli 2022). A recent study provides the first
hypergraph representation of data derived from the fossil record (Eriksson et al. 2021). This network
analysis employs the Map Equation framework to model global occurrences of the benthic marine
animals from Cambrian (541 MY) to Cretaceous (66 MY), sourced from the PaleoDB, as a hypergraph
where physical entities are fossil taxa linked through weighted hyperedges that connect all taxa
occurring at each stage. Because this network explicitly models temporal constraints in the underlying
paleontological data as hyperedges, it captures large-scale temporal structure and dynamics of system,
especially when spatial data are lacking (Figure 6).

This recent study illustrates how to use the Map Equation framework to model multigroup interactions
in fossil occurrence data (Eriksson et al. 2022). It creates unipartite, bipartite, and multilayer network
representations of hypergraph flows and evaluated how the choice of both network representation and
specific random-walk model, e.g., non-lazy and lazy random walks, with the latter allowing staying at
the current node (or self-linking) with a certain probability, impacts the number, size, depth (i.e.,
number of hierarchical levels), and overlap of multilevel communities in geohistorical data. To create
each different network model, this study represents hyperedges as nodes in the bipartite network,
projected the bipartite flow to create a unipartite flow representation (i.e., the two-step dynamics on
the network obtained with *markov time* = 2) (Kheirkhahzadeh et al. 2016), and created state nodes for
each hyperedge to which a node belongs to construct the multilayer network. Overall, the results
illustrate the advantages of using multilayer network representations of data derived from the fossil
record over bipartite and unipartite representations to quantify macroevolutionary patterns, with
different random walk models, including and excluding self-links, providing similar solutions.

Figure 6. Schematic diagram illustrating a hypergraph representation of fossil occurrence data. In this
diagram, observable entities are fossil taxa, represented by shapes of different sizes, connected through
hyperlinks. Hyperlinks are depicted with boxes of different colors connecting all taxa (species 1 to 9)
occurring at the same time interval. In the Map Equation framework, occurrences of a given taxa at
different time intervals are modeled as state nodes, which are depicted here with different shades of
grey.

4 Visualizing higher-order multiscale structure in networks

Network visualizations are essential tools for understanding the modular structure and dynamics of
higher-order networks describing geohistorical data. However, standard graphic tools developed to
represent first-order interactions among network components fail to capture higher-order and
multiscale community structure and depend on the arbitrary scale of analysis (Peixoto and Rosvall
2017; Perri and Scholtes 2020). To overcome these limitations, the Map Equation framework provides
graphic tools for mapping higher-order and multiscale community structure in network partitions. They
are freely available as a client-side web application at https://www.mapequation.org.

4.1 Infomap Network Navigator (INN)

Higher-order networks representing geohistorical systems are usually complex with hierarchical
modular structures. The Network Navigator tool was developed to explore such complex structures in
real networks. The tool creates interactive maps of hierarchical network partitions with aggregated
inter-module links. These, possibly directed, links are drawn with lengths inversely proportional -- and
width and color saturation proportional to the flow volume between modules. Weakly connected
modules are placed further apart with narrower links between them than strongly connected modules.
Circles represent the modules, with areas proportional to the contained flow volume and border
thicknesses proportional to the exiting flow (Figure 7). Like Google Maps, the modules can be explored
by zooming in and highlighting more detail until the lowest-level leaf nodes are shown. The Network
Navigator was recently used to visualize the multiscale organization of the Phanerozoic benthic marine
faunas, highlighting how the large-scale evolutionary faunas are built up from lower-scale
biogeographic entities (Rojas et al. 2021). Although the INN uses a force-directed drawing algorithm,
similar to those used in the traditional visual approach to draw observed entities and their connections
and to gain insights into the network structure (e.g., Huang et al. 2016; Penn-Clarke and Harper 2020;
Ye et al. 2021), the INN actually represent the network structure previously delineated via community

detection. Nevertheless, given the challenge of visualizing substantially different network partitions
using the same approach, the INN incorporates graphic parameters that allow users to scale the module
size and link width, and to select the level of detail displayed in the plot, making the visual output
easier to interpret in each case.

Figure 7. Infomap Network Navigator. **A.** Graphical Features. Modules are represented as circles, with
areas proportional to the internal flow and border widths proportional to the exiting flow; aggregated
bidirectional inter-module links are shown with widths proportional to inter-module flow and lengths
inversely proportional to it. **B**. Real Case Example. Stylized network navigator output illustrating the
large-scale modular structure of Phanerozoic benthic marine faunas, based on data from Rojas et al.
(2021).

4.2   Alluvial diagrams

Researchers compare network partitions typically to identify major changes in the overall modular
structure. However, common visualization tools employed in network-based paleobiology research,
which focus on the link structure among the observable entities, aim to represent all individual nodes
and their connections (Muscente et al. 2019; Penn-Clarke and Harper 2020). This approach is
challenging given the high-dimensional data but also typically unnecessary in order to answer common
research questions in paleobiology (e.g., to delineate bioregions, biozones, mega-assemblages, biotic
transitions, etc.). Alluvial diagrams are visualization tools that highlight changes in modular structure
across different network partitions, including, for instance, optimized, bootstrapped, suboptimal, and
planted solutions. In the recent paleobiology literature, alluvial diagrams have been used, for instance,
to compare a Holocene succession with present-day nearshore seabeds of the Po Adriatic system
(Scarponi et al. 2022), and to highlight major differences between alternative biostratigraphy models
for the late Permian-mid Triassic Beaufort Group in South Africa (Viglietti et al. 2022). Overall, an
alluvial diagram does not represent all individual nodes in the network but highlights changes in the
module assignment of the most important nodes across partitions. In the Map Equation framework, the
flow volume determines node importance and is calculated from the visitation rates when the Infomap
algorithm searches for the optimal partition (Rosvall and Bergstrom 2008).

Figure 8. Visualizing change in network partitions using alluvial diagrams. To compare networks with the same sets of nodes, we assemble at least two network partitions. **A**. Then, we group nodes in the same module in stacked bars with height proportional to the flow volume of each node and connect corresponding nodes with streamlines. **B**. Finally, to highlight how the partitions change, we aggregate the nodes into modules. **C**. To compare additional network partitions, we add more stacks of bars to the right and repeat the procedure b-c.

To visually simplify patterns while highlighting changes between network partitions, the alluvial diagram is constructed by grouping nodes with the same module assignment as follows (Figure 8): (*i*) Shown side-by-side, each partition is represented by a vertical stack of modules in the order we choose. (*ii*) To highlight the nodes that change module assignment between partitions, we draw streamlines between all modules in adjacent partitions that contain the same node. (*iii*) The flow volume of the modules determine their heights, whereas the flow of the nodes that connected modules have in common determine the height of the streamlines. The alluvial diagram comparing network partitions obtained from different network representations of the same underlying data (Figure 5) illustrates how this graphic tool helps to better understand changes in the modular structure between partitions.

4. Robustness evaluation

4.1. Identifying significant assignments in network partitions

To assess the support of network modules in the underlying data, it is convenient to construct a set of bootstrapped networks through resampling of the data in a standard manner (Efron and Tibshirani 1993). This approach enables calculating summary statistics such as mean values and standard deviations and identifying features that occur in a large enough proportion of bootstrapped networks to be considered robust. The Map Equation framework includes a significance clustering method (Rosvall and Bergstrom 2010), that identifies sets of nodes that are significantly assigned to a module in a reference partition. For a given module in the reference partition, the largest subset of nodes clustered together in at least a user-defined proportion of all bootstrap partitions represents its significant core. This confidence level is provided as a fraction with the default value being 0.95. This approach has been used to distinguish gradual from abrupt events in the deep-time (Rojas et al. 2021) and near-time fossil record (Pilotto et al. 2022), with gradual events assumed when the significant core of two adjacent modules co-occurs more than a fraction [1 - confidence level] of the bootstrap partitions. In addition, different aspects of a network partition can be evaluated across a set of bootstrap networks using set-theoretic measures such as the Jaccard index and measures built upon concepts from information theory (Vinh et al. 2009). The resampling procedure can also consider the underlying data by, for example, considering a discrete distribution if the data represent counts, and also a truncated distribution to avoid false negatives.

4.2. Exploring alternative solutions

Finding the best network partition is generally a non-convex optimization problem and the practitioner therefore needs to consider the possibility of multiple solutions. To this end, methods exploring solutions and their quality have been developed. One such method estimates the minimum number of searches required by the search algorithm Infomap to map the complete solution landscape, ensuring that the best solution is obtained and that alternative solutions of lesser quality can be explored (Calatayud et al. 2019). We illustrate this approach with the multilayer network representing the Phanerozoic fossil record of the benthic marine faunas, where alternative partitions are embedded using a dimension reduction technique (McInnes et al. 2018)(Figure 8), and the distance between partitions is calculated using a weighted version of the Jaccard distance. In this example, the codelength (see Table 1) varies between the partition clusters, with the best partition in the middle cluster. In practice, these variations have minimal impact on the large-scale patterns, with only a few nodes alternating between modules.

Figure 9. Quality of alternative partitions of the multilayer network representing the Phanerozoic fossil record of the benthic marine faunas mapped in a two-dimensional space. Circles represent clusters of network partitions, located at the cluster center, with size proportional to the number of partitions grouped into the cluster. Map isolines are constructed using the Jaccard distance between partitions. Despite differences in their quality (codelength), all partition clusters identified at the selected scale show a similar modular structure

Although the approach to explore the solution landscape was developed to identify the minimum number of searches required by the search algorithm Infomap to map the complete solution landscape, it also highlights the importance of exploring sub-optimal partitions when dealing with real systems, which can provide a better understanding of complex patterns. For instance, the end-Cretaceous extinction, despite being a widely known event (Alegret et al. 2022), is not captured at the resolution of the landscape illustrated in Figure 8. To find a solution showing the K-T event at the highest hierarchical level, we must consider less optimal solutions, suggesting that other global events have been more important in shaping the Phanerozoic history of the marine life.

5. Case studies on the fossil record

5.1. Delineating litho-biofacies through multilayer networks

Understanding how the distribution of organisms along environmental gradients changes through time is a primary research area in paleobiology (Patzkowsky and Holland 2012). Indirect ordination techniques applied to species occurrence data have been successfully employed to recover environmental gradients in the sedimentary record (Holland and Patzkowsky 2007; Dale et al. 2007). In general, environmental gradients are interpreted from mapping taxa or samples, coded by external factors (e.g., life habit for taxa and depositional environment for samples), into the reduced ordination space. Here we provide a multilayer network analysis that combines taxon abundance and sample attributes into the modeling. Specifically, we conceptualize the biosedimentary record as a complex system with a multilayered structure by creating a network representation with two layers, one describing taxonomic composition and the other sedimentologically-defined relationships between sampling units (Figure 10A). The underlying data were obtained from a basin-scale study carried out on Late Ordovician outcrops in central Kentucky (Holland and Patzkowsky 2004)..

Figure 10. A. A multilayer network representing litho-biofacies from Late Ordovician outcrops in central Kentucky. In this higher order network, one layer describes the biotic component (samples × taxa matrix) and the other describes the abiotic component (samples × environments matrix) of the geohistorical record (Supplementary Data 8). **B**. Litho-biofacies delineated via community detection using the Map Equation framework. Modules in the multilayer solution include taxa, samples, and environments, and can be directly interpreted as litho-biofacies (Supplementary Data 9). **C**. Detrended Component Analysis (DCA) on the samples × taxa matrix. Network modules mapped in a DCA ordination space indicating their distribution along the depth water gradient. Background colored based on the module affiliation. Data from Holland and Patzkowsky (2004).

Observable entities in this two-layered network represent sampling units, taxa, and sedimentological groups. Layers in this representation independently capture fossil assemblages (biofacies) and sedimentological groups (lithofacies) in the geohistorical record, independently. However, the multilayer network reveals litho-bio facies (Figure 10B). This higher-order approach directly interprets the gradients obtained via ordination analysis in two ways, delineating modules that comprise strongly connected taxa, samples, and sedimentological groups, and partitioning the gradient into discrete regions (Figure 10C). Although the sedimentological information underlying this case study is relatively simple, our network model can be easily extended to represent geochemical, taphonomic,

and any other complex relationship between sampling units, as well as relationships between taxa (i.e.,
ecology, body size). Even though beds are the fundamental units of both stratigraphy and paleontology
(Patzkowsky and Holland 2012), sampling units in this multilayer framework can represent
stratigraphic units of any scale. In practice, depending on the stratigraphic resolution of the underlying
data, this multilayer network model can be used to capture multitype relationships between samples,
beds, members, or broader units

5.2. Validating marine bioregionalization through Markov time models

Research employing network-based approaches to describe biogeography in the fossil record is
overwhelmingly focused on describing one-step dynamics (Markov time 1) in relatively small bipartite
networks derived from the relatively limited fossil data (Penn-Clarke and Harper 2020; Ye et al. 2021),
to reveal continental to global scale marine bioregions. Although first-order network representations
of fossil occurrences have been shown to capture a biogeographic signal at some geological stages in
the Phanerozoic (Rojas et al. 2017; Kocsis et al. 2018), these studies are unable to identify transition
zones, provide a single-scale description of the bioregions and obscure larger-scale patterns. Overall,
conventional approaches ignore that bioregions do not have a unique level of description but multiple
levels reflecting the complex spatiotemporal structuring of the marine biodiversity. Here we describe
how to use varying Markov time models through the Map Equation framework to overcome some of
the limitations of the standard models currently used in paleobiology research. This case study is based
on a standard bipartite network relevant for Devonian biogeography, but the approach can be applied
directly to higher-order networks (Calatayud et al. 2021). We use varying Markov time models to re-
examine the bioregionalization of the Middle Devonian Brachiopods from the Old-World Realm
(Penn-Clarke and Harper 2020). This approach reveals the larger-scale biogeographic structure at
different resolutions. Results provide new insights into the biogeographic affinities of the brachiopod
faunas from Southern Peru, which remains an open question (Figure 11). However, this case study
shows that we can reveal the spatially nested hierarchical organization of marine biodiversity through
varying Markov time models.

B. Nework partition obtained at Markov time 1

C. Modules obtained at Markov times 1.30 and 1.35 mapped on the partition at Markov time 1

Figure 11. Bioregionalization of the Middle Devonian Old World Realm. **A**. Varying Markov time models on the biogeographic network constructed from brachiopod occurrence data (Penn-Clarke and Harper 2020). Network partitions at different Markov times reveal the larger-scale biogeographic structures obtained at different resolutions. **B.** Network partition obtained at the Markov time 1 (7 modules). Circles represent the seven modules delineated when exploring the one-step dynamics on the assembled network. **C.** Modules obtained from partitions at Markov times 1.30 and 1.35 (3 modules) mapped on those obtained at the Markov time 1. These two partitions differ in the affiliation of the Southern Peru locality, placed alternatively into the modules representing higher (white) and lower (orange) latitudes. Overall, coarser partitions contain fewer clusters as the Markov time increases.

6. Recommendations for future research directions

Higher-order network modeling of geohistorical data holds considerable promise for paleobiology
research because it provides a framework for revealing the complex interactions between biotic and
abiotic components of the geohistorical records at multiple scales. Higher-order networks better
capture the spatiotemporal constraints inherent to the geohistorical data, providing more accurate
descriptions of patterns. We showed that different network representations capture different aspects of
the underlying data and studied systems. This can lead to potential reproducibility issues when
researchers overlook how their choice of a network model impacts the results and provide inadequate
or incomplete explanations of the analyses (e.g., inadequate description of the input network and
incomplete explanations of the clustering approach). We believe that establishing benchmark networks
from widely used compendia of paleontological data (e.g., The Paleobiology Database) and using the
Map Equation framework can enhance both reproducibility and communicability in network-based
paleobiology. Our analyses have focused on regional and global-scale examples, but this framework
can be applied to systems at any scale, ranging from individual beds up to the global biosedimentary
record.

The standard formulation of the map equation implicitly assumes complete data. It reveals the large-
scale structure of a system given the observed data (Ghasemian et al. 2019). This general approach
dominates network-based research in paleobiology and has proven useful for describing biogeography,
biostratigraphy, and macroevolution. However, geohistorical records are incomplete – not every
species that ever lived is preserved, and not all environmental conditions of every region in the globe
are recorded in the sediments (Kidwell and Flessa 1996; Council 2005). Sampling also varies due to
variations in exposure and collection effort (Holland 2016). The overall effect is an abstracted fossil
record partially observed, a network involving links that exist but are not represented in the model
because they have not been observed. Distinguishing missing links (false negatives) from non-edges
(true negatives) within the unobserved connections, a task known as link prediction, could allow to
improve abstracted fossil records where the underlying geohistorical data is highly incomplete. Such
missing links could alter conclusions when delineating network community structure and modeling
network dynamics (Ghasemian et al. 2019; Blöcker et al. 2022). In cases where we expect data to be
highly incomplete, we should use a community-detection approach that can handle this: the Bayesian
map equation, also part of the Map Equation framework, models missing data with an empirical Bayes
approach (Smiljanić et al. 2021). In addition, using the minimum description length principle (Rissanen
1978) underlying the Map Equation Framework, it is possible to use a modular partition to measure
the description length of links (Blöcker et al. 2022). Assuming that links with a shorter description are
more likely, we can rank the non-existing links in a network and select the best candidates for false
negatives, those links that are most consistent with the network dynamics and thus most likely to exist.
In practice, it can be used to improve abstracted fossil records, but it is up to the researchers to examine
and interpret those predicted links in the face of the specific question at hand. This approach can be
used for stratigraphic placement of isolated samples, refining biostratigraphic models, and improving
the overall description of bioregions. We believe these methodological efforts lay the ground for a
fertile research direction in the emergent field of network paleobiology.

7. Conflict of Interest

The authors declare that the research was conducted in the absence of any commercial or financial
relationships that could be construed as a potential conflict of interest.

8. Author Contributions

A.B.: conceptualization, data curation, formal analysis, methodology, visualization, writing—original
draft, writing, editing; A.E.: visualization, writing; M.N.: visualization, writing, editing; D.E.:
writing; C.B.: writing, editing; M.R.: writing, editing, funding.

9. Funding

A.R. was partially supported by the Kone Foundation funded project *Comparing evolutionary*
processes in nature and society (project number 202007064). A.E., M.N. and M.R. were supported
by the Swedish Foundation for Strategic Research, Grant No.\ SB16-0089. D.E. and M.R. were
supported by the Swedish Research Council, Grant No.\ 2016-00796.

Acknowledgments

We thank the contributors to the Paleobiology Database who collected data. We thank Alex Dunhill
and Andrej Spiridonov for helpful comments on an early version of the manuscript. AR thanks Steve
Holland for providing data to delineate Middle Upper Ordovician biofacies.

10. References

Aldecoa, R., and Marín, I. (2013). Exploring the limits of community detection strategies in complex
networks. Sci Rep 3, 2216. doi: 10.1038/srep02216.

Alegret, L., G. J. Arreguín-Rodríguez, and E. Thomas. 2022: Oceanic productivity after the
Cretaceous/Paleogene impact: Where do we stand? The view from the deep. Pp.449–470 in C.
Koeberl, P. Claeys, and A. Montanari, eds. From the Guajira Desert to the Apennines, and from
Mediterranean Microplates to the Mexican Killer Asteroid: Honoring the Career of Walter Alvarez.
Geological Society of America.

Allmon, W. D., Dietl, G. P., Hendricks, J. R., and Ross, R. M. (2018). "Bridging the two fossil
records: Paleontology's 'big data' future resides in museum collections," in Museums at the
Forefront of the History and Philosophy of Geology: History Made, History in the Making
(Geological Society of America). doi: 10.1130/2018.2535(03).

Aslak, U., Rosvall, M., and Lehmann, S. (2018). Constrained information flows in temporal networks
reveal intermittent communities. Phys. Rev. E 97, 062312. doi: 10.1103/PhysRevE.97.062312.

Battiston, F., E. Amico, A. Barrat, G. Bianconi, G. Ferraz De Arruda, B. Franceschiello, I. Iacopini,
S. Kéfi, V. Latora, Y. Moreno, M. M. Murray, T. P. Peixoto, F. Vaccarino, and G. Petri. 2021: The
physics of higher-order interactions in complex systems. Nature Physics 17:1093–1098.

Bairey, E., E. D. Kelsic, and R. Kishony. 2016: High-order species interactions shape ecosystem
diversity. Nature Communications 7:12285.

Barabási, A.-L., and Pósfai, M. (2016). Network science. Cambridge, United Kingdom: Cambridge
University Press.

Benson, A. R., Gleich, D. F., and Leskovec, J. (2016). Higher-order organization of complex
networks. Science 353, 163–166. doi: 10.1126/science.aad9029.

Blöcker, C., Smiljanić, J., Scholtes, I., and Rosvall, M. (2022). Similarity-based Link Prediction from
Modular Compression of Network Flows. doi: 10.48550/ARXIV.2208.14220.

Boccaletti, S., V. Latora, Y. Moreno, M. Chavez, and D. Hwang. 2006: Complex networks: Structure
and dynamics. Physics Reports 424:175–308.

Brandes, U., Robins, G., McCranie, A., and Wasserman, S. (2013). What is network science? Netw.
sci. 1, 1–15. doi: 10.1017/nws.2013.2.

Buckland, P. I. (2014). The Bugs Coleopteran Ecology Package (BugsCEP) database: 1000 sites and
half a million fossils later. Quaternary International 341, 272–282. doi: 10.1016/j.quaint.2014.01.030.

Buckland, P. I., and Eriksson, E. J. (2014). "Strategic Environmental Archaeology Database
(SEAD)," in Encyclopedia of Global Archaeology, ed. C. Smith (New York, NY: Springer New
York), 7076–7085. doi: 10.1007/978-1-4419-0465-2_833

Calatayud, J., Bernardo-Madrid, R., Neuman, M., Rojas, A., and Rosvall, M. (2019). Exploring the
solution landscape enables more reliable network community detection. Phys. Rev. E 100, 052308.
doi: 10.1103/PhysRevE.100.052308.

Calatayud, J., M. Neuman, A. Rojas, A. Eriksson, and M. Rosvall. 2021: Regularities in species'
niches reveal the world's climate regions. ELife 10:e58397.

Carletti, T., and Fanelli, D. (2022). "Pattern Formation on Hypergraphs," in Higher-Order Systems
Understanding Complex Systems., eds. F. Battiston and G. Petri (Cham: Springer International
Publishing), 163–180. doi: 10.1007/978-3-030-91374-8_5.

Csárdi, G., T. Nepusz, K. Müller, S. Horvát, V. Traag, F. Zanini, and D. Noom. 2024: igraph for R: R
interface of the igraph library for graph theory and network analysis. .

Council, N. R. (2005). The Geological Record of Ecological Dynamics: Understanding the Biotic
Effects of Future Environmental Change. Washington, DC: The National Academies Press doi:
10.17226/11209.

Dale, E. E., S. Ware, and B. Waitman. 2007: Ordination and Classification of Bottomland Forests in
the Lower Mississippi Alluvial Plain. Castanea 72:105–115.

De Domenico, M., Lancichinetti, A., Arenas, A., and Rosvall, M. (2015). Identifying Modular Flows
on Multilayer Networks Reveals Highly Overlapping Organization in Interconnected Systems. Phys.
Rev. X 5, 011027. doi: 10.1103/PhysRevX.5.011027.

Delvenne, J.-C., Yaliraki, S. N., and Barahona, M. (2010). Stability of graph communities across
time scales. Proc. Natl. Acad. Sci. U.S.A. 107, 12755–12760. doi: 10.1073/pnas.0903215107.

Dietl, G. P., and Flessa, K. W. (2011). Conservation paleobiology: putting the dead to work. Trends
in Ecology & Evolution 26, 30–37. doi: 10.1016/j.tree.2010.09.010

Dillon, E. M., E. M. Dunne, T. M. Womack, M. Kouvari, E. Larina, J. R. Claytor, A. Ivkić, M. Juhn,
P. S. Milla Carmona, S. V. Robson, A. Saha, J. A. Villafaña, and M. E. Zill. 2023: Challenges and
directions in analytical paleobiology. Paleobiology 49:377–393.

Dunhill, A. M., Bestwick, J., Narey, H., and Sciberras, J. (2016). Dinosaur biogeographical structure
and Mesozoic continental fragmentation: a network-based approach. Journal of Biogeography. doi:
10.1111/jbi.12766.

Durham, S. R., and Dietl, G. P. (2015). Perspectives on geohistorical data among oyster restoration
professionals in the United States. Journal of Shellfish Research 34, 227–239. doi:
10.2983/035.034.0204.

Edler, D., Bohlin, L., and Rosvall, M. (2017). Mapping Higher-Order Network Flows in Memory and
Multilayer Networks with Infomap. Algorithms 10, 112. doi: 10.3390/a10040112.

Efron, B., and Tibshirani, R. (1993). An introduction to the bootstrap. New York: Chapman & Hall.

Eriksson, A., Carletti, T., Lambiotte, R., Rojas, A., and Rosvall, M. (2022). "Flow-Based Community
Detection in Hypergraphs," in Higher-Order Systems Understanding Complex Systems., eds. F.

Farage, C., D. Edler, A. Eklöf, M. Rosvall, and S. Pilosof. 2021: Identifying flow modules in
ecological networks using Infomap. Methods in Ecology and Evolution 12:778–786

Battiston and G. Petri (Cham: Springer International Publishing), 141–161. doi: 10.1007/978-3-030-
91374-8_4.

Eriksson, A., Edler, D., Rojas, A., de Domenico, M., and Rosvall, M. (2021). How choosing random-
walk model and network representation matters for flow-based community detection in hypergraphs.
Commun Phys 4, 133. doi: 10.1038/s42005-021-00634-z.

Ghasemian, A., Hosseinmardi, H., and Clauset, A. (2019). Evaluating Overfit and Underfit in Models
of Network Community Structure. IEEE Trans. Knowl. Data Eng., 1–1. doi:
10.1109/TKDE.2019.2911585.

Holland, S. M. (2016). The non-uniformity of fossil preservation. Phil. Trans. R. Soc. B 371,
20150130. doi: 10.1098/rstb.2015.0130.

Holland, S. M., and Patzkowsky, M. E. (2004). Ecosystem Structure and Stability: Middle Upper
Ordovician of Central Kentucky, USA. PALAIOS 19, 316–331. doi: 10.1669/0883-
1351(2004)019<0316:ESASMU>2.0.CO;2.

Holland, S. M., and M. E. Patzkowsky. 2007: Gradient ecology of a biotic invasion: Biofacies of the
type Cincinnatian Series (Upper Ordovician), Cincinnati, Ohio Region, USA. PALAIOS 22:392–
407.

Huang, B., Zhan, R.-B., and Wang, G.-X. (2016). Recovery brachiopod associations from the lower
Silurian of South China and their paleoecological implications. Can. J. Earth Sci. 53, 674–679. doi:
10.1139/cjes-2015-0193.

Hunt, G. (2010). Evolution in Fossil Lineages: Paleontology and The Origin of Species. The
American Naturalist 176, S61–S76. doi: 10.1086/657057.

Jeon, J., Liang, K., Park, J., Kershaw, S., and Zhang, Y. (2021). Diverse labechiid stromatoporoids
from the Upper Ordovician Xiazhen Formation of South China and their paleobiogeographic
implications. J. Paleontol.

Kheirkhahzadeh, M., Lancichinetti, A., and Rosvall, M. (2016). Efficient community detection of
network flows for varying Markov times and bipartite networks. Phys. Rev. E 93, 032309. doi:
10.1103/PhysRevE.93.032309.

Kidwell, S. M., and Flessa, K. W. (1996). The Quality of the Fossil Record: Populations, Species,
and Communities. Annu. Rev. Earth Planet. Sci. 24, 433–464. doi: 10.1146/annurev.earth.24.1.433.

Kidwell, S. M., and Holland, S. M. (2002). The Quality of the Fossil Record: Implications for
Evolutionary Analyses. Annual Review of Ecology and Systematics 33, 561–588. doi:
10.1146/annurev.ecolsys.33.030602.152151.

Kidwell, S. M., and Tomasovych, A. (2013). "Implications of Time-Averaged Death Assemblages
for Ecology and Conservation Biology," in Annual Review of Ecology, Evolution, and Systematics,
Vol 44, ed. D. J. Futuyma, 539-+.

Kiel, S. (2017). Using network analysis to trace the evolution of biogeography through geologic
time: A case study. Geology, G38877.1. doi: 10.1130/G38877.1.

Kocsis, Á. T., Reddin, C. J., and Kiessling, W. (2018). The biogeographical imprint of mass
extinctions. Proc. R. Soc. B. 285, 20180232. doi: 10.1098/rspb.2018.0232.

Kocsis, Á. T., Reddin, C. J., Scotese, C. R., Valdes, P. J., and Kiessling, W. (2021). Increase in
marine provinciality over the last 250 million years governed more by climate change than plate
tectonics. Proc. R. Soc. B. 288, 20211342. doi: 10.1098/rspb.2021.1342.

Kowalewski, M., R. Nawrot, D. Scarponi, A. Tomašových, and M. Zuschin. 2023:
Marineconservation palaeobiology: What does the late Quaternary fossil record tell us about modern-
day extinctions and biodiversity threats? Cambridge Prisms: Extinction 1:e24.

Lambiotte, R., and Rosvall, M. (2012). Ranking and clustering of nodes in networks with smart
teleportation. Phys. Rev. E 85, 056107. doi: 10.1103/PhysRevE.85.056107.

Lambiotte, R., Delvenne, J.-C., and Barahona, M. (2014). Random Walks, Markov Processes and the
Multiscale Modular Organization of Complex Networks. IEEE Trans. Netw. Sci. Eng. 1, 76–90. doi:
10.1109/TNSE.2015.2391998.

Lambiotte, R., M. Rosvall, and I. Scholtes. 2019: From networks to optimal higher-order models of
complex systems. Nature Physics 15:313–320.

Lancichinetti, A., and Fortunato, S. (2009). Community detection algorithms: A comparative
analysis. Phys. Rev. E 80, 056117. doi: 10.1103/PhysRevE.80.056117.

Law, S. R., Serrano, A. R., Daguerre, Y., Sundh, J., Schneider, A. N., Stangl, Z. R., et al. (2022).
Metatranscriptomics captures dynamic shifts in mycorrhizal coordination in boreal forests. Proc.
Natl. Acad. Sci. U.S.A. 119, e2118852119. doi: 10.1073/pnas.2118852119.

Lazaridis, I., Alpaslan-Roodenberg, S., Acar, A., Açıkkol, A., Agelarakis, A., Aghikyan, L., et al.
(2022). The genetic history of the Southern Arc: A bridge between West Asia and Europe. Science
377, eabm4247. doi: 10.1126/science.abm4247.

Martins, A. F., da Cunha, B. R., Hanley, Q. S., Gonçalves, S., Perc, M., and Ribeiro, H. V. (2022).
Universality of political corruption networks. Sci Rep 12, 6858. doi: 10.1038/s41598-022-10909-2.

Masuda, N., M. A. Porter, and R. Lambiotte. 2017: Random walks and diffusion on networks.
Physics Reports 716–717:1–58.

Muscente, A. D., A. Prabhu, H. Zhong, A. Eleish, M. B. Meyer, P. Fox, R. M. Hazen, and A. H.
Knoll. 2018: Quantifying ecological impacts of mass extinctions with network analysis of fossil
communities. Proceedings of the National Academy of Sciences 115:5217–5222

Muscente, A. D., Bykova, N., Boag, T. H., Buatois, L. A., Mángano, M. G., Eleish, A., et al. (2019).
Ediacaran biozones identified with network analysis provide evidence for pulsed extinctions of early
complex life. Nat Commun 10, 911. doi: 10.1038/s41467-019-08837-3.

National Research Council. 2005: The Geological Record of Ecological Dynamics: Understanding
the Biotic Effects of Future Environmental Change. National Academies Press, Washington, D.C.,
11209 p.

Patzkowsky, M. E., and Holland, S. M. (2012). Stratigraphic paleobiology: understanding the
distribution of fossil taxa in time and space. Chicago ; London: The University of Chicago Press.

Peixoto, T. P., and Rosvall, M. (2017). Modelling sequences and temporal networks with dynamic
community structures. Nat Commun 8, 582. doi: 10.1038/s41467-017-00148-9.

Penn-Clarke, C. R., and Harper, D. A. T. (2020). Early−Middle Devonian brachiopod provincialism
and bioregionalization at high latitudes: A case study from southwestern Gondwana. GSA Bulletin.
doi: 10.1130/B35670.1.

Perri, V., and Scholtes, I. (2020). "HOTVis: Higher-Order Time-Aware Visualisation of Dynamic
Graphs," in Graph Drawing and Network Visualization Lecture Notes in Computer Science., eds. D.
Auber and P. Valtr (Cham: Springer International Publishing), 99–114. doi: 10.1007/978-3-030-
68766-3_8.

Peters, S. E., and McClennen, M. (2016). The Paleobiology Database application programming
interface. Paleobiology 42, 1–7. doi: 10.1017/pab.2015.39.

Pilotto, F., Rojas, A., and Buckland, P. I. (2022). Late Holocene anthropogenic landscape change in
northwestern Europe impacted insect biodiversity as much as climate change did after the last Ice
Age. Proc. R. Soc. B. 289, 20212734. doi: 10.1098/rspb.2021.2734.

Rissanen, J. (1978). Modeling by shortest data description. Automatica 14, 465–471. doi:
10.1016/0005-1098(78)90005-5.

Rojas, A., A. Gracia, and P. Patarroyo. 2015: Brachiopods from off the San Bernardo Archipelago
(Colombian Caribbean), with comments on specific synonymies in Tichosina Cooper, 1977. Zootaxa
3914:55.

Rojas, A., Calatayud, J., Kowalewski, M., Neuman, M., and Rosvall, M. (2021). A multiscale view
of the Phanerozoic fossil record reveals the three major biotic transitions. Commun Biol 4, 309. doi:
10.1038/s42003-021-01805-y.

Rojas, A., Gracia, A., Hernández-Ávila, I., Patarroyo, P., and Kowalewski, M. (2022). Occurrence of
the brachiopod *Tichosina* in deep-sea coral bottoms of the Caribbean Sea and its paleoenvironmental
implications. Bulletin of the Florida Museum of Natural History 59, 1–15. doi:
10.1101/2020.06.24.168658.

Rojas, A., Patarroyo, P., Mao, L., Bengtson, P., and Kowalewski, M. (2017). Global biogeography of
Albian ammonoids: A network-based approach. Geology 45, 659–662. doi: 10.1130/G38944.1.

Roopnarine, P. (2010). Networks, Extinction and Paleocommunity Food Webs. Nat Prec. doi:
10.1038/npre.2010.4433.2.

Rosvall, M., and Bergstrom, C. T. (2008). Maps of random walks on complex networks reveal
community structure. Proceedings of the National Academy of Sciences 105, 1118–1123. doi:
10.1073/pnas.0706851105.

Rosvall, M., and Bergstrom, C. T. (2011). Multilevel compression of random walks on networks
reveals hierarchical organization in large integrated systems. PloS one, 6(4). doi:
10.1371/journal.pone.0018209.

Rosvall, M., Axelsson, D., and Bergstrom, C. T. (2009). The map equation. The European Physical
Journal Special Topics 178, 13–23. doi: 10.1140/epjst/e2010-01179-1.

Rosvall, M., Delvenne, J., Schaub, M. T., and Lambiotte, R. (2019). "Different Approaches to
Community Detection," in Advances in Network Clustering and Blockmodeling, eds. P. Doreian, V.
Batagelj, and A. Ferligoj (Wiley), 105–119. doi: 10.1002/9781119483298.ch4.

Rosvall, M., Esquivel, A. V., Lancichinetti, A., West, J. D., and Lambiotte, R. (2014). Memory in
network flows and its effects on spreading dynamics and community detection. Nat Commun 5,
4630. doi: 10.1038/ncomms5630.

Shannon, C. E. (1948). A Mathematical Theory of Communication. Bell System Technical Journal
27, 379–423. doi: 10.1002/j.1538-7305.1948.tb01338.x.

Scarponi, D., and Kowalewski, M. (2007). Sequence stratigraphic anatomy of diversity patterns: Late
Quaternary benthic mollusks of The Po Plain, Italy. Palaios 22, 296–305. doi:
10.2110/palo.2005.p05-020r.

Scarponi, D., A. Rojas, R. Nawrot, A. Cheli, and M. Kowalewski. 2023: Assessing biotic response to
anthropogenic forcing using mollusc assemblages from the Po–Adriatic System (Italy). Geological
Society, London, Special Publications 529:293–310.
921

Schaub, M. T., Delvenne, J.-C., Rosvall, M., and Lambiotte, R. (2017). The many facets of
community detection in complex networks. Appl Netw Sci 2, 4. doi: 10.1007/s41109-017-0023-6.

Schaub, M. T., Lambiotte, R., and Barahona, M. (2012). Encoding dynamics for multiscale
community detection: Markov time sweeping for the map equation. Phys. Rev. E 86, 026112. doi:
10.1103/PhysRevE.86.026112.

Sepkoski, D. (2013). Towards "A Natural History of Data": Evolving Practices and Epistemologies
of Data in Paleontology, 1800–2000. J Hist Biol 46, 401–444. doi: 10.1007/s10739-012-9336-6.

Sepkoski, J. J. (1981). A factor analytic description of the Phanerozoic marine fossil record.
Paleobiology 7, 36–53. doi: 10.1017/S0094837300003778.

Smiljanić, J., Blöcker, C., Edler, D., and Rosvall, M. (2021). Mapping flows on weighted and
directed networks with incomplete observations. Journal of Complex Networks 9, cnab044. doi:
10.1093/comnet/cnab044.

Smiljanić, J., Edler, D., and Rosvall, M. (2020). Mapping flows on sparse networks with missing
links. Phys. Rev. E 102, 012302. doi: 10.1103/PhysRevE.102.012302.

Smiljanić, J., C. Blöcker, A. Holmgren, D. Edler, M. Neuman, and M. Rosvall. 2023: Community
Detection with the Map Equation and Infomap: Theory and Applications. arXiv. doi:
10.48550/arXiv.2311.04036

Smith, S. M., Sprain, C. J., Clemens, W. A., Lofgren, D. L., Renne, P. R., and Wilson, G. P. (2018).
Early mammalian recovery after the end-Cretaceous mass extinction: A high-resolution view from
McGuire Creek area, Montana, USA. GSA Bulletin. doi: 10.1130/B31926.1.

Swain, A., S. A. Maccracken, W. F. Fagan, and C. C. Labandeira. 2022: Understanding the ecology
of host plant–insect herbivore interactions in the fossil record through bipartite networks.
Paleobiology 48:239–260.

Viglietti, P. A., Rojas, A., Rosvall, M., Klimes, B., and Angielczyk, K. D. (2022). Network-based
biostratigraphy for the late Permian to mid- Triassic Beaufort Group (Karoo Supergroup) in South
Africa enhances biozone applicability and stratigraphic correlation. Palaeontology 65. doi:
10.1111/pala.12622.

Vinh, N. X., Epps, J., and Bailey, J. (2009). Information theoretic measures for clusterings
comparison: is a correction for chance necessary? in Proceedings of the 26th Annual International
Conference on Machine Learning - ICML '09 (Montreal, Quebec, Canada: ACM Press), 1–8. doi:
10.1145/1553374.1553511.

Williams, J. W., Grimm, E. C., Blois, J. L., et al. (2018). The Neotoma Paleoecology Database, a
multiproxy, international, community-curated data resource. Quat. res. 89, 156–177. doi:
10.1017/qua.2017.105.

Ye, F., Shi, G. R., and Bitner, M. A. (2021). Global biogeography of living brachiopods:
Bioregionalization patterns and possible controls. PLoS ONE 16, e0259004. doi:
10.1371/journal.pone.0259004.

Data Availability Statement

Data for this study are available in the Dryad Digital Repository:
https://doi.org/10.5061/dryad.sj3tx967z.

Figures captions

Figure 1. Network representations of geohistorical data. **A.** The physical fossil record. These
brachiopod shells aim to represent the benthic macrofauna from the R/V Pillsbury program in the
Caribbean. Modified from Rojas et al. (2022, fig. 2). **B**. A network representation of the physical
record. This bipartite network is an abstracted representation of the underlying data (sampling
stations × taxa matrix) (Rojas et al. 2015)(Supplementary Data 1). The brachiopod *Tichosina*, the
larger component of the Cenozoic brachiopod faunas in the Caribbean, is indicated. **C.** Modular
structure delineated via community detection with the Map Equation framework and using a Markov
Time = 2 (Kheirkhahzadeh et al. 2016) (Supplementary Data 2). Modules include sampling stations
and taxa. Nodes are rearranged in the circular layout by their module affiliation. Only the two larger
modules, representing 98% of the network flow (see Table 1), are displayed. **D**. Modules mapped on
a Detrended Correspondence Analysis (DCA) ordination space. E. Small example showing a bipartite
network (1B) partitioned into two modules.

Figure 2. Input and output formats. -The Map Equation framework understands different formats. A.
Input file in Pajek format. B. Output file. The resulting partition is written to a file with the extension
.tree (plain text file). The formats described here correspond to the small example network in Figure
1E.

Figure 3. Network representations of geohistorical data. A. Temporal occurrence data. B. Standard
bipartite network representation created by aggregating fossil occurrences (sp. 1) into arbitrary
spatiotemporally explicit units (g1 to g4). This standard network uses the same nodes to represent the
physical components of the system as well as to describe system's flows (see Table 1). A random
walk as the simplest information flow model forms paths across independent pairwise links on this
network washing out higher-order node interactions. C. Multilayer network representation. The Map
Equation framework for higher-order networks distinguishes physical nodes that represent the
system's components from state nodes describing the system's internal flows. This higher-order
network better captures the constraints on the information paths and thus flows tend to stay among
units from each layer.

Figure 4. The notion of multiple fossil records in modern paleobiology research. A major conceptual
change in modern paleobiology research has been the distinction between the physical fossil record,
consisting of specimens, and the abstracted fossil record derived from this physical record (Allmon et
al. 2018). The concept of the abstracted fossil record was first introduced to highlight the extensive
data already stored in paleontological databases (Sepkoski 2013). This major shift in paleobiology
research represents a transition from a specimen-based discipline to its current status as a data-driven
field (Dillon et al. 2023). Here we argue that a new major conceptual change in paleobiology has
emerged from the growing body of network-based studies that consider network representations of
fossil data as abstracted records. From a given physical fossil record and associated data,
paleobiologists can build different abstract records that capture different aspects of the underlying
system.

1002

Figure 5. Different network representations capture different aspects of the benchmark data on the
Phanerozoic benthic marine faunas (Peters and McClennen 2016). Bipartite and unipartite
representations ignore the temporal constraints inherent to the biosedimentary record. *Unipartite
projection obtained from the bipartite network by rescaling the Markov time (Kheirkhahzadeh et al.
2016). Alluvial diagram representing 98% of the network flow in each case (Supplementary Data 3-
7).

Figure 6. Schematic diagram illustrating a hypergraph representation of fossil occurrence data. In
this diagram, observable entities are fossil taxa, represented by shapes of different sizes, connected
through hyperlinks. Hyperlinks are depicted with boxes of different colors connecting all taxa
(species 1 to 9) occurring at the same time interval. In the Map Equation framework, occurrences of a
given taxa at different time intervals are modeled as state nodes, which are depicted here with
different shades of grey.

Figure 7. Infomap Network Navigator. **A.** Graphical Features. Modules are represented as circles,
with areas proportional to the internal flow and border widths proportional to the exiting flow;
aggregated bidirectional inter-module links are shown with widths proportional to inter-module flow
and lengths inversely proportional to it. **B**. Real Case Example. Stylized network navigator output
illustrating the large-scale modular structure of Phanerozoic benthic marine faunas, based on data
from Rojas et al. (2021).

Figure 8. Visualizing change in network partitions using alluvial diagrams. To compare networks
with the same sets of nodes, we assemble at least two network partitions. **A**. Then, we group nodes in
the same module in stacked bars with height proportional to the flow volume of each node and
connect corresponding nodes with streamlines. **B**. Finally, to highlight how the partitions change, we
aggregate the nodes into modules. **C**. To compare additional network partitions, we add more stacks
of bars to the right and repeat the procedure b-c.

Figure 9. A. Quality of alternative partitions of the multilayer network representing the Phanerozoic
fossil record of the benthic marine faunas mapped in a two-dimensional space. Circles represent
clusters of network partitions, located at the cluster center, with size proportional to the number of
partitions grouped into the cluster. Map isolines are constructed using the Jaccard distance between
partitions. Despite differences in their quality (codelength), all partition clusters identified at the
selected scale show a similar modular structure

Figure 10. **A**. A multilayer network representing litho-biofacies from Late Ordovician outcrops in
central Kentucky. In this higher order network, one layer describes the biotic component (samples ×
taxa matrix) and the other describes the abiotic component (samples × environments matrix) of the
geohistorical record (Supplementary Data 8). **B**. Litho-biofacies delineated via community detection
using the Map Equation framework. Modules in the multilayer solution include taxa, samples, and
environments, and can be directly interpreted as litho-biofacies (Supplementary Data 9). **C**.
Detrended Component Analysis (DCA) on the samples × taxa matrix. Network modules mapped in a
DCA ordination space indicating their distribution along the depth water gradient. Background
colored based on the module affiliation. Data from Holland and Patzkowsky (2004).

Figure 11. Bioregionalization of the Middle Devonian Old World Realm. **A**. Varying Markov time
models on the biogeographic network constructed from brachiopod occurrence data (Penn-Clarke and
Harper 2020). Network partitions at different Markov times reveal the larger-scale biogeographic
structures obtained at different resolutions. **B.** Network partition obtained at the Markov time 1 (7

modules). Circles represent the seven modules delineated when exploring the one-step dynamics on
the assembled network. **C.** Modules obtained from partitions at Markov times 1.30 and 1.35 (3
modules) mapped on those obtained at the Markov time 1. These two partitions differ in the
affiliation of the Southern Peru locality, placed alternatively into the modules representing higher
(white) and lower (orange) latitudes. Overall, coarser partitions contain fewer clusters as the Markov
time increases.

Table captions

Table 1. Glossary of terms related to the Map Equation framework in the context of network-based
paleobiology research.

Table 2. Comparison of the modular structure of different network representations of the benchmark
data on the Phanerozoic marine faunas. The multilayer representation achieves the shortest
codelength and the best compression. For each partition, we measure the compression by using the
corresponding one-level partition as a baseline. *Unipartite projection obtained from the bipartite
network by rescaling the Markov time (Kheirkhahzadeh et al. 2016).