DeepBIO: An automated and interpretable deep-learning platform for high-throughput biological sequence prediction, functional annotation, and visualization analysis

Ruheng Wang[1,2#], Yi Jiang[1,2#], Junru Jin[1,2#], Chenglin Yin[1,2#], Haoqing Yu[1,2], Fengsheng Wang[1,2], Jiuxin Feng[1,2], Ran Su[3], Kenta Nakai[4], Quan Zou[5*], and Leyi Wei[1,2*]

[1]School of Software, Shandong University, Jinan, China;

[2]Joint SDU-NTU Centre for Artificial Intelligence Research (C-FAIR), Shandong University, Jinan, China;

[3]College of Intelligence and Computing, Tianjin University, Tianjin, China;

[4]Human Genome Center, Institute of Medical Science, University of Tokyo, Tokyo, Japan;

[5]Institute of Fundamental and Frontier Sciences, University of Electronic Science and Technology of China, Chengdu, China.

[#]These authors contributed equally to this work as first authors.

[*]Corresponding authors:

Q.Z: zouquan@nclab.net

L.W: weileyi@sdu.edu.cn

Abstract

Here, we present DeepBIO, the first-of-its-kind automated and interpretable deep-learning platform for high-throughput biological sequence functional analysis. DeepBIO is a one-stop-shop web service that enables researchers to develop new deep-learning architectures to answer any biological question. Specifically, given any biological sequence data, DeepBIO supports a total of 42 state-of-the-art deep-learning algorithms for model training, comparison, optimization, and evaluation in a fully automated pipeline. DeepBIO provides a comprehensive result visualization analysis for predictive models covering several aspects, such as model interpretability, feature analysis, functional sequential region discovery, *etc*. Additionally, DeepBIO supports 9 base-level functional annotation tasks using deep-learning architectures, with comprehensive interpretations and graphical visualizations to validate the reliability of annotated sites. Empowered by high-performance computers, DeepBIO allows ultra-fast prediction with up to million-scale sequence data in a few hours, demonstrating its usability in real application scenarios. Case study results show that DeepBIO provides an accurate, robust, and interpretable prediction, demonstrating the power of deep learning in biological sequence functional analysis. Overall, we expect DeepBIO to ensure the reproducibility of deep-learning biological sequence analysis, lessen the programming and hardware burden for biologists, and provide meaningful functional insights at both sequence-level and base-level from biological sequences alone. DeepBIO is publicly available at http://inner.wei-group.net/DeepBIO.

Introduction

The development of next-generation sequencing techniques has led to an exponential increase in the amount of biological sequence data accessible, including genomic, transcriptomic, and proteomic sequences, *etc*. It naturally poses an important challenge - how to build the relationships from sequences to structures and functions (1). Given such large-scale data, traditional wet-lab experimental methods are laborious, time-consuming, and high-cost for functional analysis. Alternatively, the booming development of machine learning approaches has paved a new way to understand the complex mapping from biological sequences to their structures and functional mechanisms. Over the past few decades, data-driven machine learning approaches have emerged as powerful methods to enable the automated and fast function prediction ab initio from sequences alone, providing a new perspective on studying the functional aspects of biological sequences (2-5).

The increasing use of machine-learning workflows in biological sequence analysis and the willingness to disseminate trained machine learning models have pushed computer scientists to design more user-friendly solutions. In recent years, there is an increasing number of web servers and software packages developed for this purpose. For instance, BioSeq-Analysis is the first platform to analyze various biological sequences via machine learning approaches (6). Later, Liu et al. established BioSeq-Analysis2.0 (7) to automatically generate various predictors for biological sequence analysis at both residue level and sequence level. Additionally, iLearnplus is a popular platform that provides a pipeline for biological sequence

analysis, which comprises feature extraction and selection, model construction, and analysis

of prediction results (8). More recently, Liu et al. developed BioSeq-BLM, a web platform that

introduces different biological language models for DNA, RNA and protein sequence analysis

(9). Besides, other representative tools include iFeatureOmega (10), Rcpi (11), and protr (12),

etc. The platforms and tools have boosted the use of machine learning solutions for biological

sequence analysis tasks in biology. However, these traditional machine-learning workflows

have some drawbacks. For instance, to train a good model, strong professional knowledge is

usually required in terms of designing feature descriptors, selecting machine learning

algorithms, as well as setting up the model parameters, which limit their usability in real

applications to some extent; on the other hand, they cannot support large-scale prediction and

analysis. Recently, deep learning has played a complementary role over traditional machine

learning due to its excellent scalability and adaptivity. Therefore, some deep-learning analysis

tools have been developed, such as Kipoi (13), Pysster (14), and Selene (15). Kipoi (13) is a

repository of ready-to-use trained models for genomic data analysis. Pysster (14) is a Python

package that supports training deep-learning models only with convolutional neural networks

on biological sequence data. More recently, Chen et al. developed Selene, a PyTorch-based

deep-learning library for quick and simple development, training, and application of

deep-learning model architectures for biological sequence data (15).

These tools make the use of deep learning more convenient for data-driven biological

sequence analysis to some extent. However, there remain some key challenges that need to

be addressed. First, despite the availability of deep-learning tools, they are not completely

automated. Running the tools still faces some technical challenges for non-expert researchers.

On one hand, it requires strong professional knowledge and programming skills to set up

sophisticated software, which directly limits the generic use of deep learning in nonexpert

communities (i.e., researchers without any computer science training). On the other hand, it is

extremely difficult for researchers to train deep-learning models with the enormous scale of

data space, since the major downside of deep learning is its computational intensity, requiring

high-performance computational resources and long training time. Accordingly, a web platform

that enables an automated deep-learning pipeline is highly required. Second, most of the

existing tools cannot meet the high demand of the research community, since they provide few

deep-learning architectures (seen in **Supplementary Table 1**), such as convolutional neural

networks, for model construction. In fact, there are some state-of-the-art deep-learning models

with successful applications in bioinformatics problems. For example, Graph Neural Networks

demonstrated their ability to address complex biological problems, for example, the prediction

of microRNA-disease interaction (16). Large-scale language pre-trained models like

DNABERT and ProtBERT, showed strong capacities in discriminative feature learning in

biological sequence analysis (5,17). Thus, it is necessary to enable the use of state-of-the-art

deep-learning approaches in biology. Ultimately, existing tools lack comprehensive result

analysis, which might limit users' understanding of what the deep-learning models learn; how

reliable the deep-learning predictions are; and why the deep learning performs well.

In this work, we present DeepBIO, an automated deep-learning platform for biological

sequence prediction, functional annotation, and result visualization analysis. To be specific,

our DeepBIO distinguishes itself from other platforms with the following unique advantages: **(1)**
One-stop-shop service. DeepBIO is the first-of-its-kind platform as a code-free web portal to
ensure the reproducibility of deep-learning biological sequence analysis and to lessen the
programming burden for biologists. **(2) Pure deep-learning platform.** DeepBIO is a purely
deep-learning platform that integrates over 40 state-of-the-art mainstream deep-learning
algorithms, including convolutional neural networks, advanced natural language processing
models, and graph neural networks (detailed in **Supplementary Table 2**), which enables
researchers of interest to train, compare, and evaluate different architectures on any biological
sequence data. **(3) Two predictive modules.** DeepBIO is the first platform that supports not
only sequence-level function prediction for any biological sequence data, but also allows 9
base-level functional annotation tasks using pre-trained deep-learning architectures, covering
DNA methylation, RNA methylation, and protein-binding specificity. Besides, we further offer
an in-depth comparative analysis between the predictions by our models and by experimental
data to validate the reliability of the predictions. Notably, empowered by high-performance
computers, we demonstrate that DeepBIO supports fast prediction with up to million-scale
sequence data, demonstrating its usability in real application scenarios. **(4) Comprehensive**
result visualization analysis. Aiming to help researchers to dig into more insights from the
model predictions, DeepBIO offers a comprehensive visualization result analysis with a variety
of interactive figures and tables, covering the following five aspects: statistics analysis of input
data; prediction models' performance evaluation and comparison; feature importance and
interpretable analysis; model parameter analysis; and sequence conservation analysis. In
particular, integrating interpretable mechanisms (*e.g.*, attention heatmap, and motif discovery)
into deep-learning frameworks enables researchers to analyze which sequential regions are
important for the predictions, addressing the issue of the "black box" in deep learning and
effectively building the relationship between biological sequences to functions.
129

Materials and Methods

The overall framework of DeepBIO
The DeepBIO platform fully automates the model training process and applies more than forty
deep-learning approaches for sequence classification prediction and functional site analysis
based on genomic and proteomic data. **Figure 1A** illustrates the overall framework of the
proposed DeepBIO, which consists of four modules: (1) Data input module, (2) Deep-learning
prediction module, (3) Sequence functional annotation module, and (4) Result report module.
The workflow of DeepBIO is described as follows. Firstly, DeepBIO takes biological sequence
data from the data input module, where we can handle three biological sequence types
including DNA, RNA, and protein. Next, there are two functional modules for two types of tasks
respectively; one is the deep-learning prediction module for binary classification tasks, and the
other is the sequence functional annotation module for functional annotation tasks. The
detailed web techniques and the overview of the interaction between the front end and back
end are shown in **Figure 1B**. In the deep-learning prediction module, we support users in
automatically training, evaluating, and comparing the deep-learning models with their input
data. Specifically, there are four main steps (seen in **Figure 1C**) in this module: (I) Data
pre-processing, (II) Model construction, (III) Model evaluation, and (IV) Visualization analysis.

In the functional annotation module, we provide the base-level functional annotation using
deep-learning approaches, such as DNA methylation, RNA methylation, and protein-binding
specificity prediction. Similarly, we also curated four steps for this module (seen in **Figure 1C**):
(I) Data selection, (II) Task selection, (III) Model loading, and (IV) Result visualization.
Ultimately, in Result report module, we provide a series of visualizatioin analysis results with
various kinds of data formats. Below, we emphasize the details of the four modules.

Figure 1. **The organization of the DeepBIO platform**. **(A)** The architecture of the DeepBIO
platform. DeepBIO contains four modules, including the data input module, the deep-learning
prediction module, the sequence functional annotation module, and the result report module.
DeepBIO accepts DNA, RNA, and protein sequence data from the data input module, with
some additional user-selectable settings (*e.g*., sequence similarity setting, imbalanced data
processing, and data augmentation). The deep-learning prediction module provides the

deep-learning biological sequence binary classification service while the sequence functional annotation module supports the prediction of functional sites for user-provided sequences. In the result report module, DeepBIO provides user-friendly, interactive, and interpretable visualization representations to deliver results of the above two functional modules as a download-free report. **(B)** The web technique of DeepBIO and an overview of the framework. **(C)** The workflow of two main functional modules. The deep-learning prediction module consists of four steps: (I) Data pre-processing, (II) Model construction, (III) Model evaluation, and (IV) Visualization analysis. DeepBIO outputs classification predictions of input sequences based on the four steps and displays the result reports with interactive graphs and tables; The sequence functional annotation module includes the following steps: (I) Data selection, (II) Task selection, (III) Model loading, and (IV) Result visualization. DeepBIO offers multiple methylation annotations for DNA and RNA sequences while supporting ligand-binding site recognition for protein sequences.

Data input module

DeepBIO serves as an automatically integrated analysis platform based on biological sequence data, including DNA, RNA, and protein, which can be entered in the online input box or uploaded with the standard file format. Besides, users can select deep-learning models and different settings (*e.g.*, whether to turn on the data enhancement option). After obtaining the user's input data, DeepBIO further performs data cleaning to ensure that the user input data is ready and legal to pass into the next module and run properly.

Deep-learning prediction module

Step 1. Data pre-processing. This step is an optimization-based data processing phase that uses a variety of approaches to handle and obtain the input sequence data that is suitable for model training, ensuring the robustness of the final results and improving the success rate of our service. We design four sections to pre-process the input data: (I) Sequence legitimacy testing, (II) Sequence similarity setting, (III) Imbalanced data processing, and (IV) Data augmentation. In Section (I), for the input sequence data, we first examine whether the input data has the legal data format (*e.g.*, FASTA), and then check if the input sequences contain illegal characters (*e.g.*, other characters except for A, T, C, G in DNA sequences). In Section (II), considering that the high sequence similarity in the input data might lead to the performance evaluation bias, we thus provide a commonly used tool named CD-HIT (18) to reduce the sequence similarity in the input data. The similarity threshold ranges from 0.7 to 1. In Section (III), considering that a majority of datasets in real scenarios might exist the data imbalance issue (i.e., the number of the positives and negatives are extremely imbalanced), we further provide several imbalanced data processing strategies that are commonly used in the machine learning field, including Focal loss (19), Synthetic Minority Oversampling Technique (SMOTE) (20), and Adaptive Synthetic (ADASYN) (21). By doing so, we can prevent the biased prediction of models due to the imbalanced data distribution and perhaps achieve the improvement in the overall predictive performance . Finally, in Section (IV), to deal with the few sample learning problem, we further provide some data augmentation methods, such as sequence replacement, sequence flipping, and sequence cropping, etc, which can improve the robustness and generalization ability of the deep-learning models.

Step 2. Model construction. The pre-processed sequence data is then fed into user-selected
models to train and make the binary prediction. For the scenario that users do not provide
sequence data with training and testing labels, we randomly split the dataset into the training
and testing set by a ratio of 8:2 for model training and evaluation. **Table 1** summarizes all the
state-of-the-art deep-learning models in our platform. There are a total of 42 deep-learning
models, covering classic deep-learning methods (*e.g.*, Deep Neural Networks (DNN), and
Gate Recurrent Unit (GRU), *etc*), Natural Language Processing (NLP) methods (*e.g.*,
Transformer, and Bidirectional Encoder Representations from Transformers (BERT), etc.), and
Graph Neural Network (GNN) methods (*e.g.*, Graph Convolutional Network (GCN)). Notably,
each of the above models can be exploited to deal with all three types (DNA, RNA, and protein)
of sequence analysis tasks. In addition, DeepBIO permits users to select multiple models, train,
and compare their performance on the same datasets. It's worth noting that we have also
deployed several deep-learning models (*e.g.*, DNABERT, RNABERT, and ProtBERT) that are
well pre-trained on large-scale biological background sequences. They can be utilized for
fine-tuning the models on small datasets, if necessary, to alleviate the overfitting problem and
increase the models' generalization capability.

Table 1. Deep-learning models in DeepBIO.

Category	Methods	Refs.
Classic deep-learning methods	DNN	(22)
	RNN	(23)
	LSTM	(24)
	BiLSTM	(25)
	LSTM-Attention	(26)
	GRU	(27)
	TextCNN	(28)
	TextRCNN	(29)
	VDCNN	(30)
	RNN-CNN	(31)
Natural language processing methods	Transformer	(32)
	Reformer	(33)
	Performer	(34)
	Linformer	(35)
	RoutingTransformer	(36)
	DNABERT, RNABERT, ProtBERT	(5,17)
	BERT-Base	(37)
	BERT-CNN	(38)
	BERT-DPCNN	(39)
	BERT-RCNN	(40)
	BERT-RNN	(41)
	ERNIE	(42)

	GCN	(43)
	TextGCN	(44)
	GIN	(45)
	GAT	(46)
	GraphSage	(47)
	ChebGCN	(48)
	RECT-L	(49)
	LightGCN	(50)
Graph neural	GNN-FILM	(51)
network methods	HYPER-Conv	(52)
	HYPER-Attention	(53)
	APPNP	(54)
	TextRGNN	(55)
	TextSGC	(56)
	BertGCN	(57)
	BertGAT	(58)
	RoBERTaGCN	(59)
	RoBERTaGAT	(60)

224 **Step 3. Model evaluation.** For the performance comparison of deep-learning models, we

225 choose several commonly used evaluation metrics, including Sensitivity (SN), Specificity (SP),

226 Accuracy (ACC), and Matthews' Correlation Coefficient (MCC). The formulas of these metrics

227 are described as follows:

$$SN = \frac{TP}{TP+FN} \quad \#(1)$$

$$SP = \frac{TN}{TN+FP} \#(2)$$

$$ACC = \frac{TP+TN}{TP+TN+FP+FN} \#(3)$$

$$MCC = \frac{TP \times TN - FP \times FN}{\sqrt{(TP+FP)(TP+FN)(TN+FP)(TN+FN)}} \quad \#(4)$$

where TP, FP, TN, and FN represent the numbers of true positives, false positives, true

negatives, and false negatives, respectively. For the comprehensive performance comparison

of different models, the Area Under Receiver Operating Characteristic curve (AUC) and Area

Under Precision Recall Curve (AP), which range from 0 to 1, are calculated based on the ROC

curve and the PR curve, respectively. The ROC curve shows the proportion of true positives

versus false positives, in which the AUC equals the probability of ranking a randomly chosen

true target higher than a randomly chosen decoy target. The PR curve is used more frequently

to evaluate the performance of a model on imbalanced datasets (61). Similarly, we can

calculate the AP, which equals the average of the interpolated precisions. The higher the AUC
and AP values, the better the predictive performance of the underlying model.
239
Step 4. Visualization analysis. DeepBIO combines the prediction results and intermediate
data analysis generated from above, and helps users to better understand the input data
through the statistical analysis and the model results through various types of visualization
analyses. To provide users with intuitive and comprehensive result analysis, we design and
illustrate multiple visual presentation formats, including the pie plot, histogram, sequence logo
graph, ROC and PR curves, kernel density plot, and scatter plot. In **Table 2**, we present the
four sections of visualization analysis, which are dataset statistical analysis, result analysis,
feature analysis, and parameter optimization analysis. The details of each section are
described as follows.
249
For dataset statistical analysis, we summarize the overall status of the input datasets to assist
users in better comprehending the datasets themselves. There are the following three
statistical analyses, including sequence composition analysis, sequence motif analysis, and
the sequence-length distribution analysis. In sequence composition analysis, DeepBIO plots
the sequence composition histogram for the samples in the positive and negative dataset. In
sequence motif analysis, users can obtain the conservation of each position along the
sequences. Ultimately, the sequence-length distribution analysis provides users with the
length preference of the sequences in the dataset.
258
For result analysis, the DeepBIO visualization analysis includes plots considering all the
evaluation metrics presented in step 3, to conduct detailed performance comparisons among
different models, such as ROC and PR curves, the performance of different epochs, density
distribution of model prediction confidence, *etc*. Besides, we offer a Venn diagram and an
Upset plot to illustrate the relationship among different models from the overlapping prediction
results. It can be concluded that in this part users can get an intuitive comparison of prediction
performance for different deep-learning models.
266
For feature analysis, we use a dimensionality reduction tool called Uniform Manifold
Approximation and Projection (UMAP) (62) for feature space analysis, and a commonly used
tool Shapley Additive explanation (SHAP) (63) for feature importance analysis. UMAP can
map and visualize the high-dimensional features learned from the deep-learning models to the
low-dimensional space. It intuitively illustrates how good the learned features are. On the other
hand, SHAP gives a good explanation of the feature importance, which quantitively measures
the impact of each of the learned features on the predictive performance. Besides, for some
specific models like DNABERT and RNABERT, to further explore what the model learns, we
employ the attention heatmap to visualize the information the model captures from either
global or local perspectives. Furthermore, the motif discovery enables users to know the
conservative sequential determinants the models learn from the datasets. The details of the
motif discovery process are described as follows. Firstly, we apply the attention mechanism of
BERT-based models to identify key regions from the sequences. Then, for those identified
regions, we further extract and visualize the corresponding motifs using the attention scores

obtained from the model. In this way, we highlight the concerns of different models for different
features and enhance the interpretability of the deep-learning models.
283
For parameter optimization analysis, we provide users with some parameter options to make
their own choice to optimize the model training, including the effect of different sequence
similarities in datasets, the effect of different data augmentation strategies, and the effect of
different imbalanced data processing methods on predictive performance. Besides, we also
give some tabular information, including a summary of the input datasets and the performance
of deep-learning models. This helps the users to compare the results of the same model with
different parameters.
291
292

Table 2. Result visualization analysis in the prediction module.

Category	Type	Purpose
Statistical analysis	Pie plot	Sequence composition analysis
	Sequence statistics	Sequence statistical analysis from the datasets
	Histogram	Sequence-length distribution analysis
Result analysis	ROC and PR curve	Performance of model prediction
	Line chart	Performance of different epochs of models
	Kernel density plot	Prediction confidence by different models
	Venn diagram and Upset plot	Overlap of prediction results of different models
Feature analysis	ROC and PR curve	Feature performance comparison between hand-crafted features and the feature learned by selected models
	UMAP plot	Feature analysis result by UMAP
	SHAP plot	Feature importance analysis by SHAP
	Attention heatmap	Feature representation attention analysis
	Motif discovery	The discovery of conservative sequence motifs by models
Parameter optimization analysis	ROC and PR curve, Histogram	The effect of different parameters (Sequence similarity setting, Data augmentation, and Imbalanced data processing) on predictive performance

Sequence functional annotation module

294
The sequence functional annotation module is to predict the functions of the biological
sequences at base level using deep learning. In this module, we provide 9 annotation tasks,
including the methylation annotation for DNA and RNA sequences, and the ligand-binding site
recognition for protein sequences. The module comprises four steps: Data selection, Task
selection, Model loading, and Result visualization. The details of this module are as follows.

Step 1. Data selection. In this step, DeepBIO provides users to upload the sequences they

want to annotate. Particularly, for the DNA methylation site prediction task, we support two

ways to input sequence data, that is (1) uploading sequence data by themselves, (2) and

selecting a segment of our preset human genome by choosing a specific cell line and

chromosome.

Step 2. Task selection. There are three types of functional annotation tasks: DNA methylation

site prediction, RNA methylation site prediction, and protein-ligand binding site prediction. For

DNA methylation site prediction, there are DNA N^4-methylcytosine (4mC) site prediction, DNA

5-hydroxymethylcytosine (5hmC) site prediction, and DNA N^6-methyladenine (6mA) site

prediction. For RNA methylation site prediction, there are RNA 5-hydroxymethylcytosine

(5hmC) site prediction, RNA N^6-methyladenosine (m6A) site prediction, and RNA N^4-

methylcytidine (m4C) site prediction. For protein-ligand binding site prediction, there are

DNA-binding site prediction, RNA-binding site prediction, and Peptide-binding site prediction.

Step3. Model loading. In this step, there are two modes for deep-learning model selection.

One is default and the other is customized. For the default mode, we provide several

deep-learning models that are well pre-trained with large-scale biological data, such as

DNABERT. The well-pre-trained models generally have good generalization ability and

achieve good performance for different downstream tasks. For the customized mode, we allow

users to upload the models they trained for the same tasks in the deep-learning prediction

module.

Step 4: Result visualization. In this part, we provide users with the in-depth annotation result

analysis based on the model predictions and biological experiment data (*e.g.*, histone

modification signals and protein 3D structural information). Specifically, for DNA, we designed

two visualization sections, including functional site annotation and integrative analysis. For

functional site annotation, we predict the functional sites that match the selected task type (*e.g.*,

DNA 4mC site prediction) and perform the model-predicted confidence of the corresponding

position. In the integrative analysis, we perform statistical analysis between the expression of

DNA methylation and different histone modification signals. For RNA, due to the constraint of

data, we only perform the functional site annotation section same as in DNA. In addition, for

protein, to intuitively show the binding site annotation results, we visualize and annotate the

binding residues on the 3D structure of a given protein sequence with PDB ID.

Result report module

We list the analysis results in the form of reports, which involve various kinds of data formats

from the results of the two main functional modules. The users can view or download freely all

of the result data and charts. Notably, each submitted task is immediately notified to the

corresponding user once it is completed.

Results and discussion

Case Study

We showcase real-world applications of DeepBIO with two bioinformatic scenarios: (1) the prediction of DNA 6mA methylation and (2) the prediction of the protein toxicity. We emphasize that the underlying objective is to illustrate how to use our platform for two such diverse applications, rather than securing the top predictive performance compared to the state-of-the-art methods.

DNA methylation is closely associated with a variety of key processes, ranging from genomic imprinting, and aging, to carcinogenesis (64). Therefore, for the task of the DNA 6mA methylation prediction, we use the *D.melanogaster* dataset with 11,191 methylation sequences (as positives) and 11,191 non-methylation sequences (as negatives) as an example dataset (65) for DNA sequence functional analysis. In addition, protein toxicity is closely related to most neurodegenerative diseases and accurate toxicity prediction leads to significant promotion in new drug design. We choose a protein toxicity benchmark dataset (66), select protein sequences between 50 and 1200 amino acids, and obtain the final example dataset with 3,379 toxic animal protein sequences (as positives) and 5,464 non-toxic animal protein sequences (as negatives) for protein functional analysis. With the two example datasets, we first randomly split them into the training set and testing set and then input them into our online platform to demonstrate the data analysis and various functions of DeepBIO. More details of the visualization results of the two cases are described below.

Dataset statistics

Figure 2 illustrates the dataset statistics of the protein toxicity dataset. The proportion and number of bases or amino acids in the dataset are counted and illustrated as a pie plot and composition histogram, respectively (**Figure 2A**), from which we can clearly see the difference between the positives and the negatives from the compositional perspective. In addition, we calculate and show the sequence length distribution (**Figure 2B**), which intuitively gives users the sequence-length preference in the datasets. For example, it can be seen from **Figure 2B** that positive samples are mainly distributed in the range of 50 to 150 amino acids, while the negative samples have a relatively even distribution. Furthermore, we use a motif analysis tool called Weblogo to generate the sequence motifs of the datasets, which enables users to analyze the composition and conservation at the sequence level (**Figure 2C**).

Figure 2. The statistical analysis on the protein toxicity dataset. (A) Sequence
compositions of positive and negative samples in the training and testing sets; **(B)** Sequence
length distribution of positive and negative samples in the training and testing sets; **(C)** Motifs
of sequence statistics from the training and testing sets.

Model prediction analysis

DeepBIO provides detailed analysis for users to interpret and show comprehensive
performance comparisons among different deep-learning models. Here, we select four models
(DNABERT, DNN, LSTM, and RNN) to train and compare their prediction performance on the
DNA methylation dataset. **Figure 3A** shows the performances of the compared models in
terms of ACC, Sensitivity, Specificity, AUC, and MCC. It can be seen that DNABERT
achieves the best performance with the ACC, Sensitivity, Specificity, AUC, and MCC of 0.921,
0.896, 0.946, 0.967, and 0.844, respectively. For a better evaluation of models, **Figure 3B**
illustrates the ROC and PR curves of the compared models. As seen in **Figure 3B**, DNABERT
achieved the highest AUC and AP values of 0.968 and 0.973, respectively, which further
confirms that DNABERT is better than the other compared models. To further study the
generalization ability of the compared models, we draw the epoch plot in **Figure 3C** to show
the trends of accuracy and calculation loss for each model during the training process. From
Figure 3C, it is easy to find that except for DNN, the accuracy of the other three models
(DNABERT, LSTM, and RNN) increases rapidly at first and then the accuracy curves get
smooth gradually. Meanwhile, their calculation losses converge to lower values, indicating that
these models are well trained and their predictions are reliable. It is worth noting that during
the training process, DNN always achieves relatively low accuracy, however with high
calculation loss on the example dataset (seen in **Figure 3C**). This indicates that it is not a good
and robust model after training. In addition, to intuitively show the relationship among different
models from their prediction results, we further provide an Upset plot and a Venn diagram in
Figure 3D-E. From **Figure 3D-E**, we can see that most positive samples are successfully
predicted from the overlapping predictions of the compared models. Moreover, to clearly
understand the prediction preference for each model, we visualize the density distribution of
the prediction confidence of different deep-learning models in **Figure 3F**. As can be seen,
DNN mainly focuses its prediction confidence on around 0.5, which is the center part of the

X-axis, illustrating its poor discrimination ability between positive and negative samples on the

example dataset. On the contrary, the other three models (DNABERT, LSTM, and RNN)

achieve higher prediction confidence both on positive and negative samples, indicating that

they possess better classification ability on the example dataset. The comparison results for

this part on the dataset of protein toxicity can be seen in **Supplementary Figures 1-6.**

Figure 3. The prediction result analysis from different models using DeepBIO. (A)

Performance comparison among different models in terms of ACC, Sensitivity, Specificity, AUC,

and MCC; **(B)** ROC and PR curves of different deep-learning models; **(C)** The trends of

performance and calculation loss with each epoch, showing ACC and loss change process on

different models; **(D-E)** Upset plot and Venn diagram to express the relationships of prediction

results for different models; **(F)** Density distribution of the prediction confidence for different

deep-learning models.

Feature analysis and visualization

To compare the features automatically learned by deep-learning models with the traditional hand-crafted features, we select some commonly used feature encodings, including Accumulated Nucleotide Frequency (ANF) (67), binary (68), Composition of K-spaced Nucleic Acid Pairs (CKSNAP) (69), and Dinucleotide Composition (DNC) (70,71) for nucleotide sequences, and show the prediction performance in terms of ACC, Sensitivity, Specificity, AUC, MCC, and AP in **Figure 4A-B**. It is worth noting that in **Figure 4A-B**, the compared deep-learning models except for DNN outperformed most of the traditional feature encodings, allowing us to easily conclude that the features learnt from the deep-learning methods generally are superior to hand-crafted features.

In addition, to intuitively evaluate the feature representations learnt from different deep-learning models, we employ UMAP to conduct the dimension reduction and feature visualization (**Figure 4C**). In **Figure 4C,** each point represents a sample in the dataset, and the positive and negative classes are distinguished by different colors. In this case, we can get a better sense of the classification ability of each model from the UMAP plot. Specifically, **Figure 4C** shows that compared with the other three models (DNABERT, LSTM, and RNN), the samples belonging to different classes in the feature space of DNN are almost connected, making it difficult to distinguish the positives from the negatives. Moreover, the samples of different classes are more clearly distributed in the feature space of DNABERT than in the feature space of RNN and LSTM. In addition, we also provide the SHAP plot (**Figure 4D**), trying to assign each feature a value of importance for the model prediction. Each row represents the SHAP value distributions of a feature, and the *X*-axis refers to the SHAP value, where the value of SHAP >0 shows that the prediction favors the positive class, and a value <0 indicates that the prediction tends to be of the negative class. The color of sample points in the figure indicates the corresponding feature value; redder points mean higher feature values, while bluer points indicate lower feature values. The features are sorted according to the sum of SHAP values incorporating all the samples in the dataset. Therefore, the SHAP plot shows the relationship between the value of features and their impact on the model prediction. From **Figure 4D** we can see that the high-dimension features play a predominant role for DNABERT and the top-ranked feature values in DNABERT are more easily distinguished in the color compared with other models, indicating that DNABERT performs better in feature representation learning.

To improve the interpretability of the deep-learning models, in **Figure 4E**, we calculate the importance of the base at each position on the user-given sequence from the attention matrix in the model and visualize it with normalized attention scores, enabling us to analyze which region the model considers more important for the prediction. To further study what the models learn from the training process, we extract the important regions with high attention scores through the attention mechanism of the models to find conservative sequence motifs in **Figure 4F** from the datasets, which might be related to biological functions. The detailed feature analysis results on the dataset of protein toxicity can be seen in **Supplementary Figures 7-9**.

Figure 4. The visualization of feature analysis and model interpretation using DeepBIO.
(A) Prediction performance comparison between deep-learning models and traditional
hand-crafted feature-based methods; **(B)** ROC and PR curves of deep-learning models and
traditional hand-crafted feature-based methods; **(C)** UMAP feature visualization results of
different deep-learning models; **(D)** SHAP feature importance analysis of different
deep-learning models; **(E)** Attention heatmap of the user-choosing biological sequence; **(F)**
Motif discovery by deep-learning models.

Functional annotation analysis

To intuitively illustrate in-depth annotation result analysis of biological sequences, we provide
users with functional site prediction and result visualization analysis as in **Figure 5**. As seen in
Figure 5A, we can predict DNA methylation sites with corresponding positions and prediction
confidences based on user-provided DNA sequences or a segment of our preset human
genome. In addition, if users select a segment from our preset human genome by choosing a
specific cell line and chromosome, we will display the statistical analysis between our DNA
methylation site predictions and relevant histone modification signals queried from the
database (**Figure 5B**), assisting in mining the potential relations between them. Moreover, for
protein sequence annotation tasks, we predict and visualize the binding site annotation results
on the 3D structure of the given protein sequence with its PDB ID. Specifically, **Figure 5C**

487 shows the protein-peptide binding site prediction results of an example protein (PDB ID
488 1a81A), and the residues in red color on the protein 3D structure indicate the protein-peptide
489 binding sites.
490

491
492 **Figure 5. The biological sequence functional annotation analysis using DeepBIO. (A)**
493 Prediction results of DNA methylation site annotation tasks; **(B)** Comparison and analysis
494 between the DNA methylation site prediction results and relevant histone modification signals;
495 **(C)** Prediction results of protein-binding site annotation tasks.
496

Webserver Implementation
DeepBIO is empowered by the professional high-performance graphic processing architecture
with million-scale calculating capability. Specifically, DeepBIO is deployed with Ubuntu 18.04
Linux system, multiple Intel Xeon Silver 4210R CPUs, 256GB RAM, hundreds of TB Solid
State Drive, and NVIDIA RTX 3090 GPU clusters. Unlike other online platforms that use CPU
for training models and making predictions, the models we provide are all trained and
evaluated based on GPU, which significantly reduces the computational time. It can be seen
from **Supplementary Table 3** that we can spend less time optimizing deep-learning models
and enable fast and accurate predictions. In addition, **Supplementary Figures 10-15** show
that we have carefully designed the front-end page to give users an interactive visualization of
the results while they can download each result graph freely. To be specific, we use React
framework to set up the user interface, Spring Boot framework for server implementation in the
back end, python and R programming languages for the model's construction and visualization,
and MySQL database to manage the data storage. Besides, to make a better Web experience
for users, we also constructed interactive graphs to visualize the analysis result on the front
page. Our platform can run stably on many browsers including Internet Explorer (≥v.7.0),
Mozilla Firefox, Microsoft Edge, Safari, and Google Chrome. In conclusion, with our DeepBIO
platform, data scientists and researchers limited by equipment resources can now employ
high-performance computers to tackle their most challenging work.
516

Availability of Data and Materials

518 As an online platform for biological sequence analysis, DeepBIO can be freely accessed
519 without registration via http://inner.wei-group.net/DeepBIO. All code used in data analysis and

520 preparation of the manuscript, alongside a description of necessary steps for reproducing
521 results, can be found in a GitHub repository accompanying this manuscript:
522 https://github.com/weilab-biology-analysis/DeepBIO.
523

Competing interests

525 The authors declare that they have no competing interests.
526

Author contributions

528 L.W. conceived the basic idea and designed the DeepBIO framework. R.W., Y.J, J.J., C.Y.,
529 H.Y., F.W., and J.F. set up the server and visualized the result analysis. Y.J., R.W., L.W., and
530 C.Y. designed the interface and tested the server. R.W., C.Y., J.J., Q.Z., and L.W. wrote the
531 manuscript. K.N., R.S., Q.Z., and L.W. revised the manuscript.
532

Funding

534 The work was supported by the Natural Science Foundation of China (Nos. 62071278 and
535 62250028).

Reference

1.   Larranaga, P., Calvo, B., Santana, R., Bielza, C., Galdiano, J., Inza, I., Lozano, J.A., Armananzas,
R., Santafe, G., Perez, A. *et al.* (2006) Machine learning in bioinformatics. *Brief Bioinform*, **7**,
86-112.
2.   Wang, R., Jin, J., Zou, Q., Nakai, K. and Wei, L. (2022) Predicting protein–peptide binding
residues via interpretable deep learning. *Bioinformatics*, **38**, 3351-3360.
3.   Jiang, Y., Wang, R., Feng, J., Jin, J., Liang, S., Li, Z., Yu, Y., Ma, A., Su, R., Zou, Q. *et al.* (2022)
Explainable deep graph learning accurately modeling the peptide secondary structure
prediction. *bioRxiv doi: https://www.biorxiv.org/content/10.1101/2022.06.09.495580v2, 10*
August 2022, preprint: not peer reviewed.
4.   Jin, J., Yu, Y., Wang, R., Zeng, X., Pang, C., Jiang, Y., Li, Z., Dai, Y., Su, R. and Zou, Q. (2022)
iDNA-ABF: multi-scale deep biological language learning model for the interpretable
prediction of DNA methylations. *Genome biology*, **23**, 1-23.
5.   Elnaggar, A., Heinzinger, M., Dallago, C., Rehawi, G., Wang, Y., Jones, L., Gibbs, T., Feher, T.,
Angerer, C., Steinegger, M. *et al.* (2021) ProtTrans: Towards Cracking the Language of Lifes
Code Through Self-Supervised Deep Learning and High Performance Computing. *IEEE*
Transactions on Pattern Analysis and Machine Intelligence, 1-1.
6.   Liu, B. (2019) BioSeq-Analysis: a platform for DNA, RNA and protein sequence analysis based
on machine learning approaches. *Briefings in bioinformatics*, **20**, 1280-1294.
7.   Liu, B., Gao, X. and Zhang, H. (2019) BioSeq-Analysis2. 0: an updated platform for analyzing
DNA, RNA and protein sequences at sequence level and residue level based on machine
learning approaches. *Nucleic acids research*, **47**, e127-e127.
8.   Chen, Z., Zhao, P., Li, C., Li, F., Xiang, D., Chen, Y.Z., Akutsu, T., Daly, R.J., Webb, G.I., Zhao, Q. *et*

al. (2021) iLearnPlus: a comprehensive and automated machine-learning platform for nucleic
acid and protein sequence analysis, prediction and visualization. *Nucleic Acids Res*, **49**, e60.
9.   Li, H.-L., Pang, Y.-H. and Liu, B. (2021) BioSeq-BLM: a platform for analyzing DNA, RNA and
protein sequences based on biological language models. *Nucleic acids research*, **49**,
e129-e129.
10. Chen, Z., Liu, X., Zhao, P., Li, C., Wang, Y., Li, F., Akutsu, T., Bain, C., Gasser, R.B., Li, J. *et al.*
(2022) iFeatureOmega: an integrative platform for engineering, visualization and analysis of
features from molecular sequences, structural and ligand data sets. *Nucleic Acids Research*,
50, W434-W447.
11. Cao, D.-S., Xiao, N., Xu, Q.-S. and Chen, A.F. (2015) Rcpi: R/Bioconductor package to generate
various descriptors of proteins, compounds and their interactions. *Bioinformatics*, **31**,
279-281.
12. Xiao, N., Cao, D.-S., Zhu, M.-F. and Xu, Q.-S. (2015) protr/ProtrWeb: R package and web server
for generating various numerical representation schemes of protein sequences.
Bioinformatics, **31**, 1857-1859.
13. Avsec, Ž., Kreuzhuber, R., Israeli, J., Xu, N., Cheng, J., Shrikumar, A., Banerjee, A., Kim, D.S.,
Beier, T. and Urban, L. (2019) The Kipoi repository accelerates community exchange and reuse
of predictive models for genomics. *Nature biotechnology*, **37**, 592-600.
14. Budach, S. and Marsico, A. (2018) Pysster: classification of biological sequences by learning
sequence and structure motifs with convolutional neural networks. *Bioinformatics*, **34**,
3035-3037.
15. Chen, K.M., Cofer, E.M., Zhou, J. and Troyanskaya, O.G. (2019) Selene: a PyTorch-based deep
learning library for sequence data. *Nature methods*, **16**, 315-318.
16. Li, C., Liu, H., Hu, Q., Que, J. and Yao, J. (2019) A novel computational model for predicting
microRNA–disease associations based on heterogeneous graph convolutional networks. *Cells*,
8, 977.
17. Ji, Y., Zhou, Z., Liu, H. and Davuluri, R.V. (2021) DNABERT: pre-trained Bidirectional Encoder
Representations from Transformers model for DNA-language in genome. *Bioinformatics*.
18. Li, W. and Godzik, A. (2006) Cd-hit: a fast program for clustering and comparing large sets of
protein or nucleotide sequences. *Bioinformatics*, **22**, 1658-1659.
19. Lin, T.-Y., Goyal, P., Girshick, R., He, K. and Dollár, P. (2017), *Proceedings of the IEEE*
international conference on computer vision, pp. 2980-2988.
20. Chawla, N.V., Bowyer, K.W., Hall, L.O. and Kegelmeyer, W.P. (2002) SMOTE: synthetic minority
over-sampling technique. *Journal of artificial intelligence research*, **16**, 321-357.
21. He, H., Bai, Y., Garcia, E.A. and Li, S. (2008), *2008 IEEE international joint conference on neural*
networks (IEEE world congress on computational intelligence). IEEE, pp. 1322-1328.
22. LeCun, Y., Bengio, Y. and Hinton, G. (2015) Deep learning. *nature*, **521**, 436-444.
23. Rumelhart, D.E., Hinton, G.E. and Williams, R.J. (1986) Learning representations by
back-propagating errors. *nature*, **323**, 533-536.
24. Hochreiter, S. and Schmidhuber, J. (1997) Long short-term memory. *Neural computation*, **9**,
1735-1780.
25. Graves, A. and Schmidhuber, J. (2005) Framewise phoneme classification with bidirectional
LSTM and other neural network architectures. *Neural networks*, **18**, 602-610.
26. Wang, Q. and Hao, Y. (2020) ALSTM: An attention-based long short-term memory framework

604		for knowledge base reasoning. *Neurocomputing*, **399**, 342-351.
605	27.	Dey, R. and Salem, F.M. (2017), *2017 IEEE 60th international midwest symposium on circuits*
606		*and systems (MWSCAS)*. IEEE, pp. 1597-1600.
607	28.	Dos Santos, C. and Gatti, M. (2014), *Proceedings of COLING 2014, the 25th International*
608		*Conference on Computational Linguistics: Technical Papers*, pp. 69-78.
609	29.	Lai, S., Xu, L., Liu, K. and Zhao, J. (2015), *Twenty-ninth AAAI conference on artificial*
610		*intelligence*.
611	30.	Simonyan, K. and Zisserman, A. (2015) Very deep convolutional networks for large-scale
612		image recognition. *arXiv doi: https://arxiv.org/abs/1409.1556, 10 April 2015, preprint: not*
613		*peer reviewed.*
614	31.	Wang, J., Yang, Y., Mao, J., Huang, Z., Huang, C. and Xu, W. (2016), *Proceedings of the IEEE*
615		*conference on computer vision and pattern recognition*, pp. 2285-2294.
616	32.	Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A.N., Kaiser, Ł. and
617		Polosukhin, I. (2017), *Advances in neural information processing systems*, pp. 5998-6008.
618	33.	Kitaev, N., Kaiser, Ł. and Levskaya, A. (2020), *Proceedings of ICLR*.
619	34.	Choromanski, K., Likhosherstov, V., Dohan, D., Song, X., Gane, A., Sarlos, T., Hawkins, P., Davis,
620		J., Mohiuddin, A. and Kaiser, L. (2022) Rethinking attention with performers. *arXiv doi:*
621		*https://arxiv.org/abs/2009.14794, 19 November 2022, preprint: not peer reviewed.*
622	35.	Wang, S., Li, B.Z., Khabsa, M., Fang, H. and Ma, H. (2020) Linformer: Self-attention with linear
623		complexity. *arXiv doi: https://arxiv.org/abs/2006.04768, 14 June 2020, preprint: not peer*
624		*reviewed.*
625	36.	Roy, A., Saffar, M., Vaswani, A. and Grangier, D. (2021) Efficient content-based sparse
626		attention with routing transformers. *Transactions of the Association for Computational*
627		*Linguistics*, **9**, 53-68.
628	37.	Devlin, J., Chang, M.-W., Lee, K. and Toutanova, K. (2019), *Proceedings of NAACL*, pp.
629		4171–4186.
630	38.	Safaya, A., Abdullatif, M. and Yuret, D. (2020), *Proceedings of the Fourteenth Workshop on*
631		*Semantic Evaluation*, pp. 2054-2059.
632	39.	Li, Y.-J., Zhang, H.-J., Pan, W.-M., Feng, R.-J. and Zhou, Z.-Y. (2021), *Artificial Intelligence in*
633		*China*. Springer, pp. 524-530.
634	40.	Nguyen, Q.T., Nguyen, T.L., Luong, N.H. and Ngo, Q.H. (2020), *2020 7th NAFOSTED Conference*
635		*on Information and Computer Science (NICS)*. IEEE, pp. 302-307.
636	41.	Huang, P., Zhu, H., Zheng, L. and Wang, Y. (2021), *2021 5th International Conference on*
637		*Natural Language Processing and Information Retrieval (NLPIR)*, pp. 1-7.
638	42.	Zhang, Z., Han, X., Liu, Z., Jiang, X., Sun, M. and Liu, Q. (2019), *Proceedings of the 57th Annual*
639		*Meeting of the Association for Computational Linguistics*, pp. 1441–1451.
640	43.	Kipf, T.N. and Welling, M.J.a.p.a. (2017), *International conference on learning representations*
641		*(ICLR '17)*.
642	44.	Zhu, J., Cui, Y., Liu, Y., Sun, H., Li, X., Pelger, M., Yang, T., Zhang, L., Zhang, R. and Zhao, H.
643		(2021), *Proceedings of the Web Conference 2021*, pp. 2848-2857.
644	45.	Chen, J., Xie, Y., Wang, K., Wang, Z.H., Lahoti, G., Zhang, C., Vannan, M.A., Wang, B. and Qian,
645		Z. (2018), *International Conference on Medical Image Computing and Computer-Assisted*
646		*Intervention*. Springer, pp. 537-545.
647	46.	Wang, K., Shen, W., Yang, Y., Quan, X. and Wang, R. (2020), *Proceedings of the 58th Annual*

648   *Meeting of the Association for Computational Linguistics*, pp. 3229–3238.

649   47.   Hamilton, W., Ying, Z. and Leskovec, J. (2017) Inductive representation learning on large
650   graphs. *Advances in neural information processing systems*, **30**.

651   48.   Defferrard, M., Bresson, X. and Vandergheynst, P. (2016) Convolutional neural networks on
652   graphs with fast localized spectral filtering. *Advances in neural information processing*
653   *systems*, **29**.

654   49.   Wang, Z., Ye, X., Wang, C., Cui, J. and Philip, S.Y. (2020) Network embedding with
655   completely-imbalanced labels. *IEEE Transactions on Knowledge and Data Engineering*, **33**,
656   3634-3647.

657   50.   He, X., Deng, K., Wang, X., Li, Y., Zhang, Y. and Wang, M. (2020), *Proceedings of the 43rd*
658   *International ACM SIGIR conference on research and development in Information Retrieval*,
659   pp. 639-648.

660   51.   Brockschmidt, M. (2020), *International Conference on Machine Learning*. PMLR, pp.
661   1144-1152.

662   52.   Ma, T., Dalca, A.V. and Sabuncu, M.R. (2022), *Proceedings of the IEEE/CVF Winter Conference*
663   *on Applications of Computer Vision*, pp. 1933-1942.

664   53.   Duan, W., He, X., Zhou, Z., Rao, H. and Thiele, L. (2021), *Interspeech 2021*, pp. 3216–3220.

665   54.   Klicpera, J., Bojchevski, A. and Günnemann, S. (2019), *7th International Conference on*
666   *Learning Representations*.

667   55.   Chen, J., Zhang, B., Xu, Y. and Wang, M. (2021) TextRGNN: Residual Graph Neural Networks
668   for Text Classification. *arXiv doi: https://arxiv.org/abs/2112.15060, 30 December 2021,*
669   *preprint: not peer reviewed*.

670   56.   Wu, F., Souza, A., Zhang, T., Fifty, C., Yu, T. and Weinberger, K. (2019), *International conference*
671   *on machine learning*. PMLR, pp. 6861-6871.

672   57.   Lin, Y., Meng, Y., Sun, X., Han, Q., Kuang, K., Li, J. and Wu, F. (2021), *Findings of the*
673   *Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 1456–1462.

674   58.   Veličković, P., Cucurull, G., Casanova, A., Romero, A., Lio, P. and Bengio, Y. (2018),
675   *International conference on learning representations*.

676   59.   Wei, M., He, Y. and Zhang, Q. (2020), *Proceedings of the 43rd International ACM SIGIR*
677   *Conference on Research and Development in Information Retrieval*, pp. 2367-2376.

678   60.   Chandra, S., Mishra, P., Yannakoudakis, H., Nimishakavi, M., Saeidi, M. and Shutova, E. (2020)
679   Graph-based modeling of online communities for fake news detection. *arXiv doi:*
680   *https://arxiv.org/abs/2008.06274, 23 November 2020, preprint: not peer reviewed.*

681   61.   Saito, T. and Rehmsmeier, M. (2015) The precision-recall plot is more informative than the
682   ROC plot when evaluating binary classifiers on imbalanced datasets. *PloS one*, **10**, e0118432.

683   62.   Becht, E., McInnes, L., Healy, J., Dutertre, C.-A., Kwok, I.W., Ng, L.G., Ginhoux, F. and Newell,
684   E.W. (2019) Dimensionality reduction for visualizing single-cell data using UMAP. *Nature*
685   *biotechnology*, **37**, 38-44.

686   63.   Lundberg, S.M. and Lee, S.-I. (2017), *Proceedings of the 31st international conference on*
687   *neural information processing systems*, pp. 4768-4777.

688   64.   Richardson, B.C. (2002) Role of DNA methylation in the regulation of cell function:
689   autoimmunity, aging and cancer. *The Journal of nutrition*, **132**, 2401S-2405S.

690   65.   Lv, H., Dao, F.-Y., Zhang, D., Guan, Z.-X., Yang, H., Su, W., Liu, M.-L., Ding, H., Chen, W. and Lin,
691   H. (2020) iDNA-MS: an integrated computational tool for detecting DNA modification sites in

multiple genomes. *Iscience*, **23**, 100991.

66.   Pan, X., Zuallaert, J., Wang, X., Shen, H.-B., Campos, E.P., Marushchak, D.O. and De Neve, W.

(2020) ToxDL: deep learning using primary structure and domain embeddings for assessing

protein toxicity. *Bioinformatics*, **36**, 5159-5168.

67.   Xu, H., Hu, R., Jia, P. and Zhao, Z. (2020) 6mA-Finder: a novel online tool for predicting DNA

N6-methyladenine sites in genomes. *Bioinformatics*, **36**, 3257-3259.

68.   Chen, Z., Chen, Y.-Z., Wang, X.-F., Wang, C., Yan, R.-X. and Zhang, Z. (2011) Prediction of

ubiquitination sites by using the composition of k-spaced amino acid pairs. *PloS one*, **6**,

e22930.

69.   Chen, Z., Zhao, P., Li, F., Marquez-Lago, T.T., Leier, A., Revote, J., Zhu, Y., Powell, D.R., Akutsu, T.

and Webb, G.I. (2020) iLearn: an integrated platform and meta-learner for feature

engineering, machine-learning analysis and modeling of DNA, RNA and protein sequence

data. *Briefings in bioinformatics*, **21**, 1047-1057.

70.   Liu, B., Liu, F., Wang, X., Chen, J., Fang, L. and Chou, K.-C. (2015) Pse-in-One: a web server for

generating various modes of pseudo components of DNA, RNA, and protein sequences.

Nucleic acids research, **43**, W65-W71.

71.   Liu, B., Liu, F., Fang, L., Wang, X. and Chou, K.-C. (2015) repDNA: a Python package to

generate various modes of feature vectors for DNA sequences by incorporating user-defined

physicochemical properties and sequence-order effects. *Bioinformatics*, **31**, 1307-1309.

711