OpenLabCluster: Active Learning Based Clustering and Classification of Animal Behaviors in Videos Based on Automatically Extracted Kinematic Body Keypoints

Jingyuan Li[1]   Moishe Keselman[2]   Eli Shlizerman[1,2]

[1]Department of Electrical and Computer Engineering,
[2]Department of Applied Mathematics,
University of Washington, Seattle, WA

Abstract

Quantifying natural behavior from video recordings is a key component in ethological studies. Markerless pose estimation methods have provided an important step toward that goal by automatically inferring kinematic body keypoints. The next step in behavior quantification is utilization of these features toward organizing and interpreting behavioral segments into states. In this work, we introduce a novel deep learning toolset to address this aim. In particular, we introduce OpenLabCluster which clusters segments into groups according to the similarity of kinematic body keypoints and then employs active learning approach which refines the clusters and classifies them into behavioral states. The active learning approach is an iterative semi-supervised deep learning methodology selecting representative examples of segments to be annotated such that the annotation informs clustering and classification of all segments. With these methodologies, OpenLabCluster contributes to faster and more accurate organization of behavioral segments with only a sparse number of them being annotated. We demonstrate OpenLabCluster performance on four different datasets, which include different animal species exhibiting natural behaviors, and show that it boosts clustering and classification compared to existing methods, even when all segments have been annotated. OpenLabCluster has been developed as an open-source interactive graphic interface which includes all necessary functions to perform clustering and classification, informs the scientist of the outcomes in each step, and incorporates the choices made by the scientist in further steps.

1   Introduction

Analysis and interpretation of animal behavior are essential for a multitude of biological investigations. Behavioral studies extend from ethological studies to behavioral essays as a means to investigate biological mechanisms [1, 2, 3, 4, 5, 6, 7]. In these studies, methodologies facilitating robust, uninterrupted, and high-resolution observations are key. Indeed, researchers have been recording animal behaviors for decades with various modalities, such as video, sound, placement of physical markers, and more [8, 9, 10, 11, 12, 13, 14]. Recent enhancements in recording technologies have extended the ability for the deployment of recording devices in various environments and for extended periods. The enhancement in the ability to perform longer observations and in the number of modalities, brings forward the need to organize, interpret and associate recordings with an identified repertoire of behaviors, i.e., perform classification of the recordings into behavioral states. Performing these operations manually would typically consume a significant amount of time and would require expertise. For many recordings, manual behavior classification becomes an unattainable task. It is therefore critical to develop methodologies to accelerate classification of behavioral states and require as little involvement from the empiricist as possible [15, 16, 17].

For video recordings, deep-learning-based methods classifying behaviors directly from the video frames (image-based) have been proposed [18, 19, 20, 21, 22]. While such methods could be effective for specific scenarios, they are prone either lower accuracy. This is due to video footage including noise (e.g. camera artifacts) and extra information unrelated to behavior (e.g. background). To address

Figure 1: OpenLabCluster overview. (1) Clustering: Input of body keypoints segments is mapped to low dimensional space. Unsupervised encoder-decoder maps them to a Cluster Map. (2) Classification: Active Learning algorithms automatically select candidates for annotation after which Cluster Map is reshaped into the Behavior Classification Map where each point is associated with a behavioral state (Grooming (red), Hanging (blue), Rearing (blue)). Mouse images are reproduced from frames of videos provided in the dataset of [18].

these challenges, the methods have been extended to include image transformation techniques during training or have been accompanied with additional modalities, such as audio [23, 24, 14]. However, for general videos, background interference still presents itself as a significant challenge leading to non-robust performance. In addition, image-based methods are computationally expensive since operate with a high-dimensional input of the full video frame or a sequence of frames, and include multiple computational layers to narrow down this information to behavioral classification [21]. Furthermore, one of the most critical drawbacks of direct image-based approaches is that they are typically not generalizable across animal species and experimental setups.

In contrast, methods that focus on movements, utilizing body keypoints or kinematics extracted from video frames, could avoid these challenges [25, 26, 27, 28]. Automatic detection of body keypoints, *markerless pose estimation*, is especially advantageous since there is no need for physical markers. Indeed, several open-source packages for markerless pose estimation with admissible accuracy for general videos are readily available. Popular examples include OpenPose [29], an open-source package that performs human pose estimation, DeepLabCut [30, 31], an open-source package for estimation of animal keypoints. DeepLabCut includes an adaption of a pre-trained model to the particular video and keypoints which allows it to perform animal pose estimation across various species. Extensions and improvements of DeepLabCut, such as DeepLabCut 2+, enabling 3D pose estimation, better accuracy, and multi-animal pose estimation have been recently made available and in further development [32, 33]. Furthermore, additional approaches which address animal pose estimation have been introduced and are further developed [34, 35, 36, 37, 38, 39, 40].

Organization of such body keypoints time series into behavioral classes consists of two complementary tasks. The first task is *clustering*, in which recorded segments are mapped into groups according to the similarity of behavior that the segments represent. In such a map, segments that represent similar behavioral states would be located close to each other while segments that represent distinct behavioral states would be mapped farther from each other [2, 41]. Algorithms for clustering are typically 'unsupervised', i.e., they do not rely on the annotation of the segments. Clustering could be

achieved by first computing compressed representations of the segments. Various methods compute these representations, ranging from classical approaches such as UMAP [42, 43, 44, 41] to deep-learning-based approaches, such as Predict&Cluster [45], variational deep-learning approaches, such as VAME [46], or autoregression hidden markov modeling [47]. These representations can be then formed into clusters with various approaches as well, such as KMeans [48], BDSCAN [49], or watershed transform [50, 51, 52]. Beyond clustering, it is desired to obtain semantic meaning and associate a label of a state with each behavioral segment. Such a task is the *classification* task and is performed by generating probability distribution for each segment with respect to the behavioral states [25, 28, 53]. Classification algorithms are typically 'supervised' since these algorithms require annotation, i.e., the association of behavioral labels (states) to segments, to be used in training. The accuracy of classification depends on the quality of the annotation and the number of annotated samples. Supervised classification approaches range from classical approaches such as KNN to deep-learning-based approaches [54, 55, 56]. In general, better classification accuracy would be obtained when more labels are provided. However, in practice, annotation is a time-consuming process and prone to errors since the quality and the interpretation will vary between annotators.

While classification does not require clustering, successful clustering can enhance the classification accuracy and reduce dependence on annotation. Indeed, in the case of a prior grouped segments into well-separated clusters, annotation of a single representative in each cluster would suffice to classify all segments. This is the guiding principle of 'semi-supervised' methods which employ both unsupervised and supervised approaches to minimize the annotation efforts while at the same time not undermining accuracy [57]. Semi-supervised methods propose to perform unsupervised pre-training as a way to transfer input data into latent representations which are used in conjunction with selecting a subset of segments for annotation to classify all segments together with pseudo labels [58, 59]. In practice, the selection of segments can significantly boost or diminish performance, and approaches minimizing the number of annotations and maximizing accuracy through systematic selection are warranted. Approaches for such selection are known as *active learning* methods and multiple works in various classification applications have shown that active learning can be applied to achieve such balance between accuracy and annotation [60, 61, 62, 63].

In this work, inspired by DeepLabCut [30, 32, 31] and associated projects in computational ethology, which provide a toolbox along with a graphic interface to the deep-learning approach applied to animal videos, we extend the semi-supervised methodology to animal behavior classification. In particular, we developed the OpenLabCluster toolset, a semi-supervised platform embedded in a graphic interface for animal behavior classification from body keypoints. The system implements and allows to work with multiple semi-supervised active learning methods. Active learning is performed in an iterative way, where, in each iteration, an automatic selection of a subset of candidate segments is chosen for annotation, which in turn enhance the accuracy of clustering and classification. OpenLabCluster is composed of two components illustrated in Fig. 1A: (1) Unsupervised deep encoder-decoder clustering of action segments generating low-dimensional *Cluster Maps* which depict the segments as points and show their groupings. (2) Iterative automatic selection of segments for annotation and subsequent generation of *Behavior Classification Maps*. In each iteration, each point in the Cluster Map is being re-positioned and associated with a behavioral class (colored with a color that corresponds to a particular class). These operations are performed through training of a clustering encoder-decoder (component (1)) along with a deep classifier (component (2)). OpenLabCluster implements these methodologies as an open-source graphical user interface (GUI) to empower scientists with little or no deep-learning expertise to perform animal behavior classification. In addition, OpenLabCluster includes advanced options for experts.

2 Results

Datasets. Behavioral states and their dynamics vary from species to species and from recordings to recordings. We use four different datasets to demonstrate OpenLabCluster applicability to various settings. The datasets include videos of behaviors of four different animal species (Mouse [18], Zebrafish [2], *C. elegans* [64], Monkey [36]) with three types of motion features (body keypoints, kinematics, segments),

Figure 2: Visualization of four animal behavior datasets. (A) Home-Cage mouse dataset (Mouse) (B) *C. elegans* Movement Dataset (*C. elegans*) (C) Zebrafish free swimming dataset (Zebrafish) (D) OpenMonkeyStudio Macaque behaviors dataset (Monkey). The top row shows positions of extracted keypoints for each dataset. Images sources: A. Images are reproduced from frames of videos in the dataset of [18]. B. Images are reproduced from Figure 1 and frames of videos of [2]. C. Images are reproduced from Supplementary Figure 1 and images of [64]. D. Images are reproduced from Figure 8 and images of [36].

as depicted in Fig. 2. Two of the datasets include apriori annotated behavioral states (ground truth) (Mouse, *C. elegans*), while the Zebrafish dataset includes ground truth a priori predicted by another method, and the Monkey dataset does not include ground truth annotations. Three of the datasets have been segmented into single-action clips (Mouse, Zebrafish, *C. elegans*), while the Monkey dataset is a continuous recording that requires segmentation into clips. We describe further details about each dataset below.

Home-Cage Mouse. The dataset includes video segments of 8 identified behavioral states [18]. In particular, it contains videos recorded by front cage cameras when the mouse is moving freely and exhibits natural behaviors, such as drinking, eating, grooming, hanging, micromovement, rearing, walking, resting. Since keypoints have not been provided in this dataset, we use DeepLabcut [30, 32, 31] to automatically mark and track eight body joint keypoints (snout, left-forelimb, right-forelimb, left-hindlimb, right-hindlimb, fore-body, hind-body, and tail) in all recorded videos frames. An example of estimated keypoints overlaid on top of the corresponding video frame is shown in Fig. 2A (top). To reduce the noise that could be induced by the pose estimation procedure, we only use the segments for which DeepLabCut estimation confidence is high enough. We use 8 sessions for training the models of clustering and classification (2856 segments) and test classification accuracy on 4 other sessions (393 segments).

Zebrafish. The dataset includes video footage of zebrafish movements and was utilized in [2] for unsupervised behavior clustering using 101 precomputed kinematic features, a procedure that identified 13 clusters which were manually related to 13 behavior prototypes (see Appendix 5.2). In the application of OpenLabCluster to this dataset, we utilize only a small subset of these features (16 features) and examine whether OpenLabCluster is able to generate classes aligned with the unsupervised clustering results obtained on full 101 features (as the ground truth). We use 5294 segments for training and 2781 segments for testing.

C. elegans. The dataset is recorded with Worm Tracker 2.0 when the worm is freely moving. The body contour is identified automatically using contrast to background from which kinematic features are calculated and constitute 98 features that correspond to body segments from head to tail in 2D coordinates, see [64] and Fig. 2C. Behavioral states are divided into three classes: moving forward, moving backward, and staying stationary. We use 10 sessions (a subset) to investigate the application of OpenLabCluster to this dataset, where the first 7 sessions (543 segments) are used for training and

the remaining 3 sessions (196 segments) are used for testing.

Monkey. This dataset is from OpenMonkeyStudio repository [36] and captures freely moving macaques in a large unconstrained environment using 64 cameras encircling an open enclosure. 3D keypoints positions are reconstructed from 2D images by applying deep neural network reconstruction algorithms on the multi-view images. Among the movements, 6 behavioral classes have been identified. In contrast to other datasets, this dataset consists of continuous recordings without segmentation into action clips. We thereby segment the videos by clipping them into fixed duration clips (10 frames with 30 fps rate) which results in 919 segments, where each segment is ≈ 0.33 seconds long. OpenLabCluster receives the 3D body key points of each segment as an input. Notably, a more advanced technology could be implemented to segment the videos as described in [65]. Here, we focused on examining the ability of OpenLabCluster to work with segments that have not been pre-analyzed and thus used the simplest and most direct segmentation method.

		Home-Cage Mouse Behavior (8 classes; Keypoints)			
	Labels (%)	5	10	20	100
	Labels (#)	143	286	571	2856
	KNN	40.9	41.9	52.0	56.6
	SVM	42.2	51.0	54.7	60.0
	C	55.2	54.1	64.5	71.5
OLC	CS	**65.3**(+10.1)	75.4	**82.2** (+17.7)	83.9
	Top	58.5	58.4	76.4	83.8
	MI	63.4	**76.3** (+22.2)	78.9	**84.2** (+12.7)

Table 1: Classification accuracy of Home-Cage Mouse behaviors for increasing number of annotated segments (reported as percentage (%)). Top: Accuracy of standard classification methods KNN, SVM, and C. Bottom: Accuracy of OpenLabCluster(OLC) using active learning approaches: CS, Top, and MI. Best accuracy is highlighted in boldface and the difference between it and best standard method is shown.

Evaluation Metrics. We evaluate the accuracy of OpenLabCluster by computing the percentage of segments in the test set that OpenLabCluster correctly associated with the states given as ground truth, such that 100% accuracy will indicate that OpenLabCluster correctly classified all segments in the test set. Since OpenLabCluster implements the semi-supervised approach to minimize the number of annotations, we compute the accuracy given annotation budgets of overall 5%, 10%, 20% labels to be used over the possible iterations in conjunction with active learning. In particular, we test the accuracy when the Top, CS, and MI active learning methods implemented in OpenLabCluster are used for selections of segments to annotate. In addition, we implement non-active learning methods such as K-Nearest Neighbour (KNN) [54], support vector machine (SVM) [66], Deep Classifier containing the encoder and the classifier components of OpenLabCluster without the decoder (C). The accuracy of these methods is used to OpenLabCluster against them.

Outcomes. The results of evaluation are shown in Tables 1 and 2 and further analysed in Fig. 3 and Fig. 4. We summarize the main outcomes of the evaluation and their interpretation below.

Accuracy of Classification. We observe that *the accuracy of classification of OpenLabCluster across datasets is consistently higher than standard supervised classification methods for almost any budget of annotation.* Specifically, for the Home-Cage Mouse Behavior dataset Table 1, OpenLabCluster (OLC) achieves accuracy of 65.3% when just 143 (5% of 2856) segments have been annotated. Accuracy improves along with the inscrease in the number of annotated segments, i.e., accuracy is 76.3% when 10% of segments are annotated, and 82.2% when 20% of segments are annotated. Overall, when compared to supervised approaches, the increase in accuracy is of $\approx 16\%$ on average. We observe that among different active learning methods, CS and MI, achieve comparable accuracy and both exceed the Top selection. Notably, while active learning is expected to be especially effective in sparse annotation scenarios, when all segments are annotated (fully supervised scenario) the accuracy of the OpenLabCluster MI approach exceeds supervised classification approaches by 12.7% (rightmost column

		Zebrafish (13 classes; Kinematics)				C. elegans (3 classes; Segments)			
	Labels (%)	5	10	20	100	5	10	20	100
	Labels (#)	265	530	1059	5294	27	55	109	543
	C	72.5	70	75.8	82.0	71.3	75.2	77.5	**94.8**
OLC	CS	71.9	76.6	79.6	83.2	73.5	64.3	75.4	92.8
	Top	72.0	77.1	80.1	**83.5**	76.5	76.5	**77.8** (+0.3)	93.4
	MI	**74.2**(+1.7)	**79.1**(+9.1)	**81.1**(+5.3)	83.3	**76.7**(+5.4)	**76.8**(+1.6)	77.0	93.4

Table 2: Classification accuracy of Zebrafish and *C. elegans* behaviors for increasing number of annotated segments (reported as percentage (%)). Top: Accuracy of standard classifier network, C. Bottom: Accuracy of OpenLabCluster(OLC) using various active learning approaches: CS, Top, and MI. Best accuracy is highlighted in boldface and the difference between it and best standard method is shown.

in Table 1). This reflects the effectiveness of the targeted selection of candidates for annotation and the use of clustering latent representation to enhance the overall organization of the segments.

For Zebrafish and *C. elegans* datasets, OpenLabCluster evaluation on sparse annotation scenarios (5% - 20%) exceeds the accuracy of a standard classifier. The improvements in accuracy are in the range of $0.3\% - 9.1\%$ and are not as extreme as for the Mouse dataset. These could be associated with not having manually identified ground truth behavior states for Zebrafish and having only 3 classes for the *C. elegans* dataset. Having such a small number of classes is relatively a simpler semantic task that does not challenge classifiers. We can indeed observe that when all annotations are considered in *C. elegans* dataset, all approaches perform well (above 92%) and a standard classifier achieves the best accuracy.

The Amount of Required Annotations. Since accuracy varies across datasets and depends on the number of classes and other aspects, we examine the relationship between accuracy and the number of required annotations. In Fig. 3A, we compute the necessary number of annotations required to achieve 80% of classification accuracy with OpenLabCluster vs. standard deep-classifier (C) on the Mouse dataset. We observe that active learning methods require only 15-20% of annotated segments while standard deep classifier requires 9 times more annotated segments than the most optimal active learning approach. Classical non-deep classifiers like SVM and KNN require even more annotations to achieve the same accuracy. We also visualize the relationship between the number of annotated samples and the accuracy that OpenLabCluster can achieve for the three datasets in Fig. 3B. We observe that for most cases, OpenLabCluster methods lead to higher accuracy for given number of annotations than the counterpart supervised standard classifier. The curves indicating the accuracy of various OpenLabCluster active learning methods (red, green, blue) have a clear gap between them and the supervised curve (gray), especially in mid-range of the number of annotations. Their relative placement to each other shows that all methods could potentially contribute to effective classification. In Fig. 3C we further examine class-wise confusion matrices for the Zebrafish dataset on 4 annotation budgets (5%, 10%, 20%, 100%). From visual inspection, it appears that the matrix that corresponds to 20% annotations is close to the matrix that corresponds to 100% annotations. This proximity suggests that annotation of the full dataset might be redundant. Indeed, further inspection of Fig. 3C, indicates that samples annotated as LCS and BS classes (y-axis) by the unsupervised learning method are likely to be predicted as the LLC (x-axis) by OpenLabCluster. One possibility for the discrepancy could be annotation errors of prior clustering method which are taken as the ground truth. Re-examination of the dynamics of some of the features (e.g. tail angle) further supports this hypothesis and demonstrates that the methods in OpenLabCluster can potentially identify the outlier segments which annotation settles the organization of the Behavior Classification Map (for more details see in Appendix 5.2).

Organization of the Latent Representation. Our results indicate that the Latent Representation captured by the OpenLabCluster encoder-decoder and the classifier is able to better organize behavioral segments in comparison to direct embeddings of body keypoints. We quantitatively investigate such an organization with the Monkey dataset, for which ground truth annotations and segmentation are

Figure 3: Relation Between Accuracy and Annotation. A: The amount of annotations required to achieve 80% accuracy for classication of Home-Cage Mouse behaviors. Computed for standard supervised methods (KNN, SVM, C), and OpenLabcluster with three AL methods (Top, MI, CS). B: Prediction accuracy with increasing annotation budget on three datasets of Mouse, *C. elegans* and Zebrafish. C: Confusion matrix for zebrafish dataset for increasing annotation budget (5%,10%,20%,100%).

unavailable. Specifically, we obtain the Cluster Map of the segments with OpenLabCluster and then annotate 5% of segments through active learning methods which further train the encoder-decoder and the classifier generating a revised Cluster Map. We then depict the 2D tSNE projection of the Latent Representation and compare it with the 2D tSNE projection of body keypoints in Fig. 4. Indeed, it can be observed that within the Cluster Map, segments are grouped into more distinct and enhanced clusters. To measure the clustering properties of each embedding, we apply clustering metrics of Calinski-Harabasz (CHI) [67] and Davies-Bouldin (DBI) [68]. CHI measures the ratio of inter- and intra-cluster dispersion, with larger values indicating better clustering. DBI measures the ratio of inter-cluster distance to intra-cluster distance, with lower values indicating better clustering. CHI and DBI are shown in the bottom left of Fig. 4 considering the various number of clusters (2, 4, 6, 8, 10, 12). The comparison shows that the CHI index is higher for the Cluster Map than the embedding of the keypoints regardless of the number of clusters being considered and is monotonically increasing with the number of clusters. The DBI index for the Cluster Map is significantly lower than the index of the embedding of the keypoints for up to 10 clusters with minima at 6 and 10 clusters. This is consistent with the expectation that clustering quality will be consistent with the number of behavioral types. Indeed in these behaviors, there are 6 major behavioral classes that can be identified and possibly several transitional ones. We show in Fig. 4 (right) the Behavioral Classification Map generated by OpenLabCluster along with frames from representative segments of each class.

3   Discussion

In this paper, we introduce OpenLabCluster, a novel toolset for quantitative studies of animal behavior from video recordings in terms of automatic grouping and depiction of behavioral segments into clusters and their association with behavioral classes. OpenLabCluster works with body keypoints which describe the pose of the animal in each frame, and across frames reflecting the kinematic information of the movement that is being exhibited in the segment. The advancement and the availability of automatic tools for markerless pose estimation in recent years allows the employment of such tools in

Figure 4: 2D tSNE projection of behavioral segments. Left, Top: 2D tSNE projection of keypoints compared with 2D tSNE projection of Latent Representation (Cluster Map). Left, Bottom: CHI and DBI metrics computed for each projection for increasing number of clusters. Right: Behavior Classification Map (2D tSNE projection of Latent Representation with associated behavioral states colors) along with example video frames from segments associated with each class. Images are reproduced from images in the datset of [36].

conjunction with OpenLabCluster for performing almost automatic organization and interpretation of a variety of ethological experiments.

Efficacy of OpenLabCluster is attributed to two major components; (i) Unsupervised pre-training process which groups segments with similar movement patterns and disperses segments with dissimilar movement patterns (Clustering); (ii) Automatic selection of samples of segments for association with behavioral classes (active learning) through which all segments class labels are associated (classification) and the clustering representation is being refined.

We evaluate OpenLabCluster performance on various datasets of recorded animal species freely behaving, such as Home-Cage Mouse, Zebrafish, *C. elegans* and Monkey datasets. For the datasets for which ground-truth labels have been annotated, we show that OpenLabCluster classification accuracy exceeds the accuracy of a direct deep-classifier for any annotation budget even when all segments in the training set have been annotated. The underlying reason for the efficacy of OpenLabCluster is the unsupervised pre-training stage of the encoder-decoder which establishes similarities and clusters segments with the Latent Representation of the encoder-decoder. Such a representation turns out to be useful in informing which segments could add semantic meaning of the groupings and refine the representation further.

In practice, we observe that even a sparse annotation of a few segments (5%-20% of the training set) chosen with appropriate active learning methods would boost clustering and classification significantly. Classification accuracy continues to improve when more annotations are performed, however, we also observe that the increase in accuracy is primarily in the initial annotation steps, which demonstrates the importance of employing clustering in conjunction with active learning selection in these critical steps. Indeed, our results demonstrate that among different active learning approaches, more direct approaches such as Top, are not as effective as others considering the need to include more metrics quantifying uncertainty and similarity of the segments.

As we describe in the Methodology section, OpenLabCluster includes advanced techniques of unsupervised and semi-supervised neural network training through active learning (Appendix 5.1). Inspired by the DeepLabCut project [30, 32, 31], we implement these techniques jointly with a graphic user interface to enable scientists to use the methodology to analyze various ethological experiments with no deep learning technical expertise. In addition, OpenLabCluster is an open-source project and

is designed such that further methodologies and extensions would be seamlessly integrated into the project by developers. Beyond ease of use, the graphic interface is an essential part of OpenLabCluster functionality, since it visually informs the scientists of the outcomes in each iteration step. This provides the possibility to inspect the outcomes and assist with additional information "on-the-go". Specifically, OpenLabCluster allows for pointing at points (segments) in the maps, inspecting their associated videos, adding or excluding segments to be annotated, working with different low-dimensional embeddings (2D or 3D), switching between active learning methods, annotating the segments within the same interface, and more.

Figure 5: Latent Representation is learned by performing the reconstruction task using an encoder-decoder structure. Latent vectors (last state of the encoder) are projected onto low dimensional space with various dimension reduction techniques to visualize the Latent Representation which constitute the Cluster Map. Mouse images are reproduced from frames of videos in the dataset of [18].

4 Materials and Methods

Existing approaches for behavior classification from keypoints are supervised and require annotation of extensive datasets before training [25, 28]. The requirement limits the generalization of classification from one subject to another, from animal to animal, from a set of keypoints to another, and from one set of behaviors to another due to the need for re-annotation when such variations are introduced.

In contrast, grouping behavioral segments into similarity groups (clustering) typically does not require annotation and could be done by finding an alternative representation of behavioral segments reflecting the differences and the similarities among segments. Both classical and deep-learning approaches address such groupings [2, 41]. Notably, clustering is a 'weaker' task than classification since does not provide the semantic association of groups with behavioral classes, however, could be used as a preliminary stage for classification. If leveraged effectively, as a preliminary stage, clustering can direct annotation to minimize the number of segments that need to be annotated and at the same time to boost classification accuracy.

OpenLabCluster, that is primarily based on this concept, first infers a *Cluster Map* and then leverages it for automatic selection of sparse segments for annotation (active learning) that will both inform behavior classification and enhance clustering. It iteratively converges to a detailed *Behavior Classification Map* where segments are grouped into similarity classes and each class is homogeneously representing a behavioral state. Below we describe the components.

Clustering The inputs into OpenLabCluster denoted as $\mathcal{X}$, are sets of keypoints coordinates (2D or 3D) or kinematics features for each time segment along with the video footage (image frames that correspond to these keypoints). Effectively, each input segment of keypoints is a matrix with the row

dimension indicating the keypoints coordinate, e.g. the first row will indicate the x-coordinate of the first keypoint and the second row will indicate the y-coordinate of the first keypoint and so on.

The first stage of OpenLabCluster is to employ a Recurrent Neural Network (RNN) encoder-decoder architecture that will learn a Latent Representation for the segments as shown in Fig. 5. The encoder is composed of m bi-directional gated recurrent units (bi-GRU) [69] sequentially encoding time-series input into a Latent Representation (latent vector in $\mathbb{R}^m$ space). Thus each segment is represented as a point in the Latent Representation $\mathbb{R}^m$ space. The decoder is composed of uni-directional GRUs that receive as input the latent vector and decode (*reconstruct*) the same keypoints from the latent vector. Training optimizes encoder-decoder connectivity weights such that the reconstruction loss, the distance between the segment keypoints reconstructed by the decoder and the input segment, is minimized, see the Appendix for further details (Section 5.1). This process reshapes the latent vector points in the Latent Representation space to better represent the segments similarities and distinctions.

To visualize the relative locations of segments in the Latent Representation, OpenLabCluster implements various dimension reductions (from $\mathbb{R}^m \to \mathbb{R}^2$ or $\mathbb{R}^m \to \mathbb{R}^3$), such as PCA, tSNE, UMAP, to obtain Cluster Maps, see Fig. 5-bottom. Thus each point in the Cluster Map is a reduced-dimensional Latent Representation of an input segment. From inspection of the Cluster Map on multiple examples and benchmarks, it can be observed that the Latent Representation clusters segments that represent similar movements into same clusters, to a certain extent, typically more effectively than an application of dimension reduction techniques directly to the keypoints segments [45, 70].

Figure 6: Behavior Classification Map is generated by a fully connected classifier network (green rectangle) which receives the latent vector transformed by the encoder-decoder as input and classifies them into behavior classes (example shown: 8 classes in Home-Cage Mouse Behavior dataset). Behavioral Classification Map is generated from the Cluster Map and indicates the predicted classes of all segments.

Classification. To classify behavioral segments that have been clustered, we append a classifier, a fully connected network, to the encoder. The training of the classifier is based on segments that have been annotated and minimizes the error between the predicted behavioral states and the behavioral states given by the annotation (cross-entropy loss). When the annotated segments well represent the states and the clusters, the learned knowledge is transferable to other unlabeled segments. Active Learning methods such as Cluster Center (Top), Core-Set (CS) and Marginal Index (*MI*) aim to select such representative segments by analyzing the Latent Representation. *Top* selects representative segments which are located at the centers of the clusters (obtained by Kmeans [71]) in the Latent Representation space. This approach is effective at the initial stage. CS selects samples that cover the remaining samples with minimal distance [72]. MI is an uncertainty-based selection method, selecting

samples that the network is most uncertain about. See Appendix 5.1 for further details regarding these methods. Once segments for annotation are chosen by the active learning method, OpenLabCluster highlights the points in the Cluster Map that represent them and their associated video segments, such that they can be annotated within the graphic interface of OpenLabCluster (choosing the most related behavioral class). When the annotations are set, the full network of encoder-decoder with appended classifier is re-trained to perform classification and predict the labels of all segments. The outcome of this process is the Behavior Classification Map which depicts both the points representing segments in clusters and associated states labels with each point (color) as illustrated in Fig. 6. In this process, each time that a new set of samples is selected for annotation, the parameters of the encoder-decoder and the classifier are being tuned to generate more distinctive clusters and more accurate behavioral states classification. The process of annotation and tuning is repeated, typically until the number of annotations reaches the maximum amount of the annotation budget, or when clustering and classification appear to converge to a steady state.

Implementation. OpenLabCluster code [73] was developed in University of Washington UW NeuroAI Lab by Jingyuan Li and Moishe Keselman. OpenLabCluster interface is inspired by DeepLab-Cut [31], which code is used as a backbone for user interface panels, interaction with the back-end, logging, and visualization. OpenLabCluster also uses Google Active Learning Playground code [74] for the implementation of the K-center selection method in the Core-Set active learning option. For specific usage please see the third_party folder within the OpenLabCluster code repository [73]. OpenLabCluster is available as a GitHub Repository (OpenLabCluster) `https://github.com/shlizee/OpenLabCluster` and also can be installed with Package Installer for Python (PIP) *pip install openlabcluster* [75]. The repository includes a manual, instructions, and examples.

References

[1] Valentin Sturm et al. "A chaos theoretic approach to animal activity recognition". In: *Journal of Mathematical Sciences* 237.5 (2019), pp. 730–743.

[2] João C Marques et al. "Structure of the zebrafish locomotor repertoire revealed with unsupervised behavioral clustering". In: *Current Biology* 28.2 (2018), pp. 181–195.

[3] Robert Evan Johnson et al. "Probabilistic models of larval zebrafish behavior reveal structure on many scales". In: *Current Biology* 30.1 (2020), pp. 70–82.

[4] Gordon J Berman, William Bialek, and Joshua W Shaevitz. "Predictability and hierarchy in Drosophila behavior". In: *Proceedings of the National Academy of Sciences* 113.42 (2016), pp. 11943–11948.

[5] Mehrdad Jazayeri and Arash Afraz. "Navigating the neural space in search of the neural code". In: *Neuron* 93.5 (2017), pp. 1003–1014.

[6] Sandeep Robert Datta et al. "Computational neuroethology: a call to action". In: *Neuron* 104.1 (2019), pp. 11–24.

[7] Rebecca Zoe Weber et al. "Deep learning based behavioral profiling of rodent stroke recovery". In: *BioRxiv* (2021).

[8] Z Taiwanica. "ETHOM: event-recording computer software for the study of animal behavior". In: *Acta Zool. Taiwanica* 11 (2000), pp. 47–61.

[9] J Morrow-Tesch, JW Dailey, and H Jiang. "A video data base system for studying animal behavior". In: *Journal of animal science* 76.10 (1998), pp. 2605–2608.

[10] Jiawei Han, Jian Pei, and Micheline Kamber. *Data mining: concepts and techniques*. Elsevier, 2011.

[11] Emma Lynch et al. "The use of on-animal acoustical recording devices for studying animal behavior". In: *Ecology and Evolution* 3.7 (2013), pp. 2030–2037.

[12] Tomoya Nakamura et al. "A markerless 3D computerized motion capture system incorporating a skeleton model for monkeys". In: *PloS one* 11.11 (2016), e0166154.

[13] Alessio Paolo Buccino et al. "Open source modules for tracking animal behavior and closed-loop stimulation based on Open Ephys and Bonsai". In: *Journal of neural engineering* 15.5 (2018), p. 055002.

[14] Max Bain et al. "Automated audiovisual behavior recognition in wild primates". In: *Science advances* 7.46 (2021), eabi4883.

[15] David J Anderson and Pietro Perona. "Toward a science of computational ethology". In: *Neuron* 84.1 (2014), pp. 18–31.

[16] Anthony I Dell et al. "Automated image-based tracking and its application in ecology". In: *Trends in ecology & evolution* 29.7 (2014), pp. 417–428.

[17] Jens Krause et al. "Reality mining of animal social systems". In: *Trends in ecology & evolution* 28.9 (2013), pp. 541–551.

[18] Hueihan Jhuang et al. "Automated home-cage behavioural phenotyping of mice". In: *Nature communications* 1.1 (2010), pp. 1–10.

[19] Ulrich Stern, Ruo He, and Chung-Hui Yang. "Analyzing animal behavior via classifying each video frame using convolutional neural networks". In: *Scientific reports* 5.1 (2015), pp. 1–13.

[20] James P Bohnslav et al. "DeepEthogram, a machine learning pipeline for supervised behavior classification from raw pixels". In: *Elife* 10 (2021), e63377.

[21] Markus Marks et al. "Deep-learning-based identification, tracking, pose estimation and behaviour classification of interacting primates and mice in complex environments". In: *Nature Machine Intelligence* 4.4 (2022), pp. 331–340.

[22] Yinjun Jia et al. "Selfee, self-supervised features extraction of animal behaviors". In: *Elife* 11 (2022), e76218.

[23] Elsbeth A van Dam, Lucas PJJ Noldus, and Marcel AJ van Gerven. "Deep learning improves automated rodent behavior recognition within a specific experimental setup". In: *Journal of neuroscience methods* 332 (2020), p. 108536.

[24] Kartikeya Murari et al. "Recurrent 3D convolutional network for rodent behavior recognition". In: *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE. 2019, pp. 1174–1178.

[25] Chi Xu et al. "Lie-X: Depth image based articulated object pose estimation, tracking, and action recognition on lie groups". In: *International Journal of Computer Vision* 123.3 (2017), pp. 454–478.

[26] Eldar Insafutdinov et al. "ArtTrack: Articulated Multi-person Tracking in the Wild". In: *CVPR'17*. URL: http://arxiv.org/abs/1612.01465.

[27] Eldar Insafutdinov et al. "DeeperCut: A Deeper, Stronger, and Faster Multi-Person Pose Estimation Model". In: (). URL: http://arxiv.org/abs/1605.03170.

[28] Oliver Sturman et al. "Deep learning-based behavioral analysis reaches human accuracy and is capable of outperforming commercial solutions". In: *Neuropsychopharmacology* 45.11 (2020), pp. 1942–1952.

[29] Zhe Cao et al. "OpenPose: realtime multi-person 2D pose estimation using Part Affinity Fields". In: *IEEE transactions on pattern analysis and machine intelligence* 43.1 (2019), pp. 172–186.

[30] Alexander Mathis et al. "DeepLabCut: markerless pose estimation of user-defined body parts with deep learning". In: *Nature neuroscience* 21.9 (2018), p. 1281.

[31] *DeepLabCut: a software package for animal pose estimation GitHub repository*. https://github.com/DeepLabCut/DeepLabCut.

[32] Tanmay Nath et al. "Using DeepLabCut for 3D markerless pose estimation across species and behaviors". In: *Nature protocols* 14.7 (2019), pp. 2152–2176.

[33] Jessy Lauer et al. "Multi-animal pose estimation, identification and tracking with DeepLabCut". In: *Nature Methods* 19 (2022), pp. 496–504.

[34] Talmo D Pereira et al. "Fast animal pose estimation using deep neural networks". In: *Nature methods* 16.1 (2019), pp. 117–125.

[35] Anqi Wu et al. "Deep Graph Pose: a semi-supervised deep graphical model for improved animal pose tracking". In: *bioRxiv* (2020).

[36] Praneet C Bala et al. "Automated markerless pose estimation in freely moving macaques with OpenMonkeyStudio". In: *Nature communications* 11.1 (2020), pp. 1–12.

[37] Talmo D Pereira et al. "SLEAP: Multi-animal pose tracking". In: *BioRxiv* (2020).

[38] Pierre Karashchuk et al. "Anipose: a toolkit for robust markerless 3D pose estimation". In: *Cell reports* 36.13 (2021), p. 109730.

[39] Libby Zhang et al. "Animal pose estimation from video data with a hierarchical von Mises-Fisher-Gaussian model". In: *International Conference on Artificial Intelligence and Statistics*. PMLR. 2021, pp. 2800–2808.

[40] Ben Usman et al. "MetaPose: Fast 3D Pose from Multiple Views without 3D Supervision". In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 2022, pp. 6759–6770.

[41] Alexander I Hsu and Eric A Yttri. "B-SOiD, an open-source unsupervised algorithm for identification and fast prediction of behaviors". In: *Nature communications* 12.1 (2021), pp. 1–13.

[42] Leland McInnes, John Healy, and James Melville. "Umap: Uniform manifold approximation and projection for dimension reduction". In: *arXiv preprint arXiv:1802.03426* (2018).

[43] Kang Huang et al. "A hierarchical 3D-motion learning framework for animal spontaneous behavior mapping". In: *Nature communications* 12.1 (2021), p. 2784.

[44] Jea Kwon et al. "SUBTLE: An unsupervised platform with temporal link embedding that maps animal behavior". In: *bioRxiv* (2023), pp. 2023–04.

[45] Kun Su, Xiulong Liu, and Eli Shlizerman. "PREDICT & CLUSTER: Unsupervised Skeleton Based Action Recognition". In: *IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR)* (2020).

[46] Kevin Luxem et al. "Identifying behavioral structure from deep variational embeddings of animal motion". In: *BioRxiv* (2022), pp. 2020–05.

[47] Alexander B Wiltschko et al. "Revealing the structure of pharmacobehavioral space through motion sequencing". In: *Nature neuroscience* 23.11 (2020), pp. 1433–1443.

[48] John A Hartigan and Manchek A Wong. "Algorithm AS 136: A k-means clustering algorithm". In: *Journal of the royal statistical society. series c (applied statistics)* 28.1 (1979), pp. 100–108.

[49] Martin Ester et al. "A density-based algorithm for discovering clusters in large spatial databases with noise." In: *kdd*. Vol. 96. 34. 1996, pp. 226–231.

[50] Fernand Meyer. "Topographic distance and watershed lines". In: *Signal processing* 38.1 (1994), pp. 113–125.

[51] Gordon J Berman et al. "Mapping the stereotyped behaviour of freely moving fruit flies". In: *Journal of The Royal Society Interface* 11.99 (2014), p. 20140672.

[52] Timothy W Dunn et al. "Geometric deep learning enables 3D kinematic profiling across species and environments". In: *Nature methods* 18.5 (2021), pp. 564–573.

[53] Cristina Segalin et al. "The Mouse Action Recognition System (MARS) software pipeline for automated analysis of social behaviors in mice". In: *Elife* 10 (2021), e63720.

[54] Thomas Cover and Peter Hart. "Nearest neighbor pattern classification". In: *IEEE transactions on information theory* 13.1 (1967), pp. 21–27.

[55] Christopher M Bishop and Nasser M Nasrabadi. *Pattern recognition and machine learning*. Vol. 4. 4. Springer, 2006.

[56] Michael I Jordan and Tom M Mitchell. "Machine learning: Trends, perspectives, and prospects". In: *Science* 349.6245 (2015), pp. 255–260.

[57] Xiaojin Zhu and Andrew B Goldberg. "Introduction to semi-supervised learning". In: *Synthesis lectures on artificial intelligence and machine learning* 3.1 (2009), pp. 1–130.

[58] Chenyang Si et al. "Adversarial self-supervised learning for semi-supervised 3d action recognition". In: *European Conference on Computer Vision*. Springer. 2020, pp. 35–51.

[59] Jennifer J Sun et al. "Task programming: Learning data efficient behavior representations". In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 2021, pp. 2876–2885.

[60] David A Cohn, Zoubin Ghahramani, and Michael I Jordan. "Active learning with statistical models". In: *Journal of artificial intelligence research* 4 (1996), pp. 129–145.

[61] Burr Settles. *Active learning literature survey*. Tech. rep. University of Wisconsin-Madison Department of Computer Sciences, 2009.

[62] Burr Settles. "Active learning". In: *Synthesis lectures on artificial intelligence and machine learning* 6.1 (2012), pp. 1–114.

[63] Jingyuan Li and Eli Shlizerman. "Sparse semi-supervised action recognition with active learning". In: *arXiv preprint arXiv:2012.01740* (2020).

[64] Eviatar Yemini et al. "A database of Caenorhabditis elegans behavioral phenotypes". In: *Nature methods* 10.9 (2013), pp. 877–879.

[65] Saquib Sarfraz et al. "Temporally-weighted hierarchical clustering for unsupervised action segmentation". In: *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*. 2021, pp. 11225–11234.

[66] Corinna Cortes and Vladimir Vapnik. "Support-vector networks". In: *Machine learning* 20.3 (1995), pp. 273–297.

[67] Tadeusz Caliński and Jerzy Harabasz. "A dendrite method for cluster analysis". In: *Communications in Statistics-theory and Methods* 3.1 (1974), pp. 1–27.

[68] David L Davies and Donald W Bouldin. "A cluster separation measure". In: *IEEE transactions on pattern analysis and machine intelligence* 2 (1979), pp. 224–227.

[69] Kyunghyun Cho et al. "On the properties of neural machine translation: Encoder-decoder approaches". In: *arXiv preprint arXiv:1409.1259* (2014).

[70] Kun Su and Eli Shlizerman. "Clustering and Recognition of Spatiotemporal Features through Interpretable Embedding of Sequence to Sequence Recurrent Neural Networks". In: *arXiv preprint arXiv 1905.12176* (2020).

[71] Jingyuan Li and Eli Shlizerman. "Iterate & cluster: Iterative semi-supervised action recognition". In: *arXiv preprint arXiv:2006.06911* (2020).

[72] Ozan Sener and Silvio Savarese. "Active learning for convolutional neural networks: A core-set approach". In: *arXiv preprint arXiv:1708.00489* (2017).

[73] *OpenLabCluster GitHub repository*. https://github.com/shlizee/OpenLabCluster.

[74] *Google Active Learning Playground GitHub repository*. https://github.com/google/active-learning.

[75] Moishe Keselman Jingyuan Li. *OpenLabCluster Package*. PyPI. 2022.

[76] Maria-Florina Balcan, Andrei Broder, and Tong Zhang. "Margin based active learning". In: *International Conference on Computational Learning Theory*. Springer. 2007, pp. 35–50.

[77] Ajay J Joshi, Fatih Porikli, and Nikolaos Papanikolopoulos. "Multi-class active learning for image classification". In: *2009 IEEE Conference on Computer Vision and Pattern Recognition*. IEEE. 2009, pp. 2372–2379.

5 Appendix

5.1 Methods

The inputs of OpenLabCluster are multi-dimensional time series representing the coordinates of animal body keypoints or other kinematic features tracked during movement along with video segments frames from which these were extracted. We denote the times-series as $\mathcal{X} = \{X_u \bigcup X_l\}$, with X_u representing the sequences in the unlabeled set and X_l in the labeled set, and assume that the segments are unlabeled, $\mathcal{X} = X_u$, in the beginning. A segment $\mathbf{x}_i \in \mathcal{X}$ is represented as a sequence $\mathbf{x}_i = [x_1, x_2, .., x_t, ..., x_T]$, where x_t is the vector of features for movement at time t, $x_t \in R^p$. For the examples we consider here, the number of features is 16, 98, 16, 39 for Home-Cage Mouse, *C. elegans*, Zebrafish and Monkey datasets, respectively. OpenLabCluster includes three main components: (i) An encoder-decoder network that learns to reconstruct sequences and forms Latent Representations. (ii) A classifier network which performs behavior classification. (iii) Active Learning (AL) selection which integrates Latent Representation information with the classifier output to optimize classification and annotation.

(i) Encoder-Decoder: We adopt the Predict & Cluster encoder-decoder framework which has been shown to achieve self-organizing latent representations [45, 70]. The encoder uses bidirectional Gated Recurrent Units (GRU) and receives $\mathbf{x_i} \in \mathcal{X}$ as input. The vector $\mathbf{h}_i^T$ is the latent representation which is the hidden state of the encoder GRU at the last time step T. It encodes the dynamic properties of the whole sequence $\mathbf{x_i}$ and lies in the latent space V, where $V = \{\mathbf{h}_i^T | \mathbf{h}_i^T = encoder(\mathbf{x_i}), \mathbf{x_i} \in \mathcal{X}\}$, i.e., the space spanned by the latent codes of all sequences. The unidirectional GRU-based decoder receives $\mathbf{h_i^T}$ and generates $\hat{\mathbf{x}}_i$ - the reconstruction of the original input sequences. The encoder-decoder network is trained by minimizing the reconstruction loss

$$\mathcal{L}_{re} = |\hat{\mathbf{x}}_i - \mathbf{x}_i|. \tag{1}$$

(ii)Classification: The classifier is a one-layer fully connected network appended to the encoder. It takes Latent Representation as input and generates the probabilities that a sample belongs to each behavioral states. During training, the classifier is learned to maximize the probability of the annotated behavior state. In other words, with the annotated samples given the classifier output, the classification loss is computed as

$$\mathcal{L}_{cla}^i = \sum_{l=1}^{C} -y_i^l \log(p^l(\mathbf{x}_i)), \tag{2}$$

where $y_i^l = 1$ if $\mathbf{x}_i$ belongs to class l, and $y_i^l = 0$ otherwise. The complete loss for each sample $\mathbf{x}_i$, is then composed from the reconstruction loss $\mathcal{L}_{re}^i$ and the classification loss $\mathcal{L}_{cla}^i$ for the annotated samples.

$$\mathcal{L} = \sum_{\mathbf{x}_i \in \mathcal{X}_l} \mathcal{L}_{cla}^i + \frac{1}{|\mathcal{X}|} \sum_{\mathbf{x}_i \in \mathcal{X}} \mathcal{L}_{re}^i, \tag{3}$$

where $|\mathcal{X}|$ is the total number of samples in the dataset. This includes all labeled samples annotated in current and earlier iteration.

(iii) Active Learning: There are three Active Learning (AL) methods embedded in OpenLab-Cluster: Cluster Center (Top), Uncertainty with Marginal Index (MI), Core-Set (CS).
Cluster Center (Top) leverages clusters information in the latent space to enhance coverage and effectiveness of selected segments (samples). Specifically, *K-Means* clustering is used to transform the latent representation into a collection of clusters $\mathcal{K}$. The number of clusters k

$$k = \frac{1}{N_{iter}} \times percentage \times |\mathcal{X}|, \tag{4}$$

is chosen based on the total number of selection iterations N_{iter} and the *percentage* of data would be annotated in total. k is fixed across selection iterations such that k is the number of samples to be annotated and each is located in a different cluster.
Marginal Index (MI) is based on the classifier output and measures the difference between the classifier output, evaluating top two difference of p. The probability prediction p of each class l is

$$p^l(\mathbf{x_i}) = p^l(\hat{y}_i = l | W_\theta, W_\delta) = \mathcal{C}^l(\mathbf{x_i}),$$

where p^l denotes the probability of a sample to belong to a class l among C classes ($l \in [1, C]$) predicted by the classifier $\mathcal{C}$. $\mathcal{C}$ indicates the transformation with the classifier. MI is computed as the measure of the confidence, difference between the most probable class and the second most probable class [76, 77], i.e.,

$$MI = \max_{l \in [1:C]} \left(p^l \right) - \max_{l \in ([1:C] \setminus l^*)} \left(p^l \right), \tag{5}$$

where $l^* = \arg\max_{l \in [1:C]} \left(p^l \right)$.

Core-Set (CS) aims to discover a set of samples that can cover unlabeled samples with a certain radius [72]. The algorithm finds a set of samples such that the radius is minimal.

With the labeled samples, the classifier is trained until the classification accuracy on these labeled samples converges. Annotation iteration repeats until reaching the annotation budget.

Prototype Dynamics

Examples of disparity between OLC and GT

Figure 7: Top: Prototypical dynamics of three behavioral states (LLC, BS, LCS), envelop (blue). Bottom: Three examples of disparity between OpenLabCluster (OLC) and Ground Truth (GT) classification.

5.2 Zebrafish Behaviors and Dynamics

Zebrafish behavior is subdivided into 13 classes: "approach swims" (ASs), slow types 1 (S1), slow types 2 (S2), short and long capture swim (SCS and LCS), burst type forward swim (BS), J-turns, high-angle turn (HAT), C-start escape swims (SLC), long latency C-starts (LLC), O-bends, and routine turns (RTs), spot avoidance turn (SAT).

As shown in Fig 3C, OpenLabCluster could "misclassify" samples to belong to LLC class, although they have been annotated by previous analysis as BS or LCS. Since the annotation is obtained by a prior unsupervised learning method and not a case-by-case manual annotation, it could be possible that the annotation is made incorrectly, especially for those segments that are located near the boundaries of clusters. We show several of such conflicting examples in Fig. 7. In the top row, we show the typical

	Mouse			Zebrafish			C elegans		
Label(%)	5	10	20	5	10	20	5	10	20
Label(#)	143	286	571	265	530	1059	27	55	109
C	55.2	54.1	64.5	72.5	70	75.8	71.3	75.2	77.5
RC	53.7	54.1	63.9	66.3	72.3	74.8	71.0	76.4	79.1
IRC	63.0	66.6	76.1	72.8	75.9	79.0	73.8	**77.0**	77.3
OLC CS	**65.3**	75.4	**82.2**	71.9	76.6	79.6	73.5	64.3	75.4
OLC Top	58.5	58.4	76.4	72.0	77.1	80.1	76.5	76.5	**77.8**
OLC MI	63.4	**76.3**	78.9	**74.2**	**79.1**	**81.1**	**76.7**	76.8	77.0

Table 3: Comparison of OpenLabCluster (OLC) against its ablated versions: RC, IRC for 5%, 10% and 20% annotations on Mouse , Zebrafish and *C. elegans* datasets.

dynamics of three ground-truth (GT) classes (BS, LCS, and LLC). Inspecting the prototypical dynamics of the LCS, BS, and LLC, one can find that each profile has unique dynamic profile. For example, LLC profile peaks in the beginning and gradually decays. In the bottom row of Fig. 7, we show three examples of segments classified by OpenLabCluster as *LLC* but marked differently by prior annotation that we consider as ground-truth. It appears that while these examples are similar to LLC profile (having a peak in the beginning and decay) supporting the decision of OpenLabCluster to classify these segments as LLC, the ground truth annotations made by prior clustering analysis are contradictory.

5.3   Ablation study

The two components of OpenLabCluster of unsupervised clustering and semi-supervised classification are essential to the accuracy. In Table 3 we examined "ablated" versions of OpenLabCluster to demonstrate the impact of each component; C designates a variant that includes a classifier network only. RC designates a variant where pretraining phase of OpenLabCluster is ablated, i.e., all the weights of the encoder-decoder and the classifier are randomly initialized. In this scenario, there is no pre-organized Latent Representation. *IRC* designates a variant where active learning is not being applied but the encoder-decoder structure as well as the training paradigm including pretraining is kept the same as in OpenLabCluster (with pre-organized Latent Representation). As shown in Table 3, the accuracy of IRC is higher than that of C and RC showing the importance of pre-organized encoder-decoder Latent Representation. OpenLabCluster along with various active learning approaches further enhances the accuracy (over IRC) in most cases, especially on the Home-Cage Mouse and the Zebrafish datasets with an average improvement 5.78%. The reason that improvement of OpenLabCluster is not significant on the *C. elegans* dataset could be that the diversity is limited on the dataset, i.e., samples are equally informative for behavior states learning.