GSearch: Ultra-Fast and Scalable Microbial Genome Search by Combining Kmer Hashing with Hierarchical Navigable Small World Graphs

Jianshu Zhao[1,2,7], Jean Pierre Both[3,7], Luis M. Rodriguez-R[4,5,6], Konstantinos T. Konstantinidis[1,2,4,*]

[1]Center for Bioinformatics and Computational Biology, Georgia Institute of Technology, Atlanta, Georgia, USA

[2]School of Biological Sciences, Georgia Institute of Technology, Atlanta, Georgia, USA

[3] Université Paris-Saclay, CEA, List, Palaiseau, France

[4]School of Civil and Environmental Engineering, Georgia Institute of Technology, Atlanta, Georgia, USA

[5]Department of Microbiology, University of Innsbruck, Innsbruck, Austria

[6]Digital Science Center (DiSC), University of Innsbruck, Innsbruck, Austria

[7]Those authors contribute equally

[*]Corresponding author, Konstantinos T. Konstantinidis

(kostas.konstantinidis@gatech.edu)

Abstract

Genome search and/or classification is a key step in microbiome studies and has recently become more challenging due to the increasing number of available (reference) genomes and the fact that traditional methods do not scale well with larger databases. By combining a kmer hashing-based genomic distance metric (ProbMinHash) with a graph based nearest neighbor search algorithm (called Hierarchical Navigable Small World Graphs, or HNSW), we developed a new program, GSearch, that is at least ten times faster than alternative tools due to O(log(N)) time complexity while maintaining high accuracy. GSearch can identify/classify 8,000 query genomes against all available microbial and viral species with sequenced genome representatives (n=~65,000) within several minutes on a personal laptop, using only ~6GB of memory. Further, GSearch can scale well with millions of database genomes based on a database splitting strategy. Therefore, GSearch solves a major bottleneck of microbiome studies that require genome search and/or classification.

Keywords: genome search, microbial genomes, MAGs, MinHash, nearest neighbor search, classification, hierarchical small world graphs, HNSW

Introduction

Identifying or classifying microbial species based on either universal marker genes

(e.g., 16S or 18S rRNA genes) or entire genomes represents a re-occurring task in

environmental and clinical microbiome studies. However, this task is challenging because

i) whether or not microbes (bacteria, fungi) and viruses form discrete population clusters

(or species), remains an open question [1, 2], and ii) the microbial species in nature are still

severely under-sampled by the available genomes. For instance, there are more than

10^{12} prokaryotic and fungal species in nature according to a recent estimation based on

16S rRNA gene or ITS (Internal Transcribed Spacer) analysis [3] and even more viral

species (e.g. the number of viral cells outnumbers that of prokaryotic cells by a about a

factor of ten in most natural habitats) [4]. Yet, only ~17,000 bacterial species have been

described and even fewer (around 15,000) are represented by complete or draft genome

[5]. Due to the recent improvements in DNA sequencing and single-cell technologies,

metagenomic surveys can now recover hundreds, if not thousands, of these yet-to-be-

described species from environmental or clinical samples [6, 7], filling in the gap in the

described diversity mentioned above. This has created a new challenge, however; that

is, identifying these new genomes against the exponentially increasing number of

available (described) genomes has become computationally intractable. Nonetheless, the

recent high-throughput sequencing of isolate genomes as well as metagenomic studies

of natural populations have shown that species may exist and be commonly

circumscribed based on a 95% genome-aggregate average nucleotide identity (ANI)

threshold, at least for prokaryotes and viruses [8, 9]. This threshold represents convenient

means in searching and identifying new genomes against the already descried species

and determining whether or not they represent novel species [10].

The number of curated draft or complete prokaryotic genomes has reached 317,542 in the newest release of the GTDB database, and 2,332,702 in the latest IMG/VR database for viruses, representing 65,703 prokaryotic and 935,122 viral distinct species at the 95% ANI level [11, 12]. Searching of query genomes against these large databases to find closely-related database/reference genomes for taxonomy classification based on the traditional brute-force methods, meaning, performing all vs. all searches, has become impractical, even for fast searching algorithms and/or small-to-medium computer clusters. For this task, faster search strategies are necessary. In addition to the searching strategy, the actual algorithm used to determine overall genetic relatedness between the query and the databased genomes is critical. While the traditional blast-based ANI among closely related genomes at the species level, and the genome-aggregate average amino acid identity (AAI) for genomes related at the genus level or above, have been proven to be highly accurate for genetic relatedness estimation across microbial and viral genomes [13-15], they are too slow to use when dealing with more than a few dozen of genomes. Faster implementations based on k-mer counting have been recently described to alleviate this bottleneck such as FastANI and MASH [16, 17], but these methods still do not scale with an increasing number of database (or query) genomes, especially based on an all vs. all search strategy. Further, defining genetic distance (or relatedness) based on kmer profiles can be problematic for incomplete genomes, which are commonly recovered from metagenomic surveys, and/or genomes with extensive repeats such as those found in several microbial eukaryotic genomes. Kmer-weighted approaches are advantageous in the latter cases because repeated genomic fragments can be considered when hashing

but they have not been widely adopted yet [18, 19]. Recently, a phylogeny-based approach

using a handful of universal genes (n ≈ 100) was developed to accelerate genome

classification [20]. However, phylogenetic replacement based on a concatenated universal

gene tree can be memory demanding and slow, especially for a large number of or a few

deep-branching (novel) query genomes, and this approach cannot be applied to viral

genomes, which lack universal genes. Further, universal genes due to their essentiality,

are typically under stronger purifying selection and thus, evolve slower than the genome

average. This property makes universal genes appropriate for comparisons among

distantly related genomes, e.g., to classify genomes belonging to a new class or a new

phylum, but not the species and genus levels [20, 21].

One of the most generally used approaches for finding closely related information

to a query, while circumventing an all vs. all search, is the K-Nearest Neighbor Search

(K-NNS). The K-NNS approach has been used for 16S rRNA gene-based classification

followed by a vote strategy [22, 23] and, more recently, for whole genome and metagenome

comparisons based on shared kmers [16]. Approximate nearest neighbor search (ANN)

algorithms, such as locality-sensitive hashing (LSH) [24, 25], k-dimension tree [26], random

projection trees [27], k-graph [28] and proximity graph [29, 30] have been recently used to

accelerate search processes. Proximity graph, as implemented for example in the

hierarchical navigable small world graph (HNSW) [31], has been shown to be one of the

fastest ANN search algorithms [32]. HNSW incrementally builds a multi-layer structure

consisting of a hierarchical set of proximity graphs (layers) for nested subsets of the

stored elements. Then, through smart neighbor selection heuristics, inserting and

searching the query elements in the proximity graphs can be very fast while preserving

high accuracy, even for highly clustered data [29, 31]. Therefore, finding the closest genomes

in a database can be substantially accelerated by using HNSW.

Here, we describe GSearch (for Genome Search), a tool that combines one of the

most efficient nearest neighbor search approaches (HNSW) with a universal approach to

measure genetic relatedness among any microbial genome, including viral genomes,

ProbMinHash [33], implemented in the Rust language for higher speed. ProbMinHash is

based on shared kmers, weighted by their abundance and normalized by total kmer

count, which can account for genome incompleteness of prokaryotic genomes and

repeats commonly found in eukaryotic and sometimes in prokaryotic genomes.

Essentially, ProbMinHash computes the normalized weighted Jaccard distance between

each pair of genomes and subsequently, the weighted Jaccard distance normalized by

total kmer count is used as input to build HNSW to create the graph of the database

genomes. Accordingly, the search of the query genome(s) against the graph to find the

nearest neighbors for classification purposes becomes an ultra-fast step using GSearch

and can be universally applied to all microbial genomes. The novelty of GSearch also

includes a hierarchical pipeline that involves both nucleotide-level (when query genomes

have close relatives at the species level) and amino-acid-level searching (when query

genomes represent novel species), which provides robust classification for query

genomes regardless of their degree of novelty relative to the database genomes, as well

as a database-splitting strategy that allows GSearch to scale up well to millions of

database genome sequences.

Results

Probminhash as a robust metric of genome relatedness for prokaryotic genomes

Correlations between ProbMASH distance (we called it ProbMASH after transformation from ProbMinHash distance, see Methods & Materials) and ANI (determined by FastANI) or MASH distance showed that ProbMinHash is robust and slightly better than MASH for determining distances among bacterial genomes related at ~78% ANI, or higher, i.e., genomes assigned to the same or closely-related species (Spearman rho=0.9643 and 0.9640 of ProbMinHash and MASH values against corresponding ANI values for the same genome comparisons, respectively, *P*<0.001, Figure S1a and S1b; note that for finding best matches using the ANI approach as the reference, Spearman rank correlation is more relevant than Pearson correlation). For moderately related genomes, for which nucleotide-level ANI is known to lose accuracy, ProbMinHash was still robust compared to MASH for bacterial genomes (using the best matches found by average amino acid distance or AAI as the reference), especially among genomes showing between ~52% and 95% AAI (Spearman rho=0.90, *P*<0.01, Supplementary Figure S2a and S2b). Below ~50% AAI, both ProbMinHash and MASH distance lose accuracy compared to AAI. However, AAI of just universal genes provides a robust measurement of genetic relatedness at this level of distantly related genomes [21], and we show here that ProbMinHash distance for the same set of universal genes is also robust (Spearman rho=0.9390, *P*<0.001, Supplementary Figure S3). Thus, for query genomes of organisms with only distant relatives in the database (i.e., deep-branching), for which their closest represented genome in the database is related at the order level or higher, restricting the search to the universal genes can provide robust classifications.

Graph building and search against reference prokaryotic genomes is faster than

alternative methods

To build the database graph for the entire GTDB v207 database (65,703 unique, non-

redundant, at the species level, prokaryotic genomes) at the nucleotide level, the tohnsw

module of GSearch took 2.3 h on a 24-thread computing node and scaled moderately

well with increasing number of threads (Figure 2a). Maximum memory (RAM) required

for the building step was 28.3 GB. The total size of written database files on disk was ~3.0

GB. There are 3 layers for the resulting graph, 65180, 519, and 4 genomes for layer 0,1

and 2 respectively. The searching of query genomes against this database graph,

requesting best 50 neighbors for 1000 query genomes, which represented different

previously known as well as novel species of eight bacterial phyla (see Methods for details

on query genome selection), took 2.3 min (database loading 6 seconds) on a 24-thread

machine and also scaled well with increasing number of threads (Figure 3a). The memory

requirement for the request (search) step was only 3.0 GB for storing the entire database

file in memory. To evaluate the accuracy of these results, we compared the best

neighbors found by GSearch with brute-force FastANI and GTDB-Tk. All best neighbors

found by brute-force FastANI and GTDB-Tk for query genomes with close relatives in the

database (e.g., ANI > 78%) were found by GSearch (Supplemental File 1). Top 5

neighbors were 99.4% overlapping and top 10 were 96.3% overlapping between GSearch

and the other two methods for the testing query genomes. We also compared the speed

with MASH for the same kmer and sketch size and the MASH dist step took 7.51 min to

compare 1000 genomes with database using 24 threads. The speed difference compared

to MASH was even greater for ~8,000 query genomes. Specifically, it took 12.5 min for

GSearch to find the top 50 best hits (Supplementary Figure S4a) while MASH took 80.8

minutes on the same 24-thread machine. However, for a given number of database

genomes, the speedup of GSearch is saturated to log(N) as the number of query genome

increases, where N is the number of database genomes. Therefore, GSearch will be

orders of magnitude faster than MASH for larger species database with millions of

genomes (see also viral section below). GSearch search time for a given number of query

genomes is related to the number of database genomes in a O(log(N)) manner while

brute-force methods are O(N), and our empirical analysis is consistent with the theoretical

log(N) prediction (Supplementary Figure S4b and Supplementary Note 3).

To build the amino-acid-level graph for moderately related query genomes, all GTDB

v207 genomes were used for gene calling by FragGeneScanRs and subsequently, the

predicted amino acid sequences for each genome were used for the tohnsw module. The

graph building step took 1.4 h (Figure 2b) with a maximum memory required for the

building step to be 37.7 GB. The total size of written database files on disk by GSearch

was 5.9 GB. There were 65158, 543 and 2 genomes for layer 0,1 and 2 respectively.

Requesting 50 neighbors for 1000 genomes at the amino-acid level took 1.52 minutes

with a memory requirement of ~6.0 GB (database loading 9 seconds; Figure 3b). The top

5 neighbors had a 98.9% recall compared to the brute-force MASH or blast-based AAI

approaches, with 97.1% overlap for the 10 top neighbors. In comparison, MASH dist took

5.96 min using 24 threads; for 8000 query genomes, MASH dist took 47.2 min while

GSearch took 5.6 min.

Finally, for most distantly related query genomes, the graph building for the universal

gene set follows the same logic as the amino acid level graph mentioned above except

for using a smaller kmer size (k=5) due to the smaller kmer space of ~120 universal genes

vs. the whole-genome level (e.g., a few thousand genes). It took 7.76 min to build the

database (Figure 2c) and 32 seconds to request 50 neighbors for 1000 queries on a 24

threads node (Figure 3c) with a recall similarly high to the amino-acid level search (with

top 5 and top 10 recall ranging between 98.2% and 96.1%, respectively).

We also evaluated the effect of genome completeness on search and classification

accuracy given that bacterial genomes recovered from environmental metagenomes are

frequently incomplete. GSearch was robust to genome incompleteness down to 50%

completeness level, e.g., with 80% of top 10 best matches are found, while accuracy

decreased considerably below this level (Supplementary table S6).

Graph database building and searching for viral and fungal genomes

Graph building and requesting for viral genomes is not effective at the nucleotide level

because many viral genera are too diverse and do not have close relatives in the public

genomic database; that is, the database is too sparse. Accordingly, kmer-based methods

(e.g., MASH and ProbMinHash) will often lead to imperfect graph structure for viral

genomes. Therefore, we build only an amino acid level graph for viral genomes, using all

genes in the genome due to the lack of universal genes for viral genomes. Database

building took 13.895 h on a 24-thread node and graph file on disk is 15.8 GB

(Supplementary Figure S6 (a)). Requesting 1000 neighbors scaled well with increasing

number of threads and took about 3.63 min (database load takes additional 1.1 min) using

24 threads (Supplementary Figure S6 (b)). The top 10 neighbors for 1000 query phage

genomes were still highly overlapping (98.32% recall; Supplemental Table S1) with the

brute-force MASH-based approach. For such large database, GSearch is about 20X

faster than the brute-force MASH (Supplementary Tables S1). We also compared

GSearch with a new database building method called PhageCloud, which relies on

manually curated genome labels (e.g., environmental source) for graph database building

in Neo4j database software and Dashing software for distance/relatedness computation.

Since PhageCloud provides only a website and allows only one genome query at a time,

we searched only one viral genome at a time with GSearch and MASH against the same

database (Gut Phage Database [34]). It took 37 seconds to find the two best matches with

PhageCloud while GSearch took 15 seconds (database loading 14 seconds, search 1

second) for the same search. MASH on the other hand took 4 minutes to find the same 2

best matches. It should be noted, however, that, because the database is already

available (loaded) on PhageCloud's website, 37 seconds is only for search and website

responses (average value for 5 runs on 5 different days) whereas GSearch took only 1.5

second for the same step.

Graph building for fungal genomes is slower compared to prokaryotic genomes, despite

the smaller number of available fungal genomes (n=9700) because the average fungal

genome size is much larger and kmer and sketch size are accordingly much larger (k=21,

s=48000). It took 2.3 h on a 24-thread node to build the nucleotide level graph for these

fungal genomes. Searching step was also slower due to the larger kmer space.

Accordingly, it took 3.13 min to identify 50 neighbors for 50 query fungal genomes while

MASH tool 4.4 min. Nonetheless, top 5 recall was still very high (~99.4%) against MASH

and MUMMER-based ANI for the same datasets. For the amino acid level graph, the time

for graph building was only 0.61 h, shorter than the corresponding prokaryotic graph due

to the lower coding density of fungal genomes relative to the prokaryotic genomes.

Identifying 50 neighbors for 50 query fungal genomes at the amino-acid level took 1.24

min (MASH took 2.59 min) with similarly high top 5 and top 10 recall (99.7% and 98.5%,

respectively) against brute-force MASH (-a) and blastp-based AAI. Note that the

difference in run time will be much larger between MASH and GSearch as the number of

fungal database genomes increases in the future, as also exemplified above for the

bacterial genomes

Combining the three graphs/levels together and comparison with GTDB-Tk for prokaryotic

genome classification

A three-step pipeline was developed to allow the identification and classification of a

query genome, depending on its level of novelty compared to the database genomes

(Figure 4). Specifically, when the query genome does not find a match in the database

better than ANI > 78%, corresponding to ProbMinHash distance 0.9850, the nucleotide-

level graph is abandoned, and the amino-acid level is used instead. If no match against

the latter graph is found above 52% AAI, corresponding to 0.9375 ProbMinHash distance,

the amino-acid level is abandoned, and the universal gene graph is used instead (uAAI

based on universal gene below 80% indicates new order or higher taxonomic rank; Figure

4). The overall running time to classify 1000 prokaryotic genomes of varied levels of

taxonomic novelty on different computing platforms is showed in Table 1. On a 24-thread

Linux node with Intel Xeon Gold 6226 CPU, it took a total of 5.85 minutes while it took

19.49 minutes on an intel Core i7 laptop (2017 release) CPU personal laptop (6.02

minutes on the most recent ARM64 CPU laptop). Classifying 1000 genomes using GTDB-

Tk took 5.91 h on the same Linux node with 24 threads (Figure 3 (d), memory requirement

was ~328G) while MASH took 53.7 min for 1000 genomes using 24 threads for the 3

steps.

In terms of accuracy, all query genomes that had a best match higher than 78% ANI

against the GTDB database genomes (i.e., a match at the same or closely related

species, 699 out of the total 1000) were identically classified by GSearch, GTDB-Tk and

FastANI (Supplementary File 1, only 100/699 are shown for simplicity). For the remaining

301 genomes that did not have same or closely related species-level matches, for 266 of

them (or 87.1%), GSearch also provided the same classification with GTDB-Tk but

several inconsistencies were observed for 39/301 genomes (Supplementary Figure S5).

Specifically, we noticed that for GTDB-Tk, which relies on RED values and tree topology,

several genomes (n=14) were still classified at the genus level even though the AAI value

against the best database genome in these case was below 60% (typically, genomes

assigned to the same genus show >65% AAI [21]), and some genomes (n=16) were still

classified at the family level but not at the genus level even though their best AAI value

was above 65%. Similarly, several genomes (n=9) were classified at the order level but

not family level even though their best AAI value was above 52%. Therefore, high

consistency was overall observed between GSearch and GTDB-Tk assignments, and the

few differences noted were probably associated with contaminated (low quality) MAGs or

taxonomic inconsistencies, which was challenging to assess further, and/or the

peculiarities of each method. Since ProbMinHash distance correlated well with blastp-

based AAI in the range of AAI values between 52% and 95%, the classification results

were always consistent with AAI-based classification using previously proposed

thresholds. For example, best matches at AAI 65% ≥ AAI were classified in the same

genus by GSearch and blast-based AAI and best matches of 52% < AAI < 65% were

typically classified in the same family [35].

Database split for large genomic species database

For large databases (for example, >1 million bacterial genomes), the graph building and

requesting step could require a large amount of memory (due to the larger kmer space)

that is typically not available in a single computer node. We therefore provide a database

split solution for such large databases. The average database building time on each node

(for each piece of the database after the splitting step) scales linearly with increasing

nodes/processors (Supplementary Figure S7(a)) and requires much less memory (1/n

total memory compared to when building in one node where n is the number database

pieces after splitting; for GTDB v207 nucleotide graph building and n=5, it will be only

28.3 G/5=5.66 G). The searching time scales sub-linearly with increasing number of

nodes (Supplementary Figure S7(b)), but offers the advantage of a reduced memory

footprint with respect to the single-node search. The top 10 best neighbor by splitting the

database were exactly the same as the non-splitting strategy (Supplementary file 2). Note

that without multi-node support (e.g., run database build sequentially), database build

time is nearly the same with non-split strategy, but memory requirement is only 1/n (GTDB

v207, 28.3G/5=5.66G at nucleotide level and 37.7G/5=7.54G at amino acid level), despite

the fact that total request time will be larger (time*n in Supplementary Figure S7(b)).

However, since the request step is very fast with only 1/n memory requirement (e.g.,

loaded graph database files for GTDB v207 will be about only 3G/5=0.6G), even for a

decent number of pieces, overall runtime is still short with the database split approach.

The database split strategy is especially useful when memory requirement is not satisfied

on host machine for larger genomic species database (e.g., millions of genomes).

Discussion

A popular way to assess genetic relatedness among genomes is ANI, which

corresponds well to both 16S/18S rRNA gene identity and DNA-DNA hybridization values,

the golden standards of fungal and prokaryotic taxonomies [13]. However, the number of

available microbial genomes has recently grown at an unprecedented speed. For

example, there are 30% more (new) species in GTDB v202 (2020) vs. v207 (2022), and

the number of bacterial species represented by genomes alone is expected to surpass 1

million soon. Therefore, the traditional way that blast-based ANI or faster kmer-based

implementations (e.g., FastANI or MASH) are applied as an all vs. all search strategy

(brute-force) does not scale because the running time grows linearly with increasing

number of query genomes and/or genomes in the database. Phylogenetic approaches

based on quick (approximate) maximum likelihood algorithms and a handful of universal

genes as implemented -for example- in GTDB-Tk could be faster than brute-force

approaches but are often not precise and require a large amount of memory for the

querying step [20, 36] while the database building step could take several weeks of run time

because the underlying multiple sequence alignment of the database genomes is

computationally intensive. Further, approaches that reply on k-medoid clustering to avoid

all vs. all comparisons could be sometimes trapped into local minima because of arbitrary

partitioning of database genomes into clusters, a known limitation of these methods [21].

Our GSearch software effectively circumvents these limitations by combining a new kmer

hashing-based algorithm for fast computation of genetic relatedness among genomes

(ProbMinHash) with a graph based nearest neighbor search algorithm (HNSW).

Accordingly, GSearch is at least an order of magnitude faster than alternative approaches

for the same purposes. Note that GSearch could also be applied to whole metagenome

search and identification of the most similar metagenomes in a series because

ProbMinHash can estimate metagenomic distance in a similar way to genomes.

To the best of our knowledge, no current tool can efficiently search very large

genome databases. GSearch is able to handle a million microbial genomes on a small-

to-average computer cluster since the dumped database file size is proportional to the

total number of genomes in database for fixed sketch size and graph parameters.

Specifically, with one million genomes, the dumped file size (amino acid) will be

5.9G*20=118 GB (now we have only ~60K, for which database file size is 5.9G), a modest

computational requirement for current computer clusters or even personal laptop

computer. Further, due to the nature of graph based NNS algorithms, there is no need to

build the entire database at once, but the database can be split it into smaller pieces and

thus, a separate graph database be built for each piece as exemplified above and

depending on the computational resources available. For a modern laptop with 16 GB

memory, a database on one million species can be split into 10 pieces, so the dumped

file for each piece will be only 11.8 GB, which can be loaded into memory, and then collect

the results from each piece within an approximate total running time of 30 minutes

(assuming each part will be 3 minutes for 1000 query genomes against 0.1 million

database genomes). With this logic, a computing node with 24 threads and 256 GB of

memory available can easily deal with 20 million bacterial database genomes. This

represents a substantial improvement compared to existing tools for the same purposes.

It is also important to note that we could seamlessly replace ProbMinHash with

another relatedness algorithm should such an algorithm become available and has

advantages in terms of speed and/or precision. Related to this, ANI as currently

implemented -for instance- in FastANI is not appropriate for this function because it is not

metric (that is, for the FastANI distances calculated among three genomes A, B, and C,

(A,B) + (B, C) is not necessary larger than (A,C), especially for genomes related at the

phylum level). To solve this "metric" problem, a norm adjusted proximity graph (NAPG)

was proposed based on inner product and it shows improvements in terms of both speed

and recall [37]. This could be another direction for further improving the speed and recall of

GSearch and/or the use of other metrics in place of ProbMinHash distances. In the

meanwhile, ProbMinHash was used in GSearch because it is metric [33, 38], which ensures

neighbor diversity when building the graph, but it is equally applicable to any microbial

genome, including viral and fungal genomes, in addition to its advantages for kmer

weighting and normalization mentioned above.

Another distinguishing aspect of GSearch (tohnsw module) is the speed and

flexibility in building reference databases. Users could build reference databases (graphs)

for any number and type (e.g., prokaryotic vs. viral) of genomes, up to several millions of

genomes. The high efficiency in building graphs allows users to also test and optimize

the key parameters of the graph, the M and ef_construct parameters. For any given

database size, M and ef_construct determine the quality of the graph and graph build

speed. Small M and ef_construct may lead to frequent traps in local minima and thus, low

recall while large M and ef_construct may lead to slow speed without proportional

improvement in recall (Supplemental Table S2). Therefore, there is a tradeoff between

accuracy and speed that should be evaluated first. However, for most users this task

would not be necessary because they will work with pre-built databases such as those

provided here. Further, the search step against these pre-build databases with query

genomes of known taxonomy for evaluating recall and tradeoffs can be performed, within

minutes, on any modern laptop with 5-6 GB of memory (Table 1).

Kmer-based methods for genetic relatedness estimation such as ProbMinHash

have lower accuracy between moderately-to-distantly related genomes compare to

alignment-based tools (see supplement Note 4 for further discussion). Our empirical

evaluation showed that this relatedness level, for nucleotide searches, is around 78% ANI

and 52% AAI for the amino-acid searches (e.g., ProbMinHash distances do not correlate

well with blast-based ANI and AAI at these levels). To circumvent this limitation, we

designed a 3-step framework as part of GSearch to classify bacterial genomes that show

different levels of novelty compared to the database genomes, with high accuracy. This

framework included a search at the universal gene level for deep-branching genomes

that are novel at the phylum level (AAI < 52%), for which searching at the entire proteome

level is less accurate. Recently, methods that employ kmers that allow mismatches, that

is, spaced kmers [39], have shown promise in accurately estimating genomic relatedness

even among distantly related genomes with gains in speed. To apply spaced kmers to

entire genomes, the recently developed "tensor sketch" approaches could be explored in

the future to simplify the pipeline for bacterial and viral genomes [40]. In the meanwhile, the

ProbminHash approach, essentially a Jaccard distance estimation via MinHash-based analysis

of kmers, is highly efficiently, and, importantly, can effectively deal with incomplete

genomes or genomes of (drastically) different length, an known limitation of MASH-based

methods [41]. Comparing genomes of different length is not uncommon, e.g., bacterial

genome size can differ by more than two-fold, as can be the case between MAGs of

different level of completeness or when searching a short sequence (e.g., a

bacteriophage genome) against a large genome collection (e.g., the whole viral genome

database). Our own analysis showed that ProbMinHash is robust down to 50%

completeness level (Supplemental Table S6), which is also the most commonly used

standard for selecting MAGs of sufficient/high quality [42]. ProbMinHash is also robust with

completed genomes with repeats or gene duplications due to the kmer weighting step.

In general, the genome relatedness estimated, or best database matching

genomes identified, by GSearch were highly consistent with blast-based AAI results or

phylogenetic placement of the genome using GTDB-Tk, particularly for query genomes

with close relatives in the database related at the species or genus level (Supplementary

File 1, Supplementary Figure S5). For more distantly related query genomes relative to

database genomes, classification results of GSearch showed some differences with

GTDB-Tk. These differences were not always possible to assess further for the most

correct genome placement but could be due, at least partly, to the incompleteness and/or

contamination of query or/and database genomes, which renders the resulting

concatenated alignment of universal genes used by GTDB-Tk unreliable [43] as only a few

amino-acid positions per gene are used in the final alignment. In contrast, the AAI and

ProbMinHash approaches should be more robust to changes of a small number of genes

because the entire proteome is considered [17].

Graph-based NNS methods achieve good performance compared to tree based

and locality-sensitive hashing (LSH) methods. Building a HNSW graph relies on proximity

of the database elements; so, if the distances among database elements, in our case

genomes, cannot be effectively estimated via hashing algorithms, the navigation in graph

will be less efficient (e.g., gets trapped in local minima) because the edges to choose

from will not be accurate estimations of the relatedness of the corresponding genomes.

This is especially problematic for highly sparse/distantly related and diverse datasets, like

the viral genome database, in which two phage genomes could often share very little

genomic information (kmers). This is confirmed by our own results when using nucleotide-

level search to build the viral graph. Hence, the amino acid level will be much more robust

for viral genomes and is the recommended level to use. Finally, the HNSW graph, and

graph-based K-NNS in general, can be further improved by adding shortcut edges and

maintaining a dynamic list of candidates, compared to a fixed list of candidates by default

[44]. Graph reordering, a cache optimization that works by placing neighboring nodes in

consecutive (or near-consecutive) memory locations, can also be applied to improve the

speed of HNSW [45]. Another new direction for graph based NNS will be using Graphics

Processing Unit (GPU) instead of CPU because GPUs are more efficient in handling

matrix computations and machine learning tasks [46]. We will explore these options in future

versions of GSearch.

To summarize, GSearch, based on Probminhash and HNSW, solves a major

current challenge in classification of microbial genomes, especially given the exponential

increase in the number of newly sequenced genomes due to its efficiency and scalability.

GSearch will serve the entire microbial sciences for years to come since it can be applied

to fungal, bacterial and viral genomes, while offering a common framework to identify,

classify and study all microbial genomes, and will accelerate the process to find new

biological knowledge.

Data availability

All the mentioned pre-built database for bacteria, fungi and phage genomes can be found

at: http://enve-omics.ce.gatech.edu/data/gsearch

Author Contribution

J.Z, L.M and K.K designed the work, J.Z and J.P-B wrote the code (Genome part and

algorithm part respectively), J.P-B implemented the Rust libraries of Kmerutils,

Probminhash and Hnswlib-rs. J.Z and K.K wrote the paper. J.Z did the analysis and

benchmark.

Acknowledgment

This work was supported, in part, by the US National Science Foundation (Award No 1759831 and 2129823 to KTK). We want to thank PACE (Partnership for Advanced Computing Environment) at Georgia Tech for providing computing resources. We want to thank Kenji Gerhardt for helpful discussions on benchmarking against traditional ANI/AAI based tools and Chirag Jain for discussions on the graph based nearest neighbor search.

References

1.   Bobay, L.-M. & Ochman, H. Biological species in the viral world. *Proceedings of the National Academy of Sciences* **115**, 6040-6045 (2018).
2.   Bobay, L.-M. & Ochman, H. Biological Species Are Universal across Life's Domains. *Genome Biology and Evolution* **9**, 491-501 (2017).
3.   Locey, K.J. & Lennon, J.T. Scaling laws predict global microbial diversity. *Proceedings of the National Academy of Sciences* **113**, 5970-5975 (2016).
4.   Chevallereau, A., Pons, B.J., van Houte, S. & Westra, E.R. Interactions between bacterial and phage communities in natural environments. *Nature Reviews Microbiology* **20**, 49-62 (2022).
5.   Federhen, S. Type material in the NCBI Taxonomy Database. *Nucleic Acids Research* **43**, D1086-D1098 (2014).
6.   Almeida, A. et al. A unified catalog of 204,938 reference genomes from the human gut microbiome. *Nature Biotechnology* **39**, 105-114 (2021).
7.   Nayfach, S. et al. A genomic catalog of Earth's microbiomes. *Nature Biotechnology* **39**, 499-509 (2021).
8.   Caro-Quintero, A. & Konstantinidis, K.T. Bacterial species may exist, metagenomics reveal. *Environmental microbiology* **14**, 347-355 (2012).
9.   Deng, L. et al. Viral tagging reveals discrete populations in Synechococcus viral genome sequence space. *Nature* **513**, 242-245 (2014).
10.   Rodriguez-R, L.M., Jain, C., Conrad, R.E., Aluru, S. & Konstantinidis, K.T. Reply to: "Re-evaluating the evidence for a universal genetic boundary among microbial species". *Nature Communications* **12**, 4060 (2021).
11.   Parks, D.H. et al. GTDB: an ongoing census of bacterial and archaeal diversity through a phylogenetically consistent, rank normalized and complete genome-based taxonomy. *Nucleic Acids Research* (2021).
12.   Roux, S. et al. IMG/VR v3: an integrated ecological and evolutionary framework for interrogating genomes of uncultivated viruses. *Nucleic acids research* **49**, D764-D775 (2021).

514   13.   Konstantinidis, K.T. & Tiedje, J.M. Genomic insights that advance the species definition
515   for prokaryotes. *Proceedings of the National Academy of Sciences* **102**, 2567-2572
516   (2005).
517   14.   Konstantinidis, K.T. & Tiedje, J.M. Towards a Genome-Based Taxonomy for
518   Prokaryotes. *Journal of Bacteriology* **187**, 6258-6264 (2005).
519   15.   Goris, J. et al. DNA–DNA hybridization values and their relationship to whole-genome
520   sequence similarities. *International Journal of Systematic and Evolutionary Microbiology*
521   **57**, 81-91 (2007).
522   16.   Ondov, B.D. et al. Mash: fast genome and metagenome distance estimation using
523   MinHash. *Genome Biology* **17**, 132 (2016).
524   17.   Jain, C., Rodriguez-R, L.M., Phillippy, A.M., Konstantinidis, K.T. & Aluru, S. High
525   throughput ANI analysis of 90K prokaryotic genomes reveals clear species boundaries.
526   *Nature Communications* **9**, 5114 (2018).
527   18.   Brown, C.T. & Irber, L. sourmash: a library for MinHash sketching of DNA. *Journal of
528   Open Source Software* **1**, 27 (2016).
529   19.   Bovee, R. & Greenfield, N. Finch: a tool adding dynamic abundance filtering to genomic
530   MinHashing. *Journal of Open Source Software* **3**, 505 (2018).
531   20.   Chaumeil, P.-A., Mussig, A.J., Hugenholtz, P. & Parks, D.H. GTDB-Tk: a toolkit to
532   classify genomes with the Genome Taxonomy Database. *Bioinformatics* **36**, 1925-1927
533   (2019).
534   21.   Rodriguez-R, L.M. et al. The Microbial Genomes Atlas (MiGA) webserver: taxonomic
535   and gene diversity analysis of Archaea and Bacteria at the whole genome level. *Nucleic
536   Acids Research* **46**, W282-W288 (2018).
537   22.   Wang, Q., Garrity, G.M., Tiedje, J.M. & Cole, J.R. Naïve Bayesian Classifier for Rapid
538   Assignment of rRNA Sequences into the New Bacterial Taxonomy. *Applied and
539   Environmental Microbiology* **73**, 5261-5267 (2007).
540   23.   Schloss, P.D. et al. Introducing mothur: Open-Source, Platform-Independent,
541   Community-Supported Software for Describing and Comparing Microbial Communities.
542   *Applied and Environmental Microbiology* **75**, 7537-7541 (2009).
543   24.   Indyk, P. & Motwani, R. in Proceedings of the thirtieth annual ACM symposium on
544   Theory of computing 604-613 (1998).
545   25.   Gionis, A., Indyk, P. & Motwani, R. in Vldb, Vol. 99 518-529 (1999).
546   26.   Bentley, J.L. Multidimensional binary search trees used for associative searching.
547   *Communications of the ACM* **18**, 509-517 (1975).
548   27.   Dasgupta, S. & Sinha, K. in Proceedings of the 26th Annual Conference on Learning
549   Theory, Vol. 30. (eds. S.-S. Shai & S. Ingo) 317--337 (PMLR, Proceedings of Machine
550   Learning Research; 2013).
551   28.   Dong, W., Moses, C. & Li, K. in Proceedings of the 20th international conference on
552   World wide web 577-586 (2011).
553   29.   Malkov, Y., Ponomarenko, A., Logvinov, A. & Krylov, V. Approximate nearest neighbor
554   algorithm based on navigable small world graphs. *Information Systems* **45**, 61-68 (2014).
555   30.   Fu, C., Xiang, C., Wang, C. & Cai, D. Fast approximate nearest neighbor search with the
556   navigating spreading-out graph. *arXiv preprint arXiv:1707.00143* (2017).
557   31.   Malkov, Y.A. & Yashunin, D.A. Efficient and Robust Approximate Nearest Neighbor
558   Search Using Hierarchical Navigable Small World Graphs. *IEEE Transactions on
559   Pattern Analysis and Machine Intelligence* **42**, 824-836 (2020).

560   32.   Aumüller, M., Bernhardsson, E. & Faithfull, A. ANN-Benchmarks: A benchmarking tool
561   for approximate nearest neighbor algorithms. *Information Systems* **87**, 101374 (2020).
562   33.   Ertl, O. ProbMinHash – A Class of Locality-Sensitive Hash Algorithms for the
563   (Probability) Jaccard Similarity. *IEEE Transactions on Knowledge and Data*
564   *Engineering*, 1-1 (2020).
565   34.   Camarillo-Guerrero, L.F., Almeida, A., Rangel-Pineros, G., Finn, R.D. & Lawley, T.D.
566   Massive expansion of human gut bacteriophage diversity. *Cell* **184**, 1098-1109.e1099
567   (2021).
568   35.   Konstantinidis, K.T., Rosselló-Móra, R. & Amann, R. Uncultivated microbes in need of
569   their own taxonomy. *The ISME Journal* **11**, 2399-2406 (2017).
570   36.   Chaumeil, P.-A., Mussig, A.J., Hugenholtz, P. & Parks, D.H. GTDB-Tk v2: memory
571   friendly classification with the Genome Taxonomy Database. *bioRxiv*,
572   2022.2007.2011.499641 (2022).
573   37.   Tan, S. et al. in Proceedings of the 27th ACM SIGKDD Conference on Knowledge
574   Discovery & Data Mining 1552–1560 (Association for Computing Machinery,
575   Virtual Event, Singapore; 2021).
576   38.   Moulton, R. & Jiang, Y. in 2018 IEEE International Conference on Data Mining (ICDM)
577   347-356 (2018).
578   39.   Břinda, K., Sykulski, M. & Kucherov, G. Spaced seeds improve k-mer-based
579   metagenomic classification. *Bioinformatics* **31**, 3584-3592 (2015).
580   40.   Joudaki, A., Rätsch, G. & Kahles, A. Fast Alignment-Free Similarity Estimation By
581   Tensor Sketching. *bioRxiv* (2021).
582   41.   Koslicki, D. & Zabeti, H. Improving MinHash via the containment index with
583   applications to metagenomic analysis. *Applied Mathematics and Computation* **354**, 206-
584   215 (2019).
585   42.   Bowers, R.M. et al. Minimum information about a single amplified genome (MISAG)
586   and a metagenome-assembled genome (MIMAG) of bacteria and archaea. *Nature*
587   *Biotechnology* **35**, 725-731 (2017).
588   43.   Tan, G. et al. Current Methods for Automated Filtering of Multiple Sequence Alignments
589   Frequently Worsen Single-Gene Phylogenetic Inference. *Systematic Biology* **64**, 778-791
590   (2015).
591   44.   Prokhorenkova, L. & Shekhovtsov, A. in Proceedings of the 37th International
592   Conference on Machine Learning, Vol. 119. (eds. D. Hal, III & S. Aarti) 7803--7813
593   (PMLR, Proceedings of Machine Learning Research; 2020).
594   45.   Coleman, B., Segarra, S., Shrivastava, A. & Smola, A. Graph Reordering for Cache-
595   Efficient Near Neighbor Search. *arXiv preprint arXiv:2104.03221* (2021).
596   46.   Groh, F., Ruppert, L., Wieschollek, P. & Lensch, H. GGNN: Graph-based GPU Nearest
597   Neighbor Search. *IEEE Transactions on Big Data*, 1-1 (2022).

Methods and Materials

Briefly, GSearch is composed of the following steps. Initially, the genetic relatedness

among a collection of database genomes is determined based on the ProbMinHash

algorithm, which computes the normalized weighted Jaccard distance using the

probminhash3a algorithm implemented in the ProbMinHash paper[1]. The normalized

weighted Jaccard distances are then used as input for building HNSW graphs (note that

a distance computation is required only when that genome pair is required for graph

building, thus GSearch avoids all vs. all distance computations). Genomes are

subsequently recursively added as the nearest neighbors of each node in the built graph

file with the same distance computation procedure. The built graph database file is stored

on disk. Query genomes are then searched against graph database and subsequently,

best neighbors are returned for classification/identification. In this process, the best

neighbor (or neighbors) is also identified based on the smallest normalized weighted

Jaccard distance obtained.

ProbMinHash

Details of differences between ProbMinHash and traditional MinHash can be found in

Supplenmentary Methods & Materials. We reimplemented the Probminhash algorithm in

Rust to estimate genetic relatedness between any two genomes based on normalized

(weighted) Jaccard distances according to the original ProbMinHash paper [1]

(Supplementary Note 1) . The Rust reimplementation of Probminhash can be found at:

https://github.com/jean-pierreBoth/probminhash.   Two   important   parameters   of

Probminhash are the sketch size and kmer size. Similar to MinHash sketches,

Probminhash sketches are also shared hashes from hashed kmer set by taking into

account the kmer weights and also total kmer count (See Figure 1 of MASH paper). Time

complexity analysis for ProbMinHash is shown in Supplementary Note 3.

To benchmark probminhash against MASH, both tools were run with the same

sketch size (s=12000) and kmer size (k=16) for bacterial genomes at the nucleotide level

and kmer size (k=7) at the amino acid level for both database building and searching. For

fungal genomes a larger sketch size (48000) was used due to much larger genome sizes.

Details of kmer choosing logic can be found in Supplementary Note 2. For graph search

results, we also performed the same transformation of MASH distance from normalized

weighted Jaccard distance to probMASH distance for convenient comparison to ANI

based methods.

$$probMASH = -\frac{1}{k} ln \frac{2 * J_p}{J_p + 1}$$

Hierarchical Navigable Small World Graphs (HNSW)

Generally, the framework of graph-based ANN search algorithm (here HNSW) can be

summarized as the following two steps: 1) build a proximity graph (HNSW) where each

node represents a database vector. Each database vector will connect with a few of its

neighbors while maintaining small world property in each layer of HNSW. 2) Given a query

vector (or sequence, kmer profile in our case), perform a greedy search on the proximity

graph by comparing the query vector with database vectors under the searching

measures (e.g., cosine similarity or L2 similarity, in our case probminhash distance).

Then, the most similar candidates are returned as outputs. The key point for these two-

step methods is step 1, to construct a high-quality index graph, which provides a proper

balance between the searching efficiency and effectiveness. To guarantee the searching

efficiency, the degree (number of maximum allowed neighbors, denoted as M) of each

node is usually restricted to a small number (normally 20~200) while width of search for

neighbor during inserting (denoted as ef_construct) is usually a larger number (higher

than 1000) to increase the chance to find best M neighbors by increasing the diversity of

neighbors due to the large number of neighbors retained. Building graph and searching

query against the graph follow very similar greedy search procedures except that there is

an extra reverse updating of neighbors list for each vector when inserting database vector

(building), one by one, into the existing graph (Figure 1a). The first phase of the

insertion/building process starts from the top layer by greedily traversing the graph in

order to find maximum M closest neighbors to the inserted element P in the layer by doing

*ef_*construct times search (Figure 1a). After that, the algorithm continues the search from

the next layer using the closest neighbor found from the previous layer as entry point, and

the process repeats until to the bottom layer. Closest neighbors at each layer are found

by a greedy and heuristic search algorithm (Figure 1b and c). For building, after searches

are finished at the bottom layer for each inserted element, a reverse update step will be

performed to update the neighbor list of each node in the existing graph while for

searching this is not needed. The overall database building time complexity is

O(N*log(N)), where N is the number of nodes in the graph. For searching, since there is

no need to reverse update best neighbor list for each node in the graph, time complexity

is (only) O(log(N)) (See Supplementary Note 3). Theoretical guarantee of graph-based

algorithm can be found in Supplementary Note 5. We reimplemented the original hnswlib

library written in C++ using the Rust programming language for its memory safety and

thread use efficiency [11,] which can be found here ([https://github.com/jean-](https://github.com/jean-pierreBoth/hnswlib-rs)

[pierreBoth/hnswlib-rs](https://github.com/jean-pierreBoth/hnswlib-rs)). Benchmarks for this package against standard datasets can be

found in the Supplementary Methods & Materials.

Details of program implementation in Rust

There are 2 modules in total: tohnsw and request. Tohnsw is to build graph by gradually

inserting genomes into graph while request is to query new genomes against the graph

database built in the tohnsw step. Tohnsw starts from reading database genomes and

generating kmer profile and sketches for distance calculation. By selecting a random

genome as the first genome to insert to the graph, tohnsw module gradually add genomes

to existing graph file following HNSW constructing rules mentioned above by computing

ProbMinHash distance between genomes. Whenever a genome is going to be inserted

into the existing graph, each genome in the graph is associated with a list that stores the

M closest neighbors/genomes to the genome and the distance to these neighbors. Then,

the distances of this genome with the nearest neighbors (M) of entry genome in this layer

will be computed/searched (ef_construct times) using probminhash3a algorithm and the

smallest distance of the neighbor genomes will be the new entry genome. This process

will be repeated until the nearest genomes (<= M) in the layer are found and

subsequently, the program will go to the layer below, using the genome that was

represented by the nearest genome in the above layer as new entry genome in the new

layer. The search layer algorithm is repeated until to the bottom layer is

reached/analyzed. In contrast to the default settings in the original hnswlib, we allow the

two parameters of neighbor selecting heuristics, *extendCandidates* to be true and

keepPrunedConnections to be false because our genomic data is extremely clustered

and there is no need to fix the number of connections per element considering the

maximum connection allowed. Request module will load the graph database and then

search query genomes against it to return the best neighbors of each query, following

exact the same procedure with building step without updating the database. Both tohnsw

and request module are operating in parallel for high performance (see Supplementary

Note 6). The GSearch software can be found here: https://github.com/jean-

pierreBoth/gsearch   GSearch   relies   on   Kmerutils   (https://github.com/jean-

pierreBoth/kmerutils), which is a Rust package we developed to manipulate genomic

fasta files including kmer string compression, kmer counting, filtering using cuckoo filter

et.al.

Installation guide, manual and pre-built binaries can also be found on the website. We

provide static binaries on the release page for major platforms such as Linux and MacOS,

with support for different CPU structures, e.g. Intel x86_64 or ARM64. GSearch program

can be run like this : 1) Build a graph database, which can be done running the following

command: tohnsw -d ./GTDB_r207 -k 16 -s 12000 -n 128 --ef 1600; 2) Request neighbors

of query genomes: request -b . -r ../query_folder -n 50 (--aa). Note that with the --add

option in tohnsw module, genomes in the directory will be added to existing graph

database, loaded from current directory, thus avoiding building graph database from the

very beginning when there are only a small number of new genomes species compared

to the current database. However, for larger number of new genome species, rebuild from

start is suggested to be able to choose an optimal M and ef_construct to maintain high

accuracy.

Prokaryotic classification pipeline

The amino-acid level graph showed that closest neighbors were found, with high

recall, when the query shared at least 52% AAI to its best neighbor. For more divergent

genomes, showing lower than 52% AAI, whole-genome amino-acid level graph loses

accuracy and we had to switch to universal, single-copy protein-coding genes. For the

nucleotide-level graph, we used kmer=16 for bacteria and archaea to have high specificity

for closely related database genomes (e.g., sharing about 95% ANI). For building the

whole-genome amino-acid graph, we used k=7 to have the best specificity without

compromising sensitivity, which is also consistent with previous results on classification

of amino acid sequences based on kmers [2]. For building graph based on universal gene

set, we use k=5 because of much smaller total amino acid size. For further details on the

range of kmer to use for bacteria genome and proteome, viral genome and proteome,

see Supplemental Notes 2.

The proteome of each genome was predicted by FragGeneScanRs v0.0.1 for

performance purpose as opposed to Prodigal despite small loss in precision

(Supplementary Table S5) [3]. Hmmsearch in the hmmer (v3.3.2) software [16] was used to

extract the universal gene set for bacteria and archaea genomes (universal gene graph).

Note that for viral genomes, this last step was not used because there are no universal

single copy genes for viral genomes. Evaluation of the speed and memory requirements

for all steps mentioned above were performed on a RHEL (Red Hat Enterprise Linux)

v7.9 with 2.70 GHz Intel(R) Xeon(R) Gold 6226 CPU. Unless noted otherwise, all 24

threads of the node are available by default.

Distributed implementation and database splitting

To accommodate the increasing number of genomes that become available at an

unprecedented speed in recent years and will soon reach 1 million or more, we provide

an option to randomly split the database into a given number of pieces and build graph

database separately for each piece. In the end, all best neighbors returned from each

piece will be pooled and sorted by distance to have a new best K neighbor collection

returned to the user for each query genome. We hereby prove that in terms of requesting

top K best neighbors, the database split strategy is equivalent to non-split database

strategy as long as the requested best neighbors for each database piece is larger than

or equals to requested best neighbors in the non-split strategy. The underlying reason is

that the best neighbors globally are also the best locally [4]. The database split and request

will be done sequentially, on one node, without multi-node support. For now, we split

GTDB database in to 5 pieces for testing purposes. In theory, a large database can be

split into any pieces as long as each piece can be used to build HNSW. In practice, a

reasonable way to decide on the number of database pieces to use is so that memory

requirement for each piece is equal or smaller than the total memory of host machine.

The database split idea has been used in several graph-based larger scale (e.g., billions)

nearest neighbor search tasks in industry [4, 5].

Species database and testing genomes for benchmarking and recall

GTDB version 207 was used to build the database for bacteria and archaea genome

species [6]. The IMGVR database version 3, with species representatives at a $\geq$95% ANI,

was used for for viral database building [7]. For fungal genomes, all genomes downloaded

from the MycoCosm project (on 24th Jan., 2022) were used [8]. The amino acid sequences

of predicted gene on the genomes were obtained using FragGeneScanRs. The Universal

Single Copy Gene (USCG) gene set for GTDB genomes were extracted via hmmer

software.

To test the performance of our pipeline, we specifically chose genomes that are

not included in the GTDB database (the database was used for graph building). In

particular, the bacterial/archaeal genomes, mostly MAGs, reported by Ye and colleagues

[9] and Tara Ocean MAGs (total 8,466 MAGs) [10] were used. We randomly selected 1000

genomes/MAGs from Ye's collection and use them as query genomes to test the

performance and accuracy of GSearch. To compare with other database search tools for

large database e.g., the viral database, we compare GSearch with PhageCloud [11], which

builds a graph database based on the labels of each viral genome (e.g., environment

source) and its search algorithm is Dashing2[12].

Recall of AAI-, ANI- and MinHash-based nearest neighbor searching for

bacteria/archaea, fungi and viral genomes.

To benchmark how GSearch performs compared to ANI/AAI- and MinHash-based tools,

we ran FastANI, Diamond blastp-based AAI and Mash to find the best neighbors for the

same query genome dataset and evaluated whether or not the best neighbors found by

GSearch were the same. FastANI parameters for the bacterial dataset were the following:

fastANI --ql query_path.txt --rl gtdb_path.txt -k 16 -p 24 --minFrac 3000 -o ANI.txt. GTDB

database was split into 50 subsets and each subset was parallelly run on a multi-node

supercomputer to reduce memory requirement. MASH parameters were: mash sketch -a

(for AA only) -k 21 (7 for AA) -s 12000 -p 24 GTDB/*.fna > gtdb.msh; mash dist -p 24

gtdb.msh query.msh. For AAI calculation, the corresponding script of the enveomics

package [13] was used: aai.rb -1 query.faa -2 db.faa -p diamond -t 24. Hmmer was used to

search for universal single copy gene against pre-built hmm profiles (120 for archaea and

122 for bacteria respectively); the profiles were obtained from the GTDB-Tk software. For

viral genomes, FastANI fragment size of 1000 was used instead of 3000 while aai.rb

fragment size was 500 instead of 1000 with minimal number of matches of 5. For viral

genomes, MASH kmer size of 11 and 7 was used for nucleotide and amino acid levels,

respectively. For fungal genomes, we use MUMMER v4.0.0 with default parameters for

ANI calculation [14]. Gene prediction for fungal genomes was performed using GeneMark-

ES v2 (--fungus --ES) [15]. Kmer size 21 and 11 was used for fungal genomes in MASH for

nucleotides and amino acid levels, respectively. Detailed description of kmer size for each

type of genome can be found in Supplemental Note 2.

We calculated recall for our tool compared to standard ANI/AAI and MASH in the

following way: since biological species database are generally sparse because we are far

away from sequencing all species in the environment and likely the existence of natural

gaps in diversity, a larger top K by HNSW (e.g., 100) compared to the value used in

standard benchmark dataset will offer little, if any advantage, especially when the query

genomes are relatively new, e.g. a new family compare to database genomes. Therefore,

we use top 5 and 10. Top 5 and top 10 recall are calculated based on top 5 and 10

neighbors found by GSearch and the alterantive tools, and if all top 5 or 10 found by the

latter tools were also in top 5 or 10 of our tool, then recall was 100%. Similarly, if only 4

or 9 are found by our tools, then recall was 80% and 90% respectively. However, if the

distance of query to some of the top 10 or top 5 neighbors found by GSearch at the

nucleotide level was larger than 0.9850 for bacterial genomes, these matches will be

filtered out and only those neighbors below 0.9850 will be used (e.g. 8 out of 10 are kept,

so only top 8 is compared) because we have shown that above this threshold, MinHash-

based methods will lose accuracy and this is not specific to HNSW. Similar rules were

applied for the amino acid level searches with the threshold value of 0.9720 used for

filtering out bacterial genomes.

References

1. Ertl, O. ProbMinHash – A Class of Locality-Sensitive Hash Algorithms for the (Probability) Jaccard Similarity. *IEEE Transactions on Knowledge and Data Engineering*, 1-1 (2020).

2. Déraspe, M., Boisvert, S., Laviolette, F., Roy, P.H. & Corbeil, J. Fast protein database as a service with kAAmer. *bioRxiv*, 2020.2004.2001.019984 (2020).

3. Van der Jeugt, F., Dawyndt, P. & Mesuere, B. FragGeneScanRs: faster gene prediction for short reads. *BMC Bioinformatics* **23**, 198 (2022).

4. Malkov, Y.A. & Yashunin, D.A. Efficient and Robust Approximate Nearest Neighbor Search Using Hierarchical Navigable Small World Graphs. *IEEE Transactions on Pattern Analysis and Machine Intelligence* **42**, 824-836 (2020).

5. Fu, C., Xiang, C., Wang, C. & Cai, D. Fast approximate nearest neighbor search with the navigating spreading-out graph. *arXiv preprint arXiv:1707.00143* (2017).

6. Parks, D.H. et al. GTDB: an ongoing census of bacterial and archaeal diversity through a phylogenetically consistent, rank normalized and complete genome-based taxonomy. *Nucleic Acids Research* (2021).

7. Roux, S. et al. IMG/VR v3: an integrated ecological and evolutionary framework for interrogating genomes of uncultivated viruses. *Nucleic acids research* **49**, D764-D775 (2021).

8. Grigoriev, I.V. et al. MycoCosm portal: gearing up for 1000 fungal genomes. *Nucleic acids research* **42**, D699-D704 (2014).

9. Ye, L., Mei, R., Liu, W.-T., Ren, H. & Zhang, X.-X. Machine learning-aided analyses of thousands of draft genomes reveal specific features of activated sludge processes. *Microbiome* **8**, 1-13 (2020).

10. Nishimura, Y. & Yoshizawa, S. The OceanDNA MAG catalog contains over 50,000 prokaryotic genomes originated from various marine environments. *Scientific Data* **9**, 305 (2022).

11. Rangel-Pineros, G. et al. From Trees to Clouds: PhageClouds for Fast Comparison of~ 640,000 Phage Genomic Sequences and Host-Centric Visualization Using Genomic Network Graphs. *PHAGE* **2**, 194-203 (2021).

12. Baker, D.N. & Langmead, B. Dashing 2: genomic sketching with multiplicities and locality-sensitive hashing. *bioRxiv* (2022).

13. Rodriguez-R, L.M. & Konstantinidis, K.T. (PeerJ Preprints, 2016).

14. Marçais, G. et al. MUMmer4: A fast and versatile genome alignment system. *PLOS Computational Biology* **14**, e1005944 (2018).

15. Ter-Hovhannisyan, V., Lomsadze, A., Chernoff, Y.O. & Borodovsky, M. Gene prediction in novel fungal genomes using an ab initio algorithm with unsupervised training. *Genome research* **18**, 1979-1990 (2008).

Figures

Figure 1. **Schematic overview of GSearch building graph and searching graph**

steps. (a) Graph was clasped into hierarchical layers following exponential decay

probability. In this graph, *ef* and *M*, represent the number of searches when finding

nearest neighbors and maximum allowed number of neighbors for each node,

respectively (See Materials and Methods for details). In each layer, starting from an

entry node (random or inherit from layer above it, depending on whether it is the top

layer or not), GSearch finds the closest connected neighbor of the entry node and

assigns it as the new entry point P (b), and then traverses in a greedy manner (i.e.,

update the entry point using the newly found closest connected neighbor (c)) until the

nearest neighbor in the layer is found, and then goes to next layer. This process is

repeated until the required number of nearest neighbors are all found for the given new

querying/inserting point. For building graph, after the required number of nearest

neighbors are found, a reverse update step is performed to update neighbor list of all

nodes in the graph.

924 **Figure 2**. **Scalability of database building process with the number of threads used**.

925 Panels show total wall time (y=axes) for building GTDB genome (nucleotide level) (a), whole-

926 genome proteome (amino acid level) (b) and universal gene set proteome (c) databases. All

927 tests were run on a 24-thread Intel (R) Xeon (R) Gold 6226 processor, with 40GB memory

928 available.

942
943
Figure 3. **Total request time (wall time) for searching query genomes against the pre-built**
reference databases. Shown are all GTDB genomes (v207) at the whole-genome nucleotide
(a), whole-genome proteome (b) and universal gene set proteome (c) levels. 100, 300 and 1000
query genomes (figure key) were used on a 24-thread Intel (R) Xeon (R) Gold 6226 processor.
On average, database loading time ranged from 5-10 seconds. (d) is time needed to classify the
same genomes using GTDB-Tk on the same 24-thread node.
967 **Figure 4**. **Overview of the GSearch pipeline for classifying prokaryotic genomes**. Orange
968 boxes denote steps that aim to prepare genome files, in different formats, for graph building

while green boxes denote building steps of the graph database (in nucleotide or amino acid format). Blue boxes indicate input/query genomes to search against the database while grey boxes indicate classification output for each input. Gene prediction was done using FragGeneScanRs and hmmsearch as part of the hmmer software for homology search. Two key steps of GSearch: tohnsw (aa) and request (aa) are used to build graph database and request new genomes, respectively. Two thresholds are used in the pipeline to decide between whole nucleotide vs. whole-genome amino acid search and whole-genome amino acid vs. universal gene amino acid, 78% ANI and 52% AAI, corresponding to Probminhash distance 0.9850 and 0.9375, respectively (see main text for details).

Tables

Table 1. Request/search performance on major CPU platforms for GTDB v207 database for 1000 queries.

CPU	Number of threads	Clock speed (GHz)	**Request time for nt (min)**	Gene Prediction-FGSrs (min)[c]	**Request time for proteome (min)**	hmmsearch time (min)[d]	**Request time for USCG (min)**
Intel (R) Xeon (R) Gold 6226[a]	24	2.70	**2.329**	1.348	**1.334**	0.524	**0.117**
Intel (R) Core i7-7770HQ[b]	8	2.80	**8.654**	6.764	**2.041**	1.534	**0.510**
AMD EPYC 7513a[a]	32(24 used)	2.60	**1.937**	1.120	**1.021**	0.345	**0.102**
Apple M1 Pro[b]	10	3.22	**2.369**	2.12	**0.866**	0.498	**0.168**

997
998
[a] RHEL v7.9, Linux v3.10.0-1160, all threads used.
[b]MacOS v12.3, Darwin 21.4.0, all threads used.
[c]Parallel package was used to run multiprocess at the same time. FGSrs stands for FragGeneScanRs. Note that in practice only
those genomes failed in the Request for nt step (best found is less than 78% ANI) will be used in this step.
[d]Only 100 genomes are used for testing hmmsearch because this step is for very new genomes at order level or above and we
often do not have that many new genomes in a real-world dataset. Parallel Packages was used to run multiple processes of
hmmsearch, one thread per process for hmmsearch.
1006
1007