GSearch: Ultra-Fast and Scalable Microbial Genome Search by Combining K-mer

Hashing with Hierarchical Navigable Small World Graphs

Jianshu Zhao[1,2,7], Jean Pierre Both[3,7], Luis M. Rodriguez-R[4,5,6], Konstantinos T.

Konstantinidis[1,2,4,*]

[1]Center for Bioinformatics and Computational Genomics, Georgia Institute of Technology, Atlanta,

Georgia, USA

[2]School of Biological Sciences, Georgia Institute of Technology, Atlanta, Georgia, USA

[3]Université Paris-Saclay, CEA, List, Palaiseau, France

[4]School of Civil and Environmental Engineering, Georgia Institute of Technology, Atlanta,

Georgia, USA

[5]Department of Microbiology, University of Innsbruck, Innsbruck, Austria

[6]Digital Science Center (DiSC), University of Innsbruck, Innsbruck, Austria

[7]Those authors contribute equally

[*]Corresponding author, Konstantinos T. Konstantinidis (kostas.konstantinidis@gatech.edu)

Running title: Approximate nearest neighbor (ANN) search for microbial genomes based on

MinHash-like metrics

Abstract

Genome search and/or classification is a key step in microbiome studies and has recently become

more challenging due to the increasing number of available (reference) genomes and the fact that

traditional methods do not scale well with large databases. By combining k-mer hashing-based

probabilistic data structures (e.g., (Prob/Super/Densified)-MinHash or SetSketch) to estimate

genomic distance, with a graph-based nearest neighbor search algorithm (called Hierarchical

Navigable Small World Graphs, or HNSW), we created a new data structure and developed an

associated computer program, GSearch, that is orders of magnitude faster than alternative tools

while maintaining high accuracy and low memory usage. For example, GSearch can

identify/classify 8,000 query genomes against all available microbial or viral genomes

(n=~318,000 or ~3,000,000) within a few minutes on a personal laptop, using only ~6GB of

memory or less (e.g., 2.5G via SetSketch). Notably, GSearch will be even faster compared to

other tools with even larger database size due to $O(\log(N))$ time complexity and will scale well

with billions of database genomes based on a database splitting strategy. Further, GSearch

implements a three-step classification pipeline that accounts for the degree of novelty of query

genomes relative to the database genome to maximize specificity and sensitivity. Therefore,

GSearch solves a major bottleneck of microbiome studies that require genome search and/or

classification of microbial or viral genomes. GSearch is available at: https://github.com/jean-

pierreBoth/gsearch

Keywords: microbial genomes, MAGs, probabilistic data structure, sketching, MinHash,

HyperLogLog, nearest neighbor search, classification

Introduction

Identifying or classifying microbial species based on either universal marker genes (e.g., 16S or 18S rRNA genes) or entire genomes represents a re-occurring task in environmental and clinical microbiome studies. However, this task is challenging because the microbial genomes in nature are still severely under-sampled by the available genomes. For instance, there are more than 10^{12} prokaryotic and fungal species in nature according to a recent estimation based on 16S rRNA gene or ITS (Internal Transcribed Spacer) analysis (1), and even more viral species (e.g. the number of viral cells outnumbers that of prokaryotic cells by a about a factor of ten in most natural habitats) (2). The number of total prokaryotic genomes (not necessarily completed, named or described biologically) has reached ~318,000 in the newest release of the NCBI/RefSeq prokaryotic database (until Feb. 2023), and > 12 million in the latest IMG/VR4 database for viruses, representing 65,703 prokaryotic and 8.7 million viral distinct species if clustered at the 95% ANI (average nucleotide identity) level (3,4). The number of microbial database genomes is growing at a speed faster than transistors. This has created a new challenge, however; that is, identifying/searching newly sequenced genomes against these large databases to find closely related database/reference genomes for taxonomy classification has become impractical if an all-versus-all comparison strategy is applied. Further, due to the recent improvements in DNA sequencing and single-cell technologies, metagenomic surveys can now recover hundreds, if not thousands, of these yet-to-be-described genomes (or MAGs, metagenomic assembled genomes) from environmental or clinical samples in a single study (5,6), filling in the gap in the described diversity mentioned above but also further exacerbating the database size problem. In addition to the searching strategy, the actual algorithm used to determine overall genetic relatedness (e.g., ANI or its approximate) between the query and the databased genomes is critical. While the traditional Blastn-based ANI among closely related genomes at the species level, and the

genome-aggregate average amino acid identity (AAI) for genomes related at the genus level or

above, have been proven to be highly accurate for genetic relatedness estimation across

microbial and viral genomes (7-10), they are too slow to use when dealing with more than a few

dozen of genomes. Recently, phylogenetic replacements methods using a handful of universal

genes (n ≈ 100) have become popular, but these methods can be memory demanding and slow

(11,12), especially for a large number of or a few deep-branching (novel) query genomes. This

approach cannot be applied to viral genomes, which lack universal genes. Further, universal

genes due to their essentiality, are typically under stronger purifying selection and thus, evolve

slower than the genome average. This property makes universal genes appropriate for

comparisons among distantly related genomes, e.g., to classify genomes belonging to a new

class or a new phylum, but not the species and genus levels (11,13).

Faster and more memory efficient ANI estimation based on k-mer hashing and

evolutionary models have been recently described in tools like FastANI, Mash, Dashing and

BinDash (14-18) that aim to alleviate this computational bottleneck. The above-mentioned tools

typically rely on probabilistic data structures (or sketching algorithms) such as MinHash (a class

of locality sensitive hashing) (19), HyperLogLog (20) or a combination of two, called SetSketch

(21) to estimate genomic distance. Importantly, MinHash-like algorithms have been shown to be

an unbiased estimation of the Jaccard index $Jaccard(A, B) = \frac{A \cap B}{A \cup B}$ (note that Jaccard index

considers only element/k-mer presence/absence in a set, unweighted) between two genomes, an

accurate proxy to ANI or mutation rate after appropriate transformation (e.g., $ANI/(1 - Mash) =$

$1 + \frac{1}{k} log \frac{2*J}{1+J}$, where J is the Jaccard index and k is k-mer size, also called Mash equation) with

Poisson distribution assumption and an evolutionary model (14). However, MinHash-like

algorithm can be less space efficient (e.g., use more memory) for large number of genomes than

HyerLogLog, HyerLogLog++ or SetSketch despite being more accurate (21). The latter algorithms

can also be used to estimate Jaccard index after estimating the set cardinality (Supplementary

Note 1.) (16). However, Jaccard index (simple, unweighted) estimated by MinHash-like sketching

algorithms can be problematic for incomplete genomes due to bottom-k sketch implementation

(22) (14), which are commonly recovered from metagenomic surveys. Further, unweighted

Jaccard estimate could be similarly inaccurate for genomes with extensive repeats such as

several microbial eukaryotic genomes because this estimate does not take into account the

abundance of k-mers (k-mer multiplicity). Weighted Jaccard index such as those provided by

ICWS and ProbMinHash have been recently developed to address this limitation (23,24) (see

also Supplementary Note 1). The application of weighted (or unweighted) MinHash-like algorithms

for genome search (that is to search for the closest genomes) problem can still be slow despite

the algorithms themselves being fast, because these algorithms are typically applied in a "brute

force" manner. That is, all query genomes are searched against all database genomes (i.e., "all

vs. all"), and thus computational time grows in a linear fashion as the number of database genome

increases. More importantly, in the case of searching a database, locality sensitive hashing

property of those probabilistic data structures should be satisfied to ensure high recall or accuracy.

One of the most broadly used approaches for finding closely related information to a query,

while circumventing an all vs. all search, is the K-Nearest Neighbor Search (K-NNS). The K-NNS

approach has been used -for instance-for 16S rRNA gene-based classification followed by a vote

strategy (25). Approximate nearest neighbor search (ANNS) algorithms, such as locality-sensitive

hashing (LSH) (26), k-dimension tree (27), random projection tree (28), k-graph (29) and proximity

graph (30-32) have been recently used to greatly accelerate search processes with only small

loss in accuracy. Proximity graph, as implemented for example in the hierarchical navigable small

world graph (HNSW), has been shown to be one of the fastest ANN search algorithms(33,34)

with search time complexity $O(log(N))$. HNSW incrementally builds a multi-layer structure

consisting of a hierarchical set of proximity graphs (layers) for nested subsets of the stored

elements. Then, through smart neighbor selection heuristics, inserting and searching the query

elements in the proximity graphs can be very fast while preserving high accuracy, even for highly

clustered data (31). Therefore, finding the closest genomes in a database can be substantially

accelerated by combining two sub-linear algorithms while maintaining ANI/AAI accuracy:

MinHash-like or HyperLogLog sketching algorithms for genomic distance estimation and HNSW

for finding nearest neighbors. This is an idea that, to the best of our knowledge, has never been

applied to genome search despite its potential to greatly accelerate genome search.

Here, we describe GSearch (for Genome Search), a computer program that combines

one of the most efficient nearest neighbor search approaches (HNSW) with MinHash-based or

SetSketch-based universal approaches to measure genetic relatedness among any microbial

genomes, including fungal and viral genomes. Four MinHash-like algorithms, Densified MinHash

(35,36), ProbMinHash (24), SuperMinHash (37) and SetSketch (21), due to their locality sensitive

hashing property for nearest neighbor search, are provided as part of GSearch for the advantages

that each provides in terms of accuracy or speed. Densified MinHash, which borrows hash values

from non-empty bins to fill empty bins in the sketch vectors, which are generate based on One

Permutation MinHash, is by far the fastest MinHash-like algorithm due to just one hash function

used, also can be as accurate as classic MinHash. SuperMinHash is similar to classic MinHash

but optimized in terms of accuracy to calculate simple Jaccard index, sacrificing speed.

ProbMinHash (default) is based on shared k-mers, weighted by their abundance, and normalized

by total k-mer count. Accordingly, ProbMinHash can account for genome incompleteness of

prokaryotic genomes and repeats (k-mer multiplicity, or k-mer weight) commonly found in

eukaryotic and sometimes in prokaryotic genomes. Essentially, ProbMinHash computes the

normalized weighted Jaccard-like index J_P (Supplemenatary Note 1) between each pair of

genomes. SetSketch is a new data structure aiming at both space efficiency and speed, which

fills the gap between MinHash (speed and accuracy, locality sensitive hashing) and HyperLogLog

(space). SetSketch can be used for both cardinality estimation and set similarity (1-Jaccard index)

and is also a locality sensitive hashing algorithm, providing an advantage over HyperLogLog and

MinHash sketching algorithms (e.g., low memory usage and also high accuracy). The Jaccard

similarity (1- Jaccard index) calculated by either of the above methods is used as input to build

HNSW graph of the database genomes. Accordingly, the search of the query genome(s) against

the graph database to find the nearest neighbors for classification purposes becomes an ultra-

fast step and can be universally applied to all microbial genomes. The novelty of GSearch also

includes a hierarchical pipeline that involves both nucleotide-level (when query genomes have

close relatives at the species level) and amino-acid-level searching (when query genomes

represent novel species), which provides robust classification for query genomes regardless of

their degree of novelty relative to the database genomes, as well as a database-splitting strategy

that allows GSearch to scale up well to billions of database genome sequences. GSearch was

implemented in the Rust programming language for high performance.

Materials and Methods

GSearch is composed of the following steps. Initially, the genetic relatedness among a collection

of database genomes is determined based on the sketching algorithm Densifed MinHash,

ProbMinHash, SuperMinHash or SetSketch (24,35-37), which compute the normalized weighted

Jaccard-like index J_p using the probminhash3a algorithm (ProbMinHash option) or the simple

Jaccard index J in the SetSketch/SuperMinHash/Densified MinHash options, as implemented in

the probminhash package. The normalized weighted Jaccard-like similarity (1-J_p) or Jaccard

similarity (1-J) is then used as input for building HNSW graphs (note that a distance computation

is required only when that genome pair is required for graph building, thus GSearch avoids all vs.

all distance computations) (Figure 1a). Genomes are subsequently recursively added as the

nearest neighbors of each node in the built graph file with the same distance computation

procedure (Figure 1b). The built graph database and sketches from the MinHash-like algorithm

are stored on disk, including a graph file from HNSW as the main component of this new data

structure. Each node/genome in the graph has a corresponding sketching in the sketching file

(Figure 1c). Query genomes are then searched against graph database after loading the database

files and subsequently, best neighbors are returned for classification/identification. In this process,

the best neighbor (or neighbors depending on the number of neighbors requested) is also

identified based on the smallest ProbMinHash distance (1-J_p) or Jaccard distance (1-J) obtained.

The output can then be transformed into ANI/AAI values. The details of overall Rust

parallel/concurrent implementation can be found in Figure S9. Parallel efficiency and memory

usage of database building and searching can be found in Figures S10 and S11.

MinHash-like algorithm Implementation and Benchmark

A detailed description of the differences between ProbMinHash and traditional MinHash can be

found in Supplenmentary Materials and Methods. We reimplemented the ProbMinHash algorithm

in Rust to estimate genomic relatedness between any two genomes based on normalized

weighted Jaccard-like similarity 1-J_p according to the original ProbMinHash paper

(24)(Supplementary Note 1). The MSE (Mean Standard Error) of ProbMinHash is $J_p(1-J_p)/m$,

where m is the sketch size or number of registers, similar to that of classic Jaccard index $J(1-$

$J)/m$. Essentially, when objects/k-mers are hashed, they represent probability distributions

(Relative Frequency of k-mers after normalization), and J_p is a natural extension of J with good

properties for estimating distance among various genomes. The Rust reimplementation of

ProbMinHash, and other related MinHash-like algorithms, can be found at:

https://github.com/jean-pierreBoth/probminhash. We relied on version 0.1.10 of probminhash

package for this study. There are 11 different MinHash-like algorithms in this library (all are metric

since J and J_p is metric): One Permutation MinHash with Optimal Densification, Faster

Densification, SuperMinHash, ProbMinHash1, ProbMinHash1a, ProbMinHash2, ProbMinHash3,

ProbMinHash3a, ProbMinHash4, OrderMinHash and SetSketch (locality sensitive hashing

estimator (LSH) and Joint Maximum Likelihood Estimator, JMLE). Details of the locality sensitive

hashing and JMLE implementation for SetSketch, densified MinHash can be found in

Supplementary Methods and Materials. Specifically, when Jaccard index is smaller than 0.01 for

queries with their best neighbors/genomes found, we then use JMLE instead of LSH estimator in

SetSketch since JMLE is more accurate for small Jaccard.

To benchmark ProbMinHash against Mash and Dashing 1/2 et.al., all tools were run with

the same sketch size (s=12000) and k-mer size (k=16) for bacterial genomes at the nucleotide

level and k-mer size (k=7) at the amino acid level for both database building and searching. For

fungal genomes a larger sketch size (s=48000) was used due to much larger fungal genome sizes.

Further details on choosing the k-mer size can be found in Supplementary Note 2. For convenient

comparison of GSearch results against those of the Mash and ANI based methods, we performed

the same transformation of Mash distance from normalized weighted Jaccard like distance J_p to

probMASH distance as a proxy of ANI using the equation. Details of the mentioned benchmark

softwares can be found in Supplementary file 3.

209
$$probMASH = 1 + \frac{1}{k} log \frac{2 * J_p}{1 + J_p}$$

Hierarchical Navigable Small World Graphs (HNSW)

Generally, the framework of graph-based ANN search algorithm (here HNSW) can be

summarized in the following two steps: 1) build a proximity graph (HNSW) where each node

represents a database vector (or genome profiles in our case). Each database vector will connect

with a few of its neighbors while maintaining small world property in each layer of HNSW. 2) Given

a query vector (or sequence, kmer profile in our case), perform a greedy search on the proximity

graph by comparing the query vector with database vectors under the searching measures (e.g.,

cosine similarity or L2 similarity; in our case ProbMinHash distance). Then, the most similar

candidates are returned as outputs. The key task for these two-step methods is to construct a

high-quality index graph, which provides a proper balance between the searching efficiency and

effectiveness. To guarantee the searching efficiency, the degree (number of maximum allowed

neighbors, denoted as M) of each node is usually restricted to a small number (normally 20~200)

while width of search for neighbor during inserting (denoted as ef_construct) is usually a larger

number (higher than 1000) to increase the chance to find best M neighbors by increasing the

diversity of neighbors due to the large number of neighbors retained. Graph is subsequently

clasped into hierarchical layers following exponential decay probability. Building graph (e.g., insert

into graph) and searching query against the graph follow the same greedy search procedure

except that there is an extra reverse updating of neighbors list for each vector when inserting

database vectors (genomes), one by one, into the existing graph until all genomes are inserted

(Figure 1a). For building, after searches are finished at the bottom layer for each inserted element,

a reverse update step will be performed to update the neighbor list of each node in the existing

graph, while for searching/quering against the graph this step is not needed. The overall database

building time complexity is $O(N*log(N))$, where N is the number of nodes in the graph. The first

phase of the searching process starts from the top layer by greedily traversing the graph to find

maximum M closest neighbors to the new node element P in the layer by doing *ef*_construct times

search (Figure 1c). After that, the algorithm continues the search from the next layer using the

closest neighbor found from the previous layer as entry point, and the process repeats until to the

bottom layer. Closest neighbors at each layer are found by a greedy and heuristic search

algorithm (Figure 1d and e). For searching, since there is no need to reverse update best neighbor

list for each node in the graph, time complexity is (only) $O(\log(N))$ as explained above (See

detailed complexity analysis on Supplementary Note 3). Theoretical guarantee of graph-based

algorithm can be found in Supplementary Note 5. We reimplemented the original hnswlib library

written in C++ using the Rust programming language for memory safety, efficient parallelism and

speed. We also implemented memory map in the newest version, a feature not in the original C++

library that is useful for billions of data points or genomes. The implementation can be found at

https://github.com/jean-pierreBoth/hnswlib-rs. Version 0.1.19 was used in this study.

Benchmarking of this package against standard datasets and comparison with other

implementations can be found in the Supplementary Materials and Methods.

Details of program implementation in Rust

There are 3 modules in total: tohnsw, add and request. Tohnsw is to build the graph by gradually

inserting genomes into graph while request is to query new genomes against the graph database

built in the tohnsw step. Tohnsw starts from reading database genomes and generating k-mer

profile and sketches using ProbMinHash3a algorithm (or SuperMinHash, SetSketch and

Densified MinHash) for distance calculation (Figure 1a and c). Next, tohnsw selects, at random,

the first batch of genomes to insert into the graph (Figure 1a (1)), following HNSW constructing

rules mentioned above and taking into account the computed ProbMinHash distance ($1-J_p$) or

SetSketch/SuperMinHash/Densifed MinHash approximated Jaccard distances ($1-J$) between

genomes to connect genomes based on their relatedness (Figure 1b) until all genomes in

database have been inserted (Figure 1a (2), (3) and (4)). Finding nearest genomes for the

genome to be inserted is essentially a search process but search in a partially built graph, which

is similar to the request/search module: whenever a genome is going to be searched against the

existing graph, each genome in the graph is associated with a list that stores the M closest

neighbors/genomes to the genome and the distance to these neighbors. Then, the distances of

this genome with the nearest neighbors (M) of entry genome in each layer will be computed

(ef_construct times) using probminhash3a algorithm or SetSketch and the smallest distance of

the neighbor genomes will be the new entry genome (Figure 1d and e). This process will be

repeated until the nearest genomes (<=M) in the layer are found and subsequently, the program

will go to the layer below, using the genome that was represented by the nearest genome in the

above layer as new entry genome in the new layer. The search layer algorithm is repeated until

the bottom layer is reached/analyzed (Figure 1c). In contrast to the default settings in the original

hnswlib, we allow the two parameters of neighbor selecting heuristics, *extendCandidates* to be

true and *keepPrunedConnections* to be false because our genomic data is extremely clustered

and there is no need to fix the number of connections per element considering the maximum

connection allowed. The "Add" module is to add new genomes to pre-built HNSW database using

default parameters loaded in the pre-built database files. Request module will load the graph

database and then search query genomes against it to return the best neighbors of each query,

following exact the same procedure with building step without updating the database. Tohnsw,

add, and request modules are all operating in parallel for high performance (see Supplementary

Note 6 and Table S9, S10 and S11). GSearch relies on kmerutils v0.0.10 (https://github.com/jean-

pierreBoth/kmerutils), which is a Rust package we developed to manipulate genomic fasta files

including k-mer string compression, recursive k-mer hashing, k-mer counting, filtering using

cuckoo filter. All tests performed in this study were based on GSearch version 0.1.3. Scripts for

reproducing   the   results   of   this   study   can   be   found   here:

https://github.com/jianshu93/gsearch_analysis. The GSearch package can be found here:

https://github.com/jean-pierreBoth/gsearch.

Prokaryotic classification pipeline

The amino-acid level graph showed that the closest database neighbors were found, with high

recall, when the query shared at least 52% AAI to its best neighbor. For more divergent genomes

(<52% AAI), whole-genome amino-acid level graph loses accuracy and we had to switch to

universal, single-copy protein-coding genes. For the nucleotide-level graph, we used k-mer=16

for bacteria and archaea to have high specificity for closely related database genomes (e.g.,

sharing about 95% ANI). For building the whole-genome amino-acid graph, we used k=7 to have

the best specificity without compromising sensitivity, which is also consistent with previous results

on classification of amino acid sequences based on k-mers (38). For building graph based on

universal gene set, we use k=5 because of much smaller total amino acid size. For further details

on the range of k-mer to use for bacteria genome and proteome, and viral genome and proteome,

see Supplemental Notes 2.

The proteome of each genome was predicted by FragGeneScanRs v0.0.1 for performance

purposes as opposed to Prodigal software despite small loss in precision (39) (Supplementary

Table S11). Hmmsearch in the hmmer (v3.3.2)(40) software was used to extract the universal

gene set for bacteria and archaea genomes (universal gene graph). Note that for viral genomes,

this last step was not implemented because there are no universal single copy genes for viral

genomes. Evaluation of the speed and memory requirements for all steps mentioned above were

performed on a RHEL (Red Hat Enterprise Linux) v7.9 with 2.70 GHz Intel(R) Xeon(R) Gold 6226

CPU. Unless noted otherwise, all 24 threads of the node were available by default.

Distributed implementation and database splitting

To accommodate the increasing number of genomes that become available at an unprecedented

speed in recent years and will soon reach 1 million or more microbial genomes, we provide an

option to randomly split the database into a given number of pieces and build graph database

separately for each piece. In the end, all best neighbors returned from each piece will be pooled

and sorted by distance to have a new best K neighbor collection returned to the user for each

query genome. We hereby prove that in terms of requesting top K best neighbors, the database

split strategy is equivalent to non-split database strategy if the requested best neighbors for each

database piece is larger than or equals to requested best neighbors in the non-splitting strategy.

The underlying reason is that the best neighbors for a given query globally (non-splitting) are also

the best locally for the same piece of database (e.g., best 5 neighbors in piece #1 locally -meaning

only in this piece- maybe also be the best n=<5 neighbors genomes globally). The database

splitting and request can be done sequentially, on a single node, without multi-node support. In

theory, a large database can be split into any number of pieces. In practice, a reasonable way to

decide on the number of database pieces to use is so that memory requirement for each piece is

equal or smaller than the total memory of host machine.

Species database and testing genomes for benchmarking and recall

GTDB version 207 and entire NCBI/RefSeq prokaryotic genomes (as of Feb. 2023) was used to

build the database for bacteria and archaea genomes. The IMGVR database version 4, with

species representatives at a ≥95% ANI, was used to build the database for viruses (a total of ~3

million). For fungal genomes, all genomes downloaded from the MycoCosm project (as of Jan.

2022) were used (41). The amino acid sequences of predicted genes on the genomes were

obtained using FragGeneScanRs for bacteria/archaea and GeneMark-ES version 2 for fungi

(42). The Universal Single Copy Gene (USCG) gene set for GTDB genomes were extracted via

hmmer software (40).

To test the performance of our pipeline, we specifically chose genomes that are not included in

the GTDB database (the database was used for graph building). In particular, the

bacterial/archaeal genomes, mostly MAGs, reported by Ye and colleagues (43) and Tara Ocean

MAGs (total 8,466 MAGs) (44) were used. We randomly selected 1000 genomes/MAGs from

Ye's collection and use them as query genomes to test the performance and accuracy of

GSearch.

Recall of AAI-, ANI- and MinHash-based nearest neighbor searching for bacteria/archaea, fungi

and viral genomes.

To benchmark GSearch performance compared to traditional ANI/AAI- and/or MinHash-based

tools, we ran brute-force Blastn-ANI/FastANI (MUMMER for fungi ANI), Blastp-based AAI to find

the best neighbors for the same query genomes in different dataset and evaluated whether the

best neighbors found by GSearch were the same as those found by Blastn-ANI/FastANI and

blastp-based AAI. Briefly, we used the well-known average recall as the accuracy measurement

(45). Given a query genome, GSearch is expected to return k best genomes. Then we examined

how many genomes in this returned set were among the true k nearest neighbors (NN) of the

query found by the reference brute-force Blastn-ANI and/or Blastp-based AAI. Suppose the

returned set of k genomes given a query is R' and the true k nearest neighbors set of the query

(from   Blastn-ANI   or   blastp-based   AAI)   is   R,   the   recall   is   defined   as:

$recall(R') = \frac{|R' \cap R|}{|R|}$.   Then,   the   average   recall   represents   the   mean   of   all   the   query

datasets/genomes. We compare the accuracies of different algorithms by requiring different

number of nearest neighbors (NN) of each query genome, including 10-NN and 5-NN, using the

same approach. Since biological species databases are generally sparse due to the

undersampling of natural diversity and the existence of natural gaps in diversity among species,

a larger top k NN (e.g., 100) used in standard ANN benchmark experiments will offer little, if any

biological advantage, especially when the query genomes are relatively new, e.g., a new family

compared to database genomes. Therefore, we use top 5-NN and 10-NN. Further, if the genomic

distance (J_p) of query to some of the top 10 or top 5 neighbors found by GSearch at the nucleotide

level was larger than 0.9850 for bacterial genomes, these matches were filtered out and not used

in estimation of recall, because we have shown that above this threshold, k-mer based MinHash

methods at nucleotide level will lose accuracy and this is not related to HNSW search itself (e.g.,

8 out of 10 are kept, so only top 8 in R' is compared with top 8 in R). At proteome level, accuracy

was calculated following similar rules with the threshold value being 0.9720 (switching to the

universal gene graph at this level). For viral genomes, the threshold was 0.9800. Those thresholds

were chosen based on correlation with blast-based ANI or AAI. Detailed commands for running

each software mentioned above can be found in supplementary file 3.

Results

ProbMinHash as a robust metric of genome relatedness for prokaryotic genomes

Correlations between ProbMASH (we called it ProbMASH, after transformation from

ProbMinHash distance (J_p), see Materials and Methods for details) and ANI (determined by

FastANI) or Mash distance showed that ProbMinHash is robust and slightly better than Mash for

determining distances among bacterial genomes related at ~78% ANI, or above, i.e., genomes

assigned to the same or closely-related species (Spearman rho=0.9643 and 0.9640 for

ProbMinHash and Mash values against the corresponding ANI values for the same genome

comparisons, respectively, $P<0.001$, Figure S1a and S1b). For moderately related genomes, for

which ANI based on nucleotide k-mer is known to lose accuracy, ProbMASH (ProbMinHash)

based on amino acid k-mer was robust compared to Blast-based average amino acid identity or

AAI, especially among genomes showing between ~52% and 95% AAI (Spearman rho=0.90,

$P<0.01$, Supplementary Figure S2a and S2b). Below ~52% AAI, both ProbMinHash and Mash

distance lose accuracy compared to AAI. However, AAI of just universal genes provides a robust

measurement of genetic relatedness at this level of distantly related genomes, and we show here

that ProbMASH (from ProbMinHash distance) for this set of universal genes is also robust

(Spearman rho=0.9390, $P<0.001$, Supplementary Figure S3). Thus, for query genomes of

organisms with only distant relatives in the database (i.e., deep branching), for which their closest

matching genome in the database is related at the order level or higher, restricting the search to

the universal genes can provide robust classifications (11). Accordingly, GSearch implements a

three-step classification process, depending on the degree of novelty of the query genome against

the database genomes, using the AAI thresholds mentioned above (see also Fig. 2g). This

strategy and its accuracy are discussed further below. To show the accuracy of One Permutation

MinHash with Optimal Densification (Densifed MinHash), we calculated ANI by both Mash (classic

MinHash) and our implementation, we showed that they are almost identical (Figure S12).

Comparisons of sequence search algorithms and MinHash-like algorithms

We compared GSearch with other general-purpose sequence or genome search algorithms,

focusing on time complexity (big O annotation) of each sequence or genome search algorithm.

GSearch was, by far, the fastest genome search algorithm, with a O(log(N)) complexity (Table 1).

Other general-purpose sequence search algorithms (e.g. Sequence Bloom Tree, COBS et.al.)

are either sublinear under certain assumptions or not practical in real world applications. Also,

none of the general-purpose sequence or genome search algorithms were previously

benchmarked against an ANI-like distance; hence, their accuracy remains untested.

We then also compared available MinHash-like sketching algorithms in terms of their time

complexity (big Oh), space (memory), variance, and other important properties for large scale

applications such as mergeability (whether sketching part of dataset and then merge is equivalent

to sketching the entire dataset) to estimate Jaccard-like index (Table S1 and S2). SuperMinHash

and ProbMinHash are fast and mergeable MinHash algorithms, slower only than One Permutation

MinHash with Optimal Densification (as implemented in BinDash) (Table S1). The latter algorithm,

however, is not mergeable thus difficult to apply in a distributed computational environment.

HyperLogLog-like algorithms are significantly more space efficient albeit slightly slower. For

variance, we analyzed the rooted mean square (RMSE) error of all MinHash-like sketching

algorithms mentioned above. MinHash-like algorithms such as classic MinHash, ProbMinHash,

SuperMinHash had the smallest theoretical variance as m (the number of registers used for

sketching) increases (we use m=12,000, note that $J*(1-J)$ is much smaller than 1 for all Jaccard),

following by Densified MinHash, SetSketch (as b→1) (Table S2). Our implementation of the

Densified MinHash has almost close RMSE with classic MinHash (Figure S13). SetSketch is also

space efficient and is similar to that of HyperLogLog in terms of space and speed. HyperLogLog

sketch estimators such as those implemented in Dashing has largest variance for estimating the

cardinality of sets (followed by inclusion-exclusion rule to estimated Jaccard index,

Supplementary Note 1), consistent with experimental results when searching query genomes

against database (Supplementary Table S14 and S15), especially for small Jaccard distance (e.g.,

75% to 78% ANI, corresponding to 0.009 and 0.015 Jaccard index), where variance is more

important for accuracy.

Graph building and speed of search against reference prokaryotic genomes

To build the database graph for the entire GTDB v207 database at the nucleotide level (65,703

unique, non-redundant prokaryotic genomes at the 95% ANI species level), the tohnsw module

(database build subcommand of GSearch) took 1.3 h on a 24-thread computing node and scaled

moderately well with increasing number of threads (0.27 h using 128 threads) (Figure 2a).

Maximum memory (RAM) required for the building step was 15.3 GB. The total size of written

database files on disk was ~3.0 GB. There are 3 layers for the resulting graph, with 65180, 519,

and 4 genomes for layer 0,1 and 2 respectively. The searching of query genomes against the

GTDB database graph, requesting best 50 neighbors for 1000 query genomes, which represented

different previously known as well as novel species of eight bacterial phyla (see Methods for

details on query genome selection), took 2.3 min (database loading was 6 s) on a 24-thread

machine and scaled well with increasing number of threads (Figure 2d). The memory requirement

for the request (search) step was only 3.0 GB for loading the entire database file in memory.

We also built a database of all NCBI/RefSeq prokaryotic genomes (~318K, 2 Terabytes in total),

which took 4.1 hours using 24 threads with maximum memory usage of ~21GB (1.2 h with 128

threads) and dumped database file size of 15GB (30GB for amino acid). Searching of 8,466 query

genomes against this RefSeq database took 9.32 min (Table 2) and ~16GB of memory, which

was significantly better than alternative state-of-the-art tools for the same purposes such as

Dashing1/2 and BinDash (brute force HyperLogLog or MinHash), which took 28/42 min and 21

min, respectively (Table S3, Figure S5). To evaluate the performance against Dashing or

Sourmash more fully, we increased the number of database genomes gradually from 60K to 318K

(all RefSeq prokaryotic genomes, 2 Terabytes) while using the same number of query genomes

(8,466). We observed that GSearch follows a log fitting, consistent with the O(log(N)) theoretical

prediction, while Dashing 1/2 and Sourmash follow linear fitting, and thus the latter tools will be

increasingly slower than GSearch as the number of database genome increases (Figure 3a and

c). For example, GSearch was 3 to 4 times faster than Dashing 1/2 and skani when the number

of database genomes increased from 65,703 to 318,000 (Figure 3a, Table S3) and 20 to 30 times

faster with the 3 million reference virus genomes (Figure 3b, Table S4. see also below). The

speedup will be even larger as number of database genomes continues to grow. With Densifed

MinHash as option, GSearch can be 2-3 times faster than ProbMinHash (Table S3)

To build the amino-acid-level graph for moderately related query genomes, all GTDB v207

genomes were used for gene calling by FragGeneScanRs and subsequently, the predicted amino

acid sequences for each genome were used for building the database graph. The graph building

step took 1.4 h (Figure 2b) with a maximum memory required to be 37.7 GB on the 24-thread

node. The total size of the written database files on disk was 5.9 GB. However, when the

SetSketch option was used, graph building step took 2.3 h but only 9.4GB maximum memory

needed, with the database size being 0.5GB (Figure 3 (d)). There were 65158, 543 and 2

genomes for layer 0,1 and 2 respectively. The entire RefSeq genome database (~318K) took 3.7

hours to build at the proteome level with similar maximum memory, dumped files size was 29GB

(only 2.5GB with the SetSketch option). Requesting 50 neighbors for querying 1000 genomes at

the amino-acid level took 1.52 minutes with a memory requirement of ~6.0 GB (database loading

9 seconds; Figure 2e) for the GTDB database. Requesting 50 neighbors for 8,466 query genomes

against the NCBI/RefSeq proteome graph, took about 6.2 min (Table 2). In comparison, Mash

dist took 207.2 min against NCBI/RefSeq with 24 threads for the same task (no amino acid option

for Dashing).

Finally, for most distantly related query genomes, the graph building for the universal gene set

follows the same logic as the amino acid level graph mentioned above except for using a smaller

k-mer size (k=5) due to the smaller k-mer space of ~120 universal genes vs. the whole-genome

level. It took 7.76 min to build the database (Figure 2c) and 12 seconds to request 50 neighbors

for 1000 queries on a 24 threads node (Figure 2f) against the GTDB database graph. Building for

the entire NCBI/RefSeq database took about 27 min while requesting 1,000 against it took about

0.445 min (Table 2).

Searching accuracy and speed for prokaryotic genomes

The accuracy of GSearch and other tools in identifying the best matching genomes among the

database genomes was evaluated by comparing against the best matching genomes for the same

query genome(s) identified by traditional alignment-based methods, namely Blast-based ANI for

query genomes with close relatives in the databases and Blast-based AAI for query genomes

distantly related to their best match in the database. K-mer-based genomic distance (e.g. all tools

mentioned above) is widely known to be less accurate with higher degree of novelty of the query

genomes relative to the database genomes as also explained in Supplementary Note 2 and 4. To

address this limitation, GSearch employs a three-step framework, calculating genomic distance

at nucleotide, whole-genome amino acid (proteome) and universal gene amino acid levels for

query genomes of increasing novelty (or genetic distance) to database genomes as described

above (Fig. 2g). For query genomes from two datasets, the Tara Ocean (8,466), and the collection

put together by Ye and colleagues (997), that had closely related genomes in the RefSeq

database (showing >78% ANI, 6,992 and 906 query genomes, respectively), we observed an

average top 10 recall of 96.2% and 95.1%, respectively. Recall was estimated by comparing

(meaning % overlap) GSearch's top-10 matching genomes to top-10 found by Blastn-ANI (similar

results were obtained for top-5 matching genomes; Table 3). For query genomes with no closely

related genomes in the database showing higher than 78% ANI, 1474 and 91 genomes from the

two datasets, respectively, recall was significantly lower, only around 60% or below (Table 3).

However, when we search these genomes at the proteome level using Blastp-AAI as the

reference standard for calculating recall, the recall value was 96.9% and 95.2%, respectively

(Table 3). There were 327 and 25 genomes, respectively, that, even at proteome level, they had

no related genome in the RefSeq database showing higher than 52% AAI and these genomes

accounted for most of differences with the top-10 matching genomes by blast-AAI. These

genomes apparently reflect the fact that the public genome databases are still sparse and do not

cover well all biological diversity. When we searched these deep-branching (highly novel)

genomes at the universal gene proteome level, using the universal gene AAI as the reference

standard, we found the average top-10 recall value of 95.5% and 94.6%, respectively (Table 3).

We also compared these results obtained by GSearch to those of BinDash, Dashing 1/2 and

Sourmash for the same query genomes. We found that Sourmash is as accurate as GSearch but

much slower, while Dashing is less accurate than GSearch and Sourmash or BinDash, especially

when the closest database genomes showed less than 80% ANI to the query genomes

(moderately or distantly related) (Table S14 and S15). The results were similar independent of

the estimator used in Dashing (e.g., MLE or JMLE), consistent with theoretical predictions (Table

S2). BinDash was as accurate as Mash but much faster as previously described (Table S1 and

Table S13). We provide a theoretical derivation based on k-mer conservation and empirical

results for deriving the 78% ANI and 52% AAI thresholds to decide the switching between whole-

genome nucleotide vs. amino acid (proteome) search and whole-genome proteome vs. universal

gene only, respectively, in Supplementary Notes 2 and 4. Detailed accuracy results for all tools

based on a single query genome (not average recall across all query genomes as shown above)

can be found in Supplementary Table S13, S14 and S15.

We also evaluated the effect of genome completeness on the accuracy of GSearch given that

bacterial genomes recovered from environmental metagenomic surveys are frequently

incomplete. GSearch was robust to genome incompleteness down to 50% completeness level.

We found that at genome completeness higher than 50%, the accuracy/recall in the top 10 best

matches was higher than 80% and decreased considerably below this completeness level (Table

S12). Hence, GSearch analysis is not recommended for genome completeness less than 50%

due to the normalization step in ProbMinHash.

Graph database building and searching accuracy for viral and fungal genomes

Graph building and requesting for viral genomes is not effective at the nucleotide level because

many viral genera are genetically too distant from each other and do not have close relatives in

the public genomic database; that is, the database is too sparse. Accordingly, k-mer-based

methods for genomic distance will often lead to imperfect graph structure for viral genomes.

Therefore, we built only an amino acid level graph for viral genomes, using all genes in the

genome due to the lack of universal genes for viral genomes. Database building took 13.89 h for

all ~3 million IMG/VR4 genomes on a 24-thread node and graph file on disk was 15.8 GB (Figure

S6a). Requesting 1000 top neighbors scaled well with increasing number of threads and took

about 3.63 min (database loading took an additional 1.1 min) using 24 threads (Figure S6b). The

top-5 neighbors for 1000 query phage genomes were highly overlapping (98.32% recall; Table

S6) compared with the top-5 neighbors of the brute-force AAI approach. For such large databases

in terms of number of genomes, GSearch is about 20X faster than the brute-force Mash and

Dashing tools in finding the top-5 neighbors (Figure 3b, Tables S4). We also compared GSearch

with a new database building method, called PhageCloud, which relies on manually curated

genome labels (e.g., environmental source) for graph database building using the Neo4j software

and Dashing for genetic distance computation. Since PhageCloud provides only a web

implementation with one genome query at a time, we limited the search to one viral query genome

against the same database used by PhageCloud i.e., Gut Phage Database [38]. It took 37 seconds

to find the two best matches with PhageCloud while GSearch took 15 seconds (database loading

14 seconds, search 1.5 second) for the same search. Mash, on the other hand, took 4 minutes to

find the same two best matches. It should be noted, however, that, because the database is

already available (loaded) on PhageCloud's website, 37 seconds is only for the searching step

and website responses (average value for 5 runs on 5 different days) whereas GSearch took only

1.5 second for this same step.

Graph building for fungal genomes is slower compared to prokaryotic genomes, despite the

smaller number of available fungal genomes (n=9700), because the average fungal genome size

is much larger and k-mer and sketch size are accordingly much larger (k=21, s=48000). It took

2.3 h on a 24-thread node to build the nucleotide level graph for these fungal genomes. Searching

step was also slower due to the larger k-mer space. Accordingly, it took 3.13 min to request 50

neighbors for 50 query fungal genomes while Mash tool 4.4 min. Nonetheless, top 10 recall was

still very high (~99.4%) against Mash and MUMMER-based ANI for the same datasets. For the

amino acid level graph, the time for graph building was only 0.61 h, shorter than the corresponding

prokaryotic graph. Identifying 50 neighbors for 50 query fungal genomes at the amino-acid level

took 1.24 min (Mash took 2.59 min) with similarly high top 5 and top 10 recall (99.7% and 98.5%,

respectively) against brute-force Mash and Blastp-based AAI. Note that the difference in run time

will be much larger between Mash and GSearch as the number of fungal database genomes

increases in the future, as also exemplified above for the bacterial genomes.

Combining the three-step framework for prokaryotic genome classification and comparison with

standard tool GTDB-Tk

To evaluate the accuracy of classification/searching results based on the complete 3-step

framework of GSearch, we compared the best neighbors found by GSearch with brute-force ANI

(estimated by FastANI) and GTDB-Tk, a standard for microbial taxonomy classification these days

that is phylogenetic-tree- and alignment-based. As mentioned above, when the query genome

does not find a match in the database better than ANI > 78%, corresponding to ProbMinHash

distance 0.9850, the nucleotide-level graph is abandoned, and the amino-acid level is used

instead; similarly for no match better than 52% AAI, GSearch switches to the universal gene graph

(Figure 2g). The overall running time to classify 1000 prokaryotic genomes of varied levels of

taxonomic novelty compared to the database genomes on different computing platforms is

showed in Table S5. On a 24-thread Linux node with Intel Xeon Gold 6226 CPU, it took GSearch

a total of 5.85 minutes while it took 19.49 minutes on an intel Core i7 laptop (2017 release) CPU

personal laptop (6.02 minutes on the most recent ARM64 CPU laptop). Classifying 1000 genomes

using GTDB-Tk took 5.91 h on the same Linux node with 24 threads (memory requirement was

~328GB) while MASH took 53.7 min for 1000 genomes using 24 threads. We were not able to

assess Dashing or BinDash for this analysis because they do not provide proteome (amino acid)

level implementation.

In terms of classification accuracy, all query genomes that had a best match higher than 78% ANI

against the GTDB database genomes (i.e., a match at the same or closely related species, 699

out of the total 1000 queries) were identically classified by GSearch, GTDB-Tk and FastANI

(Supplementary file 1, only 100/699 are shown for simplicity), which means species-level

classifications are highly consistent. For the remaining 301 genomes that did not have same or

closely related species-level matches, for 266 of them (or 87.1%), GSearch also provided the

same classification with GTDB-Tk but several inconsistencies were observed for 39/301 genomes

(Figure 3e). Specifically, we noticed that for GTDB-Tk, which relies on RED values and tree

topology, several genomes (n=14) were still classified at the genus level even though the AAI

value against the best database genome in these case was below 60% (typically, genomes

assigned to the same genus show >65% AAI(46)), and some genomes (n=16) were still classified

at the family level but not at the genus level even though their best AAI value was above 65%.

Similarly, several genomes (n=9) were classified at the order level but not family level even though

their best AAI value was above 52%. Therefore, high consistency was overall observed between

GSearch and GTDB-Tk assignments, and the few differences noted were probably associated

with contaminated (low quality) MAGs or taxonomic inconsistencies, which was challenging to

assess further, and/or the peculiarities of each method. Since ProbMinHash distance correlated

well with blastp-based AAI after transformation in the range of AAI values between 52% and 95%,

the classification results were always consistent with AAI-based classification using previously

proposed thresholds. For example, best matches at AAI 65% ≥ AAI were classified in the same

genus by GSearch and blast-based AAI, and best matches of 52% < AAI < 65% were typically

classified in the same family (but different genus within the family).

Database split for large genome databases

For large databases (for example, >1 million bacterial genomes), the graph building and

requesting step could require a large amount of memory (due to the larger k-mer space) that is

typically not available in a single computer node. We therefore provide a database split solution

for such large databases. The average database building time on each node for each piece of the

database after the splitting step scales linearly with increasing nodes/processors (Figure S7a)

and requires much less memory (1/n total memory compared to when building in one node, where

n is the number database pieces after splitting; for GTDB v207 nucleotide graph building and n=5,

it will be only 28.3/5=5.66 GB). The searching time scales sub-linearly with increasing number of

nodes (Figure S7b) but offers the advantage of a reduced memory footprint with respect to the

single-node search. The top 10 best neighbor by splitting the database were exactly the same as

the non-splitting strategy (Supplementary file 2). Note that without multi-node support (e.g., run

database build sequentially), database build time is nearly the same with non-split strategy, but

memory requirement is only 1/n (GTDB v207, 28.3GB/5=5.66GB at nucleotide level and

27.7GB/5=5.54GB at amino acid level), even though total request time will be longer (time*n in

Figure S7(b)). However, since the request step is very fast, requiring only 1/n memory compared

to non-split strategy, overall runtime is still short with the database split approach even for a

relatively large number of genomes. The database split strategy is especially useful when memory

requirement is not satisfied on the host machine for larger genome database (e.g., millions of

genomes).

Discussion

A popular way to assess genetic relatedness among genomes is ANI, which corresponds

well to both 16S/18S rRNA gene identity and DNA-DNA hybridization values, the golden

standards of fungal and prokaryotic taxonomies (7). However, the number of available microbial

genomes has recently grown at an unprecedented speed. For example, there are 30% more

(new) species in NCBI/RefSeq 2022 compared to 2023, and the number of bacterial species

represented by genomes alone is expected to surpass 1 million soon. Therefore, the traditional

way that blast-based ANI or faster k-mer-based implementations (e.g., Skani, FastANI, Mash or

Dashing 1/2) are applied as an all vs. all search strategy (brute-force) does not scale because the

running time grows linearly with increasing number of query genomes and/or genomes in the

database. Phylogenetic approaches based on quick (approximate) maximum likelihood

algorithms and a handful of universal genes as implemented -for example- in GTDB-Tk could be

faster than brute-force approaches but are often not precise and require a large amount of

memory for the querying step (11) while the database building step could take several weeks of

run time because the underlying multiple sequence alignment of the database genomes is

computationally intensive. Further, approaches that reply on k-medoid clustering to avoid all vs.

all comparisons could be sometimes trapped into local minima because of arbitrary partitioning of

database genomes into clusters, a known limitation of these methods (13). GSearch effectively

circumvents these limitations by combining new k-mer hashing-based probabilistic data structures

for fast computation of genomic relatedness among genomes (i.e., ProbMinHash, SuperMinHash

and/or SetSketch) with a graph based nearest neighbor search algorithm (HNSW). Accordingly,

GSearch is at least an order of magnitude faster than alternative approaches (e.g., Mash,

Dashing, Sourmash, GTDB-Tk) for the same purposes and will be even faster as the number of

database genomes grows. Therefore, GSearch solves an important challenge associated with the

tasks to search and/or classify microbial genomes and will serve well these tasks for years to

come based on the current speed in the increase of the number of genomes that become

available.

To the best of our knowledge, no current tools have combined two sub-linear algorithms

and thus efficiently search very large genome databases while maintaining high accuracy in

calculating ANI/AAI among the genomes, and hence identifying the true best neighbors. Several

sub-linear algorithms such as Sequence Bloom Tree or COBS (cross-over between an inverted

index and Bloom filters) can do sequence to sequence (or genome to genome) search but do not

provide ANI/AAI values, which are key for microbial genome search and classification (Table 1).

Accordingly, these tools are generally less accurate than the ANI/AAI approach. GSearch can

handle several million of microbial genomes on a small-to-average computer cluster, or even

personal laptop (depending on the database size), since the created (dumped) database file size

is proportional to the total number of genomes in database for fixed sketch size and graph

parameters, and generally rather small. Specifically, with one million genomes, the dumped file

size will be 5.9GB*20=118 GB (currently, there are ~60K in the GTDB database, creating a

database file size of 5.9GB). With the SetSketch option, database file size will only be 0.5GB for

the GTDB database, 2.5G for the entire RefSeq genome databases (~318K genomes, 2

Terabytes), and 9.8GB for one million genomes. Further, due to the nature of the graph based

NNS algorithms, there is no need to build the entire database at once, but the database can be

split it into smaller pieces, as exemplified above and depending on the computational resources

available. For a modern laptop with 16 GB memory, a database on one million species can be

split into 10 pieces, so the dumped file for each piece will be only 11.8 GB, which can be loaded

into memory, and then collect the results from each piece within an approximate total running time

of 30 minutes (for querying 1000 genomes against 0.1 million database genomes for each of the

ten parts, which should take about 3 minutes). With this logic, a computing node with 24 threads

and 256 GB of memory available can easily deal with 20 million bacterial database genomes and

billions of bacterial genomes if using SetSketch. This represents a substantial improvement

compared to existing tools for the same purposes. This database split/partition idea of HNSW, or

other graph-based NNS libraries, has been successfully applied in several industrial-level

applications for other purposes (31,32). We also want to point out that the size of the compressed

sketches (database file) from SetSketch is comparable to other space efficient algorithms such

as HyperLogLog (with b=2, Setsketch asymptotically corresponds to HyperLogLog),

ExtendedHyperLogLog (47), HyperLogLogLog (48) and UltraLogLog (49) (25% more space

efficient than HyperLogLog). The Shannon entropy of SetSketch we implemented is

$\frac{m}{ln(2)ln(b)}\left(\left(1-\frac{1}{b}\right) + \int_0^1 z^{1/(b-1)} \frac{(1-z)ln(1-z)}{zln(z)} dz\right)$, where m is the number of registers, b is the key

parameter of SetSketch. For b=0.0005 that we used, the entropy is 13.24 per register (divided by

m). Therefore, compared to an uncompressed register size of 16 bits, there is still some room for

improvement for SetSketch. Theoretically, a 17.25% reduction in space can be achieved but

would add additional implementation complexity. For any HyperLogLog-like algorithms (e.g.,

SetSketch, UltraLogLog), a theoretical limit for sketch size is $O(\epsilon^{-2} + log(n))$, or slightly worse

but easy to implement (50,51), where n is the number of elements/k-mers while ϵ is error. This

means that we cannot improve further without losing accuracy as database size grows unless we

rely on database split strategy. SetSketch shares this property with HyperLogLog and thus we

cannot improve space further without theoretical breakthroughs.

Another distinguishing aspect of GSearch (tohnsw module) is the speed and flexibility in

building reference databases. Users could build reference databases (graphs) for any number

and type (e.g., prokaryotic vs. viral) of genomes. The high efficiency in building graphs allows

users to also test and optimize the key parameters of the graph, the M (maximum allowed

neighbors) and ef_construct (width of search for neighbor during building) parameters. For any

given database size, M and ef_construct determine the quality of the graph and graph build speed.

Small M and ef_construct may lead to frequent traps in local minima and thus, low recall while

large M and ef_construct may lead to slow speed without proportional improvement in recall

(Table S7). Therefore, there is a tradeoff between accuracy and speed that should be evaluated

first. However, for most users this task would not be necessary because they will work with pre-

built databases such as those provided here. Also, GSearch provides an option to add new

genomes to the database without the need to rebuild the database from scratch, making it

convenient and very fast to expand the current genome database as needed.

GSearch could also be applied to whole metagenome search and identification of the most

similar metagenomes in a series because the relatedness among metagenomes can be estimated

in a similar way to genomes using ProbMinHash as implemented -for example- in the HULK

software, which relies on the ProbMinHash algorithm in a streaming fashion (52). However, to

allow for sketching of much larger sequence files such as whole metagenomes simultaneously to

build the HNSW graph, weighted k-mer (e.g., ProbMinHash) approaches require much larger

memory than unweighted approaches due to the larger number of total k-mers (including

duplicates). Probabilistic or approximate counting of k-mer abundances such as Count-Min sketch

can be used instead for k-mer counting for metagenome search and/or when the computer

memory is limited (53,54) , or a combination of Count-Min Sketch with HyperLogLog sketch (55).

Similarly, we could seamlessly replace ProbMinHash with another relatedness algorithms should

such algorithms become available and has advantages in terms of speed and/or precision, or

more importantly, has the locality sensitive hashing property for nearest neighbor search. For

example, the SuperMinHash option is now provided for its high accuracy over traditional MinHash

but not faster (37), or other newer implementations such as the One Permutation MinHash with

Optimal Densification (OPMHOP) for estimating the unweighted Jaccard index, due to its speed

(only one hash function, average case $O(n+m)$) and locality sensitive hashing property (via

optimal densification or faster densification)(35,36) (Table S1 and S2). Note that the Bottom-K

sketch implementation in Mash or FracMinHash in Sourmash use just one single hash function

or a much smaller number of hash functions required by that of classic MinHash and thus lose

the locality sensitive hashing property and thus we cannot use it for nearest neighbor search

purposes (36). Further, BagMinHash (56) or DartMinHash (57) for weighted (but not normalized)

Jaccard index can also be used in place of ProbMinHash (also LSH). Since the number of

genomic distance computations is $O(\log(N))$ in GSearch, the computational time for estimating

genomic distance for a pair of genomes is not a major factor in overall computational speed

because $\log(N)$ is always a small number. Accuracy in the genomic distance estimate is relatively

more important in GSearch and the main reason that ProbMinHash is the default option. Related

to this, ANI as currently implemented -for instance- in FastANI is not appropriate for this function

because it is not metric; that is, for the FastANI distances calculated among three genomes A, B,

and C, (A,B) + (B, C) is not necessary larger than (A,C) and ANI(A,B) is not equal to ANI (B, A)

[15]. Similarly, mutation rates (or ANI) estimated by FracMinHash, CMash and related tools (e.g.

Sourmash or skani calculated ANI) are also not metric (58-60). To solve this "metric" problem, a

norm adjusted proximity graph (NAPG) was proposed based on inner product and it shows

improvements in terms of both speed and recall using non-metric distances (61). This could be

another direction for further improving the speed and recall of GSearch. The three options we

provided as part of GSearch to estimate Jaccard-like index are all metric, which ensures neighbor

diversity when building the graph, and they are equally applicable to any microbial genome,

including viral and fungal genomes.

K-mer-based methods for genetic relatedness estimation such as ProbMinHash have

lower accuracy between moderately-to-distantly related genomes compare to alignment-based

tools (see Supplementary Note 2 and 4 for further discussion). Our empirical evaluation showed

that this relatedness level, for nucleotide searches, is around 78% ANI and 52% AAI for the amino-

acid searches (e.g., ProbMinHash distances do not correlate well with blast-based ANI and AAI

at and below these levels). To circumvent this limitation, we designed a 3-step framework as part

of GSearch to classify bacterial genomes that show different levels of novelty compared to the

database genomes, with high accuracy. This framework included a search at the universal gene

level for deep-branching genomes that are novel at the phylum level (AAI < 52%), for which

searching at the entire proteome level is less accurate. Recently, methods that employ k-mers

that allow mismatches, that is, spaced k-mers have shown promise in accurately estimating

genomic relatedness even among distantly related genomes with gains in speed (62). To apply

spaced k-mers to entire genomes, the recently developed "tensor sketch" approaches could be

explored in the future to simplify the distance computation for distantly related bacterial and viral

genomes (63) instead of relying on the mentioned 3-step framework. In the meanwhile, the

ProbMinHash approach, essentially a Jaccard-like distance estimation via weighted and

normalized MinHash for k-mers, is highly efficiently, and, importantly, can effectively deal with

incomplete genomes or genomes of (drastically) different length, a known limitation of traditional

Mash-based methods (22). Comparing genomes of different length is not uncommon, e.g.,

bacterial genome sizes can differ by more than ten-fold, as can be the case between MAGs of

different level of completeness or when searching a short sequence (e.g., a bacteriophage

genome) against a large genome collection (e.g., the whole viral genome database). Our own

analysis showed that ProbMinHash is robust down to 50% completeness level (Table S12), which

is also the most commonly used standard for selecting MAGs of sufficient/high quality for further

analysis and reporting (64). ProbMinHash is also robust for genomes with repeats or gene

duplications (e.g., fungal genomes) due to the k-mer weighting step by weighted MinHash, a

property not shared by simple MinHash.

In general, the genome relatedness estimated, or best database matching genomes

identified, by GSearch were highly consistent with blast-based ANI/AAI results or phylogenetic

placement of the genomes using GTDB-Tk, particularly for query genomes with close relatives in

the database related at the species or genus levels (Supplementary file 1, Figure 3e). For more

distantly related query genomes relative to database genomes, classification results of GSearch

showed some differences with GTDB-Tk. These differences were not always possible to assess

further for the most correct genome placement but could be due, at least partly, to the

incompleteness and/or contamination of query or/and database genomes, which renders the

resulting concatenated alignment of universal genes used by GTDB-Tk unreliable (64,65), as only

a few amino-acid positions per gene are used in the final alignment. In contrast, the AAI and

ProbMinHash approaches should be more robust to changes of a small number of genes because

the entire proteome is considered.

Graph-based NNS methods achieve good performance compared to tree based and

locality-sensitive hashing (LSH) methods or space partitioning methods (33). Building a HNSW

graph relies on proximity of the database elements; thus, if the distances among database

elements, in our case genomes, cannot be effectively estimated, the navigation of graph becomes

less efficient (e.g., gets trapped/lost in local minima). This is especially problematic for highly

sparse/distantly related and diverse datasets, like the viral genome database, in which two phage

genomes could often share very little genomic information (k-mers), and thus the edges to choose

from during graph navigation are not accurate estimations of the relatedness of the corresponding

genomes. This is confirmed by our own results when using nucleotide-level search to build the

viral genome graph. Hence, the amino acid level will be much more robust for viral genomes and

is the recommended level to use. Finally, recent advancements in proximity graph building could

further reduce database building time from $O(N*log(N))$ to $O(N*c)$ (where c is a constant

independent of N, number of genomes) and/or achieve better search performance than existing

approximate proximity graph (APG) alone by combining locality sensitive hashing (LSH) with

approximate proximity graph (66) (or APG, e.g. HNSW is a APG) to have LSH-APG. This

approach essentially reduces the number of points/genomes to be compared during graph

building and will be explored in future versions of GSearch to provide additional speed-up and/or

robustness for graph database building. The HNSW graph, and graph-based K-NNS in general,

can also be further improved by adding shortcut edges and maintaining a dynamic list of

candidates compared to a fixed list of candidates used by default (67). Graph reordering, a cache

optimization that works by placing neighboring nodes in consecutive (or near-consecutive)

memory locations, can also be applied to improve the speed of HNSW (68). We also want to

mention that in our HNSW Rust implementation, a memory map was also implemented, which

will solve the memory limit problem when building large graph with billions of data points or

genome. Another direction to further improve GSearch could be the use of Graphics Processing

Unit (GPU) instead of CPU because GPUs are more efficient in handling matrix computations and

machine learning tasks (69). We will explore these options in future versions of GSearch.

Finally, GSearch provides a general framework/idea to create a new data structure:

combining probabilistic data structures (e.g., MinHash, HyperLogLog) with graph-based nearest

neighbor search algorithm that should be applicable not only to genomes but also text or

document searching purposes more broadly. For example, the MinHash algorithm can be applied

to document (e.g., website, text) similarity estimation, and be combined with HNSW. Further, we

can hash strings to approximate edit distance (a metric distance) to avoid expensive dynamic

programming (70) via order MinHash (71). We reimplemented order MinHash in our ProbMinHash

library, and it can be easily applied to do fast DNA string (not fragmented genomes) or general

string search.

To summarize, GSearch, based on MinHash-like algorithms and HNSW, solves a major

current challenge in search and classification of microbial genomes due to its efficiency and

scalability. Both the Densified MinHash and HNSW are approximating the theoretical optimal

limits of similar algorithms in terms of speed and accuracy. GSearch will serve the entire microbial

sciences for years to come since it can be equally applied to fungal, bacterial, and viral genomes,

and thus offer a common framework to identify, classify and study all microbial genomes, at the

million-to-billion database genome level.

Data and Code availability

All the mentioned pre-built database for bacteria, fungi and phage genomes can be found at:

http://enve-omics.ce.gatech.edu/data/gsearch.   Code   can   be   found   here:

https://github.com/jean-pierreBoth/gsearch   or   here:

https://gitlab.com/Jianshu_Zhao/gsearch. Scripts for reproducing the major results can be

found here: https://github.com/jianshu93/gsearch_analysis.

Author Contribution

J.Z, and K.K designed the work, J.Z and J.P-B wrote the code (Genome part and algorithm part

respectively), J.P-B implemented the Rust libraries of Kmerutils, Probminhash and Hnswlib-rs.

L.M.R provided constructive suggestions. J.Z did the analysis and benchmark. J.Z and K.K wrote

the manuscript.

Acknowledgment

This work was supported, in part, by the US National Science Foundation (Award No 1759831

and 2129823 to KTK). We want to thank PACE (Partnership for Advanced Computing

Environment) at Georgia Tech for providing computing resources. We want to thank Kenji

Gerhardt for helpful discussions on benchmarking against traditional ANI/AAI based tools and

Chirag Jain for discussions on MinHash and bottom-k sketch implementation. We also want to

thank Otmar Ertl for discussion on SetSketch Shannon entropy and implementation of

SuperMinHash/ProbMinHash, Xiaofei Zhao for discussions on mergeability of One Permutation

MinHash with Optimal densification, and Dingyu Wang for discussion on τ-GRA relative variance

with respect to HyperLogLog. Finally, we would like to thank two anonymous reviewers for their

suggestions, which help improve the manuscript substantially.

References

870
1.   Locey, K.J. and Lennon, J.T. (2016) Scaling laws predict global microbial diversity. *Proceedings
of the National Academy of Sciences*, **113**, 5970-5975.
2.   Chevallereau, A., Pons, B.J., van Houte, S. and Westra, E.R. (2022) Interactions between
bacterial and phage communities in natural environments. *Nature Reviews Microbiology*, **20**, 49-
62.
3.   Parks, D.H., Chuvochina, M., Rinke, C., Mussig, A.J., Chaumeil, P.-A. and Hugenholtz, P. (2021)
GTDB: an ongoing census of bacterial and archaeal diversity through a phylogenetically
consistent, rank normalized and complete genome-based taxonomy. *Nucleic Acids Research*.
4.   Camargo, A.P., Nayfach, S., Chen, I.-M.A., Palaniappan, K., Ratner, A., Chu, K., Ritter,
Stephan J., Reddy, T.B.K., Mukherjee, S., Schulz, F. *et al.* (2022) IMG/VR v4: an expanded
database of uncultivated virus genomes within a framework of extensive functional, taxonomic,
and ecological metadata. *Nucleic Acids Research*, **51**, D733-D743.
5.   Almeida, A., Nayfach, S., Boland, M., Strozzi, F., Beracochea, M., Shi, Z.J., Pollard, K.S.,
Sakharova, E., Parks, D.H., Hugenholtz, P. *et al.* (2021) A unified catalog of 204,938 reference
genomes from the human gut microbiome. *Nature Biotechnology*, **39**, 105-114.
6.   Nayfach, S., Roux, S., Seshadri, R., Udwary, D., Varghese, N., Schulz, F., Wu, D., Paez-Espino,
D., Chen, I.M., Huntemann, M. *et al.* (2021) A genomic catalog of Earth's microbiomes. *Nature
Biotechnology*, **39**, 499-509.

7.   Konstantinidis, K.T. and Tiedje, J.M. (2005) Genomic insights that advance the species definition
for prokaryotes. *Proceedings of the National Academy of Sciences*, **102**, 2567-2572.
8.   Konstantinidis, K.T. and Tiedje, J.M. (2005) Towards a Genome-Based Taxonomy for
Prokaryotes. *Journal of Bacteriology*, **187**, 6258-6264.
9.   Goris, J., Konstantinidis, K.T., Klappenbach, J.A., Coenye, T., Vandamme, P. and Tiedje, J.M.
(2007) DNA–DNA hybridization values and their relationship to whole-genome sequence
similarities. *International Journal of Systematic and Evolutionary Microbiology*, **57**, 81-91.
10.   Lee, I., Ouk Kim, Y., Park, S.-C. and Chun, J. (2016) OrthoANI: An improved algorithm and
software for calculating average nucleotide identity. *International Journal of Systematic and
Evolutionary Microbiology*, **66**, 1100-1103.
11.   Chaumeil, P.-A., Mussig, A.J., Hugenholtz, P. and Parks, D.H. (2019) GTDB-Tk: a toolkit to
classify genomes with the Genome Taxonomy Database. *Bioinformatics*, **36**, 1925-1927.
12.   Chaumeil, P.-A., Mussig, A.J., Hugenholtz, P. and Parks, D.H. (2022) GTDB-Tk v2: memory
friendly classification with the Genome Taxonomy Database. *bioRxiv*, 2022.2007.2011.499641.
13.   Rodriguez-R, L.M., Gunturu, S., Harvey, W.T., Rosselló-Mora, R., Tiedje, J.M., Cole, J.R. and
Konstantinidis, K.T. (2018) The Microbial Genomes Atlas (MiGA) webserver: taxonomic and gene
diversity analysis of Archaea and Bacteria at the whole genome level. *Nucleic Acids Research*,
46, W282-W288.
14.   Ondov, B.D., Treangen, T.J., Melsted, P., Mallonee, A.B., Bergman, N.H., Koren, S. and
Phillippy, A.M. (2016) Mash: fast genome and metagenome distance estimation using MinHash.
Genome Biology, **17**, 132.
15.   Jain, C., Rodriguez-R, L.M., Phillippy, A.M., Konstantinidis, K.T. and Aluru, S. (2018) High
throughput ANI analysis of 90K prokaryotic genomes reveals clear species boundaries. *Nature
Communications*, **9**, 5114.
16.   Baker, D.N. and Langmead, B. (2019) Dashing: fast and accurate genomic distances with
HyperLogLog. *Genome Biology*, **20**, 265.
17.   Baker, D.N. and Langmead, B. (2022) Dashing 2: genomic sketching with multiplicities and
locality-sensitive hashing. *bioRxiv*.
18.   Zhao, X. (2018) BinDash, software for fast genome distance estimation on a typical personal
laptop. *Bioinformatics*, **35**, 671-673.
19.   Broder, A.Z. (1997), *Proceedings. Compression and Complexity of SEQUENCES 1997 (Cat. No.
97TB100171)*. IEEE, pp. 21-29.
20.   Flajolet, P., Fusy, É., Gandouet, O. and Meunier, F. (2007) Hyperloglog: the analysis of a near-
optimal cardinality estimation algorithm. *Discrete Mathematics and Theoretical Computer
Science*, 137-156.
21.   Ertl, O. (2021) SetSketch: filling the gap between MinHash and HyperLogLog. *Proc. VLDB
Endow.*, **14**, 2244–2257.
22.   Koslicki, D. and Zabeti, H. (2019) Improving MinHash via the containment index with applications
to metagenomic analysis. *Applied Mathematics and Computation*, **354**, 206-215.
23.   Ioffe, S. (2010) Improved Consistent Sampling, Weighted Minhash and L1 Sketching. *2010 IEEE
International Conference on Data Mining*, 246-255.
24.   Ertl, O. (2020) ProbMinHash – A Class of Locality-Sensitive Hash Algorithms for the (Probability)
Jaccard Similarity. *IEEE Transactions on Knowledge and Data Engineering*, 1-1.
25.   Wang, Q., Garrity, G.M., Tiedje, J.M. and Cole, J.R. (2007) Naïve Bayesian Classifier for Rapid
Assignment of rRNA Sequences into the New Bacterial Taxonomy. *Applied and Environmental
Microbiology*, **73**, 5261-5267.
26.   Gionis, A., Indyk, P. and Motwani, R. (1999) Similarity search in high dimensions via hashing.
Vldb, **99**, 518-529.
27.   Ram, P. and Sinha, K. (2019) Revisiting kd-tree for nearest neighbor search. *Proceedings of the
25th acm sigkdd international conference on knowledge discovery & data mining*, 1378-1388.
28.   Dasgupta, S. and Sinha, K. (2013) Randomized partition trees for exact nearest neighbor search.
Proceedings of the 26th Annual Conference on Learning Theory, **30**, 317--337.

29. Dong, W., Moses, C. and Li, K. (2011) Efficient k-nearest neighbor graph construction for generic
similarity measures. *Proceedings of the 20th international conference on World wide web*, 577-
586.
30. Malkov, Y., Ponomarenko, A., Logvinov, A. and Krylov, V. (2014) Approximate nearest neighbor
algorithm based on navigable small world graphs. *Information Systems*, **45**, 61-68.
31. Malkov, Y.A. and Yashunin, D.A. (2020) Efficient and Robust Approximate Nearest Neighbor
Search Using Hierarchical Navigable Small World Graphs. *IEEE Transactions on Pattern*
Analysis and Machine Intelligence, **42**, 824-836.
32. Fu, C., Xiang, C., Wang, C. and Cai, D. (2017) Fast approximate nearest neighbor search with
the navigating spreading-out graph. *arXiv preprint arXiv:1707.00143*.
33. Aumüller, M., Bernhardsson, E. and Faithfull, A. (2020) ANN-Benchmarks: A benchmarking tool
for approximate nearest neighbor algorithms. *Information Systems*, **87**, 101374.
34. Wang, M., Xu, X., Yue, Q. and Wang, Y. (2021) A comprehensive survey and experimental
comparison of graph-based approximate nearest neighbor search. *Proc. VLDB Endow.*, **14**,
1964–1978.
35. Shrivastava, A. (2017) Optimal densification for fast and accurate minwise hashing. *International*
Conference on Machine Learning, 3154-3163.
36. Mai, T., Rao, A., Kapilevich, M., Rossi, R., Abbasi-Yadkori, Y. and Sinha, R. (2020), *Uncertainty*
in Artificial Intelligence. PMLR, pp. 831-840.
37. Ertl, O. (2017) Superminhash-A new minwise hashing algorithm for jaccard similarity estimation.
arXiv preprint arXiv:1706.05698.
38. Déraspe, M., Boisvert, S., Laviolette, F., Roy, P.H. and Corbeil, J. (2020) Fast protein database
as a service with kAAmer. *bioRxiv*, 2020.2004.2001.019984.
39. Van der Jeugt, F., Dawyndt, P. and Mesuere, B. (2022) FragGeneScanRs: faster gene prediction
for short reads. *BMC Bioinformatics*, **23**, 198.
40. Finn, R.D., Clements, J. and Eddy, S.R. (2011) HMMER web server: interactive sequence
similarity searching. *Nucleic Acids Research*, **39**, W29-W37.
41. Grigoriev, I.V., Nikitin, R., Haridas, S., Kuo, A., Ohm, R., Otillar, R., Riley, R., Salamov, A., Zhao,
X. and Korzeniewski, F. (2014) MycoCosm portal: gearing up for 1000 fungal genomes. *Nucleic*
acids research, **42**, D699-D704.
42. Ter-Hovhannisyan, V., Lomsadze, A., Chernoff, Y.O. and Borodovsky, M. (2008) Gene prediction
in novel fungal genomes using an ab initio algorithm with unsupervised training. *Genome*
research, **18**, 1979-1990.
43. Ye, L., Mei, R., Liu, W.-T., Ren, H. and Zhang, X.-X. (2020) Machine learning-aided analyses of
thousands of draft genomes reveal specific features of activated sludge processes. *Microbiome*,
8, 1-13.
44. Nishimura, Y. and Yoshizawa, S. (2022) The OceanDNA MAG catalog contains over 50,000
prokaryotic genomes originated from various marine environments. *Scientific Data*, **9**, 305.
45. Fu, C. and Cai, D. (2016) EFANNA: An Extremely Fast Approximate Nearest Neighbor Search
Algorithm Based on kNN Graph. arXiv 2016. *arXiv preprint arXiv:1609.07228*.
46. Konstantinidis, K.T., Rosselló-Móra, R. and Amann, R. (2017) Uncultivated microbes in need of
their own taxonomy. *The ISME Journal*, **11**, 2399-2406.
47. Ohayon, T. (2021) ExtendedHyperLogLog: Analysis of a new Cardinality Estimator. *arXiv preprint*
arXiv:2106.06525.
48. Karppa, M. and Pagh, R. (2022) HyperLogLogLog: Cardinality Estimation With One Log More.
arXiv preprint arXiv:2205.11327.
49. Ertl, O. (2023) UltraLogLog: A Practical and More Space-Efficient Alternative to HyperLogLog for
Approximate Distinct Counting. *arXiv preprint arXiv:2308.16862*.
50. Błasiok, J. (2019) Optimal streaming and tracking distinct elements with high probability. *ACM*
Transactions on Algorithms (TALG), **16**, 1-28.
51. Kane, D.M., Nelson, J. and Woodruff, D.P. (2010), *Proceedings of the twenty-ninth ACM*
SIGMOD-SIGACT-SIGART symposium on Principles of database systems, pp. 41-52.

52.   Rowe, W.P.M., Carrieri, A.P., Alcon-Giner, C., Caim, S., Shaw, A., Sim, K., Kroll, J.S., Hall, L.J.,
Pyzer-Knapp, E.O. and Winn, M.D. (2019) Streaming histogram sketching for rapid microbiome
analytics. *Microbiome*, **7**, 40.
53.   Cormode, G. and Muthukrishnan, S. (2005) An improved data stream summary: the count-min
sketch and its applications. *Journal of Algorithms*, **55**, 58-75.
54.   Ting, D. (2018) Count-Min: Optimal Estimation and Tight Error Bounds using Empirical Error
Distributions. *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge
Discovery & Data Mining*, 2319–2328.
55.   Ting, D. (2019) Approximate Distinct Counts for Billions of Datasets. *Proceedings of the 2019
International Conference on Management of Data*, 69–86.
56.   Ertl, O. (2018) BagMinHash - Minwise Hashing Algorithm for Weighted Sets. *Proceedings of the
24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, 1368–
1377.
57.   Christiani, T. (2020) DartMinHash: Fast Sketching for Weighted Sets. *arXiv preprint
arXiv:2005.11547*.
58.   Hera, M.R., Pierce-Ward, N.T. and Koslicki, D. (2022) Debiasing FracMinHash and deriving
confidence intervals for mutation rates across a wide range of evolutionary distances. *bioRxiv*,
2022.2001.2011.475870.
59.   Liu, S. and Koslicki, D. (2022) CMash: fast, multi-resolution estimation of k-mer-based Jaccard
and containment indices. *Bioinformatics*, **38**, i28-i35.
60.   Shaw, J. and Yu, Y.W. (2023) Fast and robust metagenomic sequence comparison through
sparse chaining with skani. *bioRxiv*, 2023.2001. 2018.524587.
61.   Tan, S., Xu, Z., Zhao, W., Fei, H., Zhou, Z. and Li, P. (2021), *Proceedings of the 27th ACM
SIGKDD Conference on Knowledge Discovery & Data Mining*. Association for Computing
Machinery, Virtual Event, Singapore, pp. 1552–1560.
62.   Břinda, K., Sykulski, M. and Kucherov, G. (2015) Spaced seeds improve k-mer-based
metagenomic classification. *Bioinformatics*, **31**, 3584-3592.
63.   Joudaki, A., Rätsch, G. and Kahles, A. (2021) Fast Alignment-Free Similarity Estimation By
Tensor Sketching. *bioRxiv*.
64.   Parks, D.H., Imelfort, M., Skennerton, C.T., Hugenholtz, P. and Tyson, G.W. (2015) CheckM:
assessing the quality of microbial genomes recovered from isolates, single cells, and
metagenomes. *Genome research*, **25**, 1043-1055.
65.   Bowers, R.M., Kyrpides, N.C., Stepanauskas, R., Harmon-Smith, M., Doud, D., Reddy, T.B.K.,
Schulz, F., Jarett, J., Rivers, A.R., Eloe-Fadrosh, E.A. *et al.* (2017) Minimum information about a
single amplified genome (MISAG) and a metagenome-assembled genome (MIMAG) of bacteria
and archaea. *Nature Biotechnology*, **35**, 725-731.
66.   Zhao, X., Tian, Y., Huang, K., Zheng, B. and Zhou, X. (2023) Towards Efficient Index
Construction and Approximate Nearest Neighbor Search in High-Dimensional Spaces. *VLDB
Endowment*.
67.   Prokhorenkova, L. and Shekhovtsov, A. (2020) Graph-based Nearest Neighbor Search: From
Practice to Theory. *Proceedings of the 37th International Conference on Machine Learning*, **119**,
7803--7813.
68.   Coleman, B., Segarra, S., Shrivastava, A. and Smola, A. (2021) Graph Reordering for Cache-
Efficient Near Neighbor Search. *arXiv preprint arXiv:2104.03221*.
69.   Groh, F., Ruppert, L., Wieschollek, P. and Lensch, H. (2022) GGNN: Graph-based GPU Nearest
Neighbor Search. *IEEE Transactions on Big Data*, 1-1.
70.   Šošić, M. and Šikić, M. (2017) Edlib: a C/C++ library for fast, exact sequence alignment using edit
distance. *Bioinformatics*, **33**, 1394-1395.
71.   Marçais, G., DeBlasio, D., Pandey, P. and Kingsford, C. (2019) Locality-sensitive hashing for the
edit distance. *Bioinformatics*, **35**, i127-i135.
1043

1083 **Figures**
1084

Figure 1. **Schematic overview of GSearch building graph (a), graph searching (c)**
and (Super/Prob/Dens)MinHash/SetSketch distance estimated (b). **(a)** Overview of
the HNSW building process. GSearch (tohnsw module) starts from a randomly chosen
genome to gradually build the graph at Layer 0 (1) and gradually collapse genomes(dash

grey line indicate newly clustered/collapsed representatives compare to previous step)

into Layer 1 (2) and layer 2 (3) as more genomes are being incorporated in Layer 0 until

all genomes in database are inserted into layer 0 (4). When inserting new genomes in the

graph (database), GSearch essentially searches in a partially built graph to find nearest

genomes, based on ProbMinHash/SetSketch distance values among the genomes; see

(c) for details. After the required number of nearest neighbors are found for each inserted

genome, a reverse update step is performed to update neighbor list of all nodes in the

graph. **(b)** Overview of (Super/Prob)MinHash/SetSketch algorithms to calculate J_p and J,

where h is the hash function to hash k-mers from two genomes (orange and blue) and

store the hashed values as sketches (shapes in the two big circles). ProbMinHash

calculates J_p from shared sketches while SuperMinHash, Densfified MinHash and

SetSketch calculate J from shared sketches. **(c)** To search/identify a new genome P

(orange) against the graph (request module), starting from an entry node (black, random

or inherited from layer above it, depending on whether it is the top layer or not), GSearch

finds the closest connected neighbor of the entry node (black) to the new node P to be

searched (orange) by calculating the (Super/Prob/Dens)MinHash/SetSketch distance of

the new node P (orange) with all neighbors (blue) of entry node (black) and assigns the

closes one (X5 in this case) as the new entry point (that is X5 will be the new entry node)

(panel **(d)**). GSearch is then traverses in a greedy manner (i.e., update the entry point

using the newly found closest connected neighbor of X5) until the nearest neighbors in

the layer are found (specifically, the path goes from entry node to X5, X8 and X13) (panel

(e)), and then goes to next layer. This process is repeated until the required number of

nearest neighbors (N) are all found for the given new querying data point P and

subsequently, reported to the user.

1114

1115

1116

1117

1118

1119

Figure 2. **Performance and scalability of database building (tohnsw) and searching (request) steps as the number of threads increases**. Upper panel shows total wall time (y axes) for building the GTDB v207 (65,703 genomes) at the nucleotide level **(a)**, whole-genome proteome (amino acid level) **(b)** and universal gene set proteome **(c)** reference graphs (or databases). Middle panel shows searching performance and scalability against number of threads used for different sets of query genomes at nucleotide **(d)**, amino acid level **(e)** and universal protein level **(f)**. Specifically, 100, 300 and 1000 query genomes (figure key) were used. All tests were run on a 24-thread Intel (R) Xeon (R) Gold 6226 processor, with 40GB memory available. **(g)** Overview of GSearch's the 3-step pipeline for classifying prokaryotic genomes. Orange boxes denote steps that aim to prepare

genome files, in different formats, for graph building while green boxes denote building

steps of the graph database (in nucleotide or amino acid format). Blue boxes indicate

input/query genomes to search against the database while grey boxes indicate

classification output for each input. Two key steps of GSearch: tohnsw and request are

used to build graph database and request (or search) new genomes against the database,

respectively. Two thresholds are used in the pipeline to decide between whole nucleotide

vs. whole-genome amino acid search and whole-genome amino acid vs. universal gene

amino acid; that is, 78% ANI and 52% AAI, corresponding to Probminhash distance

0.9850 and 0.9375, respectively (see main text for details).

1139

1140

1141

1142

1143

Figure 3. **Running time, memory consumption and classification accuracy of**
GSearch against Dashing, Sourmash and Blast-based ANI/AAI tools. (a) Running
time of GSearch versus Dashing for searching 8,466 query genomes against the RefSeq
prokaryotic genome database as a function of the number of genomes used in the
database (x-axis) at the nucleotide level. **(b)** Running time of GSearch (blue) versus
Dashing (orange) for 10,000 query viral genomes against the IMG/VR v4 database at
amino acid level. **(c)** Same as in (a) above but comparison is against Sourmash (orange).
(d) Memory consumption of GSearch during versus Dashing and Sourmash search.
Search is to load database into memory, thus maximum memory is directly related to

database size. Since Sourmash search is not parallelized, GNU parallel was used for

process-level parallelism. **(e)** Comparison of GSearch classification results with GTDB-

Tk and Blastp-based AAI tools for moderate-to-distantly related query genomes based on

the bacterial proteome database (e.g., ANI between the query genome and its best match

in the database was lower than 78% for these genomes). Each point represents a

comparison between two genomes, query and the best match found by GSearch,

showing RED values generated by GTDB-tk (y-axis) versus Blastp-based AAI between

these two genomes. The taxonomic rank that the query and the best database match

share is shown (see figure key). Two vertical lines indicate Blastp-based AAI threshold

for family and genus level classification threshold. Note that the best match was always

the same genome between GSearch and all vs. all Blastp AAI, and the overall consistency

between GSearch/AAI and GTDB-tk in identifying the same best database genomes for

the same query genomes. Note that y-axis values are in log scale in panels b, c, and d.

Table 1. Bioinformatics algorithms for sequence/genome searching and their comparisons. S represents a document/genome. N is the total number of documents/genomes. $U_{s \in S}$ |s| represents the total number of terms in N documents/genomes and $\sum_{s \in S}$ |s| is total unique terms/k-mer. MPH is minimal Perfect Hashing. For the Inverted Index size, the extra log (N) comes from the bit precision document IDs. For SBTs, log(N) is the height of the tree, and for Bloom Filters at each level is $O(\sum_{s \in S}$ |s|) in total. MinHash time and space complexity was based on k hash functions for N sets, each set has d' non-zero element. Note that the most recent B-bit MinHash with optimal densification can further improve to O(N*(d'+k)). O(vdlog(N)) for GSearch is O(log(N)) in practice since v and d is small and single pair genome comparison is a constant (Supplementary Note 3). τ depends on the user-specified parameter and is generally less than 0.01 in practice.

	Query Time	Space	Recall Benchmark (Biologically)	Comments
Inverted Index[1]	$O(1)$	$Best: log(N) \bigcup_{s \in S} |s|$	Only for document search/retrieval, could be applied to genomic/sequence search	**Long construction time; impractical for bigger datasets; best case needs MPH and a known k-mer (term) distribution**
BIGSCI/COBS[2,3]	$O(N)$	$\sum_{s \in S} |s|$	A hybrid between an inverted index and Bloom filters (COBS), high false positive rate, no benchmark with mutation rate by ANI/Mash	Query time is linear in N, small index size
Sequence Bloom Tree[4]	$Best: O(log(N)),$ $Worse: O(N)$	$log(N) \sum_{s \in S} |s|$	Given the k-mers from a query sequence, the task is to determine which of the N documents contain all the k-mers present in the query; no benchmark with mutation rate by ANI/Mash	**Sequential query process is bottleneck; designed for sequential implementation**
RAMBO[5]	$O(\sqrt{N} * log(N))$	$\Gamma log(N) \sum_{s \in S} |s|$	Similar to SBT, finding which of the N documents/genomes contain all the k-mers present in the query, no benchmark with ANI/Mash	Only for $\Gamma < 1$, query time is sub-linear
MinHash[6]	$O(N * d' * k)$	$O(N * k)$	Average Nucleotide Identity (ANI) or mutation rate via Mash distance	Query time is linear in N
GSearch (ProbMinHash+HNSW)	$O(vdlog(N))$	$O((1 + \tau) * N * d + k * N)$	Average Nucleotide Identity (ANI) via Mash-like mutation rate/index	Long database construction time $O(N * log(N))$, but users are free from construction.
FLINNG[7]	$O(log^2 \left(\frac{1}{\delta}\right) log^3(N) N^{\frac{1}{2}+\gamma})$	$N^{\frac{3}{2}} log^2(N)$	No Benchmark with Average Nucleotide Identity (ANI) via Mash-like mutation rate/index, only 15% of RefSeq genome meet the γ-stable criteria	The γ-stable query condition is a relatively strong requirement for the query. Limitation: works for queries for which the neighbors are all above a (relatively high) similarity threshold to the query

[1]Croft, Metzler and Strohman [1], [2]Bradley, Den Bakker, Rocha, McVean and Iqbal [2], [3]Bingmann, Bradley, Gauger and Iqbal [3], [4]Solomon and Kingsford [4], [5]Gupta, Yan, Coleman, Kille, Elworth, Medini, Treangen and Shrivastava [5], [6]Broder [6],[7]Engels, Coleman and Shrivastava [7]

Table 2. GSearch's performance on major CPU platforms for searching 8,466 query genomes against the RefSeq reference database (~318K genomes). ProbMinHash was used as the genomic distance algorithm for this benchmark, with 50 neighbors requested.

CPU	Number of threads	Clock speed (GHz)	**Request time for nt (min)**	Gene Prediction-FGSrs (min)[c]	**Request time for proteome (min)**	hmmsearch time (min)[d]	**Request time for USCG (min)[d]**
Intel (R) Xeon (R) Gold 6226[a]	24	2.70	**9.329**	3.348	**6.234**	3.524	**0.445**
Intel (R) Core i9-8950HK[b]	16	2.30	**13.654**	6.764	**7.91**	6.214	**0.613**
AMD EPYC 7513a[a]	32(24 used)	2.60	**10.245**	4.452	**6.021**	3.345	**0.402**
Apple M1 Pro[b]	10	3.22	**9.669**	4.31	**6.166**	4.603	**0.568**

[a] RHEL v7.9, Linux v3.10.0-1160, all threads used. 512G RAM available.

[b] MacOS v12.3, Darwin 21.4.0 on MacBook Pro laptops, all threads used. Database was split into two pieces to have smaller memory requirement on those 16GB RAM laptops since database size was ~15GB for entire NCBI/RefSeq.

[c] Parallel package was used to run multiprocess at the same time. FGSrs stands for FragGeneScanRs (comparisons with Prodigal can be found in Table S11). Note that in practice only those genomes failing in the request step at the nucleotide (nt) level (best match found was less than 78% ANI) will be used in this amino-acid step.

[d] Only 1000 genomes were used for testing hmmsearch and USCG request in GSearch because this step was for assessing a few genomes that were novel at the order level or above. Parallel Packages was used to run multiple processes of hmmsearch, one thread per process for hmmsearch.

Table 3. Recall of GSearch for two query genome datasets containing various levels of novel genomes relative to the genomes in the reference database. The query genome datasets are the same as those used in Table 2. Blastn-ANI, blastp-AAI and universal gene blastp-ANI were used as the reference results (or standards) to compare against. Recall is the average across all query genomes.

Dataset	Dataset size (# of genomes)	level	Recall (top 5)	Recall (top 10)
Tara (with best in database)[1]	**6,992**	**nucleotide**	**98.3%**	**96.2%**
Tara (without best hit in database)	1474	nucleotide	62.4%	43.1%
Tara (with best in database)[2]	**1147**	**proteome**	**97.2%**	**96.9%**
Tara (without best hit genome in database)	327	proteome	65.0%	50.8%
Tara (with best in database)[3]	**327**	**universal**	**96.4%**	**95.5%**
Ye (with best in database)[1]	**906**	**nucleotide**	**97.7%**	**95.1%**
Ye (without best hit in database)	91	nucleotide	54.8%	48.5%
Ye (with best in database) [2]	**66**	**proteome**	**96.3%**	**95.2%**
Ye (without best hit in database)	25	proteome	76.0%	55.5%
Ye (with best in database)[3]	**25**	**universal**	**95.7%**	**94.6%**

[1]Definded as query genomes that had best match in the database better than 78% ANI; [2]defined as query genomes that had best match in the database better than 52% AAI; [3]defined as query genomes that had best match in the database better than 55% AAI based on universal genes.

Table References

1. Croft, W.B., Metzler, D. & Strohman, T. Search engines: Information retrieval in practice, Vol. 520. (Addison-Wesley Reading, 2010).
2. Bradley, P., Den Bakker, H.C., Rocha, E.P., McVean, G. & Iqbal, Z. Ultrafast search of all deposited bacterial and viral genomic data. *Nature biotechnology* **37**, 152-159 (2019).
3. Bingmann, T., Bradley, P., Gauger, F. & Iqbal, Z. in String Processing and Information Retrieval: 26th International Symposium, SPIRE 2019, Segovia, Spain, October 7–9, 2019, Proceedings 26 285-303 (Springer, 2019).
4. Solomon, B. & Kingsford, C. Fast search of thousands of short-read sequencing experiments. *Nature biotechnology* **34**, 300-302 (2016).
5. Gupta, G. et al. Fast processing and querying of 170tb of genomics data via a repeated and merged bloom filter (rambo). *Proceedings of the 2021 International Conference on Management of Data*, 2226-2234 (2021).
6. Broder, A.Z. in Proceedings. Compression and Complexity of SEQUENCES 1997 (Cat. No. 97TB100171) 21-29 (IEEE, 1997).
7. Engels, J., Coleman, B. & Shrivastava, A. Practical near neighbor search via group testing. *Advances in Neural Information Processing Systems* **34**, 9950-9962 (2021).