Smoother: A Unified and Modular Framework for Incorporating Structural Dependency in Spatial Omics Data

Jiayu Su[*,1,2,3], Jean-Baptiste Reynier[1,4], Xi Fu[1,4], Guojie Zhong[2], Jiahao Jiang[5], Rydberg Supo Escalante[2], Yiping Wang[1,6], Luis Aparicio[1,2], Benjamin Izar[1,6], David A Knowles[2,3,7], Raul Rabadan[*,1,2,4]

[1]*Program for Mathematical Genomics, Columbia University, New York, NY, USA*

[2]*Department of Systems Biology, Columbia University, New York, NY, USA*

[3]*New York Genome Center, New York, NY, USA*

[4]*Department of Biomedical Informatics, Columbia University, New York, NY, USA*

[5]*Wellcome Centre for Human Genetics, University of Oxford, Oxford, UK*

[6]*Department of Medicine, Division of Hematology/Oncology, and Herbert Irving Comprehensive Cancer Center, Columbia University Irving Medical Center, New York, NY, USA*

[7]*Department of Computer Science, Columbia University, New York, NY, USA*

---

[*] Correspondence: js5756@cumc.columbia.edu, rr2579@cumc.columbia.edu

Abstract

Spatial omics technologies can help identify spatially organized biological processes, but existing computational approaches often overlook structural dependencies in the data. Here, we introduce Smoother, a unified framework that integrates positional information into non-spatial models via modular priors and losses. In simulated and real datasets, Smoother enables accurate data imputation, cell-type deconvolution, and dimensionality reduction with remarkable efficiency. In colorectal cancer, Smoother-guided deconvolution revealed plasma cell and fibroblast subtype localizations linked to tumor microenvironment restructuring. Additionally, joint modeling of spatial and single-cell human prostate data with Smoother allowed for spatial mapping of reference populations with significantly reduced ambiguity.

Keywords

Spatial omics, Spatial prior, Data imputation, Cell-type deconvolution, Dimensionality reduction, Reference mapping, Joint analysis of single-cell and spatial data

Background

From subcellular arrangement to tissue compartmentalization, the spatial structure in an organism is highly organized at all scales. This harmonious architecture regulates a diverse variety of biological processes, including embryonic development, neuronal plasticity, and the tumor microenvironment. Recent advances in spatially resolved omics technologies provide unique opportunities to study localization patterns of gene and epigenetic activities, as well as the dynamics of biological systems at cellular and tissue levels(1-5). While existing non-spatial omics analysis methods can be applied to spatial data, the neglect of positional information makes them inadequate in overcoming structured technical noise(6), let alone inferring

biologically meaningful spatial organization. Meanwhile, *ad-hoc* spatially aware models often

hardcode neighborhood structures into task-specific algorithms(7-15), hindering adaptation to

new applications without substantial modification. Even within the same application, models

pretrained on one sample usually cannot be applied to another, as the neighborhood graph varies

from sample to sample. Additionally, these models are also incompatible with non-spatial data,

including the rich single-cell omics atlas datasets, and therefore cannot transfer knowledge

learned from non-spatial modalities to enhance spatial analysis.

Physically adjacent spots or cells generally exhibit more similarity compared to distant pairs,

with the similarity decaying with distance at different rates (**Supplementary Fig. 1**). Such

patterns are consistently observed across tissues, technologies, and modalities — even in single-

cell resolution data**(16)** (**Supplementary Fig. 1e**) and in super-resolved tumor microenvironment

sections(17, 18) (**Supplementary Fig. 1d and f**). Permutation experiments further confirmed

that the long-range similarity structure is not an artifact of contamination or signal bleeding

(**Supplementary Fig. 1i**). Despite its universality, spatial dependency in omics data has yet to be

formally described in a generic framework independent of downstream applications. Instead,

existing algorithms developed for individual tasks often regard spatial variation as a task-specific

property, unnecessarily restricting their generalizability to new applications. For example,

Markov random field-based models like Giotto(7), BayesSpace(8), CARD(9) and

BayesTME(10), although utilizing the same Bayesian message passing mechanism, each

introduce structural dependency with unique, integrative, and non-sharable implementations.

This practice becomes especially troublesome when the prior belief needs modification, for

instance, to encode boundary information or scale to larger datasets. Similarly, graph-based

neural networks such as SpaGCN(11) and STAGATE(12) also incorporate spatial structure as a

hard constraint and integral part of the model. While interactions between neighbors can be

learned adaptively from the data, these models are essentially black boxes, leaving users with

minimal control over over-smoothing and signal dilution.

Here we present Smoother, a unified and modular framework for integrating spatial dependency

across applications. By representing data as boundary-aware weighted graphs and Markov

random fields(19, 20), Smoother explicitly characterizes the dependency structure, allowing

information exchange between neighboring locations and facilitating robust and scalable

inference of cellular and cell-type activities. Through the transformation between spatial prior

and regularization loss, Smoother is highly modularized and ultra-efficient, enabling the

seamless conversion of existing non-spatial single-cell-based models into spatially aware

versions. We demonstrate the versatility of Smoother by implementing and testing its

performance on tasks including cell-type deconvolution and dimensionality reduction. Using

simulated and real omics data of different modalities, our benchmarks highlight the substantial

advantages of explicitly modeling and incorporating spatial dependencies. Furthermore,

Smoother's soft regularization approach also supports spatially aware joint embeddings of data

with and without neighborhood structure, potentially bridging the gap between spatial and

single-cell analyses.

Results

Overview of the Smoother framework.

Smoother differs from existing models in that it treats data-specific dependencies as shared and

reusable priors across downstream tasks, encouraging local smoothness on any spatial variable of

interest (**Fig. 1, Methods and Supplementary Notes**). Inspired by penalized likelihood

methods(21), we decouple the prior belief on dependency from the likelihood of a non-spatial

data-generating model. This flexibility allows the same prior to be used in different models, and

the same model to accommodate data with varying or even zero spatial structures. In addition,

Smoother encodes boundary information that is often neglected in existing Bayesian methods

(**Fig. 2**). Specifically, it first builds a spatial graph in which edges connecting physically adjacent

locations are scaled and pruned using histological and transcriptomic similarities to remove

undesired interactions (**Fig. 2a**). Through graph weighting, users may incorporate additional

knowledge from other modalities, even though the actual region boundaries in omics data

probably being less distinct (**Fig. 2e and Supplementary Fig. 2**), The spatial graph is then

converted into a multivariate normal (MVN) prior with varying degrees of dependencies, along

with an equivalent spatial loss that can be appended to non-spatial models (**Supplementary Fig.**

3. See **Methods** for detailed recommendations on constructing the prior).

As a simple showcase of Smoother, we considered feature smoothing and resolution enhancing,

where variables at unobserved locations are inferred from a hidden Markov random field with

the MVN prior(22) (**Fig. 1 left and Methods**). Unlike other data imputation algorithms(12, 15,

23), our model does not assume feature-level dependencies, making it applicable to a single

feature of interest, especially non-expression data. We investigated whether it was possible to

overcome data sparsity using spatial context alone. Gene signature scoring is a common

approach to evaluate high-level activities of functionally associated gene sets(24), where

borrowing information across similar genes may introduce biases and artificially amplify the

signal. By penalizing local variations over space, Smoother successfully mitigated dropout

effects and improved the separation of localization patterns of cortical layer signatures in a

human dorsolateral prefrontal cortex (DLPFC) dataset(25) (**Supplementary Fig. 4**). Furthermore,

Smoother offers ultra-fast functionality, without requiring additional inputs like histological

images(15), to enhance spatial resolution to any scale in seconds (**Supplementary Fig. 5**). While

accuracy relies on the assumption that spatially adjacent spots share more similarity, this can be

practically helpful when working with shallow sequencing depths. On a Slide-seqV2 dataset of

human melanoma brain metastasis(17), we noted improved correlations in the activities of

functionally connected modules, such as chemokine and interferon response, after smoothing and

enhancing (**Supplementary Fig. 6**).

Smoother enhances cell-type deconvolution performance in simulated and real spatial

omics data.

A common challenge with barcode-based spatial omics technologies that capture a mixture of

cells at each location is to disentangle cell-type composition across space. Despite the many

deconvolution methods(26-31) developed for spatial transcriptomics (ST) data, few recognize

spatial dependency explicitly. Even for these methods, for instance CARD(9) and

BayesTME(10), the spatial covariance is hard-coded and not transferable to other models. To fill

this gap, we extended four non-spatial deconvolution models using Smoother to resolve the

distribution pattern of cell types in a spatially informed manner (**Fig. 1 bottom**). These include

non-negative least squares (NNLS), support vector regression (SVR)(32), dampened least

squares (DWLS)(33), and log-normal regression (LNR)(34). To benchmark the effect of

Smoother, we first simulated ST data with distinct patterns, diverse degrees of spatial

heterogeneity, and composition-independent structural noise corresponding to spot bleeding

(**Supplementary Fig. 7, 14 and Methods**). In almost every simulation scenario, the inclusion of

spatial context consistently yielded more accurate and realistic deconvolution results (**Fig. 3 and**

Supplementary Figs. 8-14). Compartment boundaries became notably cleaner as real signals

stood out against the prior while noise was smoothed out (**Fig. 3c and g**). This benefit proved

highly robust to the selection of models, hyperparameters, and marker genes, while the

magnitude shrinks as cell-type-independent spatial variation like spot bleeding grew

(**Supplementary Figs. 15-17**). Surprisingly, we observed that CARD failed to take advantage of

its own neighborhood modeling, and thus in some scenarios performed worse than a simple non-

spatial model. Our results indicate that the parameterization of spatial structure used in CARD is

suboptimal, underscoring the importance of a unified and modular framework for dependency

representation.

We next applied all spatially aware deconvolution methods to analyze real spatial omics data of

normal, developmental and cancer tissues. Descriptions of each dataset and preprocessing details

can be found in the Methods section (**Methods**). We first evaluated deconvolution performance

in detecting immune infiltration in a 10x Visium invasive ductal carcinoma dataset(8), where

CD3 staining provided ground truth for the presence of T cells. Smoother-guided NNLS

faithfully reflected overall T-cell distributions and accurately unveiled the invasive lymphocytic

pattern near tumor borders, whereas CARD failed to detect any T-cell signal within the tumor

(**Fig. 4a and Supplementary Fig. 18**). The advantage of spatial context modeling was further

validated by the elevated correlation of CD3 staining with estimated abundance, outcompeting

baseline correlations between gene expression and protein staining (**Fig. 4b and c**). Secondly, to

evaluate Smoother's ability to filter noise while maintaining meaningful boundaries, we

performed deconvolution on a 10x Visium dataset of mouse brain(26) and estimated the

abundances of 52 neural subtypes across brain locations simultaneously (**Fig. 4d**). As revealed

by unsupervised clustering, Smoother notably reduced local discontinuities in cell-type

composition, while preserving distinct tissue region boundaries (**Fig. 4e**). In particular,

Smoother-based models sharply distinguished excitatory neuron subtypes in cortex and

hippocampus, attenuating fluctuations within layers and subregions and producing more precise

transitions compared to CARD (**Fig. 4f and g**).

Using a spatial-CUT&Tag dataset of mouse E11 embryo, we further assessed the generalizability

of Smoother-based deconvolution across modalities (**Fig. 4h and Methods**). Spatial-

CUT&Tag(4) profiles chromatin modification using antibodies against histone proteins including

H3K27me3, H3K4me3, and H3K27ac. To align the epigenomic data with transcriptomic cell

types, we performed deconvolution on epigenomics-based gene activity scores using scRNA-seq

reference of 37 embryonic cell types(35) (**Supplementary Fig. 19**). These activity scores differ

significantly from expression counts in scale, variability, and biological meaning. Moreover,

some transcriptomic cell types may be epigenetically indistinguishable, thereby necessitating

more robust deconvolution. Regularization has long been recognized as a solution to the

multicollinearity problem(36). Consistently, Smoother salvaged the poor performance of the

non-spatial model, producing biologically coherent embryonic compartmentalization (**Fig. 4i**).

Close examination of the predicted cell-type composition showed that the Smoother-guided

approach excelled in restoring the spatial organization of the embryo with minimal unsolved

background (**Fig. 4j**). In particular, only the spatially regularized NNLS model accurately

mapped the cardiac muscle lineage to the heart region (**Supplemental Fig. 20-22**). The predicted

spatial structures of glial (*Sox9*), neural tube (*Ascl1*), cardiac muscle (*Hand2*), and definitive

erythroid (*Lmo2*) lineages were further validated by marker gene activity (**Fig. 4k**).

Smoother-guided deconvolution unveils distinct localizations of plasma cells and fibroblasts

in mismatch repair-proficient colorectal cancer.

To further demonstrate the utility of Smoother-guided deconvolution in large-scale cancer ST

datasets, we applied the method to a new Stereo-seq mismatch repair-proficient (MMRp)

colorectal cancer (CRC) dataset with paired patient-derived scRNA-seq data(18). Utilizing gene

modules from prior research(37), we identified eight major cell types and 16 functionally distinct

subsets in the scRNA-seq reference, including three plasma cell subpopulations: namely IgG+,

IgA+, and IgA+ FOS/JUN+ (**Fig. 5a and b**). *FOS* and *JUN* are B-cell receptor pathway modules

and have been shown to be upregulated in tumor-infiltrating B cells in other solid tumors(38).

We then mapped these single-cell populations to spatial locations through deconvolution. Overall,

the Smoother-guided model outperformed CARD in recapitulating the pathological structure,

particularly at region boundaries (**Fig. 5c and d**). This facilitated the discovery that the three

plasma populations resided in distinct regions: specifically, the IgG+ population were

predominantly in the tumor region (lesion) whereas the IgA+ cells were in mucosa (**Fig. 5c and**

e). We confirmed the differential localization of IgG+ and IgA+ plasma cells using marker gene

expression (**Fig. 5f and Supplementary Fig. 23**). In addition, the lesion IgG+ and mucosa IgA+

spots exhibited divergent B-cell receptor V/C gene usage, with *IGLC2*, *IGLC3*, *IGLV3-1* and

IGKV4-1 all enriched in the tumor, suggesting a difference in the adaptive response between the

two plasma cell types (**Fig. 5f**). Gene Ontology pathway analysis further emphasized this

difference, with "B-cell activation" enriched in the IgG+ plasma cell sections and "Defense

response to bacterium" in the IgA+ plasma cell sections (**Fig. 5g**). Our observation aligns with

the established role of IgA+ plasma cells in colorectal mucosal tissues(39), as well as numerous

reports of antibody class switching to IgG in the CRC tumor microenvironment(40), which has

high potential for diagnostics(41, 42) and therapeutics(37, 43). In stark contrast, CARD

incorrectly predicted all plasma cell clones to be IgG+, including in the mucosa region

(**Supplementary Fig. 23**).

Additionally, Smoother-guided deconvolution revealed three phenotypically and spatially

distinct fibroblast populations, characterized by previously reported ADAMDEC1+/CCL8+,

CXCL14+, and matrix transcriptional programs(37), all validated by marker gene expression

(**Supplementary Fig. 24**). ADAMDEC1+/CCL8+ and CXCL14+ fibroblasts were preferentially

co-localized with the IgG+ plasma cells (**Fig. 5h**), in accordance with the observed presence of

CXCL14+ cancer-associated fibroblast and ADAMDEC1+/CCL8+ fibroblast in MMRp

CRC(37). Recent work has demonstrated *ADAMDEC1*-driven fibroblastic matrix remodeling in

response to inflammation(44), which explains partially the enrichment of collagen and

extracellular matrix-related pathways in IgG+ plasma cell sections (**Fig. 5g**). Conversely, CARD

again failed to delineate these three fibroblast populations (**Supplementary Fig. 23 and 24**). We

repeated the deconvolution analysis on a paired distant normal tissue but observed no differential

localizations of plasma cell and fibroblast subpopulations (**Supplementary Fig. 25**).

Smoother-guided dimensionality reduction and integration of spatial and single-cell data.

Learning an informative low-dimensional representation is crucial for understanding the biological dynamics underlying noisy omics data. Smoother's ability to impose structural dependencies via a versatile loss function allows us to generalize existing non-spatial dimensionality reduction methods to spatial omics data (**Fig. 6a, Methods and Supplementary Notes**). This is further strengthened by the contrastive extension of the spatial loss that better separates distant locations and averts the collapse of embeddings (**Methods**). As a proof of concept, we first developed a spatially regularized principal component analysis (PCA) model(45) and applied it to the human cortex DLPFC data(25). Across all 12 samples, the inclusion of spatial loss consistently improved performance when reconstruction and regularization were balanced, with contrastive loss further strengthening its robustness (**Supplementary Fig. 26a and b**). These enhancements are manifest in the 2D visualization where outer cortical layers are increasingly separated from inner layers and the white matter with stronger regularization (**Supplementary Fig. 26c**). Nevertheless, existing graph-based autoencoders like STAGATE(12) and SpaceFlow(13) achieved even better separation, indicating the intrinsic limitation of PCA as a linear encoder. To dissect the benefit of spatial modeling from simply having a broader parameter space, we replaced the graph attention module in STAGATE with fully connected layers and again incorporated spatial loss during training (**Supplementary Fig. 26d-h**). By increasing the strength of spatial regularization, we recovered 50% - 90% of the performance as measured by embedding consistency (Silhouette score) and clustering accuracy (adjusted rand index) (**Supplementary Fig. 26d-g**). Under 2D UMAP visualization, the space progressively unfolded, and transitions between layers evolved from being non-existent to becoming clear

(**Supplementary Fig. 26h**). Together, our results support the potential of spatial loss as a fast

and versatile alternative strategy to instill spatial awareness irrespective of model architecture.

This modular approach, especially the separation of neighborhood constraints from the

autoencoder, offers unique advantages. Through Smoother, we can now adapt pretrained single-

cell based non-spatial models to spatial data by fine-tuning over a new spatially aware objective,

providing an approach to transfer knowledge from single-cell atlases to spatial omics data (**Fig.**

6a). Specifically, we designed SpatialVAE from SCVI, a prominent deep generative variational

autoencoder (VAE) for scRNA-seq data analysis(46, 47). When integrating scRNA-seq datasets,

the conventional SCVI workflow includes training a reference model on large atlas datasets,

fine-tuning on the query data, and generating joint embeddings of both for label transfer. Here

we focused on annotating a human prostate Slide-seqV2 data(48) using a single-cell reference

from the Tabular Sapiens(49). After downloading the pretrained model (**Fig. 6b**) from the SCVI

model hub, we fine-tuned the model on the spatial data while ignoring coordinates (RNA-only)

to remove batch effects. Although SCVI ranks among the top performing data integration

tools(50), the Slide-seqV2 data remained distinctly separated from the rest of single-cell data in

the joint embedding space (**Fig. 6d**), likely due to its low sequencing depth (**Fig. 6c**).

Consequently, most spots were marked as ambiguous, that is, not close to any single-cell clusters

within the uncertainty threshold (**Fig. 6e**). In contrast, SpatialVAE's spatially aware refinements

significantly reduced batch effects (**Fig. 6f**), enabling cell label transfer with dramatically

reduced ambiguity (**Fig. 6g**). Detailed examination revealed a balanced tradeoff between

reconstruction precision and spatial coherence of the embeddings, suggesting that the spatial loss

potentially acts via directing the model to focus on spatially consistent features over batch-

specific technical noise (**Supplementary Fig.27a**). Using the prostate joint embeddings, we also

corrected an annotation mistake in the original publication where cell type labels were mapped to

the Slide-seqV2 data using RCTD deconvolution(28). While initially labeled as fibroblasts, the

stromal population were indeed primarily composed of smooth muscle cells (referred to as

pericytes in(48)) according to SpatialVAE's prediction (**Supplementary Fig. 27b**). This was

confirmed by marker gene expression (**Supplementary Fig.27c-d**).

Discussion

The inherent neighborhood dependency of spatial omics data motivated us to develop an

efficient approach to introduce spatial structure across single-cell applications. Grounded in

Bayesian inference and penalized likelihood methods, Smoother imposes regularization at

minimal computational burden, particularly by leveraging the sparse nature of the neighborhood

graph. In practice, tasks such as enhancing resolution and deconvolving tens of thousands of

spots can typically be completed within seconds on a standard personal laptop. The efficiency

positions Smoother as an apt solution for the growing demands to explore spatial omics

techniques with larger field-of-view, higher resolution, and increased throughput. One caveat to

Smoother is that the optimal strength of spatial dependencies, which reflects prior assumptions

on the data, is usually agnostic beforehand in downstream applications. Still, we have

demonstrated that Smoother is remarkably robust with respect to hyperparameters. It may also be

possible to fine-tune the smoothing strength in specific tasks using cross validation and empirical

Bayes approaches(51). Collectively, Smoother offers a scalable, and versatile solution to enhance

a wide range of tasks including data imputation, deconvolution, and dimensionality reduction.

Under this framework, the spatial loss can be melded with any optimization-based non-spatial

model, pretrained or otherwise, endowing it with spatially awareness. In light of the ubiquity of

structural dependencies, we envision that Smoother may be readily extended to even more

applications, such as trajectory inference and cell-cell communication, paving the way for new

biomedical discoveries in developmental and disease settings.

Conclusion

In this study, we introduce Smoother, a powerful and adaptable computational approach

designed to integrate spatial structure into omics data analysis. Through spatial priors and losses,

Smoother provides a streamlined and efficient way to rewire existing single-cell-based models

for spatially informed applications, including feature smoothing, resolution enhancing, cell-type

deconvolution, and dimensionality reduction. Benefiting from its robustness, Smoother-

regularized deconvolution accurately mapped transcriptomic cell types to spatial epigenomics

data. When applied to colorectal cancer sections, it further revealed tumor-associated

localizations of plasma cell and fibroblast subpopulations. Furthermore, Smoother's

compatibility with non-spatial data allowed for the spatially informed integration of human

prostate data, facilitating cell type prediction with markedly lower ambiguity.

Methods

Overview of Smoother

Smoother is a two-step framework that extracts prior dependency structures from positional

information and integrates them into non-spatial models for downstream tasks to encourage local

smoothness. We use $Y_{G \times S}$ to denote the spatial omics data of G genes (or the corresponding

features in other modalities) at S locations, and $L_{F \times S}$ the spatial metadata of F spatial features

(e.g., image feature extracted from histology) at S locations. The first step of Smoother is to

construct a spatial graph G = (V, E, W) where the node set V represents locations and both the

edge set E and edge weights W are functions of $L_{F \times S}$. Then, Smoother computes a covariance

structure $\Sigma_{S \times S}$ from the graph G and imposes it through the spatial prior on $Y_{G \times S}$ or other

variables of interest. For a comprehensive explanation of Smoother, see below and the

Supplementary Notes.

Construction of spatial priors and losses.

Smoother draws from the concept of spatial stochastic process and an extensive body of spatial

priors in image processing and geographic data analysis(22, 52, 53). Intuitively, a spatial

stochastic process lets us model global dependency characteristics by assuming stationarity and

specifying the local interactions of spatial random variables. Here we represent spatial

connectivity using a weighted undirected graph G = (V, E, W) where physically adjacent

locations V are connected by edges E with varying strengths W. The adjacency matrix $W_{S \times S}$,

which is also called the spatial weights matrix of the underlying spatial process, maps out the

connectivity between spots based on physical distance. Here $w_{i,j} = 1$ if spot i and j are mutual k-

nearest neighbors, otherwise 0. For hexagonal grids like the 10x Visium chip, k is set to 6. To

encode domain boundaries, we further scale $W_{S \times S}$ using histological or transcriptomic pairwise

similarities (soft-scaling), or manual domain annotations (hard-scaling):

$$W'_{S \times S} = W_{S \times S} \odot D_{S \times S}^{soft, hard}$$

where $D_{i,j}^{soft}$ is the similarity between spot i and j, and $D_{i,j}^{hard}$ is the binary indicator of whether

spot i and j belong to the same domain. In practical applications, hard-scaling domains can be

defined from histology image segmentation(54), transcriptomic clustering, or expert pathological

annotations. For soft scaling, we extract per-spot gene expression or histological features and

compute $d_{i,j}$ as the pairwise similarity in a PCA-reduced space. If scaling by transcriptomics, the

first 10 PCs of gene expression and cosine similarity (which is approximately the cosine

similarity of Z-scores of full gene expression) are used by default and negative similarities are

clamped to zero. If scaling by histology, the feature vector of a spot is the first three PCs of the

concatenated RGB values of pixels in the square circumscribed about the spot, and similarity is

converted from the Euclidean distance by a Gaussian kernel with band width 0.1 in the

normalized PC score space. Specific choices on similarity metrics usually do not have a strong

impact on the resulting prior. Empirically, we found the scaling of gene expression to be helpful

in maximizing dissimilarity between disparate neighbors.

Subsequently, Smoother translates the spatial weights matrix $W_{S \times S}$ into a covariance structure

$\Sigma_{S \times S}$ according to assumptions on the underlying stochastic process (see **Supplementary Notes**).

The covariance is then introduced to any spatial variable of interest, X_S, through a multivariate

normal (MVN) prior. For example, in a conditional autoregressive (CAR) process where the

graph G describes a Gaussian Markov random field of X_S:

$$x_i \mid x_{\backslash i} \sim N\left(\rho \Sigma_{j \neq i} \, w_{ij} \, x_j, \sigma_i^2\right),$$

335   the joint distribution of X_S is a zero-centered MVN distribution with covariance $\Sigma_{S \times S}$, a

336   smoothing prior that can be imposed on X_S in downstream tasks:

$$\Sigma_{S \times S} = diag(\sigma_i^{-2})(I - \rho W)^{-1}$$

$$P(X_S) \propto exp\left(-\frac{1}{2} X_S^T \Sigma_{S \times S}^{-1} X_S\right).$$

Here ρ is the autocorrelation parameter to make $\Sigma_{S \times S}$ positive semi-definite and to control the

decay rate of covariance over distance (**Supplementary Fig. 3**), which can be selected by

examining the decay pattern of pairwise similarity (**Supplementary Fig. 1**). Since $\Sigma_{S \times S}$ is

constructed from a boundary-aware graph, the above MVN prior provides a unique channel for

neighboring locations to share information while still preserving boundaries.

Smoother offers five different yet related spatial processes: CAR, SAR (simultaneous

autoregressive), ICAR, ISAR, and SMA (spatial moving average). Specifically, CAR and SAR

are equivalent upon transformation, and ICAR and ISAR are the weights-scaled versions so that

the autocorrelation parameter ρ falls in [0, 1]. By adjusting ρ, these models can achieve parallel

regularization effects. Based on numerical considerations, we typically recommend using ICAR

with varying ρs (or ISAR with smaller ρs) to accommodate data with diverse neighborhood

structures. For instance, 'ICAR (ρ =0.99)' for data with clear anatomy and 'ICAR (ρ =0.9)' for

tumor data. SMA is generally not recommended since the resulting inverse covariance matrix

tends to be less sparse, potentially slowing down computation.

To render Smoother compatible with existing non-spatial methods, we propose a quadratic

regularization loss proportional to the density function of a zero-centered MVN with covariance

$\Sigma_{S \times S}$:

$$L_{sp}(X_S; \Sigma_{S \times S}) = X_S^T \Sigma_{S \times S}^{-1} X_S.$$

356   Essentially, for any given model with a loss function L_m, it is possible to morph the model into a

357   spatially aware version by minimizing a new joint loss function:

$$L_{joint}(X_S) = L_m(X_s) + \lambda_{sp} L_{sp}(X_S; \Sigma_{S \times S}).$$

The spatial loss term L_{sp} regularizes local fluctuations in X_s and makes the inference robust to

technical noise. It can be shown that optimizing the new objective is equivalent to finding the

maximum a posteriori (MAP) estimator under the spatial prior, and λ_{sp} can be viewed as the

strength (inverse variance) of the prior. Most importantly, since L_{sp} is separated from the model

loss, the same model can jointly accommodate data with or without neighborhood structures.

In addition, we implement a contrastive extension of the spatial loss to increase the penalty for

pulling distant spots too close, ensuring that the inference does not collapse into trivial solutions.

This is done by shuffling spot locations and producing corrupted covariance structures as

negative samples,

$$L_{csp} = X_S^T \Sigma_0^{-1} X_S - \frac{1}{T} \sum_t X_S^T \Sigma_t^{-1} X_S$$

where Σ_0 is the covariance derived from the correct spatial graph and $\Sigma_t, t \in [1, T]$ are those

from corrupted graphs.

Data imputation and resolution enhancement

Using local contexts in the prior dependency structure, Smoother is capable of smoothing and

imputing spatial omics data at unseen locations for any single spatial random variable of interest

X_S. For simplicity, we assume the variable follows a hidden Markov random field model with

technical noise being Gaussian iid. This implies that the observation Y_S follows the model:

$$y_s \sim N(x_s, \sigma_0^2)$$

$$X_S \sim MVN(0, \sigma_1^2 \Sigma_{S \times S})$$

376   where σ_0^2 and σ_1^2 are the variance of observation and prior, respectively. Similarly, we can

377   reparametrize the above problem and find the MAP estimator of X_S by solving the following

378   optimization task with a given spatial loss:

$$\tilde{X}_{MAP} = argmin_X \|Y_S - X_S\|^2 + \lambda_{sp} X_S^T \Sigma_{S \times S}^{-1} X_S$$

where $\lambda_{sp} \propto \sigma_0^2 / \sigma_1^2$ determines the strength of regularization. This is a special case of Tikhonov

regularization and is akin to the weighted average filter commonly used for image smoothing.

Note that the first L2 term, corresponding to the reconstruction error, can be replaced by other

likelihood-based or more sophisticated losses in deep generative models for non-Gaussian

variables. When part of the data is missing, the objective function is similar except the first

reconstruction term is computed only at observed positions. As $\Sigma_{S \times S}$ is predefined independently

of the observation, Smoother can impute the latent value at arbitrary locations and thus increase

the spatial resolution.

Cell-type deconvolution

We define spatial deconvolution as the problem of inferring cell-type abundances at each

location from the observed omics data, with or without cell-type reference information from

external data. The task is especially relevant for spatial techniques with limited resolution,

including 10x Visium, spatial-CUT&Tag(4) and spatial-ATAC-seq(5), where each profiled

location might consists of cells from multiple cell types. The deconvolution model is usually

determined by the generative model of the observations $Y_{G \times S}$. Most deconvolution methods

assume a linear relationship between observation and cell-type abundance:

$$Y_{G \times S} \sim N(g(R_{G \times C} X_{C \times S}), \sigma_0^2).$$

Here, $Y_{G \times S}$ is the observed activities of G features at S spots, $R_{G \times C}$ is the expected reference

activities of G features in C cell types, $X_{C \times S}$ is the abundance of C cell types at S spots, σ_0^2 is the

sampling variability, and g is the data generative function that introduces additional noise such as

location-specific biases. Without loss of generality, we follow the same linearity assumption and

extend existing deconvolution models to leverage neighborhood information by imposing the

spatial prior on the abundance of each cell type:

$$X_{c:} \sim MVN(0, \sigma_1^2 \Sigma_c).$$

402   Here, Σ_c is the prior covariance structure, and $1/\sigma_1^2$ represents the strength of prior. When the

403   reference $R_{G \times C}$ is known, usually from a paired single-cell dataset, we solve $X_{C \times S}$ by minimizing

404   the following regularized factorization problem:

$$\tilde{X}_{MAP} = argmin_X \, L_{deconv}(Y, RX) + \lambda_{sp} \sum_c X_{c:} \Sigma^{-1} X_{c:}^T$$

where $L_{deconv}(Y, X\beta)$ is the loss specified by the corresponding deconvolution model. We

implemented four spatially aware deconvolution models including non-negative least squares

(NNLS), support vector regression (SVR), dampened least squares (DWLS), and log-normal

regression (LNR). Further details can be found in the **Supplementary Notes**. When the

reference is unknown, the above deconvolution can be solved via matrix factorization, which is

also a special case of the dimensionality reduction task, as will be discussed in the next section.

Dimensionality reduction

The goal of dimensionality reduction is to infer a condensed low-dimensional representation

retaining the data's essential characteristics. For spatial omics data, latent dimensions should

ideally represent continuous dynamics in space. We frame the dimensionality reduction task

using a general autoencoder model,

$$Y_s \xrightarrow{E_\theta} Z_s \xrightarrow{D_\phi} Y_s{'}$$

where E_θ is the decoder that projects omics data $Y_s \in R^G$ at the location s with G features onto a

low-dimensional space R^H with H hidden dimensions, and D_ϕ is the decoder that projects the

hidden embedding $Z_s \in R^H$ back to the original space.

Using Smoother, we can again impose prior on the hidden embedding to get more coherent

representation. For any auto-encoder model with parameter θ, ϕ and reconstruction loss function

$L_m(Y_s, \theta, \phi)$, Smoother regularizes the hidden representation $Z_s(Y_s; \theta) = E_\theta(Y_s)$ using a spatial

loss L_{sp} and solves a new joint objective

$$\hat{\theta}, \hat{\phi} = argmin_{\theta,\phi} \; L_m(Y, \theta, \phi) + \lambda_{sp} L_{sp}(E_\theta(Y); \Sigma_{S \times S}) + \lambda_c L_c(\theta, \phi)$$

425   where $L_c(\theta, \phi)$ is the additional soft constraint loss on model parameters, if any. For linear

426   dimensionality reduction models, including non-negative matrix factorization (NMF)(55),

427   principal component analysis (PCA)(45), and independent component analysis (ICA)(56), the

428   encoder E_θ and decoder D_ϕ are matrix multiplication operators and can be resolved via matrix

429   factorization:

$$Y_{G \times S}{'} = W^\phi_{G \times H}\left(W^\theta_{H \times G} Y_{G \times S}\right)$$

$$\widetilde{W^\theta}, \widetilde{W^\phi} = argmin_{W^\theta, W^\phi} \; L_m\left(Y, W^\phi\left(W^\theta Y\right)\right) + \lambda_{sp} L_{sp}\left(W^\theta Y\right) + \lambda_c L_c\left(W^\theta, W^\phi\right).$$

The apparent analogy between the above linear autoencoder model and linear deconvolution

suggests that cell-type abundance itself can be viewed as the hidden factor. When the

deconvolution reference $R_{G \times C}$ (i.e., $W^{\phi}_{G \times H}$ in the autoencoder) is unknown, factorizing $Y_{G \times S}$ is

both a dimensionality reduction task and a reference-free deconvolution task. Further semi-

supervised techniques can be applied to maximize the distinguishability of inferred latent states

(cell types) using known marker genes.

In this study, we developed corresponding spatial versions of PCA, vanilla deep autoencoder,

and Variational Autoencoder (VAE) within the Smoother framework. We assume all hidden

dimensions to be independent and regularize them simultaneously. Briefly, the PCA model has

symmetric encoder and decoder, requires latent dimensions to be orthogonal and uses L2 norm to

measure reconstruction error. The deep autoencoder model removes the symmetry and

orthogonality constraints, introduces nonlinearity, and incorporates an orthogonal loss to impose

soft constraints on the latent embedding. In a VAE model that describes the data generative

process and learns the distribution of latent representations, regularization is by default applied to

the mean of the inferred latent distribution.

Model implementation

Smoother is publicly available as a Python package (https://github.com/JiayuSuPKU/Smoother/).

Models involved in this study are implemented using PyTorch(57) and all optimizations are

solved via PyTorch's gradient-based optimizers (by default Adam for deconvolution and SGD

for dimensionality reduction). For convex problems, an alternative Smoother implementation via

CVXPY(58) is also available. For VAE models, we adopted the VAE implementation from the

Python package scvi-tools(47).

Preprocess spatial omics data

Unless otherwise noted, we downloaded spatial omics datasets from the SODB database(59)

where the data were preprocessed following the Scanpy workflow(60). For data not available

through SODB, we used the default Scanpy preprocessing workflow. In **Supplementary Fig. 1**,

we used the first 20 PCs of log-normalized expression data to calculate pairwise similarity decay.

Preprocessing details of the spatial-CUT&Tag data are provided below in the corresponding

subsection. Spatial priors across applications were constructed by default using ICAR with $\rho =$

0.99 and transcriptomic soft-scaling, unless otherwise specified.

Recover spatial patterns using Smoother-guided imputation and resolution enhancement

Human dorsolateral prefrontal cortex (DLPFC) dataset

For each cortical layer, we calculated gene signature scores using the 'scanpy.tl.score_genes'

function based on the expression of the top 20 marker genes ranked by log fold change. The

spatial prior was constructed under the ICAR model with $\rho = 0.99$ and $\lambda_{sp} = 1$. For imputation,

we randomly masked out certain proportions of spots in a slide and allowed the target variable to

vary in both observed and unobserved locations. For resolution enhancement, we added new

spots according to the desired new resolution through midpoint interpolation and ran imputation

on the new slide. Variable values at observed locations were fixed during enhancing.

Human metastatic melanoma Slide-seqV2 dataset

We preprocessed the Slide-seqV2 data of melanoma brain metastasis (MBM) and extracranial

melanoma metastasis (ECM) and the paired scRNA-seq data following the original

publication(17) using the R package Seurat(61). Functional signature scores were calculated

based on the expression of genes involved in the corresponding pathway using Seurat's

'AddModuleScore' function. We built an ICAR prior with $\rho = 0.9$ and $\lambda_{sp} = 1$ to impute

function scores individually and to enhance the spatial resolution. Pairwise Pearson correlation

between functional scores was calculated to evaluate the benefits brought by data imputation.

Evaluate cell-type deconvolution performance using simulation

Simulate ST datasets with spatial patterns

To generate synthetic ST datasets for benchmark, we followed a modified procedure adapted

from the cell2location paper(26). These modifications allowed us to: (1) assign arbitrary spatial

patterns to zones (co-localized cell-type groups) and (2) introduce additional noise for cell-type-

independent dependencies (e.g. spot bleeding). In brief, we initially overlaid designated patterns

with a two-dimensional Gaussian process to generate the per-zone abundance values in space,

then assigned cell types to these patterns. Next, we sampled gene expression profiles at each

location from a scRNA-seq reference according to the simulated cell-type composition. The ST

data is further combined with various sources of noise, including lateral diffusion where each

spot shares a certain proportion of mRNA to its neighbors directly, and multiplicative per-gene

gamma noise (by default shape = 0.4586, scale = 1/0.6992) for sampling error. The simulation

code is provided as a stand-alone tool within the Smoother package to facilitate future

benchmarking on related tasks.

Model comparison and evaluation

In the study, we focused our benchmarking on CARD, the only published spatially aware

deconvolution method shown to be superior to other existing methods(9). However, Smoother is

compatible with different deconvolution strategies. Any method, including the DWLS(33), nu-

SVR(32), and LNR(34) re-implemented in this study, may be seamlessly transformed to take

advantage of neighborhood information. CARD is a non-negative linear factorization model that

introduces spatial dependencies through a conditional autoregressive prior on cell-type

abundances, which is mathematically similar to the Smoother-guided NNLS model. We adhered

to the tutorial and ran CARD with default parameters. In certain simulation scenarios, a truncated

reference signature matrix with fewer genes was used as input, bypassing CARD's internal

reference construction process. This was to reflect potential discrepancies between the external

reference and observed ST data, and to separate the impact of reference quality from algorithm

performance. For the non-spatial CARD model, we set ρ to zero, effectively disabling any spatial

interactions.

The performance of deconvolution depends on the distribution properties of the input data. For

example, RNA-seq counts are typically skewed and, if left uncorrected, can bias the estimation

against lowly expressed genes and rare cell types(34). One practical solution is to perform

deconvolution on the logarithmic scale, i.e., replacing Y and X with $log1p(Y)$ and $log1p(X)$.

Although this approach is not physically sound, it has been shown to significantly improve

model performance, so does the square root scaling $\sqrt{Y}$ and $\sqrt{X}$ albeit to a less extent (data not

shown). For benchmarking purposes, unless otherwise stated, we supplied log-scale ST data to

NNLS, DWLS, and nu-SVR and raw-scale ST data to LNR and CARD. The reference

expression matrix was computed by averaging the normalized expression of marker genes across

all cells of a given cell type from an external scRNA-seq dataset, followed by log-transformation

where necessary. For more general cases, such as in epigenomics deconvolution where the

reference and observation data may not be on the same scale or even from the same modality,

users may include whatever preprocessing steps that best fit the dataset.

For Smoother-guided models, we constructed the spatial prior using ICAR ($\rho = 0.99$, which was

also the optimal ρ in CARD) and scaled the graph using transcriptomic similarity. The strength

of the spatial prior λ_{sp} is set to 0 for all non-spatial baseline models, 1 for spatially aware NNLS,

SVR, LNR, and 3 for spatially aware DWLS to adjust for the inflated model loss after scaling.

This is not necessarily the best performing setting as revealed in the parameter sensitivity

analysis (**Supplementary Fig. 15-17**). Nevertheless, we fixed the strength across all benchmarks

since the benefit of spatial context is rather robust. Cell-type abundances were set to be non-

negative in all models and were normalized to output the final cell-type proportions at each spot.

Benchmark deconvolution performance using the simulated doughnut-shaped data

We obtained the single-nucleus RNA-seq data of mouse brain (5705STDY8058280,

5705STDY805828) along with cell type annotations for each cell from

https://www.ebi.ac.uk/arrayexpress/experiments/E-MTAB-11115/, and only kept the 15 most

abundant neural subtypes for simulation. The dataset was further split into two, one to simulate

ST data and the other as the deconvolution reference. We generated ST datasets on a 50x50 grid

containing five high-density (average of four cells per occupied spot) and 10 low-density (0.4 per

occupied spot) cell types. Each cell type was assigned to a unique but overlapping doughnut-

shaped distribution pattern. Cell-type-independent spatial dependencies were introduced by

sharing 0/10%/50% of mRNA counts at each location to its first-degree neighbors (i.e. spot

bleeding). For each simulated dataset, we performed deconvolution using four sets of genes: (1)

The union of the top 20 marker genes for each cell type (n=283), (2) the union of the top 50

marker genes (n=656), (3) all discriminative informative markers genes whose log2(fold change)

is larger than 1 in one and only one cell type (n=2693), or (4) informative genes selected by the

CARD model (n=7972). This in total brings 12 scenarios, each is replicated 10 times. All

preprocessing and differential expression analysis steps were performed using the Python

package Scanpy(60).

We evaluate deconvolution performance using three metrics: (1) The mean square error and (2)

the Pearson correlation between ground truth and the estimated proportion per cell type, and (3)

the average precision score of binary prediction of whether a cell type is present at a given

location (abundance >= 0.05) using the Python package Scikit-learn(62). Results across cell

types and experiments (replicates) are aggregated together for boxplot and barplot visualizations.

Benchmark deconvolution performance using the sci-Space data of mouse embryo

We obtained the sci-Space data(63) of 14 mouse embryonic slides from GEO under the

accession number GSE166692. Each single cell in the sci-Space data is labeled with an

approximate spatial coordinate (~200 µm pitch). Cells of low-quality or from rare cell types (less

than 100 cells in any slide) were filtered out. For the remaining eight cell types, we averaged the

expression of 298 marker genes defined in the original paper to compute the deconvolution

reference. To generate ST data of the same resolution, we pooled together all cells with the same

barcode and resampled cells in each spot to adjust for the uneven density of captured cells. The

actual cell count at each location is determined by a gamma-Poisson distribution with an

expectation of 10. Since most coordinates have only one associated cell, the resampling was

executed with replacement from both the current spot and adjacent locations (with half

probability), effectively increasing the diversity at each spot. To further challenge the

deconvolution, we down-sampled the synthetic ST data to a maximum of 5,000 UMI per spot

and added multiplicative per-gene gamma noise with the mean around 0.35.

Evaluate cell-type deconvolution performance using real spatial omics datasets

Benchmark deconvolution performance using the breast tumor dataset with staining

We obtained the invasive ductal carcinoma (IDC) data(8) with DAPI and anti-CD3 staining from

10x Genomics at https://support.10xgenomics.com/spatial-gene-expression/datasets and

performed deconvolution to evaluate T-cell infiltration. The reference gene expression of nine

cell types, including one tumor epithelial type, was computed using a scRNA-seq atlas of 26

breast cancer samples(64). For Smoother-guided models, we selected the top 20 unique

differentially expressed genes for each cell type using Seurat(61) (180 genes in total) as the input

for deconvolution. For CARD, we provided the scRNA-seq data with all genes as input and run

with default parameters. Performance was first evaluated by measuring the Spearman correlation

between the CD3 immunofluorescence (IF) intensity and the T-cell deconvolution proportion

over all spots on the slide. We then investigated if these models could reliably reveal T-cell

infiltration in tumor regions (labeled as invasive carcinoma regions in the original publication), a

question of paramount importance for immunotherapy research. Specifically, we fitted a two-

component Gaussian mixture model on the CD3 intensity and predicted 377 out of the 2078

spots in the tumor regions to be T-cell positive. Results were visualized as pie charts in

Supplementary Fig. 18.

Visualize the smoothing effect on region boundaries using the 10x Visium mouse brain data

We obtained the 10x Visium dataset of mouse brain(26) and the paired snRNA-seq reference

from ArrayExpress under accession IDs E-MTAB-11114 and E-MTAB-11115. The reference

expression matrix for deconvolution was calculated for 52 neural subtypes after removing seven

unknown or low-quality cell types. For Smoother-guided methods, the union set of the top 20

marker genes for each cell type discovered by Scanpy(60) was used as the input for

deconvolution. For CARD, all QC-passed genes were supplied, and the reference matrix was

estimated by CARD. To visualize brain regions with distinct cell-type compositions, we first

built a KNN graph based on the the first 20 PCs of inferred cell-type proportions, then applied

Leiden clustering using Scanpy(60) and aligned the resulting clusters across methods via linear

sum assignment. Clustering resolution was manually adjusted for different deconvolution

methods so that the number of clusters generated per method was approximately the same.

Spatial mapping of scRNA-seq defined cell types to the spatial-CUT&Tag data of mouse embryo

We obtained the spatial-CUT&Tag data and preprocessing scripts from the original

publication(4). Specifically, the R package ArchR(65) and the 'getGeneScore_ArchR.R' script

were used to compute gene activity scores for the top 500 variable genes using the same set of

parameters. We removed spurious spots with outlier average gene activity (more than three

standard deviations away from the mean), which lined up in one column or row on the grid and

were considered as technical artifacts. The remaining spots were used in all downstream analyses.

For deconvolution, scRNA-seq data of E11 mouse embryo was obtained from Mouse

Organogenesis Cell Atlas (MOCA)(35) and processed as described in the spatial-CUT&Tag

paper. Specifically, we used the script 'integrative_data_analysis.R' to read and preprocess the

subsampled (100k cells) data and Seurat's 'FindVariableFeatures' function to identify the top

500 variable genes. We then computed the pseudo-bulk expression of variable genes for cell

types annotated in 'Main_cell_type' group and used it as the deconvolution reference. Spatial

domains of cell types were determined and visualized using the same clustering strategy

developed in the mouse brain analysis above.

Deconvolution analysis of the Stereo-seq data of mismatch repair-proficient colorectal

cancer

Re-analyze and annotate the paired scRNA-seq data

We downloaded processed Stereo-seq and paired scRNA-seq data(18) from CNGB Nucleotide

Sequence Archive under accession ID CNP0002432. The data was further processed as

described below using Scanpy. After filtering out outliers ('n_genes_by_counts >= 2500' or

'pct_counts_mt' >= 5), we first clustered the single-cell reference into eight major cell types (T

cell, B cell, mast cell, macrophage, plasma cell, epithelial cell, endothelial cell, and fibroblast)

and confirmed their identities via marker genes. To identify functional subtypes, the three most

abundant populations (T cells, plasma cells, and epithelial cells) as well as fibroblasts were

separately re-clustered after regressing out the effect of sample donor. Each subtype was

annotated according to the gene modules reported in (37). In particular, we re-discovered three

plasma cell subsets (IgG+, IgA+, and IgA+ FOS/JUN+), three epithelial subsets (ADH1C,

FOS/JUN, and TFF3), and three fibroblast subsets (CCL8, CXCL14, and Matrix), all with clear

markers. These subpopulations were either missed or misclassified in the original publication

(18), likely due to batch effects.

Deconvolute Stereo-seq tumor and normal sections of patient P19

We extracted raw counts of the bin100 (50µm × 50µm) Stereo-seq data from the tumor and the

paired distant normal tissue samples of patient P19 for separate deconvolution. For Smoother-

guided deconvolution, the reference profile was the log averaged expression of the top 50 marker

genes for the 16 subtypes (695 genes in total). For CARD, the reference was based on the same

set of genes without log-scaling the expression. The default CARD-constructed reference

contained much more genes (15025 genes in total) and yielded worse results (data not shown).

The 'DWLS (+ spatial loss)' model shown in **Figure 5** was regularized using the ICAR prior

with $\rho = 0.99$ and $\lambda_{sp} = 3$. Spatial domains of cell-type proportions were determined and

visualized using the same clustering strategy (i.e. leiden clustering after PCA transformation)

described in the mouse brain analysis above.

Differential localization of the IgG+ and IgA+ population in the tumor section

We divided spots into IgA- and IgG-specific groups based on the log ratio between 'PC_IgA'

and 'PC_IgG' proportions estimated from the 'DWLS (+ spatial loss)' model (log ratio

thresholds: >0.5 and <-0.5). For robustness, noisy proportions less than 0.01 were removed and a

pseudo-count of 0.01 was added to all spots when calculating the log ratio. We then computed

differentially expressed genes between the two groups (Wilcoxon test, p<=0.01) and further

identified enriched 'GO:BP' pathways in each region using the function 'scanpy.queries.enrich'.

For colocalization analysis, we again removed noisy proportions (<0.01) and calculated

statistical significance using the Wilcoxon test.

Joint embedding of Slide-seqV2 human prostate data and the Tabula Sapiens prostate

scRNA-seq reference using SpatialVAE

We acquired raw Slide-seqV2 count data(48) of healthy human prostate samples and the

associated annotations from https://github.com/shenglinmei/ProstateCancerAnalysis. The

pretrained reference SCVI model and the training scRNA-seq data from the Tabula Sapiens

prostate were downloaded from SCVI model hub at https://huggingface.co/scvi-tools/tabula-

sapiens-prostate-scvi. Adhering to the conventional SCVI data integration workflow, we first

fine-tuned the pretrained model on the Slide-seqV2 data with 'unfrozen=True' for 100 epochs to

mitigate batch effects. This step also updated the latent representation of the single-cell reference.

Model convergence was confirmed by inspecting the evidence lower bound (ELBO). For

spatially informed fine-tuning, we converted the SCVI model into a new SpatialVAE model with

spatial loss (ICAR, $\rho = 0.99$, $\lambda_{sp} = 0.01$). The strength λ_{sp} was selected to balance the spatial

loss and the reconstruction accuracy (measured by log likelihood). A SpatialVAE model shares

the same architecture and initial model parameters with the baseline model, which can be either

the Tabula Sapiens reference model or the RNA-only fine-tuned model. In the study, we

initialized SpatialVAE from the updated model and further fine-tuned with respect to the new

objective for another 100 epochs. This was mainly to highlight the tradeoff between

reconstruction accuracy and spatial consistency. Skipping the RNA-only fine-tuning step will not

affect the performance of the final spatial model. To transfer cell labels, we followed the SCVI

reference mapping workflow described in (66). Briefly, for each query spot we first identified

nearest neighbors in the reference, then assigned labels to the spot based on annotations of the

neighbors. The prediction uncertainty score was calculated based on the pairwise distance

between the query and its reference neighbors in the latent space. Spots with uncertainty >0.2

were labeled as 'ambiguous'.

Evaluate dimensionality reduction performance using the DLPFC dataset

All models employed expression of the top 2000 highly variable genes in each of the 12 DLPFC

samples(25) as input for dimensionality reduction. For PCA, the expression was further scaled

after log-normalization. Based on the ground truth layer annotation, we evaluated the quality of

the obtained latent representation using two metrics: embedding consistency measured by the

Silhouette score using Scikit-learn(62), and clustering accuracy measured by adjusted rank index

where we clustered spots into the observed actual number of regions (cortical layers) using the R

package 'Mclust'(67). The STAGATE model was configured with two graph attention layers of

128 and 30 units (i.e., 30 latent dimensions) and trained using default parameters. The

SpaceFlow model had two fixed graph convolutional layers. We set the hidden dimension size

'z_dim' to 30 and again trained the model using the default setting. The baseline vanilla deep

autoencoder contained two fully connected layers of dimension 128 and 30, with batch

normalization and 'ELU' as the activation function. For Smoother-guided models, we

constructed the regular spatial loss using the ICAR model and $\rho = 0.99$. To construct the

contrastive loss, we generated 20 corrupted graphs and set the relative importance of negative

samples to 0.05. When training the deep autoencoder, we also introduced an additional

orthogonal loss regularizing the latent space to prevent embedding collapse.

Declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

The python package Smoother developed in this study, tutorials, and the scripts used to simulate ST data are publicly available at https://github.com/JiayuSuPKU/Smoother/ under the BSD 3-Clause License. All additional analysis codes for reproducing results and figures presented in this study will be made available as a separate GitHub repository upon the publication of this work. Descriptions and links to all public datasets analyzed in this study can be found in the corresponding Methods sections. These include the single-nucleus RNA-seq data and the 10x Visium data of mouse brain(26) downloaded from ArrayExpress (https://www.ebi.ac.uk/arrayexpress/experiments/) under accession IDs E-MTAB-11114 and E-MTAB-11115, the sci-Space mouse embryonic data(63) downloaded from GEO at https://www.ncbi.nlm.nih.gov/geo/query/acc.cgi?acc=GSE166692, the 10x Visium invasive ductal carcinoma (IDC) data(8) with DAPI and anti-CD3 staining from 10x Genomics at https://support.10xgenomics.com/spatial-gene-expression/datasets, and the spatial-CUT&Tag mouse embryonic data(4) downloaded from GEO at https://www.ncbi.xyz/geo/query/acc.cgi?acc=GSE165217 with preprocessing scripts from Zenodo at https://zenodo.org/record/5797109#.Y9wezOyZP0p. The CRC Stereo-seq and paired

scRNA-seq data(18) were obtained from CNGB Nucleotide Sequence Archive under accession ID CNP0002432 at https://db.cngb.org/search/project/CNP0002432/. The human prostate Slide-seqV2 data (48) were obtained from https://github.com/shenglinmei/ProstateCancerAnalysis.

Competing interests

R. Rabadan is the founder of Genotwin and member of the Scientific Advisory Board of Diatech Pharmacogenetics. None of these activities are related to the results in the current manuscript.

Funding

This work was funded by the National Institutes of Health, National Cancer Institute (R35CA253126, U01CA261822, and U01CA243073 to R.R. and X.F., R37CA258829 and R21CA263381 to B.I.), the Center for Integrated Cellular Analysis (RM1HG011014 to J.S. and R.R.), and the Edward P. Evans Center for MDS at Columbia University (to J.S. and R.R.).

Authors' contributions

J.S. conceived the original idea and developed the computational framework. R.R. and D.A.K. supervised the project. J.S., J.R., X.F., G.Z., and R.S.E carried out the analysis. J.J developed the data simulation scripts. Y.W. and B.I. contributed to the analysis of MBM data and the interpretation of the results. L.A. contributed to the analysis and interpretation on human prostate cell-type prediction. J.S. took the lead in writing and revising the manuscript with input and critical feedback from all authors. All authors read and approved the final manuscript.

Acknowledgements

The authors thank Y. Choi for contributions in benchmarking, P. Sims, Y. Shen, and C. Zhang

for early discussions, and members of the Rabadan lab and Knowles lab for helpful comments

and feedback throughout the project.

Figure legends

Figure 1: Overview of the Smoother framework.

Smoother is a versatile and modular framework designed to incorporate spatial dependencies into

various omics data analysis applications. The process initiates with the construction of a

weighted spatial graph, derived from physical positions, histology, and additional features, which

serves to represent spatial dependencies a priori (top). The prior is subsequently employed as a

sparse loss function to regularize spatial variables, such as gene activities, cell-type compositions,

and latent embeddings (bottom). Owing to its modular design, the spatial loss can be appended to

pre-existing models that were initially developed for non-spatial data, potentially bridging the

gap between single-cell and spatial data analysis. The Smoother toolbox includes a selection of

spatially aware versions of non-spatial models, including NNLS, DWLS and SVR for cell-type

deconvolution, and PCA, SCVI, and SCANVI for dimensionality reduction.

Figure 2: Construction of boundary-preserving spatial priors.

(a) Schematic illustration of the process for constructing spatial weights and covariance matrices.

Smoother first builds a distance-based spatial neighborhood graph, which is subsequently pruned

using histology or other features to encode boundary information and inhibit undesired cross-

region interactions. **(b)** The impact of hard pruning on the covariance structure. Given the

regional membership annotation, hard pruning sets the weights between adjacent spots of

different regions to zero (teal, top) or a nominal value (leak=0.01, yellow, bottom), generating

distinctive correlation distributions for boundary and interior pairs of spots. **(c)** An example

section (1160920F) from the human breast cancer datasets(64). Left to right: H&E staining,

manual pathological annotation, and depiction of boundary and interior spots as defined by the

pathological regions. **(d)** Unsupervised clustering results of the same slide in **(c).** Spots were

clustered based on gene expression (left), or image-based features extracted from the H&E

staining image (right). **(e)** The distribution of pairwise feature similarities between boundary

pairs from two regions (orange) and interior pairs from the same region (blue), as defined in **(c)**

by the pathological annotation. **(f)** The distribution of pairwise correlations imposed by the

resulting spatial priors after graph pruning. Left: Soft scaling using expression- (top) and

histology-based similarities (bottom). Right: Hard pruning using cluster memberships from

expression (top) and histology (bottom) as defined in **(d)**.

Figure 3: Evaluation of spatial regularization effects on deconvolution accuracy using

simulated data.

In the first simulation, doughnut-shaped spatial transcriptomic datasets were generated from a

scRNA-seq reference(26) on a 50x50 grid. We assigned 15 cell types of high (n=5) and low

(n=10) densities to overlapping spatial compartments **(a-d)**. In the second simulation, spatial

transcriptomic datasets of the mouse embryo were generated from the sci-Space dataset(63) by

pooling single cells of eight types barcoded at the same spot (approximately 200μm pitch) **(e-h)**.

(a) Relative abundance of two typical cell types in a single replicate. **(b)** Deconvolution accuracy

of different methods as measured by Pearson correlation, with results aggregated over ten

independent replicates. Error bars denote standard errors of the mean (50 high-density and 100

low-density cell types in total). **(c)** Binary presence status (proportion >= 0.05) of two typical

cell types in a single replicate. **(d)** Deconvolution accuracy of different methods, similar to **(b)**,

but measured by binary prediction average precision score. **(e)** Relative abundance of the lateral

plate mesoderm in one sci-Space slide. **(f)** Deconvolution accuracy of different methods as

measured by Pearson correlation, with results aggregated over 14 biological slides. Error bars

denote standard errors of the mean (112 cell types in total). **(g)** Binary presence status

(proportion >= 0.05) of the myocyte in one sci-Space slide. **(d)** Deconvolution accuracy of

different methods, similar to **(f)**, but measured by binary prediction average precision score.

Smoother-guided deconvolution models: NNLS (nonnegative least square), DWLS (dampened

weighted least squares, modified implementation), SVR (support vector regression), and LNR

(log normal regression. The CARD model features its own implementation of spatial

regularization.

Figure 4: Smoother enhances cell-type deconvolution performance in various spatial omics

data.

(a-c) Detection of tumor T-cell infiltration in a 10x Visium ductal carcinoma sample(8). **(a)** Left

to right: Images showing single channel CD3 immunofluorescence staining (FITC/green), T-cell

proportions as estimated by Smoother-guided NNLS and CARD, respectively. **(b)** Spearman

correlation of predicted T-cell proportions with CD3 fluorescence levels across all spots, with

whiskers indicating the 95% confidence intervals. **(c)** Spearman correlation of predicted T-cell

proportions with the expression of T cell marker genes across all spots, similar to **(b)**.

(d-g) Spatial mapping of neurons in the 10x Visium mouse brain section ST8059048(26). **(d)**

Left: H&E staining. Right: UMAP visualization of the paired single-nucleus transcriptomic

reference of 52 neural subtypes. **(e)** Brain subregions identified by clustering based on estimated

cell-type compositions. **(f-g)** Estimated relative abundances of cortical **(f)** and hippocampal **(g)**

excitatory neurons. Color intensities are proportional to the estimated cell-type proportion and

are scaled by the same factor across methods for visualization purposes. HPC: hippocampus; DG:

dentate gyrus (CA4).

(h-k) Spatial mapping of embryonic cell types in the spatial-CUT&Tag H3K4me3 50µm data of

mouse embryo(4). **(h)** Left: Overview of the spatial-CUT&Tag technology, adapted from(4).

Right: T-SNE visualization of the scRNA-seq reference of 37 embryonic cell types(35). **(i)**

Embryonic subregions identified by clustering based on estimated cell-type compositions. **(j)**

Estimated relative abundances of five major lineages aggregated from individual cell types.

Color intensities are proportional to the estimated cell-type proportion and are scaled by the same

factor across methods for visualization purposes. **(k)** Standardized gene activity of selected

marker genes.

Figure 5: Smoother detects tumor-specific plasma cell subtypes in colorectal

adenocarcinoma Stereo-seq slide.

(a) UMAP representation of the cell types from the patient-derived paired colorectal

adenocarcinoma scRNA-seq reference (18). **(b)** Expression dotplot of the top marker genes for

each cell type in the scRNA-seq samples. **(c)** Pathology annotation of the histology slide, adapted

from(18). **(d)** Slide subregions identified by clustering based on estimated cell-type compositions.

Arrows emphasize the mucosa delineation apparent with Smoother but not CARD. **(e)** Spatial

visualizations of the cell-type proportions of the three plasma cell subtypes. **(f)** B-cell receptor

gene expression heatmap for the IgA plasma cell spots in the mucosa and the IgG plasma cell

voxels in the lesion, normalized across spots. **(g)** Colocalization of each cell type with the IgA

and IgG plasma cells. **(h)** Gene Ontology pathway enrichment analysis of the IgA plasma cell

and IgG plasma cell spots.

Figure 6: Smoother enables spatially aware joint embeddings of single-cell and Slide-seqV2

data of human prostate and improves reference mapping accuracy.

(a) Schematic overview of the spatial conversion of non-spatial auto-encoder models in the

Smoother framework. Smoother enforces spatial consistency via the detachable loss function.

This allows the same model to be trained and applied to both spatial and non-spatial data,

generating a joint spatially aware embedding. **(b)** UMAP visualization of the latent

representation of scRNA-seq data of human prostate from the Tabula Sapiens(49), colored by

tissue compartment (left) and technical batch (right). The representation was generated from a

pretrained RNA-only SCVI prostate model(47). **(c)** Violin plots showing the number of

expressed gene (left) and total RNA counts (right) per cell or spot in data of different

technologies. **(d)** UMAP visualization of the joint latent representation of the Tabula Sapiens

prostate scRNA-seq reference and the Slide-seqV2 data of a healthy prostate section(48).

Following the SCVI data integration workflow, the RNA-only model was fine-tuned on the

query spatial data with unfrozen parameters to mitigate batch effect. **(e)** Spatial visualizations of

the tissue compartment (left) and cell type prediction (right) results based on the joint RNA-only

embeddings shown in **(d)**. **(f)** UMAP visualization of the joint latent representation generated by

SpatialVAE. The spatially aware model has the same architecture as RNA-only models in **(b)**

and **(d)**, except it was fine-tuned to minimize the proposed spatial loss in addition to the original

reconstruction and KL losses. **(g)** Spatial visualizations of the tissue compartment (left) and cell-

type prediction (right) results based on the joint RNA-only embeddings shown in **(f)**.

References

1.   Moffitt JR, Lundberg E, Heyn H. The emerging landscape of spatial profiling technologies.
Nature Reviews Genetics. 2022.
2.   Stahl PL, Salmen F, Vickovic S, Lundmark A, Navarro JF, Magnusson J, et al. Visualization
and analysis of gene expression in tissue sections by spatial transcriptomics. Science.
2016;353(6294):78-82.
3.   Stickels RR, Murray E, Kumar P, Li JL, Marshall JL, Di Bella DJ, et al. Highly sensitive
spatial transcriptomics at near-cellular resolution with Slide-seqV2. Nat Biotechnol.
2021;39(3):313-9.
4.   Deng YX, Bartosovic M, Kukanja P, Zhang D, Liu Y, Su G, et al. Spatial-CUT&Tag: Spatially
resolved chromatin modification profiling at the cellular level. Science. 2022;375(6581):681-+.
5.   Deng YX, Bartosovic M, Ma S, Zhang D, Kukanja P, Xiao Y, et al. Spatial profiling of
chromatin accessibility in mouse and human tissues. Nature. 2022.
6.   Rao A, Barkley D, Franca GS, Yanai I. Exploring tissue architecture using spatial
transcriptomics. Nature. 2021;596(7871):211-20.
7.   Dries R, Zhu Q, Dong R, Eng CHL, Li HP, Liu K, et al. Giotto: a toolbox for integrative
analysis and visualization of spatial expression data. Genome Biol. 2021;22(1).
8.   Zhao E, Stone MR, Ren X, Guenthoer J, Smythe KS, Pulliam T, et al. Spatial
transcriptomics at subspot resolution with BayesSpace. Nat Biotechnol. 2021;39(11):1375-+.
9.   Ma Y, Zhou X. Spatially informed cell-type deconvolution for spatial transcriptomics. Nat
Biotechnol. 2022;40(9):1349-+.
10.   Zhang H, Hunter MV, Chou J, Quinn JF, Zhou M, White RM, et al. BayesTME: An end-to-
end method for multiscale spatial transcriptional profiling of the tissue microenvironment. Cell
Systems. 2023;14(7):605-19. e7.
11.   Hu J, Li XJ, Coleman K, Schroeder A, Ma N, Irwin DJ, et al. SpaGCN: Integrating gene
expression, spatial location and histology to identify spatial domains and spatially variable
genes by graph convolutional network. Nature Methods. 2021;18(11):1342-+.
12.   Dong KN, Zhang SH. Deciphering spatial domains from spatially resolved transcriptomics
with an adaptive graph attention auto-encoder. Nat Commun. 2022;13(1).
13.   Ren HL, Walker BL, Cang ZX, Nie Q. Identifying multicellular spatiotemporal organization
of cells with SpaceFlow. Nat Commun. 2022;13(1).
14.   Wang YG, Song B, Wang SD, Chen MY, Xie Y, Xiao GH, et al. Sprod for de-noising spatially
resolved transcriptomics data based on position and image information. Nature Methods.
2022;19(8):950-+.
15.   Bergenstrahle L, He B, Bergenstrahle J, Abalo X, Mirzazadeh R, Thrane K, et al. Super-
resolved spatial transcriptomics by deep data fusion. Nat Biotechnol. 2022;40(4):476-+.

16.   Wei XY, Fu SL, Li HB, Liu Y, Wang S, Feng WM, et al. Single-cell Stereo-seq reveals
induced progenitor cells involved in axolotl brain regeneration. Science. 2022;377(6610):1062-+.
17.   Biermann J, Melms JC, Amin AD, Wang YP, Caprio LA, Karz A, et al. Dissecting the
treatment-naive ecosystem of human melanoma brain metastasis. Cell. 2022;185(14):2591-+.
18.   Zhang R, Feng Y, Ma W, Guo Y, Luo M, Li Y, et al. Spatial transcriptome unveils a
discontinuous inflammatory pattern in proficient mismatch repair colorectal adenocarcinoma.
Fundamental Research. 2022.
19.   Rue Hv, Held L, ProQuest. Gaussian Markov random fields : theory and applications.
Boca Raton: Chapman & Hall/CRC; 2005.
20.   Sardy S, Tseng P. On the statistical analysis of smoothing by maximizing dirty Markov
random field posterior distributions. J Am Stat Assoc. 2004;99(465):191-204.
21.   Fan JQ, Li RZ. Variable selection via nonconcave penalized likelihood and its oracle
properties. J Am Stat Assoc. 2001;96(456):1348-60.
22.   Besag J, York J, Mollie A. Bayesian Image-Restoration, with 2 Applications in Spatial
Statistics. Ann I Stat Math. 1991;43(1):1-20.
23.   Wang LH, Maletic-Savatic M, Liu ZD. Region-specific denoising identifies spatial co-
expression patterns and intra-tissue heterogeneity in spatially resolved transcriptomics data.
Nat Commun. 2022;13(1).
24.   Andreatta M, Carmona SJ. UCell: Robust and scalable single-cell gene signature scoring.
Comput Struct Biotec. 2021;19:3796-8.
25.   Maynard KR, Collado-Torres L, Weber LM, Uytingco C, Barry BK, Williams SR, et al.
Transcriptome-scale spatial gene expression in the human dorsolateral prefrontal cortex. Nat
Neurosci. 2021;24(3):425-36.
26.   Kleshchevnikov V, Shmatko A, Dann E, Aivazidis A, King HW, Li T, et al. Cell2location
maps fine-grained cell types in spatial transcriptomics. Nat Biotechnol. 2022;40(5):661-+.
27.   Elosua-Bayes M, Nieto P, Mereu E, Gut I, Heyn H. SPOTlight: seeded NMF regression to
deconvolute spatial transcriptomics spots with single-cell transcriptomes. Nucleic Acids Res.
2021;49(9).
28.   Cable DM, Murray E, Zou LLS, Goeva A, Macosko EZ, Chen F, et al. Robust decomposition
of cell type mixtures in spatial transcriptomics. Nat Biotechnol. 2022;40(4):517-+.
29.   Andersson A, Bergenstrahle J, Asp M, Bergenstrahle L, Jurek A, Fernandez Navarro J, et
al. Single-cell and spatial transcriptomics enables probabilistic inference of cell type topography.
Commun Biol. 2020;3(1):565.
30.   Dong R, Yuan GC. SpatialDWLS: accurate deconvolution of spatial transcriptomic data.
Genome Biol. 2021;22(1):145.
31.   Lopez R, Li BG, Keren-Shaul H, Boyeau P, Kedmi M, Pilzer D, et al. DestVI identifies
continuums of cell types in spatial transcriptomics data. Nat Biotechnol. 2022.
32.   Newman AM, Liu CL, Green MR, Gentles AJ, Feng W, Xu Y, et al. Robust enumeration of
cell subsets from tissue expression profiles. Nat Methods. 2015;12(5):453-7.
33.   Tsoucas D, Dong R, Chen H, Zhu Q, Guo G, Yuan GC. Accurate estimation of cell-type
composition from gene expression data. Nat Commun. 2019;10(1):2975.
34.   Danaher P, Kim Y, Nelson B, Griswold M, Yang Z, Piazza E, et al. Advances in mixed cell
deconvolution enable quantification of cell types in spatial transcriptomic data. Nat Commun.
2022;13(1).

35. Cao JY, Spielmann M, Qiu XJ, Huang XF, Ibrahim DM, Hill AJ, et al. The single-cell
transcriptional landscape of mammalian organogenesis. Nature. 2019;566(7745):496-+.
36. Zou H, Hastie T. Regularization and variable selection via the elastic net (vol B 67, pg 301,
2005). J R Stat Soc B. 2005;67:768-.
37. Pelka K, Hofree M, Chen JH, Sarkizova S, Pirl JD, Jorgji V, et al. Spatially organized
multicellular immune hubs in human colorectal cancer. Cell. 2021;184(18):4734-+.
38. Harris RJ, Cheung A, Ng JCF, Laddach R, Chenoweth AM, Crescioli S, et al. Tumor-
Infiltrating B Lymphocyte Profiling Identifies IgG-Biased, Clonally Expanded Prognostic
Phenotypes in Triple-Negative Breast Cancer. Cancer Res. 2021;81(16):4290-304.
39. Gommerman JL, Rojas OL, Fritz JH. Re-thinking the functions of IgA(+) plasma cells. Gut
Microbes. 2014;5(5):652-62.
40. Xia J, Xie ZJ, Niu GM, Lu Z, Wang ZQ, Xing Y, et al. Single-cell landscape and clinical
outcomes of infiltrating B cells in colorectal cancer. Immunology. 2023;168(1):135-51.
41. Fitzerald S, O'Reilly JA, Wilson E, Joyce A, Farrell R, Kenny D, et al. Measurement of the
IgM and IgG Autoantibody Immune Responses in Human Serum has High Predictive Value for
the Presence of Colorectal Cancer. Clin Colorectal Canc. 2019;18(1):E53-E60.
42. Liu RX, Wen CY, Ye WB, Li YW, Chen JX, Zhang Q, et al. Altered B cell immunoglobulin
signature exhibits potential diagnostic values in human colorectal cancer. Iscience. 2023;26(3).
43. Xu YQ, Wei Z, Feng M, Zhu DX, Mei SL, Wu ZE, et al. Tumor-infiltrated activated B cells
suppress liver metastasis of colorectal cancers. Cell Rep. 2022;40(9).
44. Jasso GJ, Jaiswal A, Varma M, Laszewski T, Grauel A, Omar A, et al. Colon stroma
mediates an inflammation-driven fibroblastic response controlling matrix remodeling and
healing. Plos Biol. 2022;20(1).
45. Plaut E. From principal subspaces to principal components with linear autoencoders.
arXiv preprint arXiv:180410253. 2018.
46. Lopez R, Regier J, Cole MB, Jordan MI, Yosef N. Deep generative modeling for single-cell
transcriptomics. Nature Methods. 2018;15(12):1053-+.
47. Gayoso A, Lopez R, Xing G, Boyeau P, Amiri VVP, Hong J, et al. A Python library for
probabilistic analysis of single-cell omics data. Nat Biotechnol. 2022;40(2):163-6.
48. Hirz T, Mei S, Sarkar H, Kfoury Y, Wu S, Verhoeven BM, et al. Dissecting the immune
suppressive human prostate tumor microenvironment via integrated single-cell and spatial
transcriptomic analyses. Nat Commun. 2023;14(1):663.
49. Jones RC, Karkanias J, Krasnow MA, Pisco AO, Quake SR, Salzman J, et al. The Tabula
Sapiens: A multiple-organ, single-cell transcriptomic atlas of humans. Science.
2022;376(6594):711-+.
50. Luecken MD, Buttner M, Chaichoompu K, Danese A, Interlandi M, Mueller MF, et al.
Benchmarking atlas-level data integration in single-cell genomics. Nature Methods.
2022;19(1):41-+.
51. Yang L, Shami A. On hyperparameter optimization of machine learning algorithms:
Theory and practice. Neurocomputing. 2020;415:295-316.
52. Anselin L. Spatial econometrics : methods and models. 1st 1988. ed. Dordrecht,
Netherlands: Kluwer Academic Publishers; 1988.
53. van Erp S, Oberski DL, Mulder J. Shrinkage priors for Bayesian penalized regression. J
Math Psychol. 2019;89:31-50.

54.   Palla G, Spitzer H, Klein M, Fischer D, Schaar AC, Kuemmerle LB, et al. Squidpy: a scalable
framework for spatial omics analysis. Nature Methods. 2022;19(2):171-+.
55.   Lee DD, Seung HS. Algorithms for non-negative matrix factorization. Adv Neur In.
2001;13:556-62.
56.   Comon P. Independent Component Analysis, a New Concept. Signal Process.
1994;36(3):287-314.
57.   Paszke A, Gross S, Massa F, Lerer A, Bradbury J, Chanan G, et al. PyTorch: An Imperative
Style, High-Performance Deep Learning Library. Advances in Neural Information Processing
Systems 32 (Nips 2019). 2019;32.
58.   Diamond S, Boyd S. CVXPY: A Python-Embedded Modeling Language for Convex
Optimization. J Mach Learn Res. 2016;17.
59.   Yuan ZY, Pan WT, Zhao X, Zhao FY, Xu ZM, Li X, et al. SODB facilitates comprehensive
exploration of spatial omics data. Nature Methods. 2023;20(3):387-+.
60.   Wolf FA, Angerer P, Theis FJ. SCANPY: large-scale single-cell gene expression data
analysis. Genome Biol. 2018;19.
61.   Hao YH, Hao S, Andersen-Nissen E, Mauck WM, Zheng SW, Butler A, et al. Integrated
analysis of multimodal single-cell data. Cell. 2021;184(13):3573-+.
62.   Pedregosa F, Varoquaux G, Gramfort A, Michel V, Thirion B, Grisel O, et al. Scikit-learn:
Machine Learning in Python. J Mach Learn Res. 2011;12:2825-30.
63.   Srivatsan SR, Regier MC, Barkan E, Franks JM, Packer JS, Grosjean P, et al. Embryo-scale,
single-cell spatial transcriptomics. Science. 2021;373(6550):111-+.
64.   Wu SZ, Al-Eryani G, Roden DL, Junankar S, Harvey K, Andersson A, et al. A single-cell and
spatially resolved atlas of human breast cancers. Nat Genet. 2021;53(9):1334-47.
65.   Granja JM, Corces MR, Pierce SE, Bagdatli ST, Choudhry H, Chang HWY, et al. ArchR is a
scalable software package for integrative single-cell chromatin accessibility analysis (vol 53, pg
403, 2021). Nat Genet. 2021;53(6):935-.
66.   Sikkema L, Strobl DC, Zappia L, Madissoon E, Markov NS, Zaragosi L-E, et al. An
integrated cell atlas of the human lung in health and disease. bioRxiv. 2022:2022.03. 10.483747.
67.   Scrucca L, Fop M, Murphy TB, Raftery AE. mclust 5: clustering, classification and density
estimation using Gaussian finite mixture models. The R journal. 2016;8(1):289.
1021

Figure 1

Figure 2

a

x, y

Histology   Spatial-omics

Spot | Spatial Location

Boundary detection   Graph pruning

Soft

Hard

Spot | Spatial Weights

Spot | Spatial Weights

Choose covariance decay rate

Spot | Spatial Covariance

b

Between two regions   Within each region

Frequency

Pairwise correlation

Raw   Hard pruning   Hard pruning (leak=0.01)

c

H&E staining   Pathological annotation   Region boundary

Region
- Adipose tissue
- Artefact
- Cancer trapped in lymphocyte aggregation
- DCIS
- Invasive cancer + stroma + lymphocytes
- Lymphocytes
- Normal glands + lymphocytes
- Stroma

- Interior
- Boundary

d

Expression-based clusters   Histology-based clusters

e

Expression-based similarity between two regions

Expression-based similarity within each region

Histology-based similarity between two regions

Histology-based similarity within each region

Frequency

Pairwise similarity

f

(Scaled by expression)

Between two regions   Within each region

(Scaled by histology)

Between two regions   Within each region

Frequency

(Scaled by expression)

Between two regions   Within each region

(Scaled by histology)

Between two regions   Within each region

Pairwise correlation

Pruning
- Raw
- Soft (expr)
- Soft (hist)
- Hard (expr)
- Hard (hist)

Figure 3

Figure 4

a

CD3 staining — Intensity

NNLS (+ spatial loss) — Inferred T cell proportion

CARD (phi=0.99) — Inferred T cell proportion

b T cell proportion vs CD3 staining

Spearman R

Model: NNLS, DWLS, SVR, CARD

Spatial loss: False (●), True (▲)

c Expression vs CD3 staining

Spearman R

CD3E, CD3D, CD3G, CD4, CD8A, CD8B, CD8B2

d

e DWLS (-) | DWLS (+ spatial loss) | CARD (phi=0) | CARD (phi=0.99)

f DWLS (-) | DWLS (+) | CARD (phi=0) | CARD (phi=0.99)

Cell type: ● Ext_L23 ● Ext_L25 ● Ext_L5 ● Ext_L56 ● Ext_L6

g DWLS (-) | DWLS (+) | CARD (phi=0) | CARD (phi=0.99)

Cell type: ● Ext_Hpc_CA1 ● Ext_Hpc_CA2 ● Ext_Hpc_CA3 ● Ext_Hpc_DG ● Inh_6

h

i NNLS (-) | NNLS (+ spatial loss) | CARD (phi=0) | CARD (phi=0.99)

j NNLS (-) | NNLS (+) | CARD (phi=0) | CARD (phi=0.99)

Lineage: ● Cardiac muscle ● Chondrocytes & osteoblasts & mesenchyme ● Erythroids ● Glial lineage ● Neurons & neural tube

k Ascl1 | Hand2 | Lmo2 | Sox9

Gene activity (Z-score) -3.0 to 3.0

Figure 5

Figure 6

a

Spots/cells

Features

Regularization

Encoder

Latent representations

Regularization

Decoder

Inferred features

Coordinates → Spatial covariance → Cov L3 = SpatialLoss(⬜ , C)

Pretrain Loss = L1 + L2 Fine-tune Loss = L1 + L2 + L3

L1 = Reconstruction(🟩 , 🟩)

L2 = Regularization(R)

Non-spatial data   Spatial data

scRNA-seq atlas → RNA-only embeddings
ST data → ST-only embeddings
scRNA-seq atlas → RNA-only embeddings
ST data → SpatialLoss(⬜ , C) → Spatially-aware joint embeddings

b Pretrained Tabula-Sapiens-Prostate-SCVI

Compartment
● Endothelial
● Epithelial
● Germ line
● Immune
● Stromal

Platform
● TSP8_10x 3' v3
● TSP8_Smart-seq2
● TSP14_10x 3' v3

c

Number of genes: 3000, 1000, 300, 100, 30

Total counts: 1e7, 1e5, 1e3

Platform
■ TSP8_10x 3' v3
■ TSP8_Smart-seq2
■ TSP14_10x 3' v3
■ HP1_Slide-seqV2

d RNA-only fine-tuning on ST data

Compartment
● Endothelial
● Epithelial
● Germ line
● Immune
● Stromal
● NA (ST)

Platform
● TSP8_10x 3' v3
● TSP8_Smart-seq2
● TSP14_10x 3' v3
● HP1_Slide-seqV2

e

Cell type prediction
● CD8+, alpha-beta T cell
● Club cell
● Endothelial cell
● Epithelial cell
● Epithelium basal cell
● Epithelium luminal cell
● Erythroid progenitor cell
● Fibroblast
● Macrophage
● Mature NK T cell
● Monocyte
● Myeloid cell
● Smooth muscle cell
● T cell
● Ambiguous

Compartment prediction
● Endothelial ● Epithelial ● Immune
● Stromal ● Ambiguous

f Spatial fine-tuning with spatial loss

Compartment
● Endothelial
● Epithelial
● Germ line
● Immune
● Stromal
● NA (ST)

Platform
● TSP8_10x 3' v3
● TSP8_Smart-seq2
● TSP14_10x 3' v3
● HP1_Slide-seqV2

g