Representational similarity learning reveals a graded multidimensional semantic space

in the human anterior temporal cortex

Christopher R. Cox[1※*], Timothy T. Rogers[2※*], Akihiro Shimotake[3*], Takayuki Kikuchi[4],

Takeharu Kunieda[4,5], Susumu Miyamoto[4], Ryosuke Takahashi[3], Riki Matsumoto[7*],

Akio Ikeda[6†,] Matthew A. Lambon Ralph[8†*]

※ Co-first author; † Co-senior author; * Corresponding author

Affiliations:

1. Dept. of Psychology, Louisiana State University, Audubon Hall, Baton Rouge, LA
70803
2. Dept. of Psychology, University of Wisconsin, Brogden Hall, Madison, WI 53706
3. Dept. of Neurology. Kyoto University Graduate School of Medicine, Kawaharacho,
Shogoin, Sakyo-ku, Kyoto, 606-8507, Japan
4. Dept. of Neurosurgery, Kyoto University Graduate School of Medicine, Kyoto, Japan
5. Dept. of Neurosurgery, Ehime University Graduate School of Medicine, Shizukawa
Toon city, Ehime, 791-0295, Japan
6. Dept. of Epilepsy, Movement Disorders and Physiology, Kyoto University Graduate
School of Medicine, Kyoto, Japan
7. Div. of Neurology, Kobe University Graduate School of Medicine, Kusunoki-cho,
Chuo-ku, Kobe, 650-0017, Japan
8. MRC Cognition and Brain Sciences Unit, 15 Chaucer Rd., Cambridge, UK, CB2-7EF

Corresponding Authors:

• Christopher R. Cox (chriscox@lsu.edu) 0000-0001-8287-3865
• Timothy T. Rogers (ttrogers@wisc.edu) 0000-0001-6304-755X
• Akihiro Shimotake (smtk@kuhp.kyoto-u.ac.jp) 0000-0003-3777-685X
• Riki Matsumoto (matsumot@med.kobe-u.ac.jp) 0000-0003-3985-9210
• Matt Lambon Ralph (Matt.Lambon-Ralph@mrc-cbu.cam.ac.uk) 0000-0001-5907-
2488

Keywords: Semantic memory, ECoG, temporal lobe, decoding, representational

similarity analysis, RSA, representational similarity learning, RSL

33   **Abstract**

Neurocognitive models of semantic memory have proposed that the ventral anterior

temporal lobes (vATLs) encode a graded and multidimensional semantic space—yet

neuroimaging studies seeking brain regions that encode semantic structure rarely

identify these areas. In simulations we show that this discrepancy may arise from a

crucial mismatch between theory and analysis approach. Utilizing an analysis recently

formulated to investigate graded multidimensional representations, *representational*

similarity learning (RSL), we decoded semantic structure from ECoG data collected

from the vATL cortical surface while participants named line drawings of common items.

The results reveal a graded, multidimensional semantic space encoded in neural activity

across the vATL, which evolves over time and simultaneously expresses both broad

and finer-grained semantic structure amongst animate and inanimate concepts. The

work resolves the apparent discrepancy within the semantic cognition literature and,

more importantly, suggests a new approach to discovering representational structure in

neural data more generally.

48   **Conflict of interest**

49 The Department of Epilepsy, Movement Disorders, and Physiology, Kyoto University

50 Graduate School of Medicine conducts Industry-Academia Collaboration Courses,

51 supported by Eisai Co., Ltd, Nihon Kohden Corporation, Otsuka Pharmaceutical Co.,

52 and UCB Japan Co., Ltd.

54   **Introduction**

If you encounter a wolf when walking home through a dark wood, your mind

readily accomplishes some remarkable feats: it anticipates the animal's likely behavior,

perhaps slinking closer toward you; it assigns the thing a name, which you might shout

to alert others ("wolf!"); and it directs you to change your own plans, maybe running

back down the path. These feats arise from the human ability to discern conceptual

structure—to realize that the wolf, despite its resemblance to friendly dogs in town, is

nevertheless a quite different sort of animal.

This ability to represent and exploit conceptual structure is central to human

semantic cognition. Such structure is *graded* in that similarities vary along a continuum:

wolves are highly similar to coyotes, partially similar to elk, and quite distinct from birch

trees or canoes. It is also *multidimensional* in that concepts vary along a myriad of

independent components: wolves and dogs are similar in their shapes, parts,

movements, and phylogeny, but different in their behaviors, habitats, and diets. To

capture these properties of knowledge, computational approaches to semantics often

represent concepts with *vector spaces*: the meaning of a word or image is expressed as

a point in an *n*-dimensional space (or equivalently as an *n*-dimensional vector) such that

the proximity between points expresses the similarity in meaning between the denoted

concepts. The dimensions of the vector need not correspond to nameable conceptual

components like *habitat* or *diet*; instead they may define a space, with different concepts

corresponding to different points in the space, and with the distances between points

capturing the degree of semantic/conceptual relatedness between concepts (Frisby et

al., 2023). Cognitive science and machine-learning offer many techniques for estimating

semantic vector spaces from natural language (Pereira et al., 2016), feature norms

(McRae et al., 2005), or similarity-judgments (Hebart et al., 2020), and these methods

have provided a critical empirical foundation for studying human conceptual knowledge.

The well-known "hub and spokes" theory of semantic representation suggests

that the anterior temporal lobes (ATLs) encode a graded, multidimensional semantic

vector space that expresses conceptual similarity structure for all concepts, extracted

across all input and output modalities, and from our experiences of each concept across

time (Jackson et al., 2021; Lambon Ralph et al., 2017; Patterson et al., 2007). This

proposal has been useful for understanding patterns of semantic deficits arising from

temporal lobe pathology in fronto-temporal dementia (Acosta-Cabronero et al., 2011;

Hodges & Patterson, 2007; Lambon Ralph, 2014; Lambon Ralph et al., 2010; Rogers et

al., 2004; Snowden et al., 1989), anterior temporal resection (Drane et al., 2008;

Lambon Ralph et al., 2010; Lambon Ralph et al., 2012; Rice et al., 2018; Schapiro et

al., 2013), and herpes viral encephalitis (Gainotti, 2018; Lambon Ralph et al., 2007;

Noppeney et al., 2007); stimulation and evoked response direct neurophysiological

explorations (Abel et al., 2015; Y. Chen et al., 2016; Shimotake et al., 2015); the effects

of transcranial magnetic stimulation in ATL and other parts of the cortical semantic

system (Binney et al., 2010; Binney & Lambon Ralph, 2015; Jefferies, 2013; Lambon

Ralph et al., 2009; Pobric et al., 2007, 2010); and a variety of behavioral phenomena in

developing and mature cognition (Chen et al., 2017; Jackson et al., 2021; Rogers &

McClelland, 2004, 2014).

Yet direct empirical tests of this proposal—representational similarity analysis

(RSA) of functional imaging data collected while people perform semantic tasks on

words or pictures—have not generally tended to support it. A recent review identifies 24

studies applying RSA to uncover semantic representations in the brain (Frisby et al.,

2023); of these, 18 (75%) failed to identify semantic structure in the anterior temporal

cortex (for the exceptions, see Bruffaerts et al., 2013; Devereux et al., 2018; Fairhall &

Caramazza, 2013; Martin et al., 2018; Peelen & Caramazza, 2012). Many of these

studies instead find that semantic structure is encoded in brain areas not otherwise

thought to be critical to semantic representation, including posterior cortical regions

(Connolly et al., 2012), inferior and superior frontal and motor cortex (Carota et al.,

2017; Wang et al., 2017), the left pars triangularis (Liuzzi et al., 2017), right superior

parietal cortex (Wang et al., 2017), the insula and occipeto-parietal cortex (Kivisaari et

al., 2019), and the posterior cingulate cortex (Fairhall & Caramazza, 2013). Thus RSA

studies often yield results that seem puzzling given the broader literature, finding that

semantic structure is encoded in many areas throughout cortex but not in the ATL.

113   The frequent failure of RSA to find semantic structure in ATL may reflect

limitations of fMRI, which, without specialized acquisition protocols, can yield poor

signal in ventral aspects of this brain area (Halai et al., 2015; Halai et al., 2014). An

important study by (Y. Chen et al., 2016) suggests, however, that this is not the full

story. The authors collected intracranial grid electrode voltages (ECoG) from the surface

of ventral anterior temporal lobes (vATL) while participants named line drawings of

familiar items, then conducted a searchlight-based semantic RSA from these data.

Consistent with the semantic-hub model, they found an anterior fusiform area where

similarities in the evoked neural response correlated significantly with the target

semantic similarities. Critically, however, they further showed that the evoked neural

similarities correlated *equally well* with a binary target matrix that only encoded whether

a stimulus was animate or inanimate. This result is consistent with an alternative view

that, while ECoG in vATL may express a coarse binary animacy distinction, it does *not*

otherwise encode graded or multidimensional semantic structure within or between

these domains. ECoG is not affected by the magnetic field inhomogeneities that affect

fMRI in vATL, so the finding is not easily attributable to poor signal or other data

artifacts.

Motivated by these observations, this paper considers an alternative hypothesis

about the discrepant findings for RSA versus the broader literature: that it arises

because RSA, as typically practiced, is not well-suited to finding <u>*graded*</u>

<u>*multidimensional*</u> vector spaces of the kind the ATL is hypothesized to encode. This

may seem surprising, since RSA was developed specifically as a tool for finding

cognitive similarity structure in neuroimaging data (Kriegeskorte, Mur, & Bandettini,

2008)—yet, as we will demonstrate, the reliance of the approach on correlation

significantly limits the kinds of signal it can detect.

Study 1 considers how RSA constrains what can be discovered about neuro-

semantic representations, by applying the approach to simulated data where the target

signals are designed to encode elements of structure in a true semantic similarity matrix

derived from feature-listing data. The results illustrate how and why RSA can both miss

real signal and produce positive results with the potential to mislead. Study 2 then

introduces a different approach to neural decoding, *representational similarity learning*

(RSL; Oswal et al., 2016), that can remediate these issues by making explicit which

aspects of the target structure can be successfully decoded, and by operationalizing

hypotheses about the neurosemantic code directly within the decoding model. Study 3

extends the RSL approach to the analysis of very large neural datasets and applies it to

investigate graded multidimensional semantic structure in ECoG data recorded from the

surface of human vATL—the same data for which RSA data failed to detect graded,

multidimensional and cross-domain semantic structure in a prior study (Y. Chen et al.,

2016). We empirically compare results yielded by RSL vs. RSA on these data, with

results that resolve the contradiction in the literature and suggest a new path for

multivariate neural decoding more generally.

154   **Simulation study 1: Evaluating RSA.**

155   Simulation 1 evaluated whether the results yielded by RSA reliably indicate

whether a set of neural measurements encode graded, multidimensional semantic

similarity structure of the kind typically sought in functional imaging studies. By *graded*,

we mean that the measurements encode varying and continuous degrees of similarity

between items, rather than discrete or categorical distinctions between items. By

multidimensional, we mean that the measurements encode variation along more than

one orthogonal component of a representational space. Though the general approach is

well known, its limitations may be less familiar, so we begin with a brief overview of the

method and some of the challenges it faces when seeking graded, multivariate

structure.

165   RSA aims to find sets of neural features—voxels, electrodes, or other

measurements of neuro-physiological activity—whose responses to various cognitive

events (e.g., the perception of a stimulus) jointly encode an independently-measured

target structure. Typically, the target structure is a *representational similarity matrix*

(RSM; sometimes called a representational dissimilarity matrix or RDM) in which the

rows and columns correspond to the different stimuli in an experiment and the entries

indicate the cognitive/representational similarities between stimuli. For semantic

representation, entries in the target RSM indicate similarity of meaning amongst pairs of

concepts as estimated from behavioral or corpus data. To determine if responses in a

set of neural features (e.g., voxels, electrodes, EEG sources, etc.) encode the target

similarities, the experimenter estimates the pattern of neural activity evoked over

features by each stimulus and computes the pairwise similarities between these to

create a *neural similarity matrix* (NSM). Correlations between the RSM and NSM are

computed separately for each participant, and brain regions where these are reliably

greater than zero are interpreted as encoding the target structure.

This approach faces at least five challenges when used to find *graded*,

multidimensional structure in neural codes:

1. *Discrete vs graded structure*: reliable correlations with a continuous-valued

183   target RSM can arise even if the neural response is discrete or categorical.

184   Thus, a positive result does not indicate that the neural response encodes

185   *graded* structure even if such structure is present in the target RSM.

186   2. *Unidimensionality*: the correlation between RSM and NSM is inherently

187   unidimensional. Thus, a positive result on its own does not provide evidence

188   of multidimensional structure in the neural response.

189   3. *A priori feature selection*: the experimenter must decide ahead of time which

190   neural measurements to use when computing the NSM (e.g. an ROI or a

191   searchlight). If the informative features fall across different ROIs or

searchlights or are intermixed with many non-informative features within an

ROI/searchlight, the approach can fail to discover them.

4. *Equal importance*: all selected neural features are equally weighted when

computing the NSM. If the informative neural features are sparse or vary in

signal strength, equal weighting of all features may lead to a null result. Thus,

a null result does not indicate that the selected neural features carry no target

information.

5. *Masked dimensionality*: reliable correlations between RSM and NSM can be

driven by a subset of the RSM structure or items, or even by one or two

extreme values. Thus, a positive result does not imply that all components of

the target RSM are encoded.

Simulation 1 assessed how these characteristics of RSA will influence discovery

of neuro-semantic representations by applying the approach to synthetic data designed

to encode different aspects of a real semantic similarity matrix.

Methods

The target RSM was computed from semantic feature norms for 100 items, half

animate and half inanimate, collected in prior work (Dilkina & Lambon Ralph, 2013). The

feature vectors for each item were aggregated in a matrix with rows indicating words,

columns indicating features, and binary entries indicating whether the referent of the

word possesses that feature. Matrix columns were mean-centered and the RSM was

computed as the cosine similarity for all pairs of row vectors.

To understand the latent structure of the RSM, we used singular value

decomposition (SVD) to extract three components accounting for 90% of the variance in

the full matrix (81.1%, 4.4%, 4.0%, respectively). SVD is a common matrix

decomposition algorithm that reduces a matrix to a small number of orthogonal

components ordered by the proportion of variance they explain. After applying it to the

RSM, each of the 100 items in the set receives a coordinate position along the three

orthogonal components.

Figure 1 shows the coordinates for all 100 items on each latent dimension, color

coded by semantic category (see Appendix A for full list of items and how they were

categorized). The decomposition reveals graded semantic structure along each

dimension. The first separates animate from inanimate items but also individuates

subcategories in each domain. The second strongly differentiates subcategories of

animals but also weakly distinguishes inanimate subcategories. The third differentiates

the inanimate items, though the resulting spread is less "clumpy" than within animate

items as commonly found with such data (Lambon Ralph et al., 2007). From the SVD it

is clear that the semantic vector space is both multidimensional and graded by the

definitions offered earlier.

Figure 1. Coordinates of the 100 stimuli in the three-dimensional singular-value-decomposition of the semantic similarity matrix. Colors show category membership within each domain. Component 1 separates animate from inanimate items, but also separates animate sub-categories. Component 2 largely separates animate sub-categories, while component 3 largely separates inanimate sub-categories.

The simulation assessed what results RSA would yield when applied to a set of

signals designed to encode elements of this underlying semantic structure, when those

signals are perturbed by noise and embedded in a population together with other

signals that do not code semantic information (as in brain imaging data). Specifically,

we created five simulated datasets, each capturing a different aspect of semantic

structure in the target RSM. Each dataset contained simulated responses of 24 features

to the 100 items, as a simple model analog of the responses of, for instance, voxels

within an ROI. To capture the fact that a given ROI may contain both signal-carrying

and uninformative voxels, half of the features encoded true semantic information about

the target items while half adopted random values sampled from a uniform distribution

in the same range.

The five datasets varied in which aspects of the target matrix they encoded, as

illustrated in the schematic plots in **Figure 2A.** In the *binary condition*, all signal-carrying

features adopted one state (-1 or 1) for animate items and the opposite state for

inanimate items—thus the code was both unidimensional and discrete (i.e., non-

graded). In three *one-D conditions*, all signal-carrying features only encoded a single

latent component of the target RSM—either the first, second, or third singular vector as

shown in **Figure 1**. Thus, each encoded *graded* similarity structure (the distances

between items were continuous, not binary/discrete) but only *one* dimension of

variation. In the *full structure condition,* the signal-carrying features jointly encoded all

three latent components of variation in the target RMS, with four features dedicated to

each of the three components. Thus, the code was both graded and multidimensional.

For each signal condition, we distorted the response of each feature to each

stimulus with measurement noise sampled independently from a uniform distribution

centered on 0, generated a simulated NSM, then computed the correlation between the

simulated NSM and target semantic RSM. The varying levels of noise allowed us to

investigate RSA behavior across a wide range of signal-to-noise ratios. This procedure

was conducted 20 times at each of 11 increasing noise levels. We then computed,

across runs at each noise level, the mean and 95% confidence intervals of the Pearson

correlation between simulated NSM and RSM.

Figure 2. Simulation results. A. Each plot illustrates different ways that a neural response might encode some aspects of a target RSM, schematized in the rightmost plot ("All"). Vertical bars show the hypothesized responses of neural features to various animate and inanimate stimuli (red more active; blue less active; gray random) while the squares show the neural similarity matrices that would then result (red high similarity, blue low). All conditions encode some components of the full RSM and so should be detected by a multivariate method seeking semantic structure. B. Curves showing the expected results of standard RSA when used to decode real semantic structure from the target RSM under different hypotheses about the neural code and increasing amounts of measurement noise. Dots show the mean correlation while ribbons show the 95% confidence interval. The approach can yield robust results when the neural signal is discrete and/or unidimensional, even under substantial noise, and can yield weak or null results when the neural signal faithfully encodes weaker components of the RSM, even under low-noise conditions. C. Results of RSL applied to the same simulated data, showing the correlation between true and predicted coordinates for held-out items on each latent component of the target matrix (columns) at the same 11 levels of noise as in the RSA, for the five different simulation conditions (rows), and computed across all items (black lines), animate items (red), or inanimate items (green). RSL shows a positive result in each case, identifies which components of the matrix are present in the neural code, and reveals reliable within-domain decoding only when the neural code expresses continuous similarity structure.

Results

The results are shown in **Figure 2B.** The binary code showed robust correlations

across the full noise-spectrum, illustrating that RSA with a graded and multidimensional

target RSM can yield a positive result even when the neural code is neither continuous

nor multidimensional. Amongst the one-D codes, RSA showed a strong positive result if

the simulated neural response encoded the first singular vector of the target matrix, but

much weaker results that decayed to zero with increasing noise when the neural

response encoded other components. The weak results for components 2 and 3 arise

simply because the raw similarities encoded in the target RSM are most strongly

determined by the first component. Simulated NSMs that encode just the second or

third component thus express similarities that do not correlate strongly with the pairwise

similarities encoded in the target matrix. Thus, RSA can yield weak/null results even

when the features under consideration *do* reliably encode semantic information that is

orthogonal to the primary component of the RSM. Throughout the noise range

assessed, RSA yielded the most reliable results when the simulated features encoded a

binary domain distinction or just the first component of variation. For these scenarios, all

signal-carrying features encode the same information, so noise "cancels out" across

features and the signal remains robust. When the same number of features encode

three orthogonal components, fewer resources are dedicated to each, and corruption

from noise more seriously degrades the signal—so that, counter-intuitively, the

approach yielded less reliable results when the simulated features encode all three

dimensions of the target matrix.

Discussion

The simulation shows that, when decoding semantic similarity structure of the

kind captured by semantic feature norms, RSA can yield a positive result when the

neural response is discrete and/or unidimensional, *even* though the target matrix is

continuous and multidimensional. Additionally, it can yield weak or null results when the

neural response *does* encode underlying dimensions of the target matrix beyond the

strongest. Thus, the simulation serves as a demonstration that RSA, as typically

deployed, may not reliably indicate whether a set of neural signals encode the graded,

multidimensional semantic structure existing in a target RSM. Of course, the specific

pattern of results obtained will depend upon the ratio of informative to uninformative

features within the selected set and the amount of noise perturbing the signal, in

addition to the structure encoded by the informative features.

One response to these challenges may be to consider the degree of correlation

between a given NSM and multiple different RSMs, each encoding a different kind of

structure. Yet simulation 1 suggests that this approach remains limited. Recall that Y.

Chen et al. (2016) found that an ECoG-based NSM correlated equally well with an

animacy-based binary similarity matrix as with a full continuous and multidimensional

matrix. The rationale for the comparison was the expectation that, if the NSM encodes

the full similarity structure, it should show a higher correlation with the target semantic

matrix than with the binary matrix. Figure 1B shows that this is not necessarily so—in

fact the binary code showed as good or better correlation with the target semantic

matrix than did the full (continuous, multidimensional) code. Thus, the comparison of fits

with the two different target matrices did not help to resolve the nature of the underlying

neural code.

Or, consider the interesting findings of Clarke and Tyler (2014), who used RSA to

seek areas encoding semantic structure both across and within superordinate domains

(such as "animals" and "vehicles"). When the target matrix included all items from all

domains, the analysis identified the vATL as encoding semantic structure. When limited

only to items within one semantic domain, however, the vATL did not appear to encode

such structure. The finding could mean that vATL only encodes discrete distinctions

between superordinate semantic domains, analogous to the binary condition in the

simulation—but the same result could also obtain even if the vATL does encode within-

domain structure, since such structure is mainly encoded, within the semantic target

matrix, by components orthogonal to the primary dimension.

316   More sophisticated use of RSA may overcome some of these difficulties in

interpretation; for instance, the researcher might carefully select stimulus items to

ensure that multiple orthogonal components of a representational space are equally

strongly expressed in the RSM, or to ensure that different target representational

spaces are maximally differentiated by the selected stimulus items. Indeed, one of the

few RSA studies to report semantic representational structure in ATL adopted this

approach, ensuring that semantic and visual similarity structure were completely

deconfounded in their stimuli and then comparing results for these two differently-

structure target matrices (Martin et al., 2018). While such studies are elegant and

informative, they are also challenging to design and may prevent researchers from

exploring fuller or more naturalistic distributions of stimuli. For these reasons, we were

motivated to consider an alternative approach to discovery of graded multidimensional

representations in neural data.

329   **Simulation study 2: Decoding with RSL.**

330   The approach we developed is called *representational similarity learning* (RSL;

Oswal et al., 2016). Rather than using pairwise similarities in the RSM as the target

values for correlation, RSL first decomposes the matrix into orthogonal latent

components, effectively re-representing each stimulus item as a point in a low-

dimensional semantic space as shown in **Figure 1**. It then uses linear regression to fit

decoding models that predict the coordinates of each item along each dimension from

their evoked neural responses. Simulation 2 assessed whether this approach can reveal

the graded and/or multidimensional structure obscured by RSA.

Methods

Using the same simulated neural signals from Simulation 1 as predictors, we fit

ordinary least-squares (OLS) regression models to predict coordinates of each stimulus

along each of the three latent semantic dimensions shown in **Figure 1**. For each

simulated feature set and each of 11 increasing levels of uniformly distributed noise

(i.e., the same noise manipulation as for Simulation 1), each example was assigned to

one of ten mutually exclusive test sets such that each test set had 5 animate and 5

inanimate items. Holding out each test set in turn, regression models were fit to the

remaining 90% of the examples (the training set). The model that was fit to the training

set predicts coordinates for the 10% of examples withheld as the test set. After iterating

over the ten test sets, a hold-out prediction exists for every item. These were

concatenated and correlated with the target embedding one dimension at a time. This

process was repeated 20 times with different samples of noise. Hold-out accuracy for

each condition and noise level was estimated as the mean over simulation repetitions.

Multidimensional structure in the neural code should be revealed by reliable

prediction of coordinates along more the one latent dimension. To assess whether the

neural code captures graded similarity, we evaluated how well the fitted model predicted

coordinates amongst just the animate items or just the inanimate items. If the neural

signal only categorically differentiates animate from inanimate stimuli, then predicted

and true values should correlate significantly when models are evaluated on all items

but should *not* correlate amongst just the animate or just the inanimate items

considered separately. Reliable intra- and inter-domain correlations between true and

predicted values thus indicate that the neural code captures a graded degree of

similarity structure.

Results

363   **Figure 2C** shows the mean correlation between true and predicted coordinates

for held-out items on each of the three target components (columns), for the five

different neural coding scenarios (rows), and computed across all items (black lines),

animate items (red), or inanimate items (green). The pattern of results reveals the

information encoded in each simulated neural response. With the binary neural signal

(top row), predicted and true coordinates correlated strongly for models fit to all items

but not separately for animates vs. inanimates. With continuous one-D signals, strong

correlations were observed for models fit to all items and within each domain

separately, but only for the dimension encoded by the neural response. When the

neural signal encoded graded multidimensional structure, reliable correlations were

observed on all three latent components, for models fit to all items and fit separately to

each domain. Thus, in simulation, the pattern of results uniquely revealed whether the

neural signal encodes graded or discrete structure, and which semantic dimensions it

captures.

Discussion

In contrast to the RSA simulation, RSL yielded a different, diagnostic pattern of

results for each condition, indicating which aspects of the semantic target matrix were

encoded within the simulated neural responses. The discreteness of the binary code

was revealed by reliable prediction across domains and no reliable prediction within

domain. In the 1D neural-structure conditions, RSL showed reliable prediction only on

the latent dimensions encoded by the simulated neural signal, and not on the other

dimensions. Reliable decoding both within and between domains in such conditions

indicated, in contrast to the binary condition, that the signal is graded rather than

discrete. When the simulated neural signal encoded all three semantic dimensions, RSL

showed reliable decoding of each. Thus, by considering decoding accuracy on

orthogonal components of the target matrix, RSL can test whether the neural code

expresses multidimensional structure; and by considering decoding accuracy separately

for different semantic domains, it can test whether the code is graded.

Study 3: Decoding semantic structure from ECoG using RSL

Study 3 evaluated whether neural signals in vATL encode a graded,

multidimensional and domain-general semantic space by using RSL to decode

semantic structure in ECoG data collected in a prior study of object naming (which

employed the same 100 items used in the simulations; Y. Chen et al., 2016). This

dataset is especially useful in the current context for two reasons.

First, ECoG avoids some of the limitations of non-invasive imaging methods that

can make structure in vATL difficult to decode. One recent study suggested that the

neuro-semantic code for animacy in vATL changes rapidly and nonlinearly over the

course of stimulus processing so that techniques sacrificing either spatial or temporal

resolution, including EEG, MEG, and fMRI, may obscure important signal (Rogers et al.,

2021). Additionally, magnetic field inhomogeneities make it difficult to resolve clear

BOLD signal in vATL without special acquisition sequences (Halai et al., 2015; Halai et

al., 2014). ECoG provides much better spatial and temporal resolution of

neurophysiological signals at the surface of cortex and does not suffer from the signal-

detection issues that challenge fMRI, so any failure to discover fine-grained /

multivariate semantic structure in the data cannot reflect these limitations.

Second, the results of the original RSA study (Y. Chen et al., 2016) suggest that

the measured signals, though reliably differentiating animate from inanimate items, do

not encode finer grained or multidimensional semantic structure. Specifically, the

authors compared the correlation of the stimulus evoked NSM to two different target

matrices: one encoding the full graded and multidimensional semantic similarities

amongst stimuli, and a second encoding just the binary distinction between animate vs

inanimate items. If the vATLs encode graded multidimensional semantic structure, one

might expect the NSM to correlate more strongly with the full target matrix than with the

binary animacy matrix. Instead, the authors found statistically significant and *equally*

strong correlations with both target matrices. One interpretation of this finding is that the

measured neural signals do *not* in fact encode graded or multidimensional semantic

structure, but only serve to discretely differentiate animate and inanimate items—a

conclusion also consistent with Clarke & Tyler's (2014) RSA results described earlier.

The data thus allow us to test an alternative hypothesis: that the measured signals *do*

encode a graded, multidimensional and domain-general semantic space, in a manner

that is invisible to RSA. If so, RSL should reliably decode variation along multiple

orthogonal components of the target semantic matrix, considering all items together as

well as within animate and inanimate domains considered separately.

Applying RSL to ECoG or any other brain imaging data, however, faces an

immediate challenge: such technologies produce many more spatiotemporal neural

measurements than there are stimuli, so regression models predicting stimulus

characteristics from neural data are ill-defined (i.e., there exist infinite solutions that can

perfectly predict outcomes on training data even from random input data). To find a

unique fit without a priori feature selection, the regression must be *regularized* to satisfy

some additional constraint that will guarantee a single unique solution for model fitting.

For instance, the weight optimization might jointly minimize prediction error and the size

of the model coefficients, measured as the sum of their absolute values (the *L1-norm*).

Since this sum can be minimized by placing zero coefficients on many predictors, this

form of regularization promotes a sparse solution in which only a few predictors have

non-zero coefficients in the final model (e.g., Rogers et al., 2021). Other regularizers

(such as the L2 norm or the elastic net) enforce different constraints on model fitting,

and thus lead to other solutions when applied to the same dataset (Cox & Rogers,

2021).

In this sense, the selection of a regularization function amounts to a prior

hypothesis stipulating how the neural signal is likely to be structured. As recently argued

in (Frisby et al., 2023), the choice of regularizer should be informed by explicit

hypotheses about the nature of the signal to be decoded—in this case, a hypothesis

about how neurophysiological signals measured by surface electrodes in the brain

might encode a graded, multi-variate semantic space.

To that end, we adopted a regularization function called the *group-ordered-*

weighted LASSO (grOWL) loss (Oswal et al., 2016) that was designed in prior work to

capture three theoretically-motivated assumptions about the structure of neural

representations. First, it assumes the signal is *sparse*: of all measurements taken, only

a relatively small proportion encode target information of interest, so the regularizer

should place zero coefficients on many predictors (as with L1 regularization). Second, it

assumes *redundancy* in the true signal: neural populations that do encode target

information will be correlated in their activity patterns over items, so the regularizer

should spread similar coefficients across correlated signal-carrying populations (similar

to L2 regularization). Third, it assumes that signal-carrying populations are unlikely to be

"axis-aligned" with the target semantic space (i.e., responding only to variation along a

single semantic dimension) but more likely encode multiple, varying "directions" within

the space. That is, each neural population likely carries information about an item's

coordinates along multiple dimensions of the target space. We will refer to this as the

spanning assumption, since the selected neural features span the target

representational space but are unlikely to only encode distinct, individual dimensions.

To enforce this assumption, the regularizer should prefer solutions where coefficients on

a given neural feature are either all zero (the feature does not carry any information) or

all non-zero (it predicts some variation along all target dimensions).

Oswal et al. (2016) showed that all three assumptions can be captured in a

single convex loss function, and also provided analytic guarantees and an example

application on an fMRI dataset. We describe the logic briefly here; Appendix B provides

a formal description of the decoding model and grOWL regularizer, including a definition

of the loss and explanation of how it encourages these properties in the decoding

matrix.

Rather than fitting a separate regression model for each latent component of the target

RSM (as in the simulation), we instead predict all latent components (Figure 3A)

simultaneously by estimating the parameters of a *decoding matrix* β (Figure 3C) with

regularized multitask regression. Suppose the coordinates of n stimuli on r latent

semantic dimensions are stored in matrix $U_{n \times r}$ while the responses of m neural features

to the stimuli are stored in matrix $X_{n \times m}$. RSL models the entries in U as the matrix

product of the neural activations in X and the decoding matrix $\beta_{m \times r}$: $U = X\beta$. Each row

of β corresponds to one neural feature (voxel, electrode, etc.), and each column

encodes weights for each neural feature when predicting stimulus coordinates on the

corresponding dimension of the target matrix U. Thus, the assumptions about neural

signal just listed can be formalized as constraints on the structure of the decoding

matrix β (**Figure 3D**). To capture the sparsity and spanning assumptions, β is

constrained to be *row-sparse*: most rows have all zero values (sparsity), and the rest

have all non-zero values (spanning). To capture the redundancy assumption, highly

correlated and signal-carrying neural features receive similar row-vectors in β

(**Figure 3D**). The precise degree of sparsity and redundancy in the decoding matrix are

controlled by hyper-parameters that are tuned via cross-validation. **Figure 3** shows the

full workflow decoding semantic structure from ECoG data.

Figure 3. Representational similarity learning. A. To generate the target structure for decoding, semantic feature vectors for each of n items are mean-centered and converted to a cosine similarity matrix $\mathbf{S}_{n \times n}$ of approximate rank r. This is decomposed into matrix $\mathbf{U}_{n \times r}$ containing r orthogonal singular vectors and diagonal matrix $\mathbf{D}_{r \times r}$ containing singular values for each vector. The product $\mathbf{U}\sqrt{\mathbf{D}}$ is an *nxr* matrix whose columns contain r root-weighted singular vectors that are the target of the decoding model. Note that the product of this matrix with its transpose provides an estimate of the original matrix $\mathbf{S}_{n \times n}$. B. Neural responses in a picture-naming task are recorded for each stimulus as intra-cranial voltage potentials collected at 1000Hz over electrodes implanted in vATL. Data are concatenated across electrodes to create a single *m*-dimensional "neural feature vector" for each stimulus, where m is the total number of electrodes times the size of the decoding window in milliseconds. All such vectors are compiled into a neural feature matrix $\mathbf{X}_{n \times m}$ which contains the predictors for the decoding model. C. The target structure $\mathbf{U}\sqrt{\mathbf{D}}$ is then modeled as the product of the neural feature matrix $\mathbf{X}$ and a decoding matrix of regression coefficients $\boldsymbol{\beta}$ whose values are chosen via gradient descent to minimize prediction error plus the regularization penalty $H(\boldsymbol{\beta})$ scaled by the weighting parameter α. D. Definition of the group-ordered-weighted LASSO (grOWL) regularization function and illustration of the structure it promotes in the decoding matrix.

With this overview we can consider how RSL can be applied to assess whether

neural data encode a multidimensional and graded similarity space. Parameters in $\boldsymbol{\beta}$

are estimated for a batch of training data using regression regularized with the grOWL

loss. The decoding model is then applied to predict the coordinates of held-out items

along each dimension in the target representation space. If predicted and true

coordinates for held-out items correlate reliably on more than one dimension, the neural

signal must encode multidimensional structure. To assess whether the neural code

captures graded similarity, we additionally evaluate the regression models separately

for animate and inanimate items, as in the simulation. If the neural signal only

categorically differentiates animate from inanimate stimuli as suggested by the prior

RSA analysis in Y. Chen et al. (2016), then predicted and true values should correlate

significantly across all items, but not for animate or inanimate subsets considered

separately. Observation of both inter- and intra-domain correlations thus indicates that

the neural code captures a graded degree of similarity structure. Finally, to assess how

well the decoder recovers the target semantic similarities, the predicted coordinates for

held-out items on all three latent dimensions can be used to estimate semantic

distances between stimulus pairs. These estimates can then be correlated with true

semantic distances, similar to standard RSA.

Methods

We applied this approach to the same ECoG dataset where prior work using

RSA found no evidence for graded multidimensional structure (Y. Chen et al., 2016).

The study was approved by the ethics committee of the Kyoto University Graduate

School of Medicine (No. C533) and participants provided written informed consent. The

dataset contains voltages measured from platinum subdural grid electrodes (inter-

electrode distance 1 cm and recording diameter 2.3mm; Ad-Tech, WI) implanted in the

surface of left (8) or right (2) vATL in ten patients undergoing preparation for intractable

epilepsy (9) or brain tumor (1) while they named line drawings depicting the 100 items

described in Study 1. Electrodes were implanted in the right hemisphere for two patients

where WADA testing did not clearly indicate left-lateralization of language.

Each patient had between 6 and 32 electrodes (mean of 20) covering vATL. All

patients with epilepsy had seizure onset zones outside the anterior fusiform region,

except one patient for whom it was not possible to localize the core seizure onset

region. Data were sampled at 1000Hz (eight patients) or 2000Hz (two patients) with a

band-pass filter of 0.016 – 300 (eight patients) or 0.016 – 600Hz (two patients). The

dataset included, for each stimulus, voltages measured at each electrode over a 1s

window from stimulus onset and downsampled to 100Hz. Thus, for a participant with 20

electrodes, each stimulus was associated with a 2,000-element vector of voltages (20

electrodes x 100 time points). The ECoG data were preprocessed exactly as in Y. Chen

et al (2016).

Stimuli and Procedure

One hundred line-drawings (50 animate and 50 inanimate items) were obtained

from previous norming studies (Morrison et al., 1997; Snodgrass & Vanderwart, 1980).

See Y. Chen et al. (2016) for a complete list. Animate and inanimate stimuli were

matched on age of acquisition, visual complexity, familiarity, and word frequency, and

had high name agreement. Each stimulus was presented on a computer screen for 5

seconds, one after another with no interstimulus interval, once during each of four

sessions (four times in total). Each session proceeded in a different random order.

Participants were instructed to name each item as quickly and accurately as possible.

Participants were video and audio recorded during the experiment. Video was used to

monitor eye fixations and general attention to the task. The mean response latency was

1190ms.

Semantic similarity structure and dimensionality reduction.

The same target RSM and 3-dimensional embedding used in the simulated

analysis are reused for the ECoG analysis.

ECoG data preprocessing. Preprocessing was performed in MATLAB. Data were

downsampled to 100Hz by averaging measurements within 10ms boxcars. A prior study

applying pattern classification to these data found near identical results when analyzing

raw voltages versus voltages referenced to the electrode beneath the galea

aponeurotica or to the scalp electrode on the mastoid process contralateral to the side

of electrode implantation (Rogers et al., 2021). For this reason, and because the

location of the reference electrode varied across patients, we analyzed all voltages

without referencing. For each stimulus we retained data for 1000ms from stimulus

onset. While the trial epoch may include the onset of articulation toward the end, the

critical results cannot reflect such motor activity since all key phenomena are observed

early in the epoch. Baseline correction was not performed. The mean voltage at each

electrode for each stimulus was computed across the four repetitions. Voltages from

different electrodes were concatenated into a row vector and arranged in a neural data

matrix with each row containing the vector of voltages for one stimulus sampled from

multiple electrodes over time. We rejected columns and then rows where the marginal

mean was more than five standard deviations from the grand mean to censor extreme

outliers.

Model fitting and evaluation

RSL decoding models regularized with either grOWL or the L1-norm were fit and

analyzed in MATLAB v9.5 (MathWorks, 2018) using the Whole-brain Imaging with

Sparse Correlations (WISC) toolbox (Cox, 2021), which implements the approach as a

multitask variant of group ordered weighted L1-regularized regression (grOWL; Oswal

et al., 2016; Oswal & Nowak, 2018).

Fitting a decoding model regularized with grOWL requires two hyper-parameters

that govern pressured the strength with which the decoding matrix is to be row-sparse

(λ) with similar weights across correlated neural features (ω). We chose values for λ

and ω via ten-fold nested cross-validation for each model fit. The 100 stimuli were

randomly divided into ten subsets, each containing five animate and five inanimate

items. On each of the ten folds, one of the ten subsets was held out (outer-loop

holdout). The remaining nine sets were used to search for good hyperparameter values,

involving a second "inner" cross-validation loop.

On each inner-loop fold, one of the nine remaining sets was held out and a

decoding model was fit to the remaining eight sets using a specified pair of hyper-

parameter values. The fitted model's prediction error, defined as the Frobenius norm of

true versus predicted semantic coordinates, was evaluated on the inner-loop holdout

set. This procedure was repeated once for each of the nine inner-loop holdouts before

averaging the prediction error across folds to estimate the decoder's performance with

that hyperparameter configuration. Many different hyperparameter configurations were

evaluated in the inner loop using the Hyperband procedure (Li et al., 2018). The best-

performing configuration was then used to fit a model to all examples not in the outer-

loop holdout set. This tuned model was used to predict semantic coordinates for the

outer-loop holdout set, thus completing one iteration of outer-loop cross-validation. The

whole procedure was then repeated for the remaining nine outer-loop holdout sets.

Across folds, the procedure generated out-of-sample predicted coordinates for all 100

items. These final predicted coordinates, computed separately for each time-window in

each participant, were the primary data evaluated in the results.

Statistical thresholding with permutation testing

Our analyses closely followed the simulations: correlations between predicted

and true coordinates on each dimension were computed for all 100 stimuli, just the 50

animate items, or just the 50 inanimate items. Assessing model accuracy via correlation

standardizes means and variances of the target and predicted vectors to focus on just

their covariance. This is especially critical when evaluating animate and inanimate items

separately. However, cross-validated correlation has a negative bias when evaluating

held-out items (see Zhou et al., 2017 and Appendix C); a null hypothesis of zero with a

t-distributed sampling distribution cannot be assumed. Thus, we determined statistical

reliability at the group level by constructing an empirical null distribution via a

permutation procedure described by Stelzer et al. (2013). The analysis described above

was repeated 100 times per participant, each time with a different random permutation

applied to the rows of the target matrix. This yielded 100 correlation values for each

patient, representing expected values from our workflow when no reliable relationship

exists between neural data and target matrix (due to the permutation procedure). Then,

a group-level empirical null distribution was estimated by randomly sampling one of the

100 performance metrics from each participant-level distribution and computing a

permuted-group-average 10,000 times. This provided sufficient resolution at the group

level at a fraction of the computational cost of fitting models to 10,000 permutations of

the target matrix per participant for each test (i.e., each window, for each subset of

items, in all analyses).

If m is the number of values in the permutation distribution and b is the number of

values in the distribution larger than the true correlation value, then the one-tailed p-

value can be computed (Edgington & Onghena, 2007; Phipson & Smyth, 2010) as:

614
$$p = \frac{b + 1}{m + 1}$$

Statistical significance was defined with respect to $\alpha < .05$ after adjusting the p-

values to control the false discovery rate (FDR).

Finally, to understand the effects of regularization with structured sparsity

(grOWL) vs. more standard techniques, we compared models fit with grOWL

regularization to those fit with L1 (LASSO) regularization.

Results

Analysis 1: Full window decoding with grOWL and LASSO

Figure 4a shows results from decoding the full 1000-ms time-window. For the

first component, models fit with both grOWL and LASSO reliably decoded similarity

structure across all items and for animate and inanimate subsets considered separately.

Whereas this was the only structure discovered with LASSO regularization, grOWL

regularization additionally showed reliable decoding of the second component across all

items and within animates only. Thus, RSL with grOWL regularization revealed graded,

multidimensional semantic structure in ECoG signals recorded from ventral ATL, while

the contrasting pattern for LASSO suggests that additional constraints from grOWL

aided in the discovery of multidimensional semantic structure.

Figure 4. ECoG decoding results. Correlation between true and predicted coordinates along each latent dimension (columns) for models fit to all items (green), animate items only (orange), or inanimate items only (blue), and regularized with grOWL or LASSO. Error bars reflect standard error of the mean over participants. Each value is centered on the mean of its corresponding permutation distribution. For uncentered values, see Figure S4. Colored bars / filled circles indicate reliable decoding with FDR-corrected p < .05 for all points in a panel. a) grOWL (darker bars) and LASSO (lighter bars) model performance when trained on the full 1000-ms trial epoch. b) grOWL model performance within opening windows. c) LASSO model performance within opening windows. d) Analogous to (b) except that models are fit and evaluated within a 100ms moving window instead of the opening window.

Analysis 2: Opening window

To see how this structure emerges in the ECoG signal over time, we conducted an

"opening window" analysis in which the same procedure was applied to an increasingly

wide aperture of data, beginning with just the first 50ms post-stimulus, extending to

100ms, then growing by 100ms up to 1000ms. The opening window analysis evaluates

when enough information has entered the spatiotemporal feature space to support

decoding. The goal is not to localize a representation in time, but to identify when

reliable decoding is first possible and when performance stops improving.

The results show reliable decoding of between-domain and within-animate

structure along the first component by 200ms, followed by within-inanimate structure by

300ms (Figure 4b). Decoding accuracy for superordinate and animate-subordinate

structure continually improved with wider windows along component 1, but not

inanimate-subordinate structure. Along the second component, reliable decoding was

observed after 300ms for between-domain structure and somewhat earlier (200ms) for

within-animate structure. Within-inanimate structure could not be reliably decoded along

the second component at any window-size, nor could variation along the third

component of the target matrix. Models fit with LASSO (Figure 4c) also reliably decoded

both within- and across-domain structure along the first component, beginning at 200ms

for cross-domain structure, 300ms for a within-animate structure, and 500ms for within-

inanimate structure, but as with the full window, did not reliably decode the second (or

third) component for any window size.

Analysis 3: Moving window

The opening window analysis indicates the latency with which the neural signal

contains sufficient information for reliable decoding, but since each successive window

contains all prior time points, it does not indicate whether/how the neural encoding of

semantic information changes over time. Additionally, since larger windows contain

more neural features, they afford a greater possibility of over-fitting training data.

Consequently, the opening-window approach may fail to detect semantic information

encoded only within a limited time-window. For these reasons, we fit models using the

grOWL regularizer on a 100ms *moving* window, beginning at 0ms from stimulus onset

and advancing in 50ms increments. In this analysis, each window is the same size and

thus contains the same amount of neural data. Otherwise, the analysis was identical to

the opening-window variant.

Results are shown in Figure 4d. For component 1, reliable decoding was

observed across domains and within each domain between 150 – 700ms post stimulus

onset. Reliable decoding on components 2 and 3 was observed within a more limited

time range. For component 2 (which best-separates the animate items), cross-domain

and within-animate structure was reliably and equally-well decoded for windows

beginning at 150 – 400ms. For component 3 (which best separates inanimate items),

cross-domain and within-inanimate structure was reliably and equally-well decoded for

windows beginning at 200 – 300ms. Together the analyses suggest that, from around

200 – 400ms post-stimulus, neural states measured by ECoG express both within- and

between- domain semantic structure, for both animate and inanimate items, across all

three components of the target matrix. That is, they express a graded multidimensional

and domain-general semantic space.

Analysis 4: Moving-window reconstruction of full target similarity matrix

The preceding analyses consider decoding of each matrix component separately,

allowing us to draw conclusions about which aspects of semantic structure are

represented in the neural signal at which time points. The independent consideration of

different dimensions, however, makes it difficult to compare results of RSL to RSA,

since RSA considers correlations between full pairwise similarity matrices (the NSM and

the RSM). To facilitate the comparison, we used the decoding models fit in Analysis 3 to

construct a *predicted semantic similarity matrix* at each time-window. For each fitted

model, we predicted coordinates of the corresponding held-out items along all three

target matrix components, agglomerating these predictions across hold-out sets to

create a matrix of predicted coordinates for all items. Recall that the target coordinates

are the first three singular vectors of the original semantic similarity matrix, weighted by

the *square root* of the corresponding singular values (**Figure 3**). Thus, to reconstruct

predicted pairwise distances in the original target matrix, we need only take the product

of the predicted-coordinates matrix with its transpose.

Each row of the resulting matrix contains predicted semantic similarities between

an item and all other items. We then compared these predicted similarities to a target

similarity matrix constructed directly from the three components of the original matrix

that account for 90% of its variance. That is, for each item in the dataset, we computed

the correlation between the predicted and true similarities to (a) all other items, (b) other

items in the same domain, and (c) other items in the contrasting domain. For each

metric, we then averaged the correlations across (1) all items, (2) just the animate items

or (3) just the inanimate items. These conditions thus allowed us to assess how well the

decoders model semantic similarities both within and across each domain. The full

procedure was carried out independently for each participant at each time-window.

Figure 5 Correlation between predicted semantic similarities and the best-possible similarities reconstructed from the first three singular vectors/values of the true matrix. Error bars reflect standard error of the mean over participants. Decoding models fit with RSL reliably predict semantic similarities both within (orange dots) and between (blue dots) conceptual domains, for both animate (middle panel) and inanimate (right panel) stimuli, from about 100 – 200ms post-stimulus onward.

Correlation coefficients in each condition were then averaged across participants at

each time-window.

The results are shown in **Figure 5**. Filled circles indicate where predicted/true

correlations are reliably non-zero relative to a permutation-based null distribution with

FDR of p < 0.05 (Stelzer et al., 2013). Reliable correlations were observed from 100 –

150ms post-stimulus onward, whether computed across all items, within domain only, or

between-domain only, and considering the full complement of items (left panel), animate

items only (middle), or inanimates only (right).

709  For comparison, we replicated the RSA analysis of Y. Chen et al (2016) on the

710 same data used for RSL and extended it to examine structure within animate and

711 inanimate item subsets. When conducting RSA over all items, NSMs were correlated

712 with both a multidimensional target RSM and a unidimensional categorical (i.e., binary)

713 target RSM. **Figure 6** (left) plots the average Spearman's rho over participants within

714 the same ROI reported by Y. Chen et al (2016) for each temporal window and each

715 target RSM in light and dark grey. The correlations with each target RSM are very

716 similar, consistent with the original finding that RSA did not provide clear evidence

717 about the kind of semantic information present in the vATL. The right panel shows

718 results of RSA applied to animate (light grey) and inanimate (dark grey) item subsets.

719 These correlations were indistinguishable from zero in every window.

720  Colored lines in the two panels show the correlations between the RSL predicted

721 similarity matrix and the target matrix across all items (left panel) or within animates

722 (right panel orange) and within inanimates (right panel blue). While reliably positive

723 correlations over the full set of items were observed with both RSA and RSL from

724 150ms onward (one-sample two-tailed t-tests, $\mu_0 = 0$, $\alpha = .05$, all t(9)>2.75), the

725 correlation coefficients obtained by RSL were significantly larger in all windows with

726 reliable effects (paired two-tailed t-tests, $\alpha = .05$, all t(9)>3.5). However, this is not a

727 difference that requires a statistical analysis to appreciate: over windows with reliably

728 positive correlations, the correlation coefficient obtained with RSL was between 6 to 13

729 times larger. A 10-fold increase in Spearman's rho is a 100-fold increase in the

730 proportion of variance explained. RSL produces a qualitatively different result from RSA,

731   in terms of its sensitivity to detecting structure and its ability to determine what structure

732   is present in neural signal.

Figure 6. Comparing RSA and RSL on the same data. All correlations (Spearman's rho) are averages over the 10 participants and error bars depict standard error. The left panel shows the correlation between the full predicted similarity matrix obtained using RSL and the multidimensional target RSM (green), as well as results obtained by replicating the RSA conducted by Y. Chen et al (2016) on the same data used for RSL using the multidimensional (light grey) or a categorical (dark grey) target RSM. Differences between categorical and multidimensional RSA are insignificant, while differences between RSL and RSA are large and significant from 150ms onward. The RSA results in the right panel are analogous to the left panel except that subsets of items are studied separately. RSA does not detect within-category structure while RSL does.

Discussion

Replicating Y. Chen et al. (2016), if one only relied on RSA analysis then it would

be easy to conclude that ECoG activity in vATL only encodes a discrete, binary

distinction between animate vs. inanimate items, with no information about semantic

structure within either domain considered independently. In stark contrast, the RSL

analysis shows that ECoG signals measured in human vATL encode information about

semantic similarity structure that is multidimensional (reliable decoding along three

orthogonal components of the target matrix), graded (reliable decoding of varying

degrees of similarity both within and between domains), and domain-general (reliable

decoding of within-domain similarities for both animate and inanimate items). These

properties are consistent with the predictions of the "hub and spokes" theory of

semantic representation in the brain, which proposes that neural activity in vATL

encodes a graded, multidimensional, and domain-general semantic vector space. It is

also consistent with the converging sources of evidence that gave rise to that view,

including patient studies (Patterson et al., 2006), neural stimulation (Pobric et al., 2007),

and computational modeling (Rogers et al., 2004). In this sense, the RSL results

resolves a seeming discrepancy between RSA findings and the broader literature.

General Discussion

We introduced this paper with a puzzle: neuropsychology, clinical

neurophysiology, TMS, and computational modelling all suggest that the vATLs encode

a semantic vector space of graded, multidimensional and domain-general conceptual

similarity structure, but direct tests of this hypothesis using representational similarity

analysis have often yielded null results in vATL and positive results in brain areas not

otherwise thought to encode semantic representations. In simulation we showed that

counter-intuitive limitations of RSA can obscure inferences about neurocognitive

representation. When used to decode real semantic structure as measured by feature

norms, RSA can produce positive results even if the underlying neural code is discrete

and unidimensional, or null results even if the neural code does capture latent structure

in the target matrix beyond the first component. Because RSA relies on an inherently

unidimensional measure of association (i.e., correlation), it cannot reveal whether neural

signals encode multidimensional structure. Because the technique does not fit any

parameters to data, it requires the researcher to select features a priori when

constructing the NSM (for instance, via ROI or searchlight analyses; see Frisby et al.,

2023), and cannot learn to ignore irrelevant features amongst those selected. The

simulations suggest that these characteristics of RSA may have contributed to the

puzzling state of the literature—for instance, by yielding results suggesting that vATL

only coarsely discriminates living from nonliving things (Clark & Tyler, 2014; Chen et al.,

2015).

RSL addresses these limitations by using regression to predict coordinates of

stimuli along the latent orthogonal dimensions of the RSM. In simulation, we showed

how this approach can uncover multidimensional representational structure (by showing

reliable conjoint decoding of two or more orthogonal dimensions of a target matrix) as

well as graded structure (by showing reliable decoding both within and between

semantic domains). The approach can also "select out" signal-carrying features from

amongst those included as predictors in the model, and so can be applied to all

potentially signal-carrying neural features at once, without requiring the theorist to pre-

select an ROI or to look only within small, independent searchlights (see Cox & Rogers,

2021; Frisby et al., 2023).

Applying the approach to large neural datasets requires model regularization. We

illustrated how hypothesized patterns of structured sparsity in the neural signal can

constrain model fit via grOWL regularization and applied this approach to discover

semantic structure in an ECoG dataset where prior work using RSA found only a binary

animacy code (Chen et al., 2015). We replicated this analysis using the same RSA

approach, and further showed that RSA yields null results when assessing whether the

ECoG signals express within-domain semantic structure. In contrast, RSL with grOWL

regularization uncovered a graded and multidimensional semantic space capturing

similarities within and between both animate and inanimate domains—consistent with

conclusions drawn about the nature of semantic representations in the ATL hub from

other cognitive and clinical neuroscience sources. These results thus suggest that

discrepancies in the literature between studies employing RSA versus other sources of

evidence may reflect limitations of the RSA approach as typically practiced.

Validity of grOWL assumptions about neural signal.

795   The RSL models we have deployed were fit with a regularization function

designed to promote discovery of a *row-sparse* decoding matrix (the grOWL loss). We

hypothesize that such structure reflects three characteristics of neuro-semantic

representation specifically, and neuro-cognitive codes generally. First, the signal is likely

to be sparse: of all neural measurements taken in a given experiment, only a relatively

small proportion are likely to encode the target information of interest. The sparsity

assumption serves a useful role in decoding because it pressures many coefficients in

the regression model to zero, indicating that the corresponding features are not useful in

decoding the target information. In this sense, sparsity automatically serves the function

of feature-selection that, in RSA, must be handled a-priori based on an ROI, searchlight,

or other method (Cox & Rogers, 2021). We hypothesize neural codes to be relatively

sparse in general simply because brains support many different cognitive, perceptual,

motor, language, and affective functions—consequently the likelihood that a given

neural population is important for the specific function targeted by the investigator is

relatively small.

Second, we hypothesize that the signal is *redundant*: it is unlikely that a given

target structure is only encoded by a single voxel, or a single timepoint at a single

electrode, etc. Any cognitive construct of interest—feature, category, or dimension in a

representational space—is unlikely to be encoded by the activation of a single local

neural population, such as a single voxel. More likely, such information involves multiple

neural populations, in which case those populations that *do* encode target information

will exhibit some degree of correlation with one another. This assumption is captured by

the grOWL loss because it encourages solutions in which intercorrelated sets of neural

features that help to predict target structure receive similar, non-zero coefficients in the

decoder.

Finally, we hypothesize that the neural code is unlikely to be axis-aligned with the

dimensions of the target representation space. That is, a given neural feature is unlikely

to encode variation along just one dimension of a multidimensional target space without

also encoding some information about variance along other dimensions. In grOWL, this

hypothesis is expressed as a preference for learning a row-sparse decoding matrix—

coefficients on a given neural feature should either be all zero (the feature is

unimportant) or all non-zero (the feature explains some variance along each

dimension). The reason is simply that, for any target vector space, there exists only a

small and finite number of axis-aligned encodings, but an infinite number of non-axis-

aligned encodings. Aligned and unaligned encodings express the same information

about similarities amongst objects of representation, so, absent some explicit pressure

for brains to learn axis-aligned representations, it is unlikely that an axis-aligned

encoding will occur by chance. Additionally, ECoG electrodes are influenced by

voltages generated by a mix of individual local neurons—so even if individual neurons

are selectively tuned to axis-aligned dimensions, the net responses recorded at the

electrode is likely to reflect a blend of these dimensions.

836   While the grOWL regularizer generally prefers decoding models with these

properties, note that the relative strength of these constraints is determined by

hyperparameters that can be tuned via cross-validation to fit the data. If the best

solution is not particularly sparse, the tuning process will select a small weight for the

sparsity term in the optimization, leading to a solution in which many features are

chosen. If the signal-carrying features are not particularly correlated, the tuning process

can select hyperparameters that relax the grouping of features into sets that share the

same weights. Thus, grOWL regularization is quite flexible with respect to how rigidly

the various constraints are enforced.

845   The current study suggests that the grOWL assumptions are useful for

understanding information encoded in ECoG voltages: when decoding the full time-

window, regularization with grOWL revealed multidimensional similarity structure,

whereas decoding with the sparsity assumption only (LASSO) found only

unidimensional structure. We emphasize, however, that the RSL framework can be

deployed with any form of model regularization. Alternative hypotheses about the likely

structure of neural encodings can be formulated as different regularization costs, and

the decoding success of models fit with different regularizations can then be compared

to empirically evaluate the different assumptions. Prior computational work has

contrasted grOWL regularization to other approaches (see Oswal et al., 2016 for

comparisons to some other related methods); we hope the current results with grOWL

will inspire other scientists to experiment with alternative losses to better understand the

nature of neuro-cognitive codes.

Implications for alternative theories of ATL function.

859   The current results challenge an alternative proposal about the role of ATL in

semantic cognition, namely that they support knowledge of some conceptual categories

and not others (Mahon & Caramazza, 2011; Malone et al., 2016; Simmons et al., 2009).

Such a view is consistent with prior imaging work (e.g., Anzellotti et al., 2011) including

the multivariate decoding studies cited earlier (Y. Chen et al., 2016; Clarke & Tyler,

2014), suggesting that ATL activations differentiate animates from inanimates but do not

otherwise encode or differentiate finer categories. This alternative perspective has been

difficult to reconcile with neuropsychological evidence showing that anterior temporal

atrophy and hypometabolism in semantic dementia degrades knowledge of animates

and inanimates equally (Lambon Ralph et al., 2007; Noppeney et al., 2007), and with

TMS and direct grid stimulation evidence showing that stimulation of both left and right

ATL reliably slows semantic processing for both animates and artefacts (Pobric et al.,

2010; Shimotake et al., 2015). It also struggles to explain the sensitivity of ATL-related

semantic impairment to continuous and graded semantic structure of test stimuli for

both animates and inanimates (Patterson et al., 2006; Rogers et al., 2006). The current

results suggest that prior work may have failed to discover graded cross-domain

semantic structure in ATL responses, not because such structure is absent from the

measured responses, but because limitations in both fMRI and analytic techniques

make such structure difficult to detect.

It is worth noting that intra-domain similarities were more robustly decoded for

animate compared to inanimate items. Considering each dimension separately in the

opening window analysis, within-inanimate decoding was only reliable for the first latent

dimension. In the moving window analysis, where models were trained on 100ms

increments of data without the full history of activation from stimulus onset, within-

inanimate decoding was reliable for components 1 and 3, but transiently. These are the

components that best differentiate inanimates in the target matrix (see Figure 1). When

predicting pairwise distances within moving windows, correlations with true similarities

were reliable but smallest for within-inanimate structure (i.e., the "other domain"

correlations in the middle panel of **Figure 5**, and "same domain" correlations in the

rightmost panel).

We attribute this general pattern to differences, not in the neural code itself, but

in the target similarity structure of animate and inanimate concepts. Semantic

subcategories of inanimate objects are only weakly differentiated, not just in the current

dataset, but in norming studies more generally and in other approaches to

characterizing semantic structure (e.g., Devlin et al., 1998; Garrard et al., 2001; McRae

et al., 1997; Tyler et al., 2000). Indeed, this difference in statistical structure is precisely

what leads, under some theories, to apparent category-specific patterns of semantic

impairment (Devlin et al., 2002; Lambon Ralph et al., 2007) and functional activation

(Rogers et al., 2006). The differences can be seen in **Figure 1**, where animate items fall

into somewhat well-differentiated subcategories in components 1 and 2 while

inanimates are uniformly distributed with poorly differentiated subclusters even along

component 3. Accordingly, pairwise similarities reconstructed from the first three

singular vectors of the full semantic matrix are more accurate for animate than

inanimate items (see Appendix D). Thus, the structure of the semantic matrix itself

requires that decoding be worse within inanimates than within animates, precisely

because inanimates are less well-structured. Yet despite this intrinsic disadvantage,

within-inanimate similarities were still reliably decoded along multiple components of the

embedding and in the reconstructed similarity matrix, illustrating that neural signal in

vATL does express intra-domain semantic structure even for inanimate stimuli.

In summary, the results suggest the vATLs encode a multidimensional

representation space that captures the conceptual similarities existing amongst a variety

of different concepts including both animate and inanimate items (Lambon Ralph et al.,

2007; Patterson et al., 2007; Rogers & McClelland, 2004). Better decoding within

animates may reflect the fact that animate subcategories are better-differentiated, so

that intra-domain similarities are better-approximated by a low-rank decomposition.

We also note that the current results pertain only to the nature of the semantic

information encoded within the span of vATL where electrodes were situated in our

patient sample. They do not bear on claims of possible category-specific representation

in other parts of cortex—for instance, that left infero-parietal cortex and posterior medial

temporal gyrus play a special role in knowledge about tools (Q. Chen et al., 2016;

Garcea et al., 2018; Ishibashi et al., 2016; Kalénine & Buxbaum, 2016) or that earlier

visual areas are dedicated to representing different object categories (Cichy et al., 2014;

Connolly et al., 2012; Downing et al., 2001; Kanwisher et al., 1997; Kriegeskorte, Mur,

Ruff, et al., 2008; Mahon et al., 2009; Sha et al., 2015). Indeed, prior work from (Chen

et al., 2017) showed how domain-general semantic representations can arise in vATL

even as graded category-specificity emerges in other parts of the cortical semantic

network, based on empirically-measured patterns of white-matter connectivity across

core areas. Evaluating claims of category-specificity in future work may benefit from

adopting the RSL approach developed here.

Implications for the broader literature.

The characteristics of RSA we have identified carry additional implications for

interpretation of the broader literature. A recent review (Frisby et al., 2023) identified 24

studies that have applied RSA to the discovery of semantic representations in the brain,

with positive results observed across multiple cortical regions including posterior

temporal cortex (Connolly et al., 2012), angular gyrus (Fairhall & Caramazza, 2013;

Fernandino et al., 2022), left perisylvian cortex (Devereux et al., 2013), posterior

cingulate (Fairhall & Caramazza, 2013), and prefrontal cortex (Carota et al., 2017).

Simulation 1 suggests, however, that RSA will yield a positive result for any property

correlated with the animate/inanimate distinction, including even discrete binary

properties. Many features are confounded with animacy: inanimate items tend to be

more familiar, less visually complex, more associated with action plans, less associated

with motion, more likely to have lines and corners, less predictable from color or texture,

etc. (see Chen & Rogers, 2014 for a review). Most RSA papers do not report the

magnitude of correlation between RSM and NSM where results are significant, instead

focusing on whether the estimated correlation coefficient is reliably non-zero across

participants. As shown by the prior RSA analysis of the same ECoG data explored here

(Y. Chen et al., 2016; gray line in Figure 5), this can happen even when mean

correlations are very small. Moreover, several studies use target RSMs with only a

small number of rows/columns—sometimes as few as five (Connolly et al., 2012;

Fairhall & Caramazza, 2013), meaning that correlations are computed across just 10

cells of the matrix (i.e., the lower triangle of a 5x5 RSM). Such small numbers increase

the likelihood that a small-but-non-zero correlation is driven by some arbitrary property

of the chosen stimuli or categories. Together these observations raise the possibility

that the literature contains misleading positive results—brain areas whose responses

encode unidimensional characteristics weakly confounded with animacy, rather than

multidimensional semantic structure. Testing this possibility for various brain areas

hypothesized to encode semantic structure will require analyses like those we have

developed here.

957   **Conclusion**

958   In cognitive science, semantic representations are often construed as vector

spaces that encoded graded, multidimensional similarity structure amongst the

concepts experienced in our verbal and nonverbal world. Through application of a new

technique for mapping representational similarity in neural activity, we have shown that

neural signals in vATL encode such a space. In so doing, we have identified some

limitations of representational similarity analysis, a widespread technique commonly

thought to reveal graded and multidimensional representational structure. The work

resolves an important discrepancy between behavioral and neuroimaging results in prior

work and suggests a new approach to discovering representational structure in neural

data more generally.

968   **Acknowledgments**

Funding: This work was partially supported by MRC Programme grant to MALR and

TTR (MR/R023883/1) and an intramural award (MC_UU_00005/18), and by a European

Research Council grant GAP: 502670428 - BRAIN2MIND_NEUROCOMP, and by a

Louisiana Board of Regents Research Competitiveness Subprogram grant to CRC

(LEQSF(2022-25)-RD-A-04). RM reports grants from MEXT, KAKENHI 22H04777,

22H02945. AS reports grants from MEXT, KAKENHI 22K07537

Author Contributions: Cox conducted all analysis and drafted the manuscript. Rogers

and Lambon Ralph contributed to all aspects of the study design, analysis, and

manuscript preparation. Shimotake, Kikuchi, Kunieda, Miyamoto, Takahasi, Ikeda and

Matsumoto were responsible for ECoG data collection and clinical assessment.

Competing interests: The Department of Epilepsy, Movement Disorders, and

Physiology, Kyoto University Graduate School of Medicine conducts Industry-Academia

Collaboration Courses, supported by Eisai Co., Ltd, Nihon Kohden Corporation, Otsuka

Pharmaceutical Co., and UCB Japan Co., Ltd.

Data and materials availability: RSL models were fit using the WISC MVPA toolbox

(https://github.com/crcox/WISC_MVPA). Analysis of RSL models was conducted using

custom MATLAB code (https://github.com/crcox/RSL_correlation_analysis), and the

data and script necessary to replicate them is available via the Open Science

Framework (https://osf.io/axseq/). R scripts for generating figures based on the

correlation analyses are on GitHub (https://github.com/crcox/ecog-rsl-figures).

Appendices:

Appendix A. Categorized experimental stimuli

Appendix B. Formal description of the RSL approach

Appendix C. RSL and negative correlations Anatomical distribution of decoding model

weights across vATL

Appendix D. Reconstructing item similarity from the SVD coordinates

Appendix E. Correlation between predicted and true semantic distances

Appendix F. Temporal Generalization profiles of models fit within moving windows

Appendix G. Anatomical distribution of decoding model weights across vATL

Appendix H. Predicted embeddings

References

1000

Abel, T. J., Rhone, A. E., Nourski, K. V., Kawasaki, H., Oya, H., Griffiths, T. D., Howard,

M. A., 3rd, & Tranel, D. (2015). Direct physiologic evidence of a heteromodal

convergence region for proper naming in human left anterior temporal lobe.

Journal of Neuroscience, *35*(4), 1513-1520.

https://doi.org/10.1523/JNEUROSCI.3387-14.2015

Acosta-Cabronero, J., Patterson, K., Fryer, T. D., Hodges, J. R., Pengas, G., Williams,

G. B., & Nestor, P. J. (2011). Atrophy, hypometabolism and white matter

abnormalities in semantic dementia tell a coherent story. *Brain*, *134*(7), 2025-

2035. https://doi.org/10.1093/brain/awr119

Anzellotti, S., Mahon, B. Z., Schwarzbach, J., & Caramazza, A. (2011). Differential

activity for animals and manipulable objects in the anterior temporal lobes. *J

Cogn Neurosci*, *23*(8), 2059-2067. https://doi.org/10.1162/jocn.2010.21567

Binney, R. J., Embleton, K. V., Jefferies, E., Parker, G. J. M., & Lambon Ralph, M. A.

(2010). The ventral and inferolateral aspects of the anterior temporal lobe are

crucial in semantic memory: evidence from a novel direct comparison of

distortion-corrected fMRI, rTMS, and semantic dementia. *Cerebral Cortex*,

20(11), 2728-2738. https://doi.org/10.1093/cercor/bhq019

Binney, R. J., & Lambon Ralph, M. A. (2015). Using a combination of fMRI and anterior

temporal lobe rTMS to measure intrinsic and induced activation changes across

the semantic cognition network. *Neuropsychologia*, *76*, 170-181.

https://doi.org/10.1016/j.neuropsychologia.2014.11.009

Bruffaerts, R., Dupont, P., Peeters, R., De Deyne, S., Storms, G., & Vandenberghe, R.

(2013). Similarity of fMRI activity patterns in left perirhinal cortex reflects

semantic similarity between words. *Journal of Neuroscience*, *33*(47), 18597-

18607. https://doi.org/10.1523/JNEUROSCI.1548-13.2013

Carota, F., Kriegeskorte, N., Nili, H., & Pulvermuller, F. (2017). Representational

Similarity Mapping of Distributional Semantics in Left Inferior Frontal, Middle

Temporal, and Motor Cortex. *Cerebral Cortex*, *27*(1), 294-309.

https://doi.org/10.1093/cercor/bhw379

Chen, L., Lambon Ralph, M. A., & Rogers, T. T. (2017). A unified model of human

semantic knowledge and its disorders. *Nature Human Behaviour*, *1*(3), 1-10.

https://doi.org/10.1038/s41562-016-0039

Chen, L., & Rogers, T. T. (2014). Revisiting domain-general accounts of category

specificity in mind and brain. *WIREs Cognitive Science*, *5*(3), 327-344.

https://doi.org/10.1002/wcs.1283

Chen, Q., Garcea, F. E., & Mahon, B. Z. (2016). The Representation of Object-Directed

Action and Function Knowledge in the Human Brain. *Cereb Cortex*, *26*(4), 1609-

1618. https://doi.org/10.1093/cercor/bhu328

Chen, Y., Shimotake, A., Matsumoto, R., Kunieda, T., Kikuchi, T., Miyamoto, S.,

Fukuyama, H., Takahashi, R., Ikeda, A., & Lambon Ralph, M. A. (2016). The

'when' and 'where' of semantic coding in the anterior temporal lobe: Temporal

representational similarity analysis of electrocorticogram data. *Cortex*, *79*, 1-13.

https://doi.org/10.1016/j.cortex.2016.02.015

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in

space and time. *Nature Neuroscience*, *17*(3), 455.

https://doi.org/10.1038/nn.3635

Clarke, A., & Tyler, L. K. (2014). Object-specific semantic coding in human perirhinal

cortex. *Journal of Neuroscience*, *34*(14), 4766-4775.

https://doi.org/10.1523/JNEUROSCI.2828-13.2014

Connolly, A. C., Guntupalli, J. S., Gors, J., Hanke, M., Halchenko, Y. O., Wu, Y.-C.,

Abdi, H., & Haxby, J. V. (2012). The representation of biological classes in the

human brain. *Journal of Neuroscience*, *32*(8), 2608-2618.

https://doi.org/10.1523/JNEUROSCI.5547-11.2012

Cox, C. R. (2021). *Whole-brain Imaging with Sparse Correlations*. In Github.

Cox, C. R., & Rogers, T. T. (2021). Finding Distributed Needles in Neural Haystacks.

Journal of Neuroscience, *41*(5), 1019-1032.

https://doi.org/10.1523/jneurosci.0904-20.2020

Devereux, B. J., Clarke, A., Marouchos, A., & Tyler, L. K. (2013). Representational

Similarity Analysis Reveals Commonalities and Differences in the Semantic

Processing of Words and Objects. *Journal of Neuroscience*, *33*(48), 18906-

18916. https://doi.org/10.1523/jneurosci.3809-13.2013

Devereux, B. J., Clarke, A., & Tyler, L. K. (2018). Integrated deep visual and semantic

attractor neural networks predict fMRI pattern-information along the ventral object

processing pathway. *Scientific reports*, *8*(1), 10636.

https://doi.org/10.1038/s41598-018-28865-1

Devlin, J. T., Gonnerman, L. M., Andersen, E. S., & Seidenberg, M. S. (1998).

Category-Specific Semantic Deficits in Focal and Widespread Brain Damage: A

Computational Account [Article]. *Journal of Cognitive Neuroscience*, *10*(1), 77-

94. https://doi.org/10.1162/089892998563798

Devlin, J. T., Russell, R. P., Davis, M. H., Price, C. J., Moss, H. E., Fadili, M. J., & Tyler,

L. K. (2002). Is there an anatomical basis for category-specificity? Semantic

memory studies in PET and fMRI. *Neuropsychologia*, *40*(1), 54-75.

https://doi.org/10.1016/S0028-3932(01)00066-5

Dilkina, K., & Lambon Ralph, M. A. (2013). Conceptual structure within and between

modalities. *Frontiers in Human Neuroscience*, *6*, 333.

https://doi.org/10.3389/fnhum.2012.00333

Downing, P. E., Jiang, Y., Shuman, M., & Kanwisher, N. (2001). A cortical area

selective for visual processing of the human body. *Science*, *293*(5539), 2470-

2473. https://doi.org/10.1126/science.1063414

Drane, D. L., Ojemann, G. A., Aylward, E., Ojemann, J. G., Johnson, L. C., Silbergeld,

D. L., Miller, J. W., & Tranel, D. (2008). Category-specific naming and recognition

deficits in temporal lobe epilepsy surgical patients. *Neuropsychologia*, *46*(5),

1242-1255.

https://doi.org/https://doi.org/10.1016/j.neuropsychologia.2007.11.034

Edgington, E., & Onghena, P. (2007). *Randomization Tests* (4th ed.) [Book]. Chapman

and Hall/CRC.

Fairhall, S. L., & Caramazza, A. (2013). Brain regions that represent amodal conceptual

knowledge. *Journal of Neuroscience*, *33*(25), 10552-10558.

https://doi.org/10.1523/JNEUROSCI.0051-13.2013

Fernandino, L., Tong, J.-Q., Conant, L. L., Humphries, C. J., & Binder, J. R. (2022).

Decoding the information structure underlying the neural representation of

concepts. *Proceedings of the National Academy of Sciences*, *119*(6),

e2108091119. https://doi.org/doi:10.1073/pnas.2108091119

Figueiredo, M., & Nowak, R. (2016). Ordered weighted l1 regularized regression with

strongly correlated covariates: Theoretical aspects. Artificial Intelligence and

Statistics,

Frisby, S. L., Halai, A. D., Cox, C. R., Lambon Ralph, M. A., & Rogers, T. T. (2023).

Decoding semantic representations in mind and brain. *Trends Cogn Sci*, *27*(3),

258-281. https://doi.org/10.1016/j.tics.2022.12.006

Gainotti, G. (2018). Why do herpes simplex encephalitis and semantic dementia show a

different pattern of semantic impairment in spite of their main common

involvement within the anterior temporal lobes? *Rev Neurosci*, *29*(3), 303-320.

https://doi.org/10.1515/revneuro-2017-0034

Garcea, F. E., Chen, Q., Vargas, R., Narayan, D. A., & Mahon, B. Z. (2018). Task- and

domain-specific modulation of functional connectivity in the ventral and dorsal

object-processing pathways. *Brain Struct Funct*, *223*(6), 2589-2607.

https://doi.org/10.1007/s00429-018-1641-1

Garrard, P., Lambon Ralph, M. A., Hodges, J. R., & Patterson, K. (2001).

Prototypicality, distinctiveness, and intercorrelation: Analyses of the semantic

attributes of living and nonliving concepts [Article]. *Cognitive neuropsychology*,

18(2), 125-174. https://doi.org/10.1080/02643290125857

Halai, A. D., Parkes, L. M., & Welbourne, S. R. (2015). Dual-echo fMRI can detect

activations in inferior temporal lobe during intelligible speech comprehension.

NeuroImage, *122*, 214-221. https://doi.org/10.1016/j.neuroimage.2015.05.067

Halai, A. D., Welbourne, S. R., Embleton, K., & Parkes, L. M. (2014). A comparison of

dual gradient-echo and spin-echo fMRI of the inferior temporal lobe. *Human brain*

mapping, *35*(8), 4118-4128. https://doi.org/10.1002/hbm.22463

Hebart, M. N., Zheng, C. Y., Pereira, F., & Baker, C. I. (2020). Revealing the

multidimensional mental representations of natural objects underlying human

similarity judgements. *Nature Human Behaviour*, *4*(11), 1173-1185.

https://doi.org/10.1038/s41562-020-00951-3

Hodges, J. R., & Patterson, K. (2007). Semantic dementia: a unique clinicopathological

syndrome [Review Article]. *Lancet Neurology*, *6*(11), 1004-1014.

https://doi.org/10.1016/S1474-4422(07)70266-1

Ishibashi, R., Pobric, G., Saito, S., & Lambon Ralph, M. A. (2016). The neural network

for tool-related cognition: An activation likelihood estimation meta-analysis of 70

neuroimaging contrasts. *Cogn Neuropsychol*, *33*(3-4), 241-256.

https://doi.org/10.1080/02643294.2016.1188798

Jackson, R. L., Rogers, T. T., & Lambon Ralph, M. A. (2021). Reverse-engineering the

cortical architecture for controlled semantic cognition. *Nature Human Behaviour*.

https://doi.org/10.1038/s41562-020-01034-z

Jefferies, E. (2013). The neural basis of semantic cognition: Converging evidence from

neuropsychology, neuroimaging and TMS. *Cortex*, *49*(3), 611-625.

https://doi.org/10.1016/j.cortex.2012.10.008

Kalénine, S., & Buxbaum, L. J. (2016). Thematic knowledge, artifact concepts, and the

left posterior temporal lobe: Where action and object semantics converge.

Cortex, *82*, 164-178. https://doi.org/10.1016/j.cortex.2016.06.008

Kanwisher, N., McDermott, J., & Chun, M. M. (1997). The fusiform face area: A module

in human extrastriate cortex specialized for face perception. *Journal of

Neuroscience*, *17*(11), 4302-4311. https://doi.org/10.1523/JNEUROSCI.17-11-

04302.1997

Kivisaari, S. L., van Vliet, M., Hultén, A., Lindh-Knuutila, T., Faisal, A., & Salmelin, R.

(2019). Reconstructing meaning from bits of information. *Nature

communications*, *10*(1), 927. https://doi.org/10.1038/s41467-019-08848-0

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity

analysis - connecting the branches of systems neuroscience. *Frontiers in

Systems Neuroscience*, *2*, 4. https://doi.org/10.3389/neuro.06.004.2008

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., &

Bandettini, P. A. (2008). Matching categorical object representations in inferior

temporal cortex of man and monkey. *Neuron*, *60*(6), 1126-1141.

https://doi.org/10.1016/j.neuron.2008.10.043

Lambon Ralph, M. A. (2014). Neurocognitive insights on conceptual knowledge and its

breakdown. *Philosophical Transactions of the Royal Society B: Biological

Sciences*, *369*(1634), 20120392. https://doi.org/10.1098/rstb.2012.0392

Lambon Ralph, M. A., Cipolotti, L., Manes, F., & Patterson, K. (2010). Taking both

sides: do unilateral anterior temporal lobe lesions disrupt semantic memory?

Brain, *133*(11), 3243-3255. https://doi.org/10.1093/brain/awq264

Lambon Ralph, M. A., Ehsan, S., Baker, G. A., & Rogers, T. T. (2012). Semantic

memory is impaired in patients with unilateral anterior temporal lobe resection for

temporal lobe epilepsy. *Brain*, *135*(1), 242-258.

https://doi.org/10.1093/brain/awr325

Lambon Ralph, M. A., Jefferies, E., Patterson, K., & Rogers, T. T. (2017). The neural

and computational bases of semantic cognition. *Nature Reviews Neuroscience*,

18(1), 42. https://doi.org/10.1038/nrn.2016.150

Lambon Ralph, M. A., Lowe, C., & Rogers, T. T. (2007). Neural basis of category-

specific semantic deficits for living things: evidence from semantic dementia,

HSVE and a neural network model. *Brain*, *130*, 1127-1137.

https://doi.org/10.1093/brain/awm025

Lambon Ralph, M. A., Pobric, G., & Jefferies, E. (2009). Conceptual knowledge is

underpinned by the temporal pole bilaterally: convergent evidence from rTMS.

Cereb Cortex, *19*(4), 832-838. https://doi.org/10.1093/cercor/bhn131

Li, L., Jamieson, K., DeSalvo, G., Rostamizadeh, A., & Talwalkar, A. (2018).

Hyperband: A Novel Bandit-Based Approach to Hyperparameter Optimization

[Article]. *Journal of Machine Learning Research*, *18*(154-234), 1-52.

Liuzzi, A. G., Bruffaerts, R., Peeters, R., Adamczuk, K., Keuleers, E., De Deyne, S.,

Storms, G., Dupont, P., & Vandenberghe, R. (2017). Cross-modal representation

of spoken and written word meaning in left pars triangularis. *NeuroImage*, *150*,

292-307. https://doi.org/https://doi.org/10.1016/j.neuroimage.2017.02.032

Mahon, B. Z., Anzellotti, S., Schwarzbach, J., Zampini, M., & Caramazza, A. (2009).

Category-specific organization in the human brain does not require visual

experience. *Neuron*, *63*(3), 397-405.

https://doi.org/10.1016/j.neuron.2009.07.012

Mahon, B. Z., & Caramazza, A. (2011). What drives the organization of object

knowledge in the brain? *Trends in Cognitive Sciences*, *15*(3), 97-103.

https://doi.org/10.1016/j.tics.2011.01.004

Malone, P. S., Glezer, L. S., Kim, J., Jiang, X., & Riesenhuber, M. (2016). Multivariate

Pattern Analysis Reveals Category-Related Organization of Semantic

Representations in Anterior Temporal Cortex. *J Neurosci*, *36*(39), 10089-10096.

https://doi.org/10.1523/JNEUROSCI.1599-16.2016

Martin, C. B., Douglas, D., Newsome, R. N., Man, L. L. Y., & Barense, M. D. (2018).

Integrative and distinctive coding of visual and conceptual object features in the

ventral visual stream. *Elife*, *7*, e31873. https://doi.org/10.7554/eLife.31873

MathWorks. (2018). *Matlab*. In *MATLAB* (Version 9.5 (R2018b)) The MathWorks.

McRae, K., Cree, G. S., Seidenberg, M. S., & McNorgan, C. (2005). Semantic feature

production norms for a large set of living and nonliving things. *Behavior research

methods*, *37*(4), 547-559. https://doi.org/10.3758/BF03192726

McRae, K., de Sa, V. R., & Seidenberg, M. S. (1997). On the nature and scope of

featural representations of word meaning. *Journal of Experimental Psychology:

General*, *126*(2), 99-130. https://doi.org/10.1037/0096-3445.126.2.99

Noppeney, U., Patterson, K., Tyler, L. K., Moss, H., Stamatakis, E. A., Bright, P.,

Mummery, C., & Price, C. J. (2007). Temporal lobe lesions and semantic

impairment: a comparison of herpes simplex virus encephalitis and semantic

dementia. *Brain*, *130*(Pt 4), 1138-1147. https://doi.org/10.1093/brain/awl344

Oswal, U., Cox, C. R., Lambon Ralph, M. A., Rogers, T. T., & Nowak, R. D. (2016).

Representational similarity learning with application to brain networks. ICML'16

Proceedings of the 33rd International Conference on International Conference on

Machine Learning, New York, USA.

Oswal, U., & Nowak, R. (2018, 2-5 Oct. 2018). Scalable Sparse Subspace Clustering

via Ordered Weighted l1 Regression. 2018 56th Annual Allerton Conference on

Communication, Control, and Computing (Allerton),

Patterson, K., Nestor, P. J., & Rogers, T. T. (2007). Where do you know what you

know? The representation of semantic knowledge in the human brain. *Nature*

Reviews Neuroscience, *8*(12), 976-987. https://doi.org/10.1038/nrn2277

Patterson, K., Ralph, M. A. L., Jefferies, E., Woollams, A., Jones, R., Hodges, J. R., &

Rogers, T. T. (2006). "Presemantic" Cognition in Semantic Dementia: Six Deficits

in Search of an Explanation. *Journal of Cognitive Neuroscience*, *18*(2), 169-183.

https://doi.org/10.1162/jocn.2006.18.2.169

Peelen, M. V., & Caramazza, A. (2012). Conceptual object representations in human

anterior temporal cortex. *Journal of Neuroscience*, *32*(45), 15728-15736.

https://doi.org/10.1523/JNEUROSCI.1953-12.2012

Pereira, F., Gershman, S., Ritter, S., & Botvinick, M. (2016). A comparative evaluation

of off-the-shelf distributed semantic representations for modelling behavioural

data. *Cognitive neuropsychology*, *33*(3-4), 175-190.

https://doi.org/10.1080/02643294.2016.1176907

Phipson, B., & Smyth, G. K. (2010). Permutation P-values Should Never Be Zero:

Calculating Exact P-values When Permutations Are Randomly Drawn. *Statistical*

Applications in Genetics and Molecular Biology, *9*(1).

https://doi.org/10.2202/1544-6115.1585

Pobric, G., Jefferies, E., & Lambon Ralph, M. A. (2007). Anterior temporal lobes

mediate semantic representation: mimicking semantic dementia by using rTMS in

normal participants. *Proceedings of the National Academy of Sciences*, *104*(50),

20137-20141. https://doi.org/10.1073/pnas.0707383104

Pobric, G., Jefferies, E., & Lambon Ralph, M. A. (2010). Category-specific versus

category-general semantic impairment induced by transcranial magnetic

stimulation. *Current Biology*, *20*(10), 964-968.

https://doi.org/10.1016/j.cub.2010.03.070

Rice, G. E., Caswell, H., Moore, P., Hoffman, P., & Lambon Ralph, M. A. (2018). The

Roles of Left Versus Right Anterior Temporal Lobes in Semantic Memory: A

Neuropsychological Comparison of Postsurgical Temporal Lobe Epilepsy

Patients. *Cerebral Cortex*, *28*(4), 1487-1501.

https://doi.org/10.1093/cercor/bhx362

Rogers, T. T., Cox, C. R., Lu, Q., Shimotake, A., Kikuchi, T., Kunieda, T., Miyamoto, S.,

Takahashi, R., Ikeda, A., Matsumoto, R., & Lambon Ralph, M. A. (2021).

Evidence for a deep, distributed and dynamic code for animacy in human ventral

anterior temporal cortex. *Elife*, *10*, e66276. https://doi.org/10.7554/eLife.66276

Rogers, T. T., Hocking, J., Noppeney, U., Mechelli, A., Gorno-Tempini, M. L., Patterson,

K., & Price, C. J. (2006). Anterior temporal cortex and semantic memory:

reconciling findings from neuropsychology and functional imaging. *Cognitive,*

Affective, & Behavioral Neuroscience, *6*(3), 201-213.

https://doi.org/10.3758/CABN.6.3.201

Rogers, T. T., Lambon Ralph, M. A., Garrard, P., Bozeat, S., McClelland, J. L., Hodges,

J. R., & Patterson, K. (2004). Structure and Deterioration of Semantic Memory: A

Neuropsychological and Computational Investigation. *Psychological Review*,

111(1), 205-235. https://doi.org/10.1037/0033-295X.111.1.205

Rogers, T. T., & McClelland, J. L. (2004). *Semantic cognition: A parallel distributed*

processing approach. MIT press.

Rogers, T. T., & McClelland, J. L. (2014). Parallel Distributed Processing at 25: further

explorations in the microstructure of cognition. *Cognitive Science*, *38*(6), 1024-

1077. https://doi.org/10.1111/cogs.12148

Schapiro, A. C., McClelland, J. L., Welbourne, S. R., Rogers, T. T., & Lambon Ralph, M.

A. (2013). Why bilateral damage is worse than unilateral damage to the brain. *J*

Cogn Neurosci, *25*(12), 2107-2123. https://doi.org/10.1162/jocn_a_00441

Sha, L., Haxby, J. V., Abdi, H., Guntupalli, J. S., Oosterhof, N. N., Halchenko, Y. O., &

Connolly, A. C. (2015). The animacy continuum in the human ventral vision

pathway. *Journal of Cognitive Neuroscience*, *27*(4), 665-678.

https://doi.org/10.1162/jocn_a_00733

Shimotake, A., Matsumoto, R., Ueno, T., Kunieda, T., Saito, S., Hoffman, P., Kikuchi,

T., Fukuyama, H., Miyamoto, S., Takahashi, R., Ikeda, A., & Lambon Ralph, M.

A. (2015). Direct Exploration of the Role of the Ventral Anterior Temporal Lobe in

Semantic Memory: Cortical Stimulation and Local Field Potential Evidence From

Subdural Grid Electrodes. *Cerebral Cortex*, *25*(10), 3802-3817.

https://doi.org/10.1093/cercor/bhu262

Simmons, W. K., Reddish, M., Bellgowan, P. S. F., & Martin, A. (2009). The Selectivity

and Functional Connectivity of the Anterior Temporal Lobes. *Cerebral Cortex*,

20(4), 813-825. https://doi.org/10.1093/cercor/bhp149

Snowden, J. S., Goulding, P. J., & Neary, D. (1989). Semantic dementia: A form of

circumscribed cerebral atrophy. *Behavioural Neurology*.

https://doi.org/10.1155/1989/124043

Stelzer, J., Chen, Y., & Turner, R. (2013). Statistical inference and multiple testing

correction in classification-based multi-voxel pattern analysis (MVPA): random

permutations and cluster size control. *NeuroImage*, *65*, 69-82.

https://doi.org/10.1016/j.neuroimage.2012.09.063

Tyler, L. K., Moss, H. E., Durrant-Peatfield, M. R., & Levy, J. P. (2000). Conceptual

Structure and the Structure of Concepts: A Distributed Account of Category-

Specific Deficits. *Brain and Language*, *75*(2), 195-231.

https://doi.org/10.1006/brln.2000.2353

Wang, X., Wu, W., Ling, Z., Xu, Y., Fang, Y., Wang, X., Binder, J. R., Men, W., Gao, J.-

H., & Bi, Y. (2017). Organizational Principles of Abstract Words in the Human

Brain. *Cerebral Cortex*, *28*(12), 4305-4318. https://doi.org/10.1093/cercor/bhx283

Yuan, M., & Lin, Y. (2006). Model selection and estimation in regression with grouped

1291   variables. *Journal of the Royal Statistical Society: Series B (Statistical*

1292   *Methodology)*, *68*(1), 49-67. https://doi.org/10.1111/j.1467-9868.2005.00532.x

1293   Zhou, Y., Vales, M. I., Wang, A., & Zhang, Z. (2017). Systematic bias of correlation

1294   coefficient may explain negative accuracy of genomic prediction. *Briefings in*

1295   *Bioinformatics*, *18*(6), 1093-1093. https://doi.org/10.1093/bib/bbx133

1296

1297

1298   **Appendix A: Categorized experimental stimuli**

1299   Table S1. Categorized experimental stimuli

Domain	Category	Words
Animate	*Bird*	duck, eagle, ostrich, owl, peacock, penguin, rooster, swan
	Bug	ant, bee, butterfly, caterpillar, fly, ladybird, snail, spider
	Land	bat, bear, camel, cat, cow, deer, dog, dragon, elephant, fox, frog, giraffe, goat, gorilla, horse, kangaroo, lion, monkey, mouse, pig, rabbit, raccoon, rhinoceros, sheep, snake, squirrel, tiger, tortoise, zebra
	Water	crab, fish, lobster, seahorse, whale
Inanimate	*Clothes*	dress, glove, mitten, skirt
	Music	bell, cymbals, drum, flute, guitar, harp, piano, trumpet, violin, whistle
	Object	anchor, barrel, basket, cake, cannon, chain, church, cigar, clock, crown, fence, gun, hammer, iron, kite, ladder, nut, pram, shell, slide, snowman, suitcase, swing, toaster, vase, web, wheel, windmill, yoyo
	Vehicle	aeroplane, helicopter, motorcycle, ski, sled, tractor, train

1300

1301   **Appendix B: Formal description of the RSL approach.**

1302   Let S be a symmetric $n \times n$ target matrix of approximate rank r describing

pairwise cognitive similarities amongst *n* items, which is decomposed via singular-value

decomposition (SVD) into an $n \times r$ matrix U of r orthonormal singular vectors and an

$r \times r$ diagonal matrix D containing the corresponding r singular values (**Figure 2A**). The

matrix product $U\sqrt{D}$ then contains root-weighted singular vectors that can be viewed as

encoding the coordinates of each stimulus within an r-dimensional latent semantic

space, while the product of this matrix with its transpose provides a rank r

approximation of the original similarity matrix. That is:

$$S_{n \times n} \cong U_{n \times r} D_{r \times r} U^T = U\sqrt{D}\,(U\sqrt{D})^T$$

1311   Let $X_{n \times m}$ be a data matrix recording neural responses to each of n stimuli over m

neural features (e.g., voxels in fMRI, electrode voltages at each timepoint in ECoG,

etc.). To assess whether some weighted combination of these features jointly encode

the target similarities, we seek a *decoding matrix* $\beta_{m \times r}$ such that the matrix product $X\beta$

produces *r* coordinates for each item, deviating as little as possible from those in target

matrix $U\sqrt{D}$. This search can be formulated as the convex optimization:

$$argmin_\beta \left\| U\sqrt{D} - X\beta \right\|_F$$

1318   That is, we seek β values that minimize the Froebenius norm (i.e., sum of

squared differences) between the true root-weighted singular vectors $U\sqrt{D}$ and the

predicted values $X\beta$. The optimization essentially computes a simultaneous regression

predicting all *r* coordinates for each stimulus from weighted combinations of the neural

responses they evoke. Each column of the resulting decoding matrix contains one

coefficient for each neural feature and predicts an item's coordinate along one

component of the target matrix $U\sqrt{D}$ (ie, one dimension of the semantic space).

As noted earlier, there are typically many more neural measurements (predictors)

than stimuli (i.e., target data points)—that is, $m \gg n$. Thus, the optimization just defined

is under-constrained and must be regularized with an additional loss H, itself a function

of the coefficient matrix $\boldsymbol{\beta}$:

1329
$$argmin_\beta \left(\left\| U\sqrt{D} - X\beta \right\|_F + \alpha H(\beta) \right)$$

…which is also convex so that a weighted sum of this function and the original

reconstruction loss together yield a single unique solution that can be discovered via

gradient descent. The constant α is a free weighting parameter governing the

importance of the regularization loss relative to the model error.

For RSL we wish to use a regularization function that promotes solutions

respecting the sparsity, redundancy, and spanning assumptions described earlier.

Oswal et al. (2016) formulated a regularizer that accomplishes these objectives by

constraining the structure of the decoding matrix $\boldsymbol{\beta}$ in a single convex loss called the

group ordered weighted LASSO or *grOWL.* The approach generalizes both the group

LASSO (Yuan & Lin, 2006) and the ordered-weighted LASSO (Figueiredo & Nowak,

2016) to favor solutions that are (1) row-sparse (rows of $\boldsymbol{\beta}$ are either all zero or all non-

zero), implementing both the sparsity and spanning constraints, but (2) with subgroups

of selected features sharing similar coefficients if their activations covary strongly

together (implementing the redundancy constraint). The grOWL loss is specified as:

1344
$$H(\beta) = \sum_{i=1}^{m} w_i \left\| \beta_{[i].} \right\|_2$$

Here m is the number of neural features (rows of $\boldsymbol{\beta}$), $\boldsymbol{\beta}_{[i]\cdot}$ is the row of $\boldsymbol{\beta}$ with the

i-th largest 2-norm (i.e., the i^{th} longest coefficient vector), and w_i is a vector of non-

negative, non-increasing weights (for instance a vector of positive values that decay

linearly from an initial constant). Intuitively the loss works as follows. The first element of

the weighting vector w is stipulated to be as large or larger than all other elements, and

this weight is applied to whichever neural feature has the largest coefficients in the

decoding matrix (i.e., the 2-norm or length of the corresponding row). Thus, the feature

with the largest coefficients exerts the largest regularization cost. The optimization must

therefore put the largest weights on the most informative feature to make it "worth" the

high regularization cost. If the most informative feature is also correlated with many

other features, their total cost can be further minimized by placing similar weights

across all such features, since the cost for each such weight declines with the weight

sequence in w. Thus, grOWL spontaneously clusters correlated signal-carrying neural

features and gives these a similar weight, effectively averaging them. Finally, the

weighting vector ensures that coefficients on features that do not reduce error beyond

those already selected will be pressured to zero, ensuring overall sparsity. Formal

analysis of the grOWL regularizer and mathematical proofs of its row-sparse and

clustering properties were provided by Oswal et al. (2016).

1363

Appendix C: RSL and negative correlations

The analysis protocol presented in this paper involves generating out-of-sample

predictions with k-fold cross validation and then aggregating those test-set predictions

into a single matrix before correlating with the target embedding all in one go. This is in

contrast with a more conventional protocol in which the performance metric is computed

separately within each fold and then averaged. When the metric is something like mean

squared error or classification accuracy, the two protocols are equivalent. With

correlation, however, the two protocols yield different values.

Pearson's r compares variables with zero mean and unit variance. Consequently,

when correlations between target and predicted embeddings are computed separately

by holdout-set, the scale of the predictions relative to the target is disregarded. By

aggregating over test sets and correlating one time, the standardization is done at the

level of the full dataset and not for individual test sets. We feel this is a better metric of

whether our models can embed all items appropriately within the target similarity

space—it matters how items are situated with respect to one another even if they are in

different test sets.

When models are fit with cross validation, the targets (and the data) are

standardized with respect to the values in the training set. Thus, the model predictions,

including test set predictions, are on the scale of the standardized *training set*. This

means that, to aggregate over test sets and correlate with the full set of targets, the

mean and variance of the target embeddings in the *training set* need to be added back

into the predictions for the corresponding *test set.*

Applying this adjustment will introduce negative correlations between target and

predicted embeddings for models that have been regularized to have weights that are

all zero. This will happen when relationships between the neural data and the target

embedding is weak or non-existent, because putting a weight on any neural feature

increases the model cost function without reducing the prediction error on the training

set. In such cases, the unadjusted model predictions will all be zero, and the adjusted

predictions will be the mean of the training set. If the mean of the training set is greater

than the grand mean of the full set, then the mean of the test set must be less than the

grand mean of the full set. Thus, adjusted and aggregated test set predictions will be

negatively correlated with the full target embedding when the model has all zero (or

trivially small) weights due to the LASSO or grOWL regularization penalty. These

concepts are illustrated in Figure S1 in an imagined case where all-zero models are

learned on each of three cross-validation folds.

What we found in practice is that grOWL is "more aggressive" about assigning

zero or trivially small weights than LASSO in the earliest and smallest time-windows.

We consider this to be desirable behavior because we do not expect much semantic

activity in the ATLs at 50ms post stimulus onset. Figure S2 is analogous to Figure 4 in

the main paper, except that the correlation values are not centered on the mean of their

corresponding permutation distribution. This reveals the negative correlations between

grOWL model predictions and the target embedding for small windows where we do not

expect semantic activation to be reliably present, and general consistency of

performance elsewhere. These negative correlations are an expected artifact of our

analysis protocol and do not change the interpretation of our results.

Figure S1 A schematic depiction of the relationship between test sets, training set means, the sample grand mean, and model predictions when the model consists of zero-weights on all neural features. A zero-weight model can occur when model regularization involves the LASSO penalty and the cost of applying a non-zero weight does not outweigh the benefit of reducing prediction error. If the mean of the test set differs from the grand mean, the mean of the test set must also differ from the grand mean. Importantly, if the mean of the test set is less than the grand mean, the mean of the training set must be higher. Unadjusted predictions (i.e., those that ignore the mean of the training set) will be all zero when the model weights are all zero; adjusted predictions are scaled by the training set mean. Leads to systematically negative correlations between true and predicted values for models regularized to have all-zero weights.

Figure S2. Uncentered ECoG decoding results. This figure is completely analogous to Figure 4 in the main paper, except that the raw correlations are presented, without centering on the mean of the permutation distribution. We see that the predictions of models fit with grOWL to small windows, including the least activation since stimulus onset, tend to be negatively correlated with the target values. This is due to the models being assigned very small weights, such that the variance in the predicted values associated with the training set means is large relative to the variance associated with the variability in the neural data. It is possible for negative correlations to be reliably higher than the expected value until the permutation-simulated null, as seen for the animate-subordinate structure along dimension 2 in the 200-ms window.

1409

Appendix D: Reconstructing item similarity from SVD coordinates

The main analysis uses the first three root-weighted singular vectors as the

target for fitting decoding models with RSL. Predicted coordinates are then used to

generate predicted semantic distances between pairs of held-out stimuli. To understand

the possible causes of domain differences in prediction accuracy, we considered how

well pairwise distances can be reconstructed from the first three singular vectors and

values computed from the true matrix with a subset of items excluded. The goal was to

assess whether the first three components capture inter-items distances equally well for

both domains or whether such distances are better approximated for one domain than

another.

To this end we conducted the following analysis. We generated 10,000 random

splits of the semantic norming data, each consisting of 90 training items and ten test

items (five animate and five inanimate) as in the ECoG study. For each, we computed

the SVD on the semantic distance matrix for only the items in the training set. We then

projected test-set items into the resulting space by matrix multiplying each item's

similarity with the training set items:

1426
$$\widehat{C}_{q\times r} = S'_{q\times p}U_{p\times r}D_{r\times r}; S' = \left(S_{ij}\right)_{\substack{i\in test \\ j\in training}}$$

Here $q = 10$ is the number of test set items, $p = 90$ is the number of training-set

items, $r = 3$ is the rank of the embedding, $\widehat{C}_{q\times r}$ is a matrix containing estimates

coordinates for the test items, S' is a matrix containing the true distances from test items

to training items, and U and D are matrices containing the singular vectors and values,

respectively, computed the training items. From the estimates coordinates in $\widehat{C}_{q\times r}$, the

predicted similarity matrix can be obtained as $\widehat{S}_{q\times q} = \widehat{C}D\widehat{C}^T$. To measure how well the

Figure S3. Correlation between true and reconstructed similarity matrices. Reconstructed similarity matrices are based on a SVD of a subset of the full similarity matrix expressing the pairwise similarities for 90 items, which is then used to reconstruct the similarities for the remaining 10 items as described in the text. This process was repeated 10,000 times with different 90/10 splits and each reconstruction was correlated with the corresponding true pairwise similarities. Bars show the average correlations over all similarities, just the between-category similarities (animate-inanimate), and just the within-category similarities (animate-animate and inanimate-inanimate). Error bars report the standard deviation of the means. The results for the specific 90/10 split used in the analysis of ECoG data reported in the main document are shown as black dots.

true distances are captures by the SVD, we computed correlations of lower-triangular

values between S and $\hat{S}$, either over all values at once or correlating the animate-

animate, inanimate-inanimate, and animate-inanimate similarity values separately.

Figure S3 shows the average correlations for each selection of similarities over

the 10,000 splits as bars with error bars reflecting the standard deviation over splits.

The mean over the 10 cross-validation splits used in the ECoG study are overlaid as

points. Predicted similarities that include or isolate between-category structure are most

correlated with the true similarity structure. Predicted within-category similarities are

less correlated, with predictions for inanimate items being less accurate than for

animate items. In other words, a low-rank approximation of the semantic similarity

matrix best captures between-domain distances and provides a better approximation of

within-animate than within-inanimate semantic structure. Thus, decoding models face

an intrinsic disadvantage at capturing within-domain structure generally, and within-

inanimate structure specifically.

1447

Appendix E: Correlation between predicted and full-rank semantic distances

In evaluating how well the RSL decoding models predict pairwise semantic

similarities, the main paper reports the correlation between predicted similarities and

similarities reconstructed directly from the three singular vectors computed from the

"true" full-rank matrix. We will refer to this as the *low-rank* similarity matrix. The low-rank

similarity matrix represents the best possible prediction, given that only three

components of the true matrix were used to fit the decoding model. Here we report

correlations with the *full-rank* similarity matrix—the actual pairwise similarities amongst

feature vectors as described in the main text. The low-rank and full-rank similarity

matrices are very similar, $r = .94$, such that the low-rank similarity matrix accounts for

~90% of the variance in the full-rank matrix. As one would expect given the high

correlation, **Figure S4** and **Figure 5** from the main document show the same pattern of

results. Filled circles indicate significance at Westfall-Young FWER corrected $\alpha = .05$.

Figure S4 Correlation between predicted semantic similarities and *full-rank* cosine similarities as computed from the feature vectors. These results are very similar to **Figure 5** in the main document which involves the *low-rank* similarity matrix, as reconstructed from the three semantic dimensions modeled in the primary analysis. The results

are so similar because the first three components account for ~90% of the variance in the full-rank cosine similarity matrix. The interpretation is the same as **Figure 5**.

Appendix F: Temporal generalization of models fit within moving windows

The model fit within a moving window can be used to decode target signal from

the data within all other moving windows, forming a temporal generalization profile

forwards and backwards through time. In Figure S5, each row in each panel is the

temporal generalization profile for one 100ms window. Colored points are significant

with FDR-corrected p<.05, correcting over the three panels in a single row (i.e., the

multiple subsets relative to a shared dependent variable). Profiles are shown for RSA-

style paired-matrix correlations (Cosine Similarities) and for correlations between model

predictions and the target embedding along each semantic component. Each analysis

can be performed over all items or by restricting to within-animate or within-inanimate

similarities.

Generalization is better at later time points, but some degree of reliable

generalization is seen through time for most models that perform well on the window it

was fit within for component 1 and the aggregate cosine similarities. However, this is not

seen when decoding components 2 and 3. Models fit early in the epoch do not

generalize to later time points, and models fit late in the epoch do not generalize to early

in the epoch.

The terms "early" and "late" are intentionally vague. We are not arguing for a

qualitative, discrete shift in representational content at a particular point in time. If

concepts encoded in the ATL follow a non-linear activation trajectory, as is often

observed in deep network architectures, that is sufficient to make "early" and "late"

representations importantly different while still conveying aspects of the target structure

(Rogers et al., 2021).

Figure S5. Temporal generalization profiles for each model fit within a single 100ms-moving-window and tested on all windows. Colored points are significant with FDR-corrected p<.05, correcting over the three panels in a single row (i.e., the multiple subsets relative to a shared dependent variable). The first row shows the correlations between predicted similarity matrices and the target similarity matrix. Subsequent rows show the correlation between single predicted and target components.

1484

1485   **Appendix G: Anatomical distribution of decoding model weights across vATL**

1486   The decoding results reported in the main paper demonstrate that

multidimensional semantic structure can be decoded from LFPs recorded from the

vATL, and that decoding the second semantic dimension depends on regularization via

the grOWL. This implies that local neural populations do not independently encode each

semantic dimension, but simultaneously express multiple orthogonal components of the

target semantic matrix. To evaluate whether this is so, we examined the spatial

distribution of weights across electrodes in the decoding models predicting variation on

the first via the second semantic dimensions for opening windows of size 200, 400, 600,

800, and 1000ms in the eight patients with electrodes implanted in the left hemisphere.

To obtain a single number at each electrode for each model (each component is

associated with a distinct model), the weight magnitudes (absolute values) were

summed over time. Because the number of electrodes and their placement varied

across participants, we projected these sums onto a standard MNI cortical surface and

smoothed along the surface with a 4mm Gaussian kernel before averaging across

participants. Points on the surface that are associated with data from fewer than six

participants are excluded from analysis (i.e., cortical areas outside the red-line contour

shown on surface plots in Figure 6a). To determine which sums are larger than

expected by chance, the data for each participant within each window was fit to 1,000

random row-wise permutations of the target structure. Each of these solutions were

projected onto the MNI surface as described above, resulting in 1,000 surface maps per

participant. Then we sampled a map from each participant to simulate one "experiment",

Figure S6. Significant vertices on the standard MNI N27 surface reconstruction displayed with AFNI SUMA for eight patients with left lateralized language (confirmed with the WADA test). a) RSL model coefficients (multi-task linear regression with grOWL regularization) associated with points in MNI space were projected onto and smoothed along the surface with a 4mm Gaussian kernel, separately for dimensions 1 and 2. This was repeated for 10,000 group-level maps simulating the null distribution at each vertex by permutation. Only points on the surface where data from 6 or more patients is available are considered; vertices meeting this criterion are contained within the red contour. Vertices with average weight magnitude larger than 9,500 of the 10,000 group-level values in the permutation distribution for that vertex are shown: points that meet these criteria for dimension 1 are shown in yellow, for dimension 2 are shown in blue, and for both are shown in green. b) Number of electrodes contributing to the data at each vertex after applying a 4mm Gaussian kernel. c) Tabulation of significant vertices.

and the data were summed and averaged as above. This was repeated 10,000 times to

obtain a group-level null distribution (Stelzer et al., 2013).

Figure S6a displays the points on the cortical surface where the real average is

larger than 9,500 of the values in this null distribution. Points on the surface that are

associated with large model weights for the first component (but not the second) are

shaded yellow; points that are associated with the second component (but not the first)

are shown in blue. Points on the surface that are associated with large weights for both

components in the same model are shown with green. Substantial overlap is observed

in all windows, with overlap increasing with window length (**Figure S6c**). Both semantic

dimensions are encoded across the vATL with little obvious functional localization, and

the apparent contributions of a given area to each dimension appear to change

depending on the size of the decoding window. The results are consistent with the view

that many vATL regions contribute to both dimensions of semantic structure, though

they do not rule out the possibility that there exist small local regions independently

encoding each dimension scattered across cortex.

1522

1523   **Appendix H: Predicted embeddings**

1524   Representational similarity learning (RSL) involves decomposing a target

representational similarity matrix (RSM) into orthogonal components (e.g., with singular

value decomposition; SVD), composing a target embedding from a small selection of

those components that explain most of the variance in the full matrix, and then training a

linear model to decode each component in the target embedding. In our work the target

embedding was three-dimensional (first three singular vectors of the RSM), and training

and testing was performed with 10-fold cross validation such that every stimulus was a

test item once. A model of the embedding determined with respect to the training set

can be used to map spatiotemporal patterns of neural activity to predicted positions

along each dimension of the embedding space (i.e., a coordinate referring to a point

within the embedding space), including patterns associated with items assigned to the

test set and therefore excluding from the training set. Test set predictions are obtained

by weighting and then summing the neural features in the way that minimized the

difference between predicted and target coordinates for *training set* items, and so reflect

where the model expects these items to be located based on their neural pattern

similarity with items in the training set.

1540   By collecting these predicted coordinates for test set items across the 10 cross

validation folds, we can visualize how each of the 100 items (50 animate, 50 inanimate)

is positioned along each of the three target dimensions by models trained over different

windows of time, averaged over the 10 participants. This is visualized in Figure S7. As

expected, given the results reported in Figures 4 – 6 in the main document and the

proportion of variance in the target RSM attributed to each dimension, separation of

animate from inanimate items along the first dimension is most salient in these

predicted embeddings. This separation progresses over the first 300ms and remains

relatively stable thereafter. Categories do not clearly separate along dimensions 2 or 3;

there is variance along this dimension that systematically correlates with the target

structure (Figure 4), but this presentation of predicted embeddings is not designed to

convey how within-category variance (e.g., among land animals) is correlated with each

target dimension. That there is stretching along dimensions 2 and 3, but not clear

category separation, may reflect the smaller effect size of the within-domain correlations

we report in the main paper, but is also consistent with the within-domain variance

decoded from the ECoG signal being graded and continuous within sub-categories, not

driven by ever-more minute category fractionization.

Figure S7. Predicted semantic embeddings for the 100 stimuli, averaged over 10 participants. Dots and shaded areas enclosing dots belonging to the same category are colored as in Figure 1. Which items belong to each category is reported in Appendix A, Table S1. Shaded areas were drawn by identifying the convex hull for the set of points and tracing the hull with a spline.

1557