Representational similarity learning reveals a graded multi-dimensional semantic space

in the human anterior temporal cortex

Christopher R. Cox[1][※][*], Timothy T. Rogers[2][※][*], Akihiro Shimotake[3][*], Takayuki Kikuchi[4],

Takeharu Kunieda[4,5], Susumu Miyamoto[4], Ryosuke Takahashi[3], Riki Matsumoto[7][*], Akio Ikeda[6][†],

Matthew A. Lambon Ralph[8][†][*]

[※] Co-first author; [†] Co-senior author; [*] Corresponding author

Affiliations:

1. Dept. of Psychology, Louisiana State University, Audubon Hall, Baton Rouge, LA 70803
2. Dept. of Psychology, University of Wisconsin, Brogden Hall, Madison, WI 53706
3. Dept. of Neurology. Kyoto University Graduate School of Medicine, Kawaharacho, Shogoin,
Sakyo-ku, Kyoto, 606-8507, Japan
4. Dept. of Neurosurgery, Kyoto University Graduate School of Medicine, Kyoto, Japan
5. Dept. of Neurosurgery, Ehime University Graduate School of Medicine, Shizukawa Toon
city, Ehime, 791-0295, Japan
6. Dept. of Epilepsy, Movement Disorders and Physiology, Kyoto University Graduate School
of Medicine, Kyoto, Japan
7. Div. of Neurology, Kobe University Graduate School of Medicine, Kusunoki-cho, Chuo-ku,
Kobe, 650-0017, Japan
8. MRC Cognition and Brain Sciences Unit, 15 Chaucer Rd., Cambridge, UK, CB2-7EF

Corresponding Authors:

• Christopher R. Cox (chriscox@lsu.edu) 0000-0001-8287-3865
• Timothy T. Rogers (ttrogers@wisc.edu) 0000-0001-6304-755X
• Akihiro Shimotake (smtk@kuhp.kyoto-u.ac.jp) 0000-0003-3777-685X
• Riki Matsumoto (matsumot@med.kobe-u.ac.jp) 0000-0003-3985-9210
• Matt Lambon Ralph (Matt.Lambon-Ralph@mrc-cbu.cam.ac.uk) 0000-0001-5907-2488

Open access: For the purpose of open access, the UKRI-funded author MALR has applied a

Creative Commons Attribution (CC BY) license to any Author Accepted Manuscript version

arising from this submission.

Keywords: Semantic memory, ECoG, temporal lobe, decoding, representational similarity

analysis, RSA, network RSA

31   **Abstract**

Neuro-cognitive models of semantic memory have proposed that the ventral anterior temporal

lobes (vATLs) encode a graded, distributed, and multidimensional semantic space—yet

neuroimaging studies seeking brain regions that encode semantic structure rarely identify these

areas. In computer simulations we show that this discrepancy may arise from limitations of a

commonly-used multivariate analysis, and introduce a new approach, *representational similarity*

learning (RSL), that resolves these. We then use RSL to decode semantic structure from ECoG

data collected from the vATL cortical surface while participants named line drawings of

common items. The results reveal a graded, multi-dimensional semantic space encoded in neural

activity across the vATL, which evolves over time and simultaneously expresses both broad and

finer-grained semantic structure amongst animate and inanimate concepts. The work thus

resolves the apparent discrepancy within the semantic cognition literature and suggests a new

approach to discovering representational structure in neural data more generally.

44   **Conflict of interest**

45   The Department of Epilepsy, Movement Disorders, and Physiology, Kyoto University Graduate

46   School of Medicine conducts Industry-Academia Collaboration Courses, supported by Eisai Co.,

47   Ltd, Nihon Kohden Corporation, Otsuka Pharmaceutical Co., and UCB Japan Co., Ltd.

49   **Introduction**

If you encounter a wolf when walking home through a dark wood, your mind readily

accomplishes some remarkable feats: it anticipates the animal's likely behavior, perhaps slinking

closer toward you; it assigns the thing a name, which you might shout to alert others ("wolf!");

and it directs you to change your own plans, maybe running back down the path. These feats

arise from the human ability to discern conceptual structure—to realize that the wolf, despite its

resemblance to friendly dogs in town, is nevertheless a quite different sort of animal.

This ability to represent and exploit conceptual structure is central to human semantic

cognition. Such structure is *graded* in that similarities vary along a continuum: wolves are highly

similar to coyotes, partially similar to elk, and quite distinct from birch trees or canoes. It is also

multidimensional in that concepts vary along myriad independent components: wolves and dogs

are similar in their shapes, parts, movements, and phylogeny, but different in their behaviors,

habitats, and diets. To capture these properties of knowledge, computational approaches to

semantics often represent concepts with *vector spaces*: the meaning of a word or image is

expressed as a point in an *n*-dimensional space (or equivalently as an *n*-dimensional vector) such

that the proximity between points expresses the similarity in meaning between the denoted

concepts. Cognitive science and machine-learning offer many techniques for estimating semantic

vector spaces from natural language [1], feature norms [2], or similarity-judgments [3], and these

methods have provided a critical empirical foundation for studying human conceptual

knowledge.

A central question for cognitive neuroscience concerns how semantic vector spaces are

encoded in neural activity, but progress has been hampered by contradictory findings across

different literatures. Convergent evidence from neuropsychology, clinical neurophysiology,

transcranial magnetic stimulation, and computational modeling suggests that the anterior

temporal lobes (ATLs) encode graded and multidimensional conceptual similarity structure [4-9],

but a direct empirical test of this hypothesis—multivariate decoding of functional neuroimaging

data—has yielded decidedly mixed results. A few studies have found ATL areas that encode

conceptual structure in neural activity [10-14], but others have observed such structure only in

posterior temporal areas [15-22], or within a left-lateralized peri-sylvian network [12,23-25], or even

across the entire cortex *except* the ATL [26].

79   This paper considers the possibility that the gap between imaging and other literatures

arises because the most common analytic technique employed in these studies—representational

similarity analysis (RSA)—is not actually well-suited to finding _graded_ _multidimensional_

structure. This may seem surprising, since RSA was developed specifically as a tool for finding

cognitive similarity structure in imaging data [27]—yet the reliance of the approach on

unsupervised correlation places non-trivial limits on the kinds of signal it can detect. Study 1

reports simulations assessing how these limitations will influence discovery of neuro-semantic

representations, and introduces a new approach to neural decoding, *representational similarity*

learning RSL; [28], designed to address them. Study 2 considers how RSL can be applied to

decoding of very large neural datasets by exploiting patterns of *structured sparsity* present in

neural signals. We show how such patterns can inform model fitting in RSL, then use the

approach to decode graded multidimensional semantic structure from electro-corticography

(ECoG) recorded from the surface of human vATL. The results resolve the contradiction in the

literature and suggest a new path for multivariate neural decoding more generally.

93   **Results**

94   **Study 1: Simulation experiments.**

95   RSA aims to find sets of neural features—voxels, electrodes, or other measurements of

neuro-physiological activity—whose responses to various cognitive events (e.g., the perception

of a stimulus) jointly encode an independently-measured target structure. Typically, the target

structure is a *representational similarity matrix* (RSM)[1] in which the rows and columns

correspond to the different stimuli in an experiment and the entries indicate the

cognitive/representational similarities between stimuli. For semantic representation, entries in the

target RSM indicate similarity of meaning among pairs of concepts as estimated from behavioral

or corpus data. To determine if a set of neural features (e.g., voxels, electrodes, EEG sources,

etc.) encodes the target similarities, the experimenter estimates the pattern of neural activity

evoked by each stimulus and computes the pairwise similarities between these to create a *neural*

similarity matrix (NSM). Correlations between the RSM and NSM are computed separately for

each participant, and brain regions where these are reliably greater than zero are interpreted as

encoding the target structure.

This approach faces three challenges when used to find *graded*, *multidimensional*

structure in neural codes. First, reliable correlations with a continuous-valued target RSM can

arise even if the neural response is discrete or categorical (e.g., equally active for items in one

semantic category and equally inactive for a different category). Thus, a positive result does not

indicate that the neural response encodes *graded* structure even if such structure is present in the

target RSM. Second, when computing the correlation, all neural features are equally weighted

---

[1] Many studies employ the term *representational dissimilarity matrix* or RDM instead. Since the approach is called "representational similarity analysis," and because similarity/dissimilarity are inversely related, we prefer *representational similarity matrix* or RSM.

and no parameters are fit, so the approach may yield a null result even if the target structure *is*

encoded by a weighted subset of the neural features under consideration. Thus, a negative result

does not indicate that the neural features carry no target information. Third, correlation is

inherently one-dimensional, so in itself cannot provide evidence of multidimensional structure in

the neural response. Simulation 1 assessed how these characteristics of RSA will influence

discovery of neuro-semantic representations by applying the approach to simulated neural data

encoding different aspects of a target similarity matrix.

Simulation 1: Limitations of RSA. The target RSM was computed from semantic feature

norms for 100 items, half animate and half inanimate, collected in prior work [29]. The feature

vectors for each item were aggregated in a matrix with rows indicating words and columns

indicating features and entries indicating whether the referent of the word possess that feature.

Matrix columns were mean-centered and the RSM was computed as the cosine similarity for all

pairs of row vectors.

To understand the latent structure of the RSM, we used singular value decomposition

(SVD) to extract three components accounting for 90% of the variance in the full matrix.

Figure 1 shows the coordinates for all 100 items on each latent dimension, color coded by

semantic category (see SM). The decomposition reveals graded semantic structure along each

dimension. The first separates animate from inanimate items but also individuates subcategories

in each domain. The second strongly differentiates subcategories of animals but also weakly

distinguishes inanimate subcategories. The third differentiates the inanimate items, though the

resulting spread is less "clumpy" than within animate items as commonly found with such data [5].

Figure 1. Coordinates of the 100 stimuli in the three-dimensional singular-value-decomposition of the of the semantic similarity matrix. Colors show category membership within each domain. Component 1 separates animate from inanimate items, but also separates animate sub-categories. Component 2 largely separates animate sub-categories, while component 3 largely separates inanimate sub-categories.

We investigated what results RSA would yield when applied to a neural signal known to encode some aspects of this underlying semantic structure. Specifically, we created five simulated neural datasets, each capturing a different aspect of semantic structure in the target RSM. For each dataset we simulated the responses of 24 hypothesized neural features (e.g., the BOLD response over 24 voxels in an ROI, or the mean evoked response at each of 24 electrodes) to the 100 stimuli. Half of the simulated neural features encoded true semantic information about the target items while half adopted random values sampled from a uniform distribution in the same range. The five datasets varied in which aspects of the target matrix they encoded, as illustrated in the schematic plots in **Figure 2A.** In the *binary condition*, all signal-carrying neural features adopted one state (-1 or 1) for animate items and the opposite state for inanimate items. Thus, the code was both one-dimensional and discrete. In three *one-D conditions*, all signal-

carrying neural features only encoded a single latent component of the target RSM—either the

first, second, or third singular vector as shown in **Figure 1**. Thus, each encoded *graded* similarity

structure but only *one* dimension of variation. In the *full structure condition,* the signal-carrying

units jointly encoded all three latent components of variation in the target RMS—thus the code

was both graded and multidimensional.

Figure 2. Simulation results. A. Each plot illustrates different ways that a neural response might encode some aspects of a target
RSM, schematized in the rightmost plot ("All"). Vertical bars show the hypothesized responses of neural features to various animate
and inanimate stimuli (red more active; blue less active; gray random) while the squares show the neural similarity matrices that
would then result (red high similarity, blue low). All conditions encode some components of the full RSM and so should be detected
by a multivariate method seeking semantic structure. B. Curves showing the expected results of standard RSA when used to decode
real semantic structure from the Dilkina norms under different hypotheses about the neural code and increasing amounts of
measurement noise. Dots show the mean correlation while ribbons show the 95% confidence interval. The approach can yield
robust results when the neural signal is discrete and/or one-dimensional, even under substantial noise, and can yield weak or null
results when the neural signal faithfully encodes weaker components of the RSM, even under low-noise conditions. C. Results of
RSL applied to the same simulated data, showing the correlation between true and predicted coordinates for held-out items on each
latent component of the target matrix (columns), for the five different simulation conditions (rows), and computed across all items

(black lines), animate items (red), or inanimate items (green). RSL shows a positive result in each case, identifies which components
of the matrix are present in the neural code, and reveals reliable within-domain decoding only when the neural code expresses
continuous similarity structure.

To examine the results RSA would yield for each kind of neural signal, we distorted the

simulated neural responses to each stimulus with measurement noise sampled from a uniform

distribution centered on 0, then computed the correlation between the simulated NSM and target

RSM. **Figure 2B** shows the results across increasing measurement noise and averaged over 20

runs of the simulation. The binary code showed robust correlations across the full noise-

spectrum, illustrating that RSA can yield a positive result even when the neural code is neither

continuous nor multidimensional. Amongst the one-D codes, RSA showed a strong positive

result if the neural response encoded the first singular vector of the target matrix, but much

weaker results that decayed to zero with increasing noise when the neural response encoded

other components. Thus, RSA can yield null results even when the neural features under

consideration reliably encode target information orthogonal to the primary component of the

RSM. A strong correlation was observed when the neural features encoded all three components

of the target matrix and there was little noise in the signal, but this declined steeply with noise. In

high noise conditions, RSA yielded a more reliable result when the simulated neural response

encoded a binary domain distinction or just the first component of variation. For these scenarios,

all signal-carrying features encode the same information, so noise "cancels out" across features

and the signal remains robust. When the same number of features encode three orthogonal

components, fewer resources are dedicated to each, and corruption from noise more seriously

degrades the signal.

The simulation shows that, when decoding semantic similarity structure of the kind

captured by feature norms, RSA can yield a positive result when the neural response is discrete

and/or one-dimensional, and a null result when the neural response encodes underlying

dimensions of the target matrix beyond the strongest. Thus RSA, as typically deployed, does not

reliably indicate whether a set of neural signals encode the graded, multidimensional semantic

structure existing in a target RSM.

197   *Simulation 2: Decoding with RSL.* These issues led us to consider an alternative approach

designed explicitly to decode graded, multidimensional similarity structure, which we call

representational similarity learning RSL; [28]. Rather than using pairwise similarities in the RSM

as the target values for decoding, RSL first decomposes the matrix into orthogonal latent

components, effectively re-representing each stimulus item as a point in a low-dimensional

semantic space as shown in **Figure 1**. It then fits *decoding models* to predict the coordinates of

each item along each dimension from their evoked neural responses.

204   Simulation 2 assessed whether this approach can reveal the graded and/or

multidimensional structure obscured by RSA. Using the same dataset from Simulation 1, we fit

regression models to predict coordinates of each stimulus along each of the three latent semantic

dimensions shown in **Figure 1**, then assessed model fit using 10-fold hold-out cross validation.

Multidimensional structure in the neural code should be revealed by reliable prediction of

coordinates along more the one latent dimension. To assess whether the neural code captures

graded similarity, we evaluated models fit separately to animate- or inanimate items only. If the

neural signal only categorically differentiates, for instance, animate from inanimate stimuli as

observed, for instance, by [30], then predicted and true values should correlate significantly when

models are fit to all items, but should not correlate when fit to just the animate or just the

inanimate items. Reliable intra- and inter-domain correlations thus indicate that the neural code

captures a graded degree of similarity structure.

Figure 3C shows the correlation between true and predicted coordinates for held-out

items on each of the three target components (columns), for the five different neural coding

scenarios (rows), and computed across all items (black lines), animate items (red), or inanimate

items (green). The pattern of results reveals the information encoded in each simulated neural

response. With the binary neural signal (top row), predicted and true coordinates correlated

strongly for models fit to all items but not separately for animates vs inanimates. With

continuous one-D signals, strong correlations were observed for models fit to all items and

within each domain separately, but only for the dimension encoded by the neural response. When

the neural signal encoded graded multidimensional structure, reliable correlations were observed

on all three latent components, for models fit to all items and fit separately to each domain. Thus

in simulation, the pattern of results uniquely revealed whether the neural signal encodes graded

or discrete structure, and which semantic dimensions it captures.

Study 2: Decoding semantic structure from ECoG using RSL

The simulations show how RSL can test for graded and multidimensional structure where

RSA results are ambiguous. Applying the approach to real brain imaging data, however, faces an

immediate challenge: such technologies produce many more neural measurements than there are

stimuli, so regression models predicting stimulus characteristics from neural data are ill-defined

(i.e., there exist infinite solutions that can perfectly predict outcomes even from random input

data). To find a unique fit without a-priori feature selection, the regression must be *regularized*

to satisfy some additional constraint that will guarantee a single unique solution for model

fitting. For instance, the weight optimization might jointly minimize prediction error and the size

of the model coefficients, measured as the sum of their absolute values (the *L1-norm*). Since this

sum can be minimized by placing zero coefficients on many predictors, this form of

regularization promotes a sparse solution in which only a few predictors have non-zero

coefficients in the final model e.g., [31]. Other regularizers (such as the L2 norm or the elastic net)

enforce different constraints on model fitting, and thus lead to other solutions when applied to

the same dataset [32]. The selection of a regularization function therefore amounts to a prior

hypothesis stipulating how the neural signal is likely to be structured [33].

244   *Regularization with structured sparsity.* RSL applied to real neural data adopts the *group-*

ordered-weighted LASSO or grOWL loss [28], a regularization function designed specifically in

prior work to capture three theoretically-motivated assumptions about the structure of neural

representations. First, it assumes the signal is *sparse*: of all measurements taken, only a relatively

small proportion encode target information of interest, so the regularizer should place zero

coefficients on many predictors (as with L1 regularization). Second, it assumes *redundancy* in

the true signal: neural populations that encode variation along the same dimension will be

correlated in their activity patterns over items. The regularizer should therefore spread similar

coefficients across correlated signal-carrying populations (similar to L2 regularization). Third, it

assumes that signal-carrying populations are unlikely to be "axis-aligned" with the target

semantic space (i.e., where each semantic dimension aligns perfectly and uniquely with

individual neural elements), but more likely encode multiple, varying "directions" within the

space, such that the neural population carries information about the items' coordinates within the

multiple dimensional target space. We will refer to this as the *spanning* assumption, since the

selected neural features span the target representational space but are unlikely to only encode

distinct, individual dimensions. To enforce this assumption, the regularizer should prefer

solutions where coefficients on a given neural feature are either all zero (the feature does not

carry any information) or all non-zero (it predicts some variation along all target dimensions).

All three assumptions can be captured in a single loss function, as follows. Rather than

fitting a separate regression model for each latent component of the target RSM, we instead

predict all latent components (**Figure 3A**) simultaneously by estimating the parameters of a

decoding matrix β (Figure 3C). Suppose the coordinates of n stimuli on r latent semantic

dimensions are stored in matrix $\boldsymbol{Y}_{n \times r}$ while the responses of m neural features to the stimuli are

stored in matrix $\boldsymbol{X}_{n \times m}$. RSL models the entries in $\boldsymbol{Y}$ as the matrix product of the neural

activations in $\boldsymbol{X}$ and the decoding matrix $\boldsymbol{\beta}_{m \times r}$: $\boldsymbol{Y} = \boldsymbol{X}\boldsymbol{\beta}$. Each row of $\boldsymbol{\beta}$ corresponds to one

neural feature (voxel, electrode, etc.), and each column encodes weights for each neural feature

when predicting stimulus coordinates on the corresponding dimension of the target matrix $\boldsymbol{Y}$.

With this setup, the assumptions about neural signal just listed can be formalized as constraints

on the structure of the decoding matrix $\boldsymbol{\beta}$ (**Figure 3D**). To capture the sparsity and spanning

assumptions, $\boldsymbol{\beta}$ is constrained to be *row-sparse*: most rows have all zero values (sparsity), and

the rest have all non-zero values (spanning). To capture the redundancy assumption, highly

correlated and signal-carrying neural features receive similar row-vectors in $\boldsymbol{\beta}$ (**Figure 3D**). A

formal description of the decoding model and grOWL regularizer, including a definition of the

loss and explanation of how it encourages these properties in the decoding matrix, are provided

in the Supplementary Materials. Further analysis and proofs were described by [28]. **Figure 3**

shows the full workflow decoding semantic structure from ECoG data.

Figure 3. Representational similarity learning. A. To generate the target structure for decoding, semantic feature vectors for each of n items are mean-centered and converted to a cosine similarity matrix $\mathbf{S}_{n \times n}$ of approximate rank r. This is decomposed into matrix $\mathbf{U}_{n \times r}$ containing r orthogonal singular vectors and diagonal matrix $\mathbf{D}_{r \times r}$ containing singular values for each vector. The product $\mathbf{U}\sqrt{\mathbf{D}}$ is an $n \times r$ matrix whose columns contain r root-weighted singular vectors that are the target of the decoding model. Note that the product of this matrix with its transpose provides an estimate of the original matrix $\mathbf{S}_{n \times n}$. B. Neural responses in a picture-naming task are recorded for each stimulus as intra-cranial voltage potentials collected at 1000 Hz over electrodes implanted in vATL. Data are concatenated across electrodes to create a single m-dimensional "neural feature vector" for each stimulus, where m is the total number of electrodes times the size of the decoding window in milliseconds. All such vectors are compiled into a neural feature matrix $\mathbf{X}_{n \times m}$ which contains the predictors for the decoding model. C. The target structure $\mathbf{U}\sqrt{\mathbf{D}}$ is then modeled as the product of the neural feature matrix $\mathbf{X}$ and a decoding matrix of regression coefficients $\boldsymbol{\beta}$ whose values are chosen via gradient descent to minimize prediction error plus the regularization penalty $H(\boldsymbol{\beta})$ scaled by the weighting parameter α. D. Definition of the group-ordered-weighted LASSO (grOWL) regularization function and illustration of the structure it promotes in the decoding matrix.

With this overview we can consider how RSL can be applied to assess whether neural

data encode a multidimensional and graded similarity space. Parameters in $\boldsymbol{\beta}$ are estimated for a

batch of training data using regularized regression. The decoding model is then applied to predict

the coordinates of held-out items along each dimension in the target representation space. If

predicted and true coordinates for held-out items correlate reliably with more than one

dimension, the neural signal must encode multidimensional structure. To assess whether the

neural code captures graded similarity, we additionally fit and evaluate models separately for

animate and inanimate items, as in the simulation. If the neural signal only categorically

differentiates animate from inanimate stimuli as suggested by the RSA analysis in [30], then

predicted and true values should correlate significantly across all items, but not across just the

animate or just the inanimate items. Observation of both inter- and intra-domain correlations thus

indicates that the neural code captures a graded degree of similarity structure. Finally, to assess

how well the decoder recovers the target semantic similarities, the predicted coordinates for held-

out items can be used to estimate semantic distances between stimulus pairs. These estimates can

then be correlated with true semantic distances, similar to standard RSA.

ECoG experiment. We applied this approach to an ECoG dataset where prior work using

RSA found little evidence for graded multidimensional structure [30]. While the authors did find a

reliable correlation between a semantic RSM and the NSM in the anterior ventral temporal

cortex, further analysis showed that the NSM correlated equally well with a binary matrix

capturing only stimulus animacy (similar to the binary code in Simulation 1) and did not

correlate at all with a matrix capturing within-domain semantic structure (similar to the 1D codes

in Simulation 1). These results do not seem to be in keeping with the hypothesis that vATL

activity encodes a graded, multi-dimensional semantic space; accordingly, we assessed whether

such a space could be recovered from the same data using RSL.

The dataset contains voltages measured from grid electrodes implanted in the surface of

left (8) or right (2) vATL in ten patients undergoing preparation for intractable epilepsy (9) or

brain tumor (1) while they named line drawings depicting the 100 items described in Study 1.

Each patient had between 6 and 32 electrodes (mean of 20) covering vATL. The dataset

included, for each stimulus, voltages measured at each electrode over a 1s window from stimulus

onset and downsampled to 100 Hz. Thus, for a participant with 20 electrodes, each stimulus was

associated with a 2,000-element vector of voltages (20 electrodes x 100 time points). See

Methods for further detail about the patients, stimuli and experimental procedure.

All models were fit and evaluated using a nested 10-fold cross-validation procedure: an

inner loop performed on 90% of the data was used to select model hyper-parameters; a single

model was then fit using the best hyper-parameters and was evaluated on the remaining 10% of

data. This procedure was run 10 times for 10 different final hold-out sets. In each fold, the fitted

model was used to predict coordinates of the held-out items on the three latent semantic

dimensions. The predictions were then aggregated across folds to create a single matrix of

predicted coordinates for each item when it was held out from model fitting. Separate models

were fit and evaluated independently for each participant, and we assessed whether the mean

correlation between predicted and true coordinates was reliably positive across participants.

Further model fitting and evaluation details appear in the Methods.

Our analyses closely followed the simulations: correlations between predicted and true

coordinates on each dimension were computed for all 100 stimuli, just the 50 animate items, or

just the 50 inanimate items. To determine whether the observed correlation was statistically

reliable, we compared it to bootstrapped null distributions generated via permutation testing [34; see

Methods], using a familywise error rate of 0.05. Finally, to understand the effects of regularization

with structured sparsity (grOWL) vs. more standard techniques, we compared models fit with

grOWL regularization to those fit with L1 (LASSO) regularization.

345   **Figure 4**(top) shows results from decoding the full 1s time-window. Models fit with

346   grOWL reliably decoded the first and second latent components of the semantic matrix, both

347   when fit to all items and just to animate items. Thus, grOWL reveals graded, multidimensional

348   semantic structure in ECoG signals recorded from ventral ATL. Regularization with the LASSO

349   showed similar decoding of the first latent component but null results for the second and third,

350   suggesting that additional constraints from grOWL aided in the discovery of semantic structure.

Figure 4. ECoG decoding results. Correlation between true and predicted coordinates along each latent dimension (columns) for models fit to all items (green), animate items only (orange), or inanimate items only (blue), and regularized with grOWL or LASSO. Bars show standard errors. Colored bars / filled circles indicate reliable decoding with Westfall-Young FWER < .05 for all points in a panel. Top row: grOWL and LASSO model performance when trained on the full 1000-ms trial epoch. Middle row: grOWL model performance within opening windows. Bottom row: LASSO model performance within opening windows.

To see how this structure emerges in the ECoG signal over time, we conducted an

"opening window" analysis in which the same procedure was applied to an increasingly wide

aperture of data, beginning with just the first 50 ms post-stimulus, extending to 100 ms, then

growing by 100 ms up to 1000 ms. At each window models were fit and evaluated as just

described. The results showed reliable decoding of the first dimension by 200 ms, but only for

models fit to all items, suggesting an early differentiation of animate from inanimate items. By

300 ms, models also reliably decoded component-1 variation when fit separately for just animate

or just inanimate items. Decoding accuracy along component 1 continually improved with wider

windows for models fit with all items or animates alone, but not for models fit only with

inanimate items. Decoding along the second component was not observed until 400 ms (for

animates only) or 500 ms (for all items). Decoding along the third (weakest) component of the

target matrix was not observed at any time point. Models fit with LASSO again revealed reliable

decoding of only the first latent dimension, and only for models fit to all data or just animates.

Finally, we considered how well the decoding model recovers true semantic similarities

between stimuli by reconstructing the pairwise similarity matrix from the predicted coordinates

of held-out items across all three dimensions, then correlating these decoded similarities with the

best possible reconstruction (i.e., similarities expressed by the three singular vectors/values of

the true RSM; results for the original full-rank matrix are similar and shown in SM). For

comparison to the prior RSA analysis of the same dataset [30], models were fit and evaluated on a

100 ms moving window, beginning at 0 ms from stimulus onset and advancing in 50 ms

increments (see Methods). At each window, predicted coordinates for all items were generated

using the nested cross-validation procedure described earlier and concatenating the predictions

for each hold-out set across folds. The predicted coordinates were used to compute predicted

similarities between all stimulus pairs. Each row of the resulting matrix contains predicted

similarities between an item and all other items. We then computed, for each row, the correlation

between the predicted and true similarities, and averaged these correlations across (1) all rows,

(2) just the animates or (3) just the inanimates. The full procedure was carried out independently

for each participant at each time-window. Correlation coefficients in each condition (all items,

animates, inanimates) were then averaged across participants at each time-window and compared

to a bootstrapped permutation-based null distribution using a familywise error-rate of p < 0.05.

387   The results are shown in **Figure 5** (left). Filled circles indicate where predicted/true

correlations are reliably non-zero relative to a bootstrapped permutation-based null distribution

with a familywise error-rate of p < 0.05. Reliable correlations were observed from 100 – 150 ms

post-stimulus onward, whether computed across all items, within domain only, or between-

domain only. **Figure 5** (left) also shows the mean correlation (across participants) between RSM

and NSM at each window reported in Y. Chen et al.'s [30] RSA analyses of the same data. While

reliably positive correlations were observed from 200 ms onward, the correlation coefficient was

about 1/10th the magnitude observed with RSL.

Figure 5 Correlation between predicted semantic similarities and the best-possible similarities reconstructed from the first three
singular vectors/values of the true matrix. Considering all pairwise similarities (left panel black line), predictions from RSL show
much stronger correlations with the true structure than observed in a previous study using searchlight RSA (left panel gray line;
see [30]). Moreover, where the prior study found no evidence for within-domain semantic structure in these data, decoding models
fit with RSL reliably predict semantic similarities both within (red lines) and between (green lines) conceptual domains, for both
animate (middle panel) and inanimate (right panel) stimuli, from about 100 – 200 ms post-stimulus onward.

To assess whether RSL models capture structure for both animate and inanimate items,

we computed the same three metrics separately for each domain. First considering just the

animates, we computed the correlation between true and predicted similarities to all other items,

other animate items (i.e., same domain), or inanimate items (i.e., other domain). The results in

Figure 5 (middle) show reliable decoding in all three cases, albeit at only a few time-windows

for similarities from animates to inanimates. Applying the same analysis to inanimates, we

observed reliable decoding of similarities to all items, same-domain items, and other-domain

items from about 200 ms post-stimulus. Note that the weakest reliable correlations are still about

double the magnitude of those observed in the Y. Chen, et al. [30] study using RSA.

411   **Discussion**

We introduced this paper with a puzzle: neuropsychology, clinical neurophysiology,

TMS and computational modelling all suggest that the vATLs encode a continuous

multidimensional semantic space, but multivariate analysis of brain imaging data often leads to

quite different conclusions. In simulation we showed that the puzzle might reflect more general

limitations of RSA, which can produce positive results even if the underlying neural code is

discrete and one-dimensional, or negative results even if the neural code does capture latent

structure in the target matrix beyond the first component. RSL addresses these limitations by

using regularized regression to predict coordinates of stimuli along the latent dimensions of the

RSM. For application to large neural datasets, we illustrated how hypothesized patterns of

structured sparsity in the neural signal can constrain model fit via grOWL regularization and

applied this approach to discovery of semantic structure in an ECoG dataset where prior work

using RSA found only a binary animacy code. In contrast, RSL uncovered a graded and

multidimensional semantic space capturing similarities within and between animate and

inanimate domains—reconciling the apparent discrepancy between neuroimaging and results

yielded by other methodologies.

427   We note that decoding of intra-domain similarities was always more robust for animate

compared to inanimate items. Considering each dimension separately, within-inanimate

decoding was only reliable for one time window on the first latent dimension. When predicting

pairwise distances, correlations with true similarities were always smallest for within-inanimate

structure (i.e., the "other domain" correlations in the middle panel of **Figure 5**, and "same

domain" correlations in the rightmost panel). We attribute this to differences in the similarity

structures of animate and inanimate concepts. Semantic subcategories of inanimate objects are

only weakly differentiated, not just in the current dataset, but in norming studies more generally

and in other approaches to characterizing semantic structure e.g., [35,36-38]. Indeed, this difference

in statistical structure is precisely what leads, under some theories, to apparent category-specific

patterns of semantic impairment [5,39] and functional activation [40]. The differences can be seen in

Figure 1, where animate items fall into somewhat well-differentiated subcategories in

dimensions 1 and 2 while inanimates are uniformly distributed with no clear subclusters even

along dimension 3. Indeed, pairwise similarities reconstructed from the first three singular

vectors of the full semantic matrix are more accurate for animate than inanimate items (see

SM3). Thus, the structure of the semantic matrix itself *requires* that decoding be worse within

inanimates than within animates, precisely because inanimates are less well-structured. Yet

despite this intrinsic disadvantage, within-inanimate similarities were still reliably decoded over

many time-windows, illustrating that neural signal in vATL does express some intra-domain

semantic structure even for inanimate stimuli. In summary, the results suggest the vATLs encode

a multidimensional representation space that captures the conceptual similarities existing

amongst a variety of different concepts including both animate and inanimate items [6,9,41]. Better

decoding within animates simply reflects the fact that animate subcategories are better-

differentiated, so that intra-domain similarities are better-approximated by a low-rank

decomposition.

We further note that multidimensional structure was only discovered with grOWL

regularization—that is, when the decoding model was constrained to be sparse overall, with

correlated neural features receiving similar weights, and with weights on all dimensions

encouraged to be all-zero or all-nonzero. The observation is important for two reasons. First,

consistent with other recent work [32], it shows that the form of model regularization matters

critically to conclusions about information encoded in the neural signal. Simple regularization

with the L1 norm was insufficient to reveal more than one dimension of structure in the neural

code. Second, it suggests that different dimensions in the semantic matrix are *not* encoded

separately by distinct neural populations at the resolution captured by ECoG. The pressure from

grOWL to place either all-zero or all-nonzero coefficients on each neural feature produced

reliable decoding of both the first and second latent dimensions of the semantic matrix—thus

features that predict variation along the first dimension are also likely to carry information about

the second dimension and vice versa. This observation is again consistent with the view that all

signal-carrying neural populations jointly contribute to encoding a single semantic space (see

also analysis of feature distributions across the cortical surface in SM).

Since we only analyzed electrodes situated in vATL, the current data do not shed light on

structure encoded in other parts of cortex. The characteristics of RSA we have identified do,

however, carry additional implications for interpretation of the broader literature. A recent

review [33] identified 34 studies that have applied RSA to the discovery of semantic

representations in the brain, with positive results observed across multiple cortical regions

including posterior temporal cortex [19], angular gyrus [12,42], left perisylvian cortex [25], and

prefrontal cortex [22]. Simulation 1 suggests, however, that RSA will yield a positive result for any

property correlated with the animate/inanimate distinction, including even discrete binary

properties. Many features are confounded with animacy: inanimate items tend to be more

familiar, less visually complex, more associated with action plans, less associated with motion,

more likely to have lines and corners, less predictable from color or texture, etc. see [43 for a review].

Most RSA papers do not report the magnitude of correlation between RSM and NSM where

results are significant, instead focusing on whether the estimated correlation coefficient is

reliably non-zero across participants. As shown in **Figure 5**, this can happen even when mean

correlations are very small. Moreover, several studies use target RSMs with only a small number

of rows/columns—sometimes as few as 5 e.g., [12,19], meaning that correlations are computed

across just 10 cells of the matrix (i.e., the lower triangle of a 5x5 RSM). Such small numbers

increase the likelihood that a small-but-non-zero correlation is driven by some arbitrary property

of the chosen stimuli or categories. Together these observations raise the possibility that the

literature contains misleading positive results—brain areas whose responses encode

unidimensional characteristics weakly confounded with animacy, rather than multi-dimensional

semantic structure. Testing this possibility for various brain areas hypothesized to encode

semantic structure will require analyses similar to the ones we have developed here.

490   **Conclusion**

In cognitive science, semantic representations are often construed as vector spaces that

encoded graded, multidimensional similarity structure amongst the concepts experienced in our

verbal and nonverbal world. Through application of a new technique for mapping

representational similarity in neural activity, we have shown that neural signals in vATL encode

such a space. In so doing, we have identified some limitations of representational similarity

analysis, a widespread technique commonly thought to reveal graded and multidimensional

representational structure. The work resolves an important discrepancy between behavioral and

neuroimaging results in prior work and suggests a new approach to discovering representational

structure in neural data more generally.

<div align="center">**Methods**</div>

Patients and ECoG Acquisition

Ten patients with intractable partial epilepsy (nine) or brain tumor (one) participated in this

study, including two for whom language was not left-lateralized as determined by the WADA

language lateralization test. Chen, et al. [30] provide their background clinical information.

Platinum subdural electrodes (83 per patient on average; range 56 – 107 electrodes) were

implanted in the left (8 patients) or right (2 patients) hemisphere for presurgical evaluation with

inter-electrode distance of 1 cm and recording diameter of 2.3 mm (ADTECH, WI). Between six

and 32 (mean 20) electrodes covered the vATL in each patient. Data were sampled at 1000 Hz

(eight patients) or 2000 Hz (two patients) with a band-pass filter of 0.016 – 300 (eight patients)

or 0.016 – 600 Hz (two patients), though our analyses downsampled these to 100 Hz. All patients

with epilepsy had seizure onset zones outside the anterior fusiform region, except one patient for

whom it was not possible to localize the core seizure onset region. The study was approved by

the ethics committee of the Kyoto University Graduate School of Medicine (No. C533).

Participants provided written informed consent to participate in the study.

Stimuli and Procedure

One hundred line drawings (50 animate and 50 inanimate items) were obtained from

previous norming studies (Morrison et al., 1997; Snodgrass & Vanderwart, 1980). See Chen, et

al. [30] for a complete list. Animate and inanimate stimuli were matched on age of acquisition,

visual complexity, familiarity, and word frequency, and had high name agreement. Each stimulus

was presented on a computer screen for 5 seconds, one after another with no interstimulus

interval, once during each of four sessions (four times in total). Each session proceeded in a

different random order. Participants were instructed to name each item as quickly and accurately

as possible. Participants were video and audio recorded during the experiment. Video was used

to monitor eye fixations and general attention to the task. The mean response latency was

1190 ms.

Semantic similarity structure and dimensionality reduction

Each of the 100 images used in the picture-naming task refer to concepts that have been

included in prior semantic feature norming studies (Dilkina & Lambon Ralph, 2013; McRae et

al., 2005). From these we constructed binary semantic feature vectors indicating which features

were judged to be true of each concept. The feature vectors for each concept were aggregated in

a matrix with rows indicating concepts and columns indicating features and entries indicating

whether the concept possess that feature. Matrix columns were mean-centered and the similarity

between all row vectors was then estimated as the cosine of the angle between them:

$S_{i,j} = (x_i^T x_j) / \sqrt{x_i^T x_i \times x_j^T x_j}$. The resulting symmetric cosine similarity matrix is the full-rank

semantic similarity structure among concepts. The full-rank structure was then embedded into a

3-dimensional metric space by applying singular value decomposition to the corresponding

cosine distance matrix $1 - S$. The low-dimensional embedding, shown in **Figure 1**, accounted

for 90% of the variance in the full distance matrix.

ECoG data preprocessing

Preprocessing was performed in MATLAB. Data were downsampled to 100 Hz by

averaging measurements within 10 ms boxcars. A prior study applying pattern classification to

these data found near identical results when analyzing raw voltages versus voltages referenced to

the electrode beneath the galea aponeurotica or to the scalp electrode on the mastoid process

contralateral to the side of electrode implantation (Rogers et al., 2021). For this reason, and

because the location of the reference electrode varied across patients, we analyzed all voltages

without referencing. For each stimulus we retained data for 1000 ms from stimulus onset. While

the trial epoch may include the onset of articulation toward the end, the critical results cannot

reflect such motor activity since all key phenomena are observed early in the epoch. Baseline

correction was not performed. The mean voltage at each electrode for each stimulus was

computed across the four repetitions. Voltages from different electrodes were concatenated into a

row vector and arranged in a neural data matrix with each row containing the vector of voltages

for one stimulus sampled from multiple electrodes over time. We rejected columns and then

rows where the marginal mean was and more than five standard deviations from the average

marginal mean to censor extreme outliers.

Representational similarity learning (RSL) analysis

RSL decoding models regularized with either grOWL or the L1-norm were fit and

analyzed in MATLAB v9.5 (2018b) [44] using the Whole-brain Imaging with Sparse Correlations

(WISC) toolbox [45], which implements the approach as a multitask variant of group ordered

weighted L1-regularized regression grOWL; [28,46]. Supplementary Materials provide a formal

description of the grOWL regularization and its application to neural decoding.

Fitting a decoding model regularized with grOWL requires specification of two hyper-

parameters, λ and w, which govern the strength with which the decoding matrix is pressured to

be row-sparse (λ) with similar weights across correlated neural features (w). The choice of

hyperparameters was determined by ten-fold nested cross-validation for each model fit. The 100

stimuli were randomly divided into ten subsets, each containing five animate and five inanimate

items. On each of the ten outer-loop folds, one such set was held out (outer-loop holdout). The

remaining nine sets were used to search for good hyperparameter values, using inner-loop cross

validation.

On each inner-loop fold, one of the nine remaining sets was held out (inner-loop

holdout), and a decoding model was fit to the remaining eight sets using a specified pair of

hyper-parameter values. Prediction error (Frobenius norm of true versus predicted coordinates on

latent dimensions) for the fitted model was evaluated on the inner-loop holdout set. This

procedure was repeated once for each of the nine different inner-loop holdouts, all using the

same specified hyperparameter values. We then used mean prediction error across the 9 inner-

loop hold outs as the estimated performance of the decoder when fit using the specified

hyperparameters. Many different hyperparameter values were evaluated in the inner loop, chosen

using the Hyperband procedure [47]. The best-performing values were selected from these and a

final inner-loop model was fit using those parameters and all nine data subsets. This final inner-

loop model was used to predict coordinates on the latent semantic dimension for the outer-loop

holdout set, completing one iteration of the outer-loop cross-validation. The whole procedure

was done ten times, using each data subset once as the outer-loop holdout. Across folds, the

procedure generated predicted coordinates for all 100 items when those items were completely

held out of model fitting. These final predicted, held-out coordinates, computed separately for

each time-window in each participant, were the primary data evaluated in the results.

Statistical thresholding with permutation testing.

The correlation metric we computed to assess model accuracy has many useful

properties: it standardizes means and variances of the target and predicted vectors to focus on

just their covariance. This is especially critical when evaluating animate and inanimate items

separately. Because data are mean-centered, however, cross-validated correlation has a negative

bias when evaluating held-out items [48], so that a null hypothesis of zero with a t-distributed

sampling distribution cannot be assumed. We therefore used permutation testing to generate a

group-level null distribution following the prescription of [34] with 10,000 simulated values for

each test (i.e., each window, for each subset of items, in all analyses).

For every patient, window, and experimental condition, we conducted the full analysis

pipeline just described 100 times, randomly permuting the ordering of the rows in the target

matrix each time. This yielded 100 correlation values for each patient, representing expected

values from our workflow when no reliable relationship exists between neural data and target

matrix (due to the permutation procedure). To estimate the group-level null distribution for each

window and condition, we randomly sampled one permutation-based correlation value from the

100 associated with each patient and averaged these. This was repeated 10,000 times [34]. If m is

the number of values in the permutation distribution and b is the number of values in the

distribution larger than the true correlation value, then the one-tailed p-value can be computed

[49,50] as:

604
$$p = \frac{b + 1}{m + 1}$$

605   To control the family-wise error rate, we applied the Westfall-Young procedure [51,52],

606   which involves taking the maximum value over family members for each of permutation and

607   comparing all test statistics in the family to this single distribution of maximal values.

<div align="center">

Acknowledgments

</div>

Funding: This work was partially supported by MRC Programme grant to MALR and TTR

(MR/R023883/1) and an intramural award (MC_UU_00005/18), and by a European Research

Council grant GAP: 502670428 - BRAIN2MIND_NEUROCOMP. RM reports grants from

MEXT, KAKENHI 22H04777, 22H02945. AS reports grants from MEXT, KAKENHI

22K07537

Author Contributions: Cox conducted all analysis and drafted the manuscript. Rogers and

Lambon Ralph contributed to all aspects of the study design, analysis, and manuscript

preparation. Shimotake, Kikuchi, Kunieda, Miyamoto, Takahasi, Ikeda and Matsumoto were

responsible for ECoG data collection and clinical assessment.

Competing interests: Authors declare no competing interests.

Data and materials availability: All data are available via links in the main text or the

Supplementary Information.

Supplementary Information:

S1. Formal description of the RSL approach

S2. Anatomical distribution of decoding model weights across vATL

S3. Reconstructing item similarity from the SVD coordinates

S4. Correlation between predicted and true semantic distances

626   **References**

1   Pereira, F., Gershman, S., Ritter, S. & Botvinick, M. A comparative evaluation of off-the-

shelf distributed semantic representations for modelling behavioural data. *Cognitive*

Neuropsychology **33**, 175-190 (2016). https://doi.org:10.1080/02643294.2016.1176907

2   McRae, K., Cree, G. S., Seidenberg, M. S. & McNorgan, C. Semantic feature production

norms for a large set of living and nonliving things. *Behavior Research Methods* **37**, 547-

559 (2005). https://doi.org:10.3758/BF03192726

3   Hebart, M. N., Zheng, C. Y., Pereira, F. & Baker, C. I. Revealing the multidimensional

mental representations of natural objects underlying human similarity judgements. *Nature*

Human Behaviour **4**, 1173-1185 (2020). https://doi.org:10.1038/s41562-020-00951-3

4   Rogers, T. T. *et al.* Structure and Deterioration of Semantic Memory: A

Neuropsychological and Computational Investigation. *Psychological Review* **111**, 205-

235 (2004). https://doi.org:10.1037/0033-295X.111.1.205

5   Lambon Ralph, M. A., Lowe, C. & Rogers, T. T. Neural basis of category-specific

semantic deficits for living things: evidence from semantic dementia, HSVE and a neural

network model. *Brain* **130**, 1127-1137 (2007). https://doi.org:10.1093/brain/awm025

6   Patterson, K., Nestor, P. J. & Rogers, T. T. Where do you know what you know? The

representation of semantic knowledge in the human brain. *Nature Reviews Neuroscience*

8, 976-987 (2007). https://doi.org:10.1038/nrn2277

7   Lambon Ralph, M. A. Neurocognitive insights on conceptual knowledge and its

breakdown. *Philosophical Transactions of the Royal Society B: Biological Sciences* **369**,

20120392 (2014). https://doi.org:10.1098/rstb.2012.0392

8   Shimotake, A. *et al.* Direct Exploration of the Role of the Ventral Anterior Temporal

Lobe in Semantic Memory: Cortical Stimulation and Local Field Potential Evidence

From Subdural Grid Electrodes. *Cerebral Cortex* **25**, 3802-3817 (2015).

https://doi.org:10.1093/cercor/bhu262

9   Lambon Ralph, M. A., Jefferies, E., Patterson, K. & Rogers, T. T. The neural and

computational bases of semantic cognition. *Nature Reviews Neuroscience* **18**, 42 (2017).

https://doi.org:10.1038/nrn.2016.150

10   Peelen, M. V. & Caramazza, A. Conceptual object representations in human anterior

temporal cortex. *Journal of Neuroscience* **32**, 15728-15736 (2012).

https://doi.org:10.1523/JNEUROSCI.1953-12.2012

11   Bruffaerts, R. *et al.* Similarity of fMRI activity patterns in left perirhinal cortex reflects

semantic similarity between words. *Journal of Neuroscience* **33**, 18597-18607 (2013).

https://doi.org:10.1523/JNEUROSCI.1548-13.2013

12   Fairhall, S. L. & Caramazza, A. Brain regions that represent amodal conceptual

knowledge. *Journal of Neuroscience* **33**, 10552-10558 (2013).

https://doi.org:10.1523/JNEUROSCI.0051-13.2013

13   Devereux, B. J., Clarke, A. & Tyler, L. K. Integrated deep visual and semantic attractor

neural networks predict fMRI pattern-information along the ventral object processing

pathway. *Scientific Reports* **8**, 10636 (2018). https://doi.org:10.1038/s41598-018-28865-1

14   Martin, C. B., Douglas, D., Newsome, R. N., Man, L. L. Y. & Barense, M. D. Integrative

and distinctive coding of visual and conceptual object features in the ventral visual

stream. *eLife* **7**, e31873 (2018). https://doi.org:10.7554/eLife.31873

15   Chao, L. L., Haxby, J. V. & Martin, A. Attribute-based neural substrates in temporal

cortex for perceiving and knowing about objects. *Nature Neuroscience* **2**, 913-919

(1999). https://doi.org:10.1038/13217

16   Haxby, J. V. *et al.* Distributed and overlapping representations of faces and objects in

ventral temporal cortex. *Science* **293**, 2425-2430 (2001).

https://doi.org:10.1126/science.1063736

17   Martin, A. The representation of object concepts in the brain. *Annual Review of*

Psychology **58**, 25-45 (2007). https://doi.org:10.1146/annurev.psych.57.102904.190143

18   Kriegeskorte, N. *et al.* Matching categorical object representations in inferior temporal

cortex of man and monkey. *Neuron* **60**, 1126-1141 (2008).

https://doi.org:10.1016/j.neuron.2008.10.043

19   Connolly, A. C. *et al.* The representation of biological classes in the human brain.

Journal of Neuroscience **32**, 2608-2618 (2012).

https://doi.org:10.1523/JNEUROSCI.5547-11.2012

20   Sha, L. *et al.* The animacy continuum in the human ventral vision pathway. *Journal of*

Cognitive Neuroscience **27**, 665-678 (2015). https://doi.org:10.1162/jocn_a_00733

21   Martin, A. GRAPES--Grounding representations in action, perception, and emotion

systems: How object properties and categories are represented in the brain. *Psychonomic*

Bulletin & Review **23**, 979 -- 990 (2016). https://doi.org:10.3758/s13423-015-0842-3

22   Carota, F., Kriegeskorte, N., Nili, H. & Pulvermuller, F. Representational Similarity

Mapping of Distributional Semantics in Left Inferior Frontal, Middle Temporal, and

Motor Cortex. *Cerebral Cortex* **27**, 294-309 (2017).

https://doi.org:10.1093/cercor/bhw379

23   Binder, J. R., Desai, R. H., Graves, W. W. & Conant, L. L. Where is the semantic

system? A critical review and meta-analysis of 120 functional neuroimaging studies.

Cerebral Cortex **19**, 2767-2796 (2009). https://doi.org:10.1093/cercor/bhp055

24   Binder, J. R. & Desai, R. H. The neurobiology of semantic memory. *Trends in Cognitive*

Sciences **15**, 527-536 (2011). https://doi.org:10.1016/j.tics.2011.10.001

25   Devereux, B. J., Clarke, A., Marouchos, A. & Tyler, L. K. Representational Similarity

Analysis Reveals Commonalities and Differences in the Semantic Processing of Words

and Objects. *Journal of Neuroscience* **33**, 18906-18916 (2013).

https://doi.org:10.1523/jneurosci.3809-13.2013

26   Huth, A. G., de Heer, W. A., Griffiths, T. L., Theunissen, F. E. & Gallant, J. L. Natural

speech reveals the semantic maps that tile human cerebral cortex. *Nature* **532**, 453-458

(2016). https://doi.org:10.1038/nature17637

27   Kriegeskorte, N., Mur, M. & Bandettini, P. A. Representational similarity analysis -

connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience* **2**, 4

(2008). https://doi.org:10.3389/neuro.06.004.2008

28   Oswal, U., Cox, C. R., Lambon Ralph, M. A., Rogers, T. T. & Nowak, R. D. in *ICML'16*

Proceedings of the 33rd International Conference on International Conference on

Machine Learning.   1041-1049.

29   Dilkina, K. & Lambon Ralph, M. A. Conceptual structure within and between modalities.

Frontiers in Human Neuroscience **6**, 333 (2013).

https://doi.org:10.3389/fnhum.2012.00333

30   Chen, Y. *et al.* The 'when' and 'where' of semantic coding in the anterior temporal lobe:

Temporal representational similarity analysis of electrocorticogram data. *Cortex* **79**, 1-13

(2016). https://doi.org:10.1016/j.cortex.2016.02.015

31   Rogers, T. T. *et al.* Evidence for a deep, distributed and dynamic code for animacy in

human ventral anterior temporal cortex. *eLife* **10**, e66276 (2021).

https://doi.org:10.7554/eLife.66276

32   Cox, C. R. & Rogers, T. T. Finding Distributed Needles in Neural Haystacks. *Journal of*

Neuroscience **41**, 1019-1032 (2021). https://doi.org:10.1523/jneurosci.0904-20.2020

33   Frisby, S., Halai, A. D., Cox, C. R., Lambon Ralph, M. A. & Rogers, T. T. Decoding

semantic representations in mind and brain.   https://doi.org:10.31234/osf.io/6kjtf

34   Stelzer, J., Chen, Y. & Turner, R. Statistical inference and multiple testing correction in

classification-based multi-voxel pattern analysis (MVPA): random permutations and

cluster size control. *NeuroImage* **65**, 69-82 (2013).

https://doi.org:10.1016/j.neuroimage.2012.09.063

35   McRae, K., de Sa, V. R. & Seidenberg, M. S. On the nature and scope of featural

representations of word meaning. *Journal of Experimental Psychology: General* **126**, 99-

130 (1997). https://doi.org:10.1037/0096-3445.126.2.99

36   Devlin, J. T., Gonnerman, L. M., Andersen, E. S. & Seidenberg, M. S. Category-Specific

Semantic Deficits in Focal and Widespread Brain Damage: A Computational Account.

Journal of Cognitive Neuroscience **10**, 77-94 (1998).

https://doi.org:10.1162/089892998563798

37   Tyler, L. K., Moss, H. E., Durrant-Peatfield, M. R. & Levy, J. P. Conceptual Structure

and the Structure of Concepts: A Distributed Account of Category-Specific Deficits.

Brain and Language **75**, 195-231 (2000). https://doi.org:10.1006/brln.2000.2353

38   Garrard, P., Lambon Ralph, M. A., Hodges, J. R. & Patterson, K. Prototypicality,

distinctiveness, and intercorrelation: Analyses of the semantic attributes of living and

nonliving concepts. *Cognitive Neuropsychology* **18**, 125-174 (2001).

https://doi.org:10.1080/02643290125857

39   Devlin, J. T. *et al.* Is there an anatomical basis for category-specificity? Semantic

memory studies in PET and fMRI. *Neuropsychologia* **40**, 54-75 (2002).

https://doi.org:10.1016/S0028-3932(01)00066-5

40   Rogers, T. T. *et al.* Anterior temporal cortex and semantic memory: reconciling findings

from neuropsychology and functional imaging. *Cognitive, Affective, & Behavioral*

Neuroscience **6**, 201-213 (2006). https://doi.org:10.3758/CABN.6.3.201

41   Rogers, T. T. & McClelland, J. L. *Semantic cognition: A parallel distributed processing*

approach. (MIT press, 2004).

42   Fernandino, L., Tong, J.-Q., Conant, L. L., Humphries, C. J. & Binder, J. R. Decoding the

information structure underlying the neural representation of concepts. *Proceedings of*

the National Academy of Sciences **119**, e2108091119 (2022).

https://doi.org:doi:10.1073/pnas.2108091119

43   Chen, L. & Rogers, T. T. Revisiting domain-general accounts of category specificity in

mind and brain. *WIREs Cognitive Science* **5**, 327-344 (2014).

https://doi.org:10.1002/wcs.1283

44   Matlab v. 9.5 (R2018b) (The MathWorks, Natick, MA, 2018).

45   Whole-brain Imaging with Sparse Correlations (Github, doi:10.5281/zenodo.6975270

759   2021).

760   46   Figueiredo, M. & Nowak, R. in *Artificial Intelligence and Statistics.* 930-938.

761   47   Li, L., Jamieson, K., DeSalvo, G., Rostamizadeh, A. & Talwalkar, A. Hyperband: A

762   Novel Bandit-Based Approach to Hyperparameter Optimization. *Journal of Machine*

763   *Learning Research* **18**, 1-52 (2018).

764   48   Zhou, Y., Vales, M. I., Wang, A. & Zhang, Z. Systematic bias of correlation coefficient

765   may explain negative accuracy of genomic prediction. *Briefings in Bioinformatics* **18**,

766   1093-1093 (2017). https://doi.org:10.1093/bib/bbx133

767   49   Edgington, E. S. *Randomization tests. [electronic resource]*. 3rd ed., rev. and expanded.

768   edn, (M. Dekker, 1995).

769   50   Phipson, B. & Smyth, G. K. Permutation P-values Should Never Be Zero: Calculating

770   Exact P-values When Permutations Are Randomly Drawn. *Statistical Applications in*

771   *Genetics and Molecular Biology* **9** (2010). https://doi.org:10.2202/1544-6115.1585

772   51   Alberton, B. A. V., Nichols, T. E., Gamba, H. R. & Winkler, A. M. Multiple testing

773   correction over contrasts for brain imaging. *NeuroImage* **216**, 116760 (2020).

774   https://doi.org:10.1016/j.neuroimage.2020.116760

775   52   Westfall, P. H., Young, S. S. & Wright, S. P. On Adjusting P-Values for Multiplicity.

776   *Biometrics* **49**, 941-945 (1993). https://doi.org:10.2307/2532216

777   53   Yuan, M. & Lin, Y. Model selection and estimation in regression with grouped variables.

778   *Journal of the Royal Statistical Society: Series B (Statistical Methodology)* **68**, 49-67

779   (2006). https://doi.org:10.1111/j.1467-9868.2005.00532.x

780   **Supplementary materials**

781   **S1. Formal description of the RSL approach.**

782   Let S be a symmetric $n \times n$ target matrix of approximate rank r describing pairwise

cognitive similarities amongst n items, which is decomposed via singular-value decomposition

(SVD) into an $n \times r$ matrix U of r orthonormal singular vectors and an $r \times r$ diagonal matrix D

containing the corresponding r singular values (**Figure 2A**). The matrix product $U\sqrt{D}$ then

contains root-weighted singular vectors that can be viewed as encoding the coordinates of each

stimulus within an r-dimensional latent semantic space, while the product of this matrix with its

transpose provides a rank r approximation of the original similarity matrix. That is:

789                        $$S_{n \times n} \cong U_{n \times r} D_{r \times r} U^T = U\sqrt{D} \, (U\sqrt{D})^T$$

790   Let $X_{n \times m}$ be a data matrix recording neural responses to each of n stimuli over m neural

791   features (e.g., voxels in fMRI, electrode voltages at each timepoint in ECoG, etc.). To assess

792   whether some weighted combination of these features jointly encode the target similarities, we

793   seek a *decoding matrix* $\beta_{m \times r}$ such that the matrix product $X\beta$ produces r coordinates for each

794   item, deviating as little as possible from those in target matrix $U\sqrt{D}$. This search can be

795   formulated as the convex optimization:

796                        $$argmin_\beta \left\| U\sqrt{D} - X\beta \right\|_F$$

797   That is, we seek β values that minimize the Froebenius norm (i.e., sum of squared

differences) between the true root-weighted singular vectors $U\sqrt{D}$ and the predicted values $X\beta$.

The optimization essentially computes a simultaneous regression predicting all r coordinates for

each stimulus from weighted combinations of the neural responses they evoke. Each column of

the resulting decoding matrix contains one coefficient for each neural feature and predicts an

item's coordinate along one component of the target matrix $U\sqrt{D}$ (ie, one dimension of the

semantic space).

As noted earlier, there are typically many more neural measurements (predictors) than

stimuli (i.e., target data points)—that is, $m \gg n$. Thus, the optimization just defined is under-

constrained and must be regularized with an additional loss H, itself a function of the coefficient

matrix $\boldsymbol{\beta}$:

808
$$argmin_\beta \left(\left\| U\sqrt{D} - X\beta \right\|_F + \alpha H(\beta) \right)$$

…which is also convex so that a weighted sum of this function and the original

reconstruction loss together yield a single unique solution that can be discovered via gradient

descent. The constant α is a free weighting parameter governing the importance of the

regularization loss relative to the model error.

For RSL we wish to use a regularization function that promotes solutions respecting the

sparsity, redundancy, and spanning assumptions described earlier. Oswal et al. (2016) formulated

a regularizer that accomplishes these objectives by constraining the structure of the decoding

matrix $\boldsymbol{\beta}$ in a single convex loss called the *group ordered weighted LASSO* or *grOWL.* The

approach generalizes both the group LASSO [53] and the ordered-weighted LASSO [46] to favor

solutions that are (1) row-sparse (rows of $\boldsymbol{\beta}$ are either all zero or all non-zero), implementing

both the sparsity and spanning constraints, but (2) with subgroups of selected features sharing

similar coefficients if their activations covary strongly together (implementing the redundancy

constraint). The grOWL loss is specified as:

822
$$H(\beta) = \sum_{i=1}^{m} w_i \left\| \beta_{[i]\cdot} \right\|_2$$

Here m is the number of neural features (rows of $\boldsymbol{\beta}$), $\boldsymbol{\beta}_{[i]\cdot}$ is the row of $\boldsymbol{\beta}$ with the i-th

largest 2-norm (i.e., the i^{th} longest coefficient vector), and w_i is a vector of non-negative, non-

increasing weights (for instance a vector of positive values that decay linearly from an initial

constant). Intuitively the loss works as follows. The first element of the weighting vector w is

stipulated to be as large or larger than all other elements, and this weight is applied to whichever

neural feature has the largest coefficients in the decoding matrix (i.e., the 2-norm or length of the

corresponding row). Thus, the feature with the largest coefficients exerts the largest

regularization cost. The optimization must therefore put the largest weights on the most

informative feature to make it "worth" the high regularization cost. If the most informative

feature is also correlated with many other features, their total cost can be further minimized by

placing similar weights across all such features, since the cost for each such weight declines with

the weight sequence in w. Thus, grOWL spontaneously clusters correlated signal-carrying neural

features and gives these a similar weight, effectively averaging them. Finally, the weighting

vector ensures that coefficients on features that do not reduce error beyond those already selected

will be pressured to zero, ensuring overall sparsity. Formal analysis of the grOWL regularizer

and mathematical proofs of its row-sparse and clustering properties were provided by Oswal et

al. (2016).

S2. Anatomical distribution of decoding model weights across vATL

The decoding results reported in the main paper demonstrate that multi-dimensional

semantic structure can be decoded from LFPs recorded from the vATL, and that decoding the

second semantic dimension depends on regularization via the grOWL. This implies that local

neural populations do not independently encode each semantic dimension, but simultaneously

express multiple orthogonal components of the target semantic matrix. To evaluate whether this

is so, we examined the spatial distribution of weights across electrodes in the decoding models

predicting variation on the first via the second semantic dimensions for opening windows of size

200, 400, 600, 800, and 1000 ms in the eight patients with electrodes implanted in the left

hemisphere. To obtain a single number at each electrode for each model (each component is

associated with a distinct model), the weight magnitudes (absolute values) were summed over

time. Because the number of electrodes and their placement varied across subjects, we projected

these sums onto a standard MNI cortical surface and smoothed along the surface with a 4 mm

Gaussian kernel before averaging across subjects. Points on the surface that are associated with

data from fewer than six subjects are excluded from analysis. To determine which sums are

larger than expected by chance, the data for each subject within each window was fit to 1,000

random row-wise permutations of the target structure. Each of these solutions were projected

onto the MNI surface as described above, resulting in 1,000 surface maps per subject. Then we

sampled a map from each subject to simulate one "experiment", and the data were summed and

averaged as above. This was repeated 10,000 times to obtain a group-level null distribution [34].

Figure S1. Significant vertices on the standard MNI N27 surface reconstruction displayed with AFNI SUMA for eight patients with left lateralized language (confirmed with the WADA test). a) RSL model coefficients (multi-task linear regression with grOWL regularization) associated with points in MNI space were projected onto and smoothed along the surface with a 4 mm Gaussian kernel, separately for dimensions 1 and 2. This was repeated for 10,000 group-level maps simulating the null distribution at each vertex by permutation. Only points on the surface where data from 6 or more patients is available are considered; vertices meeting this criterion are contained within the red contour. Vertices with average weight magnitude larger than 9,500 of the 10,000 group-level values in the permutation distribution for that vertex are shown: points that meet these criteria for dimension 1 are shown in yellow, for dimension 2 are shown in blue, and for both are shown in green. b) Number of electrodes contributing to the data at each vertex after applying a 4 mm Gaussian kernel. c) Tabulation of significant vertices.

Figure S1a displays the points on the cortical surface where the real average is larger

than 9,500 of the values in this null distribution. Points on the surface that are associated with

large model weights for the first component (but not the second) are shaded yellow; points that

are associated with the second component (but not the first) are shown in blue. Points on the

surface that are associated with large weights for both components in the same model are shown

with green. Substantial overlap is observed in all windows, with overlap increasing with window

length (**Figure S1c**). Furthermore, both semantic dimensions are encoded across the vATL with

little functional localization.

S3. Reconstructing item similarity from SVD coordinates

The main analysis uses the first three root-weighted singular vectors as the target for

fitting decoding models with RSL. Predicted coordinates are then used to generate predicted

semantic distances between pairs of held-out stimuli. To understand the possible causes of

domain differences in prediction accuracy, we considered how well pairwise distances can be

reconstructed from the first three singular vectors and values computed from the true matrix with

a subset of items excluded. The goal was to assess whether the first three components capture

inter-items distances equally well for both domains or whether such distances are better

approximated for one domain than another.

877   To this end we conducted the following analysis. We generated 10,000 random splits of

878   the semantic norming data, each consisting of 90 training items and ten test items (five animate

879   and five inanimate) as in the ECoG study. For each, we computed the SVD on the semantic

880   distance matrix for only the items in the training set. We then projected test-set items into the

881   resulting space by matrix multiplying each item's similarity with the training set items:

882   $$\widehat{C}_{q \times r} = S'_{q \times p} U_{p \times r} D_{r \times r}; \quad S' = \left(S_{ij}\right)_{\substack{i \in test \\ j \in training}}$$

883   Here $q = 10$ is the number of test set items, $p = 90$ is the number of training-set items,

$r = 3$ is the rank of the embedding, $\widehat{C}_{q \times r}$ is a matrix containing estimates coordinates for the test

items, S' is a matrix containing the true distances from test items to training items, and U and D

are matrices containing the singular vectors and values, respectively, computed the training

items. From the estimates coordinates in $\widehat{C}_{q \times r}$, the predicted similarity matrix can be obtained as

$\widehat{S}_{q \times q} = \widehat{C} D \widehat{C}^T$. To measure how well the true distances are captures by the SVD, we computed

correlations of lower-triangular values between S and $\widehat{S}$, either over all values at once or

correlating the animate-animate, inanimate-inanimate, and animate-inanimate similarity values

separately.

892   **Figure S2** shows the average correlations for each selection of similarities over the

10,000 splits as bars with error bars reflecting the standard deviation over splits. The mean over

the 10 cross-validation splits used in the ECoG study are overlaid as points. Predicted similarities

that include or isolate between-category structure are most correlated with the true similarity

structure. Predicted within-category similarities are less correlated, with predictions for

inanimate items being less accurate than for animate items. In other words, a low-rank

approximation of the semantic similarity matrix best captures between-domain distances and

provides a better approximation of within-animate than within-inanimate semantic structure.

Thus, decoding models face an intrinsic disadvantage at capturing within-domain structure

generally, and within-inanimate structure specifically.

Figure S2. Correlation between true and reconstructed similarity matrices. Reconstructed similarity matrices are based on a SVD

of a subset of the full similarity matrix expressing the pairwise similarities for 90 items, which is then used to reconstruct the

similarities for the remaining 10 items as described in the text. This process was repeated 10,000 times with different 90/10 splits

and each reconstruction was correlated with the corresponding true pairwise similarities. Bars show the average correlations over

all similarities, just the between-category similarities (animate-inanimate), and just the within-category similarities (animate-

animate and inanimate-inanimate). Error bars report the standard deviation of the means. The results for the specific 90/10 split

used in the analysis of ECoG data reported in the main document are shown as black dots.

S4. Correlation between predicted and full-rank semantic distances

In evaluating how well the RSL decoding models predict pairwise semantic similarities,

the main paper reports the correlation between predicted similarities and similarities

reconstructed directly from the three singular vectors computed from the "true" full-rank matrix.

We will refer to this as the *low-rank* similarity matrix. The low-rank similarity matrix represents

the best possible prediction, given that only three components of the true matrix were used to fit

the decoding model. Here we report correlations with the *full-rank* similarity matrix—the actual

pairwise similarities amongst feature vectors as described in the main text. The low-rank and

full-rank similarity matrices are very similar, $r = .94$, such that the low-rank similarity matrix

accounts for ~90% of the variance in the full-rank matrix. As one would expect given the high

correlation, **Figure S3** and **Figure 5** from the main document show the same pattern of results.

Filled circles indicate significance at Westfall-Young FWER corrected $\alpha = .05$.

Figure S3 Correlation between predicted semantic similarities and *full-rank* cosine similarities as computed from the feature
vectors. These results are very similar to **Figure 5** in the main document which involves the *low-rank* similarity matrix, as
reconstructed from the three semantic dimensions modeled in the primary analysis. The results are so similar because the first

three components account for ~90% of the variance in the full-rank cosine similarity matrix. The interpretation is the same as
Figure 5.