Title

The ground offers acoustic efficiency gains for crickets and other calling animals

Erin E. Brandt*[1], Sarah Duke[1,2], Honglin Wang[1,3], Natasha Mhatre[1]

1. Department of Biology, Western University, London, Ontario. Canada
2. Present address: Michener Institute of Education, University Health Network, Toronto,
Ontario. Canada
3. Present address: Schulich School of Medicine and Dentistry, Western University, London,
Ontario. Canada

*Corresponding Author: Erin E. Brandt, **Email:** ebrandt3@uwo.ca

Author Contributions:
Erin Brandt: Conceptualization; Resources; Data curation; Software; Formal analysis;
Supervision; Validation; Investigation; Visualization; Methodology; Writing - original draft; Project
administration; Writing - review and editing
Sarah Duke: Conceptualization; Resources; Data curation; Investigation; Methodology
Honglin Wang: Conceptualization; Resources; Data curation; Investigation; Methodology
Natasha Mhatre: Conceptualization; Resources; Supervision; Validation; Methodology; Project
administration; Writing - review and editing
18

Competing Interest Statement: The authors declare no competing interests.

Classification: Major: Biological Sciences, Minor: Biophysics and Computational Biology;
Ecology

Keywords: animal sound production | tree cricket | acoustic tool use | alternative acoustic
strategies | sound radiation efficiency

This PDF file includes:

Main Text
Figures 1 to 4
Supplementary figures and tables 1 to 13
28

Abstract
Male crickets attract females by producing calls with their forewings. Louder calls travel
further and are more effective at attracting mates. However, crickets are small, and
therefore inefficient, dipole sound-sources. Only a small group called tree crickets make
acoustic tools called baffles which reduce acoustic short-circuiting, a source of dipole
inefficiency. Here, we ask why baffling is uncommon among crickets. We hypothesize
that baffling may be rare, because like other tools they offer insufficient advantage for
most species. To test this, we modelled the calling efficiencies of crickets within the full
space of possible natural wing sizes and call frequencies, in multiple acoustic
environments. We then generated efficiency landscapes, within which we plotted the
positions of 112 cricket species across 7 phylogenetic clades. We found that all sampled
crickets, in all conditions, could gain efficiency from tool use. Surprisingly, however, we
also found that calling from the ground significantly increased efficiency, with or without
a baffle, by as much as an order of magnitude. We found that the ground provides some
reduction of acoustic short-circuiting but also halves the air volume within which sound is
radiated. It simultaneously reflects sound upwards, allowing recapture of a significant
amount of acoustic energy through constructive interference. Thus, using the ground as
a reflective baffle is a very effective strategy for increasing calling efficiency. Indeed,
theory suggests that this increase in efficiency is accessible not just to crickets, but to all
acoustically communicating animals whether they are dipole or monopole sound
sources.

Significance Statement

Loudness is a crucial feature in acoustic communication. Animals attracting mates or
warding off predators are expected to make themselves as loud as possible. Two long-
standing, seemingly unrelated unsolved problems regarding loudness in the field of
animal communication are: the rarity of acoustic tool use, and animals that call from
reflective ground-like surfaces, known to be an impediment to sound propagation. These
two ideas are related; by refocusing analysis from sound propagation to sound radiation,
we show that the ground is not an impediment, but rather an acoustic aid that can boost
loudness more than tool use. We also show that calling from a reflective surface is an
alternative strategy to maximize call loudness that is available to all animals.
60

Introduction

Male crickets make loud advertisement calls to attract females who use these calls to
locate mates (1). Louder calls travel further, cover more area, and attract more females
(2–4). When faced with a choice, females prefer louder calls (2, 5). Being louder
therefore has implications for mating success and evolutionary fitness in these singing
insects. However, despite the apparent loudness of a nighttime chorus, cricket calls are
acoustically constrained by a phenomenon known as 'acoustic short-circuiting' specific

to dipole sound sources (6, 7). Cricket wings are sound radiators that vibrate back and
forth in the air like pistons. As a wing moves in one direction, the air in front of the wing
is compressed, and the air behind it is rarified. These two changes in pressure travel
away as waves as the motion is periodically repeated. However, the waves on either
side of the wing are of opposite phase and interfere destructively where they meet, at
the edges of the wing. Thus, less sound is radiated, reducing sound radiation efficiency
(6, 8). The smaller the wings of a cricket with respect to the wavelength of the sound it
makes, the higher the short-circuiting and associated loss of efficiency. Indeed, the few
crickets that have been studied are small and experience significant short-circuiting (9).

To reduce the efficiency lost to acoustic short-circuiting, a few tree cricket species build
and use an acoustic tool known as a baffle (5–7, 10). A baffle consists of a leaf with a
hole chewed by the cricket near the middle of the leaf. When the size of the leaf and
hole are optimal, such structures reduce acoustic short-circuiting and increase efficiency
by as much as 10 dB compared to unbaffled calling, reflecting a tripling of sound
pressure levels (7). However, despite their benefits, only a handful of species among
thousands make baffles, all within the sub-family Oecanthinae (5, 7, 10, 11).

Given the obvious benefits, why is acoustic baffle use rare in crickets? Tree cricket
baffles are tools, and tool use is generally rare (12–14). Indeed, few species use tools,
whether crickets, other invertebrates or even vertebrates. Invertebrate tool use,
however, seems especially rare. For example, 56 independent occurrences of tool use
were found in mammals, whereas only 13 occurrences were found in the significantly
more speciose insects (14). Two hypotheses from the tool use literature, the "cognitive
capacity" and the "lack of utility" hypotheses offer two different reasons for this rarity.
The "cognitive capacity" hypothesis suggests that complex tool use behaviors are less
likely to evolve in animals with smaller brains and lower cognitive capacity. This is an
unlikely explanation since many animals with relatively low cognitive capacities do use,
and even make, tools which themselves are not necessarily complex objects. Small-
brained animals are even known to make very complex and highly functionally optimized
habitation structures which do not require high cognitive capacity (7, 15).

A competing hypothesis is the "lack of utility" hypothesis which posits that tool behavior
can evolve regardless of cognitive capacity, but that its evolution requires an ecological
context in which it confers sufficient selective advantage (15). Only species that can
achieve higher gains from tool use than from other strategies (e.g., morphological
features, site selection) are likely to evolve tool using behavior.

To test the lack of utility hypothesis, we must quantify tool utility and use of the tool must
have implications for evolutionary fitness. It is often difficult to meet these two conditions.
Work in chimpanzees has directly quantified tool utility by evaluating how much caloric
value can be gained by using a tool to exploit an otherwise unexploitable resource (16).
Other studies have made more indirect arguments; work in sea otters has shown that
tools are employed more frequently in populations in which tough prey require tools to

access them (17). In capuchin monkeys, larger individuals who can more effectively use
tools to crack nuts are more likely to use tools (18). However, few studies quantitatively
assess the lack of utility hypothesis, particularly outside the context of food.

Baffle use in crickets is an ideal system in which to test the lack of utility hypothesis.
First, baffle use is rare and second, we can directly measure its acoustic utility in terms
of an increase in sound radiation efficiency (12). Finally, baffle use has been shown to
have real fitness implications, by increasing the number of mates attracted to a given
male, and also by increase mating duration, both processes likely to increase
reproductive success (2).

Therefore, in this study, we tested the lack of utility hypothesis across a large group of
singing insects, the true crickets or Grylloidea. We used the finite element method (7, 19,
20) to quantify baffle utility in two ways. First, we ascertained the range of sizes of the
sound radiator (cricket wings) and frequency ranges of the calls used by 112 crickets,
spread over the cricket phylogeny and used it to define an acoustic-morphospace (Fig
1). Then we quantified a volumetric sound radiation efficiency (SRE_V), averaged across
all positions in this space, specifically the relation between the radiator vibration
amplitude, and the sound levels that are generated, similar to the previous study on tree
cricket baffle efficiency (7). Since the amplitude of the radiator vibration would reflect the
effort applied by the animal, this measure of efficiency captures a significant component
of the relationship between calling effort and output. By plotting SRE_V over the complete
acoustic-morphospace, we were able to generate efficiency landscapes. This landscape
allowed us to ascertain the efficiencies of both unbaffled and baffled crickets and
enabled us to fully investigate all possible crickets, even those that did not appear in our
sample.

In this efficiency landscape, while we are considering a morphological parameter
(radiator size), we are not positing that this parameter will be optimized. In biology, trait
optimization can be treated as a hypothesis, and can be productive if tested. In fact in
some rare instances, it may be found to be true, as was shown by Barlow in the case of
diffraction-limited ommatidial-lens sizes in insect eyes (21, 22). However, most
morphological traits are a balance of many opposing constraints which precludes
functional optimization (23, 24). Here, we quantitatively define calling efficiency and test
if there are alternative paths to higher efficiency such as through tool-use behavior, or
through the use of environmental features.

Therefore, to address the complexity of the natural environmental conditions in which
crickets call, such as, from close to the ground, and from within vegetation, we
generated additional efficiency landscapes. In both these cases, the environment
interacts with the sound radiator and the sound emanating from it across spatial scales,
and may effectively add or remove any gains from baffling (25, 26). To capture spatial
effects, we generated a second metric sound radiation efficiency, this time measured
along a transect, (SRE_T). Here we used the boundary element method and generated

new efficiency landscapes which quantified the effects of interacting surfaces on
acoustic efficiency as sound propagates away from the caller, under a range of
environmental conditions.

Crucially, we considered calling from the ground quite carefully, in terms of its effect on
efficiency. In the animal communication literature, typically the ground is considered
during propagation and not in relation of sound radiator efficiency. In this context, it is
typically seen as a severe impediment to sound propagation by causing significant
excess attenuation (27–32). Researchers also focus on the ground effect as degrading
temporal structure (31) and directional information (32, 33). While we cannot address
temporal structure in our examination of sound radiation efficiency, excess attenuation is
accounted for. Additionally, using the same models, we also quantified directionality to
test how efficiency might trade off with this biologically crucial feature.

Using these data, we asked whether the rarity of baffle use in crickets is explained by
the lack of utility hypothesis. We examined the differences between baffled and
unbaffled calling in different realistic scenarios. We expect that known baffle-users will
be animals who benefit most from baffle use, and non baffle-users might not accrue as
many benefits due to acoustic, morphological or environmental constraints.

Results
All crickets would benefit from baffle use in idealized conditions
To capture the natural range of wing sizes and calling frequencies among true crickets,
we collected wing surface area and call frequency data for 112 cricket species from a
large range of sources (Fig 1, Tables S1, S2, Fig S1). Species were distributed across 7
clades as described by the most recent phylogeny of the Grylloidae or "true cricket"
superfamily (34) (Fig 1, Fig S1).

We then constructed finite element models which predicted the sound fields produced by
wings of different sizes at different call frequencies for 1086 different combinations which
encompassed all the observed frequencies and wing sizes, i.e. the full acoustic-
morphospace (Fig 2). In all conditions, wings were modelled as suspended in free
space, vibrating with a uniform velocity perpendicular to the wing plane (Fig S2). The
model predicts the resulting sound field (see Supplementary methods for details). We
then calculate sound radiation efficiency (SRE_V (Pa/m/s)), by taking a volumetric
average of the sound pressure level generated (Pa), over a sphere of radius 20 cm
around the wing, divided by the time-space average of the wing vibration velocity (m/s).
This normalized measure of efficiency enables comparison between species, no matter
their actual wing velocity or sound pressure level.

Next we plotted an SRE_V landscape (Fig 1) for the full acoustic-morphospace. On this
landscape, we plotted the locations of the 112 species of crickets with known wing size
and frequency allowing us to infer their SRE_V (Fig 1). These data therefore demonstrate

where crickets lie in the efficiency landscape (Fig 1F), and how much they could gain
through the behavioral means of using of an optimal baffle (Fig 1G).

Previous work examining four species of crickets and a small number of other insects
determined that they each perform less efficiently than the theoretical maximum for
dipole sound sources (9). In our larger dataset, there is a clear ridge of high efficiency
running through the SRE_V landscape (red line in Fig 1C). This line indicates the radiator
size at which short-circuiting is minimized and efficiency maximized at each frequency
when the radiator is suspended in free space. Despite sampling species with a wide
range of wing areas (0.4 – 258 mm^2) and call frequencies (1.6 – 27.9 kHz), all species lie
below this line. The efficiency distribution among crickets is somewhat bimodal (Fig 1F,
G). The nine species with an SRE_V above 1 Pa/m/s all had calling frequencies above 14
kHz and belonged to the subfamily Eneopterinae, in clade g. Given the difference in their
song radiation mechanics (35) we excluded these individuals from subsequent analyses
(see methods). After excluding these high frequency callers, we found that SRE_V ranges
from 0.02 to 0.67 Pa/m/s, mean: 0.19 ± 0.01 SE, n = 103.

Next, we calculated how much efficiency each species could gain by using a baffle. A
baffle decreases acoustic short-circuiting and is functionally similar to increasing radiator
size (8, 12). The efficiency gained from an optimal baffle is the same as from an
optimally sized radiator (8). Therefore, we use the line representing optimal radiator size
to calculate how much each species could gain in efficiency by using an optimal baffle.
Each species had a calculated "baffled efficiency" by noting where its call frequency
intersects with the line. If animals were to continue using the same call frequency, but
used an ideal baffle, each species stood to gain between 1.8 – 36 times (5 – 30 dB)
above their baseline SRE_V (mean: 7.9 ± 0.41 times, 16 ± 0.48 dB, n = 103). Among
those who stood to gain the most included animals in clade b, specifically in the
subfamily Mogoplistinae (scaly crickets). These animals have very small wings (mostly
under 5 mm^2), suggesting a poor match between sound wavelength and wing size. On
the other hand, the animal closest to line was *Madasumma affinis*, belonging to the
subfamily Podoscirtinae in clade f. This animal has the largest wing at 258 mm^2,
however, even this animal stood to gain 0.5 Pa/m/s (5 dB or 1.6x increase) with the use
of an ideal baffle. Taken together, these data suggest that all crickets could increase
SRE_V, and therefore, stand to benefit from use of a baffle.

Ground calling emerges as an alternative strategy to baffle use in complex
environments
While analysis of SRE_V suggests that all crickets should use baffles, this prediction is
based on sound fields travelling in free space and over short distances. It is possible that
efficiency advantages from baffle use become negligible as sounds interact with objects
in the cricket's local environment such as the ground or the vegetation. Many baffle
users are low frequency callers, and it is also possible that higher frequency crickets

lose all advantage from baffling in complex acoustic conditions. Either of these scenarios
would lend support to the lack of utility hypothesis.

To address whether and how the efficiency landscape is changed by realistic calling
conditions, we used boundary element modeling. Specifically, we used this method to
add a "ground" component to our existing models, where the ground could have different
characteristics including vegetation cover. In these models, sound can be reflected and
dissipated by the ground and the effect of the vegetation is captured by an excess
attenuation term based on empirical data (see supplementary methods). We used
empirical measurements of ground impedance and although our modeled ground is flat
and smooth, these measures should take realistic ground variability into account. We
also varied the height of the caller above the ground (ground calling: 0 m, elevated
calling: 1 m). We measured efficiency again by normalizing sound levels against radiator
vibration levels (see methods). Sound levels were measured at two distances from the
caller: near (averaged from 0.05 – 0.2 m away), and far (averaged from 0.8 – 0.9 m
away). To simplify analysis, we always measured efficiency at the same height as the
caller. To differentiate this measure of efficiency from SRE_V, we call it sound radiation
efficiency along a transect, or SRE_T (Pa/m/s).

The most striking and unexpected result from our analysis was that calling from the
ground (Fig 2C, D) yielded much higher SRE_T than calling from one meter above it (Fig
2A, B). This is reflected in the efficiency landscapes by an average increase of about 5x
(14.5 dB) across the entire acoustic-morphospace that we measured. Indeed, the
highest SRE_T observed with a ground caller was 4 Pa/m/s (Fig 2C), two orders of
magnitude higher than peak SRE_T with an elevated caller (0.06 Pa/m/s, Fig 2A). This
increase in efficiency is likely due to two phenomena. The first is partial baffling offered
by the ground, which will prevent some acoustic short-circuiting. A second phenomenon
is likely the ground effect, in which the pressure field that would normally propagate
below the radiator is instead reflected upward from the ground and mixes with the
directly propagated field. Here, we see that the ground effect leads to constructive
interference between the direct, and the reflected and the ground wave and an increase
in sound pressure levels (36). We find that even optimally baffled animals could gain an
average of 2.8x efficiency (9.2 dB) along the measurement transect, by calling from the
ground compared to elevated calling.

On the other hand, calling from far above the ground yields SRE_T values that are similar
in level to SRE_V values calculated in the ideal free-field scenario modeled previously. At
further distances, the values decrease as predicted by spreading in open air. Taken
together, our models posit that ground calling and elevated baffled calling are two
potential alternative strategies to maximize efficiency.

Calling from the ground is still efficient when ground properties and vegetation are varied

All grounds are not equivalent and the increase in the net increase SRE_T may depend on their properties. For instance, soft grounds or those covered with vegetation would be much more dissipative and may eliminate the advantage accrued from ground calling. To test this possibility, we investigated whether this alternative strategy framework holds up when these properties of the environment are varied. We found few differences in SRE_T with different types of grounds (Fig S7). SRE_T tends to be slightly higher with a "soft" ground, which is better at dissipating sound, similar to a freshly tilled agricultural field (see methods) and this effect is magnified further away from the caller. This suggests dissipation has a higher effect further from the source, and primarily on propagation, whereas here the phase shift is more appropriate for constructive interference near the source. With a harder, more reflective ground, similar to a tightly packed forest floor, SRE_T is slightly lower. However, significant differences between these two ground types occur at wing sizes well outside the natural range for crickets. At close distances, and particularly above the ground, the differences between ground types are very small (Fig S7). Therefore, all future analyses assume a "hard" ground.

Finally, we tested whether vegetation would reduce the predicted SRE_T landscapes for ground calling. Vegetation does slightly decrease the magnitude of SRE_T overall and unsurprisingly, there is a slight frequency dependence where SRE_T is lowered slightly more at high frequencies (Fig S8). This suggests that high frequency callers may be at an increased disadvantage when calling in vegetation as suggested before (29), and will see diminishing returns when using a baffle. However, we found that excess attenuation due to vegetation does not significantly change the overall patterns of efficiency. By and large, it shifts the efficiency landscape to a lower point at most points within the parameter space (Fig S8) (37). However, the efficiency near the ground remains higher than the efficiency 1m above the ground (Fig S9). Finally, the effects of vegetation on SRE_T are undoubtedly more complicated than an excess attenuation factor. Modeling plants explicitly, at a variety of shapes and sizes, would be a useful extension to this study. However, since the efficiency of ground calling remains higher than calling from 1m above ground, we conclude that calling from the ground remains an effective alternative strategy, even if the ground is soft, or covered with some vegetation.

Ground calling does not significantly degrade call directionality

So far, our analysis has used the loudness of calls to define efficiency. However, a call must be both loud and directional to be effective. That is, the call must present a spatial gradient that a potential mate can follow to the source. Previous data has suggested that such gradients are severely degraded in ground calling crickets (29, 33, 38, 39), but not in elevated calling (40). This suggests that SRE_T gains from ground calling may trade off against call directionality. To test this, we analyzed call directionality by designing a directionality metric that captured how difficult it would be for a female cricket to follow an acoustic gradient back to the call's source (see methods). A value of one indicates

that the gradient along a transect perpendicular to the wing planes is always in the
"correct" direction, that is, sound pressure level increases as the female moves toward
the caller in steps of ~ 2 body lengths (2 cm). A lower value means that over some
stretches of this transect, SPL increases and at other steps it decreases. A value of 0.5,
for instance, means that the SPL decreases over 50% of the steps as the female moves
closer.

We find that directionality varies with respect to frequency, radiator size, and height from
ground (Figs S10, S11). Although ground calling does experience a loss of directionality
compared to elevated calling, these losses are small. Near a ground caller, calls are all
strongly directional (> 0.9) below about 5 kHz, except for very small wings. Further from
the caller, calls are strongly directional below about 3.5 kHz. Therefore, high frequency
callers would be most susceptible to the gradient effects. However, even below these
cutoffs, directionality rarely drops below 0.5 in any condition, and ground calling remains
a viable strategy. It should be noted that other studies have found more substantial
degradations in call directionality in sounds traveling along the ground, but over greater
distances than our current models (33). However, data for both field crickets and tree
crickets suggest that the SPL of typical cricket calls drop below threshold at about 1 m
from the caller (38, 40), and therefore we considered this a biologically relevant distance
over which to measure directionality.

Alternative calling strategies are likely in use by some cricket species
Based on the overall efficiency landscape, ground calling and baffled calling are
potential alternative strategies to maximize efficiency. However, we have so far
considered the full acoustic-morphospace, i.e. all possible combinations of radiator
(wing) size and call frequency, but most of these combinations are not used by real
crickets.

To shift our focus to the sampled cricket species, we tested where alternative calling
strategies may offer the largest advantage to actual crickets. For each of the 103
animals in the dataset, we calculated SRE_T for each of three alternative strategies as
measured far from the caller: calling from the open hard ground (ground calling), and
from within vegetation 1 m off the ground with no baffle (unaided calling), and from within
vegetation with a baffle (baffled calling) (Fig. 3a). We compared both baffled calling and
ground calling to unaided calling as a baseline. It would be ideal to determine whether
animals, in fact, use the strategy that we predict should maximize efficiency based on
known calling preferences. Unfortunately, we do not have data on calling preferences of
many sampled animals. Below, we give four examples of species where information
about calling behavior is available.

We start with *Oecanthus henryi*, a well-studied species of tree cricket in clade f. This
species stands to gain efficiency on the order of about 2.5x, (8 dB) from ground calling
compared to unaided calling according to our data (Fig 3A). However, they could gain
28x, (28 dB) if they baffled. Indeed, what is known of this species' natural history bears

out our predictions; *O. henryi* not only calls from vegetation, including vegetation that is
suitable for baffle building and use (6, 40), in fact, this species is well known for its
baffle-building behavior (7, 10, 12). For *Gryllus veletis*, a field cricket in clade g, on the
other hand, we predict the opposite. On average, ground calling gives an advantage of
16x (24 dB) above unaided for this species, whereas baffling gives an advantage of
about 5x (15 dB) above unaided. Again, behavioral data suggests that many field
crickets (including this species) indeed prefer to call from ground habitats that we predict
would maximize their efficiency (41). *Anaxipha hyalicetra*, a sword-tailed cricket from
clade c also stands to gain more from ground calling (20x, 26 dB) than from using a
baffle (12.5x, 12 dB). This species is known to call from the surfaces of fallen leaves and
bunch grasses (42), suggesting that other objects in the environment may act as a
"ground".

Finally, *Gryllotalpa aulstralis*, a species of mole cricket in clade a, represents an
interesting exception to this alternative strategy framework. This species stands to gain a
great deal from baffling (18x, 25 dB), compared to ground calling (2.5x, 8 dB). Yet, this
species (and all species in clade a) are known to exclusively call from the ground and do
not use baffles. However, they do use an acoustic aide. Mole crickets build and call from
burrows which function as resonators and convert them into monopole sound sources,
eliminating acoustic short-circuiting through a different mechanism than baffling (28, 43).
Indeed, it is possible that other acoustic means of maximizing call efficiency exist and
could in the future add further complexity to our hypotheses.

Finally, we find if animals baffled, but their calls propagated though vegetation compared
with no vegetation, the gains would be relatively small in most cases (< 6 dB SPL) (Fig
S9), We also performed a similar analysis for call directionality (Fig 3B, Fig S11).
However, since directionality was quite high for all calling conditions, we suggest that
directionality does not preclude one alternative strategy over another.

Discussion

Why would baffle use evolve among crickets in the first place?
From our data, exploiting the ground effect by calling from the ground emerges as a
viable alternative to tool use in crickets. This simple site selection strategy can even
exceed the efficiency gains of tool use in some scenarios. Given that making and using
tools like baffles requires a specialized behavioral repertoire, and precise execution of
these behaviors (7, 12), the real question becomes why a species would ever use this
strategy if simpler site selection preference for the ground could give similar increases in
efficiency.

There is evidence that crickets have been singing as early as the Cretaceous period
(44). These early calling crickets were likely ground dwellers, with some species
subsequently moving up into vegetation as the group diversified (45). We therefore
suggest that baffle-using crickets may have originally moved up into vegetation for non-

acoustic reasons, whether it was to exploit additional food resources or avoid predators.
Baffle use would have then evolved secondarily to recover some of the efficiency lost
when abandoning ground calling. The biophysical modeling methods presented here
open the door to testing such a hypothesis about baffle use.

It is also known that crickets call from other "ground" substrates such as tree trunks,
cave walls, or artificial structures (25, 28), which our data suggest could also increase
calling efficiency (35, Fig 4C, D). The efficiency effects of these substrates could be
further investigated using biophysical models contributing to our knowledge of acoustic
ecology. In principle, we could even model the wings of extinct crickets, and estimate
calling frequency based on the stridulatory apparatus on the wing (46, 47). By bringing
extinct crickets "back to life" in this way we could ask questions about the evolution of
acoustic tool use and calling ecology more broadly. We suggest that biophysical
modeling, grounded with data from real animals, can be a valuable tool for any biologist
wishing to better characterize and understand tool use in the context of animal
communication.

Sound radiation efficiency in animal acoustic communication
In the field of animal acoustic communication, calling from the near the ground has been
thought of as severely disadvantageous, whether in insects, birds or even primates (27,
28, 48–53). One reason for this is that reflections from the ground degrade temporal
cues in calls and songs (31). However, most animal calls are repetitive and redundant,
since they are used for functions such as sexual or territorial signaling, or as contact or
alarm calls. Here, fine temporal structure is not crucial and the primary functional factor
is how loud the sound is (28). How then is loudness affected by the presence of a
reflective surface such as the ground? In animal acoustics, it is widely believed that the
ground generates high amounts of excess attenuation compared to simple spherical
spreading of sound (27, 28, 48–53). Yet, many animals call from the ground, tree trunks,
or other vertical surfaces such as cave walls in many ecological contexts (28).

Previous acoustic analyses have typically measured excess attenuation as observed at
two distances from the source. Thus, these analyses only account for propagation
losses and fail to consider the first step in the process, sound radiation efficiency, i.e.,
the relationship between the vibration amplitude of the radiator and the level of the
sound field that is generated. Here we show that for dipole singers like crickets, calling
from the ground can actually provide a substantial boost in sound radiation efficiency,
outweighing propagation losses at distances and receiver positions relevant to cricket
behavior. It is only when we take this first step in the process of sound generation into
account, that it becomes clear that calling from the ground may be an advantage rather
than an impediment.

In fact, this phenomenon may be much more general than currently appreciated;
analytical findings from as far back as 1957 show that the acoustic power radiated by
monopoles and horizontal dipoles (such as cricket wings) increases as they get closer to

a perfectly reflecting surface, by as much as a factor of two (Fig 4) (54). When acoustic
sources are close to the ground, the reflected sound field effectively sums with the direct
sound field, and at very close distances, this summation is near perfect. In particular, the
radiated field from dipoles becomes almost monopole like when the source is close to a
reflective ground (Fig 4) (55).

Of course, real grounds are not perfectly reflective and do have a finite impedance; they
absorb some sound energy (36, 56). However, this does not significantly alter the
theoretical expectation of increased sound radiation, except that an additional ground
wave is formed in addition to the reflected wave (36). Nonetheless, dipole and monopole
sources near the ground are still theoretically expected to have higher sound radiation
efficiencies compared to the free or direct field condition (36, 57). In our analyses, we
considered dipole sound radiators of finite size, above realistically parametrized
grounds. We found sound radiation efficiency increases considerably near the ground. In
fact, in some cases efficiency increases by even more than a factor of 2, likely through
the baffling effect offered by the ground against acoustic short circuiting.

These findings extend beyond crickets, as they are true for both horizontal dipoles and
monopoles (Fig. 4). All acoustically communicating animals are considered to be either
dipole or monopole-like sound sources. Among non-cricket invertebrates, both fruit flies
and mosquitoes produce sounds with their wings, functioning as dipoles (9). Other
invertebrates that use tymbal-based sound production like cicadas and wax moths
behave like monopoles (9). Among vertebrates, the sound fields produced by bats are
well captured by a baffled-dipole piston model (58, 59) and whales have a similarly
directional sound field (60). Most acoustically active vertebrates such as fish, frogs,
reptiles, birds and mammals are considered to be monopole sound sources (27, 61).
Thus all these animals can exploit this mechanism for gaining efficiency (9, 27, 61). In
effect, by shifting the focus from sound propagation to sound radiation efficiency, we
posit an explanation for both the rarity of tool use and high number of animals that call
from the ground. Indeed, our findings, and a reconsideration of established acoustics
theory, leads us to the exciting discovery of a hitherto unknown mechanism for
increasing calling efficiency available to all acoustically communicating animals.

Materials and Methods

Specimen Data

453
We collected data on wing surface area and call frequency for 112 cricket species
distributed across 7 clades *sensu* Chintauan-Marquier et al. (34) (Fig 1, Fig S1). We
restrict our analysis to Grylloidae, since they are known to raise their wings when singing
(62). This behavior means that they are dipole sound sources , and acutely affected by
acoustic short-circuiting (5, 9). Data were obtained from a variety of databases including
Orthoptera Species File (56), Crickets North of Mexico, and numerous publications (all
references are available in Tables S1, S2). For a few species of Oecanthines, wings
were provided by Nancy Collins and photographed in the lab under a dissecting

microscope. We measured surface area of the entire left forewing including the lateral
field. Fitting an ellipse to the wing, we calculated aspect ratio (length of ellipse/width of
ellipse). All image data were gathered using ImageJ version 1.53 (64). The fundamental
frequency of cricket advertisement calls was captured using Raven Lite version 2.0
(Cornell Lab of Ornithology, 2020). In crickets, call frequency typically does not change
with environmental conditions (66), in a few exceptional groups such as tree crickets this
change is typically <1kHz (67) which we do not expect to change our conclusions
strongly. Therefore, we do not consider recording conditions and treat song frequency as
an invariant character of cricket species. For our models, we assume that call frequency
is identical to wing oscillation frequency as is widely accepted (68). Both have been
simultaneously measured in at least two species of crickets where this has been verified
(69, 70).

When multiple specimens of a single species were analyzed, averages were used for
wing size and call variables. To better represent the full range of wing size and call
frequency in our dataset, we included some specimens in the histograms showing wing
size and frequency (Fig 1D, E) for which we had only one type of data. Twelve animals
had only wing size, but not call data, and 57 animals had call, but not wing size data
(see Tables S1, S2 for details).

Finite Element Models for Sound Radiation Efficiency
We estimated the sound radiation efficiency of crickets calling in open air using finite
element (FE) analysis (Fig S2). All models were built in COMSOL Multiphysics version
5.5. All models used the pressure acoustics module and were solved in the frequency
domain assuming a steady state. The Helmholtz equation was the governing equation.

Model geometry, boundary conditions, symmetry, and vibration
Animals were represented by two ellipses which modelled the forewings sitting next to
each other along the long axis, in the same plane (see Fig S2 for description of
symmetry). The size and shape of the radiator and call frequency determines radiation
efficiency, and not the radiator's material properties (8). Surrounding the wings was a 20
cm radius spherical acoustic domain consisting of air. We applied a time- and space-
averaged velocity normal to the entire wing surface at 0.13 m/s. This was the value
measured from the wings of singing *Oecanthus henryi,* the only known estimate for
crickets (7). However, for our analysis we use efficiency rather than sound pressure
levels. Efficiency normalization allows comparison between species. We vibrated the
wings from 0.5 - 32 kHz, in increments of 0.25 kHz. SRE_V was calculated from model
outputs as a volumetric average of the absolute pressure in the acoustic domain, divided
by the time- and space-averaged velocity of 0.13 m/s, resulting in units of Pa/m/s.

Finite Elements
3D tetrahedral elements were used in both the acoustic domain and PML. After
undertaking a mesh size sensitivity study (Fig S5), we chose the "extra fine" mesh

setting in COMSOL, with about 60000 elements in the acoustic domain. This number did
vary somewhat with wing size, as fewer elements are used with very small wings.

Model Parameters
We ran the FE model at wing surface areas from 0.4 – 4000 mm^2, scaled logarithmically
by the equation 4×10^x, where x ranges from -1 to 3). We used an aspect ratio of 2
(wings are twice as long as they were wide). Our chosen aspect ratio of 2 was within the
range of most cricket species (median: 1.7, range: 0.7 - 3.7). Aspect ratio did not greatly
alter efficiency, except at aspect ratios > 5 (length of wing 5x the width), which were not
observed in real wings (Fig S4). For natural aspect ratios, differences in SRE_V at a given
wing area and frequency never exceeded 3 dB.

Other Modeling Considerations
The cricket body was not included in our models as it was found to have negligible
effects on SRE_V at all wing sizes and frequencies (mean difference: 0.05 ± 0.01 dB). We
also evaluated whether applying vibration to only a part of the wing (a "harp") influenced
sound production. Some cricket species (though not all) use this sound production
method (71). We found only minor increases in SRE_V between vibrating only a harp or
vibrating the entire wing (mean: 4 ± 0.08 dB), except at wing sizes well outside the range
of the real wings (Fig S4).

Boundary Element Models for SRE_T
To test hypotheses about how cricket calls interact with objects in the environment, we
needed to include an additional domain in the model: a "ground" with realistic
parameterized acoustic impedance. To make this model as realistic as possible and to
minimize boundary effects, we needed to make the ground element as large as possible
relative to the size of the wings. The combination of the large size of ground and the high
frequencies of interest resulted in finite element models that were too computationally
intensive to run. We therefore turned to boundary element (BE) modeling as an
alternative means of assessing SRE_T.

Boundary element models and finite element models are both numerical methods for
solving the Helmholtz equation to capture a developing sound field within a medium.
However, they discretize space within the model differently. FE models discretize
volumes by partitioning into a 3-dimensional mesh of finite elements. BE models on the
other hand reduce computational cost by discretizing only the boundaries of the acoustic
domain and assume a linear homogenous medium in all other spaces. The BE
formulation trades off some specificity in exchange for computational efficiency, allowing
us to make large, biologically relevant models to assess sound SRE in a spatially explicit
manner.

We ran our BE models using the pressure acoustics, BE module in COMSOL. All
models were run in the frequency domain and assumed steady-state behavior. The
Helmholtz equation does not take attenuation due to damping into account, which can

become an issue at distances far from the source. However, at frequencies >500 Hz,
attenuation due to damping is only about 2 dB per kilometer (32), so we considered this
effect to be negligible over the distances of interest for this study (0.2 – 1m).

Model geometry, forcing, and boundary conditions
Wings in the BE model were modeled in the same way as in the FE model (Fig S2), with
no material properties and one-way coupling between the wings and sound fields. The
ground was modeled as a rectangular slab, 0.5 m wide, 2 m long, and 0.10 m thick.
Wings were positioned perpendicular to the top surface of the ground, with the flat
surfaces of the wings aligned with the short axis of the ground. The wings were centered
with respect to ground. The wings were placed above the ground at either 0 m, or 1 m.
The same time- and space-averaged velocity was applied, and the same set of wing
surface areas were used. A sound-hard boundary was applied to the bottom surface of
the ground slab. Because we were interested in spatially-explicit measures of efficiency
as sound propagates across ground, we did not use symmetry conditions to create this
model. However, because the sound fields should be symmetric on either side of the
wings, we only measured the sound field on one side.

Model Parameters
We used a restricted frequency range for the boundary element models, ranging from of
0.5 – 10 kHz, in increments of 0.25 kHz. We chose 10 kHz as the cutoff because very
few animals call above this frequency, and those that do were Eneopterine species who
were likely using a vibrational mode inconsistent with the piston mode that we have
implemented (35). High frequency (> 10 kHz) callers were included in the finite element
models to give a general sense of where they might fit in with the other animals, but in
reality no animals occupy this space in the landscape and all analyses explicitly
comparing species exclude them.

To model how the ground interacts with sound, we applied an acoustic impedance to our
modeled ground. Acoustic impedance quantitatively describes how much sound energy
is dissipated by the ground, compared to the energy reflected. We used the
Attenborough slit-pore model to implement ground impedance. This model uses three
parameters to capture both dissipative and reflective properties: flow resistivity, pore
density, and porous layer depth. We modeled two different types of ground, a "soft"
ground (flow resistivity: 2000 kPa×s/m^2, porosity: 0.6) which is less reflective and a
"hard" ground (flow resistivity: 9 kPa×s/m^2, porosity: 0.4), which is more reflective.
Porous layer depth was held constant for both treatments, at 0.04 m. The two parameter
sets were taken from empirical measurements of a "soft" freshly-tilled field and a "hard"
forest floor (56).

Transect sound radiation efficiency
In the FE models, we calculated a volumetric average of absolute pressure within the
acoustic domain. However, this measure would not be appropriate to assess sound

radiation efficiency at a distance, as the sound waves' interactions with the ground would
accumulate as distance from the source increases. Therefore, we calculated SRE_T in a
spatially-explicit manner. We measured absolute pressure at 50 points along a 1m long
line parallel to the long axis of the ground, at the same height as the wings. The line
originated at the center between the two elliptical 'wings'. We divided this line into "near"
and "far" from the caller: near = 0.05 – 0.2 m from wings, far = 0.8 – 0.9 m from wings.
Efficiency was calculated by dividing sound pressure level (Pa) by 0.13 m/s, the space
and time averaged velocity applied to the wings. We also created an additional boundary
element model with no ground, to allow for direct comparisons between ground and no
ground and to sanity check the BE method compared with the previous finite element
models.

Finite Elements
Tetrahedral elements were used on the surface of the ground and 2D triangular
elements on the wings. After performing a similar sensitivity study as with the finite
element models, we decided on a maximum element size for the wing surfaces of 0.5
cm and 1 cm for the surface of the ground. Since the sound wave is not explicitly
modelled, this element size is not related to sound frequency, and instead captures
boundary conditions and hence can be larger than in the finite element models.

Excess attenuation due to vegetation
To calculate the effect of vegetation, we used existing models to calculate how standing
vegetation is expected to impact call efficiency. We then subtracted this excess
attenuation from the COMSOL result. We calculated excess attenuation using the
following empirically derived equation(37):

$$\frac{EA(Pa)}{FL} = 3\left[1 - \exp\left(0.3 - 0.5(ka)\right)\right], ka > 0.6$$

Where EA(Pa) represents excess attenuation due to foliage, F = foliage area per unit
volume, L = path length, k = wavenumber, and a = average leaf size. We used values
empirically derived for dense foliage with relatively large leaves (37), such as those used
to construct baffles in known baffle-using species. To approximate the foliage area and
leaf size that a typical baffle user would prefer, we used F = 6.3m^{-1} and a = 0.0784m in
our measures of excess attenuation.

Efficiency of individual species and how much they gain with baffle
To test the lack of utility hypothesis, we used the output of our models to estimate the
gains in efficiency that each species could attain if it used an optimal baffle. The
efficiency of a radiator in an optimal baffle is the same as the efficiency of an optimally
sized radiator for which short-circuiting is minimized and efficiency is optimized in free
space (8) (Fig S6).

We identified this size for both the idealized measure of efficiency (SRE_V) and the more
realistic scenario involving a ground and vegetation (SRE_T). For each modeling scenario,

we estimated the efficiency of each cricket species in our dataset, given their wing area
and call frequency. Next, we calculated the quantity ka for each surface area-frequency
combination in the model, where k is the wavenumber and a is the effective radius of the
sound radiating plates (8). ka is a dimensionless quantity used in acoustics, which helps
define when a radiator of a particular size transitions from being inefficient sound
radiator at low frequencies to an efficient high frequency radiator (an optimally sized
circular piston has ka = 1) (8). However, the radiators being considered here are two
aligned ellipses and at their particular value of maximal efficiency ka will be different. To
estimate optimal ka for cricket wings, we plotted ka versus efficiency as measured from
our models, with a separate trace for each frequency (Fig S6). We then identified the ka
at which maximal efficiency was reached for all frequencies. In our FE models, we found
optimal ka to be about 1.3. For the boundary element models at the far distance, optimal
ka was approximately 1.55 (Fig S6).

Next, we performed a simple linear regression between frequency and maximal
efficiency at optimal ka, then calculated the slope and y-intercept of this regression (Fig
S6). We used this equation to calculate optimal baffled SRE_V and SRE_T for each
species. The relationship between frequency and efficiency differed depending on
condition (open ground vs ground + vegetation) (Fig S6), so this regression was
performed separately for each environmental condition when calculating optimal baffled
efficiency for a given condition. It should be noted that due to modelling constraints we
were only able to calculate baffled efficiency on the ground for animals with a carrier
frequency >3.5 kHz.

Directionality index
To address how difficult it would be for a female to localize a male call, we assessed the
directionality of the call in each modeling scenario. In an open sound field with no
ground, the sound level is expected to decrease smoothly following the inverse square
law (72, 73). A cricket moving toward the source of a call should therefore always
experience either an increase in loudness, or, if the increase is below the animal's
difference threshold, no change in loudness. A cricket should always move in the
direction of increasing SPL to locate the singing male. However, in reality, sound fields
become more complicated when they interact with the ground, resulting in a noisy
relationship between SPL and distance (74). In such sound fields, female phonotaxis
may fail as there is no clear acoustic gradient to follow to the source. To quantify this
degree of potential "confusion", we calculated a directionality index for each modeling
scenario. First, we calculated Δ SPL between each two adjacent points 2 cm apart (~ 2
body lengths for most animals in this analysis). Δ SPL was calculated starting at 1 m
away and moving toward the source. Next, we classified each of these values as either
consistent with expected change in SPL or inconsistent. Consistent values represented
either an increase, no change, or a decrease smaller than Δ 3dB SPL (a factor of about
1.4), thought to be close to the detectable threshold for crickets (75). See (74) for a more
complex treatment of such thresholds. For our purposes, inconsistent values

represented a decrease in SPL greater than 3 dB. For each modeling scenario, we
calculated the proportion of Δ SPLs classified as consistent. This resulting value we call
"Directionality" ranging from 0 to 1 (Fig S10). We calculated directionality for two
different distance treatments, "near" was calculated from 0.05 – 0.2 m from the wings,
and "far" was calculated from 0.5 – 1m from the wings.

Data availability
Data used to create the figures can be found at DOI:10.5061/dryad.v15dv420b

665 Acknowledgments

666
We wish to acknowledge a number of undergraduate students who assisted with the
collection and databasing of cricket acoustic and morphometric data: Morteza Al Rabya,
Nancy Kim, Shanker (Matthew) Nadarajah, and Daniel Xie. Nancy Collins provided
specimens for several of the wing measurements. Graduate students Hossein Asgari
and Reese Gartly assisted with multiplexing dozens of model runs on multiple machines.
Emine Celiker and Damian Elias provided feedback on an earlier version of this
manuscript. This work would not have been possible without an extensive worldwide
network of specimen databases. We especially wish to thank those who contribute to,
curate, or maintain Orthoptera Species File, Singing Insects of North America, Museum
D'Historie Naturelle, and numerous university insect collections. We also wish to thank
the photographers who graciously provided their images free of charge for inclusion in
this manuscript. Finally, we would like to thank three anonymous reviewers whose
comments greatly improved this manuscript.

We would also like to thank the following funding sources for their support of this
research: NSERC Discovery (Grant no. 687216), and early career supplement (675248),
and an NSERC Canada research chair (Grant no. 693206) to NM; the Western SEED
grant to NM; the Western Postdoctoral Fellowship to EEB; Western Undergraduate Work
Study to SD and HW; Western Undergrad Summer Research Internship to HW.

686 References

1. J. Regen, Über die Anlockung des Weibchens von Gryllus campestris L. durch
telephonisch übertragene Stridulationslaute des Männchens. *Pflügers Archiv*
European Journal of Physiology **155**, 193–200 (1913).

2. R. Deb, S. Modak, R. Balakrishnan, Baffling: a condition-dependent alternative
mate attraction strategy using self-made tools in tree crickets. *Proceedings of the*
Royal Society B: Biological Sciences **287**, 20202229 (2020).

3.   H. E. Farris, T. G. Forrest, R. R. Hoy, The effects of calling song spacing and
intensity on the attraction of flying crickets (orthoptera: Goryllidae: Nemobiinae). *J*
Insect Behav **10**, 639–653 (1997).

4.   H. Römer, R. K. Butlin, T. Guilford, J. R. Krebs, Environmental and biological
constraints for the evolution of long-range signalling and hearing in acoustic
insects. *Philosophical Transactions of the Royal Society of London. Series B:*
Biological Sciences **340**, 179–185 (1993).

5.   T. G. Forrest, Power output and efficiency of sound production by crickets. *Behav*
Ecol **2**, 327–338 (1991).

6.   T. G. Forrest, Acoustic Communication and Baffling Behaviors of Crickets. *The*
Florida Entomologist **65**, 33–44 (1982).

7.   N. Mhatre, R. Malkin, R. Deb, R. Balakrishnan, D. Robert, Tree crickets optimize
the acoustics of baffles to exaggerate their mate-attraction signal. *eLife* **6**, e32763
(2017).

8.   S. A. Hambric, J. B. Fahnline, Structural Acoustics Tutorial—Part 2: Sound—
Structure Interaction. *Acou. Today* **3**, 9 (2007).

9.   H. C. Bennet-Clark, Size and scale effects as constraints in insect sound
communication. *Phil. Trans. R. Soc. Lond. B* **353**, 407–419 (1998).

10. L. Prozesky-Schulze, O. P. M. Prozesky, F. Anderson, G. J. J. Van Der Merwe,
Use of a self-made sound baffle by a tree cricket. *Nature* **255**, 142–143 (1975).

11. N. Collins, A Citizen Scientist's Contributions to Tree Cricket Taxonomy. *American*
Entomologist **58**, 9–10 (2012).

12. N. Mhatre, Tree cricket baffles are manufactured tools. *Ethology* **124**, 691–693
(2018).

13. J. D. Pierce, A Review of Tool Use in Insects. *The Florida Entomologist* **69**, 95–104
(1986).

14. G. R. Hunt, R. D. Gray, A. H. Taylor, "Why is tool use rare in animals?" in *Tool Use*
in Animals: Cognition and Ecology, C. Boesch, C. M. Sanz, J. Call, Eds.
(Cambridge University Press, 2013), pp. 89–118.

15. M. Hansell, G. Ruxton, Setting tool use within the context of animal construction
behaviour. *Trends in Ecology & Evolution* **23**, 73–78 (2008).

16. C. Boesch, H. Boesch, Optimisation of Nut-Cracking With Natural Hammers By
Wild Chimpanzees. *Behaviour* **83**, 265–286 (1983).

17. J. A. Fujii, K. Ralls, M. T. Tinker, Ecological drivers of variation in tool-use
frequency across sea otter populations. *Behavioral Ecology* **26**, 519–526 (2015).

18. N. Spagnoletti, E. Visalberghi, E. Ottoni, P. Izar, D. Fragaszy, Stone tool use by
adult wild bearded capuchin monkeys (Cebus libidinosus). Frequency, efficiency
and tool selectivity. *Journal of Human Evolution* **61**, 97–107 (2011).

19. A. F. Seybert, T. W. Wu, X. F. Wu, "Experimental validation of finite element and
boundary element methods for predicting structural vibration and radiated noise"
(1994) (November 13, 2022).

20. E. R. Dumont, I. R. Grosse, G. J. Slater, Requirements for comparing the
performance of finite element models of biological structures. *Journal of Theoretical*
Biology **256**, 96–103 (2009).

21. H. B. BARLOW, The Size of Ommatidia in Apposition Eyes. *Journal of*
Experimental Biology **29**, 667–674 (1952).

22. W. S. Bialek, *Biophysics: searching for principles* (Princeton University Press,
2012).

23. R. Dudley, C. Gans, A Critique of Symmorphosis and Optimality Models.
Physiological Zoology **64**, 627–637 (1991).

24. F. Jacob, Evolution and Tinkering. *Science* **196**, 1161–1166 (1977).

25. B. Erregger, A. K. D. Schmidt, Anthropogenic calling sites boost the sound
amplitude of advertisement calls produced by a tropical cricket. *Animal Behaviour*
142, 31–38 (2018).

26. M. I. Muñoz, W. Halfwerk, Amplification of frog calls by reflective leaf substrates:
implications for terrestrial and arboreal species. *Bioacoustics* **31**, 490–503 (2022).

27. J. W. Bradbury, S. L. Vehrencamp, *Principles of animal communication*, 2nd ed
(Sinauer Associates, 2011).

28. H. C. Gerhardt, F. Huber, *Acoustic Communication in Insects and Anurans:*
Common Problems and Diverse Solutions (University of Chicago Press, 2002)
(February 17, 2023).

29. H. Romer, J. Lewald, High-frequency sound transmission in natural habitats:
implications for the evolution of insect acoustic communication. *Behav Ecol*
Sociobiol **29**, 437–444 (1992).

30. M. Van Staaden, H. Römer, Sexual signalling in bladder grasshoppers: tactical
design for maximizing calling range. *Journal of Experimental Biology* **200**, 2597–
2608 (1997).

31. M. Jain, R. Balakrishnan, Does acoustic adaptation drive vertical stratification? A
test in a tropical cricket assemblage. *Behav. Ecol.* **23**, 343–354 (2012).

32.   T. F. W. Embleton, Tutorial on sound propagation outdoors. *The Journal of the*
764   *Acoustical Society of America* **100**, 31–48 (1996).

765   33.   K. Kostarakos, H. Römer, Sound transmission and directional hearing in field
766   crickets: neurophysiological studies outdoors. *J Comp Physiol A* **196**, 669–681
767   (2010).

768   34.   I. C. Chintauan-Marquier, *et al.*, Laying the foundations of evolutionary and
769   systematic studies in crickets (Insecta, Orthoptera): a multilocus phylogenetic
770   analysis. *Cladistics* **32**, 54–81 (2016).

771   35.   T. Robillard, P. Grandcolas, L. Desutter-Grandcolas, A shift toward harmonics for
772   high-frequency calling shown with phylogenetic study of frequency spectra in
773   Eneopterinae crickets (Orthoptera, Grylloidea, Eneopteridae). *Can. J. Zool.* **85**,
774   1264–1275 (2007).

775   36.   K. M. Li, S. Taherzadeh, K. Attenborough, Sound propagation from a dipole source
776   near an impedance plane. *The Journal of the Acoustical Society of America* **101**,
777   3343–3352 (1997).

778   37.   I. Bashir, S. Taherzadeh, H.-C. Shin, K. Attenborough, Sound propagation over soft
779   ground without and with crops and potential for surface transport noise attenuation.
780   *J. Acoust. Soc. Am.* **137**, 12 (2015).

781   38.   N. Mhatre, R. Balakrishnan, Male spacing behaviour and acoustic interactions in a
782   field cricket: implications for female mate choice. *Animal Behaviour* **72**, 1045–1058
783   (2006).

784   39.   H. Römer, Directional hearing: from biophysical binaural cues to directional hearing
785   outdoors. *J Comp Physiol A* **201**, 87–97 (2015).

786   40.   R. Deb, R. Balakrishnan, The opportunity for sampling: the ecological context of
787   female mate choice. *Behavioral Ecology* **25**, 967–974 (2014).

788   41.   D. B. Weissman, D. A. Gray, Crickets of the genus Gryllus in the United States
789   (Orthoptera: Gryllidae: Gryllinae). *Zootaxa* **4705**, 1–277 (2019).

790   42.   J. A. Cole, D. H. Funk, Anaxipha hyalicetra sp. n. (Gryllidae: Trigonidiinae), a new
791   sword-tailed cricket species from Arizona. *Journal of Orthoptera Research* **28**, 3–9
792   (2019).

793   43.   H. C. Bennet-Clark, The Tuned Singing Burrow of Mole Crickets. *Journal of*
794   *Experimental Biology* **128**, 383–409 (1987).

795   44.   P. Senter, Voices of the past: a review of Paleozoic and Mesozoic animal sounds:
796   review. *Historical Biology* **20**, 255–287 (2008).

45. H. Song, *et al.*, 300 million years of diversification: elucidating the patterns of
orthopteran evolution based on comprehensive taxon and gene sampling.
Cladistics **31**, 621–651 (2015).

46. J.-J. Gu, *et al.*, Wing stridulation in a Jurassic katydid (Insecta, Orthoptera)
produced low-pitched musical calls to attract females. *Proceedings of the National*
Academy of Sciences **109**, 3868–3873 (2012).

47. C. Woodrow, E. Baker, T. Jonsson, F. Montealegre-Z, Reviving the sound of a 150-
year-old insect: The bioacoustics of Prophalangopsis obscura (Ensifera:
Hagloidea). *PLOS ONE* **17**, e0270498 (2022).

48. H. Winkler, The Ecology of Avian Acoustical Signals in *Ecology of Sensing*, F. G.
Barth, A. Schmid, Eds. (Springer, 2001), pp. 79–104.

49. E. S. Morton, Ecological Sources of Selection on Avian Sounds. *The American*
Naturalist **109**, 17–34 (1975).

50. T. G. Forrest, From Sender to Receiver: Propagation and Environmental Effects on
Acoustic Signals. *Am Zool* **34**, 644–654 (1994).

51. K. Marten, P. Marler, Sound transmission and its significance for animal
vocalization. *Behav Ecol Sociobiol* **2**, 271–290 (1977).

52. K. Marten, D. Quine, P. Marler, Sound transmission and its significance for animal
vocalization. *Behav Ecol Sociobiol* **2**, 291–302 (1977).

53. R. H. Wiley, "Signal Transmission in Natural Environments" in *Encyclopedia of*
Neuroscience, (Elsevier, 2009), pp. 817–822.

54. U. Ingard, G. L. Lamb, Effect of a Reflecting Plane on the Power Output of Sound
Sources. *The Journal of the Acoustical Society of America* **29**, 743–744 (1957).

55. G. W. Swenson, M. J. White, The Field of a Sound Source Reflected from a Hard
Ground (2004).

56. K. Attenborough, I. Bashir, S. Taherzadeh, Outdoor ground impedance models.
The Journal of the Acoustical Society of America **129**, 2806–2819 (2011).

57. A. Putra, D. J. Thompson, Radiation efficiency of unbaffled and perforated plates
near a rigid reflecting surface. *Journal of Sound and Vibration* **330**, 5443–5459
(2011).

58. L. Jakobsen, J. M. Ratcliffe, A. Surlykke, Convergent acoustic field of view in
echolocating bats. *Nature* **493**, 93–96 (2013).

59. L. Jakobsen, A. Surlykke, Vespertilionid bats control the width of their biosonar
sound beam dynamically during prey pursuit. *PNAS* **107**, 13930–13935 (2010).

60.　B. Møhl, M. Wahlberg, P. T. Madsen, A. Heerfordt, A. Lund, The monopulsed
nature of sperm whale clicks. *The Journal of the Acoustical Society of America* **114**,
1143–1154 (2003).

61.　L. Jakobsen, J. Christensen-Dalsgaard, P. M. Juhl, C. P. H. Elemans, How Loud
Can you go? Physical and Physiological Constraints to Producing High Sound
Pressures in Animal Vocalizations. *Front. Ecol. Evol.* **9** (2021).

62.　L. Desutter-Grandcolas, Phylogeny and the evolution of acoustic communication in
extant Ensifera (Insecta, Orthoptera). *Zoologica Scripta* **32**, 525–561 (2003).

63.　Cigliano, M. M., Braun, D. C., Eades, D. C., Otte, D., Orthoptera Species File.
Orthoptera Species File. Version 5.0/5.0 (March 7, 2022).

64.　J. Schindelin, C. T. Rueden, M. C. Hiner, K. W. Eliceiri, The ImageJ ecosystem: An
open platform for biomedical image analysis. *Molecular Reproduction and*
Development **82**, 518–529 (2015).

65.　K. Lisa Yang Center for Conservation Bioacoustics at the Cornell Lab of
Ornithology, Raven Lite: Interactive Sound Analysis Software (Version 2.0) (2020).

66.　C. J. H. Elliott, U. T. Koch, The clockwork cricket. *Naturwissenschaften* **72**, 150–
153 (1985).

67.　S. Metrani, R. Balakrishnan, The utility of song and morphological characters in
delineating species boundaries among sympatric tree crickets of the genus
Oecanthus (Orthoptera: Gryllidae: Oecanthinae): a numerical taxonomic approach.
Journal of Orthoptera Research **14**, 1–16 (2005).

68.　H. C. Bennet-Clark, Resonators in insect sound production: how insects produce
loud pure-tone songs. *Journal of Experimental Biology* **202**, 3347–3357 (1999).

69.　F. Montealegre-Z, T. Jonsson, D. Robert, Sound radiation and wing mechanics in
stridulating field crickets (Orthoptera: Gryllidae). *Journal of Experimental Biology*
214, 2105–2117 (2011).

70.　N. Mhatre, F. Montealegre-Z, R. Balakrishnan, D. Robert, Changing resonator
geometry to boost sound power decouples size and song frequency in a small
insect. *PNAS* **109**, E1444–E1452 (2012).

71.　V. Godthi, R. Balakrishnan, R. Pratap, The mechanics of acoustic signal evolution
in field crickets. *Journal of Experimental Biology* **225**, jeb243374 (2022).

72.　J. W. Bradbury, S. L. Vehrencamp, *Principles of Animal Communication*, First
edition (Sinauer Associates, Inc., 1998).

73.　T. D. Rossing, Ed., *Springer Handbook of Acoustics* (Springer New York, 2014)
https:/doi.org/10.1007/978-1-4939-0755-7 (April 8, 2020).

74. H. Römer, Neurophysiology goes wild: from exploring sensory coding in sound
proof rooms to natural environments. *J Comp Physiol A* **207**, 303–319 (2021).

75. N. Mhatre, R. Balakrishnan, Phonotactic walking paths of field crickets in closed-
loop conditions and their simulation using a stochastic model. *Journal of*
Experimental Biology **210**, 3661–3676 (2007).

871
872

Figure 1. All crickets could increase efficiency by baffled calling. Sound radiation efficiency (SRE) landscape across the acoustic-morphospace of crickets. **A.** Representative images of cricket males with wings raised in calling posture. Species pictured are (from left): *Hoplosphyrum boreale*, *Phyllopalpus pulchellus, Lerneca inalata, Meloimorpha japonica, Oecanthus quadripunctatus*, and *Turanogryllus eous.* (Photos from left: James Bailey, Wilbur Hershberger, Richard C. Hoyer, Ryosuke Kuwahara, James P. Bailey and Taewoo Kim). Boxes with letter indicate the clade of each species. **B.** Phylogeny illustrating the seven clades defined by Chintauan-Marquier et al (2016) and subfamilies within each clade (branch lengths not to scale).

C. SRE_V achieved with different combinations of wing sizes vibrating at different frequencies.
Within this space of possibilities, wing areas and call frequencies of all sampled animals are
overlaid as points on the SRE landscape. This SRE_V is calculated from finite element models.
Red line indicates the point for optimal radiator size at each frequency, which corresponds to the
radiator size at each frequency that will have minimal short-circuiting and maximal efficiency. A
cricket singing from an optimal baffle would also experience minimal short-circuiting and lie on
this line, so the place where each animal's frequency intersects with the line is its baffled SRE_V.
D, E. Distributions of calling song frequency and wing size of different animals. Histograms
include additional species for which only wing or call measurements were available. **F.** SRE_V of
each species without use of a baffle. **G.** SRE_V of each species with use of an optimal baffle.

893
Figure 2. Sound propagation efficiency when the cricket sings near the bare hard ground is
orders of magnitude higher than in free space. Each panel represents a combination of caller
height above ground (0 m or 1 m) and receiver distance from caller (0.05 – 02 m "near" and 0.8 –
0.9 m "far"). **A.** Distance = near, height = 1m, **B.** Distance = far, height = 1 m; **C.** Distance = near,
height = 1 m, **D.** Distance = far, height = 0 m. Red lines indicate the optimal radiator size, or the
size at each frequency that would produce an ideally baffled calling scenario (see description of
baffle calculations for SRE$_V$). Note that the frequency range is reduced compared to Figure 1, in
order to exclude high frequency callers which likely use alternative vibrational modes. Each clade
of animals is represented by a colored ellipse. **E.** Phylogeny representing each clade **F**. Key to
clade represented by each ellipse.

904
905
Figure 3. The calling strategy with highest efficiency varies depending on species, whereas
directionality does not decrease greatly even with ground calling. Four representative species are
illustrated with lines. **A**. Comparison of SRE_T on bare ground with no baffle, and 1 m in vegetation
with and without an optimal baffle. These measurements were taken far from the caller, i.e., an
average of the SPL at a distance of 0.8-0.9 m from wings. Images below are not to scale and
show a schematic representation of the three different calling strategies. Red arrows represent
the location of acoustic short-circuiting. Blue arrows show sound reflection from the ground. In the
optimally baffled scenario, the baffle effectively increases the size of the radiators. In the ground
calling scenario, the ground provides some reduction of acoustic short-circuiting and halves the
air volume within which sound is radiated. It simultaneously reflects sound upwards, allowing
recapture of a significant amount of acoustic energy through constructive interference. Both
strategies improve efficiency to different degrees depending on the combination of wing size and
call frequency. **B.** Optimally baffled and ground calling do not substantially differ with respect to
directionality. Points are jittered slightly for clarity. The optimally baffled condition all had a
directionality of 1, so this condition is not shown. Note that the y-axis begins at 0.5.

Figure 4. Hard reflective surfaces like the ground or water offer all acoustically active animals an increase in sound radiation efficiency. **A.** The presence of a perfectly reflective surface near an acoustic source can lead to an increase of the power radiated in the hemisphere above the source, relative to the power that same source would radiate over a full spherical volume in free space. Both monopole and horizontal dipole sources (vibration axis parallel to the reflective surface) can get a large boost in power when they are close to the reflective surface, relative to the wavelength of sound being radiated. (Reproduced from equations in ref. (54)). In contrast, vertically oriented dipoles need to be further from the reflective surface to get an equivalent gain in efficiency. **B.** In fact, near the ground, the sound field from a dipole source is expected to become less directional and we observe this in our models. Data shown here are from a radiator of surface area of 126 mm^2 and at frequency 5 kHz, which is seen to be directional 1 m above the ground, but much less so when right next to the ground. **C-E.** Different animals, especially small animals who have low sound radiation efficiency whether they are monopole or dipole sources may call from near acoustically hard and reflective surfaces, like **C.** water, **D.** tree trunks, or even the **E.** ground may be exploiting this effect. (Photos from left: Doug Mills, Natasha Mhatre & Brandon Woo). Animals that are monopole-like sources are likely to orient themselves parallel to the surface since this is advantageous for camouflage as well. However, crickets (dipole-like acoustic sources), are constrained to expose themselves by calling with their wings perpendicular to the ground to maintain the advantageous horizontal dipole orientation.