Scene perception and visuospatial memory converge at the anterior edge of visually-responsive cortex

Adam Steel[1,*], Brenda D. Garcia[1], Kala Goyal[1], Anna Mynick[1], Caroline E. Robertson[1]

[1] Department of Psychological & Brain Sciences, Dartmouth College, Hanover, NH, 03755, USA.

* Lead contact: Adam Steel, Moore Hall, 3 Maynard Street, Dartmouth College, Hanover, NH 03755

Number of pages: 50

Number of figures: 8

Abstract: 250 words

Introduction: 642 words

Discussion: 1713 words

Data and code availability: All data and code reported in this paper will be shared by the lead contact upon request.

Acknowledgments: The authors would like to thank Yeo Bi Choi and Terry Sackett for assistance with data collection. This work was supported by grants from the National Science Foundation (#2144700) and NVIDIA to CER. AS is supported by the Neukom Institute for Computational Science.

Contributions: AS and CER conceived the idea and designed the research. BG programmed virtual reality software. KG and AM contributed tools. AS and BDG performed the research. AS, BDG, and AM analyzed the data. AS and CER wrote the paper.

Competing interests: The authors declare no competing interests.

Abstract

To fluidly engage with the world, our brains must simultaneously represent both the scene in

front of us and our memory of the immediate surrounding environment (i.e., local visuospatial

context). How does the brain's functional architecture enable sensory and mnemonic

representations to closely interface, while also avoiding sensory-mnemonic interference? Here,

we asked this question using first-person, head-mounted virtual reality (VR) and fMRI. Using VR,

human participants of both sexes learned a set of immersive, real-world visuospatial

environments in which we systematically manipulated the extent of visuospatial context

associated with a scene image in memory across three learning conditions, spanning from a single

field-of-view to a city street. We used individualized, within-subject fMRI to determine which

brain areas support memory of the visuospatial context associated with a scene during recall

(Exp. 1) and recognition (Exp. 2). Across the whole brain, activity in three patches of cortex was

modulated by the amount of known visuospatial context, each located immediately anterior to

one of the three scene perception areas of high-level visual cortex. Individual subject analyses

revealed that these anterior patches corresponded to three functionally-defined place memory

areas, which selectively respond when visually recalling personally familiar places. In addition to

showing activity levels that were modulated by the amount of visuospatial context, multivariate

analyses showed that these anterior areas represented the identity of the specific environment

being recalled. Together, these results suggest a convergence zone for scene perception and

memory of the local visuospatial context at the anterior edge of high-level visual cortex.

Significance statement

As we move through the world, the visual scene around us is integrated with our memory of the

wider visuospatial context. Here, we sought to understand how the functional architecture of the

brain enables coexisting representations of the current visual scene and memory of the

surrounding environment. Using a combination of immersive virtual reality and fMRI, we show

that memory of visuospatial context outside the current field-of-view is represented in a distinct

set of brain areas immediately anterior and adjacent to the perceptually-oriented scene-selective

areas of high-level visual cortex. This functional architecture would allow efficient interaction

between immediately adjacent mnemonic and perceptual areas, while also minimizing

mnemonic-perceptual interference.

56   Introduction

Perception is shaped by our immediate sensory input and our memories formed through prior

experience (Albright, 2012; Rust and Palmer, 2021). Yet, how memory influences ongoing

perception in the brain is poorly understood. A particular puzzle is how the brain enables sensory

and mnemonic representations to functionally interface, while avoiding interference that occurs

when the same neural population concurrently represents both sensory and mnemonic

information (Rust and Palmer, 2021). One elegant system for studying these questions is scene

perception, which relies heavily on concurrent mnemonic-sensory interactions: as we explore

our environment, memory of the visuospatial content immediately outside of the current field-

of-view informs what we will see next as we shift our gaze (Haskins et al., 2020; Draschkow et

al., 2022).

How does the brain's functional architecture support coexisting representations of the current

visual scene and memory of the surrounding environment? Recent studies suggest that scene-

related mnemonic and sensory information converge at the anterior edge of high-level visual

cortex (Baldassano et al., 2013, 2016; Silson et al., 2016; Bainbridge et al., 2020; Popham et al.,

2021; Steel et al., 2021). For example, we recently localized brain regions that preferentially

activated when participants recall personally familiar real-world places (e.g., their house) versus

faces (e.g., their mother). This revealed three patches of cortex located anterior and adjacent to

one of the three classic "scene perception areas" of high-level visual cortex that selectively

activated when recalling familiar places (Steel et al., 2021). These "place memory areas"

constituted a distinct functional network from the scene perception areas and co-fluctuated with

both spatial memory structures (i.e., the hippocampus) and scene perception areas, bridging

mnemonic and perceptual systems. Based on these results, we proposed that these paired

perceptually- and mnemonically-oriented functional networks may, respectively, represent

scenes and their remembered visuospatial context. This possibility is attractive because it would

allow efficient interaction between adjacent mnemonic and perceptual areas while minimizing

mnemonic-perceptual interference (Steel et al., 2021).

However, while previous work identified place-recall driven activity anterior to each of the scene-

perception areas, the content of the representations in these anterior regions is currently

unclear. This is partly because prior studies investigating place memory, including our own, used

participants' personally familiar real-world places as stimuli (e.g., 'your mother's kitchen') (Peer

et al., 2015, 2019; Steel et al., 2021). While personal memories elicit strong responses and are

appropriate for some experimental questions, these memories contain rich associations that go

beyond visuospatial content (i.e., the appearance of your mother's kitchen), including semantic

knowledge (e.g., where her kitchen is located), multisensory details (e.g., the smell of baking

cake), and episodic context (e.g., blowing our birthday candles). As a result, it is unclear whether

visuospatial memory *per se* is sufficient to engage the anterior memory areas. Likewise, whether

the anterior areas process information about the visuospatial context of a scene is currently

unknown.

To address this knowledge gap, we used head-mounted virtual reality (VR) to teach participants

a set of real-world environments. This approach allowed us 1) to ensure participants' memories

contained no confounding episodic information and limited semantic content, and 2) to precisely

manipulate the visuospatial context associated with each environment. We defined visuospatial

context as the spatial extent, configuration, and visual details of the local environment. Next, we

used individualized, within-subject fMRI to test whether, across the brain, the place memory

areas play a special role in processing visuospatial memory. Specifically, we asked whether these

areas represent the extent of the visuospatial context associated with a visual scene during recall

(Exp. 1) and visual recognition (Exp. 2) of single scene views from each place (Figure 1B-C). We

hypothesized that if the place memory areas process visuospatial context associated with a scene

view, i) their activity will reflect the degree of associated visuospatial context (Bar and Aminoff,

2003; Baumann and Mattingley, 2016) and ii) they should contain multivariate representations

of the scene's specific visuospatial content.

Figure 1. Experimental design to test processing of visuospatial context associated with a real-world scene. The experiment took

place over across three sessions, one study session, and two fMRI sessions. These sessions took place on three separate days. A.

In the VR study session, participants studied 20 real-world visual scenes with varying amounts of visuospatial context in head-

mounted virtual reality (VR). Each scene was associated with one of three levels of spatial visuospatial context: single images (45°

visible, 315° occluded), panoramas (270° visible, 90° occluded), and streets (three contiguous, navigable 360° photospheres).

During the two fMRI sessions, we tested the neural response during recall (B) and recognition (C) of the learned scenes using fMRI.

Methods

Participants

17 subjects (10 Female; age=21.6 ± 2.9 std years) participated in this experiment. This number

was based on a power calculation from our prior work, specifically based on the average effect

size observed when participants viewed panning movies of familiar versus unfamiliar scenes

across ROIs (Cohen's D = .76 with 80% power and Alpha = 0.05 requires a minimum of 16 subjects;

Experiment 2, (Steel et al., 2021)). Specifically, from our prior work, we calculated the difference

in activation between the place memory and scene perception areas on the lateral, ventral, and

medial surfaces to familiar versus unfamiliar videos, as this was our best proxy for visuospatial

context. We then took the average difference score across cortical surfaces for each subject and

used these values for our power calculation. We felt confident assuming this large effect size

because of the consistency in the effect across subjects (all subjects showed greater familiarity

effects in the place memory areas compared to the scene perception areas).

Participants were Dartmouth students and postdocs recruited via posters and word-of-mouth

advertising. They received monetary compensation for taking part in the study. Participants had

normal or corrected-to-normal vision, were not colorblind, and were free from neurological or

psychiatric conditions. Written consent was obtained from all participants in accordance with the

Declaration of Helsinki with a protocol approved by the Dartmouth College Committee for the

Protection of Human Subjects (CPHS).

Procedure

The study took place over three sessions (each on a different day): one study session and two

fMRI sessions. During the study session, participants studied 20 real-world places using a head-

mounted virtual reality (VR) system (see Stimulus Presentation section). The 20 places comprised

three spatial context conditions (see Stimuli section). During the first fMRI session (Experiment

1), we investigated which brain areas represent the level of known spatial context by assessing

the neural response across the three spatial context conditions using fMRI. During the second

fMRI session (Experiment 2), we tested whether the same regions that represent context during

recall also represent known spatial context during visual recognition by evaluating neural

responses when viewing images of the studied places. 17 participants took part in Experiment 1,

and 16 participants took part in Experiment 2.

Stimuli – Study Phase

Stimuli consisted of 20, 360° panoramic photospheres of outdoor real-world places from 5 cities

(Oslo, Philadelphia, Padua, Quebec, Seville), sourced from Google Maps using iStreetView

(istreetview.com). Participants were not told about the real-world locations from which the

photospheres were taken. Stimuli can be found on Open Science Framework in the 'panoramas'

folder: https://osf.io/3ygqb/?view_only=5f436411c021448abf5157df3f2b2f30. At the end of the

second fMRI session, we asked participants whether they recognized any photospheres from

real-life (i.e., had they been to any of these locations outside of VR). Importantly, no participant

recognized any stimuli, suggesting that real-world familiarity could not explain our results.

Example videos from the study phase on Open Science Framework in the 'trial videos' folder:

https://osf.io/3ygqb/?view_only=5f436411c021448abf5157df3f2b2f30. Stimuli were applied to

a virtual environment created in Unity (www.unity3d.com), and the experimental routine was

programmed using custom scripts written in C#.

The photospheres were divided into three spatial context conditions: 1) single images (45° from

a photosphere, 315° occluded by a grey screen), 2) panoramas (270° visible, 90° occluded), and

3) streets (three contiguous 360° photospheres tiling a city street, navigable via button press).

The cities were represented equally in all conditions (i.e., from each city, 2 photospheres were

used in as image trials, 1 photosphere was a panorama trial, and 3 contiguous photospheres

comprised a street trial). During the study session, we occluded a portion of the photosphere in

the Image and Panorama conditions to obscure the wider visuospatial context. Note that,

because of the unique demands of curating and presenting photospheres for the street

condition, all photospheres were assigned to the same conditions across participants. Therefore,

it is possible that different levels of memory for the photospheres could contribute to a Main

effect of condition in Exps. 1-2. Importantly, however, our *a priori* hypotheses deal with

interactions between conditions and ROI (i.e., differences in activation magnitude between

perceptual and mnemonic areas), which would not be impacted by this main effect of condition.

Moreover, we found no differences across conditions in our behavioral assessments of memory,

suggesting that condition-related differences we observed in neural activity were not driven by

stimulus-related effects.

Unbeknownst to the participants, the image condition was comprised of two sets of five images

derived from i) the occluded portion of the panorama condition and ii) an isolated photosphere

from an independent location within the same city. We found no difference between the image

conditions in any regions of interest during the recall and recognition experiments (Experiment

1 (recall): OPA: $t(16)=0.95$, $p=0.35$; PPA: $t(16)=0.81$, $p=0.43$; MPA: $t(16)=0.58$, $p=0.56$; LPMA:

t(16)=0.83, p=0.42; VPMA: t(16)=0.84, p=0.41; MPMA: t(16)=0.75; p=0.46; Experiment 2

(recognition): OPA: t=1.84, p=0.086; PPA: t(15)=0.0007, p=.99; MPA: t(15)=0.75, p=0.46; LPMA:

t(15)=0.013, p=0.99; VPMA: t(15)=0.86, p=0.40; MPMA: t(15)=0.63, p=0.53), so we considered

these images together as a single Image condition.

The Street condition consisted of three contiguous photospheres representing a city street. After

entering the trial, participants rotated 180° from their initial facing direction to see an arrow on

the floor, which indicated that they could advance forward. This rotation ensured that the key

scene view presented during fMRI (i.e., initial viewpoint) did not depict the extra visuospatial

context experienced by the participant. Participants advanced forward by pressing a button on a

handheld controller. Participants could advance forward two positions, allowing them to view

around a street corner unobservable from the initial position. Participants could not go backward

to revisit photospheres during the street trial (i.e., they could only travel 'one-way').

Stimulus presentation

During the study phase, experimental stimuli were presented to participants via an immersive,

head-mounted virtual reality display (16 Oculus Quest 2, 1 Oculus Go; Fast-switch LED display

panel 1832x1920 resolution per eye; 98° field of view; 120 Hz refresh rate). Participants stood

wearing the head-mounted VR display during the experiment. This setup offered participants a

self-directed opportunity to explore the naturalistic environment from an egocentric perspective

naturally via eye-movements and head turns. All fMRI stimuli were presented using Psychopy 3

(Version 3.2.3) (Peirce, 2007).

Procedure - Study phase

During the study session, participants studied all 20 scenes (20s each). Study trials automatically

terminated after 20 seconds. On each trial, participants were instructed to look naturally around

each environment, just as they would in real life. Importantly, although the view was restricted

in the Image and Panorama conditions, participants could still turn their heads and move their

eyes to naturally explore the environment. Therefore, the conditions only differed in the amount

of spatial context that participants learned.

Before and after each study trial, participants saw an associated place "name" (e.g., "Scallop

path") that later served as a cue during the fMRI recall experiment. We instructed participants to

learn these name-place pairings for a later memory test. After each experimental trial,

participants returned to a virtual home screen (a platform surrounded by clouds), where they

were instructed to take a break. Time between trials was self-paced (participants initiated the

beginning of a new trial via a button press).

During the study session, participants saw the 20 scenes grouped in blocks. No scene was

repeated during a study block. Scene order was randomized in each study block. All participants

completed at least 5 study blocks (approximately 1 hour of training, depending on subjective

confidence and availability). After the 5th block, we asked participants if they were confident that

they could recall each place; if participants were not confident, they completed one additional

study block. Importantly, all analyses below are within-subject, minimizing the potential impact

of across-subject differences in study session duration or stimulus familiarity.

All participants completed a "refresh" study block immediately before entering the scanner on

both scan sessions.

FMRI

Experiment 1: Memory recall

The goal of Experiment 1 was to determine what brain areas represent the known visuospatial

context associated with a scene view. To this end, we compared BOLD activation when

participants recalled places that varied in their degree of known spatial context.

Experiment 1 was performed across eight runs. Each place stimulus was cued once in each run

(20 trials/run). On each trial, participants saw the name of a place from the study phase (1 s),

followed by a dynamic mask of random alphanumeric characters that rapidly changed (1 s). After

the mask, the recall cue ('oooo') appeared on the screen for 10 s. We instructed participants to

perform mental imagery of a single field-of-view from the prompted place in as much detail as

possible while the recall cue was on the screen. The specific instructions given to the participant

are reproduced below.

"During scanning you will perform the memory recall task. In this task, you will

see the name of a place that you studied, followed by some scrambled letters

and numbers. Then four circles will appear on the screen. When the four circles

are on the screen, we want you to visually recall a view from the cued place as

vividly as you can. When you are doing the imagery, you should only imagine a

single image, whatever the first image that comes to mind when you are cued

for that place. So, for Church Street, you might immediately recall the church

at the top of the hill - you should hold that image in your mind the whole time

and not try to look around the place. When the cue goes away, a cross will

appear. When the cross is on the screen, clear your mind and prepare for the

next trial."

Imagery trials lasted 10 seconds and were separated by a jittered interstimulus interval (range 4-

8 s). The stimulus order was pseudo-randomized within each run so that conditions could only

repeat 2 times consecutively in an imaging run. Although stimuli were not presented in an

optimized sequence, we confirmed that our regressors were minimally collinear (correlation

between regressors < 0.2 for 100% of task regressors across participants) post-hoc using afni's

1d_tool.py.

Experiment 2: Spatial context during recognition

In Experiment 2, we assessed whether the same regions that represent known spatial context

during recall also represent contextual information during visual recognition. For this

experiment, we compared neural activity when participants viewed briefly presented images

while they performed an orthogonal familiarity judgement task. We hypothesized that by having

subjects perform a task that was unrelated to spatial context, any activation that was modulated

by spatial context would reflect implicit reactivation of contextual knowledge.

Experiment 2 was comprised of eight runs. Participants performed a familiar/novel judgement

task. On each trial, participants saw a single 45° portion of a photosphere (500 ms), and then

indicated whether they had studied the image in VR ('familiar') or not ('novel') (1500 ms). Trials

were separated by a jittered interstimulus interval (range 4-8 s). Each familiar stimulus was

presented once in each run, along with four novel stimuli (24 trials/run). The stimulus order was

pseudo-randomized so that conditions could only repeat two times per run. For consistency, all

stimuli were images looking down the center of a street, which limited the amount of identifying

visual information the participant saw. Because overall accuracy was high (greater than 92%

correct), all trials were included in the analysis.

Novel stimuli for each run were randomly sampled from a set of 10 images participants had not

experienced during the study session (2 novel images per city). One image was taken from the

unseen portion of the photosphere from the panorama condition (180° from the studied view).

The other was taken from a photosphere that had not been experienced by the participant and

always comprised a view looking down the street. The photospheres were chosen to be visually

similar to the other stimuli from their respective city.

Although stimuli were not presented in an optimized sequence, we confirmed that our stimulus

time series were minimally collinear (collinearity < 0.2 for 99.9% of task regressors across

participants) post-hoc using afni's 1d_tool.py

Localizer tasks

In addition to the main experimental tasks, participants underwent localizers to establish

individualized regions of interest for the scene perception areas (PPA, OPA, MPA) and place

memory areas (VPMA, LPMA, MPMA). We used the same localization procedure defined in our

prior work (Steel et al., 2021), briefly described below.

Scene perception localizer

To localize the scene perception areas, participants passively viewed blocks of scene, face, and

object images presented in rapid succession (500 ms stimulus, 500 ms ISI). Blocks were 24 s long,

and each run consisted of 12 blocks (4 blocks/condition). There was no interval between blocks.

Participants performed two runs of the scene perception localizer.

Place memory localizer

The place memory areas are defined as regions that selectively activate when an individual recalls

personally familiar places (i.e., their kitchen) compared with personally familiar people (i.e., their

mother). To establish individualized stimuli, prior to fMRI scanning, we had participants generate

a list of 36 personally familiar people and places (72 stimuli total). These stimuli were generated

based on the following instructions.

"For your scan, you will be asked to visualize people and places that are

personally familiar to you. So, we need you to provide these lists for us. For

personally familiar people, please choose people that you know in real life (no

celebrities) that you can visualize in great detail. You do not need to be in

contact with these people now, as long as you knew them personally and

remember what they look like. So, you could choose a childhood friend even if

you are no longer in touch with this person. Likewise, for personally familiar

places, please list places that you have been to and can richly visualize. You

should choose places that are personally relevant to you, so you should avoid

choosing places that you have only been to one time. You should not choose

famous places where you have never been. You can choose places that span

your whole life, so you could do your current kitchen, as well as the kitchen

from your childhood home."

During fMRI scanning, participants recalled these people and places. On each trial, participants

saw the name of a person or place and recalled them in as much detail as possible for the duration

that the name appeared on the screen (10 s, no dynamic mask). Trials were separated by a

variable ISI (4-8 s). Place memory areas were localized by contrasting activity when participants

recalled personally familiar places compared with people (see ROI definitions section).

MRI Acquisition

All data was collected at Dartmouth College on a Siemens Prisma 3T scanner (Siemens, Erlangen,

Germany) equipped with a 32-Channel head coil. Images were transformed from dicom to nifti

format using dcm2niix (v1.0. 20190902) (Li et al., 2016).

T1 image

For registration purposes, on Day 1, a high-resolution T1-weighted magnetization-prepared rapid

acquisition gradient echo (MPRAGE) imaging sequence was acquired (TR = 2300 ms, TE = 2.32 ms,

inversion time = 933 ms, Flip angle = 8°, FOV = 256 × 256 mm, slices = 255, voxel size = 1 ×1 ×

1 mm). T1 images were segmented and surfaces were generated using Freesurfer (Dale et al.,

1999; Fischl et al., 2002)(version 6.0) and aligned to the fMRI data using align_epi_anat.py and

@SUMA_AlignToExperiment (Argall et al., 2006; Saad and Reynolds, 2012).

On Day 2, we collected a fast anatomical scan (MPRAGE; TR = 2300 ms, TE = 2.32 ms, inversion

time = 933 ms, Flip angle = 8°, FOV = 256 × 256 mm, slices = 255, voxel size = 1 ×1 × 1 mm,

GRAPPA factor=4). The Freesurfer reconstructions from the scan collected in Day 1 were

registered to this scan for analysis of Experiment 2 using @SUMA_AlignToExperiment.

Functional MRI Acquisition

To mitigate the dropout artifacts and allow advanced BOLD preprocessing, FMRI data were

acquired using a multi-echo T2*-weighted sequence (Poser et al., 2006; Kundu et al., 2012, 2017;

Posse, 2012). The sequence parameters were: TR=2000 ms, TEs=[14.6, 32.84, 51.08], GRAPPA

factor=2, Flip angle=70°, FOV=240 x 192 mm, Matrix size=90 x 72, slices=52, Multi-band factor=2,

voxel size=2.7 mm isotropic. The initial two frames of data acquisition were discarded by the

scanner to allow the signal to reach steady state.

Preprocessing

Multi-echo data processing was implemented based on the multi-echo preprocessing pipeline

from afni_proc.py in AFNI (Cox, 1996). Signal outliers in the data were attenuated (3dDespike)(Jo

et al., 2013). Motion correction was calculated based on the second echo, and these alignment

parameters were applied to all runs.

The data were then denoised using multi-echo ICA denoising (tedana.py (Kundu et al., 2012;

Evans et al., 2015; DuPre et al., 2019, 2021)) to improve overall data quality in ventral temporal

and parietal cortex (Steel et al., 2022). In brief, the optimal combination of the three echoes was

calculated, and the echoes were combined to form a single, optimally weighted time series

(T2smap.py, included in the tedana package). PCA was applied, and thermal noise was removed

using the Kundu decision tree method. Subsequently, ICA was performed, and the resulting

components were classified as signal and noise based on the known properties of the T2* signal

decay of the BOLD signal versus noise. Components classified as noise were discarded, and the

remaining components were recombined to construct the optimally combined, denoised

timeseries.

Following denoising, images were smoothed with a 5 mm gaussian kernel (3dBlurInMask), and

signals were normalized to percent signal change.

ROI definitions

Scene perception and place memory areas (functionally defined)

Scene perception regions were established using the same criterion used in our prior work (Steel

et al., 2021). Scene and face areas were drawn based on a general linear test comparing the

coefficients of the GLM during scene versus face blocks. These contrast maps were then

transferred to the SUMA standard mesh (std.141) using @SUMA_Make_Spec_FS and

@Suma_AlignToExperiment (Argall et al., 2006; Saad and Reynolds, 2012). A vertex-wise

significance of p < 0.001 along with expected anatomical locations was used to define the regions

of interest (Julian et al., 2012; Weiner et al., 2018). As a control region, the FFA was defined using

the contrast of scenes versus faces using the same procedure.

To define category-selective memory areas, the familiar people/places memory data was

modeled by fitting a gamma function of the trial duration for trials of each condition (people and

places) using 3dDeconvolve. Estimated motion parameters were included as additional

regressors of no-interest. Polynomial regressors were not included in multi-echo data analysis.

Activation maps were then transferred to the SUMA standard mesh (std.141) using

@SUMA_Make_Spec_FS and @Suma_AlignToExperiment. People and place-memory areas were

drawn based on a general linear test comparing coefficients of the GLM for people and place

memory. A vertex-wise significance threshold of p < 0.001 was used to draw ROIs.

To ensure our ROIs were comparable in size, we further restricted all functional ROIs to the top

300 most selective vertices (Steel et al., 2021). Importantly, our results were consistent using

300-vertex ROIs defined using the ROI center of mass (rather than most selective vertices) as well

as 600 vertices rather than 300, suggesting that the results did not depend on the ROI definition.

Anatomical regions of interest

The hippocampus and primary visual cortex (occipital pole) were defined for each participant

using FreeSurfer's automated segmentation (aparc + aseg).

FMRI analysis

Experiment 1

Deconvolution

For Experiment 1, we employed two standard general linear model (GLM) analyses for i) group

whole-brain analysis and ii) univariate and multivariate ROI analyses.

For the group-based whole brain analysis, our general linear model included regressors for each

condition (Image, Panorama, Street) that considered each trial using a gamma function of

duration 10 s. In addition, a regressor for the memory cues and dynamic masks of each trial was

included as a regressor of no interest. These regressors, along with motion parameters and 4^{th}

order polynomials were fit to the data. Activation maps were then transferred to the SUMA

standard mesh (std.141) using @SUMA_Make_Spec_FS and @SUMA_AlignToExperiment (Argall

et al., 2006; Saad and Reynolds, 2012).

For ROI univariate and multivariate analyses, we analyzed data using a general linear model fit

with each trial modeled individually for each run using 3dDeconvolve. The memory recall period

for each trial was modeled as a single regressor using a gamma function of duration 10 s. In

addition, a regressor for the memory cue and dynamic mask was included as a regressor of no

interest using a gamma function of duration 1 s. These regressors, along with motion parameters

and 4^{th} order polynomials were fit to the data. Activation maps were then transferred to the

SUMA standard mesh (std.141) using @SUMA_Make_Spec_FS and @SUMA_AlignToExperiment

(Argall et al., 2006; Saad and Reynolds, 2012).

Whole-brain analysis

To locate where in the brain neural activity during recall was modulated by spatial context, we

conducted a whole-brain analysis on the cortical surface. Beta values for each condition from all

subjects were compared using a within-subject ANOVA (AFNI 3dANOVA2, type 3) with Condition

(Image, Panorama, Street) as a factor and Participant as a random effect. Data were thresholded

at a vertex-wise FDR-corrected p-value (q) =0.05 (F=6.4, p<0.0001). The result of this analysis (i.e.,

Main effect of Condition) was compared to the location of the place memory and scene

perception areas from an independent group of participants (Steel et al., 2021).

To determine whether the neural activity of any subcortical or allocortical structures (i.e.,

hippocampus) was modulated by spatial context, we conducted a volumetric whole-brain

analysis. Participants' anatomical data was registered to standard space (MNI template) using

auto_warp.py and the registration parameters were applied to their statistical maps. The beta

values for each condition were then compared using a within-subject ANOVA (AFNI 3dANOVA2,

type 3) with Condition (Image, Panorama, Street) as a factor and Participant as a random effect.

No subcortical or allocortical regions showed an effect of Condition even at a modest threshold

(p=0.05, uncorrected).

ROI analysis: Univariate

The t-values for all trials in all runs were extracted from all ROIs (scene perception areas [PPA,

OPA, MPA], place memory areas [VPMA, LPMA, MPMA], hippocampus, V1, FFA; see section *ROI*

definition, below). These t-statistics were averaged across runs and conditions, and these average

t-statistics were compared using an ANOVA implemented in Matlab (Matlab, Mathworks, Natick,

Massachusetts).

For comparison between the scene perception and place memory areas, ANOVAs were

conducted separately for each surface (Ventral, Lateral, Medial) with Condition (Image,

Panorama, Street), ROI (Scene perception, Place memory), and Hemisphere (left, right) as factors.

For all other regions (Hippocampus, V1, FFA), separate ANOVAs were used, with Condition

(Image, Panorama, Street) and Hemisphere (left, right) as factors. There was no significant effect

of hemisphere in any test (all ps>0.05), and thus data are presented collapsed across hemisphere.

Post-hoc tests were implemented using Bonferroni-corrected paired t-tests.

ROI-analysis: Multivariate

We sought to determine whether the scene perception and place memory areas contained

representations of the specific places that participants recalled. In other words, we tested

whether we could decode stimulus identity during trials of the recall experiment. To this end, we

performed an iterative split-half correlation analysis and looked for correspondence in the spatial

pattern of neural activity between each place across the two halves of the data. We focused on

identity decoding indices because condition (i.e., image, panorama, street) decoding could be

impacted by the differing response magnitude.

For this analysis, we iteratively half split our runs, such that we created all possible combinations

of half split data (total half splits = 70; iteration 1: 1,2,3,4 v 5,6,7,8; iteration 2, 1,2,3,5 v 4,6,7,8;

and so on). For each iteration, we averaged t-values for each place from half of the runs (e.g.,

odd versus even) together for each voxel within each ROI. We then calculated the correlation

matrix (Spearman's rho) across halves. This yielded a similarity matrix of all images for each ROI.

We then calculated the identity decoding index as the difference in correlation between the

pattern of response to a place with itself (across independent halves of data) compared to the

correlation of the places with the other members of its visuospatial context condition (i.e., images

were correlated with images, panoramas with panoramas, and streets with streets). This ensured

that condition-related effects could not explain our decoding results. This was iteratively

calculated for all combinations of runs.

Fisher-transformed correlation values for the scene perception and place memory areas on each

surface were separately compared to hippocampus and control regions (V1 and FFA) using an

ANOVA, with ROI (SPA, PMA, Hippocampus, FFA, V1) as a factor and Subject as a random effect.

Post-hoc tests were implemented using Bonferroni-corrected paired t-tests.

Experiment 2

Data was analyzed using a general linear model fit separately for each run using 3dDeconvolve.

Each familiar image trial was modeled as a single regressor using a gamma function of duration

2 s. In addition, a regressor for unfamiliar images was included as a regressor of no interest using

a gamma function of duration 2 s. Because unfamiliar images were not trial unique (i.e., some

unfamiliar stimuli were repeated across runs) and differed in number from the familiar images,

we could not analyze these data. These regressors, along with motion parameters and 3^{rd} order

polynomials were fit to the data. Activation maps were then transferred to the SUMA standard

mesh (std.141) using @SUMA_Make_Spec_FS and @SUMA_AlignToExperiment.

Whole-brain analysis

To locate where in the brain neural activity during recall was modulated by spatial context, we

conducted a whole-brain analysis on the cortical surface. Beta values for each condition from all

subjects were compared using a within-subject ANOVA (AFNI 3dANOVA2, type 3) with Condition

(Image, Panorama, Street) as a factor and Participant as a random effect. Data were thresholded

at a vertex-wise FDR-corrected p-value (q) =0.05 (F=8.1, p<0.0001). The result of this analysis (i.e.,

Main effect of Condition) was compared to the location of the place memory and scene

perception areas from an independent group of participants (Steel et al., 2021).

To determine whether the neural activity of any subcortical or allocortical structures (i.e.,

hippocampus) was modulated by spatial context, we conducted a volumetric whole-brain

analysis. Participants' anatomical data was registered to standard space (MNI template) using

auto_warp.py and the registration parameters were applied to their statistical maps. The beta

values for each condition were then compared using a within-subject ANOVA (AFNI 3dANOVA2,

type 3) with Condition (Image, Panorama, Street) as a factor and Participant as a random effect.

As we found in experiment 1, no subcortical or allocortical regions showed an effect of Condition

even at a modest threshold (p=0.05, uncorrected).

ROI analysis

In Experiment 2, we sought to determine whether the regions in which activation reflected spatial

context during recall also reflect this information during visual recognition. So, we employed the

same univariate ROI analysis approach taken in Experiment 1.

The t-values for all trials in all runs were extracted from all ROIs (Scene perception areas [PPA,

OPA, MPA], Place memory areas [VPMA, LPMA, MPMA], Hippocampus, V1, FFA; see section *ROI*

definition, below). These t-statistics were averaged across runs and conditions, and we compared

these average values using an ANOVA implemented in MATLAB.

For comparison between the scene perception and place memory areas, ANOVAs were

conducted separately for each surface (Ventral, Lateral, Medial) with Condition (Image,

Panorama, Street), ROI (Scene perception, Place memory), and Hemisphere (left, right) as factors.

For all other regions (Hippocampus, V1, FFA), separate ANOVAs were used, with Condition

(Image, Panorama, Street) and Hemisphere (left, right) as factors. There was no significant effect

of hemisphere in any test (all ps>05), and thus data are presented collapsed across hemisphere.

Post-hoc tests were implemented using Bonferroni-corrected paired t-tests.

Post-scan questionnaires

Vividness

To ensure that any differences in neural responses across the conditions during recall were not

due to a difference in vividness of imagery, we queried participants on their experience after the

scan. Specifically, participants rated each stimulus on the overall vividness of their visual imagery

on a 1-5 scale (1: Not able to visualize, 5: As though they were looking at the image). We

compared the average ratings across conditions using an ANOVA with Condition (Image,

Panorama, Street) as a Factor and Subject as a random effect.

Image naming test

To ensure participants could remember the trained images, participants performed an image

naming test after completing Experiment 2. Eleven participants completed the recognition test;

the remaining participants were not able to be contacted. One participant performed the naming

task after substantial delay (> 2 weeks after fMRI scanning) and was therefore excluded from this

analysis. Participants were shown the images used in the Experiment 2 scan session and had to

report the place name. We compared the accuracy across the conditions using an ANOVA with

Condition (Image, Panorama, Street) as a Factor and Subject as a random effect.

Results

Participants (N=17) learned a set of 20 immersive, real-world visuospatial environments in head-

mounted VR. Each environment depicted a small portion of a city (e.g., Padua, Seville, etc.) where

participants had never been. These environments comprised three levels of visuospatial context:

1) single images (45° from a photosphere, 315° occluded by a grey screen), 2) panoramas (270°

visible, 90° occluded), and 3) streets (three contiguous 360° photospheres tiling a city street,

navigable via button press) (Figure 1A, see Methods). In the street condition, the final

photosphere allowed the participant to look around a corner to view visuospatial information

that could not be seen from their original position, which ensured that the known visuospatial

context in this condition was greater than the panorama condition. The cities were equally

balanced across the conditions to control for visual and semantic components unique to each

city.

Participants explored each environment from a first-person perspective using head turns and eye

movements for 20-seconds and learned: i) each visuospatial environment and ii) a name

associated with each environment. After studying, participants could vividly imagine each scene

and accurately recall each scene-name pairing (see 'Post-scan behavioral results confirmed

memory success', below). Then, we used fMRI to assess which brain areas process visuospatial

context during recall (Exp. 1; Figure 1B) and visual recognition (Exp. 2, Figure 1C). In these tasks,

participants either visually recalled or viewed pictures of a single scene view from each place (the

key scene view, Figure 1).

We began by identifying any brain areas where visuospatial context associated with scenes

learned in VR modulated recall-related activation using an exploratory whole-brain ANOVA with

Condition (Image, Panorama, Street) as a factor and Subject as a random effect. In other words,

we tested where in the brain activity was modulated by the extent of visuospatial context

associated with a scene. The logic of this test builds on studies in the object memory literature

showing that association cortex responds more strongly to objects with strong associated context

(e.g., a bowling pin, which is strongly associated with a bowling alley) vs. weak associated context

(e.g., a chair) (Bar and Aminoff, 2003; Baumann and Mattingley, 2016). These univariate effects

are thought to reflect activation of brain areas that harbor information from memory associated

with a percept – in our case visuospatial context associated with a scene.

This group-level, whole-brain analysis revealed several distinct clusters in posterior cerebral

cortex that were modulated by known visuospatial context (Figure 2). Three clusters, in

particular, were located immediately anterior to the three scene perception areas (OPA, PPA and

MPA), as identified in an independent group of participants (Steel et al., 2021). In fact, the

location of these clusters closely corresponded to the location of the "place memory areas",

three brain areas on the brain's lateral (LMPA), ventral (VMPA), and medial surfaces (MPMA) that

selectively respond when participants recall or perceive familiar places, as defined by a group

mask from our previous work (Steel et al., 2021). On the ventral surface, the cluster fell at the

anterior edge of the VPMA, which largely overlaps with the parahippocampal cortex (Glasser et

al., 2016), a region known to represent an animal's relative position within an environment

(Julian et al., 2018; LaChance et al., 2019; LaChance and Taube, 2022) (Figure 2). These results

confirm that the place memory areas, which we previously showed are activated during recall of

personally familiar places (Steel et al., 2021), are active during recall of a purely visuospatial

environment (i.e., a photosphere learned in VR, which is devoid of episodic or semantic

information). Having found that the place memory areas are engaged during visuospatial recall

even when episodic and semantic information is controlled, we went on to test whether these

areas play a role in processing visuospatial context.

Place memory area activity reflects known visuospatial context associated with a scene view during recall

While whole-brain analyses are powerful exploratory tools, they obscure the highly detailed and idiosyncratic location of functional areas present at the individual participant-level (Braga and Buckner, 2017; Gordon et al., 2017; Braga et al., 2019; DiNicola et al., 2020). So, to determine whether the place memory and scene perception areas have dissociable roles when processing visuospatial context, we adopted an individualized ROI-based approach. We independently localized each participant's OPA, PPA, MPA, and place memory areas on the lateral, ventral, and medial surfaces (LMPA, VPMA, MPMA) (see Methods). We then compared regional activation when participants recalled (Exp. 1) or visually recognized (Exp. 2) the scene views across the three visuospatial context conditions. For each cortical surface, we used an ANOVA with Condition

(Image, Panorama, Street), ROI (scene perception/place memory area), and Hemisphere (lh/rh)

as factors and Subject as a random effect. Because we found no effect or interaction with

hemisphere, results are presented averaged across hemispheres.

Visuospatial context specifically modulates place memory area activity during recall

Figure 3. The extent of visuospatial context associated with a scene view modulates place memory area activation during recall.

A. For each participant, we compared activation of individually-localized scene perception and place memory areas across the

visuospatial context conditions during recall using an ANOVA with ROI (perception/memory area), visuospatial context (image,

panorama, street [i,p,s]) and hemisphere as factors. Across all cortical surfaces, the place memory area activation was modulated

by spatial context to a greater degree than the scene perception areas. Grey dots indicate individual participants. See Figure S1.1-

1.3 for control areas. B. Time course of activation during recall (in seconds) shows differential responses of the scene perception

and place memory areas. On all cortical surfaces, the place memory areas showed robust activation during recall (4-12 seconds),

*while the scene perception areas on the ventral and lateral surfaces did not. Grey lines indicate SEM at each TR (2s). *: p<0.05,*

**: p<0.01, ***: p<0.005

This analysis revealed a remarkable dissociation between the scene perception areas and their

anterior, memory-driven counterparts (the place memory areas) (Figure 3A). Namely, on all

cortical surfaces, visuospatial context modulated place memory area activity, while the scene

perception areas were largely unaffected.

On the lateral surface, LPMA activation increased concomitantly with visuospatial context, while

OPA did not (ROI x Condition interaction: $F_{(2,203)}=14.7$, $p<0.0001$; post-hoc ANOVAs – OPA:

$F_{(2,101)}=0.38$, $p_{corr}=0.99$; LPMA: $F_{(2,101)}=10.48$, $p_{corr}=0.0006$; difference across conditions (i.e.,

difference of differences): LPMA versus OPA – Panorama versus Image: $t_{(16)}=2.771$,

$p_{corr}=0.0408$, Cohen's $d=0.672$; Panorama versus Street: $t_{(16)}=2.767$, $p_{corr}=0.0411$, $d=0.671$;

Street versus Image: $t_{(16)}=5.21$, $p_{corr}<0.001$, $d=1.26$). The same pattern was present on the

ventral surface – VPMA's activation increased across the conditions, but PPA's did not (ROI x

Condition interaction $F_{(2,203)}=5.29$, $p=0.01$; post-hoc ANOVAs – PPA: $F_{(2,101)}=3.58$, $p=0.078$;

LPMA: $F_{(2,101)}=8.19$, $p_{corr}=0.0078$; difference across conditions: VPMA versus PPA – Panorama

versus Image: $t_{(16)}=0.13$, $p_{corr}=0.99$, Cohen's $d=0.078$; Panorama versus Street: $t_{(16)}=2.68$,

$p_{corr}=0.048$, $d=0.065$; Street versus Image: $t_{(16)}=2.83$, $p_{corr}=0.036$, $d=0.69$). On the medial surface,

both the MPA and MPMA activity increased with visuospatial context, which likely reflects the

high degree of overlap between these regions (Steel et al., 2021) (MPA: $F_{(2,101)}=12.95$, $p<0.001$;

post-hoc test: LPMA versus OPA – Panorama versus Image: $t_{(16)}=4.68$, $p_{corr}<0.001$, $d=0.74$;

Panorama versus Street: $t_{(16)}=2.55$, $p_{corr}=0.06$, $d=0.64$; Street versus Image: $t_{(16)}=4.12$,

$p_{corr}<0.001$, $d=1.17$; MPMA: $F_{(2,101)}=19.18$, $p<0.001$; post-hoc test: Panorama versus Image:

$t_{(16)}=5.61$, $p_{corr}<0.001$, $d=0.88$; Panorama versus Street: $t_{(16)}=3.15$, $p_{corr}=0.018$, $d=0.84$; Street

versus Image: $t_{(16)}=5.02$, $p_{corr}<0.001$, $d=1.51$). However, consistent with the lateral and ventral

surfaces, activity in MPMA was modulated by spatial context to a greater degree than MPA (ROI

x Condition interaction: $F_{(2,203)}=4.24$, $p=0.023$; post-hoc test: MPMA versus MPA – Panorama

versus Image: $t_{(16)}=2.01$, $p_{corr}=0.18$, $d=0.49$; Panorama versus Street: $t_{(16)}=1.4$, $p_{corr}=0.51$,

$d=0.35$; Street versus Image: $t_{(16)}=2.75$, $p_{corr}=0.042$, $d=0.69$).

To summarize, in contrast to the scene perception areas, all three place memory areas showed

a strong effect of visuospatial context. Additionally, control regions occipital pole (V1) and

fusiform face area (FFA) (Kanwisher et al., 1997), were not modulated by visuospatial context

(V1: $F_{(2,101)}=1.68$, $p=0.20$; FFA: $F_{(2,50)}=0.78$, $p=0.46$; Figure 4). Further, activity of the

hippocampus, which is involved in scene construction from memory (Spiers and Maguire, 2006;

Hassabis and Maguire, 2009; Zeidman et al., 2015; Zeidman and Maguire, 2016; Barry et al., 2019)

and represents the spatial scale of large environments (Baumann and Mattingley, 2013; Brunec

et al., 2018; Peer et al., 2019) was not modulated by visuospatial context (F(2,101)=0.13, p=0.87;

Figure 4). Together, these results emphasize the specificity of visuospatial context activity

modulation to the place memory areas.

Figure 4. Analysis of control areas suggests that modulation by visuospatial context during recall is specific to the place memory

areas. To determine whether visuospatial context was processed outside of the place memory areas, we considered additional

regions for analysis: an early visual area (occipital pole, anatomically defined), a high-level visual area that selectively responds

to faces rather than scenes (fusiform face area, FFA; functionally defined), and an area known to be involved in mnemonic

processing (hippocampus, anatomically defined). No region was modulated by visuospatial context during recall. (I: Image, P:

Panorama, S: Street)

In addition to exhibiting different activation patterns across the conditions, the place memory

and scene perception areas showed markedly different overall activity magnitude during recall.

Scene perception areas OPA and PPA were not activated above baseline in any condition (OPA –

all ts<1.30, ps>0.21; PPA – all ts<1.11, ps>0.28). On the other hand, their respective place

memory areas were significantly active in all conditions (LPMA – all ts>2.95, ps>0.009, ds>0.72;

VPMA – all ts>6.99, ps>0.0001, ds>1.69). This pattern can be readily observed by examining each

region's activity timeseries (Figure 3B). This result, which is consistent with our prior work (Steel

et al., 2021), suggests that the scene-selective perceptual areas may not play an active role in

memory reinstatement, but instead are principally involved in processing visual input.

These univariate results suggest that the place memory areas process the extent of visuospatial

context associated with a scene. But do the place memory areas actually represent the specific

environment being recalled? To answer this question, we turned to multivariate analyses. We

used an iterative split half correlation analysis to determine whether we could decode the

recalled environment's identity from the place memory areas. Importantly, to ensure that

condition-related differences did not account for our ability to discriminate across the recalled

environments, we calculated identity discrimination within each condition separately (i.e., only

image vs image, panorama vs panarama, and street vs street discrimination was considered). We

found that the place memory areas represented the stimulus identity during recall (LPMA:

$t(16)=3.13$, $p=0.0065$, $d=0.89$; VPMA: $t(16)=3.57$, $p=0.0026$, $d=0.95$; MPMA: $t(16)=4.71$, $p<0.001$,

$d=1.14$; Figure 5). Intriguingly, the scene perception areas also represented the scene being

recalled (Lateral – OPA: $t(16)=3.517$, $p=0.009$, $d=0.85$; Ventral – PPA: $t(16)=5.78$, $p<0.001$, $d=1.40$;

Medial – MPA: $t(16)=4.558$, $p<0.01$, $d=1.11$). On average, the scene perception areas contained

significantly more identity-related information compared to our control areas V1, FFA, and

hippocampus (perception areas vs V1: $t(16)=2.77$, $p=0.012$, $d=0.67$; vs FFA: $t(16)=2.55$, $p=0.02$,

$d=0.62$; hippocampus: $t(16)=4.93$, $p<0.0001$, $d=1.20$), and the place-memory areas showed a

similar trend (memory areas vs V1: $t(16)=1.89$, $p_{one-tailed}=0.0378$, $d=0.4607$; vs FFA: $t(16)=1.76$,

$p_{one-tailed}=0.043$, $d=0.4274$; hippocampus: $t(16)=4.36$, $p=0.0005$, $d=1.06$). Because the OPA and

PPA showed no univariate modulation during recall, we suggest that the stimulus-relevant

information in these areas arises via feedback from the place memory areas.

Figure 5. The place memory and scene perception areas represent the identity of the stimulus being recalled. Upper. Representational similarity matrix showing stimulus x stimulus correlation of the pattern of activity within each ROI. Each cell represents the similarity of activation patterns between two stimuli derived from an iterative half-split multi-voxel pattern analysis. The matrix diagonals represent the average similarity of a stimulus with itself across each data split (identity). Stimuli are grouped by condition (colored axis labels: image, panorama, street). Lower. Identity discrimination index for the place memory and scene perception areas. To ensure that condition-related differences could not explain identity decoding, we examined the ability to discriminate stimulus identity by comparing the average similarity between a stimulus and itself versus other stimuli within its condition. Both the scene perception and place memory areas evidenced significant identity discrimination (*=p<0.05, **=p<0.01, ***=p<0.005).

Together, the results of Exp. 1 confirmed that the place memory areas' activity: i) reflects the extent of visuospatial context associated with the key scene view and ii) contains stimulus-specific information, as would be required if they represent the remembered local visuospatial environment.

Place memory area activity reflects visuospatial context during visual recognition

Investigating neural activity during memory recall (Exp. 1) allowed us to look directly for regions

processing unseen visuospatial information. Yet focusing on an explicit recall task has limitations.

First, hypothetically, acting effectively in the real-world requires representing visuospatial

context online along with incoming visual information (Haskins et al., 2020; Ryan and Shen, 2020;

Rust and Palmer, 2021; Draschkow et al., 2022). Thus, we would expect a region that represents

visuospatial context should also be involved in perception by implicitly reactivating contextual

information from memory during recognition of perceived scene views. Second,

methodologically, we do not know the precise content of participants' imaginations, so

magnitude differences in our explicit recall task could arise from the amount of information being

recalled if participants recalled multiple scene views on each trial, or different scene views in

different trials. Furthermore, although participants were instructed to recall a single field of view

on each trial, internal reorientation during recall could activate the cortical head-direction

network (Taube, 2007; Baumann and Mattingley, 2010; Shine et al., 2016; Nau et al., 2020) and

potentially drive the apparent effect of visuospatial context observed in the place memory areas.

To address these limitations, we next turned to a visual recognition paradigm (Exp. 2). In Exp. 2,

we briefly (500ms) presented the key scene view from each learned environment and

participants performed an old/new judgment (Figure 6). We presented stimuli briefly to

discourage participants from explicitly recalling unseen details and to ensure that the task

primarily engaged recognition. In addition, we chose a recognition task to ensure that

participants were not performing any mental reorientation that could activate the head direction

network. Therefore, any difference in activation across the conditions would likely reflect implicit

reactivation of visuospatial context rather than explicit, constructive mnemonic processes. We

hypothesized that activity in the place memory areas would reflect the amount of known spatial

context when performing a recognition task on a visually recognized scene. On the other hand,

the scene perception areas would be active during the recognition task (because scenes are being

perceived), but their activation magnitude would not reflect the amount of spatial context

associated with the perceived scene.

Do the place memory areas process visuospatial context during recognition? Consistent with

their roles in visual scene processing, all scene perception and place memory areas responded

significantly during the recognition task (all ts>2.64, ps < 0.0187, ds>0.65). Importantly, however,

we again found that visuospatial context specifically modulated activity in the place memory

areas. On the lateral surface, visuospatial context impacted LPMA activity significantly more than

OPA (ROI x Condition interaction: $F(2,191)=6.95$, $p=0.003$; post-hoc ANOVAs – OPA: $F(2,95)=3.51$,

$p=0.085$; LPMA: $F(2,95)=11.93$, $p=0.0004$; difference across conditions: LPMA versus OPA –

Panorama versus Image: $t(15)=2.41$, $p_{corr}=0.084$, $d=0.60$; Panorama versus Street: $t(15)=1.35$,

$p_{corr}=0.594$, $d=0.34$; Street versus Image: $t(15)=3.567$, $p_{corr}=0.006$, $d=0.89$). On the ventral

surface, both PPA and VPMA activation was modulated by the amount of known visuospatial

context. However, VPMA was modulated to a significantly greater degree ($F(2,191)=9.95$,

$p=0.005$; post-hoc ANOVAs – PPA: $F(2,95)=6.19$, $p=0.01$; VPMA: $F(2,95)=13.23$, $p=0.0002$;

difference across conditions: VPMA versus PPA – Panorama versus Image: $t(15)=2.55$, $p_{corr}=0.06$,

$d=0.63$; Panorama versus Street: $t(15)=2.21$, $p_{corr}=0.129$, $d=0.55$; Street versus Image: $t(15)=4.19$,

$p_{corr}<0.001$, $d=1.05$). On the medial surface, both MPA and MPMA activation reflected

visuospatial context, and these regions did not differ in their scaling across conditions (ROI x

Condition – $F(2,191)=1.75$, $p=0.19$; Main effect of Condition – MPA: $F(2,95)=12.94$, $p < 0.001$;

post-hoc test: Panorama versus Image: $t(15)=2.18$, $p_{corr}=0.135$, $d=0.746$; Panorama versus Street:

$t(15)=3.15$, $p_{corr}=0.018$, $d=1.01$; Street versus Image: $t(15)=4.50$, $p_{corr}=0.0012$, $d=1.62$; MPMA:

$F(2,95)=14.31$, $p < 0.001$; post-hoc test: Panorama versus Image: $t(15)=2.385$, $p_{corr}=0.123$, $d=0.98$;

Panorama versus Street: $t(15)=2.92$, $p_{corr}=0.033$, $d=1.20$; Street versus Image: $t(15)=5.32$,

$p_{corr}<0.0001$, $d=2.24$). Importantly, control ROIs FFA and V1 were not modulated by spatial

context (V1: $F(2,95)=0.29$, $p=0.74$; FFA: $F(2,47)=3.02$, $p=0.06$; Figure 7). Although FFA approached

significance, this was driven by lower activation to street images, which is opposite to the place

memory areas. Likewise, hippocampal activity was not significantly modulated by visuospatial

context during recognition ($F(2,95)=3.02$, $p=0.06$; Figure 7). While the effect of visuospatial

context during recognition approached significance, this was driven by lower activation to

panoramas compared to streets and images.

Figure 6. The extent of visuospatial context associated with a scene view modulates place memory area activation during the

perceptual recognition task. A. We compared activation of the scene perception and place memory areas across visuospatial

context conditions during recognition using an ANOVA with ROI (perception/memory area), visuospatial context (image,

panorama, street [i,p,s]) and hemisphere as factors. On the lateral and ventral surfaces, the place memory area activation was

modulated by visuospatial context to a greater degree than the scene perception areas. On the medial surface, activity of both

*the scene perception and place memory area was modulated by known visuospatial context. *: p<0.05, **: p<0.01, ***: p<0.005*

Figure 7. Analysis of control areas suggests that modulation by visuospatial context during recall is specific to the place memory

areas. To determine whether visuospatial context was processed outside of the place memory areas, we considered additional

regions for analysis: an early visual area (occipital pole, anatomically defined), a high-level visual area that selectively responds

to faces rather than scenes (fusiform face area, FFA; functionally defined), and an area known to be involved in mnemonic

processing (hippocampus, anatomically defined). No regions outside the place memory areas were significantly modulated by

visuospatial context during recognition. I: image, P: panorama, S: Street

Finally, we wanted to determine whether the modulation by known visuospatial context was

specific to the place memory areas. To answer this question, we turned to a whole-brain analysis

(Figure 8). As we found in Experiment 1, the modulation by visuospatial context was remarkably

specific: within posterior cerebral cortex, significant vertices fell largely within the place memory

areas and did not appear in other category-selective areas. Notably, at the whole brain level, the

lateral place memory area contained only a small number of significant vertices compared to the

ventral and medial place memory areas; this is likely due to the heterogeneity in the location of

the lateral place memory area across participants. Thus, the effect of visuospatial context on

activation during recognition is largely restricted to the place memory areas.

Figure 8. Modulation by spatial context across the brain during recognition. We compared neural activation across the visuospatial

context conditions (Image, Panorama, and Street) using a vertex-wise ANOVA. We found that three clusters showed significant

modulation by known spatial context, which fell largely within the place memory areas (black). Whole brain analysis thresholded

The results of Exp. 2 suggest that, during visual recognition, the lateral and ventral place memory

areas represent the visuospatial context associated with a visual scene to a greater degree than

their perceptual counterparts, while MPA and MPMA both appear to process visuospatial

context. Together with the result of Exp. 1, these data suggest that perceptual information from

the visual system and contextual information from memory converge anterior to each of the

scene perception areas, in the place memory areas.

Post-scan behavioral results confirmed memory success

To ensure that systematic differences in i) subjective vividness and ii) memory strength could not

explain the difference in neural activity across conditions, we had participants perform two

behavioral assessments after MRI scanning. First, participants rated their ability to vividly imagine

each stimulus on a 1-5 scale, with 5 being the most vivid. Participants reported strong overall

ability to imagine the learned scenes (4.31 ± 0.5 STD) and reported no difference in imagery

ability across the conditions ($F_{(2,50)}=3.03$, $p=0.06$). Although this analysis approached

significance, it reflects a decrease in vividness in the street condition compared to the image and

panorama condition, which is in the opposite direction to our magnitude analysis results. Second,

a subset of participants completed a naming test. In the naming test, participants were shown

each key scene view and provided the name of the associated environment. Participants'

responses were highly accurate on this difficult memory assessment (0.86 ± 0.20 STD), and their

accuracy did not differ across the conditions ($F_{(2,32)}=2.48$, $p=0.109$). These results suggests that

the observed differences in activation across conditions in the place memory areas reflects

visuospatial context rather than other behavioral factors.

Discussion

A central debate in neuroscience concerns the neural mechanisms facilitating the interplay of

mnemonic and sensory information in the brain. This topic is particularly relevant for real-world

scene perception, which requires representing properties of the environment that are outside

the current field of view to inform ongoing perception and behavior (Robertson et al., 2016;

Haskins et al., 2020; Berens et al., 2021; Draschkow et al., 2022). Yet, while the neural systems

representing visual scenes are relatively well-understood (Epstein and Kanwisher, 1998; Maguire

et al., 1998; Hasson et al., 2002; Malach et al., 2002; Epstein et al., 2007a; Dilks et al., 2013, 2022;

Silson et al., 2015; Kamps et al., 2016; Malcolm et al., 2016; Bonner and Epstein, 2017a; Epstein

and Baker, 2019; Lescroart and Gallant, 2019), how memory for the surrounding environment

interfaces with scene processing is largely unknown. On one hand, visual cortex could jointly

represent mnemonic and sensory information to facilitate memory-based perception (D'Esposito

et al., 1997; O'Craven and Kanwisher, 2000; Rademaker et al., 2019). On the other hand,

dedicated systems might respectively harbor mnemonic and sensory information to prevent

mnemonic-perceptual interference (Spreng et al., 2009; Ranganath and Ritchey, 2012; Ritchey et

al., 2015; Barnett et al., 2020; Ritchey and Cooper, 2020).

Our results suggest an intriguing third possibility. Here, we demonstrate that recalling a

visuospatial environment activates a functional network immediately anterior and adjacent to

the three scene-selective areas of high-level visual cortex, the "place memory network" (Steel et

al., 2021). This arrangement could allow efficient mnemonic-perceptual interaction while

minimizing mnemonic-perceptual interference. Although we previously identified the place

memory network and described its responses to familiar stimuli and its connectivity, the nature

of mnemonic processing in these areas was not clear (Steel et al., 2021). The present study offers

three insights into the place memory areas' mnemonic representations. First, by using virtual

reality, we show that visuospatial information alone may be sufficient to drive activity in the place

memory areas, implying that the episodic and multisensory details present in personally familiar

memories may not be required. Second, we observed that the amount of known visuospatial

context associated with a scene modulates the anterior areas' activity during recall and

recognition, suggesting that these areas process visuospatial content associated with a scene

view. Third, using MVPA, we show that the place memory areas represent the specific

environment being recalled, which we had not demonstrated in our prior work (Steel et al., 2021).

Taken together with prior work showing an anterior shift for mnemonic compared with visual

information for scenes (Baldassano et al., 2013, 2016; Rugg and Thompson-Schill, 2013; Silson et

al., 2016, 2019; Peer et al., 2019; Bainbridge et al., 2020; Steel et al., 2021; Srokova et al., 2022),

these results suggest that the place memory areas likely play a key role in memory-guided scene

perception by processing the remembered visuospatial context of a scene.

The conventional view of scene perception is that integration of mnemonic and perceptual

information occurs in the MPA (a.k.a., retrosplenial complex) (Malcolm et al., 2016; Epstein and

Baker, 2019; Dilks et al., 2022). This view is based on reports showing that mnemonic tasks

engage MPA. For example, unlike OPA and PPA, MPA responds preferentially to familiar versus

unfamiliar images, and MPA activates more than OPA or PPA in memory tasks that involve linking

a scene view with its environment context (Epstein et al., 2007b). Further, unlike OPA and PPA,

MPA jointly represents both egocentric viewpoint of the current scene and the viewer's

allocentric position within the environment (Vass and Epstein, 2013; Marchette et al., 2014; Shine

et al., 2016; Nau et al., 2020). In contrast, PPA and OPA are implicated in perceptually-oriented

functions: scene categorization (Persichetti and Dilks, 2019; Dilks et al., 2022) and visually guided

navigation (Julian et al., 2016; Bonner and Epstein, 2017b; Lescroart and Gallant, 2019),

respectively (Dilks et al., 2022). Thus, the scene perception areas appeared to differ in their

degree of mnemonic function.

Our results significantly broaden our understanding of how mnemonic and perceptual

information interface during scene processing. Although the amount of known visuospatial

context largely did not impact PPA and OPA activation (consistent with the conventional view),

we found that activation of the cortical territory immediately anterior to each of these regions is

modulated by remembered visuospatial context. Thus, while the function of OPA and PPA may

be more directly linked to perception, mnemonic information likely influences representations in

these regions via their anterior mnemonic counterparts. Consistent with this view, we found that

OPA and PPA represent the identity of the recalled scene, which we hypothesize arises via

feedback from the place memory areas. Therefore, memory information likely plays a larger role

in the overall function of OPA and PPA than the conventional view of scene processing suggests.

A second, related hypothesis concerns the rigidity of visual representations in the scene

perception versus place memory areas. Specifically, it could be that the scene perception areas

focus only on the present image (i.e., the scope of information processed by these areas is limited

to the current field of view); In contrast, place memory areas may have more malleable fields of

view, such that the amount of information they represent may depend both on the extent of

memory for one's surroundings and the scope of one's internal attention based on current task-

demands (i.e., are you remembering the visuospatial context around the immediate corner, or

planning a longer journey through a city). This could relate to the slight decrease in identity

decoding within the place memory areas compared to the scene perception areas during recall if

the amount of visuospatial information within the place memory areas is not fixed across trials.

This may also relate to boundary transformations like extension and contraction (Intraub and

Richardson, 1989; Bainbridge and Baker, 2020; Hafri et al., 2022; Gandolfo et al., 2023). Thus, our

results show a new network of brain areas processing mnemonic information regarding

visuospatial context associated with a scene is interposed between structures implicated in scene

memory (e.g., the hippocampus or MPA) and the perceptually-oriented scene areas (i.e., OPA

and PPA), and future work should consider these alternative accounts of the memory area's

activity.

Our findings in MPA largely agree with the conventional understanding of this region's function.

Unlike the OPA and PPA, the degree of associated visuospatial context modulated MPA activation

in both memory tasks. Prior work has implicated MPA in representing visuospatial context. For

example, boundary extension, considered a proxy for representing visual information out of view,

has been linked to MPA (Park et al., 2007). Likewise, panoramic content associated with a scene

can be decoded from MPA (Robertson et al., 2016; Berens et al., 2021). In addition, MPA also

represents world-centered (allocentric) facing direction (Vass and Epstein, 2013; Marchette et

al., 2014; Julian et al., 2018), which requires knowledge of the environment's spatial layout

(Marchette et al., 2014). Activity in medial parietal cortex near MPA becomes more correlated

with the hippocampus after learning a new environment, suggesting that this region is important

for encoding new place memories (Steel et al., 2019). Further, damage to this area causes severe

topographic agnosia while leaving visual recognition abilities intact (Takahashi et al., 1997;

Aguirre and D'Esposito, 1999). Notably, unlike OPA and PPA, which lie immediately posterior to

a place memory area, MPA is largely contained within its corresponding place-memory area (i.e.,

MPMA (Steel et al., 2021)). Together, our findings support the conclusion that MPA could be

considered a visually-responsive sub-region of a largely mnemonic cortical area and may be

different in kind from PPA and OPA, which play an active role in visual analysis.

More broadly, our findings raise important questions about how perceptual and mnemonic

neural signals converge. Several studies have noted anterior shifts in activation when people

visualize versus perceive stimuli (Rugg and Thompson-Schill, 2013; Favila et al., 2018, 2020; Silson

et al., 2019; Bainbridge et al., 2020; Popham et al., 2021; Steel et al., 2021; Srokova et al., 2022).

What representational transformation underlies this shift? One account posits that this shift

reflects a transformation from sensory information (i.e., the visual properties of a house) in high-

level visual areas to more abstract, amodal, semantic representations (i.e., the mental concept

of a house) (Chao et al., 1999; Huth et al., 2012; Margulies et al., 2016; Huntenburg et al., 2018;

Popham et al., 2021). For example, one recent study compared a computational language model

fit to movie watching versus listening to stories and concluded that the anterior shift reflected a

transformation from visual features to representations grounded in language (Popham et al.,

2021). However, listening to stories engages many processes, including top-down imagery,

working memory, and narrative understanding, so pinpointing the nature of these

representations using naturalistic paradigms is challenging.

In contrast, our results argue against a purely semantics-based account of the anterior shift. By

focusing on one visual process (visual scene analysis) and isolating visuospatial context, we found

that the anteriorly-shifted activity reflects visuospatial context currently out of sight. As such, our

findings are not well accounted for by language-based accounts of the anterior shift. Instead, we

hypothesize that these anterior areas contain visuospatial information relevant to making

memory-based predictions of the visuospatial environment in service of perception (Steel et al.,

2023). Notably, because we focused only on visuospatial context, we cannot say whether the

anteriorly-shifted representations are exclusively visuospatial. One limitation of our approach

(i.e., modulating the amount of visuospatial content) is that increasing visuospatial context

necessarily entails the addition of other information as well as increased ecological naturalism.

For example, visual information on the left and right side of the street could include details like

houses or shops that provide semantic details about the environment, and this information

would be more prevalent in the panorama and street conditions (versus the image condition).

Relatedly, the presence of the occluder in the image condition diminishes its naturalistic and

immersive quality compared to the panorama and street conditions. Therefore, while our results

demonstrate that episodic and multisensory experiences are not necessary to elicit the anterior

shift for mnemonic information, we cannot rule out that other information could elicit this

anterior shift, such as semantic associations, multi-sensory context, and motor memories related

to head movements made during stimulus encoding, and the feeling of immersion. Could

anteriorly-shifted representations even reflect amodal, semantic-based information (Popham et

al., 2021)? Future studies will be needed to understand the nature of the representational

transformation anterior to visually-responsive cortex, and how these principles generalize

outside the case of scenes.

Conclusion

In conclusion, by using VR to precisely manipulate the visuospatial context associated with a

scene view, we found that perceptual representation of the visual scene in front of us and our

memory of the surrounding environment converge at the anterior edge of visually-responsive

cortex in the place memory areas. This functional architecture could allow efficient interaction

between the representation of the current visual scene with our memory of the wider

visuospatial context.

References

Aguirre GK, D'Esposito M (1999) Topographical disorientation: a synthesis and taxonomy. Brain
122:1613–1628   Available   at: https://academic.oup.com/brain/article-
lookup/doi/10.1093/brain/122.9.1613 [Accessed April 4, 2019].

Albright TD (2012) On the perception of probable things: neural substrates of associative
memory,   imagery,   and   perception.   Neuron   74:227–245   Available   at:
https://pubmed.ncbi.nlm.nih.gov/22542178/ [Accessed July 13, 2022].

Argall BD, Saad ZS, Beauchamp MS (2006) Simplified intersubject averaging on the cortical

surface using SUMA. Hum Brain Mapp 27:14–27 Available at:

https://pubmed.ncbi.nlm.nih.gov/16035046/ [Accessed June 28, 2022].

Bainbridge WA, Baker CI (2020) Boundaries Extend and Contract in Scene Memory Depending on

Image Properties. Curr Biol 30:537-543.e3 Available at:

https://pubmed.ncbi.nlm.nih.gov/31983637/ [Accessed May 25, 2023].

Bainbridge WA, Hall EH, Baker CI (2020) Distinct Representational Structure and Localization for

Visual Encoding and Recall during Visual Imagery. Cerebral Cortex 00:1–16 Available at:

http://fdslive.oup.com/www.oup.com/pdf/production_in_progress.pdf   [Accessed

December 7, 2020].

Baldassano C, Beck DM, Fei-Fei L (2013) Differential connectivity within the Parahippocampal

Place Area. Neuroimage 75:228–237 Available at:

https://www.sciencedirect.com/science/article/pii/S1053811913002280 [Accessed April

22, 2019].

Baldassano C, Esteva A, Fei-Fei L, Beck DM (2016) Two Distinct Scene-Processing Networks

Connecting Vision and Memory. eNeuro 3 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/27822493 [Accessed August 18, 2019].

Bar M, Aminoff E (2003) Cortical analysis of visual context. Neuron 38:347–358.

Barnett AJ, Reilly W, Dimsdale-Zucker H, Mizrak E, Reagh Z, Ranganath C (2020) Organization of

cortico-hippocampal networks in the human brain. bioRxiv:2020.06.09.142166 Available at:

http://biorxiv.org/content/early/2020/06/10/2020.06.09.142166.abstract   [Accessed

September 28, 2020].

Barry DN, Barnes GR, Clark IA, Maguire EA (2019) The Neural Dynamics of Novel Scene Imagery.

J Neurosci 39:4375–4386 Available at: http://www.ncbi.nlm.nih.gov/pubmed/30902867

[Accessed August 18, 2019].

Baumann O, Mattingley JB (2010) Medial parietal cortex encodes perceived heading direction in
humans. Journal of Neuroscience 30:12897–12901.

Baumann O, Mattingley JB (2013) Dissociable Representations of Environmental Size and
Complexity in the Human Hippocampus. Journal of Neuroscience 33:10526–10533 Available
at: https://www.jneurosci.org/content/33/25/10526 [Accessed May 4, 2022].

Baumann O, Mattingley JB (2016) Functional organization of the parahippocampal cortex:
Dissociable roles for context representations and the perception of visual scenes. Journal of
Neuroscience 36:2536–2542.

Berens SC, Joensen BH, Horner AJ (2021) Tracking the Emergence of Location-based Spatial
Representations in Human Scene-Selective Cortex. J Cogn Neurosci 33:445–462 Available at:
https://direct.mit.edu/jocn/article/33/3/445/95543/Tracking-the-Emergence-of-Location-
based-Spatial [Accessed August 4, 2022].

Bonner MF, Epstein RA (2017a) Coding of navigational affordances in the human visual system.
Proc   Natl   Acad   Sci   U   S   A   114:4793–4798   Available   at:
www.pnas.org/cgi/doi/10.1073/pnas.1618228114 [Accessed December 9, 2020].

Bonner MF, Epstein RA (2017b) Coding of navigational affordances in the human visual system.
Proc   Natl   Acad   Sci   U   S   A   114:4793–4798   Available   at:
http://www.ncbi.nlm.nih.gov/pubmed/28416669 [Accessed June 3, 2019].

Braga RM, Buckner RL (2017) Parallel Interdigitated Distributed Networks within the Individual
Estimated by Intrinsic Functional Connectivity. Neuron 95:457-471.e5.

Braga RM, van Dijk KRA, Polimeni JR, Eldaief MC, Buckner RL (2019) Parallel distributed networks
resolved at high resolution reveal close juxtaposition of distinct regions. J Neurophysiol
121:1513–1534 Available at: www.jn.org [Accessed July 1, 2020].

Brunec IK, Bellana B, Ozubko JD, Man V, Robin J, Liu ZX, Grady C, Rosenbaum RS, Winocur G,

Barense MD, Moscovitch M (2018) Multiple Scales of Representation along the Hippocampal

Anteroposterior Axis in Humans. Current Biology 28:2129-2135.e6.

Chao LL, Haxby J v., Martin A (1999) Attribute-based neural substrates in temporal cortex for

perceiving and knowing about objects. Nat Neurosci 2:913–919 Available at:

https://pubmed.ncbi.nlm.nih.gov/10491613/ [Accessed April 3, 2021].

Cox RW (1996) AFNI: Software for analysis and visualization of functional magnetic resonance

neuroimages. Computers and Biomedical Research 29:162–173.

Dale AM, Fischl B, Sereno MI (1999) Cortical surface-based analysis: I. Segmentation and surface

reconstruction. Neuroimage 9:179–194.

D'Esposito M, Detre JA, Aguirre GK, Stallcup M, Alsop DC, Tippet LJ, Farah MJ (1997) A functional

MRI study of mental image generation. Neuropsychologia 35:725–730.

Dilks DD, Julian JB, Paunov AM, Kanwisher N (2013) The occipital place area is causally and

selectively involved in scene perception. Journal of Neuroscience 33:1331–1336.

Dilks DD, Kamps FS, Persichetti AS (2022) Three cortical scene systems and their development.

Trends   Cogn   Sci   26:117–127   Available   at:

http://www.cell.com/article/S1364661321002874/fulltext [Accessed January 17, 2022].

DiNicola LM, Braga RM, Buckner RL (2020) Parallel distributed networks dissociate episodic and

social functions within the individual. J Neurophysiol 123:1144–1179 Available at:

https://journals.physiology.org/doi/10.1152/jn.00529.2019 [Accessed March 19, 2020].

Draschkow D, Nobre AC, van Ede F (2022) Multiple spatial frames for immersive working memory.

Nature   Human   Behaviour   2022   6:4   6:536–544   Available   at:

https://www.nature.com/articles/s41562-021-01245-y [Accessed June 6, 2022].

DuPre E et al. (2021) TE-dependent analysis of multi-echo fMRI with *tedana*. J Open Source
Softw 6:3669 Available at: https://joss.theoj.org/papers/10.21105/joss.03669 [Accessed
June 26, 2022].

DuPre E, Salo T, Markello R, Kundu P, Whitaker K, Handwerker D (2019) ME-ICA/tedana: 0.0.6.
Available at: https://zenodo.org/record/2558498 [Accessed February 7, 2020].

Epstein R, Kanwisher N (1998) A cortical representation the local visual environment. Nature
392:598–601.

Epstein RA, Baker CI (2019) Scene Perception in the Human Brain. Annu Rev Vis Sci 5:annurev-
vision-091718-014809 Available at: https://www.annualreviews.org/doi/10.1146/annurev-
vision-091718-014809 [Accessed July 28, 2019].

Epstein RA, Higgins JS, Jablonski K, Feiler AM (2007a) Visual Scene Processing in Familiar and
Unfamiliar   Environments.   J   Neurophysiol   97:3670–3683   Available   at:
https://www.physiology.org/doi/10.1152/jn.00003.2007 [Accessed April 22, 2020].

Epstein RA, Parker WE, Feiler AM (2007b) Where am i now? Distinct roles for parahippocampal
and retrosplenial cortices in place recognition. Journal of Neuroscience 27:6141–6149
Available at: /record/2007-19450-018 [Accessed August 5, 2022].

Evans JW, Kundu P, Horovitz SG, Bandettini PA (2015) Separating slow BOLD from non-BOLD
baseline drifts using multi-echo fMRI. Neuroimage 105:189–197.

Favila SE, Lee H, Kuhl BA (2020) Transforming the Concept of Memory Reactivation. Trends
Neurosci 43:939–950.

Favila SE, Samide R, Sweigart SC, Kuhl BA (2018) Parietal Representations of Stimulus Features
Are Amplified during Memory Retrieval and Flexibly Aligned with Top-Down Goals. Journal
of   Neuroscience   38:7809–7821   Available   at:
https://www.jneurosci.org/content/38/36/7809 [Accessed May 22, 2022].

Fischl B, Salat DH, Busa E, Albert M, Dieterich M, Haselgrove C, van der Kouwe A, Killiany R,
Kennedy D, Klaveness S, Montillo A, Makris N, Rosen B, Dale AM (2002) Whole brain
segmentation: Automated labeling of neuroanatomical structures in the human brain.
Neuron 33:341–355.

Gandolfo M, Nägele H, Peelen M V. (2023) Predictive Processing of Scene Layout Depends on
Naturalistic   Depth   of   Field.   Psychol   Sci   Available   at:
https://journals.sagepub.com/doi/full/10.1177/09567976221140341 [Accessed May 25,
2023].

Glasser MF, Coalson TS, Robinson EC, Hacker CD, Harwell J, Yacoub E, Ugurbil K, Andersson J,
Beckmann CF, Jenkinson M, Smith SM, van Essen DC (2016) A multi-modal parcellation of
human cerebral cortex. Nature 536:171–178 Available at: http://balsa.wustl.edu/WN56.
[Accessed November 5, 2020].

Gordon EM et al. (2017) Precision Functional Mapping of Individual Human Brains. Neuron
95:791-807.e7.

Hafri A, Wadhwa S, Bonner MF (2022) Perceived Distance Alters Memory for Scene Boundaries.
Psychol   Sci   33:2040–2058   Available   at:
https://journals.sagepub.com/doi/full/10.1177/09567976221093575 [Accessed May 25,
2023].

Haskins AJ, Mentch J, Botch TL, Robertson CE (2020) Active vision in immersive, 360° real-world
environments.   Scientific   Reports   2020   10:1   10:1–11   Available   at:
https://www.nature.com/articles/s41598-020-71125-4 [Accessed January 19, 2022].

Hassabis D, Maguire EA (2009) The construction system of the brain. Philosophical Transactions
of   the   Royal   Society   B: Biological   Sciences   364:1263–1271   Available   at:
https://royalsocietypublishing.org/doi/10.1098/rstb.2008.0296 [Accessed November 4,
2020].

Hasson U, Levy I, Behrmann M, Hendler T, Malach R (2002) Eccentricity bias as an organizing
1038   principle for human high-order object areas. Neuron 34:479–490 Available at:
1039   http://www.cell.com/article/S0896627302006621/fulltext [Accessed November 4, 2020].

1040   Huntenburg JM, Bazin PL, Margulies DS (2018) Large-Scale Gradients in Human Cortical
1041   Organization.   Trends   Cogn   Sci   22:21–31   Available   at:
1042   http://www.cell.com/article/S1364661317302401/fulltext [Accessed June 21, 2022].

1043   Huth AG, Nishimoto S, Vu AT, Gallant JL (2012) A Continuous Semantic Space Describes the
1044   Representation of Thousands of Object and Action Categories across the Human Brain.
1045   Neuron 76:1210–1224.

1046   Intraub H, Richardson M (1989) Wide-Angle Memories of Close-Up Scenes. J Exp Psychol Learn
1047   Mem Cogn 15:179–187.

1048   Jo HJ, Gotts SJ, Reynolds RC, Bandettini PA, Martin A, Cox RW, Saad ZS (2013) Effective
1049   Preprocessing Procedures Virtually Eliminate Distance-Dependent Motion Artifacts in
1050   Resting State FMRI. J Appl Math 2013 Available at: /pmc/articles/PMC3886863/ [Accessed
1051   June 21, 2022].

1052   Julian JB, Fedorenko E, Webster J, Kanwisher N (2012) An algorithmic method for functionally
1053   defining   regions   of   interest   in   the   ventral   visual   pathway.   Available   at:
1054   http://web.mit.edu/bcs/nklab/GSS.shtml [Accessed January 20, 2022].

1055   Julian JB, Keinath AT, Marchette SA, Epstein RA (2018) The Neurocognitive Basis of Spatial
1056   Reorientation. Current Biology 28:R1059–R1073.

1057   Julian JB, Ryan J, Hamilton RH, Epstein RA (2016) The Occipital Place Area Is Causally Involved in
1058   Representing Environmental Boundaries during Navigation. Current Biology 26:1104–1109
1059   Available   at: https://www.cell.com/current-biology/fulltext/S0960-9822(16)30177-4
1060   [Accessed May 15, 2019].

Kamps FS, Julian JB, Kubilius J, Kanwisher N, Dilks DD (2016) The occipital place area represents
the local elements of scenes. Neuroimage 132:417–424.

Kanwisher N, McDermott J, Chun MM (1997) The fusiform face area: A module in human
extrastriate cortex specialized for face perception. Journal of Neuroscience 17:4302–4311
Available at: https://www.jneurosci.org/content/17/11/4302 [Accessed May 18, 2021].

Kundu P, Inati SJ, Evans JW, Luh WM, Bandettini PA (2012) Differentiating BOLD and non-BOLD
signals in fMRI time series using multi-echo EPI. Neuroimage 60:1759–1770.

Kundu P, Voon V, Balchandani P, Lombardo M v., Poser BA, Bandettini PA (2017) Multi-echo fMRI:
A review of applications in fMRI denoising and analysis of BOLD signals. Neuroimage 154:59–
80.

LaChance PA, Taube JS (2022) Spatial Context and the Functional Role of the Postrhinal Cortex.
Neurobiol   Learn   Mem:107596   Available   at:
https://linkinghub.elsevier.com/retrieve/pii/S107474272200020X [Accessed February 10,
2022].

LaChance PA, Todd TP, Taube JS (2019) A sense of space in postrhinal cortex. Science (1979) 365
Available at: http://dx.doi. [Accessed January 19, 2022].

Lescroart MD, Gallant JL (2019) Human Scene-Selective Areas Represent 3D Configurations of
Surfaces. Neuron 101:178-192.e7.

Li X, Morgan PS, Ashburner J, Smith J, Rorden C (2016) The first step for neuroimaging data
analysis: DICOM to NIfTI conversion. J Neurosci Methods 264:47–56.

Maguire EA, Burgess N, Donnett JG, Frackowiak RSJ, Frith CD, O'Keefe J (1998) Knowing where
and getting there: A human navigation network. Science (1979) 280:921–924 Available at:
https://pubmed.ncbi.nlm.nih.gov/9572740/ [Accessed November 4, 2020].

Malach R, Levy I, Hasson U (2002) The topography of high-order human object areas. Trends Cogn
Sci 6:176–184.

Malcolm GL, Groen IIA, Baker CI (2016) Making Sense of Real-World Scenes. Trends Cogn Sci
20:843–856.

Marchette SA, Vass LK, Ryan J, Epstein RA (2014) Anchoring the neural compass: Coding of local
spatial reference frames in human medial parietal lobe. Nat Neurosci 17:1598–1606
Available   at:
https://static1.squarespace.com/static/55aaa148e4b0ba360335ef21/t/55b07091e4b0dd2
2812a8c37/1437626513802/Marchette-2014-Nature-Neuro.pdf [Accessed May 13, 2019].

Margulies DS, Ghosh SS, Goulas A, Falkiewicz M, Huntenburg JM, Langs G, Bezgin G, Eickhoff SB,
Castellanos FX, Petrides M, Jefferies E, Smallwood J (2016) Situating the default-mode
network along a principal gradient of macroscale cortical organization. Proc Natl Acad Sci U
S A 113:12574–12579.

Nau M, Navarro Schröder T, Frey M, Doeller CF (2020) Behavior-dependent directional tuning in
the   human   visual-navigation   network.   Nat   Commun   11:3247   Available   at:
http://www.nature.com/articles/s41467-020-17000-2 [Accessed December 6, 2020].

O'Craven KM, Kanwisher N (2000) Mental imagery of faces and places activates corresponding
stimulus-specific brain regions. J Cogn Neurosci 12:1013–1023.

Park S, Intraub H, Yi D-J, Widders D, Chun MM (2007) Beyond the Edges of a View: Boundary
Extension in Human Scene-Selective Visual Cortex. Neuron 54:335–342 Available at:
https://www.sciencedirect.com/science/article/pii/S0896627307002565   [Accessed   April
28, 2019].

Peer M, Ron Y, Monsa R, Arzy S (2019) Processing of different spatial scales in the human brain.
Elife 8 Available at: https://elifesciences.org/articles/47492 [Accessed September 9, 2019].

Peer M, Salomon R, Goldberg I, Blanke O, Arzy S (2015) Brain system for mental orientation in
space, time, and person. Proc Natl Acad Sci U S A 112:11072–11077 Available at:
http://www.ncbi.nlm.nih.gov/pubmed/26283353 [Accessed May 6, 2019].

Peirce JW (2007) PsychoPy—Psychophysics software in Python. J Neurosci Methods 162:8–13.

Persichetti AS, Dilks DD (2019) Distinct representations of spatial and categorical relationships
across human scene-selective cortex. Proceedings of the National Academy of
Sciences:201903057   Available   at:
http://www.pnas.org/lookup/doi/10.1073/pnas.1903057116 [Accessed October 1, 2019].

Popham SF, Huth AG, Bilenko NY, Deniz F, Gao JS, Nunez-Elizalde AO, Gallant JL (2021) Visual and
linguistic semantic representations are aligned at the border of human visual cortex. Nature
Neuroscience   2021   24:11   24:1628–1636   Available   at:
https://www.nature.com/articles/s41593-021-00921-6 [Accessed June 21, 2022].

Poser BA, Versluis MJ, Hoogduin JM, Norris DG (2006) BOLD contrast sensitivity enhancement
and artifact reduction with multiecho EPI: Parallel-acquired inhomogeneity-desensitized
fMRI.   Magn   Reson   Med   55:1227–1235   Available   at:
http://doi.wiley.com/10.1002/mrm.20900 [Accessed April 1, 2020].

Posse S (2012) Multi-echo acquisition. Neuroimage 62:665–671.

Rademaker RL, Chunharas C, Serences JT (2019) Coexisting representations of sensory and
mnemonic information in human visual cortex. Nat Neurosci 22:1336–1344 Available at:
http://www.nature.com/articles/s41593-019-0428-x [Accessed July 29, 2019].

Ranganath C, Ritchey M (2012) Two cortical systems for memory-guided behaviour. Nat Rev
Neurosci 13:713–726.

Ritchey M, Cooper RA (2020) Deconstructing the Posterior Medial Episodic Network. Trends Cogn
Sci xx Available at: https://doi.org/10.1016/j.tics.2020.03.006 [Accessed April 25, 2020].

Ritchey M, Libby LA, Ranganath C (2015) Cortico-hippocampal systems involved in memory and

cognition: the   PMAT   framework   3.   Available   at:

http://dx.doi.org/10.1016/bs.pbr.2015.04.001 [Accessed September 2, 2019].

Robertson CE, Hermann KL, Mynick A, Kravitz DJ, Kanwisher N (2016) Neural Representations

Integrate the Current Field of View with the Remembered 360° Panorama in Scene-Selective

Cortex.   Current   Biology   26:2463–2468   Available   at:

https://www.sciencedirect.com/science/article/pii/S0960982216307539 [Accessed April 8,

2019].

Rugg MD, Thompson-Schill SL (2013) Moving Forward With fMRI Data. Perspectives on

Psychological Science 8:84–87.

Rust   NC,   Palmer   SE   (2021)   Remembering   the   Past   to   See   the   Future.

https://doi.org/101146/annurev-vision-093019-112249   7   Available   at:

https://www.annualreviews.org/doi/abs/10.1146/annurev-vision-093019-112249

[Accessed September 7, 2021].

Ryan JD, Shen K (2020) The eyes are a window into memory. Curr Opin Behav Sci 32:1–6.

Saad ZS, Reynolds RC (2012) SUMA. Neuroimage 62:768–773.

Shine JP, Valdés-Herrera JP, Hegarty M, Wolbers T (2016) The Human Retrosplenial Cortex and

Thalamus Code Head Direction in a Global Reference Frame.

Silson EH, Chan AWY, Reynolds RC, Kravitz DJ, Baker CI (2015) A retinotopic basis for the division

of high-level scene processing between lateral and ventral human occipitotemporal cortex.

Journal of Neuroscience 35:11921–11935.

Silson EH, Steel A, Kidder A, Gilmore AW, Baker CI (2019) Distinct subdivisions of human medial

parietal cortex support recollection of people and places. Elife 8.

Silson EH, Steel AD, Baker CI (2016) Scene-Selectivity and Retinotopy in Medial Parietal Cortex.

Front   Hum   Neurosci   10:412   Available   at:

http://journal.frontiersin.org/Article/10.3389/fnhum.2016.00412/abstract [Accessed April

8, 2019].

Spiers HJ, Maguire EA (2006) Thoughts, behaviour, and brain dynamics during navigation in the

real world. Neuroimage 31:1826–1840.

Spreng RN, Mar RA, Kim ASN (2009) The common neural basis of autobiographical memory,

prospection, navigation, theory of mind, and the default mode: A quantitative meta-

analysis. J Cogn Neurosci 21:489–510.

Srokova S, Hill PF, Rugg MD (2022) The Retrieval-related Anterior shift is Moderated by Age and

Correlates with Memory Performance. Journal of Neuroscience:JN-RM-1763-21 Available

at: https://www.jneurosci.org/content/early/2022/01/06/JNEUROSCI.1763-21.2021

[Accessed January 17, 2022].

Steel A, Billings MM, Silson EH, Robertson CE (2021) A network linking scene perception and

spatial memory systems in posterior cerebral cortex. Nature Communications 2021 12:1

12:1–13 Available at: https://doi.org/10.1038/s41467-021-22848-z [Accessed May 18,

2021].

Steel A, Garcia BD, Silson EH, Robertson CE (2022) Evaluating the efficacy of multi-echo ICA

denoising on model-based fMRI. Neuroimage 264:119723.

Steel A, Silson EH, Garcia BD, Robertson CE (2023) A retinotopic code structures the interaction

between perception and memory systems. bioRxiv:2023.05.15.540807 Available at:

https://www.biorxiv.org/content/10.1101/2023.05.15.540807v1 [Accessed June 2, 2023].

Steel A, Thomas C, Trefler A, Chen G, Baker CI (2019) Finding the baby in the bath water –

evidence for task-specific changes in resting state functional connectivity evoked by training.

Neuroimage 188:524–538.

Takahashi N, Kawamura M, Shiota J, Kasahata N, Hirayama K (1997) Pure topographic

disorientation due to right retrosplenial lesion. Neurology 49:464–469 Available at:

http://www.ncbi.nlm.nih.gov/pubmed/9270578 [Accessed April 4, 2019].

Taube JS (2007) The Head Direction Signal: Origins and Sensory-Motor Integration. Annu Rev

Neurosci 30:181–207.

Vass LK, Epstein RA (2013) Abstract Representations of Location and Facing Direction in the

Human Brain. Journal of Neuroscience 33:6133–6142 Available at:

https://www.jneurosci.org/content/33/14/6133 [Accessed April 13, 2022].

Weiner KS, Barnett MA, Witthoft N, Golarai G, Stigliani A, Kay KN, Gomez J, Natu VS, Amunts K,

Zilles K, Grill-Spector K (2018) Defining the most probable location of the parahippocampal

place area using cortex-based alignment and cross-validation. Neuroimage 170:373–384

Available at: https://pubmed.ncbi.nlm.nih.gov/28435097/ [Accessed November 4, 2020].

Zeidman P, Maguire EA (2016) Anterior hippocampus: the anatomy of perception, imagination

and episodic memory. Nature Reviews Neuroscience 2016 17:3 17:173–182 Available at:

https://www.nature.com/articles/nrn.2015.24 [Accessed January 31, 2022].

Zeidman P, Mullally SL, Maguire EA (2015) Constructing, Perceiving, and Maintaining Scenes:

Hippocampal Activity and Connectivity. Cerebral Cortex 25:3836–3855 Available at:

https://academic.oup.com/cercor/article/25/10/3836/392503 [Accessed January 31,

2022].

1199