HoCoRT: Host contamination removal tool

Ignas Rumbavicius[1], Trine B. Rounge[2,3,*], Torbjørn Rognes[1,4,*]

[1] Centre for Bioinformatics, Department of Informatics, University of Oslo, PO Box 1080 Blindern, 0316 Oslo, Norway

[2] Centre for Bioinformatics, Department of Pharmacy, University of Oslo, PO Box 1068 Blindern, 0316 Oslo, Norway

[3] Cancer Registry of Norway, PO Box 5313 Majorstuen, 0304 Oslo, Norway

[4] Department of Microbiology, Oslo University Hospital, PO Box 4950 Nydalen, 0424 Oslo, Norway

* Correspondence: t.b.rounge@farmasi.uio.no and torognes@ifi.uio.no

Abstract

Background

Shotgun metagenome sequencing data obtained from a host environment will usually be contaminated with sequences from the host organism. Host sequences should be removed before further analysis to avoid biases, to reduce downstream computational load, or for privacy reasons in case of a human host. The tools that we identified as designed specifically to perform host contamination sequence removal were either outdated, not maintained or complicated to use. We have therefore created HoCoRT, a fast and user friendly tool that implements several methods for optimised host sequence removal, and evaluated the speed and accuracy of these methods.

Results

HoCoRT is an open-source command-line tool for host contamination removal. It is designed to be simple to install and use, including a one-step option for genome indexing. HoCoRT uses a range of well-known mapping, classification and alignment methods for the classification of reads. The underlying classification method to be used and its parameters are selectable by the user, enabling adaptation to different circumstances. Based on our investigation of the performance of a range of methods and parameters on artificial human gut and oral microbiomes, recommendations are provided for typical data sets with short and long reads.

Conclusions

To decontaminate a human microbiome with HoCoRT, the best combination of speed and accuracy was found with BioBloom, Bowtie2 in end-to-end mode, or HISAT2 for short reads,

while BioBloom performed best for long reads. For the oral microbiome, Bowtie2 was slightly

more accurate than the other two, at the expense of speed. HoCoRT using Bowtie2 in end-

to-end mode was found to be much faster and slightly more accurate than the dedicated

DeconSeq tool. HoCoRT is distributed as a Bioconda package. Source code and

documentation are available at https://github.com/ignasrum/hocort for Linux and macOS

under the MIT licence.

Keywords

microbiome, shotgun metagenome, contamination, classification, software

Background

Sequencing the genomes of microbial communities in an environment of a host organism

have opened new avenues for research on host - microbe interactions. A number of analysis

steps must be carried out after metagenomic sequencing to obtain a good picture of the

composition of the microbiome. The huge amounts of data often involved require efficient

processing, and it is therefore important to avoid unnecessary computations. Some

sequences of host origin are inevitably included in the obtained data, and when the host is

human, privacy becomes an issue. Sequences of non-microbial origin could also bias the

results of downstream analyses. These host sequences should hence be removed at an

early stage [1].

Decontamination is often handled in an ad-hoc manner by running an alignment tool to

search reads against a host genome database. This makes this essential analysis step more

complicated than necessary and could result in inferior performance. There is a lack of best

practices for this procedure, and comparison across studies is more difficult without

standardisation.

We could identify only two dedicated tools specifically designed for removal of contaminating

sequences, namely DeconSeq and GenCoF. DeconSeq [2] is a command-line tool for

identification and removal of sequence contamination from genomic and metagenomic

datasets. DeconSeq integrates its underlying classifier, a modified version of BWA-SW [3],

directly into its source code, making modifications difficult. DeconSeq only supports single-

end Illumina reads, and the code has not been updated since 2013. GenCoF [4] is a

graphical user interface to rapidly remove human genome contaminants from metagenomic

datasets. It is limited to short reads. The GUI makes it unsuited for scripting. Extending

GenCoF is also difficult as it also has its underlying classifier Bowtie2 [5] directly integrated

into its source code. Both tools clearly have severe limitations making them less suitable for

most large-scale modern datasets. We therefore decided to develop the new tool HoCoRT to

fill this need. We also examined the performance of a range of underlying classification

methods in order to be able to make recommendations about which method to use under

different circumstances and to provide default settings.

Implementation

HoCoRT is an open-source command-line based tool written in Python 3. It is designed to be

easy to use and can be easily installed as a package with Bioconda [6], or using a Docker

container. HoCoRT has a modular pipeline design and uses well established classification,

mapping and alignment tools to perform the classification of the sequences into host and

non-host (microbial) sequences. Currently available pipeline modules include the BBMap

tool in the BBTools suite [7, 8], as well as BioBloom [9], Bowtie2 [5], BWA-MEM2 [10],

HISAT2 [11], Kraken2 [12], and Minimap2 [13]. Furthermore, modules may pipe data

through different tools after each other. The configuration of the options to the pipelines can

be specified by the user, but recommended defaults are provided. New modules can be

written to extend HoCoRT to use other tools. HoCoRT also provides an extensive Python

library with an API that could be used as a backend by other tools. HoCoRT reads and

writes optionally compressed FASTQ files. The building of database index files for the

underlying classification tools is also handled by HoCoRT. The tool is documented with built-

in help functions and error messages. HoCoRT depends on Samtools [14]. Please see table

1 for a list of all software mentioned in this work, including version numbers and references.

Results and discussion

The classification speed and accuracy of HoCoRT with several different underlying methods

and settings was investigated with synthetic datasets. The GitHub repository at

https://github.com/ignasrum/hocort-eval provides the scripts used for generating the datasets

and to perform the performance evaluation. The datasets were created with HiSeq, MiSeq

and Nanopore reads containing either a mix of 1% human host sequences and 99%

microbial sequences, similar to a human gut microbiome, or a mix of 50% human host and

50% microbial sequences, similar to a human oral microbiome.

The human reads were generated from the Genome Reference Consortium Human Build 38

patch release 13 (GRCh38.p13), whereas the microbial reads are generated from a mix of

bacterial, fungal and viral sequences pseudo-randomly extracted from NCBI GenBank [15].

HoCoRT was run using several different pipelines (classification modules) and parameters

on HiSeq, MiSeq and Nanopore data. For each of these combinations, 7 different datasets

were analysed, each consisting of 5 million reads randomly generated using InSilicoSeq [16]

(HiSeq 125bp and MiSeq 300bp, paired-end) and NanoSim [17] (Nanopore, average

2159bp, range 54-98320bp, single-end).

For Illumina data the following 17 pipelines were examined: Seal, BBduk, BBsplit, BioBloom,

Bowtie2 in end-to-end and local mode, both with and without the "un_conc" option, HISAT2,

Kraken2, BBMap in default and fast mode, BWA-MEM2, Kraken2 followed by Bowtie2 in

end-to-end mode, Kraken2 followed by HISAT2, Minimap2, and finally Kraken2 followed by

Minimap2. For Nanopore data the following 4 pipelines were examined: BioBloom,

Minimap2, Kraken2 followed by Minimap2, and Kraken2. When the "un_conc" option is

given, Bowtie2 requires both reads in a pair to map concordantly to the genome. We also

considered including CONSULT [18] in the comparison, but there were no pre-compiled

binaries or packages available, and it requires 128GB of RAM, making it impractical for

many users.

The ability to detect the human host sequences was tested and the sensitivity, precision, and

accuracy was calculated, considering the correctly identified human host sequences as true

positives. We considered accuracy as most important, followed by speed. Performance

analysis was carried out using a Snakemake pipeline [19] on a desktop PC with an AMD

Ryzen 7 1700X 8 core/16 thread 3.4 GHz CPU, 64GB RAM and 4TB HDD running Linux. No

quality filtering or other pre-processing was performed.

The results for the gut microbiome are shown in figure 1, while additional results are

included in Supplementary figure S1 and table S1. Results for the oral microbiome are

shown in Supplementary figure S2 and table S2. Overall, BioBloom, Bowtie2 in end-to-end

mode, and HISAT2 performed best for Illumina reads and are recommended as they are

highly accurate in all cases and also generally very fast. Bowtie2 had the highest accuracy

for the oral microbiome, at the expense of speed. For Nanopore reads, BioBloom performed

best and is recommended due to its combination of high accuracy and speed.

The performance of HoCoRT was also compared to DeconSeq using a human gut dataset,

but with single-ended Illumina reads. The HoCoRT Bowtie2 (end-to-end) pipeline was much

faster than DeconSeq at aligning both HiSeq (34X) and MiSeq (49X) reads, and also slightly

more accurate, as shown in Supplementary table S3.

Additional results and a more detailed description of HoCoRT can be found in the first

author's master thesis [20].

Conclusions

163   A dedicated, flexible, extendable, and modular tool for host sequence contamination removal

164   is now freely available for all users. A comparison of the available classification methods has

165   been performed and recommendations are provided. The HoCoRT tool should simplify the

166   decontamination step in microbiome data analysis and provide solid performance.

Availability and requirements

Project name: HoCoRT

Project home page: https://github.com/ignasrum/hocort

Operating system(s): Linux and macOS

Programming language: Python

Other requirements: Samtools [14] and other packages. Please see GitHub repository for

details.

License: MIT license

Any restrictions to use by non-academics: None

References

1. Bharti, R., & Grimm, D. G. (2021) Current challenges and best-practice protocols for microbiome analysis. Briefings in Bioinformatics, 22(1), 178–193. https://doi.org/10.1093/bib/bbz155

2. Schmieder, R., & Edwards, R. (2011) Fast identification and removal of sequence contamination from genomic and metagenomic datasets. PLOS ONE, 6(3), e17288. https://doi.org/10.1371/journal.pone.0017288

3. Li, H., & Durbin, R. (2009) Fast and accurate short read alignment with Burrows-Wheeler transform. Bioinformatics, 25(14), 1754–1760. https://doi.org/10.1093/bioinformatics/btp324

4. Czajkowski, M. D., Vance, D. P., Frese, S. A., & Casaburi, G. (2019) GenCoF: A graphical user interface to rapidly remove human genome contaminants from metagenomic datasets. Bioinformatics, 35(13), 2318–2319. https://doi.org/10.1093/bioinformatics/bty963

5. Langmead, B., & Salzberg, S. L. (2012) Fast gapped-read alignment with Bowtie 2. Nature Methods, 9(4), 357–359. https://doi.org/10.1038/nmeth.1923

6. Grüning, B., Dale, R., Sjödin, A., Chapman, B. A., Rowe, J., Tomkins-Tinch, C. H., Valieris, R., Köster, J. & The Bioconda Team (2018) Bioconda: Sustainable and comprehensive software distribution for the life sciences. Nature Methods, 15(7), 475–476. https://doi.org/10.1038/s41592-018-0046-7

7. Bushnell, B. (2022) BBMap short read aligner, and other bioinformatic tools. https://sourceforge.net/projects/bbmap/. Accessed 1 May 2022.

8. Joint Genome Institute (2023) BBTools. https://jgi.doe.gov/data-and-tools/software-

tools/bbtools/. Accessed 30 March 2023.

9. Chu, J., Sadeghi, S., Raymond, A., Jackman, S.D., Nip, K.M., Mar R., Mohamadi, H.,

Butterfield, Y.S., Robertson, A.G., Birol, I. (2014) BioBloom tools: fast, accurate and

memory-efficient host species sequence screening using bloom filters. Bioinformatics,

30(23), 3402-4. doi: 10.1093/bioinformatics/btu558

10. Vasimuddin, M., Misra, S., Li, H., & Aluru, S. (2019) Efficient architecture-aware

acceleration of BWA-MEM for multicore systems. 2019 IEEE International Parallel and

Distributed Processing Symposium (IPDPS), 314–324.

https://doi.org/10.1109/IPDPS.2019.00041

11. Kim, D., Paggi, J. M., Park, C., Bennett, C., & Salzberg, S. L. (2019) Graph-based

genome alignment and genotyping with HISAT2 and HISAT-genotype. Nature

Biotechnology, 37(8), 907–915. https://doi.org/10.1038/s41587-019-0201-4

12. Wood, D. E., Lu, J., & Langmead, B. (2019) Improved metagenomic analysis with

Kraken 2. Genome Biology, 20(1), 257. https://doi.org/10.1186/s13059-019-1891-0

13. Li, H. (2018) Minimap2: Pairwise alignment for nucleotide sequences. Bioinformatics,

34(18), 3094–3100. https://doi.org/10.1093/bioinformatics/bty191

14. Li, H., Handsaker, B., Wysoker, A., Fennell, T., Ruan, J., Homer, N., Marth, G.,

Abecasis, G., Durbin, R., & 1000 Genome Project Data Processing Subgroup (2009) The

sequence alignment/map format and SAMtools. Bioinformatics, 25(16), 2078–2079.

https://doi.org/10.1093/bioinformatics/btp352

15. Sayers, E. W., Cavanaugh, M., Clark, K., Pruitt, K. D., Schoch, C. L., Sherry, S.T.,

Karsch-Mizrachi, I. (2022) GenBank. Nucleic Acids Res, 50(D1), D161-D164.

https://doi.org/10.1093/nar/gkab1135

16. Gourlé, H., Karlsson-Lindsjö, O., Hayer, J., & Bongcam-Rudloff, E. (2019) Simulating

illumina metagenomic data with InSilicoSeq. Bioinformatics, 35(3), 521–522.

https://doi.org/10.1093/bioinformatics/bty630

17. Yang, C., Chu, J., Warren, R. L., & Birol, I. (2017) NanoSim: Nanopore sequence read

simulator based on statistical characterization. GigaScience, 6(4).

https://doi.org/10.1093/gigascience/gix010

18. Rachtman, E., Bafna, V., Mirarab, S. (2021) CONSULT: accurate contamination removal

using locality-sensitive hashing. NAR Genomics and Bioinformatics, 3(3), lqab071.

https://doi.org/10.1093/nargab/lqab071

19. Koster, J., & Rahmann, S. (2012) Snakemake–a scalable bioinformatics

workflow engine. Bioinformatics, 28(19), 2520–2522.

https://doi.org/10.1093/bioinformatics/bts480

20. Rumbavicius, I. (2022) Tool to remove specific organisms from microbiome sequencing

data - Host Contamination Removal Tool (HoCoRT). Master thesis, Department of

Informatics, University of Oslo, Norway. http://urn.nb.no/URN:NBN:no-98212

Acknowledgements

258 Thanks to the anonymous reviewers of a previous version of the manuscript for suggesting

259 additional tools to consider.

Funding

This project received funding for data collection from the Norwegian Cancer Society (project numbers 190179 and 198048).

Authors' contributions

IR developed and evaluated the tool, performed experiments, made tables and figures and wrote the initial description of the tool. TR initiated the project and drafted the manuscript. TBR provided datasets. TBR and TR provided advice in all stages of the project. All authors analysed and interpreted the results. All authors edited, read and approved the final manuscript.

Ethics declarations

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Competing interests

The authors declare that they have no competing interests.

Additional files

Filename: additional-file-1.pdf

Format: PDF

Title: Supplementary material

Description: Figures and tables with additional results

Tables

Table 1. Software. The software packages used or mentioned are listed with version

numbers and references.

Software	Version	References
BBDuk	39.01	[7, 8]
BBMap	39.01	[7, 8]
BBSplit	39.01	[7, 8]
BioBloom Tools	2.3.5	[9]
BioConda	23.1.0	[6]
Bowtie2	2.4.5	[5]
BWA-SW		[3]
BWA-MEM2	2.2.1	[10]
CONSULT		[18]
DeconSeq	0.4.3	[2]
GenCoF		[4]
HISAT2	2.2.1	[11]
HoCoRT	1.2.2	[20]
InSiliconSeq	1.5.4	[16]
Kraken2	2.1.2	[12]
MiniMap2	2.24	[13]
NanoSim	3.0.0	[17]
Samtools	1.16.1	[14]
Seal	39.01	[7, 8]
SnakeMake	7.19.1	[19]

288 Figures

Fig. 1. HoCoRT performance on simulated gut microbiome datasets. Boxplots of

HoCoRT runtime in seconds (top) and classification accuracy (bottom) using several

different classification modules and parameters on Illumina (HiSeq) (yellow, left), and

Nanopore data (cyan, right). Supplementary figure S1 is similar, but also includes results for

MiSeq data. Supplementary table S1 contains additional results, including those for BBMap

in default mode, BBsplit, Bowtie2 with the "un_conc" option, and BWA-MEM2, which were

excluded from the figures due to outliers.