Heard or understood?

Neural tracking of language features in a comprehensible story, an incomprehensible story and a word list

Marlies Gillis[*], Jonas Vanthornhout[*], Tom Francart[*]

[*]: Experimental Oto-Rhino-Laryngology, Department of Neurosciences, KU Leuven, Belgium

Corresponding author:

Marlies Gillis (marlies.gillis@kuleuven.be)

Word count: abstract (), introduction (), methods (), results (), discussion (), conclusion ()

Keywords: neural tracking, language tracking, speech comprehension

Funding: The research received funding from the European Research Council under the European Unions Horizon 2020 research and innovation programme (grant agreement No. 637424, ERC starting grant to Tom Francart). Marlies Gillis (PhD) and Jonas Vanthornhout (Post-Doc) are both supported by grant of the Research Foundation Flanders (FWO): project number 1SA0620N and project number 1290821N, respectively.

Acknowledgements: The authors would like to thank Marte De Jonghe for substantial help in collecting the data. Additionally, a big 'thank you' goes to Babs Gezelle Meerburg en Ronald Noppers for their effort and help in creating the different speech materials. We acknowledge Hugo Van Hamme, Jelske Dijkstra, Henk van den Heuvel and Martijn Bentum for their aid in acquiring the language models used in this study. Lastly, we would like to thank all the participants for partaking in the study, without whom this study would not have been possible.

Author contributions: MG, JV and TF conceived and designed research; MG analyzed data; MG, JV and TF interpreted results of experiments; MG prepared figures and drafted manuscript; MG, JV and TF edited and revised manuscript; MG, JV and TF approved final version of manuscript.

Abstract

Speech comprehension is a complex neural process on which relies on activation and integration of multiple brain regions. In the current study, we evaluated whether speech comprehension can be investigated by neural tracking. Neural tracking is the phenomenon in which the brain responds in a time-locked fashion to specific features of the speech. These features can be acoustic, i.e., acoustic tracking, or derived from the content of the speech using language properties, i.e., language tracking. We evaluated whether neural tracking of speech differs between a comprehensible story, an incomprehensible story, and a word list. We evaluated the neural responses to speech of 19 participants (6 men). No significant difference regarding acoustic tracking was found. However, significant language tracking was only found for the comprehensible story. The most prominent effect was visible to word surprisal, a language feature at the word level. The neural response to word surprisal showed a prominent negativity between 300 and 400 ms, similar to the N400 in evoked response paradigms. This N400 was significantly more negative when the story was be comprehended, i.e., when words could be integrated in the context of previous words. These results show that language tracking can capture the effect of speech comprehension.

Significance statement: Most neural tracking studies focus on how the brain tracks acoustic speech features. However, whether acoustic tracking reflects speech comprehension is unclear. Therefore, in the pursuit of finding a neural marker for speech comprehension, language tracking might be a more suitable candidate. The results of this study showed that, indeed, language tracking can capture the effect of speech comprehension. This indicates that language tracking is a potential neural marker of speech comprehension. Such a neural marker would allow testing speech comprehension in populations that are currently difficult to test with behavioral tests, such as young children and persons with cognitive impairment.

1 Introduction

Speech comprehension is a complex neural process that relies on the activation and integration of different brain regions. Bottom-up and top-down processes allow speech comprehension to be fast and efficient, which is necessary to engage in conversations. However, the neural processes underlying speech comprehension are not well understood. Although fMRI can gain useful insight into these processes, this neuro-imaging modality cannot investigate these fast temporal responses associated with understanding. To overcome this, EEG or MEG can be used to investigate these responses with a higher temporal resolution, however compromising with a lower spatial resolution. To investigate the neural responses to sounds and speech, evoked responses to repetitive simple sounds can be investigated, for example, auditory brainstem response (for a review on evoked responses, see Picton, 2010). However, by using simple sounds, the insight gained is limited as these simple sounds do not require in-depth processing to yield comprehension. In recent years, there has been progress towards understanding the brain responses to continuous, natural running speech, relying on neural tracking. This is the phenomenon in which the brain time-locks to specific characteristics of the incoming speech (for a review, see Brodbeck and Simon, 2020). These characteristics can range from acoustic to language properties of speech.

Most neural tracking research focuses on acoustic aspects of the incoming sounds, called acoustic tracking. The link between acoustic tracking and speech comprehension is not clear. Some studies showed that, by using acoustic tracking of different speech fragments with varying signal-to-noise ratios, an objective measure could be derived similarly to the behaviorally measured speech comprehension (Vanthornhout et al., 2018; Lesenfants et al., 2019). This suggests that there is a link between acoustic tracking and speech comprehension. However, recent studies by Kosem et al. (2022) and Verschueren et al. (2022) showed that this link between acoustic tracking and comprehension is not always observed. More specifically, by manipulating speech comprehension by either using noise-vocoded speech or changing the speech rate, they observed that as the speech became comprehensible, acoustic tracking did not increase. Moreover, significant acoustic tracking can observed to music (Tierney and Kraus, 2014) and the ignored talker in a multi-speaker background (e.g. Horton et al., 2014; O'Sullivan et al., 2015; Ding and Simon, 2012, and many more). Altogether, this suggests that acoustic tracking is required to comprehend speech but does not necessarily imply speech comprehension. We might overcome this issue by investigating neural tracking of language properties of the speech, hereafter called language tracking (Gillis et al., 2022).

Over the last few years, language tracking has attracted more attention. Initially, it was identified which language properties were significantly tracked by the brain (e.g. Broderick et al., 2018; Brodbeck et al., 2018; Weissbart et al., 2020; Gillis et al., 2021; Heilbron et al., 2022). These studies show that the

brain shows a negative response around 400 ms after word onset, which is modulated by the information conveyed by the word, indicated by, e.g., word surprisal. This response is similar to the N400 as observed in evoked response studies and it is thought to resemble the activation of the lexical item and integration of this item into the context of the previous words (for a review on the N400, see Lau et al., 2008; Kutas and Federmeier, 2011). More recently, it was assessed whether language tracking is related to behavioral speech comprehension. By comparing listeners listening to their second language to native speakers of the language, Di Liberto et al. (2021) showed that as language proficiency increases, the response around 400 ms becomes more similar to a native speaker. Two other studies manipulated the amount of speech comprehension by manipulating the speech via word scrambling (Broderick et al., 2020) or manipulating the speech rate (Verschueren et al., 2022). Both studies observed that as the speech became incomprehensible, the N400 disappeared. However, these studies did not rely on natural spoken speech as they relied on either synthetic scrambled speech (Broderick et al., 2020) or artificially sped up speech (Verschueren et al., 2022).

In this study, we used natural spoken speech. We presented three different speech materials, a comprehensible story, an incomprehensible story and a word list, naturally spoken by the same speaker. We hypothesized that when native Flemish participants listened to a story in a foreign language, here Frisian, they did not track the content of the presented speech, and thus we would not see language tracking. Accordingly, we hypothesized that no N400 would be observed. For the word list, the listener does have access to the meaning of the word, but the word cannot be integrated in the context of the previous words. Therefore, both processes would affect the presence of the N400 to language features at the word level. Similar hypotheses could be made about the language features at the phoneme level, which elicit an N250 which is less well studied. Overall, this study aims to assess whether language tracking can capture the effect of speech comprehension.

2 Methods

2.1 Participants

For this study, 19 participants were included (6 men; mean age $\pm$ std $= 22 \pm 3$ years). The inclusion criteria were normal hearing, Dutch as a mother tongue and the absence of attention problems, learning disabilities, or severe head trauma. The latter were identified via a questionnaire. Pure tone audiometry was conducted at center frequencies from 125 to 8000 Hz to assess the hearing capacity. Participants,

where a hearing threshold exceeded 20 dB HL, were excluded from this study.

2.2   Speech stimuli

We created custom speech stimuli for this study, resulting in three conditions: Dutch speech, Frisian speech and a word list, all spoken by the same speaker. The speech materials were derived from two episodes of 'De Volksjury', a Flemish podcast series about crime cases. The podcast episodes were transcribed and rewritten in an entertaining story, resulting in two fragments: a story about Jack The Ripper and a shorter story about the disappearance of Madeleine McCann. The latter consisted of only the beginning part of the original podcast and was used to create the Frisian story and the word list. For the Frisian story, the story was translated into Frisian. We opted for Frisian as this language is related to Dutch and follows similar grammatical rules. However, it is poorly understood by Dutch listeners without knowledge of Frisian. All the words in the story were randomly shuffled for the word list, thereby not preserving the syntax. The word list contained sentences matched in length with the original story to aid the speaker in using natural prosody.

The speech materials were all spoken by the same native Dutch male speaker who learned Frisian as a second language. We manually edited the speech recordings to remove stutters, clicks, and mispronunciations. In the Frisian story, we removed sentences that consisted of a high amount of loanwords. In total 5 sentences, i.e. 52 words, were removed from the speech material. After inspection, for the word list, we removed sentences with unnatural prosody (in total 199 words).

The Dutch story lasted around 45 minutes and was divided in four parts, each lasting between 10 to 13 minutes. The Frisian story lasted around 7 minutes, and the word list around 9 minutes. As the listener could not understand these two speech materials, we aimed to motivate the listener to attend attentively to the stimulus by keeping the speech material shorter and making the listener perform a word identification task. Therefore, the latter two speech materials were divided in four parts, each lasting around 2 minutes.

The speech was presented bilaterally to the participants at an intensity of 65 dB (A-weighted). The speech materials were presented in a different random order for each participant; however, the order of the fragments within one speech material was preserved. After each fragment, a content question was asked in case of the Dutch speech fragments, or a word identification task was conducted to keep the participant motivated to listen to the stimulus attentively. Additionally, we asked the participant to rate

₁₁₃ their speech understanding by asking the question *how much did you understand about the content of the*

₁₁₄ *story?* ranging from 0 to 100%.

2.3 Speech features

₁₁₆ Similar to Gillis et al. (2021), we used 8 speech features. To control for the acoustic energy of the speech

₁₁₇ signal, we used two continuous speech features, i.e., the speech spectrogram and acoustic edges. We

₁₁₈ included two (pre-)lexical speech features which denote the onset of phonemes and words. Although

₁₁₉ neural responses to these (pre-)lexical speech features are not purely acoustic, these features are included

₁₂₀ in the model as acoustic controls for the language features. Additionally, we included four language

₁₂₁ features, i.e., phoneme surprisal, cohort entropy, word surprisal and word frequency. Unlike the acoustic

₁₂₂ and (pre-)lexical features, the language features are derived from the content of the speech. All speech

₁₂₃ features for the first sentence of the three speech materials are visualized in Figure 1.

₁₂₄ The spectrogram and acoustic edges reflect the continuous acoustic energy of the speech material. The

₁₂₅ spectrogram was created using the Gammatone Filterbank Toolkit 1.0 (Heeris, 2014, center frequencies

₁₂₆ between 70 and 4000 Hz with 256 filter channels and an integration window of 0.01 second). By

₁₂₇ combining 32 consecutive filter outputs, the 256 filter outputs were averaged in eight frequency bands.

₁₂₈ Additionally, the spectrogram was downsampled to match the sampling frequency of the preprocessed

₁₂₉ electroencephalography (EEG) data, namely 128 Hz. To obtain the acoustic edges, the derivative of the

₁₃₀ spectrogram is calculated and negative values are set to 0.

₁₃₁ Using a forced aligner (Duchateau et al., 2009), we constructed a word and phoneme segmentation.

₁₃₂ This forced aligner was also applied for the Frisian condition and corrected manually with the PRAAT

₁₃₃ software (Boersma and Van Heuven, 2001). These segmentations were used to create the (pre-)lexical

₁₃₄ and language features. All these features are discrete, one-dimensional arrays with impulses on onsets of

₁₃₅ phonemes or words. These impulses have a fixed amplitude for the (pre-)lexical features, while for the

₁₃₆ language features, the impulses are modulated by the information value of a phoneme or word.

₁₃₇ Phoneme surprisal and cohort entropy are two language features at the phoneme level. Both metrics are

₁₃₈ derived from the active cohort of words, i.e., the words congruent with the previously uttered phonemes.

₁₃₉ Phoneme surprisal reflects how surprising a phoneme is, given its previously uttered phonemes. It reflects

₁₄₀ the phoneme's prediction error, which is intrinsically related to the information a phoneme contributes to

₁₄₁ its context. The more likely a specific phoneme is, the lower its surprisal value, and the less information

Figure 1: **Speech features at acoustic, (pre-)lexical and language level** We visualized the speech features used in this study for the three speech materials. In panel A, the different features are visualized for the first sentence of each speech material, respectively the Dutch story (orange), the Frisian story (blue) and the word list (yellow). In panel B, the distribution of the non-zero values of the different language features is depicted. In panel C, the Dutch and Frisian language models are compared. For the top plot, the phoneme frequency at a specific place in the word in Dutch compared to Frisian is visualized. In the plot below, the word frequencies are visualized for the Frisian word, derived from the Frisian language model, versus its Dutch translation, derived from the Dutch language model.

is gained (and vice versa). Cohort entropy reflects the uncertainty of the phoneme prediction. If the uncertainty of the phoneme prediction is high, the active cohort consists of a large number of words with a similar probability of being uttered.

Phoneme surprisal is calculated as a negative logarithm of the inverse conditional probability of the phoneme given the previously uttered phonemes. Cohort entropy is calculated as the Shannon entropy of the active cohort of words. To project cohort entropy to similar scales, the values of cohort entropy were divided by the maximal value of cohort entropy in the speech fragment. More details and the mathematical determinations of these metrics can be found in Brodbeck et al. (2018). For the Dutch language features at the phoneme level, the phoneme segmentation of the words was obtained using a custom word-to-phoneme dictionary (as used in Gillis et al., 2021), while the word frequencies were derived from SUBTLEX-NL (Keuleers et al., 2010). For the Frisian language features at the phoneme level, both the word-to-phoneme dictionary and the word frequencies were used from Yilmaz et al. (2016).

Similar to phoneme surprisal, word surprisal reflects how surprising a word is given the previously uttered words. It reflects the word's prediction error, which is related to how much information the word contributes to its context. Word frequency reflects the probability of the word independent of its context.

Word surprisal was calculated as the negative logarithm of the conditional probability of the considered word given the four preceding words. This conditional probability was obtained with a 5-gram model created by Verwimp et al. (2019) for the Dutch material and by Yilmaz et al. (2016) for the Frisian material. Using these models, word frequency was obtained by calculating the negative probability of the uni-gram probability of the word.

Remark that the language models used to derive the Dutch and Frisian language features differ. Therefore, we investigated the phoneme and word frequency to assess whether the language model had a significant impact on the values of the speech features. In the first comparison, we compared the probability of a phoneme occurring at a specific position in Dutch to this probability in Frisian, e.g., the probability of the phoneme /a/ occurring second is fairly similar in Dutch as in Frisian (visualized in figure 1.C top panel). These phoneme frequencies in Dutch were significantly correlated with those in Frisian (Pearson's r = 0.68, p < 0.001). This suggests that phoneme frequencies are similar in Dutch and Frisian. Additionally, we compared the word frequency of a Dutch word derived from the Dutch language model to the word frequency of its Frisian translation using the Frisian language model. Indeed, these word frequencies are significantly correlated (Pearson's r = 0.88, p < 0.001). Additionally, we visually

inspected the distribution of the feature values to ensure no drastic differences between the different conditions (figure 1.B). Using language models of different sizes, which are also trained on different text corpora, is sub-optimal. However, these outcomes reassure us that the usage of these different language models is valid to do.

2.4 EEG preprocessing

To decrease preprocessing time, the measured EEG data were downsampled to 265 Hz. After this initial downsampling step, using the multichannel Wiener filtering (Somers et al., 2018), the spatio-temporal characteristics of eye-blink artifacts were estimated in the EEG to the second part of the Dutch story. These characteristics are then used to filter out eye-blink artifacts in the EEG measured to the first part of the Dutch story, the Frisian story, and the word list. Subsequently, the EEG data were referenced to the common average reference. The EEG data and the continuous acoustic speech features were filtered between 0.5 and 25 Hz using Least Squares Filtering (using least-squares linear-phase FIR filter function of MATLAB with the high-pass filter order of 5000, low-pass filter order of 250, with a stopband frequency 10% outside the passband frequency and passband weight of 100 and stopband weight of 1). Afterwards, the EEG data were downsampled to 128 Hz and normalized, i.e. z-scoring (subtracted the mean and divided by the standard deviation). This normalization was performed across the EEG data of the three conditions.

To further clean the EEG data, denoising source separation (DSS) (de Cheveigné and Simon, 2008) was applied. This method allows for further removal of non-stimulus-related activity. It estimates spatial filters and associated components which capture the stimulus-related activity repeated across the different trials or participants, sorted according to power. Here, we estimated the spatial filters across the EEG data of all participants listening to the second part of the Dutch story. To train DSS, we used a filter between 2 and 25 Hz (Least square filtering with order 400; see further filter descriptions above). Note that this filter band is only used to train the DSS filters. Additionally, remark that this second part is solely used to estimate the DSS components and to estimate the filter for the multichannel Wiener filtering to prevent a biased analysis. Subsequently, we selected the six components with the highest power to apply to the first part of the Dutch story, the Frisian story and the word list. Using these six components, we projected the EEG data back to sensor space.

Because the duration of the speech material varied, we limited the duration to the first 455 seconds for all three speech materials (discarding most of the data in the Dutch condition).

2.5 Encoding modeling approach

We applied a linear encoding model to get insight in how the brain responds to different speech features. This modeling approach estimates the spatial and temporal pattern of the neural responses to the speech features. This pattern is called a temporal response function (TRF). This TRF can then be used to predict the EEG responses associated with specific speech features. A prediction accuracy can be obtained by correlating the predicted EEG responses with the measured EEG responses. The prediction accuracy is a measure of neural tracking: the more the brain *tracks* the speech, the higher the prediction accuracy will be.

To apply this encoding modeling approach, we used the Eelbrain Toolbox (Brodbeck, 2020). This toolbox estimates the TRF using an iterative boosting approach (David et al., 2007). We estimate the TRF using 10-fold cross-validation. This implies that the data is divided in ten equally long folds: 8 folds are used for estimating the TRF, i.e., training the model, one fold for validation of TRF TRF estimation, and one fold to evaluate this TRF by determining the prediction accuracy, i.e., testing the model. This is repeated for all train and test combinations. Further used parameters for the model estimation were an integration window from -100 to 600 ms, a convolution with a basis window of 50 ms (Hamming window) which was used to make the TRF less sparse and the use of early stopping based on the ℓ2-norm of the difference between the actual and predicted EEG responses.

2.6 Determination of acoustic and language tracking

Acoustic tracking is here denoted as the prediction accuracy obtained with a model which includes acoustic speech features, i.e., the spectrogram and acoustic edges.

To determine whether or not the brain significantly tracked the language features, we used an approach that relies on the difference in prediction accuracies between two models (as applied in, e.g., Di Liberto et al., 2015; Brodbeck et al., 2018; Gillis et al., 2021). Here, we focused on the added value of all four language features combined. We constructed a baseline model, which included the acoustic and (pre-)lexical features, which served as acoustic controls for the included language features. Subsequently, we constructed a complete model that included the language features on top of the acoustic and (pre-)lexical features. The increase in prediction accuracy between the complete and baseline model signifies the improvement of the model due to the language features. This improvement is here called *language tracking*.

2.7 Determine the peak characteristics

We defined the maximal amplitude of the TRF, averaged across a channel selection, within specific time regions to determine the peak amplitudes and latencies. The time regions were determined based upon the average TRF of each speech feature. The channel selections were set a priori. For acoustic tracking, we used the channel selection suggested by Lesenfants et al. (2019) while for language tracking, the same channel selection as Gillis et al. (2021) was used. If the found peak was at the edges of the time region, the peak was discarded. The time regions used for the different peaks for each feature and the number of peaks are summarized in Table 1.

Table 1: Time regions selected per speech feature to determine the peak characteristics. The number of participants for whom a peak was found is reported as well (of the 19 participant included in this study).

feature	time region	peak name	Dutch story	Frisian story	word list
spectrogram	0 - 65 ms	P1	12	11	11
	70 - 110 ms	N1	4	6	6
	115 - 200 ms	P2	9	14	9
acoustic edges	0 - 90 ms	P1	19	18	18
	95 - 140 ms	N1	12	7	9
phoneme surprisal	150 - 350 ms	N250	17	17	17
cohort entropy	150 - 350 ms	N250	14	18	18
word surprisal	300 - 500 ms	N400	17	16	17
word frequency	300 - 500 ms	N400	16	16	18

2.8 Statistics

We performed pairwise comparisons to compare whether the behavioral results, neural tracking, or neural response amplitudes and latencies differed between the different speech materials. As not all the data were normally distributed, we opted for non-parametric tests, namely the pairwise Wilcoxon signed-rank test and Mann-Whitney U Test, with a Benjamini-Hochberg correction for multiple comparisons. To investigate the differences between the speech materials for the behavioral results and for the neural tracking, we used the paired Wilcoxon signed-rank test, grouping the results from the same subject. However, these paired tests could not be used when investigating the differences in neural response amplitude or latency. For some subjects, no peak could be found, and the paired Wilcoxon sign-rank test cannot handle missing data. Therefore, the Mann-Whitney U Test was used in these cases. The outcomes of these tests are reported with the *z*- or *u*-score and p-value for, respectively, the Wilcoxon signed-rank test or Mann-Whitney U Test. These tests were applied using the Eelbrain (Brodbeck, 2020) implementation for pairwise comparisons.

To determine whether the TRF or the spatial distribution of the (difference in) prediction accuracy were significantly different from 0, we used cluster-based permutation tests as recommended by Maris and Oostenveld (2007), using the Eelbrain (Brodbeck, 2020) implementation. This test was applied for each TRF individually with a significance level of $\alpha=0.017$, i.e., the significance level of $\alpha=0.05$ divided by the three as we performed this test for the three different speech materials.

To determine whether a peak was observed, we assessed whether the TRF is significantly negative in the region of interest (reported in Table 1) using the cluster-based permutation test (see description above). Moreover, we applied these tests in a one-sided fashion to identify whether the TRF was significantly positive or negative according to the considered peak.

3 Results

3.1 Behavioral Results

The behavioral results obtained in this study consisted of a subjective rating (*how much did you understand about the content of the story?*) and a word identification task which the participants only did for the Frisian story and the word list. The behavioral results are visualized in Figure 2.

There are significant differences between the subjective rating of all three speech materials. The subjective ratings for the Dutch story (median = 100 %) were significantly different from those for Frisian (median = 50 %; $z_{(18)} < 0.01$, p < 0.01) and the word list (median = 10.5 %; $z_{(18)} < 0.01$, p < 0.01). Also, the subjective rating for the Frisian story differed significantly from the rating for the word list ($z_{(18)} < 0.01$, p < 0.01). These results suggest that the Dutch story is better comprehended than the Frisian story, which is better comprehended than the word list.

The results on the word identification score, were significantly higher for the Frisian story (median = 75 %) than the word list (median = 58.3 %; $z_{(18)} = 35.50$, p = 0.029).

Figure 2: **Behavioral results** Panel A: The subjectively rated speech understanding as a function of the speech material, respectively the Dutch story (orange), Frisian story (blue) and word list (yellow). Panel B: The results of the word identification task for the Frisian story and the word list. *(*: p < 0.05, **:p < 0.01, ***: p < 0.001)*

3.2 Neural Tracking

To evaluate the acoustic tracking of speech, we investigated the prediction accuracies obtained with the acoustic model, i.e., the model including only the spectrogram and acoustic edges (shown in panel A of Figure 3). The results of the cluster-based permutation test showed that for all three speech materials, a prediction accuracy significantly higher than zero is obtained (1 cluster containing all 64 EEG sensors, $p < 0.001$ for all speech materials; corrected for 3 comparisons). Additionally, we investigated the differences between the three speech materials by applying a pairwise comparison test on the prediction accuracies averaged across a frontal channel selection. The results of the pairwise comparison test did not identify a significant difference between the three speech materials.

Additionally, we investigated language tracking across the three speech materials. Language tracking was calculated as increased prediction accuracy when language features are included on top of acoustic and (pre-)lexical features. Only for the Dutch story, the results of the cluster-based permutation test showed that some central and left-lateralized channels drove the increase in prediction accuracy to be significantly higher than zero ($p = 0.008$; corrected for 3 comparisons). However, the pairwise comparisons

Figure 3: **Neural tracking**: Panel A: Acoustic tracking is shown are shown for the three speech materials, respectively the Dutch story (orange), Frisian story (blue), and word list (yellow). More specifically, the spatial distribution of the prediction accuracies obtained with only the acoustic features is visualized on the left side. The same prediction accuracies are visualized on the right side but averaged across a frontal channel selection (see head plot). Panel B: Linguistic tracking across the three speech materials. The spatial distribution of the increase in prediction accuracy when linguistic features are included on top of acoustic and (pre-)lexical features is visualized on the left side. The encircled channels indicate the cluster, which drives the spatial distribution to be significantly higher than zero as obtained by the cluster-based permutation test. The same increases in prediction accuracy are visualized on the right side, averaged across a central channel selection (see head plot).

289 of the prediction accuracies averaged across a central channel selection did not show significant differences

290 between the three speech materials.

3.3 Neural response to acoustic and (pre-)lexical features

To investigate how the brain responds to acoustic speech features, one can investigate the pattern of the TRF (see Figure 4). The TRF to the spectrogram is characterized by three prominent peaks: a first positive peak (P1) followed a negative peak (N1) and a later second positive peak (P2). This pattern differs from the one seen for acoustic edges, where only a first positive peak (P1) and a following negative peak (N1) are observed.

The TRF reaches significance for all positive peaks in the acoustic features. However, the N1 peak for the spectrogram did not reach significance for all three conditions (top panel in Figure 4). At the same time, for acoustic edges only the Dutch story and the Frisian story showed a significant negative N1 peak (bottom panel in Figure 4). We investigated the peak amplitudes and latencies to quantify the differences between the TRFs. For all peak amplitudes and latencies, no significant differences were found between the three conditions for all peaks of the TRF to acoustic features.

Figure 4: **Neural response to acoustic speech features** For each acoustic speech feature, the TRFs in a frontal channel selection (shown as a right inset on the top panel) are depicted (left). The significance of the TRF is indicated by the thick lines in the corresponding colour and the horizontal lines below the TRF. The vertical grey blocks mark the time regions used for peak determination. For each of these peaks, the associated peak topographies are visualized (right) for respectively the Dutch story (orange), Frisian story (blue) and word list (yellow).

3.4 Neural response to language features

Within the time regions of interest, we identified whether the TRF was significantly below zero (corrected for three comparisons).

For phoneme surprisal, we observe that all three speech materials show at least one cluster. For the Dutch story, we observed 4 clusters: from 165 to 197 ms, from 123 to 244 ms, from 260 to 283 ms, and from 306 to 314 ms. For the word list, 2 clusters were identified ranging from 196 to 259 ms and 282 to 345 ms. A small cluster at the boundary of the time region was identified for the Frisian story, i.e., from 345 to 353 ms. After peak determination, no differences in amplitude or latency between the three speech materials were found for phoneme surprisal evaluated in a central channel selection.

For cohort entropy, the N250 of the TRF was less prominent than for phoneme surprisal. For the Dutch story, two small clusters were found: around 260 ms and 310 ms. Three clusters were found for the word list ranging from 212 to 228 ms, 244 to 267 ms, and 330 to 353 ms. One cluster was observed for the Frisian story around 220 ms. Similar to phoneme surprisal, the differences between the peak amplitudes or latencies did not reach significance.

For word surprisal, only for the Dutch conditions, the TRF showed a peak which was significantly below zero. The cluster-based permutation test identified three clusters ranging from 330 to 345 ms, 361 to 400 ms, and 423 to 447 ms. The TRF to word surprisal for the word list showed two small clusters around 440 and 480 ms. Here, the amplitude difference reached significance: the N400 amplitude for the Dutch story (median = -0.00063) is different from the Frisian story (median = -0.00005; $u_{(30)} = 222$, $p < 0.001$; corrected after Benjamini-Hochberg) as well as from the word list (median = -0.0001; $u_{(32)} = 71$, $p = 0.024$; corrected after Benjamini-Hochberg). Altogether these results suggest only a prominent N400 is found in response to the Dutch story but not to the Frisian story or the word list. No differences were found regarding the latency of this N400 peak.

For word frequency, the N400 in the TRF for both the Dutch story and word list were significantly below zero. For the Dutch story, we identified two clusters, ranging from 314 to 345 ms and around 370 ms. Also, two small clusters were identified for the word list, around 400 and 495 ms. No differences were found regarding the amplitude or latency of the N400 peak to word frequency.

Figure 5: **Neural response to language features** For each language feature, the TRFs in a central channel selection (shown as a left inset on the top panel) are depicted (left). The significance of the TRF is indicated by the thick lines in the corresponding colour and the horizontal lines below the TRF. The time region used for peak determination is marked by the vertical grey block. The associated peak topographies are visualized as insets on each panel for, respectively, the Dutch story (orange), Frisian story (blue) and word list (yellow). On the right side of each panel, the peak amplitudes are visualized. *(*: p < 0.05, **:p < 0.01, ***: p < 0.001)*

4 Discussion

We observed that acoustic features were similarly tracked across the three different speech materials. Likewise, the pattern of neural responses (TRFs) for frontal channels was similar across the different speech materials. Regarding language tracking of speech, only the Dutch condition reached significance. For the TRFs in central channels, we observed different patterns for the different speech materials. Only for language features at the phoneme level, the TRF for the Frisian story showed a significant negativity in the time window of interest, which was not the case for the language features at the word level. For the Dutch fragments, all four language features evoke a significant negative response. However, for word surprisal, only a prominent N400 was observed in the TRF for the Dutch story, which significantly differed from the Frisian story and the word list.

Regarding the behavioral results, it is unsurprising that the Dutch story was better understood than the Frisian story and the word list. Although the study aimed to present an incomprehensible story with a similar syntax to the Dutch story, this was probably not achieved. The subjective ratings of speech understanding showed that some participants understood the Frisian story quite well. This is presumably because Frisian and Dutch are related languages which helps the listener to grasp the content of the story to some extent (Van Bezooijen and Gooskens, 2007). By getting an idea of the story's content, the context could aid the word identification task, which could explain the higher word identification scores. A similar trend is seen in Broderick et al. (2020), the more the text is shuffled, the lower the performance on the word identification task. In sum, we could conclude that the content of the Dutch story is fully understood, while around 50% for the Frisian story and very limited for the content of the word list is captured by the participants. However, as a side note, the subjectively rated speech understanding is difficult to estimate to a story in a foreign language, i.e., it is not necessarily because someone thinks they understood 50% of the content that this is actually the case.

Previous studies suggest that the comprehension of speech is reflected by acoustic neural tracking. By manipulating the signal-to-noise ratio of the speech, Vanthornhout et al. (2018) showed that as speech comprehension increases, acoustic speech tracking increases as well. Additional evidence comes from the study by Etard and Reichenbach (2019). They investigated acoustic tracking to a comprehensible and foreign story and reported that acoustic tracking in the delta band encoded speech comprehension. However, we did not find a difference in acoustic tracking between the three speech materials. We could speculate that the difference in acoustic tracking observed in Etard and Reichenbach (2019) is due to the speaker characteristics. Etard and Reichenbach (2019) did not keep the speaker constant while the speaker acoustics affect acoustic neural tracking. Another important difference is the frequency range, Etard and

Reichenbach (2019) observed the effect in the delta band but not the theta band. Here, a broader frequency range is investigated. However, as EEG follows a 1/f-characteristics, a broader frequency range would follow similar patterns as the delta band. In line with our results, Kosem et al. (2022) and Verschueren et al. (2022) also did not see a link between acoustic tracking and speech comprehension. Altogether, this suggests that acoustic tracking is a necessity rather than a sufficient condition for speech comprehension.

In neural response patterns (the TRFs), no prominent differences were found between the three speech materials. This suggests that acoustic TRFs do not depend on whether or not the speech is understood. Often the P2 peak to acoustic features is associated with speech comprehension (Ding and Simon, 2012; Vanthornhout et al., 2019; Verschueren et al., 2022). However, here a P2 peak is found for all three speech materials. One hypothesis might be that the P2 peak is associated with speech segmentation but not necessarily comprehension. As the Frisian language follows a similar structure to Dutch, words could be segmented but not necessarily understood. Overall our results suggest that when someone listens attentively to speech in silence, acoustic tracking or the pattern of the TRF is not sufficient to determine whether or not the listener understood the speech. A solution might be to investigate the neural tracking of language features.

Languages tracking quantifies to what extent the brain time-locks to language features derived from the content of the speech. Only for the Dutch story, we observed that language features were significantly tracked (Figure 3). This effect was prominent in a small cluster from central to left-lateralized channels. This finding is similar to the findings of Gillis et al. (2021) using the same language features. However, the effect was more prominent in the study of Gillis et al. (2021), which is likely due to the effect of more training data as impulsive features require more data (Mesik and Wojtczak, 2022). If the amount of data is small, the TRFs are noisier but have a similar pattern as those determined with more data (Mesik and Wojtczak, 2022). This justified investigating the TRFs for language features in more detail.

Regarding the TRFs at the phoneme level, we observed only one cluster for the Frisian story, which was situated around 350 ms for phoneme surprisal. The determination of phoneme surprisal is independent of previously uttered words and solely relies on the phoneme probability in the active cohort of words (unigram frequency of the word, independent of its context). As the phoneme frequencies are similar between Frisian and Dutch (Figure 1), we can expect that Dutch listeners try to form a word based on the uttered phonemes, which might explain the marginal negative response. The later negative peak, around 400 ms, to phoneme surprisal in the Frisian condition has a similar topography (not shown) as the N250 response for the Dutch story. Presumably, the increase in latency indicates that more processing

time is required to integrate the information of the new phoneme with the previously uttered phonemes to recognize a known word. For the Dutch story and the word list, the N250 peak is observed, which is as expected. For these two speech materials, the active cohort can be estimated accurately, so a prediction of an upcoming phoneme can be made.

Cohort entropy also depends on the active cohort of words. Following the same reasoning, we expected that the N250 to cohort entropy is only visible for the Dutch story and the word list but not for the Frisian story. However, unexpectedly, we observed a small cluster around 220 ms. Gillis et al. (2021) speculated that both phoneme surprisal and cohort entropy captured different aspects of a similar underlying neural process. Following their reasoning, these results suggest that some underlying phoneme processing occurs when listening to the Frisian story. Overall, the observed responses at the phoneme level to the Frisian story are not prominent, indicating that underlying phoneme processing is less pronounced than for the Dutch story or the word list.

Regarding the TRF at the word level, we observed that only the Dutch story obtains a significant N400 for the word surprisal. The N400 is thought to represent multiple processes, such as activation of the lexical item in memory and integration of the word in its context (for reviews, see Lau et al., 2008; Kutas and Federmeier, 2011). Therefore, it is not surprising that only an N400 is observed for the Dutch story, as only for the Dutch story can a word be integrated in its context. As there is no meaningful context for the word list condition, a word cannot be integrated into its context, and therefore, it was expected and verified that there is no N400 to word surprisal for the word list.

Although the Dutch listeners reported that they could understand around 50% of the Frisian story's content, no N400 was observed to word surprisal nor word frequency. The reasons are threefold. Firstly, the effect of an N400 is not consistently present for all words as not all words are understood. Secondly, the 5-gram model captures the context of the four preceding words, which might be too limited as the participants only capture around half of the story's content. Lastly, although the word frequencies are similar between Frisian and their translated items, it is not necessarily easier for the participant to map Frisian words to their Dutch translations. For example, *bern*, the Frisian word for children is unlikely to be mapped to its Dutch translation *kinderen* while for the Frisian word *twa* (two) is easier mapped to the Dutch translation *twee*.

Overall our results regarding the observed patterns in the TRFs to language features converge with the findings of Di Liberto et al. (2021) and Broderick et al. (2020): the worse the listener can integrate a word in its context due to lower language proficiency or higher word scrambling, the less prominent the N400

response. Therefore, activation of a word and integration of the word in its context are more difficult, explaining why no significant clusters are found for both word surprisal and word frequency for the Frisian story. For word frequency, negative clusters are found for the Dutch story and the word list. For the word list, this was expected as word frequency is modelled independently of its context. It is noticeable that the amplitude of N400 negativity is smaller than word surprisal, which is in agreement with Gillis et al. (2021). Gillis et al. (2021) speculated that the response to word frequency might resemble the activation of a lexical item, while the response to word surprisal captures the activation of a lexical item and its integration into the context. This converges with our results for the Dutch story and the word list. In both cases, an N400 was observed for word frequency, while only a prominent N400 was observed for word surprisal in the Dutch story, which significantly differed from the Frisian story and the word list.

The current study's caveats lie in determining language tracking. Firstly, the amount of data gathered for the Frisian story and word list condition is limited. This decreases the statistical power to obtain significant language tracking and causes the TRFs to have a noisier pattern. However, we opted for a limited amount of data as listening to a word list, or incomprehensible story is less attractive, and attention might drift away from the speech stimulus. Secondly, we could further optimize language tracking by determining channel selection in a data-driven way. Here, the channel selection was determined based on Gillis et al. (2021). However, this might be suboptimal as this channel selection did not contain the cluster which drove the significance of the linguistic tracking. We believe that the channel selection should either be defined a priori, as was done in the current study, or should be determined in a data-driven, cross-validated way. However, as the data is limited, we opted for the first approach. Lastly, the current evaluation is performed at the population level. Due to the limited amount of data, the TRFs are noisy and, therefore, averaging across all participants improves the signal-to-noise ratio to allow interpretations of the TRF. If more data is collected, one could relate the behavioral measures to peak amplitudes of the language features, assessing neural tracking of language features in more detail.

In sum, we only observed language tracking for the comprehensible story while not for the incomprehensible story or the word list. The observed patterns in the TRFs were as expected. The most prominent effect was found for word surprisal: a prominent N400 response was only present for the Dutch story, which significantly differed form the Frisian story or the word list. This corresponds with the hypothesis that the N400 response to word surprisal resembles a word's integration in its context. Overall, this indicates that language tracking is related to speech comprehension. Future research should focus on making this measure robust on a subject-specific level. If language tracking is suitable to evaluate speech comprehension at a subject-specific level, one could use it as an objective measure of speech comprehension, which would allow testing speech comprehension in populations that are currently difficult

458 to test with behavioral tests, such as young children and persons with cognitive impairment.

References

Boersma, P. and Van Heuven, V. (2001). Speak and unspeak with praat. *Glot International*, 5(9/10):341–347.

Brodbeck, C. (2020). Eelbrain 0.34. `10.5281/zenodo.4455651`.

Brodbeck, C., Hong, L. E., and Simon, J. Z. (2018). Rapid transformation from auditory to linguistic representations of continuous speech. *Current Biology*, 28(24):3976–3983.

Brodbeck, C. and Simon, J. Z. (2020). Continuous speech processing. *Current Opinion in Physiology*, 18:25–31.

Broderick, M. P., Anderson, A. J., Di Liberto, G. M., Crosse, M. J., and Lalor, E. C. (2018). Electrophysiological correlates of semantic dissimilarity reflect the comprehension of natural, narrative speech. *Current Biology*, 28(5):803–809.

Broderick, M. P., Zuk, N. J., Anderson, A. J., and Lalor, E. C. (2020). More than words: Neurophysiological correlates of semantic dissimilarity depend on comprehension of the speech narrative. *bioRxiv*.

David, S. V., Mesgarani, N., and Shamma, S. A. (2007). Estimating sparse spectro-temporal receptive fields with natural stimuli. *Network: Computation in neural systems*, 18(3):191–212.

de Cheveigné, A. and Simon, J. Z. (2008). Denoising based on spatial filtering. *Journal of neuroscience methods*, 171(2):331–339.

Di Liberto, G. M., Nie, J., Yeaton, J., Khalighinejad, B., Shamma, S. A., and Mesgarani, N. (2021). Neural representation of linguistic feature hierarchy reflects second-language proficiency. *Neuroimage*, 227:117586.

Di Liberto, G. M., O'sullivan, J. A., and Lalor, E. C. (2015). Low-frequency cortical entrainment to speech reflects phoneme-level processing. *Current Biology*, 25(19):2457–2465.

Ding, N. and Simon, J. Z. (2012). Emergence of neural encoding of auditory objects while listening to competing speakers. *Proceedings of the National Academy of Sciences*, 109(29):11854–11859.

Duchateau, J., Kong, Y. O., Cleuren, L., Latacz, L., Roelens, J., Samir, A., Demuynck, K., Ghesquière, P., Verhelst, W., and Van hamme, H. (2009). Developing a reading tutor: Design and evaluation of dedicated speech recognition and synthesis modules. *Speech Communication*, 51(10):985–994.

Etard, O. and Reichenbach, T. (2019). Neural speech tracking in the theta and in the delta frequency band differentially encode clarity and comprehension of speech in noise. *Journal of Neuroscience*, 39(29):5750–5759.

Gillis, M., Van Canneyt, J., Francart, T., and Vanthornhout, J. (2022). Neural tracking as a diagnostic tool to assess the auditory pathway. *bioRxiv*.

Gillis, M., Vanthornhout, J., Simon, J. Z., Francart, T., and Brodbeck, C. (2021). Neural markers of speech comprehension: measuring eeg tracking of linguistic speech representations, controlling the speech acoustics. *Journal of Neuroscience*, 41(50):10316–10329.

Heeris, J. (2014). Gammatone filterbank toolkit 1.0. `https://github.com/detly/gammatone`.

Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P., and De Lange, F. P. (2022). A hierarchy of linguistic predictions during natural language comprehension. *Proceedings of the National Academy of Sciences*, 119(32):e2201968119.

Horton, C., Srinivasan, R., and D'Zmura, M. (2014). Envelope responses in single-trial eeg indicate attended speaker in a 'cocktail party'. *Journal of neural engineering*, 11(4):046015.

Keuleers, E., Brysbaert, M., and New, B. (2010). Subtlex-nl: A new measure for dutch word frequency based on film subtitles. *Behavior research methods*, 42(3):643–650.

Kosem, A., Dai, B., McQueen, J., and Hagoort, P. (2022). Neural tracking of speech does not unequivocally reflect intelligibility. *bioRxiv*.

Kutas, M. and Federmeier, K. D. (2011). Thirty years and counting: finding meaning in the n400 component of the event-related brain potential (erp). *Annual review of psychology*, 62:621–647.

Lau, E. F., Phillips, C., and Poeppel, D. (2008). A cortical network for semantics:(de) constructing the n400. *Nature Reviews Neuroscience*, 9(12):920–933.

Lesenfants, D., Vanthornhout, J., Verschueren, E., Decruy, L., and Francart, T. (2019). Predicting individual speech intelligibility from the cortical tracking of acoustic-and phonetic-level speech representations. *Hearing research*, 380:1–9.

Maris, E. and Oostenveld, R. (2007). Nonparametric statistical testing of eeg-and meg-data. *Journal of neuroscience methods*, 164(1):177–190.

Mesik, J. and Wojtczak, M. (2022). The effects of data quantity on performance of temporal response function analyses of natural speech processing. *bioRxiv*.

O'Sullivan, J. A., Power, A. J., Mesgarani, N., Rajaram, S., Foxe, J. J., Shinn-Cunningham, B. G., Slaney, M., Shamma, S. A., and Lalor, E. C. (2015). Attentional selection in a cocktail party environment can be decoded from single-trial eeg. *Cerebral cortex*, 25(7):1697–1706.

Picton, T. W. (2010). *Human Auditory Evoked Potentials*. Plural Pub.

Somers, B., Francart, T., and Bertrand, A. (2018). A generic eeg artifact removal algorithm based on the multi-channel wiener filter. *Journal of neural engineering*, 15(3):036007.

Tierney, A. and Kraus, N. (2014). Neural entrainment to the rhythmic structure of music. *Journal of Cognitive Neuroscience*, 27(2):400–408.

Van Bezooijen, R. and Gooskens, C. (2007). Interlingual text comprehension. *Receptive Multilingualism: Linguistic Analyses, Language Policies, and Didactic Concepts*, page 249.

Vanthornhout, J., Decruy, L., and Francart, T. (2019). Effect of task and attention on neural tracking of speech. *Frontiers in neuroscience*, 13:977.

Vanthornhout, J., Decruy, L., Wouters, J., Simon, J. Z., and Francart, T. (2018). Speech intelligibility predicted from neural entrainment of the speech envelope. *Journal of the Association for Research in Otolaryngology*, 19(2):181–191.

Verschueren, E., Gillis, M., Decruy, L., Vanthornhout, J., and Francart, T. (2022). Speech understanding oppositely affects acoustic and linguistic neural tracking in a speech rate manipulation paradigm. *bioRxiv*.

Verwimp, L., Van hamme, H., and Wambacq, P. (2019). Tf-lm: Tensorflow-based language modeling toolkit. In *http://www. lrec-conf. org/proceedings/lrec2018/index. html*, pages 2968–2973. Proceedings LREC.

Weissbart, H., Kandylaki, K. D., and Reichenbach, T. (2020). Cortical tracking of surprisal during continuous speech comprehension. *Journal of cognitive neuroscience*, 32(1):155–166.

Yilmaz, E., Heuvel, H., Dijkstra, J., Velde, H., Kampstra, F., Algra, J., and van Leeuwen, D. A. (2016). Open source speech and language resources for frisian. In *Proceedings of Interspeech 2016*, pages 1536–1540. [Interspeech].