Transformer-based spatial-temporal detection of apoptotic cell death in live-cell imaging.

Alain Pulfer[1,2,&], Diego Ulisse Pizzagalli[1,3,&], Paolo Armando Gagliardi[4,&], Lucien Hinderling[4], Paul Lopez[5], Romaniya Zayats[5], Pau Carrillo-Barberà[1,6], Paola Antonello[1,4], Miguel Palomino-Segura[7], Benjamin Grädel[4], Mariaclaudia Nicolai[3], Alessandro Giusti[8], Marcus Thelen[1], Luca Maria Gambardella[8], Thomas T. Murooka[5], Olivier Pertz[4], Rolf Krause[3], Santiago Fernandez Gonzalez[1,*]

[1] Institute for Research in Biomedicine, Faculty of Biomedical Sciences, USI—Switzerland

[2] Department of Information Technology and Electrical Engineering, ETH Zurich—Switzerland

[3] Euler Institute, USI—Switzerland

[4] Institute of Cell Biology, University of Bern—Switzerland

[5] University of Manitoba, Winnipeg—Canada

[6] Instituto de Biotecnología y Biomedicina (BioTecMed), Universitat de València—Spain.

[7] Centro Nacional de Investigaciones Cardiovasculares—Spain

[8] Dalle Molle Institute for Artificial Intelligence, IDSIA—Switzerland

[&] Contributed equally

[*] Corresponding author santiago.gonzalez@irb.usi.ch

Abstract

Intravital microscopy has revolutionized live cell imaging by allowing the study of spatial-temporal cell dynamics in living animals. However, the complexity of the data generated by this technology has limited the development of effective computational tools to identify and quantify cell processes. Amongst them, apoptosis is a crucial form of regulated cell death involved in tissue homeostasis and host defense. Live-cell imaging enabled the study of apoptosis at the cellular level, enhancing our understanding of its spatial-temporal regulation. However, at present, no computational method can deliver robust detection of apoptosis in microscopy time-lapses. To overcome this limitation, we developed ADeS, a deep learning-based apoptosis detection system that employs the principle of activity recognition. We trained ADeS on extensive datasets containing more than 10,000 apoptotic instances collected both *in vitro* and *in vivo*, achieving a classification accuracy above 98% and outperforming state-of-the-art solutions. ADeS is the first method capable of detecting the location and duration of multiple apoptotic events in full microscopy time-lapses, surpassing human performance in the same task. We demonstrated the effectiveness and robustness of ADeS across various imaging modalities, cell types, and staining techniques. Finally, we employed ADeS to quantify cell survival *in vitro* and tissue damage *in vivo*, demonstrating its potential application in toxicity assays, treatment evaluation, and inflammatory dynamics. Our findings suggest that ADeS is a valuable tool for the

accurate detection and quantification of apoptosis in live-cell imaging and, in particular, intravital microscopy data, providing insights into the complex spatial-temporal regulation of this process.

Keywords: *Apoptosis; Deep Learning, Transformers, Cell death, Intravital 2-photon microscopy; Bioimaging Analysis; Artificial Intelligence; Activity Recognition; Computer Vision; Spatial-temporal Dynamics.*

1. Introduction

In the last two decades, Intravital microscopy (IVM) has revolutionized live-cell imaging by enabling microscopy acquisitions *in situ* across different organs, making it one of the most accurate model to describe cellular activities within a living host(Sumen et al. 2004). In particular, multiphoton intravital microscopy (MP-IVM) generates in-depth 3D data that encompass multiple channels for up to several hours of acquisition (x,y,z + t)(Helmchen and Denk 2005; Rocheleau and Piston 2003; Secklehner, Celso, and Carlin 2017), thus providing unprecedented insights into cellular dynamics and interactions(Pizzagalli et al. 2019). The resulting MP-IVM data stream is a complex and invaluable source of information, contributing to enhance our understanding of several fundamental processes(Beltman et al. 2009; Sumen et al. 2004).

Apoptosis is a form of regulated cell death(D'Arcy 2019; D. Tang et al. 2019) which plays a crucial role in several biological functions, including tissue homeostasis, host protection, and immune response(Opferman 2008). This process relies on the proteolytic activation of caspase-3-like effectors(Shalini et al. 2015), which yields successive morphological changes that include cell shrinkage, chromatin condensation, DNA fragmentation, membrane blebbing(Elmore 2007; Galluzzi et al. 2018; Saraste and Pulkki 2000), and finally, apoptotic bodies formation(Coleman et al. 2001). Due to its crucial role, dysregulations of apoptosis can lead to severe pathological conditions, including chronic inflammatory diseases and cancer(Fesik 2005; Hotchkiss and Nicholson 2006). Consequently, precise tools to identify and quantify apoptosis in different tissues are pivotal to gain insights on this mechanism and its implications at the organism level.

Traditional techniques to quantify apoptosis rely on cellular staining on fixed cultures and tissues(Atale et al. 2014; Kyrylkova et al. 2012; Loo 2011; Sun et al. 2008; Vermes et al. 1995) or flow cytometry(Darzynkiewicz, Galkowski, and Zhao 2008; Vermes et al. 1995). However, these methods do not allow the temporal characterization of the apoptotic process. Moreover, they potentially introduce artifacts caused by sample fixation(Schnell et al. 2012). Live-cell imaging can overcome these limitations by unraveling the dynamic aspects of apoptosis with the aid of fluorescent reporters, such as Annexin staining(Atale et al. 2014) or the activation of Caspases(Takemoto et al. 2003). However, the use of fluorescent probes *in vivo* could potentially interfere with physiological functions

or lead to cell toxicity(Jensen 2012). For these reasons, probe-free detection of apoptosis represent a
critical advancement in the field of cell death.

Computational methods could address this need by automatically detecting individual apoptotic cells
with high spatial and temporal accuracy. In this matter, deep learning (DL) and activity recognition
(AR) could provide a playground for the classification and detection of apoptosis based on
morphological features(Poppe 2010). Accordingly, recent studies showed promising results regarding
the classification of static frames(Kranich et al. 2020; Verduijn et al. 2021) or time-lapses(Mobiny et al.
2020) portraying single apopotic cells. However, none of the available methods can be applied for the
detection of apoptosis in microscopy movies depicting multiple cells. Therefore we developed ADeS,
a novel apoptosis detection system which employs a transformer DL architecture and computes the
location and duration of multiple apoptotic events in live-cell imaging. Here we show that our
architecture outperforms state-of-the-art DL techniques and efficiently detects apoptotic events in a
broad range of imaging modalities, cellular staining, and cell types.

2. Results

2.1. An *in vitro* and *in vivo* live-cell imaging data. Curated and high-quality datasets containing
numerous instances of training samples are critical for developing data-hungry methods such as
supervised DL algorithms(Adadi 2021). To this end, we generated two distinct datasets encompassing
epithelial cells (*in vitro*) and leukocytes (*in vivo*) undergoing apoptotic cell death. In addition, the two
datasets include different imaging modalities (confocal and intravital 2-photon), biological models, and
training-set dimensionalities. A meaningful difference between the datasets pertains to the staining
methods and the morphological hallmarks, which define the apoptotic process in both models. In the
in vitro model, the expression of nuclear markers allowed us to observe apoptotic features such as
chromatin condensation and nuclear shrinkage(Saraste and Pulkki 2000), whereas in the *in vivo*
model, cytoplasmic and membrane staining highlighted morphological changes such as membrane
blebbing and the formation of apoptotic bodies(Saraste and Pulkki 2000). Accordingly, we have
manually annotated these datasets based on the presence of the specific hallmarks, ensuring that
each dataset includes two class labels depicting either apoptotic or non-apoptotic cells. These two
datasets constitute the first step toward creating, testing, and validating our proposed apoptosis
detection routine.

To generate the *in vitro* dataset we used epithelial cells because, among the human tissues, they
have the highest cellular turnover driven by apoptosis(Van Der Flier and Clevers 2009). Nevertheless,
from the bioimaging perspective, the epithelium is a densely packed tissue with almost no
extracellular matrix, making it extremely challenging to analyze. As such, in epithelial research, there
is a pressing need for computational tools to identify apoptotic events automatically. To this end, we
imaged and annotated the human mammary epithelial cells expressing a nuclear fluorescent marker
(Fig.1A), obtaining 13120 apoptotic nuclei and 301630 non apoptotic nuclei image sequences (Fig.
1B-C, Supplementary 1A). Nuclear shrinkage and chromatin condensation, two of the most

prototypical hallmarks of apoptosis (Fig. 1C), formed our criteria for manual annotation. We confirmed
that non-apoptotic nuclei had constant area and chromatin density from the generated time-lapses. In
contrast, apoptotic nuclei underwent a decrease in area and an increase in chromatin condensation
(Fig. 1D). The resulting dataset captured the heterogeneity of apoptotic cells in epithelial tissue,
including early nuclear fragmentation, a rapid shift along the x and y axes, and extrusion through the z
dimension (Supplementary Fig. 1B–C). Moreover, our dataset incorporates the typical difficulties of
automatically annotating apoptotic events from live microscopy of a densely packed tissue
(Supplementary Fig. 1D) with the accumulation of apoptotic bodies (Supplementary Fig. 1E) and
across multiple microscope hardware settings (Supplementary Fig. 1F).

To generate an *in vivo* dataset, we focused on polymorphonucleated leukocytes (neutrophils and
eosinophils) that expressed a fluorescent marker. In these early immune responders, apoptosis is a
crucial process that orchestrates their disposal, consequently determining the duration of the
inflammation(Fox et al. 2010). To acquire instances of apoptotic leukocytes, we performed MP-IVM in
anesthetized mice by surgically exposing either the spleen or the popliteal lymph node (Fig. 1E-F).
The resulting time-lapses (Fig. 1G) provided 3D imaging data encompassing consecutive multi-focal
planes (3D) and multiple imaging channels. Then, from the generated MP-IVM movies, we generated
cropped sequences of fixed size that tracked apoptotic cells for the duration of their morphological
changes (59x59 pixels + time; Fig. 1H-I). This procedure was applied to 30 MP-IVM movies,
generating 120 apoptotic sequences (supplementary Fig. 1G). Furthermore, we annotated random
instances of non-apoptotic events, generating 535 cropped samples. To characterize the
heterogeneity of the movies, we manually quantified the cell number per field of view (87 ± 76), the
shortest distance between cells (21.2 µM ± 15.4), and the signal-to-noise ratio (8.9 ± 3.6;
supplementary Fig. 1 H–J). We assumed that the morphological changes associated with apoptosis
occur within defined time windows for detection purposes. Hence, we estimated the median duration
of the morphological changes corresponding to 8 frames (supplementary Fig. 1K–L, respectively). In
addition, to classify apoptotic cells within defined spatial regions, we considered them to be non-
motile. This assumption was confirmed when we found that apoptotic cells, despite having a longer
track-length due to passive transport, exhibited a speed that was not significantly different from those
of arrested cells (supplementary Fig. 1M).

2.2. ADeS, a pipeline for apoptosis detection. Detecting apoptosis in live-cell imaging is a two-step
process involving the correct detection of apoptotic cells in the movies (x,y) and the correct estimation
of the apoptotic duration (*t*). To fulfill these requirements, we designed ADeS as a set of independent
modules assigned to distinct computational tasks (Fig. 2). As an input, ADeS receives a 2D
representation of the microscopy acquisitions (Fig. 2A) obtained from the normalization of 2D raw
data or the maximum projection of 3D data(Shi et al. 2015). This processing step ensures the
standardization of the input, which might differ in bit depth or acquisition volume. After that, we employ
a selective search algorithm(Girshick 2015; Uijlings et al. 2013) to compute regions of interest (ROIs)
that might contain apoptotic cells (Fig. 2B). For each ROI at time (*t*), ADeS extracts a temporal

sequence of *n* frames ranging *from t - n*/2 to *t + n*/2 (Fig. 2C). The resulting ROI sequence is

standardized in length and passed to a DL classifier (Fig. 3), which determines whether it is apoptotic

or non-apoptotic. Finally, each apoptotic sequence is depicted as a set of bounding boxes and

associated probabilities (Fig. 2D) generated from the predicted trajectories (x, y, t, ID; Fig. 2E). From

this readout, ADeS can generate a heatmap representing the likelihood of apoptotic events

throughout a movie (Fig. 2F, left), together with a cumulative sum of the predicted cell deaths (Fig. 2F,

right).

For the classification of apoptotic sequences, we proposed a Conv-Transformer architecture (Fig. 3).

In the proposed architecture, a convolutional module extracts the spatial features of the apoptotic

cells, whereas attention-based nlocks evaluates the temporal relationship between consecutive

frames.

2.3. Training and deployment *in vitro*. As previously described, ADeS is a multiple-block pipeline,

and its application and validation to detect apoptotic cells in live-cell imaging follow two main steps:

(1) the training of the DL classifier with a target dataset and (2) its deployment on live-cell imaging

acquisitions. As opposed to *in vivo* acquisitions, *in vitro* time-lapses are more homogeneous in their

content and quality, thus representing the first dataset in order of complexity for the training of ADeS.

For this reason, we formulated the learning problem as a binary classification task that assigned non-

apoptotic sequences to the class label 0 and apoptotic sequences to the class label 1 (Supplementary

Fig. 2A). The class label 0 included instances of healthy nuclei and nuclei undergoing mitotic division

(which can resemble apoptotic events).

Successively, to validate the proposed Conv-Transformer architecture for apoptosis classification, we

compared it with the performances of a convolutional neural network (CNN), a 3DCNN, and a

convolutional long-short term memory (Conv-LSTM) network. To this end, the four models were

trained on a dataset containing 13.120 apoptotic and 13.120 non-apoptotic events, using a 0.12

validation split (Table 1). Results show that the frame accuracy of the CNN is low, possibly due to

morphological heterogeneity over consecutive frames, and therefore unsuitable for the task. By

contrast, the 3DCNN and the Conv-LSTM displayed high sequence accuracy, F1 score and AUC,

confirming that the temporal information within frames is pivotal to correctly classifying image

sequences containing apoptotic cells. Nonetheless, the proposed Conv-Transformer outperformed

both the 3DCNN and the Conv-LSTM, establishing itself as the final DL architecture at the core of

ADeS.

Successively, we deployed a preliminary trained network on control movies without apoptotic events

to collect false positives that we used to populate the class label 0, thus ensuring a systematic

decrease in the misclassification rate (Supplementary Fig. 2B). Using the latter generated dataset, we

trained the Conv-Transformer for 100 epochs using an unbalanced training set with a 1:10 ratio of

apoptotic to non apoptotic cells (Fig. 4A). After deploying the trained model on 1000 testing samples,

the confusion matrix (Fig. 4B) displayed a scant misclassification rate (2.68%), similarly distributed

between false positives (1.04%) and false negatives (1.64%). Accordingly, the receiver operating

characteristic (ROC) of the model skewed to the left (AUC = 0.99, Fig. 4C). This skew indicates a

highly favorable tradeoff between the true positive rate (TPR) and false positive rate (FPR), which the

overall predictive accuracy of 97.32% previously suggested (Fig. 4B). Altogether, these metrics

suggest an unprecedented accuracy of the DL model in the classification of apoptotic and non-

apoptotic sequences. However, they only reflect the theoretical performances of the classifier applied

to cropped sequences depicting a single cell at a time.

To validate ADeS on full-length microscopy acquisitions, we deployed it on six testing movies that

were not part of the training set. Each testing movie had been annotated manually and contained a

variable number of ground-truth apoptosis (98 ± 21) and a comparable cell density (1705 ± 124).

Moreover, all movies had identical magnification (20x), duration (21 h), and sampling rate (5 min). In

order to test ADeS on these movies, we adopted an unbiased approach and we did not hard-tune the

hyper-parameters of the model (see Material and Methods), specifying only a stringent confidence

threshold (0.995) and a temporal window based on the average duration of the nuclear hallmarks (9

frames). As a result, ADeS could predict the location and timing of the apoptotic nuclei (Fig. 4D,

Supplementary Movie 1), enabling the detection of multiple apoptoses in a densely packed field of

view (Fig. 4E–F). To quantify these performances, we compared the prediction of ADeS to the

annotated ground truths (x,y,t). By doing this, we found that the average TPR, or sensitivity, was

82.01% (ranging from 77% to 92%), while the average FPR was 5.95% (Fig. 4G). The undetected

apoptotic events were likely a consequence of the heterogeneity of nuclear fragmentation, which can

vastly differ in signal intensity, size, focal plane, and duration (Supplementary Fig.1). Nonetheless,

hard tuning the model could further increase the sensitivity without additional training data, such as by

adjusting the temporal interval or by lowering the confidence threshold. With respect to the false

positives, most were mitotic cells, due to their morphological similarities with aoptotic nuclei.

Nevertheless, the FPR was contained, translating into a new false positive every 4 frames (or 20

minutes of acquisition). This rate confirmed that ADeS is overall robust, especially in light of movies

depicting 1700 cells per frame.

Concerning the spatial-temporal dynamics, the apoptotic count over time highlighted a tight

relationship between ground truth apoptosis and correct detections of ADeS (Fig. 4H). Accordingly,

the two curves were divergent but highly correlative (Pearson r = 0.998), proving that ADeS can

successfully capture cell death dynamics. A 2D scatterplot (x, y, t = radius; Fig. 4I) visually depicted

the spatial-temporal proximity between ADeS and the ground truth, indicating overlap between the

two scatter populations. Nearest neighbor (NN) analysis further captureed this relationship; the

average distance between all ADeS predictions (true positives + false positives) and the NN in the

ground truth was 30 pixels. In contrast, randomly generated predictions had a ground truth NN within

a 52-pixel radius (Fig. 4J). Considering instead the true positives only, we observed that they were in

close spatial proximity to the ground truth, with most predictions falling within a 20-pixel radius (Fig.

4K). The difference between the predicted timing of apoptosis and the one annotated in the ground
truth was also slight, with an average discard of 3.46 frames (Fig. 4L). Interestingly, ADeS showed a
bias toward late detections, which is explained considering that operators annotated the beginning of
the apoptosis, whereas ADeS learned to detect nuclear disruption, occurring at the end of the
process. Altogether, these quantifications indicate that ADeS detects apoptotic nuclei with high spatial
and temporal accuracy, establishing a novel comparative baseline for this task.

2.4. 3D rotation of the *in vivo* dataset. Upon the successful application of ADeS *in vitro*, the next
step in complexity was detecting apoptosis *in vivo* time lapses. The latter is inherently more
challenging due to different factors, including high background signal, autofluorescence, and the
presence of collagen(Pizzagalli et al. 2018), among others. For this purpose, we re-trained ADeS
using the *in vivo* data described in Figure 1. However, one of the main limitations of supervised DL is
the need for large datasets, and the finite number of MP-IVM acquisitions and apoptotic instances
represented a bottleneck for the training of ADeS. To overcome this limitation, we implemented a
custom data augmentation strategy that exploits 3D volumetric rotations, as previously performed in
other studies (Xu, Li, and Zhu 2020; Zhuang et al. 2019). Accordingly, each 3D apoptotic sequence
underwent multiple spatial rotations and was successively projected in 2D (Fig. 5A). This procedure
enabled us to increase the dataset of a 100 fold factor without introducing imaging artifacts, as each
volume rotation was a physiological representation of the cell (Fig. 5B).

2.5. Training and deployment *in vivo*. To train ADeS using the latter rotated *in vivo* dataset, we
defined a binary classification task in which ROIs containing apoptotic cells were assigned to the class
label 1. In contrast, all remaining ROIs, including healthy cells and background elements, were
assigned to the class label 0 (Supplementary Fig. 3A). Subsequently, we trained the DL classifier for
200 epochs. Finally, we performed 5-fold cross-validation according to the ID of the movies (Fig. 6A).
The resulting confusion matrix demonstrated a classification accuracy of 97.80% and a 2.20%
missclassification rate that is primarily due to type II error (1.80% false negatives) (Fig. 6B).
Analogous to the tests *in vitro*, classification *in vivo* proved highly effective in predicting apoptotic and
non-apoptotic instances. The ROC of the model, which indicated high sensitivity and a low FPR,
supported this favorable result (Fig. 6C).

We then benchmarked ADeS in the detection task performed on a set of 23 MP-IVM acquisitions of
immune cells undergoing apoptosis. Unlike *in vitro* settings, *in vivo* acquisitions displayed high
variability in cell number, auto-fluorescence, signal intensity, and noise levels (Supplementary Fig.
3B). Still, ADeS correctly predicted the location and timing of cells undergoing apoptosis (Fig. 6H,
Supplementary Movie 2), indicating its robustness to increasingly populated fields of view
(Supplementary Fig. 3C). In addition, we successfully applied the pipeline to neutrophils imaged in the
lymph node (Fig. 6D) and eosinophils in the spleen (Fig. 6E). By comparing ADeS predictions with the
annotated ground truths, we found that our pipeline detected apoptotic events with a TPR of 81.3%
and an FPR of 3.65% (Fig. 6F). The detections, provided in the form of bounding boxes and
trajectories, indicated the coordinates and duration of the events. Hence, to measure how close they

were to the annotated trajectories, we employed the tracking accuracy metric (TRA), a compound
measure that evaluates the similarities between predicted and ground truth trajectories. The average
TRA was above 0.9, indicating the high fidelity of the trajectories predicted by ADeS (Fig. 6G).

Next, we compared ADeS to human annotation performed by three operators on five testing movies.
As a result, ADeS displayed an upward trend of the TPR and a downward trend of the FPR. However,
we found no significant difference in the TPR and FPR (Fig. 6H). Regardless, ADeS performances
appeared to be distributed across two distinct groups: a predominant group with an average sensitivity
of 100% (> 75% range) and a smaller group with an average sensitivity of 53% (41-75% range, Fig.
6H). To understand this discrepancy, we applied hierarchical clustering to the testing videos according
to their imaging properties and biological content (Fig. 6I), thus generating two major dendrograms.
The first dendrogram mostly contained videos with reduced sensitivity (yellow) and was defined by a
high cell number, high noise levels, short cell distance, and a saturated and fluctuating image signal.
Most notably, the cell number played a crucial role in overall performance, as reflected in the fact that
an increment of this parameter resulted in a pronounced decrease in the TPR and a moderate
increase in the FPR (Fig. 6J). Incidentally, the positive predictive value (PPV) was significantly lower
in videos with poor signal-to-noise ratio (SNR) and, although not statistically significant, the PPV was
lower when the signal standard deviation was higher (Fig. 6K, Supplementary Movie 3). As similar
findings were observed *in vitro* (Supplementary Fig. 4), we hypothesized that the quality of a movie
predicts ADeS performance. Hence, we combined the parameters highlighted by the clustering
analysis (Fig. 6I) into a single score ranging from zero to one (one indicating the highest and ideal
score) and, in doing so, found there to be a weak correlation between the video quality and the
sensitivity of ADeS (Fig. 6L). However, this trend was evident only when we considered videos with
suboptimal sensitivity; indeed, in these cases, we found a strong correlation (0.72), confirming that the
video quality partially explains the observed performances (Fig. 6M).

Finally, we evaluated how the biological variability *in vivo* could affect the readout of ADeS, defining
nine distinct biological categories, including apoptotic cells, healthy cells, and background elements.
For all biological categories, the classification accuracy was above 80%, except for overlapping cells
and cells with high membrane plasticity (Supplementary Fig. 3D).

2.6. Comparison with the state-of-the-art. To compare the performance of ADeS with other state-
of-the-art algorithms for cell death quantification, we conducted a comprehensive literature review. For
each study, we reported the attained classification accuracy, the experimental setup, the architecture
of the classifier, the capability of detecting cell death events in movies, and the number of cell deaths
in the training set (Table 2). Initial results indicate that ADeS achieved the highest classification
accuracy, but a direct comparison in terms of accuracy is not meaningful due to the differences in
datasets, including distinct cell types, different types of cell death, and varying dataset sizes. For a
more appropriate benchmark, we refer to Table 1, which shows that our classifier outperformed the
baseline re-implementations of the main classifiers used in other studies.

From Table 2, we observe that ADeS is the only algorithm for cell death quantification that has been applied *in vivo*. Additionally, only ADeS and the study by Vicar and colleagues(Vicar et al. 2020) effectively detected apoptotic cells in fully uncropped microscopy movies, which is a significant achievement given the computational challenge associated with the task. However, Vicary and colleagues relied on the temporal analysis of cell trajectories, while ADeS used vision-based methods to directly analyze consecutive frames of a movie. As a result, ADeS offers a comprehensive and pioneering pipeline for effectively applying vision-based classifiers to detect cell death in imaging time-lapses.

2.7. Applications for toxicity assay *in vitro*. A common application of cell death staining is the evaluation of the toxicity associated with different compounds(Atale et al. 2014; Schmid, Uittenbogaart, and Jamieson 2007) or the efficacy of an apoptotic-inducing treatment. Here, we show that ADeS has analogous purposes and can effectively quantify the toxicity of different compounds *in vitro*. For this application, we grew epithelial cells *in vitro*, treating them with PBS and three increasing concentrations of doxorubicin, a chemotherapeutic drug that elicits apoptosis in the epithelium(Eom et al. 2005). Epithelial cells were seeded with the same density of cells per well, and all four conditions had the same confluence before the treatment. However, at 24 h. post-acquisition, the number of survivor cells was inversely proportional to the doxorubicin concentration (Fig. 7A). We confirmed this trend using ADeS (Supplementary Movies 4–7), which measured the lowest mortality after 24 h. in PBS (62 cells), followed by doxorubicin concentrations of 1.25 µM (95 cells), 2.50 µM (167 cells), and 5.00 µM (289 cells). Moreover, ADeS predicted distinct pharmacodynamics (Fig. 7B), which can define the drug concentration and experimental duration required to reach a specific effect in the apoptotic count. To this end, each time point in Figure 7B also defines a dose-response relationship. Here we provide two dose-responses curves at 5 h. and 24 h. post-treatment, showing different pharmacodynamics (EC50 5h = 2.35, Hill slope 5h = 3.81, EC50 24h = 4.47, Hill slope 24h = 1.93, Fig. 7C–D). Notably, the fit can project the dose-responses for higher drug concentrations, predicting the maximum effect size at a given time. For instance, at 24 h. post treatment, a 10 µM titration attains 86% of the maximum effect (456 apoptotic cells), whereas a further increase in the concentration of the drug leads only to a moderate increase of the toxicity (Fig. 7E). We argue that this approach helps to maximize the effect of a drug on a designated target, while minimizing collateral damage done to non-target cells. For instance, in chemotherapies employing doxorubicin, apoptosis of epithelial cells is an undesired effect. Therefore, researchers can select a titration of the drug and a duration of the treatment that does not affect the epithelium yet still positively affects the tumor. Finally, we also demonstrated the reproducibility of the toxicity assay by targeting another cell type (T-cells) treated with a different apoptotic inducer (staurosporine, Supplementary Fig. 5).

2.8. Measurement of tissue dynamics *in vivo*. To test the application of ADeS in an *in vivo* setting, we applied it to study the response of bystander cells following apoptotic events in the lymph nodes of mice treated with an influenza vaccine. We computed the spatial and temporal coordinates of a neutrophil undergoing apoptosis (Fig. 8A), which, combined with the tracks of neighboring cells,

allowed us to characterize cellular response patterns following the apoptotic event. Among other
parameters, we observed a sharp decrease in the distance between the neighboring cells and the
apoptotic centroid (Fig. 8B) in addition to a pronounced increase in the instantaneous speed of the
cells (Fig. 8C).

Successively, we evaluated the detection of apoptotic cells following laser ablation in the spleen of an
anesthetized mouse (Fig. 8D). Previous research has employed this method to study immune cell
responses to tissue damage(Uderhardt et al. 2019). The insult caused prompt recruitment of
neutrophils, leading to the formation of a local swarm (Fig. 8E, left). After that, the neutrophils within
the swarm underwent apoptotic body formation in a coordinated manner (Fig. 8E, right). To quantify
this event, we processed the generated time-lapse with ADeS, resulting in a probability map of
apoptotic events throughout the acquisition (x,y,t,p; Fig. 8F). Accordingly, the location with the highest
probability corresponded to the area damaged by the laser, while the visual representation of the
probability map enabled us to infer the morphology and location of the swarm. This result
demonstrates the potential application of ADeS in digital pathology, showing how the distribution of
apoptotic events throughout the tissue can identify areas enriched by cell death events.

3. Discussion

Automated bio-image analysis obviates the need for manual annotation and avoids bias introduced by
the researcher. In this regard, recent studies showed the promising usage of DL to classify static
images(Jimenez-Carretero et al. 2018; Kranich et al. 2020; Verduijn et al. 2021) or time-lapses
containing single apoptotic cells(Mobiny et al. 2020). However, these approaches are unsuitable for
microscopy time-lapses because they do not address two fundamental questions: the location, over
the whole field of view, at which an event occurs, and its duration. These questions define a detection
task(Zhao et al. 2019) in space and time, which has a computational cost that can rapidly grow with
the size and lenght of a movie. Moreover, live-cell imaging data present specific challenges which
further increase the difficulty of detection routines, including densely packed fields of view,
autofluorescence, and imaging artifacts(Pizzagalli et al. 2018).

Consequently, computational tools to effectively detect apoptotic events in live-cell imaging remained
unavailable. Thus, we created an apoptosis detection pipeline that could address the abovementioned
challenges *in vitro* and *in vivo*. In this regard, ADeS represents a crucial bridge between AR and
bioimaging analysis, being the first apoptosis detection routine with demonstrated applicability to full
microcopy time-lapses. In addition, we presented two comprehensive and curated datasets
encompassing multiple cell types, fluorescent labels, and imaging techniques to encourage
reproducibility and foster the development of apoptosis detection routines.

In human activity recognition benchmark, 3DCNNs(Vrskova et al. 2022), two-streams networks(Ye et
al. 2019), and RNNs(Mohd Noor, Tan, and Ab Wahab 2022) have proved to score the highest
accuracy on most kinetic datasets(Ullah et al. 2021). However, in most studies for the classification of

apoptosis, authors unanimely employed RNNs such as Conv-LSTMs. This choice, although produced
valid results, is not necessarily optimal for the task. In this regard, Ullah and colleagues highlighted
that the performances of different DL architectures are highly dependent on the AR dataset(Ullah et
al. 2021). Therefore, selecting the most suitable one is only possible after an extensive benchmark. In
our comparison, we demonstrated for the first time that attention-based networks are suitable for the
classification and detection of apoptotic events. Accordingly, our Conv-Transformer network
outperformed DL architectures previously employed in other studies, including 3DCNNs and RNNs.
This result established a landmark in the application of attention-based networks in AR for live-cell
imaging. Moreover, it suggests the possible benefits of employing transformers for the classification of
different biological activities other than cell death.

Similar to most diagnostic tools, ADeS displayed a tradeoff between sensitivity (TPR) and specificity
(1 - FPR), which is a known challenge in binary classification(Pang et al. 2021). This tradeoff can be
attributed to the fact that apoptosis is rare in normal physiological conditions, leading to a high degree
of class imbalance during training. As a result, the choice of the training set had a significant impact
on the performances of ADeS. For instance, we highlighted the importance of a training and validation
set that included challenges related to real live-cell imaging acquisitions, such as overlapping cells
and low signal-to-noise samples. Including these challenges instances enabled ADeS to attain low
misclassification rate and robust real-life performanes. Nonetheless, we observed residual
misclassifications due to shared similarities between healthy and apoptotic cells. For instance, *in vitro*
mitotic divisions could mislead the detection of apoptotic nuclei, while *in vivo*, overlapping cells were
sometimes mistaken for apoptotic cells. Therefore, to effectively address these challenges, it is crucial
to implement strategies to increase the representativeness of the dataset, such as integrating multiple
data sources and data augmentation techniques.

From a biological perspective, ADeS has multiple applications in fundamental and clinical research.
Among other advantages, it can provide insights into pivotal cell death mechanisms, monitor the
therapies used to modulate apoptosis in various diseases and characterize the toxicity of different
compounds. In this regard, ADeS readout is analogous to standard fluorescent probes for apoptosis
detection, with the advantage that it can be applied directly to nuclear or cytoplasmic staining without
the need of additional fluorescent reporters. Therefore, ADeS avoids using any additional acquisition
channel, which can be used for multiplexing purposes. Moreover, common probes(Atale et al. 2014;
Kyrylkova et al. 2012; Loo 2011; Sun et al. 2008; Vermes et al. 1995) flag early apoptosis stages,
activated up to several minutes before the point at which morphological changes in the cell(Green
2005; Takemoto et al. 2003); meanwhile, these cells can reverse the apoptotic process (Geske et al.
2001; Masri and Chandrashekhar 2008; H. L. Tang et al. 2009). By contrast, ADeS indicates the exact
instant of cell disruption, thus adding specificity to the spatial-temporal dimension. For these reasons,
we suggest that ADeS can complement the information provided by classic apoptotic biomarkers,
which will prove advantageous in experimental assays where the temporal resolution delivers more
information than the sole apoptotic count. Moreover, ADeS can be usefully applied in processing high-
throughput live-cell imaging, minimizing annotation time and research bias.

Finally, in tissue dynamics the spatial-temporal activity of cells can reveal connections between
signaling pathways and the fate decision of individual cells, such as mitosis or apoptosis(Gagliardi et
al. 2021). These intricate systems can display complex dynamics, which can be better comprehended
incorporating spatial and temporal coordinates provided by ADeS. Consequently, we propose that
integrating these spatial-temporal characteristics with experimental observations could lay the
groundwork for understanding the mechanism governing complex signaling pathways. Furthermore,
we contend that this information has the potential to facilitate the development of predictive models,
establishing a correlation between specific cell death dynamics and the underlying stimuli. This, in
turn, could serve as the foundation for innovative diagnostic tools capable of inferring the cause of cell
death.

(Fesik 2005; Hotchkiss and Nicholson 2006)(*15*, *16*)[15], [16] [15,16]In conclusion, ADeS constitutes a
novel solution for apoptosis detection that combines state-of-the-art microscopy and DL. Its
successful implementation represents a step towards the general application of AR methods to live-
cell imaging. By bridging these two distinct fields, ADeS leverages succesfully the benefits of
automated routines. Further work could expand the proposed pipeline to encompass diverse cell
populations, various types of cell death, and potentially broader cellular activities.

4. Material and methods

4.1. MCF10A cell line and image acquisition. The normal-like mammary epithelial MCF10A cells
(provided by Joan Brugge(Debnath, Muthuswamy, and Brugge 2003)), stably expressing the nuclear
marker, were generated as previously described(Gagliardi et al. 2021). Briefly, the nuclear marker
H2B-miRFP703, provided by Vladislav Verkhusha (Addgene plasmid # 80001)(Shcherbakova et al.
2016), was subcloned in the PiggyBac plasmid pPBbSr2-MCS. After cotransfection with the
transposase plasmid(Yusa et al. 2011), cells were selected with 5 µg/ml Blasticidin and subcloned.
For time-lapse imaging, the cells were seeded on 5 µg/ml fibronectin (PanReac AppliChem) coated
1.5 glass-bottom 24 well plates (Cellvis) at 1×10^5 cells/well density. After 48 hours, when the optical
density was reached, the confluent cell monolayer was acquired every 1 or 5 minutes for several
hours with a Nikon Eclipse Ti inverted epifluorescence microscope with 640nm LED light source,
ET705/72m emission filter and a Plan Apo air 203 (NA 0.8) or a Plan Apo air 403 (NA 0.9) objectives.
The collection of biological experiments used in this study includes different stimulation of apoptosis,
such as growth factors, serum starvation and doxorubicin at various concentrations.

4.2. Apoptosis induction of MCF10A cells with doxorubicin. Normal-like mammary epithelial
MCF10A cells were grown in 24 well glass coated with fibronectin with a seeding of 1×10^5 cells/well.
After two days, cells were starved for three hours and treated with doxorubicin at 1.25, 2.50, and 5.00
µM concentrations.

4.3. Mice. Prior to imaging, mice were anesthetized with a cocktail of Ketamine (100 mg/Kg) and
Xylazine (10 mg/Kg) as previously described(Sumen et al. 2004). All animals were maintained in
specific pathogen-free facilities at the Institute for Research in Biomedicine (Bellinzona, CH). All the

experiments were performed according to the regulations of the local authorities and approved by the
Swiss Federal Veterinary Office.
473
4.6. Intravital Two-Photon Microscopy. Surgery in the popliteal lymph node was performed as
previously reported(Miller et al. 2004). The exposed organs were imaged on a custom up-right two-
photon microscope (TrimScope, LaVision BioTec). Probe excitation and tissue second-harmonic
generation (SHG) were achieved with two Ti:sapphire lasers (Chamaleon Ultra I, Chamaleon Ultra II,
Coherent) and an optical oscillator that emits in the 1,010–1,340 nm range (Chamaleon Compact
OPO, Coherent) and has an output wavelength between 690–1,080 nm.
480
481 **4.5. Neutrophil isolation from mouse bone marrow.** Bone marrow samples were extracted via
482 flushing with PBS from the long bones of UBC-GFP mice (https://www.jax.org/strain/004353). Then,
483 the bone marrow was filtered through a 40um strainer and resuspended in PBS. Primary bone
484 marrow neutrophils were isolated with Ficoll gradient and resuspended in PBS.
485
4.6. T-cell culture in a 3D collagen matrix. Human CD4+ T cells were isolated from the PBMC
fraction of healthy donors obtained from NetCAD (Canadian Blood Services). Cell purity was above
95%. Naïve CD4+ T cells were activated by adding Dynabeads coated with anti-human CD3e/CD28
antibody (1:1 bead:cell ratio, Life Technologies Cat #11131D) in RPMI1640 supplemented with 10%
FBS (VWR Seradigm Cat #1500-500), 2 mM GlutaMAX (Gibco Cat #3050-061), 1mM sodium
pyruvate (Corning Cat #25-000-CI) and 10mM HEPES (Sigma-Aldrich Cat #H4034). After two days,
beads were removed and cells were cultured for another 4-6 days in a medium containing 50 IU/mL
human rIL-2 (Biotechne Cat #202-IL-500), keeping cell density at 2×10^5 cells/mL. Cells were used for
all experiments between days 6 to 8. All work with human blood has been approved by the University
of Manitoba Biomedical Research Ethics Board (BREB).
4.7. Apoptosis live-cell imaging of T-cells in 3D collagen chambers. T cells were labeled at day
6-8 using CMAC (10µM) cell tracker dye (Invitrogen) and glass slide chambers were constructed as
previously described(Lopez et al. 2019, 2022). Briefly, 2×10^6 cells were mixed in 270µL of bovine
collagen (Advanced Biomatrix cat #5005-100ML) at a final concentration of 1.7 mg/mL. Collagen
chambers were solidified for 45 minutes at 37°C / 5% CO2 and placed onto a custom-made heating
platform attached to a temperature control apparatus (Werner Instruments). For the induction of
apoptosis, 1µM of Staurosporine (Sigma Cat #569397-100UG) and 800ng of TNF-a (Biolegend Cat
#570104) in 100µL RPMI were added on top of the solidified collagen. Cells were imaged as soon as
the addition of apoptosis inducers using a multiphoton microscope with a Ti:sapphire laser (Coherent),
tuned to 800 nm for optimized excitation of CMAC. Stacks of 13 optical sections (512 x 512 pixels)
with 4 mm z-spacing were acquired every 15 seconds to provide imaging volumes of 44mm in depth
(with a total time of 60 - 120 minutes). Emitted light was detected through 460 / 50nm, 525 / 70 nm,
and 595 / 50 nm dichroic filters with non-descanned detectors. All images were acquired using the 20
x 1.0 N.A. Olympus objective lens (XLUMPLFLN; 2.0mm WD).

4.8. Data Processing and Image Analysis. The raw video data, composed by uint8 or uint16 TIFFs, were stored as HDF5 files. No video pre-processing was applied to the raw data before image analysis. Cell detection, tracking, and volumetric reconstruction of microscopy videos were performed using Imaris (Oxford Instruments, v9.7.2). The resulting data were further analyzed with custom Matlab and Python scripts (see code availability section).

4.9. Apoptosis annotation of epithelial MCf10A cells *in vitro*. We manually annotated apoptotic events of MCF10A cells by visual inspection of the movies. The annotation was done by observing the morphological changes associated with apoptosis (e.g. nuclear shrinkage, chromatin condensation, epithelial extrusion, nuclear fragmentation) across multiple consecutive frames. Using a custom Fiji(Schindelin et al. 2012) macro, we automatically stored x and y centroids of the apoptotic nucleus. The time t of each apoptotic annotation was defined as the beginning of nuclear shrinkage.

4.10. Generation of the *in vitro* training dataset. The 16-bit raw movies were min-max scaled to the 0.001 and 0.999 quantiles and downsampled to 8-bit resolution. Using the database of manually labeled coordinates of apoptotic events (x,y,t), we extracted crops with 59 x 59 pixels resolution (2x scaling for the field of view acquired with the 20x objective). Seven time-steps of the same location were extracted, with linear spacing from -10 minutes to +50 minutes relative to the apoptosis annotation. This time frame was chosen to capture the cell before the onset of apoptosis, and the morphological changes associated with apoptosis (nuclear shrinkage, decay into apoptotic bodies, extrusion from epithelium). The resulting image cube has dimensions of 59 x 59 x 7. To create the training data for the non-apoptotic class, we excluded areas with an annotated apoptotic event with a safety margin from the movies. From the remaining regions without apoptoses, we extracted image cubes from cells detected with StarDist(Jacquemet et al. 2020) and from random locations. The random crops also included debris, apoptotic bodies from earlier apoptotic events, empty regions, and out-of-focus nuclei.

4.11. Apoptosis annotation of leukocyte cells *in vivo*. Three operators independently annotated the videos based on selected morphological criteria. To label apoptotic cells, the annotators considered only the sequences of cells that displayed membrane blebbing followed by apoptotic bodies formation and cell disruption (Fig. 2B). For each frame in the apoptotic sequence, the operators placed a centroid at the center of the cell with the Imaris "Spots" function, generating an apoptotic track. Successively, ground truth tracks were generated according to a majority voting system, and 3D volume reconstruction was performed on ground truth cells using the Imaris "Surface" function. Nearby non-apoptotic cells were also tracked. In addition, other non-apoptotic events were automatically sub-sampled from regions without apoptotic cells.

4.12. 3D rotation of the *in vivo* annotations. *In vivo* annotations presented a class unbalance in favor of non-apoptotic cells, with a relative few apoptotic instances. Hence, to compensate for this bias, we produced several representations of the raw data by interpolating the raw image stacks in 3D

550 volumes and rotating them in randomly sampled directions, with rotational degrees between 0° and
551 45°. After each manipulation, the rotated volume underwent flattening by maximum projection and
552 symmetric padding to preserve the original dimension. The 2D images were successively resized and
553 cropped to match the 59 x 59 pixels input of the classifier. Finally, the training sequences were saved
554 as uint8 gray-scale TIFFs files.
555
4.13. Generation of the *in vitro* and *in vivo* training datasets. To detect apoptotic cells in
microscopy acquisitions, we defined a 2D binary classification task in which apoptotic events are
labeled with class 1, while non-apoptotic events belonged to the class label 0. The resulting
unprocessed data consisted of frame sequences composed of 3D crops. The content of the class
label 0 in vitro included: healthy nuclei, background, cell debris and mitotic cells. The content of the
class label 0 *in vivo* included: motile cells, arrested cells, highly deformed cells, overlapping cells, cell
debris or blebs, empty background, noisy background, and collagen.
563
4.14. Data augmentation and data loader. Given the varying length of the training sequences
contained in the TIFFs, upon training, we used a custom data loader that uniformly samples the input
data and produces sequences with a fixed number of frames. The fixed number of frames was set to
5, corresponding to the frame-length of the shortest apoptotic sequence. During training, each sample
underwent horizontal shift, vertical shift, zoom magnification, rotation, and flipping. All data
augmentations were performed in python using the Keras library.
570
4.15. Deep learning architecture. As a deep learning classifier, we employed a custom architecture
relying on time-distributed convolutional layers stacked on top of a transformer module (Conv-
Transformer). The input size consists of 5 single-channel images with 59x59 pixel size. The
convolutional network has three layers of size 64, 128, and 256 length. Each layer has a 3x3 kernel,
followed by Relu activation, batch normalization, and a dropout set to 0.3. The inclusion of padding
preserves the dimension of the input, while 2D max-pooling is at the end of each convolutional block.
After 2D max pooling, the output is passed to a transformer module counting 6 attention heads, and
successively to a fully connected decision layer. The fully connected network has four layers with
1024, 512,128, and 64 nodes, each one followed by Relu activation and a 0.3 dropout layer. The last
layer is a softmax activation, which predicts a decision between the two classes.
581
582 **4.16. Training and hyper-parameters.** Our model was trained in TensorFlow with Adam optimizer,
583 using binary cross-entropy loss and an initial learning rate of 0.0001. The optimal mini-batch size was
584 32, and the number of training epochs was 200. In training mode, we set a checkpoint to save the
585 model with the best accuracy on the validation dataset, and a checkpoint for early stopping with
586 patience set to 15 epochs. In addition, the learning rate decreased when attending a plateau.
587
4.17. ADeS deployment For the deployment of the classifier on microscopy videos, we generative
region proposals using the selective search algorithm, obtaining a set of ROIs for each candidate

frame of the input movie. For each ROI computed by the region proposal at time t, a temporal
sequence is cropped around t and classified with the Conv-Transformer. The resulting bounding
boxes are filtered according to a probability threshold and processed with the non-maxima
suppression utils from Pytorch. Consecutive bounding boxes classified as apoptotic are connected
using a custom multi-object tracking algorithm based on Euclidean distance. The generated
trajectories are filtered by discarding those with less than two objects.

4.18. Default and user-defined parameters. ROIs detected with the region proposal are filtered
according to their size, discarding the ones with edges below 20 pixels and above 40 pixels.
Furthermore, a threshold on intensity is applied to exclude uint8 patches with an average brightness
below 40. Upon classification, a temporal window corresponding to the expected duration of the
apoptotic event is set by the user (9 frames by default). This temporal window is subsampled to match
the number of input frame of the classifier (5). The filtering of the predictions depends on a user-
specified threshold, which by default corresponds to 0.95 *in vivo* and 0.995 *in vitro*. Non-maxima
suppression is based on the overlapping area between bounding boxes, set to 0.1 by default. The
centroid tracking has the following adjustable parameters: gap and distance threshold. The "gap"
parameter, set to three frames, specifies for how long a centroid can disappear without being
attributed a new ID upon reappearance. A threshold on the distance, set by default to 10 pixels,
allows the connection of centroids within the specified radius. All the reported quantifications had
default parameters.

4.19. Statistical analyses. Statistical comparisons and plotting were performed using GraphPad
Prism 8 (Graphpad, La Jolla, USA). All statistical tests were performed using non-parametric Kruskal-
Wallis test or Mann-Witney test For significance, p value is represented as * when $p < 0.05$, ** when p
< 0.005 and *** when $p < 0.0005$.

614 5. Data availability

615 Imaging data: https://zenodo.org/uploads/10260643
616 Code: https://github.com/mariaclaudianicolai/ADeS

618 5. Aknowledgements

619 We would like to thank Dr. Coral Garcia (IQS, Barcelona, Spain) for the support in generating
620 graphical content. Moreover, we would like to aknowledge Gabriele Abbate (IDSIA, Lugano,
621 Switzerland) for his help during an early implementation of the DL classifier.

623 5.1. Funding

Suisse National Science Foundation grant 176124 (AP, DU, MP, SG)
Swiss Cancer League grant KLS-4867-08-2019, Suisse National Science Foundation grant Div3
310030_185376 and IZKSZ3_62195, Uniscientia Foundation (PG, LH, OP)
SystemsX.ch grant iPhD2013124 (DU, RK, SG)

Novartis Foundation for medical-biological Research, The Helmut Horten Foundation, SwissCancer

League grant KFS-4223-08-2017-R (PA, MT)

Canadian Institute for Health Research (CIHR) Project grants PJT-155951 (RZ, PL, TM)

NCCR Robotics program of the Swiss National Science Foundation (AG, LG)

Biolink grant 189699 (DU, PC, SG)

634   5.2. Authors contributions

Conceptualization: SG, DU, AP

Methodology: AP, DU

Experiments: PG, PA, MP, RZ, PL

Data annotation: PG, AP, LH, DU, PC

Data analysis and visualization: AP, LH, AG

Figures: AP, PG, LH

Testing and validation: AP, LH, AG

Supervision: SG, DU, RK, LG, OP, TM, MT

Writing—original draft: AP, PC, DU, PG

Writing—review & editing: AP, SG

646   5.3. Competing interests

647   Authors declare that they have no competing interest.

648
649

651   6. Bibliography

Adadi, Amina. 2021. "A Survey on Data-efficient Algorithms in Big Data Era." *Journal of Big Data* 8(1).

Atale, N., S. Gupta, U. C.S. Yadav, and V. Rani. 2014. "Cell-Death Assessment by Fluorescent and

Nonfluorescent Cytosolic and Nuclear Staining Techniques." *Journal of Microscopy* 255(1): 7–19.

Beltman, Joost B et al. 2009. "Analysing Immune Cell Migration." *Nature reviews. Immunology* 9(11): 789–98.

Coleman, Mathew L. et al. 2001. "Membrane Blebbing during Apoptosis Results from Caspase-Mediated

Activation of ROCK I." *Nature Cell Biology* 3(4).

D'Arcy, Mark S. 2019. "Cell Death: A Review of the Major Forms of Apoptosis, Necrosis and Autophagy." *Cell*

Biology International 43(6).

Damián La Greca, Alejandro et al. 2021. "Celldeath: A Tool for Detection of Cell Death in Transmitted Light

Microscopy Images by Deep Learning-Based Visual Recognition." *PLoS ONE* 16(6 June).

Darzynkiewicz, Zbigniew, Dariusz Galkowski, and Hong Zhao. 2008. "Analysis of Apoptosis by Cytometry Using

TUNEL Assay." *Methods* 44(3).

Debnath, Jayanta, Senthil K. Muthuswamy, and Joan S. Brugge. 2003. "Morphogenesis and Oncogenesis of

MCF-10A Mammary Epithelial Acini Grown in Three-Dimensional Basement Membrane Cultures." *Methods*

30(3).

Elmore, Susan. 2007. "Apoptosis: A Review of Programmed Cell Death." *Toxicologic Pathology.*

Eom, Young Woo et al. 2005. "Two Distinct Modes of Cell Death Induced by Doxorubicin: Apoptosis and Cell

Death through Mitotic Catastrophe Accompanied by Senescence-like Phenotype." *Oncogene* 24(30).

Fesik, Stephen W. 2005. "Promoting Apoptosis as a Strategy for Cancer Drug Discovery." *Nature Reviews Cancer* 5(11): 876–85.

Van Der Flier, Laurens G., and Hans Clevers. 2009. "Stem Cells, Self-Renewal, and Differentiation in the Intestinal Epithelium." *Annual Review of Physiology* 71.

Fox, Sarah et al. 2010. "Neutrophil Apoptosis: Relevance to the Innate Immune Response and Inflammatory Disease." *Journal of Innate Immunity* 2(3): 216–27.

Gagliardi, Paolo Armando et al. 2021. "Collective ERK/Akt Activity Waves Orchestrate Epithelial Homeostasis by Driving Apoptosis-Induced Survival." *Developmental Cell* 56(12).

Galluzzi, Lorenzo et al. 2018. "Molecular Mechanisms of Cell Death: Recommendations of the Nomenclature Committee on Cell Death 2018." *Cell Death and Differentiation* 25(3).

Geske, F. J., R. Lieberman, R. Strange, and L. E. Gerschenson. 2001. "Early Stages of P53-Induced Apoptosis Are Reversible." *Cell Death and Differentiation* 8(2).

Girshick, Ross. 2015. "Fast R-CNN." In *Proceedings of the IEEE International Conference on Computer Vision*,.

Green, Douglas R. 2005. "Apoptotic Pathways: Ten Minutes to Dead." *Cell* 121(5).

Helmchen, Fritjof, and Winfried Denk. 2005. "Deep Tissue Two-Photon Microscopy." *Nature Methods* 2(12): 932–40.

Hotchkiss, Richard S., and Donald W. Nicholson. 2006. "Apoptosis and Caspases Regulate Death and Inflammation in Sepsis." *Nature Reviews Immunology* 6(11): 813–22.

Jacquemet, Guillaume et al. 2020. "Automated Cell Tracking Using StarDist and TrackMate." *F1000Research* 9.

Jensen, Ellen C. 2012. "Use of Fluorescent Probes: Their Effect on Cell Biology and Limitations." *Anatomical Record* 295(12).

Jimenez-Carretero, Daniel et al. 2018. "Tox_(R)CNN: Deep Learning-Based Nuclei Profiling Tool for Drug Toxicity Screening." *PLoS Computational Biology* 14(11).

Jin, Jenny et al. 2022. "Machine Learning Classifies Ferroptosis and Apoptosis Cell Death Modalities with TfR1 Immunostaining." *ACS Chemical Biology* 17(3).

Kabir, Md Alamgir et al. 2022. "Automated Detection of Apoptotic versus Nonapoptotic Cell Death Using Label-Free Computational Microscopy." *Journal of Biophotonics* 15(4).

Kranich, Jan et al. 2020. "In Vivo Identification of Apoptotic and Extracellular Vesicle-Bound Live Cells Using Image-Based Deep Learning." *Journal of Extracellular Vesicles* 9(1). https://doi.org/10.1080/20013078.2020.1792683.

Kyrylkova, Kateryna, Sergiy Kyryachenko, Mark Leid, and Chrissa Kioussi. 2012. "Detection of Apoptosis by TUNEL Assay." *Methods in Molecular Biology* 887.

Loo, Deryk T. 2011. "In Situ Detection of Apoptosis by the TUNEL Assay: An Overview of Techniques." *Methods in Molecular Biology* 682.

Lopez, Paul et al. 2022. "T Cell Migration Potentiates HIV Infection by Enhancing Viral Fusion and Integration." *Cell Reports* 38(8).

Lopez, Paul, Wan Hon Koh, Ryan Hnatiuk, and Thomas T. Murooka. 2019. "HIV Infection Stabilizes Macrophage-T Cell Interactions To Promote Cell-Cell HIV Spread." *Journal of Virology* 93(18).

Masri, Carolina, and Y. Chandrashekhar. 2008. "Apoptosis: A Potentially Reversible, Meta-Stable State of the Heart." *Heart Failure Reviews* 13(2).

Miller, Mark J. et al. 2004. "T Cell Repertoire Scanning Is Promoted by Dynamic Dendritic Cell Behavior and Random T Cell Motility in the Lymph Node." *Proceedings of the National Academy of Sciences of the United States of America* 101(4).

Mobiny, Aryan et al. 2020. "Automated Classification of Apoptosis in Phase Contrast Microscopy Using Capsule

Network." *IEEE Transactions on Medical Imaging* 39(1): 1–10.

Mohd Noor, Mohd Halim, Sen Yan Tan, and Mohd Nadhir Ab Wahab. 2022. "Deep Temporal Conv-LSTM for
Activity Recognition." *Neural Processing Letters* 54(5).

Opferman, J. T. 2008. "Apoptosis in the Development of the Immune System." *Cell Death and Differentiation*
15(2).

Pang, Guansong, Chunhua Shen, Longbing Cao, and Anton Van Den Hengel. 2021. "Deep Learning for Anomaly
Detection: A Review." *ACM Computing Surveys* 54(2).

Pizzagalli, Diego Ulisse et al. 2018. "Data Descriptor: Leukocyte Tracking Database, a Collection of Immune Cell
Tracks from Intravital 2-Photon Microscopy Videos." *Scientific Data* 5: 1–13.

———. 2019. "Characterization of the Dynamic Behavior of Neutrophils Following Influenza Vaccination."
Frontiers in Immunology 10(November): 1–17.

Poppe, Ronald. 2010. "A Survey on Vision-Based Human Action Recognition." *Image and Vision Computing*
28(6): 976–90.

Rocheleau, Jonathan V., and David W. Piston. 2003. "Two-Photon Excitation Microscopy for the Study of Living
Cells and Tissues." *Current Protocols in Cell Biology* 20(1).

Saraste, Antti, and Kari Pulkki. 2000. "Morphologic and Biochemical Hallmarks of Apoptosis." *Cardiovascular*
Research 45(3).

Schindelin, Johannes et al. 2012. "Fiji: An Open-Source Platform for Biological-Image Analysis." *Nature Methods*
9(7).

Schmid, Ingrid, Christel Uittenbogaart, and Beth D. Jamieson. 2007. "Live-Cell Assay for Detection of Apoptosis
by Dual-Laser Flow Cytometry Using Hoechst 33342 and 7-Amino-Actinomycin D." *Nature Protocols* 2(1):
187–90.

Schnell, Ulrike, Freark Dijk, Klaas A. Sjollema, and Ben N.G. Giepmans. 2012. "Immunolabeling Artifacts and the
Need for Live-Cell Imaging." *Nature Methods* 9(2).

Secklehner, Judith, Cristina Lo Celso, and Leo M. Carlin. 2017. "Intravital Microscopy in Historic and
Contemporary Immunology." *Immunology and Cell Biology* 95(6).

Shalini, S., L. Dorstyn, S. Dawar, and S. Kumar. 2015. "Old, New and Emerging Functions of Caspases." *Cell*
Death and Differentiation 22(4).

Shcherbakova, Daria M. et al. 2016. "Bright Monomeric Near-Infrared Fluorescent Proteins as Tags and
Biosensors for Multiscale Imaging." *Nature Communications* 7.

Shi, Xingjian et al. 2015. "Convolutional LSTM Network: A Machine Learning Approach for Precipitation
Nowcasting." In *Advances in Neural Information Processing Systems*, , 802–10.

Sumen, Cenk, Thorsten R. Mempel, Irina B. Mazo, and Ulrich H. Von Andrian. 2004. "Intravital Microscopy:
Visualizing Immunity in Context." *Immunity* 21(3).

Sun, Lei, Tongsheng Chen, Longxiang Wang, and Huiying Wang. 2008. "Analysis of Caspase3 Activation in
ChanSu-Induced Apoptosis of ASTC-a-1 Cells by Fluorescence Techniques." In *Biophotonics and Immune*
Responses III,.

Takemoto, Kiwamu, Takeharu Nagai, Atsushi Miyawaki, and Masayuki Miura. 2003. "Spatio-Temporal Activation
of Caspase Revealed by Indicator That Is Insensitive to Environmental Effects." *Journal of Cell Biology*
160(2).

Tang, Daolin et al. 2019. "The Molecular Machinery of Regulated Cell Death." *Cell Research* 29(5).

Tang, H. L., K. L. Yuen, H. M. Tang, and M. C. Fung. 2009. "Reversibility of Apoptosis in Cancer Cells." *British*
Journal of Cancer 100(1).

Uderhardt, Stefan et al. 2019. "Resident Macrophages Cloak Tissue Microlesions to Prevent Neutrophil-Driven
Inflammatory Damage." *Cell* 177(3).

Uijlings, J. R.R., K. E.A. Van De Sande, T. Gevers, and A. W.M. Smeulders. 2013. "Selective Search for Object
Recognition." *International Journal of Computer Vision* 104(2): 154–71.

Ullah, Hadiqa Aman et al. 2021. "Analysis of Deep Neural Networks for Human Activity Recognition in Videos - A
Systematic Literature Review." *IEEE Access* 9.

Verduijn, Joost, Louis Van der Meeren, Dmitri V. Krysko, and André G. Skirtach. 2021. "Deep Learning with
Digital Holographic Microscopy Discriminates Apoptosis and Necroptosis." *Cell Death Discovery* 7(1).

Vermes, István, Clemens Haanen, Helga Steffens-Nakken, and Chris Reutellingsperger. 1995. "A Novel Assay
for Apoptosis Flow Cytometric Detection of Phosphatidylserine Expression on Early Apoptotic Cells Using
Fluorescein Labelled Annexin V." *Journal of Immunological Methods* 184(1).

Vicar, Tomas, Martina Raudenska, Jaromir Gumulec, and Jan Balvan. 2020. "The Quantitative-Phase Dynamics
of Apoptosis and Lytic Cell Death." *Scientific Reports* 10(1).

Vrskova, Roberta, Robert Hudec, Patrik Kamencay, and Peter Sykora. 2022. "Human Activity Classification
Using the 3DCNN Architecture." *Applied Sciences (Switzerland)* 12(2).

Xu, Ju, Mengzhang Li, and Zhanxing Zhu. 2020. "Automatic Data Augmentation for 3d Medical Image
Segmentation." In *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial
Intelligence and Lecture Notes in Bioinformatics)*, , 378–87.

Ye, W., J. Cheng, F. Yang, and Y. Xu. 2019. "Two-Stream Convolutional Network for Improving Activity
Recognition Using Convolutional Long Short-Term Memory Networks." *IEEE Access* 7.

Yusa, Kosuke et al. 2011. "A Hyperactive PiggyBac Transposase for Mammalian Applications." *Proceedings of
the National Academy of Sciences of the United States of America* 108(4).

Zhao, Zhong Qiu, Peng Zheng, Shou Tao Xu, and Xindong Wu. 2019. "Object Detection with Deep Learning: A
Review." *IEEE Transactions on Neural Networks and Learning Systems* 30(11).

Zhuang, Xinrui et al. 2019. "Self-Supervised Feature Learning for 3d Medical Images by Playing a Rubik's Cube."
In *Lecture Notes in Computer Science (Including Subseries Lecture Notes in Artificial Intelligence and
Lecture Notes in Bioinformatics)*, , 420–28.

7. Tables

788 ***Table 1. Comparison of deep learning architectures for apoptosis classification.*** *Comparative table
789 reporting accuracy, F1 and AUC metrics for a CNN, 3DCNN, Conv-LSTM, and Conv-Transformer. The
790 classification accuracy is reported for static frames or image-sequences. N.A. stands for non applicable. The last
791 column shows which cell death study employed the same baseline architecture displayed in the table..*

Classifier architecture	Frame accuracy	Sequence accuracy	F1	AUC	Study
CNN	74 % ± 1.3	N.A.	0.77	0.779	(Damián La Greca et al. 2021; Verduijn et al. 2021)
3DCNN	N.A.	91.22 %± 0.15	0.91	0.924	-
Conv-LSTM	N.A.	97.42 % ± 0.09	0.97	0.994	(Kabir et al. 2022; Mobiny et al. 2020)
Conv-Transformer	N.A	98.27 % ± 0.25	0.98	0.997	Our

793
794 ***Table 2. Comparison of cell death identification studies.*** *Table reporting all studies on cell death classification
795 based on machine learning. For each study, we included the reported classification accuracy, the experimental*

Study	Input of the classifier	Reported classification accuracy	*In vitro*	*In vivo*	Detection In frame	Detection in movies	Classifier architecture	N cell death
Our	Frame sequence	98.27 %	✓	✓	✓	✓	Conv-Transformer	13'120
(Jin et al. 2022)	Frame	93 %	✓	✗	✗	✗	Logistic regression	N.A.
(Verduijn et al. 2021)	Frame	87 %	✓	✗	✗	✗	VGG-19	19'339
(Kabir et al. 2022)	Frame sequence	93 %	✓	✗	✗	✗	ResNet101-LSTM	3'172
(Damián La Greca et al. 2021)	Frame	96.58 %	✓	✗	✗	✗	ResNet50	11'036
(Mobiny et al. 2020)	Frame sequence	93.8 %	✓	✗	✗	✗	CapsNet-LSTM	41'000
(Kranich et al. 2020)	Frame	93.2 %	✓	✗	✗	✗	CAE-RandomForest	27'224
(Vicar et al. 2020)	Frame sequence	N.A.	✓	✗	✓	✓	biLSTM	1'745
(Jimenez-Carretero et al. 2018)	Frame	N.A.	✓	✗	✓	✗	R-CNN	255'215

8. Figures

Figure 1: Generation of **in vitro** *and* **in vivo** *live-cell imaging data. A. Micrographs depicting mammary*
epithelial MCF10A cells transduced with H2B-miRFP703 marker and grown to form a confluent monolayer. The
monolayer was acquired with a fluorescence microscope for several hours with 1-, 2- or 5-min time resolution. **B.**
The centroid (x, y) and the time (t) of apoptotic events were annotated manually based on morphological features
associated with apoptosis. Non-apoptotic cells were identified by automatic segmentation of nuclei. **C.** *Image*
*time-lapses showing a prototypical apoptotic event (**upper panels**), with nuclear shrinkage and chromatin*
*condensation, and a non-apoptotic event (**bottom panels**).* **D.** *Charts showing the quantification of nuclear size*
*(**left**) and the standard deviation (SD) of the nuclear pixel intensity (**right**) of apoptotic and non-apoptotic cells (n*
= 50). Central darker lines represent the mean, gray shades bordered by light colored lines represent the
standard deviation. Nuclear area over time expressed as the ratio between areas at Tn and T0. **E.** *Simplified*
drawing showing the surgical set-up for lymph node and spleen. **F-G.** *Organs are subsequently imaged with*
intravital 2-photon microscopy (IV-2PM, **F**), *generating 3D time-lapses (**G**).* **H.** *Representative IV-2PM micrograph*
and **I.** *selected crops showing GFP-expressing neutrophils (white) undergoing apoptosis. The apoptosis*
*sequence is depicted by raw intensity signal (**upper panels**) and 3D surface reconstruction (**bottom panels**).*

838
839

Figure 2. ADeS, a pipeline for apoptosis detection. A. *ADeS input consists of single channel 2D microscopy*
videos (x,y,t) **B.** *Each video frame is pre-processed to compute the candidate Regions of Interest (ROI) with a*
selective search algorithm. **C.** *Given the coordinates of the ROI at time t, ADeS extracts a series of snapshots*
ranging from t-n to t+n. A deep learning network classifies the sequence either as non-apoptotic (0) or apoptotic
(1). **D.** *The predicted apoptotic events are labelled at each frame by a set of bounding boxes which,* **E.** *are*
successively linked in time with a tracking algorithm based on euclidean distance. **F.** *The readout of ADeS*
consist of bounding boxes and associated probabilities, which can generate a probability map of apoptotic events
*over the course of the video (**left**) as well as providing the number of apoptotic events over time (**right**).*

Figure 3. Conv-Transformer architecture at the core of ADeS. *Abstracted representation of the proposed Conv-Transformer classifier. The input sequence of frames is processed with warped convolutional layers, which extract the features of the images. The extracted features are passed into the 4 transformer modules, composed of attention and feedforward blocks. Finally, a multi layer perceptron enables classification between apoptotic and non-apoptotic sequences.*

Figure 4. Training and performance in vitro. A. *Confusion matrix of the trained model at a decision-making*

threshold of 0.5. **B.** *Receiver operating characteristic displaying the false positive rate (specificity) corresponding*

to each true positive rate (sensitivity). **C.** *Training accuracy of the final model after 100 epochs of training.* **D.**

Representative example of apoptosis detection in a time-lapse acquired in vitro. **E.** *Multiple detection of nuclei*

undergoing apoptosis displays high sensitivity in densely packed field of views. **F.** *Heatmap representation*

depicting all apoptotic events in a movie and the respective probabilities. **G.** *Bar plots showing the true positive*

rate (TPR) and false positive rate (FPR) of ADeS applied to five testing movies, each one depicting an average of

98 apoptosis. **H.** *Time course showing the cumulative sum of ground truth apoptosis (blue) and correct*

predictions (red). **I.** *2D visualization of spatial-temporal coordinates of ground truth (blue) and predicted apoptosis*

(red). In the 2D representation, the radius of the circles maps the temporal coordinates of the event. **J.** *Pixel*

distance between ADeS predictions and the nearest neighbor (NN) of the ground truth (left) in comparison with

the NN distance obtained from a random distribution (right). The plot depicts all predictions of ADeS, including

true positives and false positives. **K.** *Scatterplot of the spatial distance between ground truth and true positives of*

ADeS. Ground truth points are centered on the X = 0 and Y = 0 coordinates. **L. Distribution of** *the temporal*

distance (frames) of the correct predictions from the respective ground truth nearest neighbor. Statistical
comparison was performed with Mann-Whitney test. Columns and error bars represent the mean and standard
deviation respectively. Statistical significance is expressed as: p ≤ 0.05 (*), p ≤ 0.01 (**), p ≤ 0.001 (***), p ≤
0.0001 (****).
876

877
878   **Figure 5. 3D rotation of the** in vivo **dataset. A** *Depiction of a 3D volume cropped around an apoptotic cell.*
879   *Each collected apoptotic sequence underwent multiple 3D rotation in randomly sampled directions. The rotated*
880   *3D images were successively flattened in 2D.* **B.** *Gallery showing the result of multiple volume rotations applied*
881   *to the same apoptotic sequence. The vertical axis depicts the sequence over time, whereas the horizontal*
882   *describes the rotational degree applied to the volumes.*

Apoptosis detection of neutrophil cells *in vivo*

Figure 6. Training and performance in vivo. A*. Confusion matrix of the trained model at a decision-making*

threshold of 0.5. ***B****. Receiver operating characteristic displaying the false positive rate (FPR) corresponding to*

each true positive rate (TPR). ***C****. Training accuracy of the final model trained for 200 epochs with data*

augmentations. ***D****. Image gallery showing ADeS classification to sequences with different disruption timing. The*

generated heatmap reaches peak activation (red) at the instant of cell disruption ***D****. Representative snapshots of*

a neutrophil undergoing apoptosis. Green bounding boxes represents ADeS detection at the moment of cell

disruption ***E****. Representative micrograph depicting the detection of two eosinophil undergoing cell death in the*

*spleen (****left****) and the respective probability heatmap (****right****).* ***F****. ADeS performances expressed by means of true-*

positive rate (TPR) and false-positive rate (FPR) over a panel of 23 videos. ***G****. TRA measure distribution of the*

trajectories predicted by ADeS with respect to the annotated ground truth (n = 8) ***H****. Comparison between human*

and ADeS by means of TPR and FPR on a panel of 5 randomly sampled videos ***I****. Hierarchical clustering of*

several video parameters producing two main dendrograms (n = 23). The first dendrogram includes videos with

reduced sensitivity and is enriched in several parameters related to cell density and signal intensity. ***J****. Graph*

showing the effect of cell density on the performances expressed in terms of TPR and FPR (n = 13). ***K****.*

  *Comparison of the positive predictive value between videos with large and small signal to noise ratio (**left**), and*
900 *videos with large and small shortest cell distance (**right**). **L-M.** Selected video parameters are combined into a*
901 *quality score that weakly correlates with the TPR in overall data (**M, n = 23**) and strongly correlates with the TPR*
902 *in selected underperforming data (**N, n = 8**). Statistical comparison was performed with Mann-Whitney test.*
903 *Columns and error bars represent the mean and standard deviation respectively. Statistical significance is*
904 *expressed as: p ≤ 0.05 (*), p ≤ 0.01 (**), p ≤ 0.001 (***), p ≤ 0.0001 (****).*

906
907

***Figure 7. Applications for toxicity assay** in vitro. **A**. Representative snapshots depicting epithelial cells in vitro*
at 0 and 24 hours after the addition of PBS and three increasing doses of doxorubicin, a chemotherapeutic drug
*and apoptotic inducer **B**. Plot showing the number of apoptotic cells detected by ADeS over time for each*
*experimental condition. **C-D**. Dose-response curves generated from the drug concentrations and the respective*
*apoptotic counts at 5 h. and 24 h.post-treatment. Vertical dashed lines indicates the EC50 concentration. **E.***
*Dose-response curve projected from the fit obtained in (**D**). The predicted curve allows to estimate the response*
at higher drug concentrations than the tested ones.

916
917
Figure 8. Measurement of tissue dynamics *in vivo.* ***A****. Intravital 2-photon micrographs showing ADeS*
detection of an apoptotic neutrophil (Blue, left) and the subsequent recruitment of neighboring cells (right) in the
popliteal LN at 19 h. following influenza vaccination. ***B****. Plot showing the distance of recruited neutrophils with*
respect to the apoptotic coordinates over time (n = 22) ***C****. Plot showing the instantaneous speed of recruited*
neutrophils over time (n = 22). The dashed vertical lines indicate the instant in which the apoptotic event occurs.
Gray area defines the boundaries of maximum and minimum values. ***D****. Schematic drawing showing the intravital*
surgical set up of a murine spleen after inducing a local laser ablation. ***E****. Intravital 2-photon micrographs showing*
the recruitment of GFP-expressing neutrophils (Green) and the formation of a neutrophil cluster (red arrows) at
60 min after photo burning induction. ***F****. Application of ADeS to the generation of a spatiotemporal heatmap*
indicating the probability of encountering apoptotic events in the region affected by the laser damage. The
dashed circle indicates a hot spot of apoptotic events.