Using deep convolutional neural networks to test why human face recognition works the way it does

Katharina Dobs[1,2,3,4*], Joanne Yuan[1,2], Julio Martinez[1,2,5], Nancy Kanwisher[1,2]

[1]Department of Brain and Cognitive Sciences, Massachusetts Institute of Technology, Cambridge, MA, USA
[2]McGovern Institute for Brain Research, Massachusetts Institute of Technology, Cambridge, MA, USA
[3]Department of Psychology, Justus Liebig University Giessen, Giessen, Germany
[4]Center for Mind, Brain and Behavior (CMBB), University of Marburg and Justus Liebig University Giessen, Giessen, Germany
[5]Department of Psychology, Stanford University, CA, USA.

*Correspondence: katharina.dobs@psychol.uni-giessen.de

Abstract

Human face recognition is highly accurate, and exhibits a number of distinctive and well documented behavioral "signatures" such as the use of a characteristic representational space, the disproportionate performance cost when stimuli are presented upside down, and the drop in accuracy for faces from races the participant is less familiar with. These and other phenomena have long been taken as evidence that face recognition is "special". But why does human face perception exhibit these properties in the first place? Here we use convolutional neural networks (CNNs) to test the hypothesis that all of these signatures of human face perception result from optimization for the task of face recognition. Indeed, as predicted by this hypothesis, these phenomena are all found in CNNs trained on face recognition, but not in CNNs trained on object recognition, even when the amount of face experience is matched. To test whether these signatures are in principle specific to faces, we optimized a CNN on car discrimination and tested it on upright and inverted car images. As for face perception, the car-trained network showed a drop in performance for inverted versus upright cars. Similarly, CNNs trained only on inverted faces produce an inverted inversion effect. These findings show that the behavioral signatures of human face perception reflect and are well explained as the result of optimization for the task of face recognition, and that the nature of the computations underlying this task may not be so "special" after all.

Introduction

For over fifty years, cognitive psychologists have documented the many ways that face recognition is "special" (1, 2). Face recognition performance drops disproportionately for inverted faces (i.e., face-inversion effect) (3), is higher for faces of familiar than unfamiliar races (i.e., other-race effect) (4), and makes use of a characteristic "face space" (5). These and other behavioral signatures of the face system have been collected and curated as evidence that qualitatively distinct mechanisms are engaged in the recognition of faces compared to other objects. But largely missing from this long-standing literature is the question of *why* the human face recognition system might have these particular properties. Ideal observer methods have long been used to test whether specific behaviorally-observed phenomena reflect optimized solutions to simple perceptual tasks, but this method is not well suited for complex real-world tasks (6) like face recognition. Recently, however, task-optimized deep neural networks are providing new traction on this classic question (7). In particular, if a specific human behavioral phenomenon is the expected result of optimization for a given task (whether through evolution or individual experience), then we should observe a similar phenomenon in a deep neural network optimized for that same task. Here, we use this logic to test the hypothesis that the classic behavioral signatures of face recognition result specifically from optimization for the task of discriminating one face from another, by testing the prediction that these signatures will be found in convolutional neural networks (CNNs) trained on face recognition, but not in CNNs trained on object categorization, even when their overall face experience is matched.

Specifically, we tested humans and convolutional neural networks (CNNs) on tasks that measure performance on real-world face recognition, "face space", and two of the classic signatures of human face perception: the face inversion effect and other-race effect. These behavioral face perception signatures were then directly compared to multiple CNNs based on the same architecture but optimized for either face recognition or object categorization, or not trained at all (i.e. the same CNN with random weights). A recent study found that face-trained but not object-trained CNNs approached human face recognition accuracy (8). Here we begin by replicating this phenomenon in a large-scale cohort. We then compared not only overall accuracy, but also the representational similarity space between the networks and humans. Next asked whether human face signatures emerge only from an optimization for face recognition, or whether an optimization for face detection would suffice. To find out, we introduced a CNN optimized for object and face categorization (assigning all faces to one output category) and compared it to human behavior. Lastly, we tested whether a classic face signature – the face inversion effect – is specific for faces per se or whether it can, in principle, emerge for other categories in networks optimized for fine-grained discrimination of those categories (9). Critically, although all CNNs necessarily start with a particular architecture and learning rule, none of the networks had any built-in inductive biases – except those introduced by the different objective functions – to produce these specific behavioral signatures.

Results

Does humanlike face recognition performance reflect optimization for face recognition in particular? One of the most basic properties of human face recognition is simply that we are very good at it. Could our excellent accuracy at face recognition result from generic object categorization abilities, or does it reflect optimization for face recognition in particular? To measure face recognition performance in people and CNNs, we used a difficult target-matching task of choosing which of two face images belong to the same identity as a third target image (Fig. 1B, left panel). Target and nontarget faces were all white females between 20-35 years of age, so discrimination of age, gender, or race alone would not suffice for high accuracy on this task. The correctly matching face image differed from the target face image in many low-level features and often in viewpoint, lighting, and facial expression, requiring participants to abstract across these differences to match the identity. Humans (n=1552) were tested in a large-scale online experiment using Amazon Mechanical Turk.

Four CNNs were tested on the same task. All four were based on the VGG16 architecture (Fig. 1A): one trained to discriminate face identities (Face-ID CNN in red), one trained on object categorization, excluding all animal categories (Obj-Cat CNN in yellow), one trained on object and face categorization (including all the faces and object training images, but assigning all face images to a single category; Obj-Face-Cat CNN in orange), and one untrained, randomly initialized CNN (Untrained CNN in gray). We chose the VGG16 architecture (10) because it provides a good fit to neural visual processing (11), it has been successfully trained for face recognition (12) and is widely used in cognitive neuroscience (see Supplementary Note 2 for similar results from two other commonly-used architectures: Alexnet (13) and ResNet (14, 15)). In CNNs, we extracted activation patterns from the penultimate fully-connected layer (i.e., the decoding stage in a CNN; see Supplementary Note 1 for results from other layers) to the same images and computed the correlation distance (1 – Pearson's r) between the activation patterns of each pair of images (Fig. 1B, right panel). The network's choice was determined by which of the two matching images had an activation pattern that was closest to the target image. Importantly, none of the networks was trained on the face identities used as test stimuli.

Human participants were able to correctly match the target face in 87.5% of all trials (1C, light-gray horizontal line; chance level was 50%). Although we intentionally chose less well-known faces for this test, it remained possible that our participants recognized some of the individuals, possibly inflating performance. To find out, we asked each participant if one or more of the identities were familiar to them. Indeed, 71% of participants indicated that they were familiar with at least one of the identities, and 10% indicated that they were 'not sure'. When we ran the same analysis separately on those participants who indicated that they were familiar with at least one identity or 'not sure' (n=1250) versus those that were not familiar with any of the identities (n=302), we found a significant but small drop in performance from 88.2% to 84.3% (p=0, bootstrap test). This finding suggests that any contribution of familiarity

with particular faces to the observed performance in this task was small (cf. Fig. 3A for very similar performance on completely unfamiliar faces).

Might this characteristically high human accuracy on a difficult, high-variance face recognition task, result from a system optimized only for generic object categorization, or would specific optimization for faces be required? We found that CNNs trained on object categorization performed far worse (Obj-Cat CNN: 63.0%; Fig. 1C, yellow) than humans, whereas the face-identity trained CNN achieved human-level performance at 86.9% correct (Face-ID CNN; Fig. 1C, red; p=0.44, bootstrap test), consistent with prior studies (8, 16–19). Does the human-level accuracy of the face identity-trained CNN result from an optimization specifically for face identity discrimination, or would a CNN with the same amount of face experience but optimized for coarse face detection also achieve it? We found that the CNN trained to categorize objects and faces performed significantly better than the CNN trained on object categorization only (Obj-Face-Cat CNN: 67%; Fig. 1C, orange; p<0.01, bootstrap test), but it performed significantly worse than human performance (p=0, bootstrap test). This finding is in line with a recent study suggesting that even removing all faces from the training set (here the object-trained CNN was still exposed to faces present in the object categories (20)) may not have large effects on its face detection performance (21). The untrained CNN achieved a performance of 56.7%, which was significantly above chance (Fig. 1C, gray; p=0, bootstrap test) but much lower than human performance (Fig. 1C, light-gray horizontal line) or performance of all other trained networks (all p=0, bootstrap tests.

Thus, we found that CNNs optimized for face recognition were able to achieve face recognition performance comparable to humans (consistent with prior studies (8, 17, 18)), but this was not the case for CNNs trained on object categorization (despite their high usefulness for other tasks (22, 23)) or untrained CNNs. Further, the CNN trained on both object classification and face detection, which had "experienced" as many faces as the CNN optimized for face recognition but was trained to assign all faces to a single face category, performed far worse than the CNN trained on face recognition. Taken together, these findings suggest that humans' high accuracy at face recognition is not the result of a system optimized for generic object categorization, even with large numbers of faces in the training data, but more likely reflects optimization (through evolution or individual experience) for face recognition in particular.

Figure 1 | Only CNNs trained on face recognition achieve human-level accuracy. (A) We compared four CNNs with the VGG16 architecture to human behavior: one trained on face identity recognition (Face-ID CNN, red), one trained on object categorization (Obj-Cat CNN, yellow), one on object and face categorization, with all faces used for training the face-ID CNN assigned to one category (Obj-Face-Cat CNN, orange), and another untrained, randomly initialized CNN (Untrained CNN). **(B)** Human face recognition performance (n=1552) was measured in a target-matching task on 40 female identities (5 images each) on Amazon Mechanical Turk. To measure performance in CNNs on the same task, we extracted the activation to each of the images in a triplet and computed the correlation distance (1 – Pearson's r) between the target (T) and the two matching images (A and B). The network's choice was modeled as the minimal distance between the target and each of the matching images (e.g., dist(T,A)). **(C)** Human performance was 87.5% correct (light gray horizontal line; chance level was 50%). Only the face-trained CNN (red) achieved face recognition performance close to humans. Networks trained on object categorization only (yellow), or object categorization and face detection (orange) performed better than untrained CNNs (gray), but did not reach human-level recognition performance. Error bars denote bootstrapped 95% CIs. Black lines on the bottom indicate pairwise significant differences (p<0.05, bootstrap tests, fdr-corrected). Images shown are not examples of the original stimulus set due to copyright; images shown are in public domain and available at https://commons.wikimedia.org.

Do CNNs represent faces in a similar fashion to humans? The analyses so far show that CNNs trained on face recognition achieve accuracy levels similar to humans when tested on the same task. But do they achieve this high performance in the same way? To address this question, we assessed the perceived similarity of face images in humans and compared them to CNNs using representational similarity analysis (RSA). Specifically, we asked whether the similarity between face representations in CNNs resemble those in humans. Human participants (n=14) performed a multi-arrangement task (24) on images belonging to 16 different identities (5 images each) for a total of 80 face images (Fig. 2A). In this task, participants were asked to place each image in a 2D space that captures similarities in the appearance of faces. Using RSA, we compared the resulting behavioral representational dissimilarity matrices (RDMs) to the RDMs of all three CNNs, obtained by computing the correlation distance

between the activation patterns from the penultimate fully-connected layer for the same stimuli (see Supplementary Note 3 for results from other layers and Supplementary Note 4 for similar results from two other architectures: Alexnet and ResNet).

For the face-identity trained CNN (Fig. 2B; Face-ID CNN in red), correlations between the network's face representations and human behavior were high in the penultimate layer (Spearman's r: 0.34), almost reaching the noise ceiling (i.e., the maximum correlation possible given the consistency across participants; light gray vertical bar). In contrast, the CNN trained object categorization only (Obj-Cat CNN in yellow) and the CNN trained on object and face categorization (Obj-Face-Cat CNN in orange) represented faces significantly less similarly to humans (Obj-Cat CNN: Spearman's r: 0.19; Obj-Face-Cat CNN: Spearman's r: 0.21; both p=0, bootstrap test). The representational dissimilarities of the untrained CNN (Fig. 2B; Untrained CNN in dark gray) showed a significant but low correlation with human behavior (Spearman's r: 0.03; p=0.02, bootstrap test). Thus, the decoding stage of processing in face-identity trained CNNs, but not CNNs trained on object categorization, face detection or untrained CNNs, match human behavior well, indicating that faces are similarly represented in human behavior and face-identity trained CNNs.

The previous dataset contained multiple images of the same identity, thus human participants might have been biased to simply place images of the same identity together, without taking into account fine-grained details within or between identities. Do these results generalize to other tasks and datasets that rely less on identity recognition? To find out, we measured representational dissimilarities in humans (n=635) and CNNs on a completely different dataset using 60 images of distinct, non-famous young (approximate age between 20 and 30 years) male identities and a similarity-matching task (cf. Fig. 1B for the same task but on identity matching instead of similarity matching). We found the same pattern of results (Fig. 2C). Specifically, the face-identity trained CNN was again more similar to human behavioral similarities (Spearman's r: 0.40) than the other three networks (Obj-Cat CNN r: 0.09, Obj-Face-Cat CNN r: 0.17, untrained CNN r: 0.05, all correlated with behavior above chance, all ps =.02 or lower), all p=0, bootstrap test. Taken together, face-identity trained networks, but not networks that were untrained or did not have training on face identification, represented faces similarly to humans (consistent with a recent study (19) testing view-invariant face representations), suggesting that optimization for face identification was necessary to match the human face representations tapped in behavioral judgements.

Figure 2 | Face-trained but not object-trained CNNs match human face behavior. (A) To measure human representational similarities of faces, participants (n=14) performed a multi-arrangement task on 16 face identities (5 images each) resulting in a representational dissimilarity matrix (RDM) for each participant. The correlation distance (1 – Pearson's *r*) between activations to each pair of the corresponding images in the penultimate fully-connected layer was used to compute the networks' RDM. Spearman rank correlation was used to measure the similarity between human behavioral and networks' RDMs. **(B)** The face-identity trained CNN (Face-ID CNN, red) matched human behavioral representational similarity best (close to noise ceiling; light gray bar). Neither the untrained CNN (Untrained CNN, dark gray) nor the object-categorization trained CNN (Obj-Cat CNN, yellow) or the CNN trained to categorize objects and detect faces (Obj-Face-Cat CNN, orange) matched human representational similarities well. Error bars represent bootstrapped SEMs across participants. **(C)** The results of (B) were replicated in a similarity-matching task (see Fig. 1B for the same task but on identity matching instead of similarity matching) on Amazon Mechanical Turk based (n=635) on a distinct dataset of 60 unfamiliar male identities (one image each). The face-trained CNN (Face CNN, red) again matched human behavioral representational similarity best, far outperforming the untrained CNN (gray), the object-categorization trained CNN (Obj-Cat CNN, yellow) and the object categorization and face detection CNN (Obj-Face-Cat CNN, orange). Note that each participant performed a different number of trials in this task, so that we could not compute the noise ceiling as we have done in (B). Error bars denote bootstrapped SEMs across triplets. Images shown are not examples of the original stimulus set due to copyright restrictions; images shown are in public domain and available at https://commons.wikimedia.org.

Do CNNs show classic signatures of human face processing? So far, we have found that CNNs optimized for face recognition achieve human-level face recognition performance and represent faces in a similar way, but CNNs optimized for object classification (even when trained extensively on face detection) do not. These findings suggest human face recognition performance is unlikely to reflect a system optimized (through evolution, individual experience or both) generically for object categorization and/or face detection alone. Optimization for face recognition in particular seems to

be required to capture human face recognition performance. But what about the classic behavioral signatures of human face processing, like the other-race effect and the face inversion effect? Why might human face recognition exhibit these phenomena? Might they also result from optimization for face recognition in particular? If so, we should expect to find that a CNN trained on face recognition, but not a CNN trained on object recognition (even if faces are included as an object category), would exhibit these same phenomena. In both cases, we predict the *presence* of the two signatures in the face-trained network, but not its magnitude, because the networks do not exactly match human experience.

In the other-race effect (25), humans show lower performance recognizing subgroups of faces they have had less exposure to during development. Previous work has suggested that CNNs also show such experience-dependent deficits when specific demographics are under-represented during training (26–28). But are these effects comparable to the other race effect in humans, and could they result directly from optimization for recognition of faces of predominantly one race? Or is passive exposure to faces of one predominant race (in Imagenet images during object classification training) sufficient? To find out, we tested white and Asian participants on a set of unfamiliar white and Asian female identities and compared them to CNNs using the same target-matching task (Fig. 1B). To test the other-race effect in CNNs, we trained a CNN on face recognition on a dataset of only Asian identities (Face-ID-Asian CNN), and another CNN on a predominantly white dataset with all Asian identities removed (Face-ID-white CNN).

Face recognition performance of the white participants (n=287) was lower for this Asian female test set (82.5%) set than for the white female test set (86.6%), replicating the other-race effect (Fig. 3A; light-gray bars; p=0, bootstrap test across participants). Importantly, Asian participants (n=102) showed the opposite, performing significantly better on the Asian test set (90.1%) than on the white test set (87.4%; p=0, bootstrap test). We found a significant interaction between the stimulus set and participants' race (p=0, bootstrap test across participants), indicating that this effect cannot be simply due to differences in difficulty between stimuli sets. Our key question was whether this effect can be explained as a direct, perhaps inevitable, result of optimization for face recognition based on the demographically biased samples typical of human experience. Indeed, the recognition performance of the CNN trained on faces with Asian identities removed from the training set (Fig. 3A; Face-ID-white CNN) was significantly lower on Asian faces (88.8%) than on white faces (96.8%; p=0, bootstrap test), while the performance of the CNN trained on Asian faces (Face-ID-Asian CNN) was lower for white (86.6%) than for Asian face stimuli (91.5%; p=0, bootstrap test). Neither the CNN trained on object categorization nor the untrained CNN showed a significant drop in performance for the Asian set compared to the dataset of white female identities (Obj-Cat CNN: 62.5% white vs. 62.6% Asian; p=0.93, bootstrap test; Untrained CNN: 57.2% white versus 60.2% Asian; p=0.12, bootstrap test). Overall, these results suggest a reason why humans show an other-race effect: it is a natural consequence of training (and not just exposure in Imagenet) on a specific demographic of faces.

Might optimization for recognition of (upright) faces similarly explain why humans show a face inversion effect? To test this prediction, we used the target-matching task with the white female identities used before (see Fig. 1B) but we presented them upside-down to both humans (n=1219) and networks (Fig. 3B; see Fig. 4 for similar results using SVM decoding). Replicating multiple prior studies (3), human participants showed lower performance for inverted (76.8%) than for upright faces (87.5%; p=0; bootstrap test). This significant drop was also found as a significant within-participant difference using the subset of participants who performed both the upright and inverted tasks (n=404; p=0, bootstrap test). We found that the face-identity trained CNN (red) was the only network whose performance was lower for inverted than upright images (86.9% upright vs. 66.4% inverted; p=0, bootstrap test). Neither the object-categorization trained (yellow) nor the object-and-face-categorization trained (orange) or the untrained CNN (dark gray) showed a significant difference in performance between upright and inverted faces (Obj-Cat CNN: 63% upright vs. 64.2% inverted, p=0.30; Obj-Face-Cat CNN: 67.1% upright vs. 65.6% inverted, p=0.24 Untrained CNN: 59.4% upright versus 57.4% inverted; p=0.08, bootstrap test). Moreover, the face inversion effect was significantly larger for the face-identity trained than for all other CNNs (all p=0, bootstrap test). Thus, even though the object-trained network and the object-and-face-categorization trained network were exposed to faces, and much more to upright than inverted faces, neither shows the robust face inversion effect seen in the face-identity trained network. These findings show that the face inversion effect does not automatically arise from even extensive exposure to upright but not inverted faces, but it does result from optimization on (upright) face identification, providing a likely explanation of why humans show this effect.

Figure 3 | Face-identity trained CNNs show the other-race and face inversion effects similar to humans. Face recognition performance was measured in a target-matching task (see Fig. 1B) in human participants (light gray), multiple face-trained CNNs (red), an object-and-face-trained CNN (Obj-Face-Cat CNN, orange), an object-trained CNN (Obj-Cat CNN, yellow) and an untrained CNN (Untrained CNN, dark gray). In CNNs, activations were extracted from the penultimate fully-connected layer to different stimuli sets and compared to human behavior (see Fig. 1B). **(A)** To measure the other-race effect, performance on

unfamiliar, young female white identities (darker bars) was compared to performance on unfamiliar, young Asian female identities (lighter bars). Human white participants (n=287) and the face-identity trained CNN (Face-ID-white CNN; with Asian identities removed from the training set), but not the object-trained or untrained CNN, showed significantly lower performance on Asian than white faces. In contrast, human Asian participants (n=102) and the CNN trained on Asian identities (Face-ID-Asian CNN) showed significantly lower performance on white than on Asian faces. Asterisks above bars indicate significant differences between conditions (*p=0, bootstrap test). **(B)** Identity matching accuracy for upright (n=1,512; darker bars) and inverted (n=1,219; lighter bars) on white female identities from human behavior and CNNs. Only the face-identity trained CNN (Face-ID CNN) showed the face inversion effect, i.e. lower performance for inverted than upright faces, mirroring human behavior. Error bars denote bootstrapped 95% CIs. Asterisks above bars indicate significant differences between conditions (*p=0, bootstrap test).

If indeed optimization for the recognition of upright faces is sufficient to produce a face inversion effect, hence explaining why humans show this phenomenon, does this reflect something special about face stimuli per se? Or, might any stimulus category produce inversion effects given sufficient training at fine-grained discrimination of exemplars within a category (2)? This question has long been pursued in the psychology literature (29), but the evidence that face-like inversion effects can result from perceptual expertise is mixed (30, 31). On the other hand, few if any humans have as much perceptual expertise on another stimulus category as they do for faces, and it remains unclear whether face-sized behavioral inversion effects might arise for non-face stimuli if they did. But with machine learning methods, we can give a network as much training on nonfaces as on faces. Here, we trained and tested a linear support vector machine (SVM) on activations for upright and inverted stimulus sets extracted from the penultimate fully-connected layer of CNNs with varying training experiences (Fig. 4A).

Indeed, we can produce an "inverted inversion effect" or faces by training the network only on inverted faces (Fig. 4B; Face-ID-inv CNN). That is, face decoding accuracy of 100 face identities (10 images each) from activations in the penultimate fully-connected layer of a CNN trained on inverted faces was significantly larger for inverted faces (99.3%) than for upright faces (70.1%; p<1e-5; two-sided paired t-test). In contrast, the decoding accuracy of a CNN trained on upright faces showed the regular face inversion effect (Face-ID CNN: 99.4% upright vs. 67.7% inverted; p<1e-5). Furthermore, we even find that a network trained on car discrimination shows a car inversion effect (Fig. 4C; Car CNN: 76.7% upright vs. 34.6% inverted; p<1e-5), but neither a network trained on object categorization (without cars included in the training set; Obj-Cat CNN: 30.3% upright vs. 29% inverted; p=0.66) nor a face-identity trained model (Face-ID CNN: 14.9% upright vs. 14% inverted; p=0.66) or an untrained model (Untrained CNN: 15.4% upright vs. 16.4% inverted; p=0.66) does. These findings indicate that inversion effects are not in principle specific to faces per se, but can in principle arise naturally for other stimulus classes from training on only upright stimuli.

Figure 4 | Inversion effects are not specific to upright faces per se. (A) Fine-grained category decoding accuracy was measured in CNNs trained on multiple tasks. Activations were extracted from the penultimate fully-connected layer to different stimuli sets shown upright (darker bars) and inverted (lighter bars) and used to train and test a support vector machine (SVM). **(B)** To measure an "inverted face inversion" effect, 100 face identities were decoded from two face-identity trained CNNs: one trained on upright faces (Face-ID CNN, left), and one trained on inverted faces (Face-ID-inv CNN, right). While the CNN trained on upright faces showed higher accuracy for upright than inverted faces, the CNN trained on inverted faces showed the opposite. **(C)** We decoded 100 car model/make categories from a face-identity trained CNN (Face-ID CNN, red), a CNN trained on object categorization (Obj-Cat CNN, yellow), an untrained CNN (Untrained CNN, gray) and a CNN trained to categorize car models/makes (Car CNN, purple). Only the car-trained CNN showed an inversion effect for cars, i.e. lower performance for inverted than upright cars. Error bars denote SEMs across classification folds. Asterisks above bars indicate significant differences across conditions (*p<1e-5, two-sided paired t-test).

Discussion

Why does human face recognition show the particular behavioral signatures it does? Here we show that the characteristic human high accuracy, face space, other race effects, and face inversion effects, are all found in CNNs optimized for face identification (on upright demographically biased training stimuli characteristic of human experience), but none of these effects are found in networks optimized for generic object categorization. Further, none of these effects arise in networks that have the same amount of face experience as the face-identity trained networks, if all the faces are assigned to one output category. This finding shows that face experience alone is not sufficient to produce these effects. Rather, it is optimization for the specific task of discriminating individual faces from each other that produces these effects. These findings enable us to go beyond the mere documentation of the "special" signatures of the human face system, to provide an answer to the question of *why* human face recognition exhibits these phenomena. What our findings suggest is that these classic behavioral signatures of face recognition in humans result from optimization for face recognition in particular. Thus we might expect any system optimized on this task to show the same phenomena.

We further find that the most classic signature of the face system, the face inversion effect, need not in principle be restricted to face stimuli. In CNNs trained on cars, we find a car inversion effect, and in CNNs trained only on inverted faces, we find an inverted inversion effect. This kind of behavioral inversion effect for nonface objects of expertise has long been sought experimentally in humans, but the enterprise has remained inconclusive (29–31), probably because it is very difficult to find any stimulus class for which humans have as much expertise as they do for faces. With CNNs however, we can control exactly how much experience and what task each network is trained on. These methods have enabled us to show that we should not expect faces to be "special" in the kinds of representations we extract from them. Rather, faces are special in the human brain (32), and in networks jointly trained of face and object recognition (33) in that distinct neurons and network units are engaged in their processing.

Our results also give some hints about the possible origins of the other-race effect. Like our human participants, we found that the CNN trained on predominantly white faces (Asian identities were removed from the training set) showed a drop in performance for Asian faces. This finding mirrors recent reports of bias in AI face recognition systems (26–28, 34) and suggests a computational account of the other-race effect in humans (25). Thus, achieving high face recognition accuracy in machines (and possibly also humans) requires not only extensive face experience, but extensive experience within each of multiple face types. This finding, along with our finding that the face inversion effect arises spontaneously in face-identity trained but not object-trained CNNs, is in line with other findings showing signatures of human face perception in face-identity trained networks, such as face familiarity effects (8), the Thatcher illusion (35) and view-invariant identity representations (19, 36, 37).

Of course, CNNs differ from brains in myriad ways, perhaps most strikingly in how they learn. We are not arguing that the human face system develops in the same way CNNs do, certainly not from extensive labelled examples trained with backpropagation (38). Rather, our point is that CNNs allow us to move beyond the mere documentation of behavioral signatures of face processing as curiosities to be collected, to the more interesting enterprise of asking which of these signatures may be explained as a consequence of the computational optimization for face recognition (6, 7).

Despite the consistency of our results with CNNs trained on face recognition, many puzzles remain. For example, given our finding that face-identity trained networks better explain human face perception, why do object-trained CNNs do similarly or even better at explaining face-specific neural responses (39, 40)? One possible explanation is that human face behavior might be read out from later stages of neural processing than have been investigated so far in studies examining the correspondence between CNNs and neural responses. This hypothesis is supported by several findings suggesting that face-specific regions in the superior temporal sulcus (41, 42), or areas beyond the core system of face perception (43, 44) may be involved in face identity recognition in humans or monkeys (45). Another explanation could be that the resolution of neuroimaging methods in humans is insufficient to read

out identity information in face-specific areas (46). However, methodological limitations of fMRI cannot fully explain this discrepancy, because face-trained models also did not outperform object-trained models in predicting human intracranial data (39), which provides higher spatial resolution than fMRI. Thus, our results are more consistent with the hypothesis that human face behavior reflects a later stage of face processing, potentially more anterior or outside the ventral visual pathway. In the future, this question might be answered by combining human behavior, fMRI and deep neural networks to find out where in the brain the face representations tapped in behavioral tasks reside.

Would more complex types of networks better match human face perception? While it is possible that recurrent neural networks (47, 48) or 3D-based generative models of face perception (40, 49–51) could also explain our data, it is unlikely that they will outperform face-identity trained CNNs given the high consistency we observed (sometimes nearly reaching noise ceiling) between CNNs and human face perception behavior. This finding suggests that simple feedforward CNNs are sufficient to model behavioral face signatures. However, feedforward CNNs do not perform as well on all face tasks (e.g., the Hollow-face effect (49)) and it will be critical to study these tasks further. Moreover, our task was designed to test face recognition under relatively high image variation conditions, but it remains possible that tests with even higher image variation would reveal a gap between humans and feed-forward networks.

Our work also provides some clues into the origins of the human face system, by showing that humanlike face recognition can in principle arise from face-specific experience alone, but only if networks are trained to discriminate faces individually. Importantly, however, training on object classification alone, even with extensive experience on face detection appears not to be sufficient. This finding highlights the fact that the behavior of a network depends not only on the training diet, but also on the training task. It remains an open question whether the relevant face experience that shaped the human face recognition system occurred during evolution, or modern individual experience, or (as is usually the case) both.

In sum, our findings, that face-identity trained but not object-trained models, even with the same amount of face experience, match many of the classic signatures of human face recognition enable us to explain these signatures of human face processing as the expected result of optimization for this specific task. Our study joins several other recent investigations that use deep neural networks to explain human perceptual phenomena as the result of optimization for a given task (6, 7). For example, many phenomena in auditory processing were mimicked in networks trained on natural sounds (52, 53). Moreover, the existence of special neural populations selectively engaged in face recognition can also be explained as the result of joint optimization for face and object recognition (33). Each of these studies uses CNNs to move beyond the mere characterization of perceptual phenomena to address the more fundamental question of why our perceptual systems work the way they do. This

new strategy builds upon earlier work using ideal observer methods in perception, but enables us to now tackle more complex real-world perceptual problems.

Methods

Participants. A total of 2,282 individual workers from the online crowdsourcing platform Amazon Mechanical Turk participated in the target-matching tasks (Figure 1b) on white upright (1,540 workers) and inverted (1,237 workers) stimuli. Workers were allowed to perform both tasks: 25% (575) participated in both tasks on inverted and white stimuli. A total of 29 workers were excluded from the analysis due to overly fast responses (response time in more than five trials < 500ms or more than 10 trials <800 ms). All workers were located in the United States. We asked workers to voluntarily provide their sex, race and age (i.e., in ranges '18-24', '25-34', '35-44', '45-54', '55-64', '65 or older'). The average workers' age was between 25 and 34 years, 57% of workers were female, 41% were male and 2% reported 'other' or did not report their sex. The majority of the workers were white (70%), 15% were Black, 10% were Asian and 5% reported 'other' or did not report their race. To avoid familiarity effects with identities, each worker was only allowed to perform one set of 21 trials (using all 40 distinct identities) per task. Some workers were still able to perform more sets of trials due to technical restrictions on Amazon Mechanical Turk. In this case, only the first set of trials was included in the analysis. The number of workers was chosen such that each trial was sampled 20 times across workers. This number was chosen based on previous studies that sampled triplets on Amazon Mechanical Turk (54).

To study the other-race effect (Fig. 3A), we further collected data on unfamiliar, young white and Asian female stimuli using the same target-matching task. To sample white participants (n=401), we also used Amazon Mechanical Turk and only included workers who were located in the United States, who listed their race as white and who reported that during elementary school at least 50% of their peers were white and less than 50% were Asian. Of those workers, 114 had to be excluded due to overly fast responses, overly deterministic responses (more than 65% left or right clicks only, when chance level was 50%) or because their response differed in the catch trial. The average workers' age was between 35 and 44 years, 46% of workers were female, 52% were male and 2% reported 'other' or did not report their sex. Amazon Mechanical Turk does not provide access to workers that are based in East-Asian countries. Therefore, to additionally collect Asian participants on the same task, we used Clickworker (www.clickworker.com; which provides access to workers from some countries in East Asia) to recruit participants and directed them to perform the experiment on the Meadows platform (www.meadows-research.com). We were able to recruit 132 participants who listed their race as Asian and who reported that during elementary school at least 50% of their peers were Asian. Of those participants 30 had to be excluded using the same exclusion criteria as for the white participants. The average workers' age was between 35 and 44 years, 44% of workers were female, 54% were male and 2% reported 'other' or did not report their sex.

An additional set of 697 individual workers participated in the similarity-matching task (Fig. 2C) on Amazon Mechanical Turk. A total of 62 workers were excluded from the analysis due to overly fast responses (response time in more than five trials < 500ms or more than 10 trials <800 ms). All workers were located in the United States. The average workers' age was between the ranges of '25-34' (41%) and '35-44' (23%) years, 56% of workers were female, 42% were male and 2% reported 'other' or did not report their sex. The majority of the workers were white (71%), 19% were Black, 8% were Asian and 2% reported 'other' or did not report their race. For this task, workers were not restricted in the number of trials they could perform.

All workers provided informed consent and were compensated financially for their time. The experimental protocol was approved by the Massachusetts Institute of Technology (MIT) Committee on the Use of Humans as Experimental Subjects (COUHES No 1806424985) and conducted following all ethical regulations for conducting behavioral experiments.

In addition, behavioral data from 14 laboratory participants (7 female; mean age 25.9, SD = 4.33) from a previously published study (55) were used to perform the representational similarity analysis. As described previously, all participants provided informed, written consent prior to the experiment and were compensated financially for their time. The Massachusetts Institute of Technology (MIT) Committee on the Use of Humans as Experimental Subjects approved the experimental protocol (COUHES No 1606622600).

Stimuli and behavioral target-matching task. To measure human behavioral face recognition performance, participants performed a target-matching task on Amazon Mechanical Turk. To construct this task, we chose 5 images of each of 40 identities. To ensure that the task would not merely rely on external face dimensions (e.g., age, gender), we restricted the stimuli to white female identities of similar age (approximately 20-35 years). We further tried to choose individuals who were less famous to reduce familiarity effects. Moreover, we chose images of these identities that varied across lighting, hairstyle, pose and other low- and mid-level image features (as validated by the low performance of early convolutional layers on this task, around 60% correct; see Supplementary Note 1). We first selected identities which fulfilled these criteria from the Labeled Faces in the Wild dataset (56). Since the Faces in the Wild dataset did not contain sufficient identities to fulfill these criteria, we manually supplemented more identities by selecting them from the internet and by using identities from the VGGFace2 dataset. We then randomly chose images to build triplets in which each target identity (2 images) was paired with each other identity as distractor (1 image) for a total of 1560 (40x39) triplets. Critically, none of the test identities were used for training the Face CNN. Also importantly, from the 156,000 possible triplets (40 identities x 5 images x 4 images (same identity) x 195 images (distractor identity)) available, we only used the 1560 triplets that were presented to the human participants to compute the identity recognition performance of CNNs. On Amazon Mechanical Turk, we asked human participants to choose which of two face images (e.g., matches A or B) belonged to the same identity as the third target image.

The position of the matching images (left or right) was pseudo-randomized across trials. To reduce perceptual and behavioral noise as much as possible, participants had unlimited time to perform each trial. Each participant performed 20 trials in which 20 distinct identities were paired with the remaining half of the 20 identities such that each identity was shown only once during the set of trials. To measure within-participant reliability, participants also performed an additional trial in which one randomly chosen trial from the initial set of 20 trials was repeated. Each triplet was repeated 20 times across participants and the average identity matching performance across all triplets and human participants (n=1552) served as measure for human face recognition performance. To measure the behavioral face inversion effect on the same stimuli, we performed the same experiment (using the same triplets), but showed the inverted stimuli to human participants (n=1,219).

To test the other-race effect in humans and compare them to CNNs (see section below), we ran the same test on another set of face stimuli: unfamiliar, young, female white and Asian faces. We recruited white human participants (n=287) using Amazon Mechanical Turk, only including participants who were white and who reported that more than 50% of their peers were white during elementary school. Due to restriction of workers on Amazon Mechanical Turk, we had to recruit participants from Asia using Clickworker. Once they signed up for the experiment on Clickworker, participants were forwarded to the Meadows platform running the same task as our white participants on Amazon Mechanical Turk. To exclude that familiarity with some of the identities would influence the results, we collected a novel set of 80 identities (40 of each race) by using photos provided by colleagues, and by sampling photos of identities on Instagram (with less than 2,000 followers). All of the identities were female and between 20-35 years of age, and none of them was used as training for the CNNs. For each race, we built triplets in which each target identity (2 images) was paired with each other identity as distractor (1 image) for a total of 1560 (40x39) triplets. During the experiment, each participant performed 20 trials of each race, randomly interleaved, for a total of 40 trials. For each participant, 20 distinct identities of a race were paired with the remaining half of the 20 identities of the same race, such that each identity was shown only once during the set of trials. To measure within-participant reliability, we included an additional trial in which one randomly chosen trial from the set of 40 trials was repeated. All other experimental parameters were identical to the target-matching task described above.

Untrained and trained convolutional neural networks. To explore the role of face experience in face recognition, we trained four CNNs with varying amounts and kinds of visual experience. All CNNs were based on the VGG16 architecture (10) (see Supplementary Note 2 and 4 for parallel results based on Alexnet (13) and ResNet (14, 15) architectures). First, to test the performance of an untrained network, we used a randomly-initialized VGG16 network (Untrained CNN). Second, to measure the performance on face recognition on a CNN trained on generic objects, we trained a randomly-initialized VGG16 architecture on object categorization only (Obj-Cat CNN). The Object CNN was trained on 423 manually sampled object categories of the

ILSVRC-2012 database (57). To obtain an object-trained CNN, we removed all categories from the original dataset that were not prototypical objects (e.g., scene-like categories, animals). The remaining 423 categories consisted of prototypical objects (e.g., trumpet, hammer, coffee cup). For each of the 423 selected object categories, we used 1000 images for training and 50 for validation, for a total of 423k training and ~21k validation images. Third, we trained a VGG16 network on face identity categorization only (Face-ID CNN). The network was trained on 1,714 identities (857 female) from the VGGFace2 database (16). Specifically, we chose identities with a minimum of 300 images per identities but otherwise the identities were randomly selected from the VGGFace2 database. Importantly, to allow for better comparison with humans, we further tried to match the number of identities to the minimum number of identities typically known by humans (range 1,000 – 10,000) (58). To best match the training set size to the object-trained CNN, we randomly chose 246 images per face identity for training, and 50 images per category for validation, for a total of ~422k training and ~85k validation images. Finally, to test whether mere face experience (without discriminating individual faces) was sufficient to match human face processing, we included a CNN that was matched in the amount of face experience to the face-identity trained CNN, but trained on coarse face detection only. Specifically, we trained a CNN on object and face categorization (Obj-Face-Cat CNN) on the exact same 423 object categories as the object-trained CNN with one additional category (i.e., 424 categories in total) that included all face images used to trained the face-identity trained CNN. Note, that this network did not only included the same amount of face images as the face-identity trained model, but also a much larger training set.

For both trained networks (i.e., Object and Face CNN), we used similar training parameters as suggested in (10): stochastic gradient descent (SGD) with momentum with an initial learning rate of 10^{-3}, a weight decay of 10^{-4} and momentum of 0.9. We trained each network for 100 epochs (i.e., full passes over the training set) and the learning rate was reduced twice when the training loss saturated to 10^{-4} and 10^{-5}, respectively. To update the weights during training, we computed the cross-entropy loss on random batches of 128 images and backpropagated the loss. Each image was scaled to a minimum side length (height or width) of 256 pixels, normalized to a mean and standard deviation of 0.5. For data augmentation, we showed images randomly as gray-scale with a probability of 20% and chose random crops of the size of 224 x 224 pixels (out of the 256 x 256 pixel-sized images) for each image during training. All training parameters were selected in pilot experiments. The test images were scaled, normalized and center-cropped before extracting the activation patterns.

To test whether a CNN trained on inverted faces (Face-inv CNN) would show an inverted face inversion effect, we additionally trained a CNN on inverted face images. We used the same architecture, training dataset and parameters as for the Face CNN but showed all images inverted instead of upright during training.

To test the other-race effect in CNNs, we first trained a VGG16 architecture on a dataset of mainly white identities (Face-ID-white CNN). To obtain such a dataset, we manually removed all Asian identities from the identities we previously selected from the VGGFace2 dataset. Specifically, we removed 60 Asian identities from the set of

1,714 identities, for a total of 1,654 remaining mainly white identities. We then trained another VGG16 network on Asian identities (Face-ID-Asian CNN) using the Asian Face Dataset (AFD (59)). We randomly chose 1,654 identities of this dataset to match the number of identities of the Face-white CNN. These identities had a minimum of 105 images per identity (~174k images). To avoid imbalanced classes, we therefore chose 105 images for each of the identities of both datasets using 100 for training and five images for validating.

Finally, to test whether another domain-specific CNN would show an inversion effect, we trained a VGG16 architecture on car model/make discrimination (Car CNN) using the CompCars dataset (60). To obtain enough images per class, we concatenated images of this dataset from the same model/make but of different years into one class. In this fashion, we ended up with 1109 classes with 45 images for training and 5 images for validating per class (~50k training and ~5.5k validation images).

Since the datasets of Asian identities and car model/makes were smaller than the ones used for the face- and the object-trained CNN introduced above, we trained all three networks (i.e., Face-ID-white CNN, Face-ID-Asian CNN, Car CNN) for 200 epochs. Otherwise we used the same training parameters as for the Face and Object CNN.

Target-matching task in CNNs. To directly compare the face recognition performance between humans and CNNs, for the behavioral target-matching tasks on upright and inverted white face images, we presented the same stimuli to the three different CNNs: i) untrained CNN, ii) object-trained CNN and iii) face-trained VGG16 models (see Supplementary Note 2 for parallel results on Alexnet and Resnet). For the behavioral tasks on unfamiliar white and Asian face stimuli, we presented those stimuli to four CNNs: i) untrained, ii) object-trained and iii) trained on white faces and iv) trained on Asian faces. For each tasks and stimuli, we simulated the behavioral task in CNNs by extracting activation from the penultimate fully-connected layer to each of the 200 images (see Supplementary Note 1 for additional layers). We measured the pairwise similarity for each pair of images using correlation distance (1 – Pearson's r) between the activation patterns. The network's choice was modeled as which of the two matching images was closest to the target image. Critically, from the 156,000 possible triplets (40 identities x 5 images x 4 images (same identity) x 195 images (distractor identity)) available, we only used the 1560 triplets that were presented to the human participants to compute the identity recognition performance. Note that when we compared CNNs to participants who indicated that they were unfamiliar with all identities, we only compared the performance on the triplets performed by those participants. By averaging the choice accuracy (0 or 1 for incorrect or correct, respectively) across all 1560 triplets, we obtained a corresponding identity matching performance for each of the different CNNs.

Stimuli and behavioral representational dissimilarities. To find out whether humans and CNNs represent faces similarity, we performed representational similarity analysis. The experimental design and stimuli to obtain the behavioral data has been explained in detail previously (55), so here we just briefly summarize the stimuli and task. Participants performed a multi-arrangement task (24) using 80 face stimuli. Stimuli consisted of 16 celebrities, which varied orthogonally in gender and age, such that half were female and half were male and half of them were young (below ~35 years) and half were old (above ~60 years). Participants performed the multi-arrangement experiment online using their own computer. During the task, participants were instructed to arrange different subsets of the images based on their perceived similarity ("similar images together, dissimilar images apart") by dragging and dropping them in a circle. After the completion of the experiment, the pairwise squared on-screen distances between the arranged images was computed, thus representing a behavioral representational dissimilarity matrix (RDM). For each participant, we extracted the lower off-diagonal data from the behavioral RDM to obtain a vector of pairwise dissimilarities used for computing the correlations.

We additionally computed the noise ceiling for the representational dissimilarities given the inconsistencies across participants using a method described previously (61). Briefly, we estimated the upper bound of the noise ceiling as the mean correlation of each participant's vector of perceived dissimilarities with the group mean (including the participant itself). In contrast, the lower bound was computed by taking the mean correlation of each participant with all other participants.

To test whether the results from the multi-arrangement task would generalize to a different dataset and task, we conducted a similarity-matching task on Amazon Mechanical Turk. To construct this task, we chose 60 images of unfamiliar male identities (one image each) from the Flickr-Faces-HQ database (62). The stimuli included 60 young male identities of similar age (approximately between 20 and 30 years old) with a neutral facial expression. Participants were asked to choose which of two images was more similar to a third target image (i.e., triplet). Each triplet was sampled 50 times. The proportion of choices for a specific triplet resulted in two dissimilarity values: between the target and each of the matching images. We extracted the lower triangle excluding the diagonal from the resulting similarity matrix to obtain a vector of pairwise dissimilarities. Note that since participants were not limited in the number of trials they could perform, participants contributed with varying degrees to the final dissimilarity matrix. Therefore, we could not compute the noise ceiling as we did before. We then used the combined vector of dissimilarity values to compute the similarity with the CNNs.

Representational similarity analysis between humans and CNNs. To obtain representational dissimilarities in CNNs, we presented the same stimuli as used for the human participants to the CNNs. For each CNN, we extracted the activation patterns to each image separately for each of the 13 convolutional layers and the first two fully connected layers and computed the correlation distance (1 – Pearson's r) between each pair of activation patterns. This resulted in one RDM per layer for each

of the three CNNs. For the first task (participant-wise RDMs), to compute the similarity between the human RDMs and the RDMs obtained for the CNNs, we rank correlated each participant's behavioral dissimilarities vector with the corresponding CNN dissimilarities vectors. The average rank correlation across participants served as similarity measure between human participants and CNNs. We further computed the bootstrapped confidence intervals by bootstrapping the participants and computing the correlation with the CNN RDMs 10,000 times and computed the 95% CI of the resulting distribution. For the second task, we were able to run more powerful participant-wise analyses as we obtained one RDM per subject (61). Here, we rank correlated the behavioral dissimilarity vector with the corresponding CNN dissimilarities vectors constructed from the same stimuli. To obtain confidence intervals, we bootstrapped the dissimilarity values of the behavioral and the CNN RDMs 10,000 times and computed the correlation. We then computed the 95% CI of the resulting distribution of correlations.

Decoding of visual categories in CNNs. To test whether CNNs with varying experience differ in how much information about a visual category they contain, we decoded exemplars of independent sets of visual categories from activations extracted from those networks (Fig. 4A).

To test the inverted face inversion effect, we used 100 held-out face identities (50 female; 10 images per identity; 1000 images in total) from the VGGFace2 dataset that were not included in the training set of the CNNs. We presented these images upright and inverted and extracted activations from both the CNN trained on upright faces (Face CNN) and the CNN trained on inverted images (Face-inv CNN).

To test whether the inversion effect was specific to faces, we further tested for an inversion effect for fine-grained car decoding. We selected 10 images of 100 model/make categories from the CompCars dataset (1000 images in total) that were not including in the training of any network and extracted activations to those images from the face-trained CNN, the object-trained CNN (which had no vehicle-related categories in the training set), the untrained CNN and a CNN trained on car discrimination.

For both of these analyses, we extracted the activation in the penultimate layer of each network (i.e., the last layer before the classification layer) to the image sets. For each task and activations from each network, we trained and tested a 100-way linear support vector machine (with L2 regularization) on the corresponding activation patterns using a leave-one-image-out (i.e., 10-fold) cross-validation scheme. We computed the mean and SEM across classification folds and used two-sided paired t-tests across classification folds to test for differences between decoding accuracies.

Statistical inference. For all analyses, we used non-parametric statistical tests that do not rely on assumptions about the distributions of the data. For the target-matching task, we bootstrapped the combination of paired identities shown as a trial (i.e., 1560 triplets) 10,000 times and averaged the responses to obtain a distribution of accuracies. The 2.5th and the 97.5th percentile of this distribution were used as 95%

confidence interval (CI) for the behavioral and CNN performances. For statistical inference of the differences between performances, we bootstrapped the triplets 10,000 times and computed the mean difference between accuracies resulting in an empirical distribution of performance differences. To test for differences between differences (i.e., interaction effects), we performed the same analysis but bootstrapped the difference of the differences 10,000 times. The number of differences (or differences of differences) that were smaller or larger than zero divided by the number of bootstraps defined the p-value (i.e., two-sided testing). In the case of within-participant tests, we performed the same analysis but bootstrapped the participants (instead of triplets) 1,000 times to obtain a distribution of performance differences or difference of differences in case of interaction effects. All p-values were corrected for multiple comparisons using false discovery rate (FDR) at a 0.05 level.

For the representational similarity analysis, we also used bootstrap tests. In the multi-arrangement task, we bootstrapped the participant-specific RDMs 10,000 times and correlated them with the CNN RDMs obtained from the penultimate fully-connected layer of each network to obtain an empirical distribution of the correlations. The standard deviation of these distributions defined the SEM for the correlation between humans and CNNs. To test for differences (or differences of differences) between correlations, we bootstrapped the participants 10,000 times and computed the mean difference between correlations resulting in an empirical distribution of correlation differences. In the similarity-matching task, we performed the same analysis, but bootstrapped the triplets instead of participants. Specifically, we bootstrapped the proportional choices for the triplets and correlated them with the CNN RDMs to obtain SEMs, or to compute a distribution of correlation differences. The p-values were derived as explained above. All p-values were corrected for multiple comparisons using FDR at a 0.05 level.

Data availability. All stimuli used for the online experiments are available at https://osf.io/dbks3/. The stimuli used for the laboratory experiment have been previously made available at https://osf.io/gk6f5/. The data underlying Figures 1-4 and Supplementary Figures 1-8 will be made available on OSF upon acceptance.

Code availability. To reproduce the relevant analyses and figures, the Python and Matlab scripts will be made available on OSF upon acceptance. The code to train computational models has been previously made available at https://github.com/martinezjulio/sdnn.

Acknowledgements

We thank Martin Hebart for his help and advice in setting up the experiments on Amazon Mechanical Turk, Rebecca Saxe for valuable comments on the manuscript, Elizabeth Mieczkowski for help with online experiments and members of the Kanwisher lab for fruitful discussions and feedback. This work was supported by a Feodor-Lynen postdoctoral fellowship of the Humboldt Foundation and the DFG-

funded Collaborative Research Center on "Cardinal Mechanisms of Perception" (SFB-TRR-135) to K.D., NIH grant Grant DP1HD091947 to N.K and National Science Foundation Science and Technology Center for Brains, Minds, and Machines.

References

1. M. J. Farah, Is face recognition 'special'? Evidence from neuropsychology. *Behav Brain Res* 76, 181–189 (1996).

2. R. Diamond, S. Carey, Why Faces Are and Are Not Special: An Effect of Expertise. *J. Exp. Psychol. Gen.* 115, 107–117 (1986).

3. R. K. Yin, Looking at upside-down faces. *J. Exp. Psychol.* 81, 1–5 (1969).

4. R. K. Bothwell, J. C. Brigham, R. S. Malpass, Cross-racial identification. *Personality and Social Psychology Bulletin* 15, 19–25 (1989).

5. T. Valentine, "Face-space models of face recognition" in Computational, geometric, and process perspectives on facial cognition: Contexts and challenges., M. J. Wenger, J. T. Townsend, Eds. (2001), pp. 83–113.

6. A. J. Kell, J. H. McDermott, Deep neural network models of sensory systems: windows onto the role of task constraints. *Curr. Opin. Neurobiol.* 55, 121–132 (2019).

7. N. Kanwisher, M. Khosla, K. Dobs, Using Artificial Neural Networks to Ask Why Questions of Minds and Brains. *under review at Trends in Neurosciences*.

8. N. M. Blauch, M. Behrmann, D. C. Plaut, Computational insights into human perceptual expertise for familiar and unfamiliar face recognition. *Cognition* 208, 104341 (2020).

9. C. Rezlescu, A. Chapman, T. Susilo, A. Caramazza, Large inversion effects are not specific to faces and do not vary with object expertise. *Preprint at PsyArXiv* (2016) https:/doi.org/10.31234/osf.io/xzbe5.

10. K. Simonyan, A. Zisserman, Very deep convolutional networks for large-scale image recognition in *International Conference on Learning Representations*, International Conference on Learning Representations., (2015), pp. 1–14.

11. M. Schrimpf, *et al.*, "Brain-Score: Which Artificial Neural Network for Object Recognition is most Brain-Like?" (2018).

12. O. M. Parkhi, A. Vedaldi, A. Zisserman, Deep face recognition in *Proceedings of the British Machine Vision Conference (BMVC)*, British Machine Vision Conference., (2015), p. 41.1-41.12.

13. A. Krizhevsky, I. Sutskever, G. E. Hinton, ImageNet Classification with Deep Convolutional Neural Networks in *Adv. Neural Inf. Process. Syst.*, NIPS., (2012), pp. 1097–1105.

14. D. Han, J. Kim, J. Kim, Deep Pyramidal Residual Networks in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR))*, Conference on Computer Vision and Pattern Recognition (CVPR)., (2017), pp. 6307–6315.

15. K. He, X. Zhang, S. Ren, J. Sun, Deep Residual Learning for Image Recognition in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, Conference on Computer Vision and Pattern Recognition (CVPR)., (2016), pp. 770–778.

16. Q. Cao, L. Shen, W. Xie, O. M. Parkhi, A. Zisserman, VGGFace2: A dataset for recognising faces across pose and age in *IEEE International Conference on Automatic Face & Gesture Recognition*, IEEE International Conference on Automatic Face & Gesture Recognition., (2018), pp. 67–74.

17. Y. Taigman, M. Yang, M. A. Ranzato, L. Wolf, DeepFace: Closing the Gap to Human-Level Performance in Face Verification in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, Proc. Computer Vision and Pattern Recognition., (2014), pp. 1701–1708.

18. P. J. Phillips, *et al.*, Face recognition accuracy of forensic examiners, superrecognizers, and face recognition algorithms. *Proc. Natl. Acad. Sci. U.S.A.* 115, 6171–6176 (2018).

19. N. Abudarham, I. Grosbard, G. Yovel, Face recognition depends on specialized mechanisms tuned to view-invariant facial features: Insights from deep neural networks optimized for face or object recognition. *Cogn. Sci.* 45, e13031 (2021).

20. K. Yang, J. Yau, L. Fei-Fei, J. Deng, O. Russakovsky, "A Study of Face Obfuscation in ImageNet" (2021).

21. S. Xu, Y. Zhang, Z. Zhen, J. Liu, The Face Module Emerged in a Deep Convolutional Neural Network Selectively Deprived of Face Experience. *Front. Comput. Neurosci.* 15, 626259 (2021).

22. M. Huh, P. Agrawal, A. A. Efros, What makes ImageNet good for transfer learning? in *NIPS Workshop on Large Scale Computer Vision Systems*, NIPS Workshop on Large Scale Computer Vision Systems., (2016), pp. 1–10.

23. R. Zhang, P. Isola, A. A. Efros, E. Shechtman, O. Wang, The Unreasonable Effectiveness of Deep Features as a Perceptual Metric in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition., (2018), pp. 586–595.

24. N. Kriegeskorte, M. Mur, Inverse MDS: Inferring Dissimilarity Structure from Multiple Item Arrangements. *Front. Psychol.* 3, 245 (2012).

25. C. A. Meissner, J. C. Brigham, Thirty years of investigating the own-race bias in memory for faces: A meta-analytic review. *Psychol. Public Policy Law* 7, 3–35 (2001).

26. I. D. Raji, *et al.*, Saving Face: Investigating the Ethical Concerns of Facial Recognition Auditing in *AAAI/ACM Conference on AI, Ethics, and Society*, (2020), pp. 145–151.

27. J. G. Cavazos, P. J. Phillips, C. D. Castillo, A. J. O'Toole, Accuracy comparison across face recognition algorithms: Where are we on measuring race bias? *IEEE Trans. Biom. Behav. Identity Sci.* 3, 101–111 (2021).

28. J. Tian, H. Xie, S. Hu, J. Liu, Multidimensional Face Representation in a Deep Convolutional Neural Network Reveals the Mechanism Underlying AI Racism. *Front. Comput. Neurosci.* 15, 620281 (2021).

29. I. Gauthier, C. A. Nelson, The development of face expertise. *Curr. Opin. Neurobiol.* 11, 219–224 (2001).

30. R. Robbins, E. McKone, No face-like processing for objects-of-expertise in three behavioural tasks. *Cognition* 103, 34–79 (2007).

31. A. Campbell, J. W. Tanaka, Inversion Impairs Expert Budgerigar Identity Recognition: A Face-Like Effect for a Nonface Object of Expertise. *Perception* 47, 647–659 (2018).

32. G. Schalk, *et al.*, Facephenes and rainbows: Causal evidence for functional and anatomical specificity of face and color processing in the human brain. *Proc. Natl. Acad. Sci. U.S.A.* 114, 12285–12290 (2017).

33. K. Dobs, J. Martinez, A. J. E. Kell, N. Kanwisher, Brain-like functional specialization emerges spontaneously in deep neural networks. *Sci. Adv.* 8, eabl8913 (2022).

34. J. Buolamwini, T. Gebru, Gender Shades: Intersectional Accuracy Disparities in Commercial Gender Classification in *Proceedings of Machine Learning Research*, (2018), pp. 77–91.

35. G. Jacob, R. T. Pramod, H. Katti, S. P. Arun, Qualitative similarities and differences in visual object representations between brains and deep networks. *Nat. Commun.* 12, 1872 (2021).

36. G. Yovel, N. Abudarham, From concepts to percepts in human and machine face recognition: A reply to Blauch, Behrmann & Plaut. *Cognition* 208, 104424 (2020).

37. A. Farzmahdi, K. Rajaei, M. Ghodrati, R. Ebrahimpour, S.-M. Khaligh-Razavi, A specialized face-processing model inspired by the organization of monkey face patches explains several face-specific phenomena observed in humans. *Sci. Rep.* 6, 25025 (2016).

38. C. Zhuang, *et al.*, Unsupervised neural network models of the ventral visual stream. *Proc. Natl. Acad. Sci. U.S.A.* 118, e2014196118 (2021).

39. S. Grossman, *et al.*, Convergent evolution of face spaces across human face-selective neuronal groups and deep convolutional networks. *Nat. Commun.* 10, 4934 (2019).

40. L. Chang, B. Egger, T. Vetter, D. Y. Tsao, Explaining face representation in the primate brain using different computational models. *Curr. Biol.* (2021) https:/doi.org/10.1016/j.cub.2021.04.014.

41. S. Anzellotti, A. Caramazza, Multimodal representations of person identity individuated with fMRI. *Cortex* 89, 85–97 (2017).

42. K. Dobs, J. Schultz, I. Bülthoff, J. L. Gardner, Task-dependent enhancement of facial expression and identity representations in human cortex. *NeuroImage* 172, 689–702 (2018).

43. J. S. Guntupalli, K. G. Wheeler, M. I. Gobbini, Disentangling the Representation of Identity from Head View Along the Human Face Processing Pathway. *Cereb. Cortex* 27, 46–53 (2016).

44. N. Kriegeskorte, E. Formisano, B. Sorger, R. Goebel, Individual faces elicit distinct response patterns in human anterior temporal cortex. *Proc. Natl. Acad. Sci. U.S.A.* 104, 20600–20605 (2007).

45. S. M. Landi, W. A. Freiwald, Two areas for familiar face recognition in the primate brain. *Science* 357, 591–595 (2017).

46. J. Dubois, A. O. de Berker, D. Y. Tsao, Single-Unit Recordings in the Macaque Face Patch System Reveal Limitations of fMRI MVPA. *J. Neurosci.* 35, 2791–2802 (2015).

47. T. C. Kietzmann, *et al.*, Recurrence is required to capture the representational dynamics of the human visual system. *Proc. Natl. Acad. Sci. U.S.A.* 116, 21854–21863 (2019).

48. K. Kar, J. Kubilius, K. Schmidt, E. B. Issa, J. J. DiCarlo, Evidence that recurrent circuits are critical to the ventral stream's execution of core object recognition behavior. *Nat. Neurosci.* 22, 974–983 (2019).

49. I. Yildirim, M. Belledonne, W. Freiwald, J. Tenenbaum, Efficient inverse graphics in biological face processing. *Sci. Adv.* 6, eaax5979 (2020).

50. K. M. Jozwik, *et al.*, Face dissimilarity judgments are predicted by representational distance in morphable and image-computable models. *Proc National Acad Sci* 119, e2115047119 (2022).

51. C. Daube, *et al.*, Grounding deep neural network predictions of human categorization behavior in understandable functional features: The case of face identity. *Patterns* 2, 100348 (2021).

52. A. Francl, J. H. McDermott, Deep neural network models of sound localization reveal how perception is adapted to real-world environments. *Nat. Hum. Behav.* 6, 111–133 (2022).

53. M. R. Saddler, R. Gonzalez, J. H. McDermott, Deep neural network models reveal interplay of peripheral coding and stimulus statistics in pitch perception. *Nat. Commun.* 12, 7278 (2021).

54. M. N. Hebart, C. Y. Zheng, F. Pereira, C. I. Baker, Revealing the multidimensional mental representations of natural objects underlying human similarity judgements. *Nat. Hum. Behav.* 4, 1173–1185 (2020).

55. K. Dobs, L. Isik, D. Pantazis, N. Kanwisher, How face perception unfolds over time. *Nat. Commun.* 10, 1258 (2019).

56. G. B. Huang, M. Mattar, T. Berg, E. Learned-Miller, Labeled Faces in the Wild: A Database for Studying Face Recognition in Unconstrained Environments in *Workshop on Faces in "Real-Life" Images: Detection, Alignment, and Recognition*, (2008), pp. 1–11.

57. J. Deng, *et al.*, ImageNet: A large-scale hierarchical image database in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, Conference on Computer Vision and Pattern Recognition (CVPR)., (2009), pp. 248–255.

58. R. Jenkins, A. J. Dowsett, A. M. Burton, How many faces do people know? *Cereb. Cortex* 285, 20181319–6 (2018).

59. Z. Xiong, *et al.*, An Asian Face Dataset and How Race Influences Face Recognition in *Pacific Rim Conference on Multimedia*, Pacific Rim Conference on Multimedia., (2018), pp. 372–383.

60. L. Yang, P. Luo, C. C. Loy, X. Tang, A Large-Scale Car Dataset for Fine-Grained Categorization and Verification in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, (2015), pp. 3973–3981.

61. H. Nili, *et al.*, A Toolbox for Representational Similarity Analysis. *PLoS Comp. Biol.* 10, e1003553-11 (2014).

62. T. Karras, S. Laine, T. Aila, A Style-Based Generator Architecture for Generative Adversarial Networks in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, (2019), pp. 4401–4410.