A three-dimensional, discrete-continuum model of blood flow in microvascular networks

Paul W. Sweeney[1,2*], Claire Walsh[2,3], Simon Walker-Samuel[3], and Rebecca J. Shipley[2*]

[1]Cancer Research UK Cambridge Institute, University of Cambridge

[2]Department of Mechanical Engineering, University College London

[3]Centre for Computational Medicine, University College London

[*]Correspondance

Abstract

We introduce a hybrid, discrete-continuum method to model blood pressure across large microvascular networks with incomplete architectural information. Our multiscale approach couples a 1D Poiseuille flow description in large, discrete arteriolar and venular networks, via point sources of flux, to a continuum-based Darcy model for transport in the capillary bed. We test our hybrid framework using a vascular network imaged from the mouse brain medulla / pons using multi-fluorescence high-resolution episcopic microscopy. The fully-resolved vascular network is used to predicted the hydraulic conductivity of the capillary network and to generate a fully-discrete pressure solution to benchmark our novel method against. We show that the discrete-continuum methodology is a computationally tractable and effective tool for predicting blood pressure in real-world microvascular tissues when capillary microvessels are not well-defined.

Keywords — Blood flow, microcirculation, Darcy flow, homogenisation, brain, medulla

Introduction

The microcirculation is a hierarchical structure of blood vessels consisting of arterioles, capillaries and venules. These vessels are typically classified as those with diameters $< 300 \ \mu$m and by several distinctive characteristics, such as mural cell coverage[1] and resistance to flow[2]. Structurally, arterioles and venules form branching structures which

supply and drain an interconnected, mesh-like network of capillaries with diameters < 10 μm. In physiological conditions, capillaries are the principal source for delivery of oxygen and nutrients to meet the metabolic demands of parenchymal tissue. In particular, the distance over which oxygen can diffuse into tissue is small ($20 - 100$ μm), and so metabolic needs are met by the density of capillaries and their fine-tuned, tissue-dependent spatial configuration[3]. Hence, studying the impact of network architecture on fluid and mass transport in microvascular tissues is essential for a comprehensive understanding of microcirculatory function.

Advances in biomedical imaging of vascular tissues[4–7] have paved the way for computational studies which integrate complete vascular architectures with biophysical models to probe the microenvironment *in silico* in a manner that is currently inaccessible in a traditional experimental setting[8]. Due to the computational challenges of simulating network-scale blood rheology and dynamics using mesh-based methods, many studies apply one-dimensional (1D) Poiseuille flow models (see Figure 1A) to these vascular network datasets to provide insight into a wide range of biological applications, for example, in cerebral blood flow[9–12], angiogenesis[13,14] and cancer[4,15–17]. Nonetheless, with the emergence of whole-organ vascular imaging[6], the computational demands of fully-discrete 1D fluid and mass transport models are increasing due to the sheer number of blood vessels in imaged samples ($> \mathcal{O}(10^6)$). Moreover, difficulties such as boundary condition assignment arise when considering incomplete vascular networks which are acquired using a modality with a resolution higher than the size of some of the vessels. For example, photoacoustic imaging is an emerging modality which can image vascular structure and function *in vivo*[18] at a resolution of $30 - 40$ μm, and so is unable to monitor the smallest capillary vessels or spatially-resolved flows in individual vessels[19]. This leads to discontinuities in vascular network architecture which increases the number of boundary conditions that require accurate parameterisation. With these in mind, versatile mathematical models are required which are computationally tractable and can bridge the information gap for imaging modalities that cannot resolve vessels or functional parameters down to the micron-scale.

Mathematical homogenisation provides the opportunity to circumnavigate the problem of solving tissue-scale fluid and mass transport in the absence of complete vascular datasets (see Figure 1B). Vascular tissues are represented by a single or coupled continua and modelled as porous media via Darcy's equation[20–27]. For example, by assuming two well-separated capillary and tissue length scales, these models enable averaged predictions of pressure and velocity fields with reduced computational cost. However, several challenges remain in their application[28]. For instance, the range of hierarchical vascular structures may not be fully characterised by two length scales in isolation and assuming periodicity of small-scale structures may not be reasonable. Further, these models assume that networks are highly interconnected and so small-scale vessel pressures are correlated which may not be the case, depending on vascular topology. Thus, model parameters, such as the hydraulic conductivity in Darcy's equation, are difficult to estimate.

Numerous hybrid blood flow models have been formulated which embed larger individual (or discrete) vessels into a homogenised representation of the surrounding tissue[28–37]. These studies apply a 1D flow model to discrete vessels, coupled to a 3-dimensional (3D) porous medium Darcy model (see Figure 1C). As a consequence of explicitly

Figure 1: Blood flow modelling summary. (A) Vascular networks can be represented discretely by a series of nodes interconnected by segments each with a defined diameter and length. In healthy tissue, microvasculature can be classified in terms of (red) arterioles, (green) capillaries and (blue) venules. By assigning blood flow or pressures at boundary nodes, a 1D Poiseuille flow model can solved for internal nodal pressures and consequently segment flows. (B) Mathematical homogenisation can be used to predict tissue-scale blood flow using Darcy's law. Tissue hydraulic conductivity can be calculated using mathematical averaging techniques. (C) Hybrid models may improve prediction of blood flow heterogeneity across the tissue as discrete arteriolar and venular structures are retained and modelled in a discrete fashion, coupled to a (left) mesh or (right) our analytic Green's function method to solve for blood flow in the capillary continuum.

representing the hierarchical structure of larger branching vessels and therefore providing a better prediction of flow distribution in these vessels compared to an averaged description, hybrid models may provide a better prediction of blood flow heterogeneity in the homogenised domain. Typically, hybrid models solve for blood flow numerically using semi-analytic or fully finite mesh schemes [28,30,33,34,36,37]. However, as with fully-discrete blood flow models, these can be computationally intensive for large domains. To remove the need to resolve a mesh, analytical methods have been developed which couple discrete vessel structures with the Darcy continuum domain (representing the capillary bed) via point sources of flux solved using analytic Green's functions [29,35]. To date, this has only been achieved for 2-dimensional (2D) networks with the venular network represented by a single, spatially-homogeneous drainage term. Thus, a hybrid blood flow model is required which predicts flow in the discrete, larger arteriolar and venular structures, coupled to a 3D analytical Green's function solution for the homogenised capillary domain.

In this study, we develop a 3D hybrid discrete-continuum model for blood flow in microvascular networks. Blood pressure is modelled discretely (1D Poiseuille flow) in the arteriolar and venular branching networks and coupled to a continuum description of blood flow in the capillary bed via point sources of flux. Our continuum model utilises the model of Shipley [38] in the limiting case of no capillary leakage into the interstitium, reducing capillary flow to a single-phase Darcy model. We calculate the 3D capillary bed hydraulic conductivity tensor by local averaging of 3D synthetic, periodic micro-cell representations of the capillary vasculature, following established homogenisation approaches. We provide a Green's function-based solution for the averaged capillary blood pressure in 3D. Compared to similar approaches [29,35], we do not impose conservation of mass between terminal branches of arteriolar and venular

vessels, allowing for capillary flux at the tissue boundaries in the case where imaged vasculatures are a sub-volume of real-world networks.

Our model is intended for application in the case where the structure of branching arteriolar and venular vessels are largely known, whereas the discrete capillary network structure is unknown. In this study, we utilise a fully-resolved vascular network ($1.14 \times 1.14 \times 1.72 um$ μm^3 resolution) from the mouse cerebral medulla/pons to develop our methodology, although our approach is readily applicable to a range of microvascular tissues. By classifying the blood vessels of the discrete network into arterioles, capillaries and venules, we use the 3D structural information to generate synthetic micro-cells which, via local averaging, we use to estimate a 3D hydraulic conductivity tensor of the capillary bed. Next, we apply a 1D Poiseuille flow model to the fully-discrete medulla network to generate a blood pressure solution. Using the simulated predictions of capillary hydraulic conductivity and capillary boundary drainage (via the discrete flow solution) our hybrid, discrete-continuum model estimates vascular blood pressure across the capillary continuum. The resulting pressure solution is then benchmarked against the fully-discrete medulla prediction and the relative merits of each model's solution discussed. Finally, we perform sensitivity analysis of key parameters in our hybrid model to explore the role of pivotal structural (e.g., branching order) and functional (e.g., tissue hydraulic conductivity and far-field capillary pressure) parameters in influencing the discrete-continuum model predictions.

Methods

Animal model

All animal studies were licensed under the UK Home Office regulations and the Guidance for the Operation of Animals (Scientific Procedures) Act 1986 (Home Office, London, United Kingdom) and United Kingdom Coordinating Committee on Cancer Research Guidelines for the Welfare and Use of Animals in Cancer Research.

MF-HREM of Brain

Mouse brain were prepared as described in Walsh et al.[5]. Briefly, animals were administered with 200 μl Lectin (Tomato) bound to DyeLyte-649 (Vector UK) (1 mg/ml), administered via tail vein injection and allowed to circulate for 10minutes before euthanasia. Perfusion fixation was carried out, the brain removed, and prepared through a graded dehydration and resin embedding process[5].

MF-HREM images were collected with voxel size $0.57 \times 0.57 \times 1.72$ μm^3 allowing the entirety of the vascular network to be captured. Images were deconvolved using a diffraction kernel as specified in Walsh et al.[6]. The deconvolved images were downsampled to voxel sizes of $1.14 \times 1.14 \times 1.27$ μm^3 and segmented semi-manually in Amira v2020.2, using a magic wand tool. The segmentation was skeletonised using Amira autoskeletonise module (with distance thinning mode enabled) to provide a graph description of the vascular network. Here, vessels are

Figure 2: Structure of the vasculature in the mouse medulla. 3D visualisations of the medulla vasculature indicating (A) blood vessel diameters and (B) manually identified arteriolar and venular vessels. (C) Distributions of blood vessel diameters and lengths for arterioles, capillaries and venules in our dataset. Note, a full description of parameters are provided in Table 1.

represented by segments with a defined diameter and length, interconnected by nodes with defined 3D coordinates. A 3D volume of the skeleton was taken from the medulla/pons (located at the base of the brainstem - here on referred as the medulla) and used as the geometrical input into our mathematical model.

In the medulla, larger arteriolar and venular blood vessels penetrate through the tissue with intermediate vessels branching off[39]. A mesh of capillaries form from the intermediate vessels, connecting the arteriolar and venular branches. We classified vessels according to their type (arteriolar, venular, capillary - see Figure 2) enabling the capillary network to be removed, mimicking an imaging modality constrained by spatial resolution. This left the larger, branching arteriolar and venular networks as discretely-modelled structures in our hybrid approach.

Vessel classifications are not known *a priori* for the medulla dataset. As such, we pragmatically classified vessels based on vascular morphology[39]. Penetrating vessels were identified via visual inspection and intermediate branching vessels were located using a breadth-first search with a diameter threshold of 9 μm and all remaining vessels were labelled as capillaries (see Figure 2). Sensitivity of model predictions to the diameter threshold is explored in our results and a summary of the architectural information for the skeletonised vascular network, as well as vessel classifications, is provided in Table 1.

Simulating blood pressure using a 1D Poiseuille model requires boundary conditions at all the network boundaries. However, functional information for all boundaries, especially for high-resolution data, is rare. As a result, we initially introduce a 1D Poiseuille flow model for incomplete boundary conditions[40] which has been applied across a range of real-world tissues[4,11,17,41] and estimates unknown boundary data by matching to target mean pressure and shear stress across the network. We apply this model to predict blood pressure across the fully-discrete medulla network

Table 1: A summary of vascular network properties for the medulla network. Note, vascular density is defined as the ratio of network volume to tissue volume.

Metric	Value
Tissue Dimensions (mm^3)	$3.09 \times 2.33 \times 0.54$
Vascular Density (%)	3.10
No. of penetrating vessels	32
No. of branching vessels	90,176
No. of branch points (vertices)	73,175
No. of segments	319,534
No. of nodes	302,554
No. of boundary nodes	21,983
Mean vessel diameter (μm)	
Arterioles	11.11 ± 3.08
Capillaries	7.44 ± 2.49
Venules	11.08 ± 3.43
Mean vessel length (μm)	
Arterioles	37.91 ± 36.31
Capillaries	32.19 ± 24.96
Venules	43.96 ± 52.20

to generate our baseline pressure solution, as well as predict the flow distribution in branching vessels in our hybrid model.

Next, we present our hybrid model which predicts blood pressure in the homogenised capillary bed coupled to the discrete arteriolar and venular branches. To predict the resistance to flow through the capillary bed, we detail a 3D micro-cell problem to estimate hydraulic conductivity in synthetic networks[42,43]. This is followed by the computational implementation of the hybrid discrete-continuum model to predict the pressure distribution in microvascular tissue, in the absence of a spatially-resolved capillary network. Finally, we detail our methodology behind boundary condition and parameter assignment for our hybrid, discrete-continuum approach.

Discrete blood flow model

Vascular networks can be represented by a graph(s) consisting of an interconnected set of nodes, N, and segments, S. Defining a positive flow direction from the start node to end node of each vessel segment and conserving flow at blood vessel junctions, the relationship between nodal pressures, p_k, and the boundary boundary fluxes, Q_{0i}, is given by

$$\sum_{k \in N} K_{ik} p_k = -Q_{0i} \quad \text{for} \quad i \in I \cup B, \tag{1}$$

where I is the set of all interior nodes and B the set of boundary nodes with know flow conditions. If i is a boundary node with a known boundary condition, Q_{0i} is equal to a prescribed pressure or flow value (positive or negative

dependent on inflow or outflow, respectively) at node i. Network conductance to flow, K_{ik}, is defined as

$$K_{ik} = \sum_{j \in S} L_{ij} M_{jk} \quad \text{for} \quad i \in I \cup B \quad \text{and} \quad k \in N, \tag{2}$$

where

$$L_{ij} = \begin{cases} -1, & \text{if } i \text{ is the start node of segment } j, \\ +1, & \text{if } i \text{ is the end node of segment } j, \\ 0, & \text{otherwise,} \end{cases} \tag{3}$$

and

$$M_{jk} = \begin{cases} +\pi d_j^4 / (128 \mu_j l_j), & \text{if } k \text{ is the start node of segment } j, \\ -\pi d_j^4 / (128 \mu_j l_j), & \text{if } k \text{ is the end node of segment } j, \\ 0, & \text{otherwise.} \end{cases} \tag{4}$$

The variables l_j, d_j and μ_j denote the length, diameter and effective blood viscosity of segment j, respectively. In this study, we define blood viscosity, $\mu(d, H_d)$, as a function of vessel diameter and haematocrit, H_d, employing a commonly used empirically-derived blood viscosity law[44]. For simplicity, we assign a constant haematocrit value of 0.45, however, red blood cell phase separation can be incorporated[45] in future work.

When a set of boundary conditions are unknown, we formulate a constrained problem in terms of a Lagrangian objective function[40]

$$L = \frac{1}{2} k_p \sum_{k \in N} w_k (p_k - p_{0k})^2 + \frac{1}{2} k_\tau \sum_{j \in S} l_j (\tau_j - \tau_{0j})^2 + \sum_{i \in I \cup B} \lambda_i \left(\sum_{k \in N} K_{ik} p_k + Q_{0i} \right), \tag{5}$$

which seeks to minimise the deviation between target nodal pressure, p_{0k} and segment wall shear stresses, τ_{0j} subject to the assignment of weighting factors k_p and k_τ. Here, τ_j is the vessel wall shear stress for vessel j, λ_i is a Lagrange multiplier and w_k is a weighting factor, which summed over the length of segments j connected to node k.

Equation (1) and $dL/dp_i = 0$ can be combined into the following linear system:

$$\begin{bmatrix} \mathbf{K} & \mathbf{0} \\ k_\tau \mathbf{H} + k_p \mathbf{W} & \mathbf{K^T} \end{bmatrix} \begin{bmatrix} \mathbf{p} \\ \boldsymbol{\lambda} \end{bmatrix} = \begin{bmatrix} -\mathbf{Q_0} \\ k_p \mathbf{W} \mathbf{p_0} + k_\tau \mathbf{M^T} (\boldsymbol{\tau_0} \cdot \mathbf{c} \cdot \boldsymbol{l}) \end{bmatrix}, \tag{6}$$

where $\mathbf{K}$, $\mathbf{H}$, $\mathbf{W}$ and $\mathbf{M}$ denote the matrix forms of K_{ik}, H_{ik}, w_k and M_{ij}, respectively, noting $\mathbf{W}$ is a diagonal matrix with entries w_k; $\mathbf{p}$, $\boldsymbol{\lambda}$, $\mathbf{Q_0}$, $\mathbf{p_0}$, $\boldsymbol{\tau_0}$, $\mathbf{c}$ and $\boldsymbol{l}$ are the vector forms of p_k, λ_k, Q_{0i}, p_{0k}, τ_{0j}, c_j and l_j, respectively. Here, H_{ik} is defined as

$$H_{ik} = \sum_{j \in S} c_j^2 M_{ji} M_{jk} l_j \quad \text{where} \quad c_j = \frac{32 \mu_j}{\pi d_j^3} \quad \text{for} \quad i, k \in N. \tag{7}$$

The linear system (6) can be solved for unknowns p_i and λ_i using standard numerical methods. In the case where all boundary conditions are known, (1) is solved for all nodal pressures.

Continuum blood flow model

Our hybrid model incorporates Poiseuille's law to describe blood flow through arteriolar and venular branching structures, coupled to a volume-average description of blood velocity, $\mathbf{u}$ and pressure, p, within the capillary continuum domain[38] (see Figure 1C). The coupling occurs via points sources of flux located at the terminal branches of the discrete vasculature and feeding into the continuum capillary domain.

Arteriolar and venular networks can supply or drain neighbouring tissues and so if a sub-region of tissue is imaged, it is likely that adjoining tissue will supply / drain fluid in the image sub-region. To emulate this, we retain a drainage term whose rate is not known *a priori*. As such, conservation of mass of the continuum domain yields

$$-\nabla \cdot (\boldsymbol{\mathcal{K}} \cdot \nabla p) = -\beta (p - p_c) + \sum_{j \in N_s} \varphi_j(\mathbf{x})\delta(\mathbf{x} - \mathbf{x}_j), \tag{8}$$

where $\boldsymbol{\mathcal{K}}$ is the hydraulic conductivity of the capillary network, p_c is a constant far-field pressure, β is the rate of capillary fluid drainage into neighbouring tissues, N_s is the set of sources of flux into the continuum domain, and $\mathbf{x}_j$ and φ_j are the spatial coordinates and strength of source j, respectively.

Equation (8) is subject to the condition that

$$p \to p_c \quad \text{as} \quad |\mathbf{x}| \to \infty, \tag{9}$$

whereby it is assumed that the continuum pressure tends to a constant value, p_c.

Hydraulic conductivity, $\boldsymbol{\mathcal{K}}$, is a 3×3 anisotropic tensor where we assume $\mathcal{K}_{ij} \ll \mathcal{K}_{ii}$ for $i, j = 1, 2, 3$ for $i \neq j$[23,28]. By setting $\mathcal{K}_{11} = \kappa$, $\mathcal{K}_{22} = \kappa a^2$ and $\mathcal{K}_{33} = \kappa b^2$ we can introduce the linear transformation $(\tilde{x}, \tilde{y}, \tilde{z}) = (x, y/a, z/b)$ which reduces (8) to

$$-\kappa \nabla^2 p = -\beta (p - p_c) + \sum_{j \in N_s} \varphi_j(\tilde{\mathbf{x}})\delta(\tilde{\mathbf{x}} - \tilde{\mathbf{x}}_j), \tag{10}$$

which is subject to $p \to p_c$ as $|\tilde{\mathbf{x}}| \to \infty$. The solution to (10) is given by

$$p(\tilde{\mathbf{x}}) = p_c + \int_V \sum_{j \in N_s} G(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}_j)\varphi_j(\tilde{\mathbf{x}}_j)dV, \tag{11}$$

where V the volume of the tissue and $G(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}_j)$ is a Green's function which can be found by solving the adjoint problem:

$$-\kappa \nabla^2 G + \beta G = \delta(\tilde{\mathbf{x}} - \tilde{\mathbf{x}}^*),$$
$$G \to 0 \quad \text{as} \quad |\tilde{\mathbf{x}}| \to \infty. \tag{12}$$

Seeking a 3D, analytical representation of (12), we approximate $G(\tilde{\mathbf{x}}, \tilde{\mathbf{x}}^*)$ by distributing the delta function uniformly over a sphere of finite radius, r_0. Considering a single source with local axisymmetric fluid flux, an

axisymmetric spherical coordinate system is used whereby $r = 0$ corresponds to the source centre. Consequently, we seek the Green's function solution, $G(r)$, for the system

$$-\frac{\kappa}{r^2}\frac{d}{dr}\left(r^2\frac{dG}{dr}\right) + \beta G = \begin{cases} 3/4\pi r_0^3, & \text{for} \quad r \leq r_0 \\ 0, & \text{for} \quad r > r_0 \end{cases},$$
(13)

$$G \to 0 \quad \text{as} \quad r \to \infty,$$

where the factor $3/4\pi r_0^3$ ensures unity when integrating $\delta(\tilde{\mathbf{x}} - \tilde{\mathbf{x}}^*)$ over the source volume. By ensuring continuity of $G(r)$ and $G'(r)$ at the interface $r = r_0$, and that G is finite in the limit $r \to 0$, we arrive at the solution

$$G(r) = \begin{cases} C_1 i_0(\lambda r) + 3/4\pi r_0^3\beta, & \text{for} \quad r \leq r_0 \\ C_2 k_0(\lambda r), & \text{for} \quad r > r_0 \end{cases},$$
(14)

where i_0 and k_0 are the zeroth- order modified spherical Bessel functions of the first and second kinds, respectively,

$$\lambda = \sqrt{\frac{\beta}{\kappa}},$$
(15)

$$C_1 = -\frac{3}{4\pi r_0^3\beta} \cdot \frac{k_1(\lambda r_0)}{i_1(\lambda r_0)k_0(\lambda r_0) + i_0(\lambda r_0)k_1(\lambda r_0)},$$
(16)

and

$$C_2 = \frac{3}{4\pi r_0^3\beta} \cdot \frac{i_1(\lambda r_0)}{i_1(\lambda r_0)k_0(\lambda r_0) + i_0(\lambda r_0)k_1(\lambda r_0)}.$$
(17)

We note that if blood pressure is modelled in an isolated tissue volume where flow is conserved between the branching structures, $\beta = 0$ and so (13) reduces to the model of Sweeney et al.[17] for vascular and interstitial fluid transport. See Supplementary Material for further details.

Computational implementation of the discrete-continuum model

Here we outline the numerical implementation to predict the hydraulic conductivity of the capillary bed and capillary continuum pressure using our discrete-continuum model. A summary of the hybrid model, (6) to (17), is presented in Figure 3.

Hydraulic conductivity of capillary tissue

Hydraulic conductivity is a tissue-specific parameter in our model which captures the resistance to flow in the capillary continuum domain. We calculate hydraulic conductivity by solving a micro-cell problem defined on 3D synthetic and periodic sub-units which are generated by sampling key features (such as diameters, lengths and connectivity) of the medulla capillary network. We average the micro-cell flow velocities, (18) to (28), on our synthetic, periodic

Figure 3: The discrete-continuum pipeline to solved for capillary bed pressure. (Top row) The discrete network matrix, $\mathbf{M}^{net}$, is populated by solving for discrete nodal pressures. (Bottom row) Capillary continuum source pressures found by solving the linear system, (34), (indicated by the dashed arrow). Conserving mass via optimisation of the capillary drainage parameter, β, ensures fluid drainage by neighbouring tissue is accurately calculated when validating against experimental, or in our case computational, methods.

architecture to calculate hydraulic conductivity tensors which describe how micro-scale flow properties are transmitted to the macro-scale of the medulla. First we provide a generalised description of solving the micro-cell problem in 3D, then our synthetic micro-cell generation method.

By assuming well-separated microscopic and macroscopic tissue length-scales, asymptotic homogenisation theory can be used to derive a system which averages microscopic capillary-scale flow to describe macroscopic tissue-scale fluid transport[38]. An analytical solution to the multi-scale, micro-cell problem can be found by assuming non-leaky vessels, no-slip and no-flux at the capillary walls, which provides an expression for cell flux $\mathbf{q}_m^j$ (μm^5 s kg^{-1})[42]:

$$\mathbf{q}_j^i = -\frac{\pi d_j^4}{128\mu_j}\left(\frac{\Delta P_j^i}{l_j} - \mathbf{e}_i \cdot \mathbf{e}_j\right)\mathbf{e}_j, \quad \text{for} \quad i = 1, 2, 3. \tag{18}$$

Here, d_j, l_j and μ_j are the diameter, length and blood viscosity (calculated empirically[44]) for capillary j, respectively, ΔP_j^i is micro-cell pressure gradient along the vessel length, $\mathbf{e}_i$ is the unit vector aligned with the capillary centreline and $\mathbf{e}_j$ is the principal direction.

Equation (18) is composed of a linear superposition of contributions proportional to the tissue-scale pressure gradient in each principal direction, $\mathbf{e}_j$. The following details how a periodic boundary value problem is formed in terms of capillary-scale variations in flow, $\mathbf{q}^i$, and pressure, P^j, over periodic micro-cells, enable the weightings of these contributions to be solved. Similar approaches have been used to calculate hydraulic conductivity for rat myocardium[46], human cerebral cortex[23] and rat mesentery[35].

Equation (18) can be rewritten in terms of micro-cell pressure at node k,

$$\mathbf{q}_j^i = -\frac{\pi d_j^4}{128\mu_j}\left(\sum_{k \in N} A_{jk} P_k^i - \mathbf{e}_i \cdot \mathbf{e}_j\right)\mathbf{e}_j, \tag{19}$$

where P_k^i is the micro-cell pressure at node k, N is the set of all nodes and

$$
A_{jk} = \begin{cases} +1/l_j & \text{if } k \text{ is the start node of segment } j, \\ -1/l_j & \text{if } k \text{ is the end node of segment } j, \\ 0 & \text{otherwise.} \end{cases} \tag{20}
$$

To solve for micro-cell flux and consequently micro-cell hydraulic conductivity, conservation of micro-cell flux, periodic Dirichlet boundary conditions for pressure and flux, and volume average of cell pressures equal to zero are enforced across the micro-cell.

Conservation of cell flux at nodes $m \in I$, where I is the set of interior nodes yields

$$
\sum_{j \in S} B_{mj} \frac{\pi d_j^4}{128 \mu_j} \left(\sum_{k \in N} A_{jk} P_k^i - \mathbf{e}_i \cdot \mathbf{e}_j \right) \mathbf{e}_j = 0 \quad \text{for} \quad m \in I, \tag{21}
$$

where S is the set of all segments and B_{mj} is defined as

$$
B_{mj} = \begin{cases} -1 & \text{if } m \text{ is the start node of segment } j, \\ +1 & \text{if } m \text{ is the end node of segment } j, \\ 0 & \text{otherwise.} \end{cases} \tag{22}
$$

Separating boundary nodes into two sets, B_{in} and B_{out}, where a node in B_{in} is paired with the node in B_{out} at the opposite side of the micro-cell, we impose periodic pressure boundary conditions via

$$
\sum_{k \in N} D_{mk} P_k^i = 0 \quad \text{for} \quad m \in B_{in}, \tag{23}
$$

where

$$
D_{mk} = \begin{cases} +1 & \text{if } k \text{ is the } m^{th} \text{ node in } B_{in}, \\ -1 & \text{if } k \text{ is the } m^{th} \text{ node in } B_{out}, \\ 0 & \text{otherwise.} \end{cases} \tag{24}
$$

Similarly, for periodicity of flux, vessel flux leaving the m^{th} node of B_{out} is equal to the flux entering the m^{th} node of B_{in},

$$
\sum_{j \in S} E_{mj} \frac{\pi d_j^4}{128 \mu_j} \left(\sum_{k \in N} A_{jk} P_k^i - \mathbf{e}_i \cdot \mathbf{e}_j \right) \mathbf{e}_j = 0 \quad \text{for} \quad m \in B_{in}, \tag{25}
$$

where

$$
E_{mj} = \begin{cases} +1 & \text{if segment } j \text{ is connected to the } m^{th} \text{ node in } B_{in}, \\ -1 & \text{if segment } j \text{ is connected to the } m^{th} \text{ node in } B_{out}, \\ 0 & \text{otherwise.} \end{cases} \tag{26}
$$

Finally, to ensure a unique solution, the volume average micro-cell pressure is defined to be zero:

$$\frac{1}{|\Omega|}\frac{\pi}{8}\sum_{j\in S}l_j d_j^2 \left(\sum_{k\in N}F_{jk}P_k^i\right)=0,\tag{27}$$

where

$$F_{jk}=\begin{cases}1 & \text{if } k \text{ is the start or end node of segment } j,\\ 0 & \text{otherwise.}\end{cases}\tag{28}$$

Equations (20) to (28) form three linear system of equations which can be solved for micro-cell nodal pressures P_k^i and consequently cell flux, (19). The hydraulic conductivity matrix $\boldsymbol{\mathcal{K}}=\left[\boldsymbol{\mathcal{K}}^1|\boldsymbol{\mathcal{K}}^2|\boldsymbol{\mathcal{K}}^3\right]$ (mm^{3}s/kg) is then calculated via,

$$\boldsymbol{\mathcal{K}}^i=\frac{1}{|\Omega|}\sum_{j\in S}\mathbf{q}_j^i l_j,\tag{29}$$

where Ω is the volume of the micro-cell and components $\mathcal{K}_{1j}^i$, $\mathcal{K}_{2j}^i$ and $\mathcal{K}_{3j}^i$ for $j=1,2,3$ represent the volume-averaged flow in the $\mathbf{e}_1$, $\mathbf{e}_2$ and $\mathbf{e}_3$ directions, respectively, due to forcing in the $\mathbf{e}_i$-direction.

Generating 3D synthetic micro-cells

Key structural characteristics that influence perfusion in microvascular networks are vessel diameter and length, connectivity and vascular density (the network volume fraction with respect to tissue volume). Here, we define our methodology to generate 3D synthetic micro-cells which are representative of capillary vasculature by capturing these key attributes. For the medulla, we extract structural parameters of capillary networks directly from the fully-resolved network. In doing so, we approximate hydraulic conductivity for the medulla capillary bed which these sub-units represent.

1. A 3D cuboidal grid lattice with dimensions $1\times 1\times 1\ \mu$m^2. We arbitrarily chose a lattice with 5×5 boundary nodes on each face of the lattice and $5\times 5\times 5$ internal nodes, each of which interconnected by vessel segments (see Supplementary Figures).

2. To ensure physiological connectivity across the vessel lattice, and consequently physiological tissue perfusion, vessels were randomly removed until all nodes have a maximum of three vessel connections. Boundary vessels were exempt from removal to ensure boundary periodicity is maintained.

3. Vessels aligned with each axis were uniformly stretched in each dimension by factors randomly sampled from a log-normal distribution with mean and standard deviation for capillary lengths obtained from the medulla network. Similarly, diameters were individually sampled from known mean and standard deviation values.

4. Medulla vascular density was calculated to be 3.1%, and so if micro-cell vascular density is outside the interval $3.0\pm 0.5\%$, step (3) is repeated.

²⁵¹ Micro-cell hydraulic conductivity for a defined geometry is calculated using (29). Given micro-cell network

²⁵² generation is stochastic, steps (3) and (4) were repeated for a total of 10^3 iterations, and average tensor components

²⁵³ calculated.

²⁵⁴ Capillary continuum blood pressure

²⁵⁵ To calculate the continuum pressure field, we assume that the pressures at the inlet/outlet of the discrete arteriolar

²⁵⁶ and venular trees, $\mathbf{p}^{base}$, and the far-field capillary pressure, p_c are known. The vector $\mathbf{p}^{base}$ is of length N_s where

²⁵⁷ source i is assigned the base pressure of its respective vascular tree. From (11), the source pressure, p_i^s, of source i at

²⁵⁸ location $\tilde{\mathbf{x}}_i$ is given by

$$p_i^s = p_c + \sum_{j \in N_s} M_{ij}^{cap} q_j^s \quad \text{for} \quad i \in N_s. \tag{30}$$

²⁵⁹ where

$$M_{ij}^{cap} = G(r_{ij}) \quad \text{and} \quad r_{ij} = |\tilde{\mathbf{x}}_i - \tilde{\mathbf{x}}_j|, \tag{31}$$

²⁶⁰ and q_i^s is the flow rate of source i.

²⁶¹ The discrete blood flow model is used to calculate the pressures at nodes of the partial discrete networks as a

²⁶² function of the unknown flow conditions at the interface between the discrete and continuum domains:

$$p_i^s = p_i^{base} - \sum_{j \in N_s} M_{ij}^{net} q_j^s \quad \text{for} \quad i \in N_s, \tag{32}$$

²⁶³ where the matrix $\mathbf{M}^{net}$ characterises the pressure-flow relationship across the discrete networks.

²⁶⁴ The set of source nodes includes capillary side branches of the vascular trees. Following Shipley et al.[35], in order

²⁶⁵ for all source points to be terminal branches of their respective discrete network, dummy segments of 1 μm length

²⁶⁶ and diameter equal to the minimum diameter of its corresponding vascular tree were added. Then we perform a

²⁶⁷ sequence of $i \in N_s$ discrete flow calculations to populate M_{ij}^{net} using (1)-(4). In each case, the following boundary

²⁶⁸ conditions are applied: 1) if a node is a boundary node for the fully-discrete network (i.e., at the tissue boundary),

²⁶⁹ the boundary condition on pressure or flow for the full network is imposed, or if unknown, approximated using (6);

²⁷⁰ 2) the flow at source node j when $i = j$ is set to ± 1 nl/min, where the positive / negative sign indicates whether the

²⁷¹ source belongs to an arteriole of venule, respectively, and zero for $i \neq j$, so that (30) gives

$$M_{ij}^{net} = \left| p_j^{base} - p_j^s \right|. \tag{33}$$

²⁷² Combining the pressure solutions for (30) and (32) yields

$$\sum_{j \in N_s} \left(M_{ij}^{net} + M_{ij}^{cap} \right) q_j^s = p_i^{base} - p_c, \tag{34}$$

Table 2: A summary of the parameter descriptions for the 3D discrete-continuum model and corresponding values for the medulla. Structural and flow-based parameters are assigned to calculate capillary continuum pressure. Optimisation-based parameters are fine-tuned to ensure flow conservation.

Structure-based parameters	Description	Medulla
$N_{s,b}$	No. of arteriolar / venular boundary sources	219
$N_{s,d}$	No. of capillary side branch sources	271
$\mathbf{r}_0$ (μm)	Source radii	18.0 ± 16.1
κ (mm^3 s/kg)	Conductivity scalar of capillary bed	9.54×10^{-4}
Flow-based parameters		
p_c (mmHg)	Far-field capillary pressure	40.7
$\mathbf{p}^{base}$ (mmHg)	Base pressures of discrete trees	20.2 / 59.8
Optimisation-based parameters		
β (μm s/kg)	Rate of capillary drainage	7.22×10^{-7}
λ (1/μm)	$\sqrt{\beta/\kappa}$	8.70

which can be solved for source strengths, $\mathbf{q}^s$.

Boundary Conditions & Parameter Values

No flow or pressure information paired with the medulla dataset was obtained to parameterise either the fully-discrete or our hybrid model. Consequently, pressure boundary conditions at the bases of the arteriolar and venular trees were set using simulated cortex pressure-diameter curves from the literature[9,10]. Vessel haematocrit was uniformly set to a value of 0.45. Based on previous studies, target blood pressure, $\mathbf{p}_0$, and vessel wall shear stress, τ_0 were uniformly set to 31 mmHg and 5 dyn/cm^2, respectively[11]. Following the Fry et al.[40] flow optimisation scheme, k_p was set to a value of 0.1 and a final k_τ value of 7.21×10^{12} was found.

Parameter descriptions for the discrete-continuum model alongside values for the medulla network are provided in Table 2. Source radii were set to the half-distance to the nearest neighbouring source so all sources act independently when solving for continuum pressure. The pressure solution of the fully-discrete network was used to parameterise base pressures, $\mathbf{p}^{base}$, and non-source, terminal boundaries conditions. Similarly, the fully-discrete pressure solution was used to set the far-field capillary pressure, p_c, to 40.2 mmHg. Sensitivity analysis to test the influence of $\mathbf{r}_0$ and p_c on model predictions are also performed by increasing and decreasing thresholds.

With a predicted value for κ, a root-finding algorithm was used to compute β, and hence λ, by minimising the difference between the sum of source fluxes from the fully-discrete and hybrid pressure solutions (see Supplementary Material). Once source fluxes are found, pressure contour plots can be generated by computing (32) at grid points in the untransformed (x, y, z) domain. To enable comparison between the fully-discrete flow solution, we use the hybrid solution to predict nodal pressures at the spatial location of all nodes in the fully-discrete network.

Figure 4: Micro-cell and discrete flow solutions. (A, B, C) Exemplar simulated micro-cell pressures for each principal direction $i = 1, 2, 3$ for x, y and z, respectively, used to estimated capillary hydraulic conductivity. Blood flow is simulated through the medulla using the fully-discrete model with predicted distributions of blood (D) pressure, (E) flow and (F) absolute velocity shown. Note, distributions in (E) and (F) are shown in a log scale.

Results

Estimating hydraulic conductivity of the medulla capillary bed A total of 10^3 synthetic vascular micro-cells, characteristic of capillary networks in the medulla, were generated. For each periodic sub-unit, blood pressure was simulated (see Figure 4A-C) and hydraulic conductivity calculated using (29). Our computed averaged hydraulic conductivity tensor is given by

$$\mathcal{K} = \begin{pmatrix} 9.54 & 0.03 & 0.02 \\ 0.03 & 9.48 & 0.06 \\ 0.01 & 0.06 & 9.44 \end{pmatrix} \times 10^{-4} \mathrm{mm}^3 \mathrm{s/kg}. \tag{35}$$

The diagonal components of the tensor are larger than the off-diagonal components thereby satisfying our assumption which enabled us to linearly transform the capillary continuum in (10). This result is consistent with previous estimates of hydraulic conductivity for the cortex[23] and myocardium[46]. By introducing the linear scalings $a = 0.997$ and $b = 0.995$ where $y = a\tilde{y}$ and $z = b\tilde{z}$, we reduce hydraulic conductivity to a scalar $\kappa = 9.54 \times 10^{-4}$ mm^{3}s/kg in the transformed coordinate system. We note that the scalings $a \approx b \approx 1$ is expected due to the stochastic method used to generate our synthetic micro-cells.

Discrete, complete network predictions Arteriolar, venular and capillary pressures were predicted to be

44.63 ± 5.04 mmHg, 31.37 ± 5.34 mmHg and 40.70 ± 3.03 mmHg, respectively (mean ± standard deviation - see

Figure 4D-F). To our knowledge, no experimental or computational predictions of microcirculatory blood pressure

in the mouse medulla are available; however, our simulations are consistent with prior studies of the cortex[9–12].

Additionally, minimum and maximum capillary pressures are within tolerances expected based on arteriolar and

venular boundary condition assignment (see Table 3).

Hybrid modelling of blood pressure in the medulla Continuum predictions of capillary blood pressure in

the medulla were simulated using the parameters given by Table 2. With a hydraulic conductivity of $\kappa = 9.54 \times 10^{-4}$

mm^{3}s/kg, the Green's parameter λ was optimised to a value of 8.7 μm^{-1} with a rate of capillary drainage of

$\beta = 7.22 \times 10^{-7}$ μm s kg^{-1}, indicating very low levels of vessel flux across the tissue boundaries.

The hybrid model calculated blood pressure at sources of 44.4 ± 3.41 mmHg and 33.8 ± 3.03 mmHg, for arterioles

and venules, respectively, which are consistent with values calculated from the discrete model (see Table 2). Further,

the hybrid and discrete model blood pressure predictions were strongly correlated for both arteriolar (Spearman cor-

relation: $r = 0.950$ with $P < 0.0001$) and venular (Spearman correlation: $r = 0.891$ with $P < 0.0001$) sources, with

pressures weighted towards the far-field capillary pressure, $p_c = 40.7$ mmHg. Compared to the fully-discrete predic-

tions, the pressure difference of arteriolar sources increased particularly for those with pressure smaller than p_c (see

Figure 5A). In comparison, venular source pressures exhibited increasingly larger errors for nodes with decreasingly

lower pressures computed in the discrete model (see Figure 5B).

Once source pressures were computed, blood pressure was estimated across the entire capillary continua (see

Figure 5C) which allowed our hybrid model estimates of blood pressure to be mapped onto the fully-discrete network

(see Figure 5D,E). This enabled a comparison between blood pressures at all nodal locations of the fully-discrete

network between the hybrid and discrete models. Whilst similar nodal pressure distributions were observed (see

Figure 5F), there was a significant difference between the two models (Wilcoxon test: $P < 0.0001$) due to the heavy

weighting towards the far-field capillary pressure in the hybrid model.

Blood pressure sensitivity to hybrid model parameters Sensitivity analyses of hybrid model predictions

were performed to assess the impact of key parameters. We focus on source pressures as an indicitive metric. Unless

stated otherwise, statistical significance ($P < 0.05$) compared to the baseline hybrid solution is calculated using a

Table 3: Predicted pressures (mean ± standard deviation) for the discrete and hybrid models applied to the medulla network.

Simulated Pressures (mmHg)	Discrete	Hybrid
Arteriolar Pressure	44.63 ± 5.04	-
Venular Pressure	31.37 ± 5.34	-
Capillary Pressure	40.70 ± 3.03	40.09 ± 2.035
Min. / Max. Capillary Pressure	20.88 / 56.47	19.32 / 55.65
Arteriolar Source Pressure	-	44.40 ± 3.41
Venular Source Pressure	-	33.80 ± 3.03

Figure 5: Hybrid blood pressure predictions in the mouse medulla. Discrete versus hybrid blood pressure predictions at (A) arteriolar and (B) venular point source locations. Distributions of hybrid source pressures for each vessel type are also illustrated. (C) Discrete-continuum model predictions of blood pressure in a 2D slice through the medulla. Here, arterioles, venules and capillaries are shown in red, blue and green, respectively. (D) A 2D intensity projection of the fully-resolved medulla network with continuum blood pressure predictions mapped onto the discrete vessels. (E) Associated absolute blood flow predictions. (F) Frequency distributions of blood pressures in the discrete and hybrid models at nodal locations in the fully-discrete medulla network. 2D intensity projections of the continuum blood pressure predictions mapped onto the fully-resolved medulla for (G) far-field capillary pressure, p_c, and (H) source radii, r_0, sensitivity analyses.

Kruskal-Wallis test.

First, we tested how sensitive the simulated source pressures are to an arbitrary $\pm 10\%$ change of magnitude to the hydraulic conductivity scalar, κ. No significant difference was found for either arteriolar or venular sources when modifying this parameter, which indicates that the model is not susceptible to subtle changes in hydraulic conductivity (see Figure 6A). However, we noted that during testing, order of magnitude differences can significantly impact the simulated pressure distribution in the capillary bed which can result in a homogeneous or unphysiological pressure distributions.

Next, we perturb the far-field capillary pressure, p_c, by $\pm 10\%$ (see Figure 5G). Increasing p_c resulted in a significant decrease in venular pressures whereas no significant change was observed for arteriolar sources (see Figure 6B). In comparison, decreasing p_c widened the range of arteriolar source pressures, whereas venular sources exhibited a significant increase in simulated pressures. This is a consequence of optimising the drainage parameter, β, to satisfy a known tissue flux, subject to the pressure range dictated by the pressures at the bases of the arteriolar and venular trees. In both cases, β-optimisation terminated outside of defined tolerances, with flow errors of 328.1 nl/min and -377.9 nl/min for $+10\%$ and -10% changes, respectively. This indicates that this parameter needs to be carefully parameterised in order to the reduce the relative conservation of mass error compared to the fully-discrete pressure solution.

For the baseline hybrid pressure (pre-sensitivity analysis) solution, each source radius was set equal to the half-distance to its closest neighbour. We found that decreasing these radii resulted in an unintuitive response to β. For example, distances of 25% and 10% relative to the closest neighbour, resulted in β values of 1.20×10^{-7} $\mu\mathrm{m}\,s\,\mathrm{kg}^{-1}$ and 0.98×10^3 $\mathrm{mm}\,s\,\mathrm{kg}^{-1}$. For the latter case arteriolar and venular source pressures exhibited a significant shift towards $p_c = 40.7$ mmHg (see Figure 5H). This may indicate that radii passed a critical threshold whereby the capillary drainage term needed to compensate for the lack of flow transfer between arterioles and venules, due to large decreases in the pressure gradient between neighbouring sources (see Figure 6C). In comparison, for radii set to the quarter-distance, arteriolar source pressures shifted towards the far-field pressure. However, a response of similar magnitude was not observed for the venules, which may indicate that arterioles are be more susceptible to this parameter due to larger pressure gradients on the arteriolar side of the vascular hierarchy.

The final parameter we investigated was the minimum diameter threshold which was used to define the minimal cut-off of discrete vascular tree branches. Increasing the threshold from 9 μm to 10 μm resulted in a a non-significant change in arteriolar source pressures. However, venular source pressures exhibited a significant widening in distribution (see Figure 6D). By comparison setting the threshold to 8 μm resulted in significant shifts in both the arteriolar ($P < 0.05$) and venular ($P < 0.0001$) pressures. In the case of arterioles, minimum source pressure was approximately equal to p_c which may be expected, as lowering the threshold increases correlation with the fully-discrete solution by allowing the hybrid model to incorporate more architectural heterogeneity. This would enable the discrete arteriolar networks to contain a greater portion of the pressure gradient. Comparatively, the change in venular distributions

³⁶⁴ may be a product of a decrease in proximity to arteriolar sources as a result of a greater number of discrete branching

³⁶⁵ orders. This may allow for lower venular source pressures at some locations.

³⁶⁶

Figure 6: Sensitivity analysis to the hybrid model parameters. Source pressures solved using the hybrid model are plotted against nodal pressures at equivalent locations solved using the discrete model, with inset

hybrid source pressure distributions. (A) Sensitivity to hydraulic conductivity scalar, κ, for a 10% (left) increase or (decrease) in magnitude. (B) Sensitivity to the far-field pressure, p_c for a 10% (left) increase or (decrease) in magnitude. (C) Sensitivity to the source radii $\mathbf{r}_0$ where each radius is set to (left) 10% or (right) 25% of the maximum distance to its nearest neighbour. (D) Sensitivity to the branching generation diameter threshold. Discrete branching vessels with a minimum diameter of (left) 8 μm and 10 μm are tested. Note, arterioles are shown in red and venules in blue.

Discussion

The simultaneous measurement of blood pressure, flow and vascular structure *in vivo* is practically infeasible throughout whole tissues down to the microvascular resolution. This therefore motivates the development of mathematical models that can take vascular structures derived from biomedical images as inputs, predict fluid transport, and provide biological insights that are otherwise inaccessible. Several micron-scale imaging modalities exist which can extract complete vascular networks; however, the increasing size of these networks presents computational challenges for standard blood flow models. Moreover, some imaging modalities fail to retrieve the full detail of networks, particularly at the capillary scale, which limits applicability to standard discrete mathematical models.

Motivated by these limitations, we developed a hybrid discrete-continuum model to simulate blood pressure across incomplete 3D microvascular networks, extending upon prior 2D hybrid models[29,35]. Our multiscale method models 1D Poiseuille flow through discrete branching arteriolar and venular structures, coupled to a single-phase Darcy model to estimate blood pressure through a continuum capillary bed. These discrete and continuum domains are connected via point sources of flux using an analytic Green's function approach. Our model has two key tissue-specific parameters to effectively predict tissue blood pressure. Firstly, hydraulic conductivity in Darcy's equation is approximated by local averaging of the capillary bed, by solving capillary flow through 3D, periodic and synthetically generated mico-cells[21,29]. Secondly, conservation of mass between discrete branching structures is not imposed which allows for capillary flux at the tissue boundary. This rate of capillary flux is optimised against a known value of flow between the arteriolar and venular branches.

We apply our hybrid methodology to a complete vascular network from a mouse medulla, imaged using MF-HREM. Initially we simulated a baseline blood pressure solution with a standard 1D Poiseuille model across the fully-discrete medulla vasculature. Next, we retrospectively classified blood vessels in terms of arterioles, capillaries and venules which enabled us: 1) to quantify capillary structure in order to create medulla-specific micro-cells and predict the hydraulic conductivity of the medulla; 2) to provide discrete arteriolar and venular branching vessels for input into the hybrid model; and 3) an approximation of the capillary flow drainage at the tissue boundaries. Using these data and parameter estimations, we simulated blood pressure across the capillary bed and mapped the continuum solution back onto the discrete capillary network to directly compare the hybrid model versus the

fully-discrete blood pressure solution.

Our baseline hybrid capillary solution emulated pressure distributions observed in its fully-discrete counterpart. This highlights the power of the hybrid model to estimate physiological blood pressure distribution in the capillary bed in the absence of complete architectural data. Next we sought to understand how sensitive the model is to variance in a range of model parameters. In the first instance we targeted our estimation of medulla hydraulic conductivity. No experimental or computational value exists for the medulla in the literature, however, our initial approximation matched the order of magnitude for values found for other tissues[23,46]. Artificially modifying hydraulic conductivity by $\pm 10\%$ did not result in significant differences in capillary pressure. Nevertheless, tests of our model indicate order of magnitude differences can result in unphysiological blood pressure predictions.

Next, we altered the far-field capillary pressure and found that this is a key parameter when optimising for capillary drainage, as incorrect assignment can significantly reduce the accuracy of flow conservation between arterioles and venules. In contrast, reducing the size of source radii still enabled drainage optimisation to converge; however, it caused local pressure gradients at each source to decrease. This results in a uniform pressure gradient across the capillary bed. Finally, we investigated the impact of retaining more structural arteriolar and venular architecture on the discrete-side of our model. By representing more vessels in a discrete fashion our hybrid model was better able to capture capillary pressure heterogeneity.

Here, we used the fully-discrete pressure solution as a gold standard to compare our hybrid model simulations against, despite it being an approximation. Nonetheless, our comparisons with the fully-discrete model provided insights into some limitations of the hybrid approach. The continuum representation of the capillary bed tended to smooth distributions towards the far-field capillary pressure. As a result, the hybrid model predicts lower levels of heterogeneity in pressure compared to the discrete model. This naturally presents several avenues to improve the modelling methodology. For example, the pressure field around each point source of flux into the continuum could be compartmentalised into several regions to better capture the pressure gradients in these regions[28]. Further, constant values for the far-field capillary pressure and tissue hydraulic conductivity are an oversimplification, and so improved boundary conditions or spatially heterogeneous hydraulic conductivity could better approximate capillary pressure variability. Finally, capillary drainage is parameterised by a flow balance calculated from the fully-discrete pressure solution. This is not practical in the experimental sense and so requires parameterisation via other means, such as perfusion MRI.

Conclusion

In summary, hybrid discrete-continuum models continue to present a promising and computationally-tractable approach to approximating the functionality of the microcirculation when limited structural information is available. Such models could prove complementary to *in vivo* experimentation which currently cannot observe tissue structure

and transport across entire vascular networks, in particular for the smallest vessels.

Acknowledgements

The authors also acknowledge support received from EPSRC (EP/L504889/1), Rosetrees Trust/Stoneygate Trust (M135-F1 and M601), the Wellcome Trust (WT100247MA) and Cancer Research UK (C44767/A29458).

Author Contributions

Conceptualisation: PWS, RJS. Methodology: PWS, RJS. Software: PWS. Validation: PWS. Formal Analysis: PWS. Investigation: PWS. Resources: PWS, CW, SWS, RJS. Data Curation: PWS, CW. Writing - original draft: PWS, RJS. Writing - review & editing: PWS, CW, SWS, RJS. Visualisation: PWS. Supervision: RJS. Project Administration: PWS, RJS. Funding Acquisition: PWS, CW, SWS, RJS.

References

[1] Roger I Grant, David A Hartmann, Robert G Underly, Andrée Anne Berthiaume, Narayan R Bhat, and Andy Y Shih. Organizational hierarchy and structural diversity of microvascular pericytes in adult mouse cortex. *Journal of Cerebral Blood Flow and Metabolism*, pages 1–15, 2017. ISSN 15597016. doi: 10.1177/0271678X17732229. URL http://journals.sagepub.com/doi/pdf/10.1177/0271678X17732229.

[2] Timothy W Secomb. Hemodynamics. *Comprehensive Physiology*, 6(2):975–1003, 1 2016. ISSN 2040-4603. doi: 10.1002/cphy.c150038.

[3] T.W. Secomb, R. Hsu, M.W. Dewhirst, B. Klitzman, and J.F. Gross. Analysis of oxygen transport to tumor tissue by microvascular networks. *International Journal of Radiation Oncology*Biology*Physics*, 25(3):481–489, 2 1993. ISSN 03603016. doi: 10.1016/0360-3016(93)90070-C.

[4] Angela D'Esposito, Paul W. Sweeney, Morium Ali, Magdy Saleh, Rajiv Ramasawmy, Thomas A. Roberts, Giulia Agliardi, Adrien Desjardins, Mark F. Lythgoe, R. Barbara Pedley, Rebecca Shipley, and Simon Walker-Samuel. Computational fluid dynamics with imaging of cleared tissue and of in vivo perfusion predicts drug uptake and treatment responses in tumours. *Nature Biomedical Engineering*, 2(10):773–787, 10 2018. ISSN 2157-846X. doi: 10.1038/s41551-018-0306-y. URL http://www.nature.com/articles/s41551-018-0306-y.

[5] Claire Walsh, Natalie A. Holroyd, Eoin Finnerty, Sean G. Ryan, Paul W. Sweeney, Rebecca J. Shipley, and Simon Walker-Samuel. Multifluorescence High-Resolution Episcopic Microscopy for 3D Imaging of Adult Murine

Organs. *Advanced Photonics Research*, 2(10):2100110, 10 2021. ISSN 2699-9293. doi: 10.1002/ADPR.202100110. URL https://onlinelibrary.wiley.com/doi/full/10.1002/adpr.202100110.

[6] C. L. Walsh, P. Tafforeau, W. L. Wagner, D. J. Jafree, A. Bellier, C. Werlein, M. P. Kühnel, E. Boller, S. Walker-Samuel, J. L. Robertus, D. A. Long, J. Jacob, S. Marussi, E. Brown, N. Holroyd, D. D. Jonigk, M. Ackermann, and P. D. Lee. Imaging intact human organs with local resolution of cellular structures using hierarchical phase-contrast tomography. *Nature Methods*, 18(12):1532–1541, 11 2021. ISSN 15487105. doi: 10.1038/s41592-021-01317-x. URL https://www.nature.com/articles/s41592-021-01317-x.

[7] Suhaas Anbazhakan, Pamela E. Rios Coronado, Ana Natalia L. Sy-Quia, Lek Wei Seow, Aubrey M. Hands, Mingming Zhao, Melody L. Dong, Martin R. Pfaller, Zhainib A. Amir, Brian C. Raftrey, Christopher K. Cook, Gaetano D'Amato, Xiaochen Fan, Ian M. Williams, Sawan K. Jha, Daniel Bernstein, Koen Nieman, Anca M. Pașca, Alison L. Marsden, and Kristy Red Horse. Blood flow modeling reveals improved collateral artery performance during the regenerative period in mammalian hearts. *Nature Cardiovascular Research 2022 1:8*, 1(8):775–790, 8 2022. ISSN 2731-0590. doi: 10.1038/s44161-022-00114-9. URL https://www.nature.com/articles/s44161-022-00114-9.

[8] Maxime Berg, Natalie Holroyd, Claire Walsh, Hannah West, Simon Walker-Samuel, and Rebecca Shipley. Challenges and opportunities of integrating imaging and mathematical modelling to interrogate biological processes. *International Journal of Biochemistry and Cell Biology*, 146:106195, 5 2022. ISSN 18785875. doi: 10.1016/j.biocel.2022.106195.

[9] S. Lorthois, F. Cassot, and F. Lauwers. Simulation study of brain blood flow regulation by intra-cortical arterioles in an anatomically accurate large human vascular network. Part II: Flow variations induced by global or localized modifications of arteriolar diameters. *NeuroImage*, 54(4):2840–2853, 2011. ISSN 10538119. doi: 10.1016/j.neuroimage.2010.10.040.

[10] S. Lorthois, F. Cassot, and F. Lauwers. Simulation study of brain blood flow regulation by intra-cortical arterioles in an anatomically accurate large human vascular network: Part I: Methodology and baseline flow. *NeuroImage*, 54(2):1031–1042, 2011. ISSN 10538119. doi: 10.1016/j.neuroimage.2010.09.032.

[11] Paul W. Sweeney, Simon Walker-Samuel, and Rebecca J. Shipley. Insights into cerebral haemodynamics and oxygenation utilising in vivo mural cell imaging and mathematical modelling. *Scientific Reports*, 8(1):1373, 12 2018. ISSN 20452322. doi: 10.1038/s41598-017-19086-z. URL http://www.nature.com/articles/s41598-017-19086-z.

[12] Jose T Celaya-Alcala, Grace V Lee, Amy F Smith, Bohan Li, Sava Sakadžić, David A Boas, and Timothy W Secomb. Simulation of oxygen transport and estimation of tissue perfusion in ex-

tensive microvascular networks: Application to cerebral cortex. *Journal of Cerebral Blood Flow and Metabolism*, 41(3):656–669, 6 2021. ISSN 15597016. doi: 10.1177/0271678X20927100. URL http://journals.sagepub.com/doi/10.1177/0271678X20927100.

[13] Timothy W. Secomb, Jonathan P. Alberding, Richard Hsu, Mark W. Dewhirst, and Axel R. Pries. Angiogenesis: An Adaptive Dynamic Biological Patterning Problem. *PLoS Computational Biology*, 9(3), 2013. ISSN 1553734X. doi: 10.1371/journal.pcbi.1002983.

[14] Jonathan P. Alberding and Timothy W. Secomb. Simulation of angiogenesis in three dimensions: Application to cerebral cortex. *PLOS Computational Biology*, 17(6): e1009164, 6 2021. ISSN 1553-7358. doi: 10.1371/JOURNAL.PCBI.1009164. URL https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1009164.

[15] Vasileios Vavourakis, Peter A. Wijeratne, Rebecca Shipley, Marilena Loizidou, Triantafyllos Stylianopoulos, and David J. Hawkes. A Validated Multiscale In-Silico Model for Mechano-sensitive Tumour Angiogenesis and Growth. *PLoS Computational Biology*, 13(1):e1005259, 1 2017. ISSN 15537358. doi: 10.1371/journal.pcbi.1005259.

[16] Vasileios Vavourakis, Triantafyllos Stylianopoulos, and Peter A. Wijeratne. In-silico dynamic analysis of cytotoxic drug administration to solid tumours: Effect of binding affinity and vessel permeability. *PLoS Computational Biology*, 14(10):e1006460, 10 2018. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1006460. URL https://journals.plos.org/ploscompbiol/article?id=10.1371/journal.pcbi.1006460.

[17] Paul W. Sweeney, Angela D'Esposito, Simon Walker-Samuel, and Rebecca J. Shipley. Modelling the transport of fluid through heterogeneous, whole tumours in silico. *PLOS Computational Biology*, 15(6):e1006751, 6 2019. ISSN 1553-7358. doi: 10.1371/journal.pcbi.1006751. URL http://dx.plos.org/10.1371/journal.pcbi.1006751.

[18] Emma Brown, Joanna Brunker, and Sarah E Bohndiek. Photoacoustic imaging as a tool to probe the tumour microenvironment. *Disease Models and Mechanisms*, 12(7):dmm039636, 2019. ISSN 17548411. doi: 10.1242/dmm.039636. URL https://dmm.biologists.org/content/dmm/12/7/dmm039636.full.pdf.

[19] Emma L. Brown, Thierry L. Lefebvre, Paul W. Sweeney, Bernadette J. Stolz, Janek Gröhl, Lina Hacker, Ziqiang Huang, Dominique-Laurent Couturier, Heather A. Harrington, Helen M. Byrne, and Sarah E. Bohndiek. Quantification of Vascular Networks in Photoacoustic Mesoscopy. *Photoacoustics*, 26:100357, 6 2022. ISSN 22135979. doi: 10.1016/j.pacs.2022.100357. URL https://linkinghub.elsevier.com/retrieve/pii/S221359792200026X.

[20] S Jonathan Chapman, Rebecca J Shipley, and Rossa Jawad. Multiscale modeling of fluid transport in tumors. *Bulletin of mathematical biology*, 70(8):2334–57, 11 2008. ISSN 1522-9602. doi: 10.1007/s11538-008-9349-7.

[21] Rebecca J Shipley and S Jonathan Chapman. Multiscale modelling of fluid and drug transport in vascular tumours. *Bulletin of mathematical biology*, 72(6):1464–91, 8 2010. ISSN 1522-9602. doi: 10.1007/s11538-010-9504-9.

[22] Tiina Roose and Melody A. Swartz. Multiscale modeling of lymphatic drainage from tissues using homogenization theory. *Journal of Biomechanics*, 45(1):107–115, 1 2012. ISSN 0021-9290. doi: 10.1016/J.JBIOMECH.2011.09.015.

[23] Wahbi K El-Bouri and Stephen J Payne. Multi-scale homogenization of blood flow in 3-dimensional human cerebral microvascular networks. *Journal of Theoretical Biology*, 380:40–47, 9 2015. ISSN 10958541. doi: 10.1016/j.jtbi.2015.05.011.

[24] R. Penta and D. Ambrosi. The role of the microvascular tortuosity in tumor transport phenomena. *Journal of Theoretical Biology*, 364:80–97, 1 2015. ISSN 10958541. doi: 10.1016/j.jtbi.2014.08.007.

[25] R. Penta, D. Ambrosi, and A. Quarteroni. Multiscale homogenization for fluid and drug transport in vascularized malignant tissues. *Mathematical Models and Methods in Applied Sciences*, 25(1):79–108, 11 2015. ISSN 02182025. doi: 10.1142/S0218202515500037.

[26] Pietro Mascheroni and Raimondo Penta. The role of the microvascular network structure on diffusion and consumption of anticancer drugs. *International Journal for Numerical Methods in Biomedical Engineering*, 33(10):e2857, 10 2017. ISSN 20407947. doi: 10.1002/cnm.2857. URL https://onlinelibrary.wiley.com/doi/full/10.1002/cnm.2857.

[27] Rebecca J. Shipley, Paul W. Sweeney, Stephen J. Chapman, and Tiina Roose. A four-compartment multiscale model of fluid and drug distribution in vascular tumours. *International Journal for Numerical Methods in Biomedical Engineering*, 36(3):e3315, 3 2020. ISSN 2040-7947. doi: 10.1002/CNM.3315. URL https://onlinelibrary.wiley.com/doi/full/10.1002/cnm.3315.

[28] Myriam Peyrounette, Yohan Davit, Michel Quintard, and Sylvie Lorthois. Multiscale modelling of blood flow in cerebral microcirculation: Details at capillary scale control accuracy at the level of the cortex. *PLoS ONE*, 13 (1):e0189474, 2018. doi: 10.1371/journal.pone.0189474.

[29] Amy F. Smith, Bianca Nitzsche, Martin Maibier, Axel R. Pries, and Timothy W. Secomb. Microvascular hemodynamics in the chick chorioallantoic membrane. *Microcirculation*, 23(7):512–522, 8 2016. ISSN 15498719. doi: 10.1111/micc.12301.

[30] M. Kojic, M. Milosevic, V. Simic, E. J. Koay, J. B. Fleming, S. Nizzero, N. Kojic, A. Ziemys, and M. Ferrari. A composite smeared finite element for mass transport in capillary systems and biological tissue. *Computer methods*

in applied mechanics and engineering, 324:413–437, 9 2017. ISSN 0045-7825. doi: 10.1016/J.CMA.2017.06.019. URL https://pubmed.ncbi.nlm.nih.gov/29200531/.

[31] S. J. Payne and W. K. El-Bouri. Modelling dynamic changes in blood flow and volume in the cerebral vasculature. *NeuroImage*, 176:124–137, 8 2018. ISSN 10959572. doi: 10.1016/j.neuroimage.2018.04.037.

[32] Wahbi K. El-Bouri and Stephen J. Payne. Investigating the effects of a penetrating vessel occlusion with a multi-scale microvasculature model of the human cerebral cortex. *NeuroImage*, 172:94–106, 5 2018. ISSN 10959572. doi: 10.1016/j.neuroimage.2018.01.049.

[33] Johannes Kremheller, Anh Tu Vuong, Bernhard A. Schrefler, and Wolfgang A. Wall. An approach for vascular tumor growth based on a hybrid embedded/homogenized treatment of the vasculature within a multiphase porous medium model. *International Journal for Numerical Methods in Biomedical Engineering*, 35(11):e3253, 11 2019. ISSN 2040-7947. doi: 10.1002/CNM.3253. URL https://onlinelibrary.wiley.com/doi/full/10.1002/cnm.3253.

[34] Ettore Vidotto, Timo Koch, Tobias Köppl, Rainer Helmig, and Barbara Wohlmuth. Hybrid Models for Simulating Blood Flow in Microvascular Networks. *Multiscale modeling & simulation : a SIAM interdisciplinary journal*, 17(3):1076–1102, 9 2019. ISSN 15403467. doi: 10.1137/18M1228712. URL https://epubs.siam.org/doi/abs/10.1137/18M1228712.

[35] Rebecca J Shipley, Amy F Smith, Paul W Sweeney, Axel R Pries, and Timothy W Secomb. A hybrid discrete–continuum approach for modelling microcirculatory blood flow. *Mathematical Medicine and Biology: A Journal of the IMA*, 37(1):40–57, 3 2020. ISSN 1477-8599. doi: 10.1093/imammb/dqz006. URL https://academic.oup.com/imammb/advance-article/doi/10.1093/imammb/dqz006/5393647.

[36] Timo Koch, Martin Schneider, Rainer Helmig, and Patrick Jenny. Modeling tissue perfusion in terms of 1d-3d embedded mixed-dimension coupled problems with distributed sources. *Journal of Computational Physics*, 410: 109370, 6 2020. ISSN 0021-9991. doi: 10.1016/J.JCP.2020.109370.

[37] Johannes Kremheller, Sebastian Brandstaeter, Bernhard A. Schrefler, and Wolfgang A. Wall. Validation and parameter optimization of a hybrid embedded/homogenized solid tumor perfusion model. *International Journal for Numerical Methods in Biomedical Engineering*, 37(8):e3508, 8 2021. ISSN 20407947. doi: 10.1002/cnm.3508.

[38] Rebecca J Shipley. *Multiscale modelling of fluid and drug transport in vascular tumours*. PhD thesis, University of Oxford, 2008.

[39] Benyi Xiong, Anan Li, Yang Lou, Shangbin Chen, Ben Long, Jie Peng, Zhongqin Yang, Tonghui Xu, Xiaoquan Yang, Xiangning Li, Tao Jiang, Qingming Luo, and Hui Gong. Precise cerebral vascular atlas in stereo-

taxic coordinates of whole mouse brain. *Frontiers in Neuroanatomy*, 11:128, 12 2017. ISSN 16625129. doi: 10.3389/fnana.2017.00128.

[40] Brendan C. Fry, Jack Lee, Nicolas P. Smith, and Timothy W. Secomb. Estimation of Blood Flow Rates in Large Microvascular Networks. *Microcirculation*, 19:530–538, 2012. ISSN 10739688. doi: 10.1111/j.1549-8719.2012.00184.x.

[41] Spyros k. Stamatelos, Eugene Kim, Arvind P. Pathak, Popel, and Aleksander S. A bioimage informatics based reconstruction of breast tumor microvasculature with computational blood flow predictions. *Microvascular Research*, 91:8–21, 2014. doi: https://doi.org/10.1016/j.mvr.2013.12.003.

[42] Amy Smith. *Multi-scale modelling of blood flow in the coronary microcirculation*. PhD thesis, University of Oxford, 2013.

[43] Paul W. Sweeney. *Realistic numerical image-based modelling of biological tissue substrates*. PhD thesis, University College London, 2018. URL `http://discovery.ucl.ac.uk/id/eprint/10049410`.

[44] A R Pries and T W Secomb. Microvascular blood viscosity in vivo and the endothelial surface layer. *American journal of physiology. Heart and circulatory physiology*, 289(6):H2657–H2664, 2005. ISSN 0363-6135. doi: 10.1152/ajpheart.00297.2005.

[45] A R Pries, K Ley, M Claassen, and P Gaehtgens. Red cell distribution at microvascular bifurcations. *Microvascular research*, 38(1):81–101, 7 1989. ISSN 0026-2862.

[46] Amy F Smith, Rebecca J Shipley, Jack Lee, Gregory B Sands, Ian J LeGrice, and Nicolas P Smith. Transmural variation and anisotropy of microvascular flow conductivity in the rat myocardium. *Annals of biomedical engineering*, 42(9):1966–77, 9 2014. ISSN 1573-9686. doi: 10.1007/s10439-014-1028-2.