Neural correlates of probabilistic information processing in gesture-speech integration

Wanying Zhao[1]; Xiang Li[1,2]; Yi Du[1,2,3,4*]

[1] CAS Key Laboratory of Behavioral Science, Institute of Psychology, Chinese Academy of Sciences, Beijing, China 100101

[2] Department of Psychology, University of Chinese Academy of Sciences, Beijing, China 100049

[3] CAS Center for Excellence in Brain Science and Intelligence Technology, Shanghai, China 200031

[4] Chinese Institute for Brain Research, Beijing, China 102206

* Corresponding author:

Dr. Yi Du, Email: duyi@psych.ac.cn

16 Lincui Road, Chaoyang district, Beijing, China 100101

Abstract

How information of different modalities (e.g., speech and gesture) frame into a unified one remains unclear in the neurobiology of language. Leveraging the information-theoretic complexity metrics of entropy and mutual information (MI) to quantify gestures and speech, the present event-related potentials and chronometric double-pulse transcranial magnetic stimulation (TMS) study investigated the neural processes during probabilistic gesture-speech integration. In the early processing stage, we found a positive correlation of P1 amplitude with speech entropy and a negative correlation of N1-P2 amplitude with gesture entropy, while the TMS disruption effect of posterior middle temporal gyrus (pMTG) was negatively correlated with speech entropy. In the lexico-semantic processing stage, we observed a negative correlation of N400 amplitude with both gesture entropy and gesture-speech MI, a negative correlation of late positive component amplitude with speech entropy, together with correlations of the TMS interruption effect of inferior frontal gyrus (IFG) with gesture entropy, speech entropy and their MI. Our findings suggest a probabilistically updated lexical representation that was dynamically framed by top-down gesture constrain, bottom-up speech encoding and their interplay. A 5-step process in the pMTG-IFG-pMTG neural circuit is hypothesized for probabilistic gesture–speech processing, which promises a better understanding of the predictive multisensory language processing.

Keywords: gesture-speech integration; probabilistic representation; information theory; ERP; TMS

1. **Introduction**

In communication, gestures often co-exist with speech to convey a coherent sense. Gestures are regarded as 'part of language' (1) or functional equivalents of lexical units in spoken language that alternate and integrate with speech (2). It is suggested that information from gesture and speech is incorporated into a 'single unification space' during language comprehension (3-5). Empirical evidence has shown a bidirectional interaction between these two (6-8) as reflected by the N400 latency and amplitude (5), as well as common neural underpinnings (9-11). An unanswered question is how the spatial-motoric and synthetic gesture integrates with the linear-analytic speech into a unified representation of meaning during language comprehension.

Traditionally, language comprehension is understood as retrieving word meaning from memory and subsequently integrating them into a compositional representation of sentence meaning (12) in a manner that is governed by the apparatus of formal grammar. Recent research has conceptualized language processing as a sequence of mental states that are defined by a particular parser and function quantitively (13). According to this theory, there is inherent uncertainty in the information available to the senses, as well as in the encoding of that information by the sensory systems. Consequently, the neural representations that guide behavior are probabilistic (14). In fact, the probabilistic model has been applied to explain structural parsing principles (for a review, see (15)), word recognition (16), word processing (17) and syllable perception (18). Further studies have shown an updated probabilistic representation with the coming of each word in a sentence, the magnitude of which is correlated with the amplitude of the N400 event-related potential (ERP) component (19, 20) , the cortical response recorded from the high-density electrocorticography (ECoG) (21), and the brain oscillatory activities of theta (4-10 Hz) and delta (0.5-4 Hz) bands (22). However, empirical evidence of probabilistically updated representation during gesture-speech integration is still lacking.

The present study directly tested the neurocognitive processes underlying the probabilistic semantic integration of gesture and speech. To this end, we adopted the information-theoretic complexity metrics of *entropy* and *mutual information* (MI) to

mathematically quantify the information of gesture and speech during integration. Entropy captures the disorder or randomness of information and is used as a measurement of the uncertainty of probabilistic representation activated when an event occurs (23). MI illustrates the mutual constraint that the two variables impose on each other (18) and was used herein as an index of the magnitude of gesture–speech integration. In Experiment 1 (**Figure 1B**), ERPs with high temporal resolution were used to determine the time course of the gesture-speech integration process. Previous studies have reported various stages of gesture–speech integration, indexed by ERP components of the early N1–P1 and P2 sensory effects (24, 25), the N400 semantic anomaly effect (5, 25, 26), and the late positive component (LPC) restructuring effect (27, 28). Therefore, Experiment 1 hypothesized a proportional amplitude of different ERP components as a change of the gesture entropy, speech entropy or their MI. Using double-pulse transcranial magnetic stimulation (TMS) to locate the time windows (TWs) for the involvement of the posterior middle temporal gyrus (pMTG) and inferior frontal gyrus (IFG) in integration, Experiment 2 (**Figure 1C**) aimed to unpack the information processing within the pMTG–IFG–pMTG neural circuit during gesture–speech integration, as found in our prior study (10). We hypothesized different correlation patterns between the TW-selective disruption effect of the pMTG and IFG with the gesture entropy, speech entropy and MI. Together, the present study aimed to elucidate the probabilistic neural processing in gesture–speech integration by uncovering how ERP components and time-sensitive regional engagement were modulated by the information presented from gesture and speech.

2. Material and methods

2.1 Experiment 1

2.1.1 Participants

Twenty-two native Chinese participants signed written informed consent forms and took part in Experiment 1 (12 female; 19-29 years, mean = 21). All of the participants were right-handed (laterality quotient (LQ) = 88.49, SD = 12.65), had normal or corrected-to-normal vision and were paid ¥100 per hour for their participation. This study was approved by the Ethics Committee of the Institute of Psychology, Chinese Academy of Sciences.

2.1.2 Stimuli

Twenty gestures with 20 semantically congruent speech signals were used in the present study. The stimuli set were recorded from two native Chinese speakers (1 male, 1 female) and validated by replicating the semantic congruency effect with 30 participants. Results showed a significantly larger reaction time when participants were asked to judge the gender of the speaker if gesture contained incongruent semantic information with speech (a 'cut' gesture paired with speech word '喷 pen1 (spray)': Mean = 554.51 ms, SE = 11.65) relative to when they were semantically congruent (a 'cut' gesture paired with '剪 jian3 (cut)' word: Mean = 533.90 ms, SE = 12.02) (for details, see (10)). To create a semantic constrain of gesture upon the unfolding speech, the present study presented speech onset at the DP of gesture (**Figure 1A**), a magnitude of the minimal length of each gesture required for semantic identification that was determined by a gating pre-test with another 30 participants. On average, the DP of gestures was 183.78 ms (SD = 84.82) (for details, see (10)). Additionally, two separate pre-tests with 30 subjects in each (pre-test 1: 16 females, aged 19-35 years, SD = 11.03; pre-test 2: 15 females, aged 19-30 years, SD=10.26) were conducted to determine the nameability values of gesture and speech. Participants were presented with isolated gesture/speech and were asked to use one verb to describe the gesture they saw or the speech they heard. The nameability of gesture/speech was defined as the percentage of participants who provided the most frequently used label. The overall nameability of gesture (Mean =.574, SD =.271) and that of speech (Mean =.947, SD =.109) were calculated (**Table S1**).

To increase the statistical power, the gesture–speech combinations were sorted into 10 bins according to gesture entropy and MI (**S1**), from the highest (90%–100%) to the lowest (0–10%) (29). Given that there were only eight steps for speech entropy, pairs of gesture–speech items were sorted into 8 bins of speech entropy (**S1**). For each of the information model, each 10% bin was averaged first within and then across participants.

2.1.3 Experimental procedure

To test the automatic interaction of gesture and speech information, an irrelevant factor of gender congruency (e.g., a man making a gesture combined with a female voice) was created.

In total, 20 gender congruent and 20 gender incongruent trials were presented to each

participant. Gesture–speech pairs were presented randomly using Presentation software

(www.neurobs.com). Participants were asked to look at the screen but respond as quickly and

accurately as possible only to the gender of the voice they heard. The RT and the button

being pressed were recorded. Responses were made using the left and right index fingers,

and key assignment was counterbalanced across participants. The experiment started with a

fixation cross presented on the center of the screen, and the duration of the fixation cross was

set to be random at 0.5-1.5 sec.

2.1.4 Electroencephalogram (EEG) recording

Data from Experiment 1 were recorded from 48 Ag/AgCl electrodes mounted in a cap

according to the 10-20 system (48). EEG was amplified with a PORTI-32/MREFA amplifier

(TMS International B.V., Enschede, NL) and digitized online at 500 Hz (bandpass, 0.01-70

Hz). Vertical and horizontal eye movements were measured with 4 electrodes placed above

the left eyebrow and below the left orbital ridge and at the left and right external canthus. All

electrodes were referenced online to the left mastoid. Electrode impedance was maintained

below 5 KΩ.

2.1.5 Data analysis

All incorrect responses were excluded (147 out of 1760, 8.35% of trials). To eliminate the

influence of outliers, a 2 SD trimmed mean was calculated for every participant in each

condition. Next, the MATLAB-based toolbox EEGLAB was used (49). Epochs were time

locked to the onset of speech and lasted for 1000 ms. To ensure that the baseline correction

was clean with no stimulus presented, a 200 ms pre-stimulus baseline correction was applied

before the onset of gesture stoke (**Figure 1B**). The average of the left and right mastoids was

used for re-referencing. A high-pass filter with a cutoff of 0.05 Hz and a low-pass filter with a

cutoff of 30 Hz were applied. Artifacts were removed semiautomatically. Overall, participants

were excluded from future analysis if their rejected trials were more than 30% of the total

number.

To select the activated component window more objectively, grand-average ERPs at

electrode Cz for the higher half (60–100%) and the lower half (0–50%) were compared for

each model before being submitted to correlation analyses. Trials were averaged regardless of gender congruency as no difference was revealed by paired t-tests on each component. To analyze the scalp distribution of the ERP effect, 7 ROIs were defined: left anterior: F1, F3, F5, FC1, FC3, and FC5; left central: C1, C3, C5, CP1, CP3, and CP5; left posterior: P1, P3, P5, PO3, PO5, and O1; right anterior: F2, F4, F6, FC2, FC4, and FC6; right central: C2, C4, C6, CP2, CP4, and CP6; right posterior: P2, P4, P6, PO4, PO6, and O2; and midline electrodes: Fz, FCz, Cz, Pz, Oz, and CPz. Pearson correlations were calculated between each model (gesture entropy, speech entropy, and MI) and each ERP amplitude in each ROI, separately. FDR correction was applied for multiple comparisons.

2.2 Experiment 2

2.2.1 Participants

Another set of 24 participants was recruited for Experiment 2 (11 female; 18-28 years, mean = 23). All were right-handed (LQ = 89.02, SD = 13.25), had normal or corrected-to-normal vision, paid ¥100 per hour for their participation and were approved by the Ethics Committee of the Institute of Psychology, Chinese Academy of Sciences.

2.2.2 Experimental procedure

Similar as in Experiment 1, two factors were manipulated: semantic congruency and gender congruency. Value of MI only refers to trials when gesture contained semantic congruent information with speech. To eliminate the effect caused by stimuli in the semantically incongruent gesture-speech condition, the 20 gestures and 20 speech were combined into 10 pairs with a reverse combination of the semantic information (e.g., a 'spray' gesture while saying Mandarin speech word '剪 jian3 (cut)' was paired with a 'cut' gesture while saying Mandarin speech word '喷 pen1 (spray)'). For each stimulation site, a total of 800 trials for 4 types of conditions (semantic congruency x gender congruency) and 5 TWs were further split into 3 blocks (320 trials in one block and 240 trials in the last two blocks). In each block, pairs of stimuli were kept intact. Participants completed all 3 blocks for each stimulation site, the order of which was counterbalanced using a Latin square design. During the experiment, participants were asked to look at the screen but respond only to the gender of the voice they heard.

2.2.3 TMS protocol

At an intensity of 50% of the maximum stimulator output, double-pulse TMS was delivered via a 70 mm figure-eight coil using a Magstim Rapid² stimulator (Magstim, UK) over either the left IFG (-62, 16, 22) in TW3 and TW6 or the left pMTG (-50, -56, 10) in TW1, TW2 and TW7 (**Figure 1C**). The coordinates of the left IFG and left pMTG corresponded to Montreal Neurological Institute (MNI) coordinates. The vertex was used as a control site (for details, see (10)).

2.2.4 Data analysis

All incorrect responses (922 out of the total number of 19200, 4.8% of trials) were excluded. Since TMS upone the IFG and pMTG did not affect the gender congruency effect as shown in our prior study (10), gender incongruent trials were also included for analysis. To eliminate the influence of outliers, a 2 SD trimmed mean of RT for every participant in each session was conducted. Correlations of the TMS effect (active TMS minus vertex TMS) over the semantic congruency effect (RT difference between semantic congruent and incongruent trials) with the three information models (gesture entropy, speech entropy and MI) were calculated. FDR correction was applied where necessary.

3. Results

3.1 Stimulus entropy and MI

Twenty gestures and 20 corresponding speech signals were used in the present study. To capture the distribution of information in gestures and speech, the nameability for each item, which was defined as the percentage of participants who provided the most frequently used label, was transformed into Shannon's entropy (H) using the relevant formula (**Figure 1D**). Here, $p(x_i)$ and $p(y_i)$ represent the nameability for a given gesture and speech, respectively. High entropy indicates that participants provided many answers for that gesture/speech with a low nameability score, implying a broad distribution of gesture/speech representation. In contrast, low entropy indicates that participants' comprehension for that certain item was quite centralized, and the nameability score was high. Additionally, the interplay of gesture and

speech was captured by MI, which represents the amount of information obtained about

gesture by observing speech, and vice versa. That is, the higher MI of gesture and speech,

the stronger interplay and integration between the two.

To increase the statistical power, according to scores in each information model, stimuli

were sorted into 10 bins for the gesture entropy and MI, and 8 bins for the speech entropy

(see **Table S1**) (29). Correlation analyses were conducted between scores of each model and

ERP amplitudes (Experiment 1), and between scores of each model and the TMS disruption

effects of gesture-speech integration as indexed by reaction time (RT) difference (Experiment

2).

3.2 P1, N1-P2, N400 and LPC components were modulated by gesture and speech

probabilities

In Experiment 1, electroencephalogram (EEG) data were recorded with epochs time locked to

the onset of speech when subject were presented with semantically congruent gesture-

speech pairs (**Figure 1B**). ERPs in relative to speech onset rather than gesture onset was

focused as we aimed to assess the impacts of the gesture entropy and MI on speech

processing when gestures always precede speech in natural settings. **Figure 2A** presents

grand-average ERPs at the electrode Cz classified by either the gesture entropy, speech

entropy or MI when each measurement was split into the higher half (60-100%) and the lower

half (0-50%). Four ERP components were identified and put into the following analyses: the

P1 component at 0-100 ms, the N1-P2 component at 150-250 ms, the N400 component at

250-450 ms and the LPC at 550-1000 ms. Notably, gender congruent and gender incongruent

trials (see details in Methodology) were averaged, as the paired t-test failed to show a

significant effect of gender congruency on the amplitude of P1 ($t(50) = 1.442$, $p = .156$), N1-

P2 ($t(50) = -.539$, $p = 5.92$), N400 ($t(100) = .063$, $p = .95$), and LPC ($t(224) = .974$, $p = .331$).

As shown, stimuli with the higher 50% speech entropy elicited a larger P1 amplitude ($t(50) =$

24.18, $p < .001$) and a smaller LPC amplitude ($t(224) = 46.83$, $p < .001$) than stimuli with the

lower 50% speech entropy (**Figure 2A** middle). Meanwhile, a larger N400 amplitude ($t(100) =$

12.43, $p < .001$) and a larger N1-P2 amplitude ($t(50) = 14.58$, $p < .001$) were found by the

lower 50% compared to the higher 50% gesture entropy (**Figure 2A** left). For the MI, a larger

N400 amplitude was found for stimuli of the lower 50% than the higher 50% (t(100) = 6.45, *p*

< .001, **Figure 2A** right).

Further correlation analyses found that the P1 amplitude significantly increased as the

speech entropy increased in the left central (LC) region-of-interest (ROI) (r = .825, false

discovery rate (FDR)-corrected *p* = .036), the right central (RC) ROI (r = .850, FDR-corrected

p = .024), and the middleline (ML) ROI (r = .833, FDR-corrected *p* = .03). No correlation was

found between the P1 amplitude and the gesture entropy (|r| < 0.315) or the MI (|r| < 0.493).

Topographical voltage maps of the r values at various recording sites are shown in **Figure 2B.**

Entropy has been considered to be a reflection of the strength of expectations about the

upcoming word (30). The correlation of this early sensory response with the speech entropy is

interpreted as a difficulty effect of the bottom-up phonological encoding and word access.

That is, the larger speech entropy, the less speech intelligibility, therefore resulting in a larger

P1 response.

For the N1-P2 amplitude, a negative correlation was found with the gesture entropy in the

left anterior (LA) ROI (r = -.84, FDR-corrected *p* = .014) and the right anterior (RA) ROI (r = -

.765, FDR-corrected *p* = .035). No correlation of the N1-P2 amplitude with the speech entropy

(|r| < .719) or the MI (|r| < .694) has been spotted. Since N1-P2 represents the neural

encoding of phonetic features, the correlation with the gesture entropy implies a top-down

modulation of gesture over the phonological processing of speech. The smaller the gesture

entropy, the higher intelligibility it presents, thus leading to a larger top-down modulation over

speech phonological processing with an enlarged N1-P2 amplitude.

In terms of the N400 effect, a negative correlation between the N400 amplitude and the

gesture entropy (r = -.677, FDR-corrected *p* = .047) and MI (r = -.704, FDR-corrected *p* = .047)

was detected in the RA ROI. There was no correlation of the N400 effect with the speech

entropy (|r| < .68). When gesture entropy is high, a broad distribution of gesture

representations would be activated, resulting in weakened confidence of the predicted word

and less cross-modal interplay with a reduced N400 amplitude. With the presentation of the

coming word, the brain compares the semantic features being predicted by the top-down

gesture and those being activated by the bottom-up speech, the larger the overlap, the

smaller the amplitude of the scalp N400 (31), giving the inverse relation between the N400

effect and the MI of gesture and speech.

With regards to the LPC effect, a significant negative correlation with the speech entropy

was found in ROIs of LA (, r = -.812, FDR-corrected *p* = .042); LC (r = -.858, FDR-corrected *p*

= .018); left posterior (LP, r = -.822, FDR-corrected *p* = .036); RA (r = -.856, FDR-corrected *p*

= .021) and ML (r = -.858, FDR-corrected *p* = .018). For the gesture entropy and MI, there

were no significant correlation with the LPC (|r| < .55). The results were comprehended as

that the representation activated by the bottom-up speech information would reweight the

predicted candidates elicited by the top-down gesture information (32), which would give rise

to a coherent meaning. With the centralization of the bottom-up speech representation, as

quantified by a smaller entropy, confidence for the reanalysis of the predicted candidates

becomes stronger, leading to a larger LPC amplitude.

3.3 Engagements of the left pMTG and IFG in integration were modulated by gesture

and speech probabilities

Using the same stimuli as in Experiment 1, Experiment 2 manipulated the experimental factor

of semantic congruency, with gesture containing either semantically congruent information or

semantically incongruent information with the accompanying speech. Double-pulse TMS was

delivered to either the left IFG or the left pMTG in one of the five 40-ms TWs in relative to

speech identification point (IP) (TW1: -120 ~ -80 ms , TW2: -80 ~ -40 ms, TW3: -40~0 ms,

TW6: 80~120 ms, and TW7: 120~160 ms), which showed a TW-selective disruption of

gesture-speech integration in our prior study (**Figure 1C**) (for details, see (10)). We focused

our current analysis on the correlation of the TMS interruption (active TMS minus vertex TMS)

of the semantic congruency effect (RT of semantic incongruent minus RT of semantic

congruent pairs) with the gesture entropy, speech entropy or MI. By doing this, we can

determine how the time-sensitive contribution of the left IFG and pMTG to gesture–speech

integration was affected by gesture and speech information distribution.

The results illustrated a significant negative correlation between the TMS effect and the

speech entropy when the pMTG was inhibited in TW2 (r = -.877, FDR-corrected *p* = .012).

Since a more negative TMS effect over the semantic congruency effect represents a stronger

interruption of the integration effect, the negative correlation here indicates that the higher

uncertainty of speech, the stronger engagement of the pMTG in integrating gesture and

speech segment before speech identification (TW2). Meanwhile, when the IFG activity was

interrupted in TW6, a significant negative correlation was found between the TMS effect and

the gesture entropy (r = -.876, FDR-corrected p = .003), speech entropy (r = -.736, FDR-

corrected p = .037), and MI (r = -.761, FDR-corrected p = .017) (**Figure 3**). This suggests that

the higher uncertainty of gesture or speech and higher MI of gesture and speech would result

in stronger involvement of the IFG in multimodal integration after speech identification.

4. Discussion

In this study, we investigated how gesture-primes and speech were integrated for

comprehension. By mathematically quantifying gesture and speech information with entropy

and MI, we assessed directly the ERP correspondence (Experiment 1) and the regional

involvement (Experiment 2) during probabilistic information processing in gesture–speech

integration. From an integrated perspective, our results indicate dynamic neural stages within

the pMTG-IFG-pMTG neurocircuit of gesture-speech integration that were differentially

mediated by top-down gesture prediction (gesture entropy), bottom-up speech encoding

(speech entropy) and their interplay (MI) in forming the probabilistically updated lexical

representation. Our findings thus extend the current knowledge of how multimodal information

is processed and integrated in the brain.

Semantic representation encodes knowledge of concepts that are experienced through

multisensory channels abstract away from modality specific attributes (33) and are stored in

transmodal regions (34, 35). Empirical evidence has shown that the process of gesture–

speech integration involves the incorporation of information into a 'single unification space' (3-

5) with common neural underpinnings in pMTG and IFG (9, 10). While pMTG is believed to be

involved in perceptual matching and activation of a common stable representation, IFG has

been reliably associated with selection, control and unification of semantic information (36). In

fact, a recurrent neurocircuit connecting the left IFG and pMTG in semantic unification has

been proposed extensively (37). In particular, by segmenting the possible integration period

into eight TWs relative to the speech IP and applying inhibitory double-pulse TMS over each

TW, our previous study hypothesized two stages within the pMTG-IFG-pMTG neurocircuit in

gesture–speech integration. In the first pre-lexical stage, semantic information extracted from

gesture constrains the phonological encoding of speech, while in the post-lexical stage, the

most feasible lexical candidate is selected, retrieved and unified with the gesture semantics to

form a context-appropriate semantic representation (10). As an extension, the current study

quantified the information of gesture and speech with entropy and MI, and discovered that

TW-specific regional contribution of pMTG and IFG to gesture-speech semantic integration

were distinctively correlated with the entropy of gestures and speech and their MI. In an early

pre-lexical gesture-speech integration time window (TW2), speech entropy was negatively

correlated with activity of pMTG, while in a later post-lexical time window of gesture-speech

integration (TW6), a negative correlation of the IFG activity with both gesture entropy, speech

entropy and their MI was found. Our results confirmed that semantic representation irrelevant

of modalities builds up probabilistically within the neurocircuit connecting the transmodal

regions of pMTG and IFG during gesture-speech integration.

Moreover, we disentangled the sub-processes taken place during gesture-speech

comprehension with the use of high temporal resolution of ERPs, when representations of

gesture and speech were probabilistically presented. Four ERP components were segmented:

a P1-N1-P2 complex that was considered to be responsible for speech phonological encoding,

and a N400 component followed by the LPC component that reflect the lexico-semantic

processing stage. Early P1-N1 and P2 sensory effects in gesture-speech integration has been

reported in previous studies and were linked to perception and attentional processes (25, 38).

Here, the P1-N1-P2 complex was comprehended as a reflection of the early audiovisual

gesture-speech integration taken place during the sensory and perceptual processing chain

(39). Note that a semantic priming paradigm was adopted here by presenting the onset of

speech to be at the gesture DP (9, 10), during which a semantic top-down prediction of

gesture over speech has been created. The early interaction of gesture-speech information

happened with both top-down gesture prediction and bottom-up speech processing, as shown

by a positive correlation of the P1 effect with speech entropy and a negative correlation of the

N1-P2 effect with gesture entropy. Additionally, the lexico-semantic effect of the N400 and the

LPC that have consistently been found in previous studies investigating gesture-speech

integration (5, 25-28) were differentially mediated by top-down gesture prediction, bottom-up

speech encoding and their interaction. As reflected by a negatively correlation between the

N400 effect with both the gesture entropy and their MI, as well as a correlation of the LPC

with the speech entropy. In the present study, activation of representation of meaning is

modulated probabilistically. The input stimuli activate a dynamically distributed neural

landscape, the state of which constructs probabilistically as measured by entropy and MI and

correlates with the electrophysiological signals (N400 and LPC) indicating a change of lexical

representation. Consistent with a recent 'Sentence Gestalt' account proposed by Rabovsky

(2018) in the multisensory gesture-speech information processing (20), our findings further

indicate that the changed activation pattern was induced from directions of both top-down and

bottom-up gesture-speech processing. This process was associated with the N400 effect,

followed by the LPC which might reflect an update weighing of the semantic cues that

provided the changes of activation pattern.

Considering the close alignment of the ERP components with the TWs of TMS effect, i.e.

the P1 component (0-100 ms of speech onset) was aligned with TW2 (96-136 ms of speech

processing), and the N400 effect (250-450 ms of speech onset) coincided with TW6 (256-296

ms of speech processing) (**Figure 1A**), it is quite reasonable to associate the ERP

components with the cortical involvements that both were interrelated with the same

information measure (e.g., gesture entropy). Hence, hypothesis was made that the early

sensory effect of the P1 component was associated mainly with the pMTG due to their

temporal co-occurrence and correlation with the speech entropy, while the N400 component

was a reflection of the IFG activity because of their temporal overlap and correlation with both

the gesture entropy and MI (**Figure 4**). Specifically, double-pulse TMS over the supramodal

pMTG could both feedforward and feedback affect the phonological processing of speech in

the superior temporal gyrus/sulcus (STG/S) as indexed by the P1 component and the N1-P2

component respectively (40). The hypothesis that the IFG is the major generator of the N400

component is also consistent with previous findings using the semantic priming paradigm (41),

especially when the stimulus-onset asynchrony of two different modalities is long enough and

the prime word is fully processed. During that process, IFG activity is considered to ease the

effort of word selection or facilitate the controlled semantic retrieval that is made available by

the top-down prediction from the context or primes over the target word (42). Besides,

although the LPC component lagged behind TW6 in which the IFG was involved, the LPC

amplitude and the TMS effect of the IFG were co-related with the speech entropy. A link of the

LPC to the IFG has been provided by several studies (for a review, see (43)), in which the IFG

is considered to integrate the current stimulus with prior context into an updated utterance

representation. Similarly, the present study reported a significant correlation of IFG with the

speech entropy, which we comprehended as a reanalysis of semantic information, and further

led to a coherent understanding.

In emphasizing the probabilistic notion in gesture-speech integration, we recognized a

distributional property of the language input that is inherently graded and/or stochastic. Here,

we estimated the probabilities of gesture and speech by computing the amount of information

conveyed by each modality with entropy and MI and revealed distinct contributions of gesture

and speech information within both the early speech processing stage and the late lexico-

semantic processing stage. Referencing the recurrent neurocircuit connecting the left IFG and

pMTG for semantic unification (44) , we extended the two-stage gesture-speech integration

circuit proposed in our previous study (10) into 5 steps (**Figure 4**). First, bottom-up speech

processing mapping acoustic signal to its lexical representation was performed from the

STG/S to the pMTG. The larger speech entropy was, the greater effort was made during the

matching of the acoustic input with its stored lexical representation, thus leading to a larger

involvement of the pMTG at pre-lexical stage (TW2) and a larger P1 effect (**Figure 4①**).

Second, the gesture representation was activated in the pMTG and further exerted a top-

down modulation over the phonological processing of speech in the STG/S (45). The higher

certainty of gesture, a larger modulation of gesture would be made upon speech, as indexed

by a smaller gesture entropy with an enhanced N1-P2 amplitude (**Figure 4②**). Third,

information was relayed from the pMTG to the IFG for sustained activation, during which a

semantic constraint from gesture has been made on the semantic retrieval of speech. Greater

TMS effect over the IFG at post-lexical stage (TW6) accompanying with a reduced N400

amplitude were found with the increase of gesture entropy, when the representation of

gesture was wildly distributed and the constrain over the following speech was weak **(Figure

4③)**. Fourth, the activated speech representation was compared with that of the gesture in

the IFG. At this stage, the larger overlapped neural populations activated by gesture and

speech as indexed by a larger MI, a greater TMS disruption effect of the IFG and a reduced

N400 amplitude indexing easier integration and less semantic conflict were observed (**Figure**

4④). Last, the activated speech representation would disambiguate and reanalyze the

semantic information that was stored in the IFG and further unify into a coherent

comprehension in the pMTG (3, 46). The more uncertain information being provided by

speech, as indicated by an increased speech entropy, a stronger reweighting effect was made

over the activated semantic information, resulting in a strengthened involvement of the IFG as

well as a reduced LPC amplitude (**Figure 4⑤**).

Certain limitations should be noted. Firstly, the ERP components and the cortical

engagements were measured in two separate experiments and their link was reflected

through mediating variables of the entropy and MI. We provided no direct evidence of the

brain structures underpinning the corresponding ERP components, and we even failed to find

the TMS evidence responsible for the top-down gesture effect on the N1-P2 component.

Hence, the cortical implementation of the ERP components in gesture–speech integration

needs to be clarified by future studies. Secondly, the causal effect of TMS on behavioral

performance is much more complex than previously thought (47), making the conclusion of

the information flow within the pMTG–IFG-pMTG loop less convincing due to a close

functional connection between the two locations. On the one hand, we cannot tell whether the

significantly reduced activity in the left IFG was due to a solo contribution of the IFG or a joint

involvement of the left pMTG and the left IFG in gesture–speech integration (9). On the other

hand, neither could we exclude the involvement of other brain areas, such as the anterior

temporal lobe (34), which may modulate activities in the IFG and pMTG.

5. Conclusion

In summary, with the help of the information-theoretic complexity metrics of entropy and MI,

we show that in multisensory semantic processing of gesture and speech, a probabilistically

updated representation is constructed in a dynamic interplay between gesture-primed

prediction and speech presentation. The probabilistic updating process is connected to

different ERP components and sequential cortical involvement of the pMTG-IFG-pMTG circuit.

A 5-step neural stage model is proposed for processing probabilistic gesture–speech

information, which advances our knowledge about the dynamic multisensory integration and

probabilistic language processing.

Funding: This research was supported by grants from the National Key Research and
Development Program of China (2021ZD0201501), the National Natural Science Foundation
of China (31822024, 31800964), the Scientific Foundation of Institute of Psychology, Chinese
Academy of Sciences (E2CX3625CX), and the Strategic Priority Research Program of
Chinese Academy of Sciences (XDB32010300).

Author contributions: Conceptualization, W.Y.Z. and Y.D.; Investigation, W.Y.Z.; Formal
Analysis, W.Y.Z.; Methodology, W.Y.Z.; Validation, X.L.; Visualization, W.Y.Z. and X.L.;
Funding Acquisition, W.Y.Z. and Y.D.; Supervision, Y.D.; Project administration, Y.D.; Writing –
Original Draft, W.Y.Z.; Writing – Review & Editing, W.Y.Z., X.L. and Y.D.

Declaration of interests: The authors declare no competing interests.

 Figure legends

Figure 1. Experimental design, stimulus characteristics, and quantification formulas. (**A**)

Experimental stimuli. Twenty gestures were paired with 20 relevant speech stimuli. Two

gating studies were executed to define the minimal length of each gesture and speech

required for semantic identification, namely, the discrimination point (DP) of gesture and the

identification point (IP) of speech. Overall, a mean of 183.78 ms (SD = 84.82) was found for

the DP of gestures and the IP of speech was 176.40 ms (SD = 66.21). The onset of speech

was set at the gesture DP. Eight time windows (TWs, duration = 40 ms) were segmented in

relative to the speech IP. (**B**) Procedure of Experiment 1. Semantically congruent gesture-

speech pairs were presented randomly with Electroencephalogram (EEG) recorded

simultaneously. Epochs were time locked to the onset of speech and lasted for 1000 ms. A

200 ms pre-stimulus baseline correction was applied before the onset of gesture stoke. (**C**)

Procedure of Experiment 2. Among the eight TWs, five (TW1, TW2, TW3, TW6, and TW7)

were chosen based on the significant results in our prior study (10). Double-pulse TMS was

delivered over each of the TW of either the pMTG or the IFG. (**C**) Quantification formulas.

Another two separate pre-tests were carried out to determine the nameability of isolated

gestures and speech, which was defined as the percentage of participants that provided the

mostly used label. Nameability for each item (*p(xi)* represents nameability of gesture and *p(yi)*

for nameability of speech) was transformed into Shannon's entropy (H) and the MI (I (gesture;

speech)) to capture the contribution of gesture and speech in multisensory information

processing.

Figure 2. ERP results. (**A**) Grand-average ERPs at the Cz electrode comparing trials with

the lower 50% (red lines) and the higher 50% (blue lines) of gesture entropy, speech entropy

or MI. Four ERP components in which there was a significant difference between the bottom

and top halves were selected (paired t test, p values corrected by FDR). (**B**) Correlations of

ERP amplitudes with three information models with best-fitting regression lines and

topographical voltage maps. Significant correlations are marked in red with spotted subset of

electrodes (Spearman correlation analysis, p values corrected by FDR). The solid rectangles

demarcate ROIs that showed a maximal value of correlation. LC: left central; LP: left posterior;

RA: right anterior; RC: right central.

Figure 3. Cortical engagement correlated with gesture entropy, speech entropy and MI.

Correlations of the TMS effect over the semantic congruency effect with three information

models are displayed with best-fitting regression lines. Significant correlations are marked in

red**.** * p <.05, ** p <.01 after FDR correction.

Figure 4. Proposed stages for probabilistic processing of gesture–speech information.

Correlations of cortical involvement over semantic congruency effect with three information

models were indicated by the Blue line and the Red lines, which reflect the TMS-disruption of

the pMTG and the IFG activities respectively. Black lines show the strongest correlations of

the ERP amplitudes with three information models. * p <.05, ** p <.01 after FDR correction.

References

1.   A. Kendon, Gesture. *Annu Rev Anthropol* **26**, 109-128 (1997).

2.   T. Slamacazacu, Nonverbal Components of Oral Communication and the Concept of
So-Called Mixed-Syntax - a Synthesis. *Degres*, E1-E24 (1993).

3.   P. Hagoort, On Broca, brain, and binding: a new framework. *Trends Cogn Sci* **9**, 416-423
(2005).

4.   P. Hagoort, L. Hald, M. Bastiaansen, K. M. Petersson, Integration of word meaning and
world knowledge in language comprehension. *Science* **304**, 438-441 (2004).

5.   A. Ozyurek, R. M. Willems, S. Kita, P. Hagoort, On-line integration of semantic
information from speech and gesture: Insights from event-related brain potentials. *J*
Cognitive Neurosci **19**, 605-616 (2007).

6.   H. Holle, T. C. Gunter, The role of iconic gestures in speech disambiguation: ERP
evidence. *J Cognitive Neurosci* **19**, 1175-1192 (2007).

7.   S. Kita, A. Ozyurek, What does cross-linguistic variation in semantic coordination of
speech and gesture reveal?: Evidence for an interface representation of spatial thinking
and speaking. *J Mem Lang* **48**, 16-32 (2003).

8.   P. Bernardis, M. Gentilucci, Speech and gesture share the same communication system.
Neuropsychologia **44**, 178-190 (2006).

9.   W. Y. Zhao, K. Riggs, I. Schindler, H. Holle, Transcranial magnetic stimulation over left
inferior frontal and posterior temporal cortex disrupts gesture-speech integration.
Journal of Neuroscience **38**, 1891-1900 (2018).

10.   W. Zhao, Y. Li, Y. Du, TMS reveals dynamic interaction between inferior frontal gyrus and
posterior middle temporal gyrus in gesture-speech semantic integration. *The Journal of*
Neuroscience 10.1523/jneurosci.1355-21.2021, 10356-10364 (2021).

11.   R. M. Willems, A. Ozyurek, P. Hagoort, Differential roles for left inferior frontal and
superior temporal cortex in multimodal integration of action and language. *Neuroimage*
47, 1992-2004 (2009).

12.   R. Jackendoff, Foundations of Language: Brain, Meaning, Grammar, Evolution. (2002).

13.   J. R. Brennan, E. P. Stabler, S. E. Van Wagenen, W. M. Luh, J. T. Hale, Abstract linguistic
structure correlates with temporal activity during naturalistic comprehension. *Brain and*
Language **157**, 81-94 (2016).

14.   K. Armeni, R. M. Willems, S. L. Frank, Probabilistic language models in cognitive
neuroscience: Promises and pitfalls. *Neuroscience Biobehavioral Review* **83**, 579-588
(2017).

15.   N. Chater, C. D. Manning, Probabilistic models of language processing and acquisition.
Trends in Cognitive Sciences **10**, 335-344 (2006).

16.   D. Norris, The Bayesian reader: Explaining word recognition as an optimal Bayesian
decision process. *Psychological Review* **113**, 327-357 (2006).

17.   B. R. Payne, C. L. Lee, K. D. Federmeier, Revisiting the incremental effects of context on
word processing: Evidence from single-word event-related brain potentials.
Psychophysiology **52**, 1456-1469 (2015).

18.   P. Tremblay, I. Deschamps, M. Baroni, U. Hasson, Neural sensitivity to syllable frequency

and mutual information in speech perception and production. *Neuroimage* **136**, 106-
121 (2016).

19.   A. Hodapp, M. Rabovsky, The N400 ERP component reflects an error-based implicit
learning signal during language comprehension. *European Journal of Neuroscience* **54**,
7125-7140 (2021).

20.   M. Rabovsky, S. S. Hansen, J. L. McClelland, Modelling the N400 brain potential as
change in a probabilistic representation of meaning. *Nat Hum Behav* **2**, 693-705 (2018).

21.   M. K. Leonard, K. E. Bouchard, C. Tang, E. F. Chang, Dynamic Encoding of Speech
Sequence Probability in Human Temporal Cortex. *Journal of Neuroscience* **35**, 7203-
7214 (2015).

22.   P. W. Donhauser, S. Baillet, Two Distinct Neural Timescales for Predictive Speech
Processing. *Neuron* **105**, 385-+ (2020).

23.   C. E. Shannon, A Mathematical Theory of Communication. *Bell Syst Tech J* **27**, 379-423
(1948).

24.   K. D. Federmeier, H. Mai, M. Kutas, Both sides get the point: hemispheric sensitivities to
sentential constraint. *Mem Cognit* **33**, 871-886 (2005).

25.   S. D. Kelly, C. Kravitz, M. Hopkins, Neural correlates of bimodal speech and gesture
comprehension. *Brain and Language* **89**, 253-260 (2004).

26.   Y. C. Wu, S. Coulson, Meaningful gestures: Electrophysiological indices of iconic gesture
comprehension. *Psychophysiology* **42**, 654-667 (2005).

27.   I. Fritz, S. Kita, J. Littlemore, A. Krott, Multimodal language processing: How preceding
discourse constrains gesture interpretation and affects gesture integration when
gestures do not synchronise with semantic affiliates. *J Mem Lang* **117**, 104191 (2021).

28.   T. C. Gunter, J. E. D. Weinbrenner, When to Take a Gesture Seriously: On How We Use
and Prioritize Communicative Cues. *J Cognitive Neurosci* **29**, 1355-1367 (2017).

29.   K. A. DeLong, T. P. Urbach, M. Kutas, Probabilistic word pre-activation during language
comprehension inferred from electrical brain activity. *Nature Neuroscience* **8**, 1117-1121
(2005).

30.   R. M. Willems, S. L. Frank, A. D. Nijhof, P. Hagoort, A. van den Bosch, Prediction During
Natural Language Comprehension. *Cerebral Cortex* **26**, 2506-2516 (2016).

31.   G. Baggio, P. Hagoort, The balance between memory and unification in semantics: A
dynamic account of the N400. *Lang Cognitive Proc* **26**, 1338-1367 (2011).

32.   R. Levy, Expectation-based syntactic comprehension. *Cognition* **106**, 1126-1177 (2008).

33.   A. Caramazza, A. E. Hillis, B. C. Rapp, C. Romani, The multiple semantics hypothesis:
Multiple confusions? *Cognitive Neuropsychology* **7**, 161-189 (1990).

34.   K. Patterson, P. J. Nestor, T. T. Rogers, Where do you know what you know? The
representation of semantic knowledge in the human brain. *Nature Reviews*
Neuroscience **8**, 976-987 (2007).

35.   M. A. L. Ralph, E. Jefferies, K. Patterson, T. T. Rogers, The neural and computational
bases of semantic cognition. *Nature Reviews Neuroscience* **18**, 42-55 (2017).

36.   X. Xu, I. L. Hanganu-Opatz, M. Bieler, Cross-talk of low-level sensory and high-level
cognitive processing: Development, mechanisms, and relevance for cross-modal abilities
of the brain. *Frontiers in Neurorobotics* **14**, 7 (2020).

37.   H. Damasio, T J. Grabowski, D. Tranel, R D. Hichwa, A R. Damasio, A neural basis for

600   lexical retrieval. *Nature* **380**, 499-505 (1996).

601   38.   L. Fadiga, L. Craighero, E. Olivier, Human motor cortex excitability during the perception
602   of others' action. *Curr Opin Neurobiol* **15**, 213-218 (2005).

603   39.   M. H. Giard, F. Peronnet, Auditory-visual integration during multimodal object
604   recognition in humans: A behavioral and electrophysiological study. *J Cognitive*
605   *Neurosci* **11**, 473-490 (1999).

606   40.   L. H. Arnal, B. Morillon, C. A. Kell, A. L. Giraud, Dual Neural Routing of Visual Facilitation
607   in Speech Processing. *Journal of Neuroscience* **29**, 13445-13453 (2009).

608   41.   B. T. Gold *et al.*, Dissociation of automatic and strategic lexical-semantics: Functional
609   magnetic resonance imaging evidence for differing roles of multiple frontotemporal
610   regions. *Journal of Neuroscience* **26**, 6523-6532 (2006).

611   42.   G. R. Kuperberg, T. Sitnikova, B. M. Lakshmanan, Neuroanatomical distinctions within the
612   semantic system during sentence comprehension: Evidence from functional magnetic
613   resonance imaging. *Neuroimage* **40**, 367-388 (2008).

614   43.   H. Brouwer, M. W. Crocker, N. J. Venhuizen, J. C. J. Hoeks, A Neurocomputational Model
615   of the N400 and the P600 in Language Processing. *Cogn Sci* **41 Suppl 6**, 1318-1352
616   (2017).

617   44.   P. Hagoort, MUC (Memory, Unification, Control) and beyond. *Frontiers in Psychology* **4**,
618   416 (2013).

619   45.   J. K. Bizley, R. K. Maddox, A. K. C. Lee, Defining auditory-visual objects: Behavioral tests
620   and physiological mechanisms. *Trends in Neurosciences* **39**, 74-85 (2016).

621   46.   C. M. J. Y. Tesink *et al.*, Unification of Speaker and Meaning in Language Comprehension:
622   An fMRI Study. *J Cognitive Neurosci* **21**, 2085-2099 (2009).

623   47.   T. O. Bergmann, G. Hartwigsen, Inferring causality from noninvasive brain stimulation in
624   cognitive neuroscience. *Journal of Cognitive Neuroscience* . **33**, 195-225 (2021).

625   48.   M. R. Nuwer *et al.*, IFCN standards for digital recording of clinical EEG. The International
626   Federation of Clinical Neurophysiology. *Electroencephalogr Clin Neurophysiol Suppl* **52**,
627   11-14 (1999).

628   49.   A. Delorme, S. Makeig, EEGLAB: an open source toolbox for analysis of single-trial EEG
629   dynamics including independent component analysis. *J Neurosci Methods* **134**, 9-21
630   (2004).

633   **Figure 1**

A Experimental stimuli

Gesture DP: M=183.78 ms (SD=84.82)

Gesture

Speech

Speech IP: M=176.40 ms (SD=66.21)

B Experiment 1

C Experiment 2

D Quantification formulas

Figure 1. Experimental design, stimulus characteristics, and quantification formulas. (A)
Experimental stimuli. Twenty gestures were paired with 20 relevant speech stimuli. Two
gating studies were executed to define the minimal length of each gesture and speech
required for semantic identification, namely, the discrimination point (DP) of gesture and the
identification point (IP) of speech. Overall, a mean of 183.78 ms (SD = 84.82) was found for
the DP of gestures and the IP of speech was 176.40 ms (SD = 66.21). The onset of speech
was set at the gesture DP. Eight time windows (TWs, duration = 40 ms) were segmented in
relative to the speech IP. **(B)** Procedure of Experiment 1. Semantically congruent gesture-
speech pairs were presented randomly with Electroencephalogram (EEG) recorded
simultaneously. Epochs were time locked to the onset of speech and lasted for 1000 ms. A
200 ms pre-stimulus baseline correction was applied before the onset of gesture stoke. **(C)**
Procedure of Experiment 2. Among the eight TWs, five (TW1, TW2, TW3, TW6, and TW7)
were chosen based on the significant results in our prior study (10). Double-pulse TMS was
delivered over each of the TW of either the pMTG or the IFG. **(C)** Quantification formulas.
Another two separate pre-tests were carried out to determine the nameability of isolated
gestures and speech, which was defined as the percentage of participants that provided the
mostly used label. Nameability for each item ($p(xi)$ represents nameability of gesture and $p(yi)$
for nameability of speech) was transformed into Shannon's entropy (H) and the MI (I (gesture;
speech)) to capture the contribution of gesture and speech in multisensory information
processing.

Figure 2

Figure 2. ERP results. (**A**) Grand-average ERPs at the Cz electrode comparing trials with the lower 50% (red lines) and the higher 50% (blue lines) of gesture entropy, speech entropy or MI. Four ERP components in which there was a significant difference between the bottom and top halves were selected (paired t test, p values corrected by FDR). (**B**) Correlations of ERP amplitudes with three information models with best-fitting regression lines and topographical voltage maps. Significant correlations are marked in red with spotted subset of electrodes (Spearman correlation analysis, p values corrected by FDR). The solid rectangles demarcate ROIs that showed a maximal value of correlation. LC: left central; LP: left posterior; RA: right anterior; RC: right central.

672   **Figure 3**

675   **Figure 3. Cortical engagement correlated with gesture entropy, speech entropy and MI.**

676   Correlations of the TMS effect over the semantic congruency effect with three information

677   models are displayed with best-fitting regression lines. Significant correlations are marked in

678   red. * p <.05, ** p <.01 after FDR correction.

Figure 4

 Figure 4. Proposed stages for probabilistic processing of gesture–speech information.
Correlations of cortical involvement over semantic congruency effect with three information
models were indicated by the Blue line and the Red lines, which reflect the TMS-disruption of
the pMTG and the IFG activities respectively. Black lines show the strongest correlations of
the ERP amplitudes with three information models. * *p* <.05, ** *p* <.01 after FDR correction.

 Supplementary Table 1. Stimuli characteristics.

Item	pair	Gesture nameability	Speech nameability	Gesture entropy	Speech entropy	MI	Gesture bins	Speech bins	MI bins
an4 (press)	1	0.59	0.9	0.449	0.137	0.496	6	6	7
yun4 (iron)	1	0.16	0.98	0.423	0.029	0.447	5	2	6
bai1 (break)	2	0.86	0.98	0.187	0.029	0.191	2	2	2
yao2 (shake)	2	0.2	0.98	0.464	0.029	0.487	7	2	6
ca1 (wipe)	3	0.46	0.9	0.515	0.137	0.582	8	6	9
reng1 (throw)	3	0.73	1	0.331	0.000	0.331	4	1	4
ding1(hammer)	4	0.5	1	0.500	0.000	0.500	8	1	7
tui1 (push)	4	0.76	1	0.301	0.000	0.301	4	1	4
ti2 (lift)	5	0.37	1	0.531	0.000	0.531	10	1	8
feng2 (sew)	5	0.8	1	0.258	0.000	0.258	3	1	2
ji3 (squeeze)	6	0.46	1	0.515	0.000	0.515	9	1	8
si1 (tear)	6	0.96	1	0.057	0.000	0.057	1	1	1
jiao3 (stir)	7	1	1	0.000	0.000	0.000	1	1	1
shan1 (slap)	7	0.21	0.75	0.473	0.311	0.697	7	8	10
ju4 (saw)	8	0.71	0.89	0.351	0.150	0.381	5	7	5
ning2 (twist)	8	0.79	0.96	0.269	0.057	0.279	3	4	3
sao3 (sweep)	9	0.17	1	0.435	0.000	0.435	6	1	5
jian3 (cut)	9	0.81	0.89	0.246	0.150	0.260	2	7	3
pen1 (spray)	10	0.45	0.97	0.518	0.043	0.541	9	3	9
qie1 (cut)	10	0.33	0.91	0.528	0.124	0.607	10	5	10

692
693