Progressive neural engagement within the IFG-pMTG circuit as gesture and speech entropy and MI advances

Wanying Zhao[1,2*]; Zhouyi Li[1,5]; Xiang Li[1,2]; Yi Du[1,2,3,4*]

[1] CAS Key Laboratory of Behavioral Science, Institute of Psychology, Chinese Academy of Sciences, Beijing, China 100101

[2] Department of Psychology, University of Chinese Academy of Sciences, Beijing, China 100049

[3] CAS Center for Excellence in Brain Science and Intelligence Technology, Shanghai, China 200031

[4] Chinese Institute for Brain Research, Beijing, China 102206

[5] School of Psychology, Central China Normal University, Wuhan, China 430079

* Corresponding author:

Dr. Yi Du, Email: duyi@psych.ac.cn

16 Lincui Road, Chaoyang district, Beijing, China 100101

Dr. Wanying Zhao, Email: zhaowy@psych.ac.cn

Lincui Road, Chaoyang District, Beijing, China 100101

Abstract

Semantic representation emerges from distributed multisensory modalities, yet a

comprehensive understanding of the functional changing pattern within convergence zones or

hubs integrating multisensory semantic information remains elusive. In this study, employing

information-theoretic metrics, we quantified gesture and speech information, alongside their

interaction, utilizing entropy and mutual information (MI). Neural activities were assessed via

interruption effects induced by High-Definition transcranial direct current stimulation (HD-

tDCS). Additionally, chronometric double-pulse transcranial magnetic stimulation (TMS) and

high-temporal event-related potentials were utilized to decipher dynamic neural changes

resulting from various information contributors. Results showed gradual inhibition of both

inferior frontal gyrus (IFG) and posterior middle temporal gyrus (pMTG) as degree of gesture-

speech integration, indexed by MI, increased. Moreover, a time-sensitive and staged

progression of neural engagement was observed, evidenced by distinct correlations between

neural activity patterns and entropy measures of speech and gesture, as well as MI, across

early sensory and lexico-semantic processing stages. These findings illuminate the gradual

nature of neural activity during multisensory gesture-speech semantic processing, shaped by

dynamic gesture constraints and speech encoding, thereby offering insights into the neural

mechanisms underlying multisensory language processing.

Keywords: gesture-speech integration; pMTG-IFG circuit; information theory; multisensory;

semantic; dual-stage modal

Introduction

Semantic representation, distinguished by its cohesive conceptual nature, emerges from distributed modality-specific regions. Consensus acknowledges the presence of 'convergence zones' within the temporal and inferior parietal areas [1], or the 'semantic hub' located in the anterior temporal lobe[2], pivotal for integrating, converging, or distilling multimodal inputs. Contemporary perspectives on semantic processing portray it as a sequence of quantitatively functional mental states defined by a specific parser[3], unified by statistical regularities among multiple sensory inputs[4] through hierarchical prediction and multimodal interactions[5-9]. Hence, proposals suggest that the coherent semantic representation emerges from statistical learning mechanisms within these 'convergence zones' or 'semantic hub' [10-12], potentially functioning in a graded manner[12,13]. However, the exact nature of the graded structure within these integration hubs, along with their temporal dynamics, remains elusive.

Among the many kinds of multimodal extralinguistic information, representational gesture is the one that is related to the semantic content of co-occurring speech[14,15]. Representational gesture is regarded as 'part of language'[16] or functional equivalents of lexical units that alternate and integrate with speech into a 'single unification space' to convey a coherent meaning[17-19]. Empirical studies have investigated the semantic integration between representational gesture (gesture in short hereafter) and speech by manipulating their semantic relationship[20-23] and revealed a mutual interaction between them[24-26] as reflected by the N400 latency and amplitude[19] as well as common neural underpinnings in the left inferior frontal gyrus (IFG) and posterior middle temporal gyrus (pMTG)[20,27,28]. Quantifying the amount of information from both sources and their interaction, the present study delved into cortical engagement and temporal dynamics during multisensory gesture-speech integration, with a specific focus on the IFG and pMTG, alongside various ERP components.

To this end, we developed an analytic approach to directly probe the contribution of gesture and speech during multisensory semantic integration, while adopting the information-theoretic complexity metrics of *entropy* and *mutual information* (MI). Entropy captures the disorder or randomness of information and is used as a measurement of the uncertainty of representation activated when an event occurs[29]. MI illustrates the mutual constraint that the

two variables impose on each other[30]. Herein, during gesture-speech integration, entropy

measures the uncertainty of information of gesture or speech, while MI indexes the degree of

integration.

Three experiments were conducted to unravel the intricate neural processes underlying

gesture-speech semantic integration. In **Experiment 1,** High-Definition Transcranial Direct

Current Stimulation (HD-tDCS) was utilized to administer Anodal, Cathodal and Sham

stimulation to either the IFG or the pMTG. HD-tDCS induces membrane depolarization with

anodal stimulation and membrane hyperpolarisation with cathodal stimulation[31], thereby

respectively increasing or decreasing cortical excitability in the targeted brain area. Hence,

Experiment 1 aimed to determine whether the facilitation effect (Anodal-tDCS minus Sham-

tDCS) and/or the inhibitory effect (Cathodal-tDCS minus Sham-tDCS) on the integration hubs

of IFG and/or pMTG were modulated by the degree of gesture-speech integration, indexed

with MI. Considering the different roles of IFG and pMTG during integration[28], as well as the

various ERP components reported in prior investigations, such as the early sensory effect as

P1 and N1–P2[33,34], the N400 semantic conflict effect[19,34,35], and the late positive component

(LPC) reconstruction effect[36,37]. **Experiment 2** employed chronometric double-pulse

transcranial magnetic stimulation (TMS) to target short time windows along the gesture-

speech integration period[32]. In parallel, **Experiment 3** utilized high-temporal event-related

potentials to explore whether the various neural engagements were temporally and

progressively modulated by distinct information contributors during gesture-speech integration.

Material and methods

Participants

Ninety-eight young Chinese participants signed written informed consent forms and took part

in the present study (Experiment 1: 29 females, 23 males, age = 20 ± 3.40 years; Experiment

2: 11 females, 13 males, age = 23 ± 4.88 years; Experiment 3: 12 females, 10 males, age =

21 ± 3.53 years). All of the participants were right-handed (Experiment 1: laterality quotient

(LQ)[38] = 88.71 ± 13.14; Experiment 2: LQ = 89.02 ± 13.25; Experiment 3: LQ = 88.49 ±

12.65), had normal or corrected-to-normal vision and were paid ¥100 per hour for their

participation. All experiments were approved by the Ethics Committee of the Institute of

Psychology, Chinese Academy of Sciences.

Stimuli

Twenty gestures (**Appendix Table 1**) with 20 semantically congruent speech signals taken

from previous study[28] were used. The stimuli set were recorded from two native Chinese

speakers (1 male, 1 female) and validated by replicating the semantic congruency effect with

30 participants. Results showed a significantly (t(29) = 7.16, p < 0.001) larger reaction time

when participants were asked to judge the gender of the speaker if gesture contained

incongruent semantic information with speech (a 'cut' gesture paired with speech word '喷

pen1 (spray)': mean = 554.51 ms, SE = 11.65) relative to when they were semantically

congruent (a 'cut' gesture paired with '剪 jian3 (cut)' word: mean = 533.90 ms, SE = 12.02)[28].

Additionally, two separate pre-tests with 30 subjects in each (pre-test 1: 16 females, 14

males, age = 24 ± 4.37 years; pre-test 2: 15 females, 15 males, age = 22 ± 3.26 years) were

conducted to determine the comprehensive values of gesture and speech. Participants were

presented with segments of increasing duration, beginning at 40 ms, and were prompted to

provide a single verb to describe either the isolated gesture they observed (pre-test 1) or the

isolated speech they heard (pre-test 2). For each pre-test, the response consistently provided

by participants for four to six consecutive instances was considered the comprehensive

answer for the gesture or speech. The initial instance duration was marked as the

discrimination point (DP) for gesture (mean = 183.78 ± 84.82ms) or the identification point (IP)

for speech (mean = 176.40 ± 66.21ms) (**Figure 1A top**).

To quantify information content, responses for each item were converted into Shannon's

entropy (H) as a measure of information richness (**Figure 1A bottom**). With no significant

gender differences observed in both gesture (t(20) = 0.21, p = 0.84) and speech (t(20) = 0.52,

p = 0.61), responses were aggregated across genders, resulting in 60 answers per item

(**Appendix Table 2**). Here, p(x_i) and p(y_i) represent the distribution of 60 answers for a given

gesture (**Appendix Table 2B**) and speech (**Appendix Table 2A**), respectively. High entropy

indicates diverse answers, reflecting broad representation, while low entropy suggests

focused lexical recognition for a specific item (**Figure 2B**). The joint entropy computation for

gesture and speech, represented by H(xi, yi), involved amalgamating datasets of gesture and

speech responses to depict their combined distributions. For specific gesture-speech

combinations, equivalence between the joint entropy and the sum of individual entropies

(gesture or speech) indicates absence of overlap in response sets. Conversely, significant

overlap, denoted by a considerable number of shared responses between gesture and

speech datasets, leads to a noticeable discrepancy between joint entropy and the sum of

gesture and speech entropies. This quantification of gesture-speech overlap was

operationalized by subtracting the joint entropy of gesture-speech from the combined

entropies of gesture and speech, indexed by Mutual Information (MI) (see **Appendix Table**

2C). Elevated MI values thus signify substantial overlap, indicative of a robust mutual

interaction between gesture and speech. The quantitative information for each stimulus,

including gesture entropy, speech entropy, joint entropy, and MI are displayed in **Appendix**

Table 3.

To accurately assess whether entropy/MI corresponds to stepped neural changes, the

current study aggregated neural responses (Non-invasive brain stimulation (NIBS) inhibition

effect or ERP amplitude) with identical entropy or MI values prior to conducting correlational

analyses.

Experimental procedure

Adopting a semantic priming paradigm of gestures onto speech[16,32], speech onset was set to

be at the DP of each accompanying gesture. An irrelevant factor of gender congruency (e.g.,

a man making a gesture combined with a female voice) was created[27,28,39]. This involved

aligning the gender of the voice with the corresponding gender of the gesture in either a

congruent (e.g., male voice paired with a male gesture) or incongruent (e.g., male voice

paired with a female gesture) manner. This approach served as a direct control mechanism,

facilitating the investigation of the automatic and implicit semantic interplay between gesture

and speech[39]. In light of previous findings indicating a distinct TMS-disruption effect on the

semantic congruency of gesture-speech interactions[28], both semantically congruent and

incongruent pairs were included in Experiment 1 and Experiment 2. Experiment 3, conversely,

exclusively utilized semantically congruent pairs to elucidate ERP metrics indicative of

nuanced semantic progression.

Gesture–speech pairs were presented randomly using Presentation software

(www.neurobs.com). Participants underwent Experiment 1, comprising 480 gesture-speech

pairs, across three separate sessions spaced one week apart for each participant. In each

session, participants received one of three stimulation types (Anodal, Cathodal, or Sham).

Experiment 2 consisted of 800 pairs and was conducted across 15 blocks over three days,

with one week between sessions. The order of stimulation site and time window (TW) was

counterbalanced using a Latin square design. Experiment 3, comprising 80 gesture-speech

pairs, was completed in a single-day session. Participants were asked to look at the screen

but respond with both hands as quickly and accurately as possible merely to the gender of the

voice they heard. The RT and the button being pressed were recorded. The experiment

started with a fixation cross presented on the center of the screen, which lasted for 0.5-1.5

sec.

Experiment 1: HD-tDCS protocol and data analysis

HD-tDCS protocol employed a constant current stimulator (The Starstim 8 system) delivering

stimulation at an intensity of 2000mA. A 4 * 1 ring-based electrode montage was utilized,

comprising a central electrode (stimulation) positioned directly over the target cortical area

and four return electrodes encircling it to provide focused stimulation. For targeting the left

IFG at Montreal Neurological Institute (MNI) coordinates (-62, 16, 22), electrode F7 was

selected as the optimal cortical projection site[40], with the four return electrodes placed on AF7,

FC5, F9, and FT9. For stimulation of the pMTG at coordinates (-50, -56, 10), TP7 was

identified as the cortical projection site[40], with return electrodes positioned on C5, P5, T9, and

P9. The stimulation parameters included a 20-minute duration with a 5-second fade-in and

fade-out for both Anodal and Cathodal conditions. The Sham condition involved a 5-second

fade-in followed by only 30 seconds of stimulation, then 19'20 minutes of no stimulation, and

finally a 5-second fade-out (**Figure 1B**). Stimulation was controlled using NIC software, with

participants blinded to the stimulation conditions.

All incorrect responses (702 out of the total number of 24960, 2.81% of trials) were

excluded. To eliminate the influence of outliers, a 2SD trimmed mean for every participant in

each session was also calculated. Our present analysis focused on Pearson correlations

between the interruption effects of HD-tDCS (active tDCS minus sham tDCS) on the semantic

congruency effect (difference in reaction time between semantic incongruent and semantic

congruent pairs) and the variables of gesture entropy, speech entropy, or MI. This

methodology seeks to determine whether the neural activity within the left IFG and pMTG is

gradually affected by varying levels of gesture and speech information during integration, as

quantified by entropy and MI.

Experiment 2: TMS protocol and data analysis

At an intensity of 50% of the maximum stimulator output, double-pulse TMS was delivered via

a 70 mm figure-eight coil using a Magstim Rapid² stimulator (Magstim, UK) over either the left

IFG in TW3 (-40~0 ms in relative to speech identification point (IP)) and TW6 (80~120 ms,) or

the left pMTG in TW1 (-120 ~ -80 ms), TW2 (-80 ~ -40 ms) and TW7 (120~160 ms). Among

the TWs that covering the period of gesture-speech integration, those that showed a TW-

selective disruption of gesture-speech integration were selected[28] (**Figure 1C**).

High-resolution (1 × 1 × 0.6 mm) T1-weighted MRI scans were obtained using a Siemens

3T Trio/Tim Scanner for image-guided TMS navigation. Frameless stereotaxic procedures

(BrainSight 2; Rogue Research) allowed real-time stimulation monitoring. To ensure precision,

individual anatomical images were manually registered by identifying the anterior and

posterior commissures. Subject-specific target regions were defined using trajectory markers

in the MNI coordinate system. Vertex was used as control.

All incorrect responses (922 out of the total number of 19200, 4.8% of trials) were

excluded. We focused our analysis on Pearson correlations of the TMS interruption effects

(active TMS minus vertex TMS) of the semantic congruency effect with the gesture entropy,

speech entropy or MI. By doing this, we can determine how the time-sensitive contribution of

the left IFG and pMTG to gesture–speech integration was affected by gesture and speech

information distribution. FDR correction was applied for multiple comparisons.

Experiment 3: Electroencephalogram (EEG) recording and data analysis

EEG were recorded from 48 Ag/AgCl electrodes mounted in a cap according to the 10-20

system[41], amplified with a PORTI-32/MREFA amplifier (TMS International B.V., Enschede, NL)

and digitized online at 500 Hz (bandpass, 0.01-70 Hz). EEGLAB, a MATLAB toolbox, was

used to analyze the EEG data[42]. Vertical and horizontal eye movements were measured with

4 electrodes placed above the left eyebrow, below the left orbital ridge and at bilateral

external canthus. All electrodes were referenced online to the left mastoid. Electrode

impedance was maintained below 5 KΩ. The average of the left and right mastoids was used

for re-referencing. A high-pass filter with a cutoff of 0.05 Hz and a low-pass filter with a cutoff

of 30 Hz were applied. Semi-automated artifact removal, including independent component

analysis (ICA) for identifying components of eye blinks and muscle activity, was performed

(**Figure 1D**). Participants with rejected trials exceeding 30% of their total were excluded from

further analysis.

All incorrect responses were excluded (147 out of 1760, 8.35% of trials). To eliminate the

influence of outliers, a 2 SD trimmed mean was calculated for every participant in each

condition. Data were epoched from the onset of speech and lasted for 1000 ms. To ensure a

clean baseline with no stimulus presented, a 200 ms pre-stimulus baseline correction was

applied before gesture onset.

To objectively identify the time windows of activated components, grand-average ERPs at

electrode Cz were compared between the higher (≥50%) and lower (<50%) halves for gesture

entropy (**Figure 5A1**), speech entropy (**Figure 5B1**), and MI (**Figure 5C1**). Consequently,

four ERP components were predetermined: the P1 effect observed within the time window of

0-100 ms[33,34], the N1-P2 effect observed between 150-250ms[33,34], the N400 within the

interval of 250-450ms[19,34,35], and the LPC spanning from 550-1000ms[36,37]. Additionally, seven

regions-of-interest (ROIs) were defined in order to locate the modulation effect on each ERP

component: left anterior (LA): F1, F3, F5, FC1, FC3, and FC5; left central (LC): C1, C3, C5,

CP1, CP3, and CP5; left posterior (LP): P1, P3, P5, PO3, PO5, and O1; right anterior (RA):

F2, F4, F6, FC2, FC4, and FC6; right central (RC): C2, C4, C6, CP2, CP4, and CP6; right

posterior (RP): P2, P4, P6, PO4, PO6, and O2; and midline electrodes (ML): Fz, FCz, Cz, Pz,

Oz, and CPz[43].

Subsequently, cluster-based permutation tests[44] in Fieldtrip was further used to determine

the significant clusters of adjacent time points and electrodes of ERP amplitude between the

higher and lower halves of gesture entropy, speech entropy and MI, respectively. The

electrode-level type I error threshold was set to 0.025. Cluster-level statistic was estimated

through 5000 Monte Carlo simulations, where the cluster-level statistic is the sum of T-values

for each stimulus within a cluster. The cluster-level type I error threshold was set to 0.05.

Clusters with a p-value less than the critical alpha-level are considered to be conditionally

different.

Paired t-tests were conducted to compare the lower and upper halves of each information

model for the averaged amplitude within each ROI or cluster across the four ERP time

windows, separately. Pearson correlations were calculated between each model value and

each averaged ERP amplitude in each ROI or cluster, individually. False discovery rate (FDR)

correction was applied for multiple comparisons.

Results

Experiment 1: Modulation of left pMTG and IFG engagement by gradual changes in

gesture-speech semantic information

In the IFG, one-way ANOVA examining the effects of three tDCS conditions (Anodal, Cathodal,

or Sham) on semantic congruency (RT (semantic incongruent) – RT (semantic congruent))

demonstrated a significant main effect of stimulation condition (F(2, 75) = 3.673, p = 0.030,

ηp2 = 0.089). Post hoc paired t-tests indicated a significantly reduced semantic congruency

effect between the Cathodal condition and the Sham condition (t(26) = -3.296, p = 0.003, 95%

CI = [-11.488, 4.896]) (**Figure 3A left**). Subsequent Pearson correlation analysis revealed that

the reduced semantic congruency effect was progressively associated with the MI, evidenced

by a significant correlation between the Cathodal-tDCS effect (Cathodal-tDCS minus Sham-

tDCS) and MI (r = -0.595, p = 0.007, 95% CI = [-0.995, -0.195]) (**Figure 3B**).

Similarly, in the pMTG, a one-way ANOVA assessing the effects of three tDCS conditions

on semantic congruency also revealed a significant main effect of stimulation condition (F(2,

75) = 3.250, p = 0.044, ηp2 = 0.080). Subsequent paired t-tests identified a significantly

reduced semantic congruency effect between the Cathodal condition and the Sham condition

(t(25) = -2.740, p = 0.011, 95% CI = [-11.915, 6.435]) (**Figure 3A right**). Moreover, a

significant correlation was observed between the Cathodal-tDCS effect and MI (r = -0.457, p =

0.049, 95% CI = [-0.900, -0.014]) (**Figure 3B**). RTs of congruent and incongruent trials of IFG

and pMTG in each of the stimulation conditions were shown in **Appendix Table 4A.**

Experiment 2: Time-sensitive modulation of left pMTG and IFG engagements by

gradual changes in gesture-speech semantic information

A 2 (TMS effect: active - Vertex) × 5 (TW) ANOVA on semantic congruency revealed a

significant interaction between TMS effect and TW (F(3.589, 82.538) = 3.273, p = 0.019, ηp2

= 0.125). Further t-tests identified a significant TMS effect over the pMTG in TW1 (t(23) = -

3.068, p = 0.005, 95% CI = [-6.838, 0.702]), TW2 (t(23) = -2.923, p = 0.008, 95% CI = [-6.490,

0.644]), and TW7 (t(23) = -2.005, p = 0.047, 95% CI = [-5.628, 1.618]). In contrast, a

significant TMS effect over the IFG was found in TW3 (t(23) = -2.335, p = 0.029, 95% CI = [-

5.928, 1.258]), and TW6 (t(23) = -4.839, p < 0.001, 95% CI = [-7.617, -2.061]) (**Figure 4A**).

Raw RTs of congruent and incongruent trials were shown in **Appendix Table 4B.**

Additionally, a significant negative correlation was found between the TMS effect (a more

negative TMS effect represents a stronger interruption of the integration effect) and speech

entropy when the pMTG was inhibited in TW2 (r = -0.792, p = 0.004, 95% CI = [-1.252, -

0.331]). Meanwhile, when the IFG activity was interrupted in TW6, a significant negative

correlation was found between the TMS effect and gesture entropy (r = -0.539, p = 0.014, 95%

CI = [-0.956, -0.122]), speech entropy (r = -0.664, p = 0.026, 95% CI = [-1.255, -0.073]), and

MI (r = -0.677, p = 0.001, 95% CI = [-1.054, -0.300]) (**Figure 4B**).

Experiment 3: Temporal modulation of P1, N1-P2, N400 and LPC components by

gradual changes in gesture-speech semantic information

Topographical maps illustrating amplitude differences between the lower and higher halves of

speech entropy demonstrate a central-posterior P1 amplitude (0-100 ms, **Figure 5B2 middle**).

Aligning with prior findings[33], the paired t-tests demonstrated a significantly larger P1

amplitude within the ML ROI (t(22) = 2.510, p = 0.020, 95% confidence interval (CI) = [1.66,

3.36]) when contrasting stimuli with higher 50% speech entropy against those with lower 50%

speech entropy (**Figure 5B2 left**). Subsequent correlation analyses unveiled a significant

increase in the P1 amplitude with the rise in speech entropy within the ML ROI ($r = 0.609$, $p =$

0.047, 95% CI = [0.039, 1.179], **Figure 5B2 right**). Furthermore, a cluster of neighboring

time-electrode samples exhibited a significant contrast between the lower 50% and higher 50%

of speech entropy, revealing a P1 effect spanning 16 to 78 ms at specific electrodes (FC2,

FCz, C1, C2, Cz, and CPz, **Figure 5B3 middle**) ($t(22) = 2.754$, $p = 0.004$, 95% confidence

interval (CI) = [1.65, 3.86], **Figure 5B3 left**), with a significant correlation with speech entropy

($r = 0.636$, $p = 0.035$, 95% CI = [0.081, 1.191], **Figure 5B3 right**).

Additionally, topographical maps comparing the lower 50% and higher 50% gesture

entropy revealed a frontal N1-P2 amplitude (150-250 ms, **Figure 5A2 middle**). In accordance

with previous findings on bilateral frontal N1-P2 amplitude[33], paired t-tests displayed a

significantly larger amplitude for stimuli with lower 50% gesture entropy than with higher 50%

entropy in both ROIs of LA ($t(22) = 2.820$, $p = 0.011$, 95% CI = [2.21, 3.43]) and RA ($t(22) =$

2.223, $p = 0.038$, 95% CI = [1.56, 2.89]) (**Figure 5A2 left**). Moreover, a negative correlation

was found between N1-P2 amplitude and gesture entropy in both ROIs of LA ($r = -0.465$, $p =$

0.039, 95% CI = [-0.87, -0.06]) and RA ($r = -0.465$, $p = 0.039$, 95% CI = [-0.88, -0.05]) (**Figure**

5A2 right). Additionally, through a cluster-permutation test, the N1-P2 effect was identified

between 184 to 202 ms at electrodes FC4, FC6, C2, C4, C6, and CP4 (**Figure 5A3 middle**)

($t(22) = 2.638$, $p = 0.015$, 95% CI = [1.79, 3.48], (**Figure 5A3 left**)), exhibiting a significant

correlation with gesture entropy ($r = -0.485$, $p = 0.030$, 95% CI = [-0.91, -0.06], **Figure 5A3**

right).

Furthermore, in line with prior research[45], a left-frontal N400 amplitude (250-450 ms) was

discerned from topographical maps of both gesture entropy (**Figure 5A4 middle**) and MI

(**Figure 5C2 middle)**. Notably, a larger N400 amplitude in the LA ROI was consistently

observed for stimuli with lower 50% values compared to those with higher 50% values, both

for gesture entropy ($t(22) = 2.455$, $p = 0.023$, 95% CI = [1.95, 2.96], **Figure 5A4 left**) and MI

($t(22) = 3.00$, $p = 0.007$, 95% CI = [2.54, 3.46], **Figure 5C2 left**). Concurrently, a negative

correlation was noted between the N400 amplitude and both gesture entropy ($r = -0.480$, $p =$

0.032, 95% CI = [-0.94, -0.03], **Figure 5A4 right**) and MI ($r = -0.504$, $p = 0.028$, 95% CI = [-

0.97, -0.04], **Figure 5C2 right**) in the LA ROI.

The identified clusters with the N400 effect for gesture entropy (282 – 318 ms at

electrodes FC1, FCz, C1, and Cz, **Figure 5A5 middle**) (t(22) = 2.828, p = 0.010, 95% CI =

[2.02, 3.64], **Figure 5A5 left**) exhibited significant correlation between the N400 amplitude

and gesture entropy (r = -0.445, p = 0.049, 95% CI = [-0.88, -0.01], **Figure 5A5 right**).

Similarly, the cluster with the N400 effect for MI (294 – 306 ms at electrodes F1, F3, Fz, FC1,

FC3, FCz, and C1, **Figure 5C3 middle**) (t(22) = 2.461, p = 0.023, 95% CI = [1.62, 3.30],

Figure 5C3 left) also exhibited significant correlation (r = -0.569, p = 0.011, 95% CI = [-0.98, -

0.16], **Figure 5C5 right**).

Finally, consistent with previous findings[33], an anterior LPC effect (550-1000 ms) was

observed in topographical maps comparing stimuli with lower and higher 50% speech entropy

(**Figure 5B4 middle**). The reduced LPC amplitude was evident in the paired t-tests

conducted in ROIs of LA (t(22) = 2.614, p = 0.016, 95% CI = [1.88, 3.35]); LC (t(22) = 2.592, p

= 0.017, 95% CI = [1.83, 3.35]); RA (t(22) = 2.520, p = 0.020, 95% CI = [1.84, 3.24]); and ML

(t(22) = 2.267, p = 0.034, 95% CI = [1.44, 3.10]) (**Figure 5B4 left**). Simultaneously, a marked

negative correlation with speech entropy was evidenced in ROIs of LA (r = -0.836, p = 0.001,

95% CI = [-1.26, -0.42]); LC (r = -0.762, p = 0.006, 95% CI = [-1.23, -0.30]); RA (r = -0.774, p

= 0.005, 95% CI = [-1.23, -0.32]) and ML (r = -0.730, p = 0.011, 95% CI = [-1.22, -0.24])

(**Figure 5B4 right**). Additionally, a cluster with the LPC effect (644 - 688 ms at electrodes Cz,

CPz, P1, and Pz, **Figure 5B5 middle**) (t(22) = 2.754, p = 0.012, 95% CI = [1.50, 4.01],

Figure 5B5 left) displayed a significant correlation with speech entropy (r = -0.699, p = 0.017,

95% CI = [-1.24, -0.16], **Figure 5B5 right**).

Discussion

Through mathematical quantification of gesture and speech information using entropy and

mutual information (MI), we examined the functional pattern and dynamic neural structure

underlying multisensory semantic integration. Our results, for the first time, unveiled a

progressive inhibition of IFG and pMTG by HD-tDCS as the degree of gesture-speech

interaction, indexed by MI, advanced (**Experiment 1**). Additionally, the gradual neural

engagement was found to be time-sensitive and staged, as evidenced by the selectively

interrupted time windows (**Experiment 2**) and the distinct correlated ERP components

(**Experiment 3**), which were modulated by top-down gesture constrain (gesture entropy) and

bottom-up speech. These findings significantly expand our understanding of the cortical

foundations of statistically regularized multisensory semantic information.

It is widely acknowledged that a single, amodal system mediates the interactions among

perceptual representations of different modalities[11,12,46]. Moreover, observations have

suggested that semantic dementia patients experience increasing overregularization of their

conceptual knowledge due to the progressive deterioration of this amodal system[47].

Consequently, a graded function and structure of the transmodal 'hub' representational

system has been proposed[12,48,49]. In line with this, through the use of NIBS techniques such

as HD-tDCS and TMS, the present study provides compelling evidence that the integration

hubs of gesture and speech, namely the pMTG and IFG, function in a graded manner. This is

supported by the progressive inhibition effect observed in these brain areas as the entropy

and mutual information of gesture and speech advances.

Moreover, by dividing the potential integration period into eight TWs relative to the

speech IP and administering inhibitory double-pulse TMS across each TW, the current study

attributed the gradual TMS-selective regional inhibition to distinct information sources. In the

early pre-lexical TW2 of gesture-speech integration, the suppression effect observed in the

pMTG was correlated with speech entropy. Conversely, in the later post-lexical TW6, the IFG

interruption effect was influenced by both gesture entropy, speech entropy, and their MI. A

dual-stage pMTG-IFG-pMTG neurocircuit loop during gesture-speech integration has been

proposed previous[28]. As an extension, the present study unveils a staged accumulation of

engagement within the neurocircuit linking the transmodal regions of pMTG and IFG, arising

from distinct contributors of information.

Furthermore, we disentangled the sub-processes of integration with high-temporal ERPs,

when representations of gesture and speech were variously presented. Early P1-N1 and P2

sensory effects linked to perception and attentional processes[34,50] was comprehended as a

reflection of the early audiovisual gesture-speech integration in the sensory-perceptual

processing chain[51]. Note that a semantic priming paradigm was adopted here to create a top-

down prediction of gesture over speech. The observed positive correlation of the P1 effect

with speech entropy and the negative correlation of the N1-P2 effect with gesture entropy

suggest that the early interaction of gesture-speech information was modulated by both top-

down gesture prediction and bottom-up speech processing. Additionally, the lexico-semantic

effect of the N400 and the LPC were differentially mediated by top-down gesture prediction,

bottom-up speech encoding and their interaction: the N400 was negatively correlated with

both the gesture entropy and MI, but the LPC was negatively correlated only with the speech

entropy. Nonetheless, activation of representation is modulated progressively. The input

stimuli would activate a dynamically distributed neural landscape, the state of which

constructs gradually as measured by entropy and MI and correlates with the

electrophysiological signals (N400 and LPC) which indicate the change of lexical

representation. Consistent with recent account in multisensory information processing[4,52], our

findings further confirm that the changed activation pattern can be induced from directions of

both top-down and bottom-up gesture-speech processing.

Considering the close alignment of the ERP components with the TWs of TMS effect, it is

reasonable to speculate the ERP components with the cortical involvements (**Figure 6**).

Consequently, referencing the recurrent neurocircuit connecting the left IFG and pMTG for

semantic unification[53], we extended the previously proposed two-stage gesture-speech

integration circuit[28] into sequential steps. First, bottom-up speech processing mapping

acoustic signal to its lexical representation was performed from the STG/S to the pMTG. The

larger speech entropy was, the greater effort was made during the matching of the acoustic

input with its stored lexical representation, thus leading to a larger involvement of the pMTG

at pre-lexical stage (TW2) and a larger P1 effect (**Figure 6①**). Second, the gesture

representation was activated in the pMTG and further exerted a top-down modulation over the

phonological processing of speech in the STG/S[54]. The higher certainty of gesture, a larger

modulation of gesture would be made upon speech, as indexed by a smaller gesture entropy

with an enhanced N1-P2 amplitude (**Figure 6②**). Third, information was relayed from the

pMTG to the IFG for sustained activation, during which a semantic constraint from gesture

has been made on the semantic retrieval of speech. Greater TMS effect over the IFG at post-

lexical stage (TW6) accompanying with a reduced N400 amplitude were found with the

increase of gesture entropy, when the representation of gesture was wildly distributed and the

constrain over the following speech was weak **(Figure 6③)**. Fourth, the activated speech

representation was compared with that of the gesture in the IFG. At this stage, the larger

overlapped neural populations activated by gesture and speech as indexed by a larger MI, a

greater TMS disruption effect of the IFG and a reduced N400 amplitude indexing easier

integration and less semantic conflict were observed (**Figure 6④**). Last, the activated speech

representation would disambiguate and reanalyze the semantic information that was stored in

the IFG and further unify into a coherent comprehension in the pMTG[17,55]. The more uncertain

information being provided by speech, as indicated by an increased speech entropy, a

stronger reweighting effect was made over the activated semantic information, resulting in a

strengthened involvement of the IFG as well as a reduced LPC amplitude (**Figure 6⑤**).

Note that the sequential cortical involvement and ERP components discussed above are

derived from a deliberate alignment of speech onset with gesture DP, creating an artificial

priming effect with gesture semantically preceding speech. Caution is advised when

generalizing these findings to the spontaneous gesture-speech relationships, although

gestures naturally precede speech[56].

Limitations exist. ERP components and cortical engagements were linked through

intermediary variables of entropy and MI. Dissociations were observed between ERP

components and cortical engagement. Importantly, there is no direct evidence of the brain

structures underpinning the corresponding ERPs, necessitating clarification in future studies.

Additionally, not all influenced TWs exhibited significant associations with entropy and MI.

While HD-tDCS and TMS may impact functionally and anatomically connected brain

regions[43,44], the graded functionality of every disturbed period is not guaranteed. Caution is

warranted in interpreting the causal relationship between NIBS inhabitation effects and

information-theoretic metrics (entropy and MI). Finally, the current study incorporated a

restricted set of entropy and MI measures. The generalizability of the findings should be

assessed in future studies using a more extensive range of matrices.

In summary, utilizing information-theoretic complexity metrics such as entropy and mutual

information (MI), our study demonstrates that multisensory semantic processing, involving

gesture and speech, gives rise to dynamically evolving representations through the interplay

between gesture-primed prediction and speech presentation. This process correlates with the

progressive engagement of the pMTG-IFG-pMTG circuit and various ERP components.

These findings significantly advancing our understanding of the neural mechanisms

underlying   multisensory   semantic   integration.

Acknowledgments

This research was supported by grants from the STI 2030—Major Projects 2021ZD0201500, the National Natural Science Foundation of China (31822024, 31800964), the Scientific Foundation of Institute of Psychology, Chinese Academy of Sciences (E2CX3625CX), and the Strategic Priority Research Program of Chinese Academy of Sciences (XDB32010300).

Author contributions

Conceptualization, W.Y.Z. and Y.D.; Investigation, W.Y.Z. and Z.Y.L.; Formal Analysis, W.Y.Z. and Z.Y.L.; Methodology, W.Y.Z. and Z.Y.L.; Validation, Z.Y.L. and X.L.; Visualization, W.Y.Z. and Z.Y.L. and X.L.; Funding Acquisition, W.Y.Z. and Y.D.; Supervision, Y.D.; Project administration, Y.D.; Writing – Original Draft, W.Y.Z.; Writing – Review & Editing, W.Y.Z., Z.Y.L., X.L., and Y.D.

Competing interests

The authors declare no competing interests.

References

1. Damasio, H., Grabowski, T.J., Tranel, D., Hichwa, R.D., and Damasio, A.R. (1996). A

neural basis for lexical retrieval. Nature *380*, 499-505. DOI 10.1038/380499a0.

2. Patterson, K., Nestor, P.J., and Rogers, T.T. (2007). Where do you know what you

know? The representation of semantic knowledge in the human brain. Nature

Reviews Neuroscience *8*, 976-987. 10.1038/nrn2277.

3. Brennan, J.R., Stabler, E.P., Van Wagenen, S.E., Luh, W.M., and Hale, J.T. (2016).

Abstract linguistic structure correlates with temporal activity during naturalistic

comprehension. Brain and Language *157*, 81-94. 10.1016/j.bandl.2016.04.008.

4. Benetti, S., Ferrari, A., and Pavani, F. (2023). Multimodal processing in face-to-face

interactions: A bridging link between psycholinguistics and sensory neuroscience.

Front Hum Neurosci *17*, 1108354. 10.3389/fnhum.2023.1108354.

5. Armeni, K., Willems, R.M., and Frank, S.L. (2017). Probabilistic language models in

cognitive neuroscience: Promises and pitfalls. Neurosci Biobehav R *83*, 579-588.

10.1016/j.neubiorev.2017.09.001.

6. Leonard, M.K., Bouchard, K.E., Tang, C., and Chang, E.F. (2015). Dynamic encoding

of speech sequence probability in human temporal cortex. Journal of Neuroscience

35, 7203-7214. 10.1523/JNEUROSCI.4100-14.2015.

7. Goldstein, A., Zada, Z., Buchnik, E., Schain, M., Price, A., Aubrey, B., Nastase, S.A.,

Feder, A., Emanuel, D., Cohen, A., et al. (2022). Shared computational principles for

language processing in humans and deep language models. Nature Neuroscience *25*,

369-+. 10.1038/s41593-022-01026-4.

8.   Heilbron, M., Armeni, K., Schoffelen, J.-M., Hagoort, P., and de Lange, F.P. (2022). A

496   hierarchy of linguistic predictions during natural language comprehension. P Natl

497   Acad Sci USA *119*, e2201968119-e2201968119. 10.1073/pnas.2201968119.

498   9.   Kuperberg, G.R., and Jaeger, T.F. (2016). What do we mean by prediction in

499   language comprehension? Lang Cogn Neurosci *31*, 32-59.

500   10.1080/23273798.2015.1102299.

501   10.   Ralph, M.A.L. (2014). Neurocognitive insights on conceptual knowledge and its

502   breakdown. Philos T R Soc B *369*. ARTN 20120392 10.1098/rstb.2012.0392.

503   11.   Rogers, T.T., Ralph, M.A.L., Garrard, P., Bozeat, S., McClelland, J.L., Hodges, J.R.,

504   and Patterson, K. (2004). Structure and deterioration of semantic memory: A

505   neuropsychological and computational investigation. Psychological Review *111*, 205-

506   235. 10.1037/0033-295x.111.1.205.

507   12.   Ralph, M.A.L., Jefferies, E., Patterson, K., and Rogers, T.T. (2017). The neural and

508   computational bases of semantic cognition. Nature Reviews Neuroscience *18*, 42-55.

509   10.1038/nrn.2016.150.

510   13.   Holler, J., and Levinson, S.C. (2019). Multimodal language processing in human

511   communication. Trends in Cognitive Sciences *23*, 639-652.

512   10.1016/j.tics.2019.05.006.

513   14.   Hostetter, A., and Mainela-Arnold, E. (2015). Gestures occur with spatial and Motoric

514   knowledge: It's more than just coincidence. Perspectives on Language Learning and

515   Education *22*, 42-49. doi:10.1044/lle22.2.42.

15.   McNeill, D. (2005). Gesture and though (University of Chicago Press).

10.7208/chicago/9780226514642.001.0001.

16.   Kendon, A. (1997). Gesture. Annu Rev Anthropol *26*, 109-128.

10.1146/annurev.anthro.26.1.109.

17.   Hagoort, P. (2005). On broca, brain, and binding: a new framework. Trends in

Cognitive Sciences *9*, 416-423. 10.1016/j.tics.2005.07.004.

18.   Hagoort, P., Hald, L., Bastiaansen, M., and Petersson, K.M. (2004). Integration of

word meaning and world knowledge in language comprehension. Science *304*, 438-

441. 10.1126/science.1095455.

19.   Ozyurek, A., Willems, R.M., Kita, S., and Hagoort, P. (2007). On-line integration of

semantic information from speech and gesture: Insights from event-related brain

potentials. J Cognitive Neurosci *19*, 605-616. 10.1162/jocn.2007.19.4.605.

20.   Willems, R.M., Ozyurek, A., and Hagoort, P. (2009). Differential roles for left inferior

frontal and superior temporal cortex in multimodal integration of action and language.

Neuroimage *47*, 1992-2004. 10.1016/j.neuroimage.2009.05.066.

21.   Drijvers, L., Jensen, O., and Spaak, E. (2021). Rapid invisible frequency tagging

reveals nonlinear integration of auditory and visual information. Human Brain

Mapping *42*, 1138-1152. 10.1002/hbm.25282.

22.   Drijvers, L., and Ozyurek, A. (2018). Native language status of the listener modulates

the neural integration of speech and iconic gestures in clear and adverse listening

conditions. Brain and Language *177*, 7-17. 10.1016/j.bandl.2018.01.003.

23.   Drijvers, L., van der Plas, M., Ozyurek, A., and Jensen, O. (2019). Native and non-

native listeners show similar yet distinct oscillatory dynamics when using gestures to

access speech in noise. Neuroimage *194*, 55-67. 10.1016/j.neuroimage.2019.03.032.

24.   Holle, H., and Gunter, T.C. (2007). The role of iconic gestures in speech

disambiguation: ERP evidence. J Cognitive Neurosci *19*, 1175-1192.

10.1162/jocn.2007.19.7.1175.

25.   Kita, S., and Ozyurek, A. (2003). What does cross-linguistic variation in semantic

coordination of speech and gesture reveal?: Evidence for an interface representation

of spatial thinking and speaking. J Mem Lang *48*, 16-32. 10.1016/S0749-

596x(02)00505-3.

26.   Bernardis, P., and Gentilucci, M. (2006). Speech and gesture share the same

communication system. Neuropsychologia *44*, 178-190.

10.1016/j.neuropsychologia.2005.05.007.

27.   Zhao, W.Y., Riggs, K., Schindler, I., and Holle, H. (2018). Transcranial magnetic

stimulation over left inferior frontal and posterior temporal cortex disrupts gesture-

speech integration. Journal of Neuroscience *38*, 1891-1900. 10.1523/Jneurosci.1748-

17.2017.

28.   Zhao, W., Li, Y., and Du, Y. (2021). TMS reveals dynamic interaction between inferior

frontal gyrus and posterior middle temporal gyrus in gesture-speech semantic

integration. The Journal of Neuroscience, 10356-10364. 10.1523/jneurosci.1355-

21.2021.

29.   Shannon, C.E. (1948). A mathematical theory of communication. Bell Syst Tech J *27*,

379-423. 10.1002/j.1538-7305.1948.tb01338.x.

30.   Tremblay, P., Deschamps, I., Baroni, M., and Hasson, U. (2016). Neural sensitivity to

syllable frequency and mutual information in speech perception and production.

Neuroimage *136*, 106-121. 10.1016/j.neuroimage.2016.05.018.

31.   Bikson, M., Inoue, M., Akiyama, H., Deans, J.K., Fox, J.E., Miyakawa, H., and

Jefferys, J.G.R. (2004). Effects of uniform extracellular DC electric fields on

excitability in rat hippocampal slices. J Physiol-London *557*, 175-190.

10.1113/jphysiol.2003.055772.

32.   Pitcher, D., Walsh, V., Yovel, G., and Duchaine, B. (2007). TMS evidence for the

involvement of the right occipital face area in early face processing. Current Biology

17, 1568-1573. 10.1016/j.cub.2007.07.063.

33.   Federmeier, K.D., Mai, H., and Kutas, M. (2005). Both sides get the point:

hemispheric sensitivities to sentential constraint. Memory & Cognition *33*, 871-886.

10.3758/bf03193082.

34.   Kelly, S.D., Kravitz, C., and Hopkins, M. (2004). Neural correlates of bimodal speech

and gesture comprehension. Brain and Language *89*, 253-260. 10.1016/s0093-

934x(03)00335-3.

35.   Wu, Y.C., and Coulson, S. (2005). Meaningful gestures: Electrophysiological indices

of iconic gesture comprehension. Psychophysiology *42*, 654-667. 10.1111/j.1469-

8986.2005.00356.x.

36.   Fritz, I., Kita, S., Littlemore, J., and Krott, A. (2021). Multimodal language processing:

How preceding discourse constrains gesture interpretation and affects gesture

integration when gestures do not synchronise with semantic affiliates. J Mem Lang

117, 104191. 10.1016/j.jml.2020.104191.

37.   Gunter, T.C., and Weinbrenner, J.E.D. (2017). When to take a gesture seriously: On

584   how we use and prioritize communicative cues. J Cognitive Neurosci *29*, 1355-1367.

585   10.1162/jocn_a_01125.

586   38.   Oldfield, R.C. (1971). The assessment and analysis of handedness: the Edinburgh

587   inventory. Neuropsychologia *9*, 97-113. 10.1016/0028-3932(71)90067-4.

588   39.   Kelly, S.D., Creigh, P., and Bartolotti, J. (2010). Integrating speech and iconic

589   gestures in a Stroop-like task: Evidence for automatic processing. Journal of

590   Cognitive Neuroscience

591   *22*, 683-694. 10.1162/jocn.2009.21254.

592   40.   Koessler, L., Maillard, L., Benhadid, A., Vignal, J.P., Felblinger, J., Vespignani, H.,

593   and Braun, M. (2009). Automated cortical projection of EEG sensors: Anatomical

594   correlation via the international 10-10 system. Neuroimage *46*, 64-72.

595   10.1016/j.neuroimage.2009.02.006.

596   41.   Nuwer, M.R., Comi, G., Emerson, R., Fuglsang-Frederiksen, A., Guerit, J.M., Hinrichs,

597   H., Ikeda, A., Luccas, F.J., and Rappelsberger, P. (1999). IFCN standards for digital

598   recording of clinical EEG. The International Federation of Clinical Neurophysiology.

599   Electroencephalogr Clin Neurophysiol Suppl *52*, 11-14. 10.1016/S0013-

600   4694(97)00106-5.

601   42.   Delorme, A., and Makeig, S. (2004). EEGLAB: an open source toolbox for analysis of

602   single-trial EEG dynamics including independent component analysis. J Neurosci

603   Methods *134*, 9-21. 10.1016/j.jneumeth.2003.10.009.

604   43.   Habets, B., Kita, S., Shao, Z.S., Ozyurek, A., and Hagoort, P. (2011). The Role of

605   Synchrony and Ambiguity in Speech-Gesture Integration during Comprehension. J

606   Cognitive Neurosci *23*, 1845-1854. 10.1162/jocn.2010.21462.

607 44.   Oostenveld, R., Fries, P., Maris, E., and Schoffelen, J.-M. (2011). FieldTrip: Open

608   Source Software for Advanced Analysis of MEG, EEG, and Invasive

609   Electrophysiological Data. Computational Intelligence and Neuroscience *2011*,

610   156869. 10.1155/2011/156869.

611 45.   Kutas, M., and Federmeier, K.D. (2011). Thirty Years and Counting: Finding Meaning

612   in the N400 Component of the Event-Related Brain Potential (ERP). Annual Review

613   of Psychology, Vol 62 *62*, 621-647. 10.1146/annurev.psych.093008.131123.

614 46.   Noppeney, U. (2021). Perceptual Inference, Learning, and Attention in a Multisensory

615   World. Annual Review of Neuroscience, Vol 44, 2021 *44*, 449-473. 10.1146/annurev-

616   neuro-100120-085519.

617 47.   Rogers, T.T., Hodges, J.R., Ralph, M.A.L., and Patterson, K. (2003). Object

618   recognition under semantic impairment: The effects of conceptual regularities on

619   perceptual decisions. Lang Cognitive Proc *18*, 625-662.

620   10.1080/01690960344000053.

621 48.   Krieger-Redwood, K., Wang, X., Souter, N., Gonzalez Alam, T.R.d.J., Smallwood, J.,

622   Jackson, R.L., and Jefferies, E. (2024). Graded and sharp transitions in semantic

623   function in left temporal lobe. Brain and Language *251*, 105402.

624   https://doi.org/10.1016/j.bandl.2024.105402.

625 49.   Plaut, D.C. (2002). Graded modality-specific specialisation in semantics: A

626   computational account of optic aphasia. Cognitive Neuropsychology *19*, 603-639.

10.1080/02643290244000112.

50.   Fadiga, L., Craighero, L., and Olivier, E. (2005). Human motor cortex excitability

during the perception of others' action. Current Opinion in Neurobiology *15*, 213-218.

10.1016/j.conb.2005.03.013.

51.   Giard, M.H., and Peronnet, F. (1999). Auditory-visual integration during multimodal

object recognition in humans: A behavioral and electrophysiological study. J

Cognitive Neurosci *11*, 473-490. 10.1162/089892999563544.

52.   Trujillo, J.P., and Holler, J. (2023). Interactionally Embedded Gestalt Principles of

Multimodal Human Communication. Perspect Psychol Sci *18*, 1136-1159.

10.1177/17456916221141422.

53.   Hagoort, P. (2013). MUC (Memory, Unification, Control) and beyond. Frontiers in

Psychology *4*, 416. 10.3389/fpsyg.2013.00416.

54.   Bizley, J.K., Maddox, R.K., and Lee, A.K.C. (2016). Defining auditory-visual objects:

Behavioral tests and physiological mechanisms. Trends in Neurosciences *39*, 74-85.

10.1016/j.tins.2015.12.007.

55.   Tesink, C.M.J.Y., Petersson, K.M., van Berkum, J.J.A., van den Brink, D., Buitelaar,

J.K., and Hagoort, P. (2009). Unification of speaker and meaning in language

comprehension: An fMRI study. J Cognitive Neurosci *21*, 2085-2099.

10.1162/jocn.2008.21161.

56.   McNeill, D. (1992). Hand and mind : what gestures reveal about thought (University of

Chicago Press). 10.2307/1576015.

Figure 1. Experimental design, and stimulus characteristics.

(**A**) **Experimental stimuli.** Twenty gestures were paired with 20 relevant speech stimuli. Two gating studies were executed to define the minimal length of each gesture and speech required for semantic identification, namely, the discrimination point (DP) of gesture and the identification point (IP) of speech. Overall, a mean of 183.78 ms (SD = 84.82) was found for the DP of gestures and the IP of speech was 176.40 ms (SD = 66.21). The onset of speech was set at the gesture DP. Responses for each item were assessed utilizing information-theoretic complexity metrics to quantify the information content of both gesture and speech during integration, employing entropy and MI.

(**B**) **Procedure of Experiment 1.** HD-tDCS, including Anodal, Cathodal, or Sham conditions, was administered to the IFG or pMTG) using a 4 * 1 ring-based electrode montage. Electrode F7 targeted the IFG, with return electrodes placed on AF7, FC5, F9, and FT9. For pMTG stimulation, TP7 was targeted, with return electrodes positioned on C5, P5, T9, and P9. Sessions lasted 20 minutes, with a 5-second fade-in and fade-out, while the Sham condition involved only 30 seconds of stimulation.

(**C**) **Procedure of Experiment 2.** Eight time windows (TWs, duration = 40 ms) were segmented in relative to the speech IP. Among the eight TWs, five (TW1, TW2, TW3, TW6, and TW7) were chosen based on the significant results in our prior study[28]. Double-pulse TMS was delivered over each of the TW of either the pMTG or the IFG.

(**D**) **Procedure of Experiment 3.** Semantically congruent gesture-speech pairs were presented randomly with Electroencephalogram (EEG) recorded simultaneously. Epochs were time locked to the onset of speech and lasted for 1000 ms. A 200 ms pre-stimulus baseline correction was applied before the onset of gesture stoke. Various elicited

components were hypothesized.

(E-F) Proposed gradations in cortical engagements during gesture-speech information

changes. Stepwise variations in the quantity of gesture and speech information during

integration, as characterized by information theory metrics (**E**), are believed to the

underpinned by progressive neural engagement within the IFG-pMTG gesture-speech

integration circuit (**F**).

Figure 2. Quantification formulas (A) and distributions of each stimulus in Shannon's entropy (B).

Two separate pre-tests (N = 30) were conducted to assign a single verb for describing each of the isolated 20 gestures and 20 speech items. Responses provided for each item were transformed into Shannon's entropy using a relative quantification formula. Gesture (**B left**) and speech (**B right**) entropy quantify the randomness of gestural or speech information, representing the uncertainty of probabilistic representation activated when a specific stimulus occurs. Joint entropy (**B middle**) captures the widespread nature of the two sources of information combined. Mutual information (MI) was calculated as the difference between joint entropy with gesture entropy and speech entropy combined (**A**), thereby capturing the overlap of gesture and speech and representing semantic integration.

Figure 3. tDCS effect over semantic congruency.

(A) tDCS effect was defined as active-tDCS minus sham-tDCS. The semantic congruency effect was calculated as the reaction time (RT) difference between semantically incongruent and semantically congruent pairs.

(B) Correlations of the tDCS effect over the semantic congruency effect with three information models (gesture entropy, speech entropy and MI) are displayed with best-fitting regression lines. Significant correlations are marked in red. * $p < 0.05$, ** $p < 0.01$ after FDR correction.

706
Figure 4. TMS effect over semantic congruency.
(A) TMS effect was defined as active-TMS minus vertex-TMS. The semantic congruency
effect was calculated as the reaction time (RT) difference between semantically incongruent
and semantically congruent pairs.
(B) Correlations of the TMS effect over the semantic congruency effect with three information
models (gesture entropy, speech entropy and MI) are displayed with best-fitting regression
lines. Significant correlations are marked in red**.** * $p < 0.05$, ** $p < 0.01$, *** $p < 0.001$ after
FDR correction.
715

Figure 5. ERP results of gesture entropy (A), speech entropy (B) or MI (**C**)**.**
Four ERP components were identified from grand-average ERPs at the Cz electrode, contrasting trials with the lower 50% (red lines) and the higher 50% (blue lines) of gesture entropy, speech entropy or MI (**Top panels**). Clusters of adjacent time points and electrodes were subsequently identified within each component using a cluster-based permutation test (**Bottom right**). Topographical maps depict amplitude differences between the lower and higher halves of each information model, with significant ROIs or electrode clusters highlighted in black. Solid rectangles delineating the ROIs that exhibited the maximal correlation and paired t-values (**Bottom left**). T-test comparisons with normal distribution lines and correlations with best-fitting regression lines are calculated and illustrated between the average ERP amplitude within the rectangular ROI (**Bottom left**) or the elicited clusters (**Bottom right**) and the three information models individually. * $p < 0.05$, ** $p < 0.01$ after FDR correction.

Figure 6. Progressive processing stages of gesture–speech information within the pMTG-IFG loop.

Correlations between the TMS disruption effect of pMTG and IFG with three information models are represented by the orange line and the green lines, respectively. Black lines denote the strongest correlations of ROI averaged ERP components with three information models. * p < 0.05, ** p < 0.01 after FDR correction.

739 **Appendix Table 1. Gesture description and paring with incongruent and congruent**
740 **speech.**

Gesture	Description	Congruent speech	Incongruent speech
an4 (press)	press button	an4 (press)	yun4 (iron)
bai1 (break)	break chopsticks	bai1 (break)	yao2 (shake)
ca1 (wipe)	wipe desk	ca1 (wipe)	reng1 (throw)
ding1 (hammer)	hammer nail	ding1 (hammer)	tui1 (push)
feng2 (sew)	sew cloth	feng2 (sew)	ti2 (lift)
ji3 (squeeze)	squeeze sponge	ji3 (squeeze)	si1 (tear)
jian3 (cut)	cut paper	jian3 (cut)	sao1 (sweep)
jiao3 (stir)	stir flour	jiao3 (stir)	shan1 (slap)
ju4 (saw)	saw wood	ju4 (saw)	ning3 (twist)
ning3 (twist)	twist towel	ning3 (twist)	ju4 (saw)
pen1 (spray)	spray water	pen1 (spray)	qie1 (slice)
qie1 (slice)	slice fruit	qie1 (slice)	pen1 (spray)
reng1 (throw)	throw ball	reng1 (throw)	ca1 (wipe)
shan1 (slap)	slap face	shan1 (slap)	jiao3 (stir)
sao1 (sweep)	sweep floor	sao1 (sweep)	jian3 (cut)
si1 (tear)	tear paper	si1 (tear)	ji3 (squeeze)
ti2 (lift)	lift basket	ti2 (lift)	feng2 (sew)
tui1 (push)	push door	tui1 (push)	ding1 (hammer)
yao2 (shake)	shake bag	yao2 (shake)	bai1 (break)
yun4 (iron)	iron cloth	yun4 (iron)	an4 (press)

743 **Appendix Table 2. Examples of 'an4 (press)' for the calculation of speech entropy,**
744 **gesture entropy and mutual information (MI)**

746 **Table 2A:** Calculation of speech entropy for 'an4.wav (press)'

Answer	Number	p(yi)
a	1	0.016666667
an	33	0.55
e	1	0.016666667
en	23	0.383333333
eng	2	0.033333333

Equation: $-\sum_{i=1}^{n} p(y_i)\log\big(p(y_i)\big)$

748 **Table 2B:** Calculation of gesture entropy for 'an4.avi (press)'

Answer	Number	p(xi)
dian	6	0.1
bp	1	0.016666667
chuo	2	0.033333333
dain	1	0.016666667
an	33	0.55
diao	1	0.016666667
en	1	0.016666667
hua	1	0.016666667
shu	3	0.05
zhi	11	0.183333333

Equation: $-\sum_{i=1}^{n} p(x_i)\log\big(p(x_i)\big)$

750 **Table 2C:** Calculation of MI for 'an4.avi (press) + an4.wav (press)'

Answer	Number	p(xi,yi)
a	1	0.008333333
an	66	0.55
bp	1	0.008333333
chuo	2	0.016666667
dain	1	0.008333333
dian	6	0.05
diao	1	0.008333333
e	1	0.008333333
en	24	0.2
eng	2	0.016666667
hua	1	0.008333333
shu	3	0.025
zhi	11	0.091666667

Equation:

$$-\sum_{i=1}^{n} p(x_i)\log\big(p(x_i)\big) - \sum_{i=1}^{n} p(y_i)\log\big(p(y_i)\big) - \big\{-\sum_{i=1}^{n} p(x_i,y_i)\log\big(p(x_i|y_i)\big)\big\}$$

751
752

753 **Appendix Table 3. Quantitative information for each stimulus.**

Stimuli	Gesture entropy	Speech entropy	Joint entropy	Mutual information
an4 (press)	2.13	1.37	2.15	1.35
bai1 (break)	0.91	0.11	0.61	0.41
ca1 (wipe)	2.07	0.56	1.67	0.96
ding1 (hammer)	2.55	0.00	1.28	1.27
feng2 (sew)	3.04	0.00	1.95	1.09
ji3 (squeeze)	2.50	0.00	1.86	0.64
jian3 (cut)	0.12	0.00	0.07	0.05
jiao3 (stir)	1.83	0.63	1.46	1.01
ju4 (saw)	4.34	0.00	2.77	1.57
ning3 (twist)	0.59	0.63	0.53	0.69
pen1 (spray)	3.29	0.80	2.61	1.49
qie1 (slice)	3.23	0.47	2.31	1.38
reng1 (throw)	1.59	0.29	1.09	0.79
sao1 (sweep)	4.01	1.12	4.47	0.66
shan1 (slap)	1.54	0.33	1.10	0.78
si1 (tear)	0.21	0.00	0.12	0.09
ti2 (lift)	1.48	0.00	0.88	0.60
tui1 (push)	1.62	0.00	0.96	0.66
yao2 (shake)	4.26	0.12	2.93	1.46
yun4 (iron)	4.15	0.00	2.78	1.37

 Appendix Table 4. Raw RT of semantic congruent (Sc) and semantic incongruent (Si)

758 **in Experiment 1 and Experiment 2.**

760 **Table 4A:** RT of Sc and Si in three HD-tDCS stimulation conditions for IFG and pMTG

	Anodal		Cathodal		Sham	
	Sc (ms) (Rt±SE)	Si (ms) (Rt±SE)	Sc (ms) (Rt±SE)	Si(ms) (Rt±SE)	Sc (ms) (Rt±SE)	Si(ms) (Rt±SE)
tDCS over IFG	521.95 ±13.41	537.46 ±15.05	518.41 ±11.95	530.33 ±13.01	513.96 ±14.40	537.46 ±15.53
tDCS over pMTG	531.94 ±11.43	553.61 ±13.43	531.88 ±11.43	545.08 ±11.97	545.08 ±11.97	569.57 ±14.32

770 **Table 4B:** RT of Sc and Si in each time window (TW) for IFG, pMTG, and Vertex

	TW1		TW2		TW3		TW6		TW7	
	Sc (ms) (Rt±SE)	Si (ms) (Rt±SE)	Sc (ms) (Rt±SE)	Si(ms) (Rt±SE)	Sc (ms) (Rt±SE)	Si(ms) (Rt±SE)	Sc(ms) (Rt±SE)	Si(ms) (Rt±SE)	Sc (ms) (Rt±SE)	Si(ms) (Rt±SE)
TMS over Vertex	507.20 ±12.36	527.06 ±13.44	499.09 ±13.17	534.59 ±15.20	497.65 ±13.99	525.93 ±13.31	497.93 ±13.91	534.46 ±15.85	502.78 ±13.45	524.65 ±11.72
TMS over IFG	485.11 ±13.80	507.56 ±15.05	486.00 ±13.48	511.71 ±16.01	499.03 ±14.26	507.87 ±15.03	503.21 ±15.32	508.58 ±15.99	490.92 ±14.84	507.38 ±15.71
TMS over pMTG	498.16 ±15.77	504.78 ±15.10	500.52 ±16.35	510.24 ±16.45	498.42 ±15.26	509.74 ±15.89	497.32 ±15.57	514.01 ±15.87	497.54 ±16.82	502.57 ±16.08