# Deep Learning for Predicting 16S rRNA Gene Copy Number

**Jiazheng Miao[1], Tianlai Chen[1], Mustafa Misir[1, *], and Yajuan Lin[1, *]**

[1]*Department of Applied and Natural Science, Duke Kunshan University, Suzhou, China*

Correspondence*:

Mustafa Misir

Division of Natural and Applied Sciences, Duke Kunshan University, Duke Avenue No: 8,

Suzhou, 215316, China

mustafa.misir@dukekunshan.edu.cn

Yajuan Lin

Division of Natural and Applied Sciences, Duke Kunshan University, Duke Avenue No: 8,

Suzhou, 215316, China

linyajuan@gmail.com

**ABSTRACT**

**Background**

16S rRNA is a commonly used technique for identifying prokaryotes. However, this

approach can only reflect the proportion of sequencing reads, rather than the actual cell fraction.

To accurately represent actual cell fraction, bioinformatic tools that estimate the 16S gene copy

number (GCN) of unmeasured species are required. All currently available tools rely on

taxonomy or phylogeny to predict 16S GCN.

**Method**

This study develops a deep learning-based method that establishes a novel route. The

proposed approach, i.e., Artificial Neural Network Approximator for 16S rRNA Gene Copy

Number (ANNA16), essentially links 16S sequence string directly to GCN without the

construction of taxonomy or phylogeny.

**Results**

The computational analysis revealed the success of the deep learning model built on 16S

GCN data retrieved from rrnDB (N = 27,579). The resulting deep learning model outperforms

all the major and state-of-the-art algorithms in the literature.

**Conclusion**

ANNA16 is a state-of-the-art 16S GCN prediction tool based on deep learning. Its

advantages include a simple structure, faster inference speed, less computing consumption, and

satisfactory performance. For the accessibility of ANNA16, it is released as a public, end-to-

end, web-based tool that predicts copy numbers from 16S rRNA sequences.

## 1    INTRODUCTION

16S rRNA is the small subunit ribosomal RNA molecule found in prokaryotic ribosomes. As ribosomes are self-replicating, 16S rRNA is readily isolated, and its sequence changes slowly over time [1]. This characteristic allows 16S rRNA to be highly conserved within species [2], while the variance increases as inter-species relatedness decreases [1]. Therefore, 16S rRNA is used commonly to identify prokaryotes, or to detect relatedness among distant species by matching next-generation sequencing (NGS) data to reference databases [3], such as RDP and Greengenes. The relatedness can be represented as genetic distance among 16S rRNAs, such as mean nucleotide substitutions per site [3]. This technique, known as 16S rRNA metabarcoding, has been established as the gold standard for inferring organismal phylogeny and microbial ecology for over 20 years [4].

One of the critical limitations of 16S rRNA metabarcoding is that NGS determines the proportion of 16S rRNA read counts, rather than cell counts. Since it is typical for prokaryotes to have more than one copy of the 16S rRNA gene, the proportion of 16S rRNA read counts (also known as relative abundance) may not accurately reflect the taxonomic composition of a microbial community [5]. To address this issue and accurately represent the profile of the microbiota, the proportion of 16S rRNA read counts needs to be weighted by the inverse of 16S rRNA gene copy numbers (GCN). This step yields a corrected microbial composition that represents the proportion of cell counts of each lineage in the community [5].

To calculate 16S GCN, scientists typically rely on experimental methods such as whole genome sequencing [6] or competitive PCR [7]. However, these methods can be expensive or

culture-dependent, and so far, GCN data is only available for a limited number of species. To

overcome this limitation, bioinformatics tools have been developed to predict the GCN of

unmeasured species from measured species. Fortunately, 16S GCN is correlated with

relatedness across species [5, 8], meaning that 16S GCN variation is relatively low within

species but increases as relatedness decreases. This trait allows 16S GCN to be estimated from

phylogeny or taxonomy [8]. Currently, all available tools rely on this kind of method [3, 5, 6].

For example, one correction tool could construct one taxonomy or phylogenetic tree of the 16S

sequence and estimate the GCN of the unmeasured species from its close measured relatives.

For instance, rrnDB [6] is a well-established tool that corrects 16S GCN based on taxonomy.

Its algorithm calculates the mean 16S GCN of a taxon from the means of its sub-taxa.

Deep learning, as a popular machine learning strategy, comes with its potential of learning

complex patterns from biological sequencing data [9, 10]. This aspect can be beneficial as a

novel approach for predicting 16S GCN. Deep learning is essentially an Artificial Neural

Network (ANN). The concept of ANN is inspired by the way a human brain learns and

processes information through synaptic interactions between neurons [11]. An ANN is a

computational model that is constituted by multiple interconnected processing elements—

artificial neurons [11]. Neurons are utilized in groups as the layers of a network. Each artificial

neuron receives and processes input with a non-linear function, known as the activation

function [12]. Collectively, one ANN model learns to solve a specific task through capturing

non-linear trends and relationships from the presented data. Beyond these capabilities, ANNs

are even competent in disclosing relationships or mechanisms that are still unknown to

scientists [13]. Deep learning gets its name by having more than one (hidden) layer connecting

the input and output units. Having deeper networks refer to representing complex input-output

relationships while accommodating a large amount of data. In that sense, high-dimensional

biological data is a popular target for deep learning.

Recently, a broad spectrum of deep learning approaches has been applied to microbiology

research. Various deep learning architectures like Convolutional Neural Network (CNN), and

Recurrent Neural Network (RNN), have been used for metagenomic-based taxonomy

classification [14], host phenotype prediction [15], disease prediction [16], and microbial

community predication [17]. Some other works focus on data mining for antibiotic resistance

genes [18], antimicrobial peptides [19], microbial source [20], and raw sequencing data [21].

All these applications show the great potential of deep Learning for microbial studies. With

these present successes, it should be possible to estimate GCN directly from the 16S sequence

through an ANN, without the construction of taxonomy or phylogeny. To the best of our

knowledge, there are no deep learning-based methods utilized for the 16S rRNA-based copy

number estimation.

This study first trains SEM, the developed deep learning model, on the 16S full-length

sequence and compares the performance to the taxonomy-based and phylogeny-based

algorithms. However, due to drawbacks such as the relatively high error rate or higher costs,

microbiologists less commonly sequence the full length of 16S rRNA at present [22]. Full-

length 16S could be more widely used when the cost of long-read sequencing (also known as

third-generation sequencing) methods is further decreased. Alternatively, microbial studies

tend to target the hypervariable regions in 16S rRNA. 16S rRNA contains nine hypervariable

regions, interspersed among conserved regions (V1-V9) [23]. Mostly, microbiologist sequence

only one to three adjacent hypervariable regions by NGS to study the microbial ecology [22].

Therefore, this study also trains deep learning models on different combinations of the adjacent

hypervariable regions in 16S rRNA and compares the performance with conventional

algorithms. Finally, a deep learning-based bioinformatic tool for 16S GCN correction is

developed. The tool is compared with existing correction tools to assess the performance. One

state-of-the-art method of model explanation is also adopted to uncover how the deep learning

model understands a 16S sequence.

Based on the Stacked Ensemble Model, the most accurate method, this study presents

ANNA16 (Artificial Neural Network Approximator for 16S rRNA Gene Copy Number), an

end-to-end, web-based tool that predicts copy numbers from 16S rRNA sequences.

**2    MATERIALS AND METHODS**

**2.1.   Data Source and Preprocessing**

16S rRNA sequences and the GCN data used to train deep learning models in this study

are retrieved from rrnDB, version 5.8 [6]. The dataset includes a total of 29,267 16S genes with

unique accession numbers. Because raw 16S sequence data contains both (+) strands and (-)

strands, using it directly for taxonomy-based and phylogeny-based algorithms may cause bias.

Therefore, this study uses the BLASTN algorithm in the BLAST+ application, version 2.11.0

[24], to identify the sequence orientation. The first 50 nucleotides of the *E. coli* 16S sequence

(+) strand (accession number: GCF_002953035.1), which belong to the conserved region on

16S rRNA [25], were used as a template to determine the orientation of each 16S sequence.

Sequences with High-Scoring Segment Pairs (HSPs) that had sstart > send and evalue < 0.01

are considered (+) strands, while those with sstart < send and evalue < 0.01 are considered (-)

strands. Sequences that did not meet these criteria are labeled as unrecognizable and dropped

from the dataset. The reverse complement of (-) strand sequences is generated and added to the

(+) strands.

This study also addresses the issue of varied starting positions among 16S sequences in

the dataset by using employs HyperEx [26] to extract full-length sequences between primer

27F and primer 1492R (as listed in Table S1) to simulate NGS results of PCR amplicons. This

ensures all 16S sequences have uniform starting and ending positions. After this step, the

preprocessed dataset contains 27,579 sequences, including 1,550 genera. The average sequence

length is 1,499.03 nucleotides, with a standard deviation of 21.49 nucleotides. Gene copy

number ranges from 1 copy per genome to 21 copies per genome, with a mean value of 5.39

and a standard deviation of 2.78. This preprocessed dataset will be referred to as such in the

following content. Moreover, Abellan-Schneyder et al. (2021) [22] reported that V1-V2, V1-

V3, V3-V4, V4, V4-V5, V6-V8, and V7-V9 are frequently targeted subregions. Thus, this study

also uses primers listed in Table S1 and HyperEx to extract these subregions from the

preprocessed dataset.

Because a previous study points out that the performance of existing GCN correction tools

is unsatisfactory on clades that are distant from training data [3], this study would like to test

if deep learning could perform better on these distant clades. Therefore, this study splits the

preprocessed dataset into the train and test datasets based on when the sequences are published.

Specifically, sequences that already exist in the previous rrnDB release (version 5.7) are

selected as the train dataset for cross-validation, while sequences newly added in version 5.8

are selected as the test dataset. This splitting method produces a near-random test dataset

containing newly published sequences. The train dataset contains 19,520 sequences, involving

1,331 genera, with an average sequence length of 1,498.72 nucleotides and a standard deviation

of 21.41 nucleotides. Gene copy number ranges from 1 copy per genome to 21 copies per

genome, with a mean value of 5.26 and a standard deviation of 2.74. The test dataset contains

8,059 sequences, involving 676 genera, with an average sequence length is 1,499.79

nucleotides and a standard deviation of 21.67 nucleotides. Gene copy number ranges from 1

copy per genome to 20 copies per genome, with a mean value of 5.72 and a standard deviation

of 2.85. The test dataset includes 219 genera that are not present in the train dataset.

**2.2.  Conventional Algorithms and Existing Tools**

Sub-taxa averaging (TA) is one taxonomy-based algorithm. The algorithm calculates the

mean 16S GCN of a taxon from the means of its sub-taxa. To implement this algorithm, 16S

sequences are first input to *assignTaxonomy* function in the DADA2 package in R (version

1.21.0) [27], which yields two taxonomies based on RDP (version 18, formatted by DADA2)

[28] and Greengenes (version 13.8) [29] database, respectively. The algorithm first receives the

taxonomic and GCN data from the database and converts the data structure of the taxonomy to

an inheritance tree. In the tree, every taxon is viewed as a node on the tree, and the algorithm

computes the copy number of every node by taking the mean of its sub-nodes. If an unknown

query is given, it assigns the value of the query's parent node to the query node as an estimation.

This study also employs five phylogeny-based algorithms to compare with the deep

learning method: empirical probabilities (EP), subtree averaging (SA), phylogenetic

independent contrasts (PIC) [30], Sankoff's maximum-parsimony (MPR) [31], and weighted-

squared-change parsimony (WSCP) [32]. These algorithms first receive a pre-constructed tree

of 16S sequences and estimate the GCN of each ancestral node from its daughter species

through weighing each labeled daughter node with its phylogenetic distance to the parental

node [33]. To implement the algorithms, 16S sequences in the dataset are first aligned by

MAFFT v7.490 [34] and then converted to a phylogenetic tree by FastTree 2.1.10 [35]. The

algorithms are performed using the castor package in R [33], adjusted from the R script in

Louca, Doebeli, and Parfrey (2018) [3] (MPR is implemented by function *hsp_max_parsimony*,

WSCP by function *hsp_squared_change_parsimony*, SA by function *hsp_subtree_averaging*,

EP by function *hsp_empirical_probabilities*, and PIC by *hsp_independent_contrasts*). All

functions are set to default parameters.

After developing the deep learning-based tool, this study compares it with all available

tools on the test dataset, which are rrnDB [6], CopyRighter [5], PAPRICA [36], PICRUSt2

[37]. rrnDB is a taxonomy-based tool using sub-taxa averaging, while the latter three tools are

phylogeny-based. CopyRighter uses the PIC algorithm to pre-compute the copy number of all

taxa in the Greengenes database [29] and makes predictions by searching the lineages of the

queries in its pre-computed GCN table [5]. The original mission of PAPRICA and PICRUSt2

is to predict the metabolic profile of a microbial community based on the 16S data, but they

have the function of predicting the copy number of any given gene according to the phylogeny

[36, 37]. These two tools first utilize EPA-ng [38] to place the queries on their built-in

phylogenetic tree and use subtree-averaging (PAPRICA) or maximum parsimony (PICRUSt2)

algorithms to predict the copy number of the queries [36, 37]. Because rrnDB and CopyRighter

application output microbial community abundance instead of 16S GCN values directly, this

study retrieves their precomputed tables (rrnDB version 5.7) and predict GCN values by

searching the precomputed tables for assigned lineages. The taxonomy of full-length sequences

and all subregion sequences are generated by the *assignTaxonomy* function in the DADA2

package through RDP (version 18) and Greengenes (version 13.8, formatted by DADA2) [29]

database. The assigned RDP lineages are searched in the rrnDB precomputed table, and

Greengenes lineages are searched in CopyRighter precomputed table. As for PAPRICA and

PICRUSt2, the DNA sequences in the test dataset are directly input to the tools. For PAPRICA,

*paprica-run.sh* is called without additional parameters. For PTCRUSt2, *place_seqs.py* and

*hsp.py* are called without additional parameters.

**2.3.   Development of ANNA16**

2.3.1.   Framework

To build our deep predictive models, this study first implements a three-layer MLP

prototype model. The sequences in the train dataset are split for training and testing by 3:1. The

DNA sequences are preprocessed with K-merization. An example of a set with three 6-mers is

displayed in Figure 1a). The K-mers are converted into the number of counts in the set via the

*CountVectorizer* function in the scikit-learn module (version 0.23.2) [39]. The deep learning

model will intake the vector of occurrence counts and predicts the gene copy number.

After testing K from 3 to 7 on the prototype model, the model performance is found to

improve as K increased. However, a larger K also required significantly more memory.

Therefore, the optimal K value was determined to be 6, which provides good performance

without requiring excessive memory. 6-merization is to decompose the DNA sequence into a

set of sub-sequences of length 6.   With the K value determined, a Stacked Ensemble Model

(SEM) is constructed for 16S GCN prediction. The framework is demonstrated in Figure 1b).

The performance of the model is evaluated by compareing it with conventional algorithms

using a 5-fold cross-validation on full-length and subregional DNA sequences. Shapley

Additive exPlanations (SHAP) [40] is introduced here for post-hoc interpretability. The entire

study is conducted with Python 3.8 and Tensorflow 2.8.0 on Nividia RTX 3090.

2.3.2.  Model Construction

The deep learning model employs a strategy of ensemble learning, known as model

stacking. This involves training multiple base-models on the available data and then using a

meta-model to accept the output of all base-models and make the final prediction. The stacked

model would typically perform better than any single base-model [41, 42]. In this study, the

Stacked Ensemble Model combines one MLP model with other classic machine learning

models. MLP is a type of artificial neural network that consists of layers of artificial neurons,

and the input is processed layer by layer [11]. The calculation of the output for each neuron is

as follows [11]:

235
$$v_k = \sum_{i=0}^{n} \omega_{k,i} x_i$$

236
$$\gamma_k = \varphi(v_k + v_{k_0})$$

237 where $v_k$ is the net output of neuron $k$, with $x_1, x_2, \ldots, x_n$ being the input from the last

238 layer, and $\omega_{k,1}, \omega_{k,2}, \ldots, \omega_{k,n}$ being the weights on the input. $\gamma_k$ is the output of the neuron,

239 where $v_{k_0}$ represents the bias, and $\varphi(.)$ refers to the activation function. And the MLP part

240 is trained with Rooted Mean Squared Error (RMSE) loss:

241
$$\text{RMSE} = \sqrt{\frac{\sum_{i=0}^{n}(Y_{true} - Y_{pred})^2}{n}}$$

where $n$ is the size of the input dataset, $Y_{true}$ is the true value of copy number, $Y_{pred}$ is the

value of the predicted copy number.

To build the Stacked Ensemble Model, several classic machine learning algorithms are

tested as base-models. These algorithms include Support Vector Machine (SVM) [43], Random

Forest [44], K-nearest Neighbors [45], and Gradient Boosting [46]. Linear Regression, Ridge

Regression [47], and Lasso Regression [48] are tested as meta-models. All machine learning

algorithms are implemented by the scikit-learn module (version 0.23.2). After testing, MLP

and SVM are selected as the base-models and Ridge Regression as the meta-model, as shown

in Figure 2c). For dimensionality reduction, Principal Component Analysis (PCA) is

implemented using the *PCA* function in scikit-learn, with *n_components* set to 100. SVM is

implemented by the *SVR* function in scikit-learn, and Ridge Regression by the *Ridge* function

in scikit-learn.

The parameter of SEM is optimized through the *SMAC4BB* function in the SMAC3

package (version 1.4.0) [49] for 500 iterations. For the MLP component, hyperparameters

including the number of dense layers, hidden layer size, activation functions, and learning rate

are tuned. The number of dense layers of the model is tested in the range of [1, 7], hidden layer

size from the range of [1, 1024], activation functions are selected among Rectified Linear Unit

(ReLU), Exponential Linear Unit (ELU), Gaussian Error Linear Unit (GELU), Scaled

Exponential Linear Unit (SELU), and Linear, and the learning rate is tested in the range of

[0.00005, 0.1]. The final MLP architecture (Figure 2d) contains a dense block of 6 hidden

layers, with neuron numbers of 489, 926, 645, 929, 582, and 82 respectively, and the activation

functions are GELU, ReLU, ReLU, ELU, GELU, and Linear respectively. For SVM, the *kernel*

value is chosen from "rbf", "sigmoid", and "linear", *gamma* is tested between "scale" and

"auto", and *C* is tested as a float in the range of [0.3, 0.9] or as an integer in the range of [1,

100]. For Ridge, the value of *alpha* tested as a float in the range of [0.3, 0.9] or as an integer in

the range of [1, 100]. After tuning, the optimized parameters are *kernel = 'rbf', gamma =*

*'auto', C = 11*, and *alpha = 49* (a complete list of parameters is shown in Table S2).

2.3.3.  Dismissed Machine Learning Algorithms

This study also used tested a Transformer model and a Residual Multi-layer Perceptron for

16S GCN prediction. The Transformer model is based on the original transformer encoder

architecture with cosine learning rate decay [50]. It is followed by global average pooling, and

two dense layers. Embedding and position encoding are used as input for the Transformer

model. Residual Multi-layer Perceptron uses Residual Connection architectures, which involve

skipping connections to jump over two to three layers [51]. However, these models do not

perform well in the study and are therefore excluded.

**2.4.   Case Study**

Based on the SEM method, this study presents ANNA16 (Artificial Neural Network

Approximator for 16S rRNA Gene Copy Number), an end-to-end tool that predicts copy

numbers from 16S rRNA sequences. To demonstrate ANNA16's performance, a case study is

designed that simulates two mock communities *in silico*. rrnDB, CopyRighter, PAPRICA, and

PTCRUSt2 are also applied to estimate the mock communities' microbial profile as a positive

control. The simulated communities are two commercially available mock communities, one

even community (ATCC MSA-2003) and one staggered community (ATCC MSA-1001). The

information of the mock communities is shown in Table S3. Such mock communities have

been used by Moriya (2021) to study methods of quantifying a microbial community [52]. Both

mock communities consist of ten common bacterial strains, but with different ratios. This study

retrieves genome sequences of the ten strains from NCBI, copy number data from rrnDB

(version 5.7), and assigns a cell count value to each strain by assuming each community has

1,000,000 cells. Table S3 shows the basic information about the mock communities. To extract

16S full-length sequences from the genomes, HyperEx is used in the same way as described in

the Data Source and Preprocessing.

To evaluate the accuracy of community profile prediction, Bray-Curtis Dissimilarity [53]

is calculated between the true cell fraction and the estimated cell fraction by each tool. The

Bray-Curtis Dissimilarity is a commonly used method in ecology and biology to measure the

compositional dissimilarity between two different communities. A higher Bray-Curtis

Dissimilarity value indicates the greater dissimilarity between the two communities [53]. Its

calculation is as follows:

$$BC = 1 - \frac{2C_{AB}}{S_A + S_B}$$

where *BC* is the Bray-Curtis Dissimilarity value, *A* and *B* are two communities, $C_{AB}$ is the sum

of the lesser values for species present in both communities, $S_A$ and $S_B$ are the total number of

species counted at both communities. The *vegdist* function in the vegan (version 2.5-7) package

of R are used to calculate the Bray-Curtis Dissimilarity values, with the *method* parameter set

to "bray".

**2.5.   Deep Learning Model Explanation**

To further explain ANNA16's prediction, this study uses SHAP [40], a unified

measurement of feature importance by quantifying the individual contribution of each feature

to a model prediction. This method is based on both collational game theory [54] and the

classical Shapley method [55] and views each feature as a player in Shapley. The marginal

contribution can be estimated under multiple feature subsets, and the final contribution is the

sum of all marginal contributions. A positive SHAP value denotes that the feature contributes

positively to the model's prediction over the model expectation, whereas a negative value

denotes that the feature contributes negatively. In this study, each K-mer is considered a feature.

To calculate the SHAP value for each K-mer, the preprocessed dataset and pre-trained

ANNA16 are input to the *KernelExplainer* function in shap module (version 0.41.0) in Python.

The function views each prediction of every single sequence in the dataset as an independent

game and calculates SHAP values for each game.

This study randomly samples 10% of the whole dataset for SHAP value analysis (N =

2758). As a result, a list of 2,758 SHAP values is assigned to every K-mer to represent the K-

mer's overall contribution. These SHAP values are mapped back to the 16S sequence to

investigate if there is a positional pattern in contribution. Each sequence is first transformed

into an array of K-mers, and then each K-mer is replaced with its corresponding SHAP value.

As a result, the contribution of each position in a sequence is represented as an array of SHAP

values. What is more, to study the relationship between contribution and nucleotide

conservation in a position, the information content of each position is calculated. The

information content is a measurement of the average information available in a position,

representing how conserved a position is if applied to analyzed nucleotides [56]. This

measurement has been widely used in genetics, and one well-known application is to serve as

the height of characters in sequence logos [57]. The information content is calculated using

previously aligned 16S sequences during the implementation of phylogeny-based algorithms.

The calculation is as follows:

$$H_i = -\sum f_{char,i} \times \log_2(f_{char,i}), char \in [A, T, C, G, -, N]$$

$$R'_i = \log_2(6) - H_i - \left(\frac{1}{\ln 2} \times \frac{s-1}{2n}\right)$$

$$R_i = R'_i \times \sum f_{nt,i}, nt \in [A, T, C, G]$$

where $H_i$ is the uncertainty of position $i$, f is the frequency of a character, $-$ represents gaps

generated in multiple sequence alignment, $N$ = ambiguous nucleotides, $R_i{}'$ is information

content of all characters in position $i$, $s$ is the number of characters (which is 6 in this

calculation), $n$ is the number of sequences in alignment (which is 2758), $R_i$ is the information

content of the four nucleotides, and $nt$ represents nucleotides. $R_i$ is used to represent the degree

of conservation of the position $i$.

**3    RESULTS**

This study evaluates the performance of SEM in comparison with other algorithms for 16S

GCN correction. Figure 2 and Table 1 summarize the results of 5-fold cross-validation. The

results first show sub-taxa averaging based on RDP and Greengenes exhibit a mean RMSE of

1.18 and 2.52 copies/genome, respectively, with a standard deviation of RMSE being 0.0356,

and 0.0388. Due to the much higher mean RMSE of TA(Greengenes), the results are excluded

from Figure 2. RDP is found to be the more accurate database for this task which produces the

lowest error range. All phylogeny-based algorithms perform better than sub-taxa averaging (EP:

Mean = 0.845, SD = 0.0443; MPR: Mean = 0.787, SD = 0.0375; PIC: Mean = 0.789, SD =

0.0243; SA: Mean = 0.774, SD = 0.0329; WSCP: Mean = 0.775, SD = 0.0273). The error range

of all phylogeny-based algorithms is lower than those of taxonomy-based algorithms, with no

overlap. With low RMSE and small SD, WSCP turns out to be the optimal phylogeny-based

algorithm. SEM, the deep learning model, outperforms all other algorithms with the lowest

mean RMSE (0.685 copies/genome) with a standard deviation of 0.0379. Its error range on the

16S full-length is the lowest among all algorithms and does not overlap with the phylogeny-

based algorithms.

Next, Figure 2 and Table 1 also present the performance of the algorithms for the 16S

subregions. All algorithms produce an increased Mean RMSE on subregions compared with

the performance for 16S full-length. EP experiences the most significant increase, with the

mean RMSE rising to 0.9312 copies/genome on the V7-V9 region. Among phylogeny-based

algorithms, WSCP is the most stable one, with mean RMSE on subregions ranging from 0.7792

(V3-V4) to 0.8227 (V4) copies/genome. SEM also displays relatively consistent performance

on subregions, ranging from 0.731 (V1-V3) to 0.774 (V4) copies/genome. Notably, the error

range of SEM on subregions is lower than EP and MPR in all subregions, and partially lower

than SA, PIC, and WSCP, as demonstrated in Figure 2. These findings indicate SEM

completely outperforms EP and MPR and partially outperforms SA, PIC, and WSCP.

The first cycle of cross-validation results produced by SEM are presented in Figure 3. The

figure shows a strong linear relationship between the predicted values and the true values, and

the data point also have similar distribution patterns. However, it is worth noting that SEM

tends to underestimate the GCN when the true value is greater than 14. This issue will be

discussed in more detail in the **Discussion** section.

Due to its superior performance, a bioinformatics tool, ANNA16, is developed based on

SEM and compared with other available tools in the final test. Figure 4 and Table 2 demonstrate

the results of the final test. Because PICRRUSt2 has a much higher RMSE (larger than 3.4

copies/genome for all regions) as shown in Table 2, it is excluded from Figure 4 and the

following case study. ANNA16 achieves the lowest RMSE among the tools at full-length and

every subregion. It produces the smallest RMSE appears at the full-length, which is 0.683

copies/genome, and the highest RMSE at the V4 region, which is 0.780 copies/genome. In

contrast, the RMSE of CopyRighter ranges from 1.822 (V4-V5) to 2.181 (V7-V9)

copies/genome, rrnDB from 1.079 (V4-V5) to 1.207 (V4) copies/genome, PAPRICA from

0.773 (V3-V4) to 1.321 (V4-V5), and PICRUSt2 from 3.459 (V4-V5) to 4.731 (V6-V8).

ANNA16 outperformed all other tools, demonstrating superior performance at all subregions

and full-length.

Figure 5, Table S4, and Table S5 show uncorrected copy fraction, true cell fraction, and

cell fraction (microbial profiles) estimated by ANNA16, rrnDB (version 5.7), CopyRighter,

and PAPRICA. The difference in uncorrected copy fraction and true cell fraction demonstrates

that GCN correction is necessary for obtaining an accurate microbial profile. The Bray-Curtis

Dissimilarity analysis shows that the dissimilarity values of the four tools for the even

community are considerably higher than those for the staggered community. This coincides

with the compositional patterns, where the estimated staggered patterns by the four tools are

more similar to the patterns of true cell fractions. However, the cell fraction estimated by

ANNA16 has the smallest dissimilarity value for both communities. For the even community,

PAPRICA and CopyRighter exhibit very close dissimilarity values and are the second most

accurate tools. For the staggered community, PAPRICA is the second most accurate tool,

followed by rrnDB, but CopyRighter is the least accurate one. Overall, ANNA16 outperforms

the other tools in terms of similarity patterns with the true cell fraction.

To illustrate how ANNA16 makes its predictions, the shap module in Python is used to

calculate the SHAP value of each K-mer. Figure S1 displays the top 20 K-mers ranked by mean

absolute SHAP value, while Figure 6 shows the distribution of SHAP values across the

sequences. To determine the range of hypervariable regions, the sequence of conserved regions

of *E. coli* is first extracted according to region coordinates provided by Yarza et al. [25]. All

sampled sequences undergo BLASTN (version 2.11.0) against *E. coli* conserved sequences to

determine the range of conserved regions in each sequence. The range of hypervariable regions

is thus deduced from conserved regions. To reduce complexity, only 500 randomly chosen

sequences are labeled in Figure 6. The results indicate that ANNA16 does not simply extract

information from hypervariable regions; conserved regions also provide information. To

further illustrate the relationship between SHAP value and the information content (degree of

conservation), the mean absolute SHAP value on each position against the degree of

conservation of each position is plotted in Figure 7. Interestingly, the mean absolute SHAP

value reaches its peak when the degree of conservation is extremely low. This phenomenon

will be further discussed in the **Discussion** section.

**4   DISCUSSION**

This study presents a novel approach for predicting 16S GCN based on 16S sequence using

the Stacked Ensemble Model (SEM), a deep learning model. The method outperforms

taxonomy- and phylogeny-based algorithms in predicting GCN at both the 16S full-length and

subregions. ANNA16, a bioinformatic tool based on SEM, is subsequently developed and

compared to existing 16S GCN correction tools, rrnDB, CopyRighter, PAPRICA, and

PICRUSt2, through the final test and a case study. The SHAP method is used to explain how

ANNA16 achieves good performance in predicting GCN.

First and foremost, ANNA16 emerges as the most accurate and state-of-the-art GCN

correction tool for the 16S full-length and all subregions tested in this study. As demonstrated

in Figure 2, the algorithm used by ANNA16—Stacked Ensemble Model of MLP, SVM, and

Ridge (SEM)—outperforms all taxonomy- and phylogeny-based algorithms at 16S full-length,

exhibiting a consistently lower error range. As for subregions, SEM still maintains the lowest

error ranges despite some overlap with the counterparts of PIC, SA, WSCP. These results

underscore the superior accuracy of SEM in GCN correction compared to existing algorithms

across all regions tested, with 16S full-length being its main strength. In addition, as Figure 4

and Table 2 show, ANNA16 achieves the lowest RMSE among the tools at the full-length and

every subregion in the final test, indicating its superior ability to predict GCN in newly

discovered species. The case study results in Figure 5, Table S4, and Table S5 also support this

finding, showing that the true cell fraction of both communities more closely resembles those

presented by ANNA16, especially for the staggered community. Overall, the results confirm

that ANNA16 is currently the most accurate 16S GCN correction tool.

In addition to its superior performance, ANNA16 also offers an advantage in inference

speed without the need for pre-computation. Existing GCN correction tools can be classified

into two categories based on their inference strategies: pre-computation or real-time

phylogenetic placement. On the one hand, pre-computational tools (i.e., rrnDB & CopyRighter)

compute the GCN value for every taxon in the database beforehand, and the tools retrieve the

GCN values from the database when a query is given. On the other hand, real-time phylogenetic

placement tools (i.e., PAPRICA and PICRUSt2) place a query sequence into their built-in

phylogenetic trees to predict the GCN value at runtime. Compared with real-time phylogenetic

placement, pre-computation tools have short inference time, but are also bound to their

database, which can lead to errors if used with databases having differences in nomenclature.

For example, the SILVA database [58] merges *Allorhizobium*, *Neorhizobium*, *Pararhizobium*,

and *Rhizobium* as one genus, named *Allorhizobium-Neorhizobium-Pararhizobium-Rhizobium*,

but in RDP these are independent genera. ANNA16, however, is free from this limitation as it

predicts GCN values directly for each 16S sequence and allows users to assign taxonomy

separately, leading to faster prediction time and database-independence.

After demonstrating the supremacy of ANNA16, an interesting question arises: how does

the model understand the complex relationship between the 16S sequence and 16S GCN?

Traditionally, microbiologists have considered the nine hypervariable regions to be the most

informative for inferring the phylogeny of one species. One hypothesis, therefore, is that K-

mers from hypervariable regions would contribute more to prediction than those from

conserved regions. However, Figure 6 shows that the distribution of SHAP values does not

entirely align with the location of hypervariable regions. Though high SHAP values tend to

cluster in the V2, V3, V5, V6, V7, and V9 regions, conserved regions between V2-V3, V4-V5,

and V8-V9 also contribute considerably.

To further explore how ANNA16 perceives the relationship the 16S sequence and 16S

GCN, Figure 7 is created. Though a linear relationship is expected between information content

and mean absolute SHAP values at each position, the scatter plot actually shows an L-shaped

trend. High SHAP values aggregate at positions with extremely low information content, while

SHAP values are generally constant in other positions. This trend indicates extremely variable

positions or positions with insertion of extremely low frequency are most informative for

ANNA16, and ANNA16 can identify these positions and assign high weights to them. This

may help explain why ANNA16 or MLP has better performance than conventional algorithms.

Conventional algorithms typically weigh every position equally by converting the variance in

the sequence-to-sequence similarity, which can underrepresent informative positions. However,

by weighing K-mers unequally according to how much information they contain, ANNA16

could more effectively utilize the information contained in the 16S sequence. This finding

underscores the potential of deep learning in genetics. Not only can deep learning accurately

predict traits based on sequencing data, but by investigating the contribution of each feature,

scientists can also discover which genes or loci are most closely related to the trait.

Although ANNA16 has shown remarkable performance in 16S GCN prediction, several

aspects could still be improved. First, one limitation of ANNA16 is its tendency to

underestimate the GCN of species with high GCN. As shown in Figure 3, ANNA16's

predictions become increasingly underestimated when the true GCN is greater than or equal to

14. This limitation could be attributed to the imbalanced distribution of GCN in the dataset.

Figure S2 shows the distribution of GCN in the preprocessed dataset. Sequences with GCN $\geq$

12 account for only a small proportion of the whole dataset, and sequences with GCN > 15 are

extremely rare. One solution to this problem is to wait for more sequence data with high GCN

to be collected, as new sequencing techniques are rapidly generating more genomic data.

Alternatively, data imbalance methods, such as class re-balancing, information augmentation,

and module improvement [59] could be applied to ANNA16 to address the issue of

underestimation. Furthermore, due to the limited amount of 16S GCN data currently available,

transfer learning could be explored as a potential solution. Future studies could collect a large

amount of unlabeled 16S rRNA sequences and pre-train a model with an autoregression or

autoencoder task, similar to models like BERT [60] or GPT-2/3/4 [61], to further improve the

accuracy of 16S GCN prediction.

**5　CONCLUSIONS**

In conclusion, this study developed ANNA16 as a deep learning-based new bioinformatic

tool for predicting the gene copy number of 16S rRNA. Compared to existing taxonomy-based

and phylogeny-based algorithms, ANNA16 showed significantly lower error ranges at 16S

full-length and all 16S subregions in the cross-validation. Furthermore, in the final test and

case study, ANNA16 outperformed existing tools such as rrnDB, CopyRighter, PICRUSt2, and

PAPRICA. ANNA16's simple structure also offers several advantages, including faster

inference speed, independence of pre-computation, and less demand for computing resources.

The SHAP analysis implies ANNA16 could utilize the information contained in the 16S

sequence more effectively by weighing K-mers unequally according to how much information

they contain. Future studies may combine strategies such as pre-training the model on

unlabeled data and addressing data imbalance to further decrease the error of copy number

correction.

**LIST OF ABBREVIATIONS**

GCN: Gene Gopy Number

MLP: Multi-layer Perceptron

SEM: Stacked Ensemble Model

SHAP: Shapley Additive exPlanation

**DECLARATIONS**

***Ethics approval and consent to participate***

Not applicable.

***Consent for publication***

Not applicable.

***Availability of data and materials***

16S rRNA sequences and the GCN data analyzed during the current study are available in the

rrnDB repository, https://rrndb.umms.med.umich.edu/. The codes and model files of ANNA16

are available at https://github.com/Merlinaphist/ANNA16. ANNA16 is deployed on Google

Colaboratory,

https://colab.research.google.com/drive/1XwpTMCHSfTmzpHyKrmiD8aC8C_1nndUV#scro

llTo=M0jLLsHC9W4M.

***Competing interests***

This study receives funding from the Oracle Cloud Starter Award by the Oracle Corporation.

***Funding***

This work was supported by the Summer Research Scholars (SRS) program at Duke Kunshan

University (DKU), the startup funds of Y.L. and M.M. granted by DKU, and the Oracle Cloud

Starter Award by the Oracle Corporation.

***Authors' contributions***

J.M. conceived the study. J.M. and T.C. analyzed the data and implemented the models. Y.L.

and M.M. provided mentorship for the study. All authors contributed to the manuscript writing.

***Acknowledgments***

The authors would like to thank Dr. Jiang Long for his kind comments on algorithm design.

**REFERENCES**

1. Woese CR, Fox GE: **Phylogenetic structure of the prokaryotic domain: the primary**

**kingdoms**. *Proc Natl Acad Sci U S A* 1977, **74**(11):5088-5090.

2. STACKEBRANDT E, GOEBEL BM: **Taxonomic Note: A Place for DNA-DNA**

**Reassociation and 16S rRNA Sequence Analysis in the Present Species Definition**

**in Bacteriology**. *International Journal of Systematic and Evolutionary Microbiology*

1994, **44**(4):846-849.

3. Louca S, Doebeli M, Parfrey LW: **Correcting for 16S rRNA gene copy numbers in**

**microbiome surveys remains an unsolved problem**. *Microbiome* 2018, **6**(1):41.

4. Woo PC, Leung PK, Leung KW, Yuen KY: **Identification by 16S ribosomal RNA**

**gene sequencing of an Enterobacteriaceae species from a bone marrow transplant**

**recipient**. *Mol Pathol* 2000, **53**(4):211-215.

5. Angly FE, Dennis PG, Skarshewski A, Vanwonterghem I, Hugenholtz P, Tyson GW:

**CopyRighter: a rapid tool for improving the accuracy of microbial community**

**profiles through lineage-specific gene copy number correction**. *Microbiome* 2014,

**2**(1):11.

6. Stoddard SF, Smith BJ, Hein R, Roller BR, Schmidt TM: **rrnDB: improved tools for**

**interpreting rRNA gene abundance in bacteria and archaea and a new foundation**

**for future development**. *Nucleic Acids Res* 2015, **43**(Database issue):D593-598.

7.      Fogel GB, Collins CR, Li J, Brunk CF: **Mini-Review Article: Prokaryotic Genome**

**Size and SSU rDNA Copy Number: Estimation of Microbial Relative Abundance**

**from a Mixed Population**. *Microbial Ecology* 1999, **38**(2):93-113.

8.      Kembel SW, Wu M, Eisen JA, Green JL: **Incorporating 16S Gene Copy Number**

**Information Improves Estimates of Microbial Diversity and Abundance**. *PLOS*

*Computational Biology* 2012, **8**(10):e1002743.

9.      Jurtz VI, Johansen AR, Nielsen M, Almagro Armenteros JJ, Nielsen H, Sønderby CK,

Winther O, Sønderby SK: **An introduction to deep learning on biological sequence**

**data: examples and solutions**. *Bioinformatics* 2017, **33**(22):3685-3690.

10.    Park Y, Kellis M: **Deep learning for regulatory genomics**. *Nature Biotechnology* 2015,

**33**(8):825-826.

11.    Lancashire LJ, Lemetre C, Ball GR: **An introduction to artificial neural networks in**

**bioinformatics—application to complex microarray and mass spectrometry**

**datasets in cancer studies**. *Briefings in Bioinformatics* 2009, **10**(3):315-329.

12.    Schmidt B, Hildebrandt A: **Deep learning in next-generation sequencing**. *Drug*

*Discov Today* 2021, **26**(1):173-180.

13.    Stepniewska-Dziubinska MM, Zielenkiewicz P, Siedlecki P: **Development and**

**evaluation of a deep learning model for protein–ligand binding affinity prediction**.

*Bioinformatics* 2018, **34**(21):3666-3674.

14.    Fioravanti D, Giarratano Y, Maggio V, Agostinelli C, Chierici M, Jurman G, Furlanello

583           C: **Phylogenetic convolutional neural networks in metagenomics**. *BMC*

584           *Bioinformatics* 2018, **19**(2):49.

585    15.    Lo C, Marculescu R: **MetaNN: accurate classification of host phenotypes from**

586           **metagenomic data using neural networks**. *BMC Bioinformatics* 2019, **20**(12):314.

587    16.    Wang Y, Bhattacharya T, Jiang Y, Qin X, Wang Y, Liu Y, Saykin AJ, Chen L: **A novel**

588           **deep learning method for predictive modeling of microbiome data**. *Brief Bioinform*

589           2021, **22**(3).

590    17.    Zha Y, Chong H, Qiu H, Kang K, Dun Y, Chen Z, Cui X, Ning K: **Ontology-aware**

591           **deep learning enables ultrafast and interpretable source tracking among sub-**

592           **million microbial community samples from hundreds of niches**. *Genome Medicine*

593           2022, **14**(1):43.

594    18.    Arango-Argoty G, Garner E, Pruden A, Heath LS, Vikesland P, Zhang L: **DeepARG:**

595           **a deep learning approach for predicting antibiotic resistance genes from**

596           **metagenomic data**. *Microbiome* 2018, **6**(1):23.

597    19.    Ma Y, Guo Z, Xia B, Zhang Y, Liu X, Yu Y, Tang N, Tong X, Wang M, Ye X *et al*:

598           **Identification of antimicrobial peptides from the human gut microbiome using**

599           **deep learning**. *Nature Biotechnology* 2022, **40**(6):921-931.

600    20.    Chong H, Zha Y, Yu Q, Cheng M, Xiong G, Wang N, Huang X, Huang S, Sun C, Wu S

601           *et al*: **EXPERT: transfer learning-enabled context-aware microbial community**

602           **classification**. *Briefings in Bioinformatics* 2022:bbac396.

603    21.    Zhao Z, Woloszynek S, Agbavor F, Mell JC, Sokhansanj BA, Rosen GL: **Learning,**

604            **visualizing and exploring 16S rRNA structure using an attention-based deep**

605            **neural network**. In: *PLoS computational biology.* vol. 17; 2021: e1009345.

606    22.    Abellan-Schneyder I, Matchado MS, Reitmeier S, Sommer A, Sewald Z, Baumbach J,

607            List M, Neuhaus K: **Primer, Pipelines, Parameters: Issues in 16S rRNA Gene**

608            **Sequencing**. *mSphere* 2021, **6**(1).

609    23.    Woese CR, Kandler O, Wheelis ML: **Towards a natural system of organisms:**

610            **proposal for the domains Archaea, Bacteria, and Eucarya**. *Proc Natl Acad Sci U S*

611            *A* 1990, **87**(12):4576-4579.

612    24.    Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, Madden TL:

613            **BLAST+: architecture and applications**. *BMC Bioinformatics* 2009, **10**(1):421.

614    25.    Yarza P, Yilmaz P, Pruesse E, Glöckner FO, Ludwig W, Schleifer K-H, Whitman WB,

615            Euzéby J, Amann R, Rosselló-Móra R: **Uniting the classification of cultured and**

616            **uncultured bacteria and archaea using 16S rRNA gene sequences**. *Nature Reviews*

617            *Microbiology* 2014, **12**(9):635-645.

618    26.    Ebou A, Koua D, Zeze A: **HyperEx: A Tool to Extract Hypervariable Regions from**

619            **16S rRNA Sequencing Data**. *bioRxiv* 2021:2021.2009.2003.455391.

620    27.    Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJ, Holmes SP: **DADA2:**

621            **High-resolution sample inference from Illumina amplicon data**. *Nat Methods* 2016,

622            **13**(7):581-583.

28. Cole JR, Wang Q, Fish JA, Chai B, McGarrell DM, Sun Y, Brown CT, Porras-Alfaro

A, Kuske CR, Tiedje JM: **Ribosomal Database Project: data and tools for high**

**throughput rRNA analysis**. *Nucleic Acids Research* 2013, **42**(D1):D633-D642.

29. DeSantis TZ, Hugenholtz P, Larsen N, Rojas M, Brodie EL, Keller K, Huber T, Dalevi

D, Hu P, Andersen GL: **Greengenes, a chimera-checked 16S rRNA gene database**

**and workbench compatible with ARB**. *Appl Environ Microbiol* 2006, **72**(7):5069-

5072.

30. Felsenstein J: **Phylogenies and the Comparative Method**. *The American Naturalist*

1985, **125**(1):1-15.

31. Sankoff D: **Minimal Mutation Trees of Sequences**. *SIAM Journal on Applied*

*Mathematics* 1975, **28**(1):35-42.

32. Maddison WP: **Squared-Change Parsimony Reconstructions of Ancestral States**

**for Continuous-Valued Characters on a Phylogenetic Tree**. *Systematic Zoology*

1991, **40**(3):304-314.

33. Louca S, Doebeli M: **Efficient comparative phylogenetics on large trees**.

*Bioinformatics* 2017, **34**(6):1053-1055.

34. Katoh K, Misawa K, Kuma Ki, Miyata T: **MAFFT: a novel method for rapid multiple**

**sequence alignment based on fast Fourier transform**. *Nucleic Acids Research* 2002,

**30**(14):3059-3066.

35. Price MN, Dehal PS, Arkin AP: **FastTree 2 – Approximately Maximum-Likelihood**

**Trees for Large Alignments**. *PLOS ONE* 2010, **5**(3):e9490.

36.    Bowman JS, Ducklow HW: **Microbial Communities Can Be Described by**

**Metabolic Structure: A General Framework and Application to a Seasonally**

**Variable, Depth-Stratified Microbial Community from the Coastal West Antarctic**

**Peninsula**. *PLOS ONE* 2015, **10**(8):e0135868.

37.    Douglas GM, Maffei VJ, Zaneveld JR, Yurgel SN, Brown JR, Taylor CM, Huttenhower

C, Langille MGI: **PICRUSt2 for prediction of metagenome functions**. *Nature*

*Biotechnology* 2020, **38**(6):685-688.

38.    Barbera P, Kozlov AM, Czech L, Morel B, Darriba D, Flouri T, Stamatakis A: **EPA-ng:**

**Massively Parallel Evolutionary Placement of Genetic Sequences**. *Systematic*

*Biology* 2019, **68**(2):365-369.

39.    Buitinck L, Louppe G, Blondel M, Pedregosa F, Mueller A, Grisel O, Niculae V,

Prettenhofer P, Gramfort A, Grobler J *et al*: **API design for machine learning software:**

**experiences from the scikit-learn project**. *CoRR* 2013, **abs/1309.0238**.

40.    Lundberg SM, Lee S-I: **A Unified Approach to Interpreting Model Predictions**. In:

*Advances in Neural Information Processing Systems: 2017*: Edited by Guyon I,

Luxburg UV, Bengio S, Wallach H, Fergus R, Vishwanathan S, Garnett R. Curran

Associates, Inc. 2017.

41.    Wolpert DH: **Stacked generalization**. *Neural Networks* 1992, **5**(2):241-259.

42.    Breiman L: **Stacked regressions**. *Machine Learning* 1996, **24**(1):49-64.

43.    Cortes C, Vapnik V: **Support-vector networks**. *Machine Learning* 1995, **20**(3):273-

297.

44.    Ho TK: **Random Decision Forests**. In: *Proceedings of the Third International*

*Conference on Document Analysis and Recognition (Volume 1) - Volume 1: 1995*. M:

IEEE Computer Society 1995: 278-282.

45.    Cover TM, Hart PE: **Nearest neighbor pattern classification**. *IEEE Trans Inf Theory*

1967, **13**:21-27.

46.    Friedman JH: **Greedy function approximation: a gradient boosting machine**.

*Annals of statistics* 2001:1189-1232.

47.    Hoerl AE, Kennard RW: **Ridge Regression: Biased Estimation for Nonorthogonal**

**Problems**. *Technometrics* 1970, **12**(1):55-67.

48.    Tibshirani R: **Regression Shrinkage and Selection via the Lasso**. *Journal of the Royal*

*Statistical Society Series B (Methodological)* 1996, **58**(1):267-288.

49.    Lindauer M, Eggensperger K, Feurer M, Biedenkapp A, Deng D, Benjamins C,

Ruhkopf T, Sass R, Hutter F: **SMAC3: A Versatile Bayesian Optimization Package**

**for Hyperparameter Optimization**. In: *ArXiv: 210909831: 2021*.    2021.

50.    Loshchilov I, Hutter F: **SGDR: Stochastic Gradient Descent with Restarts**. *CoRR*

2016, **abs/1608.03983**.

51.    He K, Zhang X, Ren S, Sun J: **Deep Residual Learning for Image Recognition**. In:

*2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR): 27-30*

*June 2016 2016*. 770-778.

52.    Moriya S: **Simple mapping-based quantification of a mock microbial community**

**using total RNA-seq data**. *PLoS One* 2021, **16**(7):e0254556.

53.    Bray JR, Curtis JT: **An Ordination of the Upland Forest Communities of Southern**

**Wisconsin**. *Ecological Monographs* 1957, **27**(4):325-349.

54.    Shapley LS: **A Value for N-Person Games**. Santa Monica, CA: RAND Corporation;

1952.

55.    Štrumbelj E, Kononenko I: **Explaining prediction models and individual predictions**

**with feature contributions**. *Knowledge and Information Systems* 2014, **41**(3):647-665.

56.    Schneider TD, Stormo GD, Gold L, Ehrenfeucht A: **Information content of binding**

**sites on nucleotide sequences**. *J Mol Biol* 1986, **188**(3):415-431.

57.    Schneider TD, Stephens RM: **Sequence logos: a new way to display consensus**

**sequences**. *Nucleic Acids Res* 1990, **18**(20):6097-6100.

58.    Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glöckner FO:

**The SILVA ribosomal RNA gene database project: improved data processing and**

**web-based tools**. *Nucleic Acids Research* 2012, **41**(D1):D590-D596.

59.    Zhang Y, Kang B, Hooi B, Yan S, Feng J: **Deep Long-Tailed Learning: A Survey**.

*CoRR* 2021, **abs/2110.04596**.

60.    Devlin J, Chang M-W, Lee K, Toutanova K: **Bert: Pre-training of deep bidirectional**

**transformers for language understanding**. *arXiv preprint arXiv:1810 04805* 2018.

61.    Brown TB, Mann B, Ryder N, Subbiah M, Kaplan J, Dhariwal P, Neelakantan A, Shyam

P, Sastry G, Askell A *et al*: **Language Models are Few-Shot Learners**. *CoRR* 2020,

**abs/2005.14165**.

## TABLES

708 **Table 1.** Performance of all algorithms at 16S full-length and subregions (Mean RMSE ± SD).

| | Full Length | V1-V2 | V1-V3 | V3-V4 | V4 | V4-V5 | V6-V8 | V7-V9 |
|---|---|---|---|---|---|---|---|---|
| SEM | 0.685 ± 0.0379 | 0.751 ± 0.0285 | 0.727 ± 0.0301 | 0.730 ± 0.0450 | 0.774 ± 0.0453 | 0.746 ± 0.0364 | 0.733 ± 0.0368 | 0.737 ± 0.0423 |
| EP | 0.845 ± 0.0443 | 0.928 ± 0.0331 | 0.889 ± 0.0476 | 0.902 ± 0.0447 | 0.916 ± 0.0569 | 0.910 ± 0.0340 | 0.909 ± 0.0563 | 0.931 ± 0.0354 |
| MPR | 0.787 ± 0.0375 | 0.867 ± 0.0370 | 0.836 ± 0.0305 | 0.858 ± 0.0477 | 0.879 ± 0.0475 | 0.858 ± 0.0413 | 0.852 ± 0.0400 | 0.846 ± 0.0370 |
| PIC | 0.789 ± 0.0243 | 0.810 ± 0.0281 | 0.805 ± 0.0307 | 0.789 ± 0.0503 | 0.824 ± 0.0377 | 0.785 ± 0.0277 | 0.781 ± 0.0404 | 0.802 ± 0.0393 |
| SA | 0.774 ± 0.0329 | 0.829 ± 0.0321 | 0.805 ± 0.0430 | 0.811 ± 0.0379 | 0.822 ± 0.0388 | 0.810 ± 0.0283 | 0.807 ± 0.0391 | 0.830 ± 0.0334 |
| WSCP | 0.775 ± 0.0273 | 0.793 ± 0.0242 | 0.782 ± 0.0330 | 0.779 ± 0.0483 | 0.823 ± 0.0405 | 0.785 ± 0.0354 | 0.779 ± 0.0377 | 0.790 ± 0.0375 |
| TA(RDP) | 1.18 ± 0.0356 | 1.58 ± 0.0538 | 1.41 ± 0.0517 | 1.47 ± 0.0370 | 1.93 ± 0.0954 | 1.48 ± 0.0622 | 1.44 ± 0.0329 | 1.73 ± 0.129 |
| TA(Greengenes) | 2.52 ± 0.0388 | 2.08 ± 0.122 | 2.63 ± 0.147 | 1.85 ± 0.0939 | 2.12 ± 0.0590 | 2.00 ± 0.0961 | 2.19 ± 0.232 | 2.54 ± 0.434 |

709 EP: empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent contrast; SA: Subtree Averaging; WSCP:

710 weighted-squared-change parsimony; TA(RDP): sub-taxa averaging based on RDP database; TA(Greengenes): sub-taxa averaging based on

711 Greengenes database; SEM: Stacked Ensemble Model.

715 **Table 2.** Performance of 16S GCN Correction Tools in the Final Test (RMSE)

| | Full Length | V1-V2 | V1-V3 | V3-V4 | V4 | V4-V5 | V6-V8 | V7-V9 |
|---|---|---|---|---|---|---|---|---|
| CopyRighter | 1.994 | 1.934 | 1.989 | 1.825 | 1.848 | 1.822 | 1.952 | 2.181 |
| rrnDB5.7 | 1.083 | 1.094 | 1.082 | 1.101 | 1.207 | 1.079 | 1.109 | 1.110 |
| ANNA16 | 0.683 | 0.711 | 0.710 | 0.716 | 0.780 | 0.715 | 0.720 | 0.713 |
| PICRUSt2 | 4.198 | 4.353 | 4.175 | 4.393 | 3.807 | 3.459 | 4.731 | 4.677 |
| PAPRICA | 0.817 | 0.857 | 1.319 | 0.773 | 0.896 | 1.321 | 0.987 | 0.778 |

717    **FIGURES**

a) Illustration of K-merization

b) Framework of Developing ANNA16

c) Architecture of the Stacked Ensemble Learner          d) Architecture of the MLP model

719    **Figure 1.** Illustration of the Framework and Architecture of the Deep Learning Models. a) K-

720    mer strategy (K = 6). b) Framework of Designing ANNA16. c) Architecture of the Stacked

721    Ensemble Model. d) Architecture of the MLP model inside the Stacked Ensemble Model.

**Figure 2.** Performance of all algorithms or models at 16S full-length and subregions. EP:

empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent

contrast; SA: Subtree Averaging; WSCP: weighted-squared-change parsimony; TA(RDP): sub-

taxa averaging based on RDP database; SEM: stacked ensemble model.

**Figure 3.** Prediction by SEM on 16S full length and subregions in the first cycle of 5-fold cross-validation. The red line is a diagonal line illustrating to which extent the predicted values are derived from the true values. The density plot filled in violet shows the distribution of the true values, and the green density plot shows the distribution of the predicted values.

**Figure 4.** Comparison of performance on the test dataset among CopyRighter, rrnDB, ANNA16, and PAPRICA.

**Figure 5.** Uncorrected copy fraction, true cell fraction, and cell fraction (microbial profiles)

745 estimated by ANNA16, rrnDB (version 5.7), CopyRighter, and PAPRICA. The right panel

746 shows the value of Bray-Curtis Dissimilarity of each estimated profile to the true cell fraction.

747 Uncorrected: Uncorrected copy fraction; True: True cell fraction; ANNA16: Cell fraction

748 estimated by ANNA16; rrnDB5.7: Cell fraction estimated by rrnDB (version 5.7); CopyRighter:

749 Cell fraction estimated by CopyRighter; PAPRICA: Cell fraction estimated by PAPRICA.

**Figure 6.** Distribution of SHAP values at 16S full-length sequences. To make the figure

interpretable, only the value of the top 100 K-mers ranked by mean absolute SHAP value is

shown. Hypervariable regionsare labeled as grey shadows. V-region labels on the x-axis show

the general position of *E. coli* V-regions according to coordinates from Yarza et al. [25].

**Figure 7.** Relationship of mean absolute SHAP values and the information content (unit: bits)

on each position of aligned 16S full-length sequence.