A Novel Method for Predicting 16S rRNA Gene Copy Number

Jiazheng Miao[1], Tianlai Chen[1], Mustafa Misir[1, *], and Yajuan Lin[1, *]

[1]*Department of Applied and Natural Science, Duke Kunshan University, Suzhou, China*

Correspondence*:

Mustafa Misir

Division of Natural and Applied Sciences, Duke Kunshan University, Duke Avenue No: 8,

Suzhou, 215316, China

mustafa.misir@dukekunshan.edu.cn

Yajuan Lin

Division of Natural and Applied Sciences, Duke Kunshan University, Duke Avenue No: 8,

Suzhou, 215316, China

linyajuan@gmail.com

ABSTRACT

Culture-independent 16S rRNA gene metabarcoding is a commonly used method in

microbiome profiling. However, this approach can only reflect the proportion of sequencing

reads, rather than the actual cell fraction. To achieve more quantitative cell fraction estimates,

we need to resolve the 16S gene copy numbers (GCN) for different community members.

Currently, there are several bioinformatic tools available to estimate 16S GCN, either based on

taxonomy assignment or phylogeny. Here we develop a novel algorithm, Stacked Ensemble

Model (SEM), that estimates 16S GCN directly from the 16S rRNA gene sequence strings,

without resolving taxonomy or phylogeny. For accessibility, we developed a public, end-to-

end, web-based tool based on the SEM model, named ANNA16. Based on 27,579 16S rRNA

gene sequence data (rrnDB database), we show that ANNA16 outperforms the most commonly

used 16S GCN prediction algorithms. The prediction error range in the 5-fold cross validation

of SEM is completely lower than all other algorithms for the 16S full-length sequence and

partially lower at 16S subregions. The final test and a mock community test indicate ANNA16

is more accurate than all currently available tools (i.e., rrnDB, CopyRighter, PICRUSt2, &

PAPRICA). SHAP value analysis indicates ANNA16 mainly learns information from

extremely variable nucleic positions, rather than merely the hypervariable regions. Compared

to the traditional GCN prediction tools, ANNA16 has a simple structure, faster inference speed

without precomputing, and higher accuracy. If more 16S GCN data is available, future studies

could improve the larger prediction error for high GCN taxa caused by data imbalance.

1   INTRODUCTION

16S rRNA is the small subunit ribosomal RNA molecule of prokaryotic ribosomes. Since

ribosome is a self-replicating system, 16S rRNA is readily isolated and its sequence changes

slowly with time [1]. This characteristic allows 16S rRNA to be highly conserved within

species [2] and the variance increases as inter-species relatedness decreases [1]. Therefore, 16S

rRNA is used to identify prokaryotes, or detect relatedness among distant species, through

matching next-generation sequencing (NGS) data to reference databases [3] such as RDP and

SILVA. The relatedness may be represented as genetic distance among 16S rRNAs like mean

nucleotide substitutions per site [3]. This technique, named 16S rRNA metabarcoding, has been

established as the gold standard to infer organismal phylogeny and microbial ecology for over

20 years [4].

One critical limitation of 16S rRNA metabarcoding is that NGS determines the proportion

of 16S rRNA read counts, instead of cell counts. Because it is typical for prokaryotes to have

more than one copy of the 16S rRNA gene, the proportion of 16S rRNA read counts (also called

relative abundance) could not exactly reflect the taxonomic composition of a microbial

community [5]. To represent the profile of a microbial community, the proportion of 16S rRNA

read counts needs to be weighted by an inverse of 16S rRNA gene copy number (GCN). This

step yields a corrected microbial composition as the community profile, which represents the

proportion of cell counts of each lineage in the community [5]. To calculate 16S GCN,

scientists rely on experimental methods such as whole genome sequencing [6] or competitive

PCR [7]. Nevertheless, experimental methods are usually costly or culture-dependent, and so

far, only a limited number of species have GCN data. This situation catalyzes the development

of bioinformatics tools that predict the GCN of unmeasured species from measured species.

Luckily, 16S GCN is correlated with relatedness across species [5, 8], which means 16S GCN

variation is relatively low within species but increases as relatedness decreases. This trait

allows 16S GCN to be estimated from phylogeny or taxonomy [8]. In general, all current tools

rely on this kind of method [3, 5, 6]. Specifically, one correction tool could construct one

taxonomy or phylogenetic tree of the 16S sequence and estimate the GCN of the unmeasured

species from its close measured relatives. For instance, rrnDB [6] is one well-established tool

that corrects 16S GCN based on taxonomy. Its algorithm calculates the mean 16S GCN of a

taxon from the means of its sub-taxa.

Deep learning as a popular machine learning strategy comes with its potential of learning

complex patterns from biological sequencing data [9, 10]. This aspect can be beneficial as a

novel approach for predicting 16S GCN. Deep learning is essentially an Artificial Neural

Network (ANN). The concept of ANN is inspired by the way a human brain learns and

processes information through synaptic interactions between neurons [11]. An ANN is a

computational model that is constituted by multiple interconnected processing elements—

artificial neurons [11]. Neurons are utilized in groups as the layers of a network. Each artificial

neuron receives and processes input with a non-linear function, known as the activation

function [12]. Collectively, one ANN model learns to solve a specific task through capturing

non-linear trends and relationships from the presented data. Beyond these capabilities, ANN is

even competent to disclose relationships or mechanisms that are still unknown to scientists

[13]. Deep learning gets its name by having more than one (hidden) layer connecting the input

and output units. Having deeper networks refer to representing complex input-output

relationships while accommodating a large amount of data. In that sense, high-dimensional

biological data is a popular target for deep learning.

Recently, a broad spectrum of deep learning approaches has been applied to microbiology

research. Various deep learning architectures like Convolutional Neural Network (CNN), and

Recurrent Neural Network (RNN), have been used for metagenomic-based taxonomy

classification [14], host phenotype prediction [15], disease prediction [16], and microbial

community predication [17]. Some other works focus on data mining for antibiotic resistance

genes [18], antimicrobial peptides [19], microbial source [20], and raw sequencing data [21].

All these applications show the great potential of deep Learning for microbial studies. With

these present successes, it should be possible to estimate GCN directly from the 16S sequence

through an ANN, without the construction of taxonomy or phylogeny. To the best of our

knowledge, there is not any deep learning-based method utilized for the 16S rRNA-based copy

number estimation.

This study first trains SEM, the developed deep learning model, on the 16S full-length

sequence and compares the performance to the taxonomy-based and phylogeny-based

algorithms. However, due to drawbacks such as the relatively high error rate or higher costs, at

present, it is less common for microbiologists to sequence the full length of 16S rRNA [22].

Full-length 16S could be more commonly used only if new long sequencing methods are

invented. Alternatively, microbial studies tend to target the hypervariable regions in 16S rRNA.

16S rRNA contains nine hypervariable regions, interspersed among conserved regions (V1-V9)

[23]. Mostly, microbiologist sequence only one to three adjacent hypervariable regions by NGS

to study the microbial ecology [22]. Therefore, this study also trains deep learning models on

different combinations of the adjacent hypervariable regions in 16S rRNA and compare the

performance with conventional algorithms. Finally, a deep learning-based bioinformatic tool

for 16S GCN correction is developed. The tool is compared with existing correction tools to

assess the performance. One state-of-the-art method of model explanation is also adopted to

uncover how the deep learning model understands a 16S sequence.

Based on the Stacked Ensemble Model, the most accurate method, this study presents

ANNA16 (Artificial Neural Network Approximator for 16S rRNA Gene Copy Number), an

end-to-end, web-based tool that predicts copy numbers from 16S rRNA sequences.

2   MATERIALS AND METHODS

2.1.   Data Source and Preprocessing

16S rRNA sequences and the GCN data used to train deep learning models in this study

are retrieved from rrnDB, version 5.8 [6]. In total, 29,267 16S genes with unique accession

numbers are included in the dataset. Because raw 16S sequence data contains both (+) strands

and (-) strands, bias may be caused if the data is directly used for taxonomy-based and

phylogeny-based algorithms. Therefore, this study uses the BLASTN algorithm in the

BLAST+ application, version 2.11.0 [24], with the first 50 nucleotides of *E. coli* 16S sequence

(+) strand (accession number: GCF_002953035.1) being the subject, to determine the

orientation of each 16S sequence. The first 50 nucleotides of E. coli belong to the conserved

region on 16S rRNA [25], so it qualifies as a template. Returned HSPs with sstart > send and

evalue < 0.01 are considered (+) strands, and HSPs with sstart < send and evalue < 0.01 are

considered (-) strands. The remaining sequences are labeled as unrecognizable and dropped

from the dataset. The reverse complement of (-) strand sequences is generated and added to the

(+) strands.

In addition, because 16S sequences in the dataset have varied starting positions, this study

employs HyperEx [26] to extract full-length sequences between primer 27F and primer 1492R

(as listed in Table S1) to simulate NGS results of PCR amplicons. This ensures all 16S

sequences have uniform starting and ending positions. After this step, the preprocessed dataset

contains 27,579 sequences, involving 1,550 genera. The average sequence length is 1,499.03

nucleotides, with a standard deviation of 21.49 nucleotides. Gene copy number ranges from 1

copy per genome to 21 copies per genome, with a mean value of 5.39 and a standard deviation

of 2.78. This dataset is referred to as the preprocessed dataset in the following content.

Moreover, according to Abellan-Schneyder et al. (2021) [22], V1-V2, V1-V3, V3-V4, V4, V4-

V5, V6-V8, and V7-V9 are frequently targeted subregions. Thus, this study also uses primers

listed in Table S1 and HyperEx to extract these subregions from the preprocessed dataset.

Because a previous study points out that the performance of all the existing GCN

correction tools is unsatisfactory on clades that are distant from training data [3], this study

would like to test if deep learning could perform better on these distant clades. Therefore, this

study splits the preprocessed dataset into train and test datasets according to when the

sequences are published. Specifically, sequences that already exist in the previous rrnDB

release (version 5.7) are selected as the train dataset for cross-validation. Sequences that are

newly added in version 5.8 are selected as the test dataset. This splitting method produces a

near-random test dataset containing newly published sequences. The train dataset contains

19,520 sequences, involving 1,331 genera. The average sequence length is 1,498.72

nucleotides, with a standard deviation of 21.41 nucleotides. Gene copy number ranges from 1

copy per genome to 21 copies per genome, with a mean value of 5.26 and a standard deviation

of 2.74. The test dataset contains 8,059 sequences, involving 676 genera. The average sequence

length is 1,499.79 nucleotides, with a standard deviation of 21.67 nucleotides. Gene copy

number ranges from 1 copy per genome to 20 copies per genome, with a mean value of 5.72

and a standard deviation of 2.85. The test dataset contains 219 genera that are not present in

the train dataset.

2.2.   Conventional Algorithms and Existing Tools

Sub-taxa averaging (TA) is one taxonomy-based algorithm. The algorithm calculates the

mean 16S GCN of a taxon from the means of its sub-taxa. To implement this algorithm, 16S

sequences are first input to *assignTaxonomy* function in the DADA2 package in R (version

1.21.0) [27] and yield two taxonomies, based on RDP (version 18, formatted by DADA2) [28],

and Greengenes (version 13.8) [29] database respectively. The algorithm first receives

taxonomy and GCN from the database and converts the data structure of the taxonomy to an

inheritance tree. In the tree, every taxon is viewed as a node on the tree, and it computes the

copy number of every node by taking the mean of its sub-nodes. If an unknown query is given,

it assigns the value of the query's parent node to the query node as an estimation.

This study also employs six phylogeny-based algorithms to compare with deep learning

methods: empirical probabilities (EP), subtree averaging (SA), phylogenetic independent

contrasts (PIC) [30], Sankoff's maximum-parsimony (MPR) [31], and weighted-squared-

change parsimony (WSCP) [32]. These algorithms first receive a pre-constructed tree of 16S

sequences and estimates the GCN of each ancestral node from its daughter species through

weighing each labeled daughter node with its phylogenetic distance to the parental node [33].

To implement the algorithms, 16S sequences in the dataset first undergo multiple sequence

alignment by MAFFT v7.490 [34], and are converted to a phylogenetic tree by FastTree 2.1.10

[35]. The algorithms are performed by castor package in R [33], adjusted from the R script in

Louca, Doebeli, and Parfrey (2018) [3] (MPR is implemented by function *hsp_max_parsimony*,

WSCP by function *hsp_squared_change_parsimony*, SA by function *hsp_subtree_averaging*,

EP by function *hsp_empirical_probabilities*, and PIC by *hsp_independent_contrasts*). All

functions are set on default parameters.

What is more, after the deep learning-based tool is developed, this study compares it with

all the existing tools on the test dataset that can be used for 16S GCN correction, which are

rrnDB [6], CopyRighter [5], PAPRICA [36], PICRUSt2 [37]. rrnDB is a taxonomy-based tool

using sub-taxa averaging, while the latter three tools are phylogeny-based. CopyRighter uses

PIC algorithm to pre-compute the copy number of all taxa in the Greengenes database [29] and

makes predictions by searching the lineages of the queries in its pre-computed GCN table [5].

The original function of PAPRICA and PICRUSt2 is to predict the metabolic profile of a

microbial community based on the 16S data, but they possess the function of predicting the

copy number of any given gene according to the phylogeny [36, 37]. These two tools first

utilize EPA-ng [38] to place the queries on their built-in phylogenetic tree, and use subtree-

averaging (PAPRICA) or maximum parsimony (PICRUSt2) algorithms to predict the copy

number of the queries [36, 37].

Because rrnDB and CopyRighter application will directly output microbial community

abundance instead of 16S GCN values, this study retrieves their precomputed tables (rrnDB

version 5.7) and predict GCN values by searching the precomputed tables for assigned lineages.

Taxonomy of full-length sequences and all subregion sequences are generated by the

assignTaxonomy function in the DADA2 package through RDP (version 18) and Greengenes

(version 13.8, formatted by DADA2) [29] database. The assigned RDP lineages are searched

in the rrnDB precomputed table, and Greengenes lineages are searched in CopyRighter

precomputed table. As for PAPRICA and PICRUSt2, the DNA sequences in the test dataset are

direct input to the tools. For PAPRICA, *paprica-run.sh* is called without additional parameters.

For PTCRUSt2, *place_seqs.py* and *hsp.py* is called without additional parameters.

2.3.   Development of ANNA16

2.3.1.   Framework

To build our deep predictive models, this study first implements a three-layer MLP

prototype model. The sequences in the train dataset are split for training and testing by 3:1. The

DNA sequences are preprocessed with K-merization. The K-mers are converted into the

number of counts in the set via *CountVectorizer* function in the the scikit-learn module (version

0.23.2) [39]. Deep learning models will intake the vector of occurrence counts and predicts the

gene copy number.

After testing K from 3 to 7 on the prototype model, the model performance is found to

improve as K increased, but the requirement for memory size also expands sharply. Therefore,

the value 6 appears to be the optimal length which results in a good performance and does not

require an extremely large memory size. 6-merization is to decompose the DNA sequence into

a set of sub-sequences of length 6. An example of a set with three 6-mers is displayed in Figure

1 a). After determining the length of K-mers, a Stacked Ensemble Model (SEM) is

implemented for 16S GCN prediction. The framework is demonstrated in Figure 1 b). After

model construction, the performance of the SEM is compared with conventional algorithms

through a 5-fold cross-validation at full-length and subregional DNA sequence. Shapley

Additive exPlanations (SHAP) [40] is introduced here for post-hoc interpretability. The whole

study was conducted with Python 3.8 and Tensorflow 2.8.0 on Nividia RTX 3090.

2.3.2. Model Construction

The deep learning model employs one strategy of ensemble learning: model stacking,

which first trains multiple base-models on the available data, and then uses a meta-model to

accept the output of all base-models and make the final prediction. The stacked model would

typically perform better than any single base-model [41, 42]. In this study, the Stacked

Ensemble Model is a combination of one MLP model with other classic machine learning

models. MLP is the most common form of ANN, in which artificial neurons are organized into

layers and the input is processed layer by layer [11]. The calculation of the output for each

neuron is as follows [11]:

236
$$v_k = \sum_{i=0}^{n} \omega_{k,i} x_i$$

237
$$\gamma_k = \varphi(v_k + v_{k_0})$$

238 where v_k is the net output of neuron k, with $x_1, x_2, \ldots, x_n$ being the input from the last

239 layer, and $\omega_{k,1}, \omega_{k,2}, \ldots, \omega_{k,n}$ being the weights on the input. γ_k is the output of the neuron,

240 where v_{k_0} represents the bias, and $\varphi(.)$ refers to the activation function. And the MLP part

241 is trained with Rooted Mean Squared Error (RMSE) loss:

242
$$\text{RMSE} = \sqrt{\frac{\sum_{i=0}^{n}(Y_{true} - Y_{pred})^2}{n}}$$

where n is the size of the input dataset, Y_{true} is the true value of copy number, Y_{pred} is the

value of the predicted copy number.

In addition to MLP, classic machine learning algorithms including Support Vector Machine

(SVM) [43], Random Forest [44], K-nearest Neighbors [45], and Gradient Boosting [46] are

tested as base-models. Linear Regression, Ridge Regression [47], and Lasso Regression [48]

are tested as meta-models. All machine learning algorithms are implemented by the scikit-learn

module (version 0.23.2). After testing, the SEM uses one MLP and one SVM as the base-

models and Ridge Regression as the meta-model, as shown in Figure 2 c). Principle Component

Analysis (PCA) is implemented by *PCA* function in scikit-learn with the value of

n_components set to 100, SVM is implemented by *SVR* function in scikit-learn, and Ridge

Regression is implemented by *Ridge* function in scikit-learn.

The parameter of SEM is tuned through the *SMAC4BB* function in the SMAC3 package

(version 1.4.0) [49] for 500 iterations. For the MLP part, the number of dense layers, hidden

layer size, activation functions, and learning rate. Layers of the model are tested in the range

of [1, 7], hidden layer size from the range of [1, 1024], activation functions are selected among

ReLU, Exponential Linear Unit (ELU), Gaussian Error Linear Unit (GELU), Scaled

Exponential Linear Unit (SELU), and Linear, and the learning rate is tested in the range of

[0.00005, 0.1]. The final architecture of MLP is shown in Figure 2 d), which contains a dense

block of 6 hidden layers. The number of neurons is 489, 926, 645, 929, 582, and 82 respectively.

The activation functions are GELU, ReLU, ReLU, ELU, GELU, and Linear respectively. For

SVM, the *kernel* value is tested among "rbf", "sigmoid", and "linear", *gamma* tested between

"scale" and "auto", and *C* tested as a float in the range of [0.3, 0.9] or as an integer in the range

of [1, 100]. For Ridge, the value of *alpha* tested as a float in the range of [0.3, 0.9] or as an

integer in the range of [1, 100]. After tuning, the parameters are *kernel = 'rbf'*, *gamma = 'auto'*,

C = 11, and *alpha = 49*. A complete list of parameters is shown in Table S2.

2.3.3. Dismissed Machine Learning Algorithms

This study also used tested one Transformer model and one Residual Multi-layer

Perceptron for 16S GCN prediction. The Transformer model leveraged the original transformer

encoder architecture with cosine learning rate decay [50], followed by global average pooling,

and two dense layers. Embedding and position encoding are used as input for the Transformer

model. Residual Multi-layer Perceptron are MLP models utilizing Residual Connection

architectures. In this architecture, skip connections are built to jump over two to three layers.

Such design may help avoid the problem of vanishing gradients or degradation [51]. However,

because these models do not exhibit a good performance, they are dismissed from the study.

2.4. Case Study

Based on the SEM method, this study presents ANNA16 (Artificial Neural Network

Approximator for 16S rRNA Gene Copy Number), an end-to-end tool that predicts copy

numbers from 16S rRNA sequences. In addition to the final test, this study designs a case study

that simulates two mock communities *in silico* to demonstrate ANNA16's performance. rrnDB,

CopyRighter, PAPRICA, and PTCRUSt2 are also applied to estimate the mock communities'

microbial profile as a positive control. The simulated communities are two commercially

available mock communities, one even community (ATCC MSA-2003) and one staggered

community (ATCC MSA-1001). The information of the mock communities is shown in Table

S3. Such mock communities have been used by Moriya (2021) to study methods of quantifying

a microbial community [52]. Both mock communities consist of similar 10 bacterial strains,

but with different ratios. This study retrieves genome sequences of the 10 strains from NCBI,

copy number data from rrnDB (version 5.7), and assigns a cell counts value to each strain by

assuming each community has 1,000,000 cells. Table S3 shows the basic information about the

mock communities. After genome sequences of the ten strains are retrieved from NCBI,

HyperEx is used to extract 16S full-length sequences from the genomes. The method is the

same as described in the Data Source and Preprocessing.

After estimating the profile of the mock communities, Bray-Curtis Dissimilarity [53] is

calculated between estimated cell fraction and true cell fraction to represent the accuracy of

community profile prediction. Bray-Curtis Dissimilarity is a method widely used in ecology

and biology for quantifying the compositional dissimilarity between two different communities

[53]. The larger the Bray-Curtis Dissimilarity value is, the more distinct two communities will

be. Its calculation is as follows:

302
$$BC = 1 - \frac{2C_{AB}}{S_A + S_B}$$

where *BC* is the Bray-Curtis Dissimilarity value, *A* and *B* are two communities, C_{AB} is the sum

of the lesser values for species present in both communities, S_A and S_B are the total number of

species counted at both communities. The Bray-Curtis Dissimilarity values are calculated by

the *vegdist* function in the vegan (version 2.5-7) package of R, with *method* parameter set to

"bray".

2.5.   Deep Learning Model Explanation

SHAP [40] is used to further explain our model prediction. SHAP is based on both

collational game theory [54] and the classical Shapley method [55]. It is a unified measure of

feature importance that determines the individual contribution of each feature to a model

prediction by viewing each feature as a player in Shapley. The marginal contribution can be

estimated under multiple feature subsets, and the final contribution is the sum of all marginal

contributions. A positive SHAP value denotes that the feature contributes positively to the

model's prediction over the model expectation, whereas the negative value denotes that the

feature contributes negatively. In this study, each individual K-mer is considered a feature. To

calculate the SHAP value for each K-mer, the preprocessed dataset and ANNA16's pre-trained

neural network are input to shap.KernelExplainer function in shap module (Version 0.41.0) in

Python. The function views each prediction of every single sequence in the dataset as an

independent game and calculates SHAP values in each game.

This study randomly samples 10% of the whole dataset for SHAP value analysis (N =

2758). As a result, a list of 2,758 SHAP values will be assigned to every K-mer to represent

the K-mer's overall contribution. After the SHAP values of K-mers are calculated, the SHAP

values are mapped back to the 16S sequence to see if there is any positional pattern in

contribution. Each sequence is first transformed into an array of K-mers, and next each K-mer

is replaced by its corresponding SHAP value. As a result, the contribution of each position in

a sequence is represented as an array of SHAP values. What is more, to study the relationship

between contribution and nucleotide conservation in a position, the information content of each

position is calculated. The information content is a measurement of the average information

available in a position, and it represents how conserved a position is if applied to analyzed

nucleotides [56]. This measurement has been widely used in genetics, and one well-known

application is to serve as the height of characters in sequence logos [57]. Previously aligned

16S sequences during the implementation of phylogeny-based algorithms are used to calculate

the information content. The calculation is as follows:

$$H_i = -\sum f_{char,i} \times \log_2(f_{char,i}), char \in [A, T, C, G, -, N]$$

$$R'_i = \log_2(6) - H_i - \left(\frac{1}{\ln 2} \times \frac{s-1}{2n}\right)$$

$$R_i = R'_i \times \sum f_{nt,i}, nt \in [A, T, C, G]$$

where H_i is the uncertainty of position i, f is the frequency of a character, $-$ represents gaps

generated in multiple sequence alignment, N = ambiguous nucleotides, $R_i{'}$ is information

content of all characters in position i, s is the number of characters (which is 6 in this

calculation), n is the number of sequences in alignment (which is 2758), R_i is the information

content of the four nucleotides, and nt represents nucleotides. R_i is used to represent the degree

of conservation of the position i.

3 RESULTS

This study first compares the performance of SEM with all other potential algorithms for

the task of 16S GCN correction. Figure 2 and Table 1 summarize the results of 5-fold cross-

validation. First, looking at the performance of these algorithms for the 16S full-length, sub-

taxa averaging based on RDP and Greengenes exhibit a mean RMSE of 1.18 and 2.52

copies/genome respectively, with a standard deviation of RMSE being 0.0356, and 0.0388.

Because TA(Greengenes) has much higher Mean RMSE at all regions, the results are not shown

in Figure 2. RDP proves to be the more accurate database for this task which produces the

lowest error range. All phylogeny-based algorithms perform better than sub-taxa averaging (EP:

Mean = 0.845, SD = 0.0443; MPR: Mean = 0.787, SD = 0.0375; PIC: Mean = 0.789, SD =

0.0243; SA: Mean = 0.774, SD = 0.0329; WSCP: Mean = 0.775, SD = 0.0273). The error range

of all phylogeny-based algorithms is lower than those of taxonomy-based algorithms with no

overlap. With low RMSE and small SD, WSCP turns out to be the optimal phylogeny-based

algorithm. As for deep learning models, SEM outperforms all other algorithms with the lowest

Mean RMSE (0.685 copies/genome) with a standard deviation of 0.0379. Its error range on the

16S full-length is the lowest among all algorithms and has no overlap with the phylogeny-

based algorithms.

Next, Figure 2 and Table 1 also show the performance of the algorithms for the 16S

subregions. Compared with the performance for 16 full-length, all algorithms produce an

increased Mean RMSE on subregions. EP experiences the most significant increase, with the

Mean RMSE rising to 0.9312 copies/genome on the V7-V9 region. WSCP is the most stable

phylogeny-based algorithm, with Mean RMSE on subregions ranging from 0.7792 (V3-V4) to

0.8227 (V4) copies/genome. The mean RMSE of SEM on subregions is relatively consistent,

ranging from 0.731 (V1-V3) to 0.783 (V4) copies/genome. Notably, as shown in Figure 2, the

error range of SEM on subregions is lower than EP and MPR in all subregions, and partially

lower than SA, PIC and WSCP. This indicates the performance of SEM on subregions is

consistent with that on full-length, completely better than EP and MPR, and partially better

than SA, PIC, and WSCP.

Figure 3 illustrates the prediction produced by SEM in the first cycle of cross-validation.

It can be seen that the predicted values possess a good linear relationship with the true values.

The predicted values and true values also have similar patterns in data distribution. But one

issue is that the models tend to make underestimated predictions when the true value > 12. This

will be further discussed in the discussion section.

Due to its superior performance, a bioinformatics tool, ANNA16, is developed based on

SEM and compared with other existing tools in the final test. Figure 4 and Table 2 demonstrate

the results of the final test. Because PICRRUSt2 has a much higher RMSE (Table 2), it is not

shown in Figure 4 and excluded from the case study. Figure 4 and Table 2 show that ANNA16

achieves the lowest RMSE among the tools at full-length and every subregion. The smallest

RMSE of SEM appears at full length, which is 0.683 copies/genome, and the highest RMSE is

at the V4 region, being 0.780 copies/genome. In contrast, the RMSE of CopyRighter ranges

from 1.822 (V4-V5) to 2.181 (V7-V9) copies/genome, rrnDB from 1.079 (V4-V5) to 1.207

(V4) copies/genome, PAPRICA from 0.773 (V3-V4) to 1.321 (V4-V5), and PICRUSt2 from

3.459 (V4-V5) to 4.731 (V6-V8). The performance of ANNA16 is better than other tools.

Figure 5, Table S4, and Table S5 show uncorrected copy fraction, true cell fraction, and

cell fraction (microbial profiles) estimated by ANNA16, rrnDB (version 5.7), and CopyRighter,

and PAPRICA. The difference in uncorrected copy fraction and true cell fraction proves GCN

correction is a necessary procedure if researchers aim to present an accurate microbial profile.

Bray-Curtis Dissimilarity analysis shows that the dissimilarity values of the four tools for the

even community is considerably higher than those for the staggered community. This coincides

with the compositional patterns, where the estimated staggered patterns by the four tools are

more similar to the patterns of true cell fractions. But, whichever the community, cell fraction

estimated by ANNA16 has the smallest dissimilarity value for both the even community and

staggered community. For the even community, PAPRICA and CopyRighter exhibit very close

dissimilarity values and are the second accurate tools. For the staggered community, PAPRICA

is the second accurate tool, followed by rrnDB, but CopyRighter becomes the most accurate

one. In summary, ANNA16 has the most similar patterns with true cell fraction compared to

the counterparts of other tools.

To illustrate how ANNA16 makes a prediction, the shap module in Python is used to

calculate the SHAP value of each K-mer. Figure S1 shows the top 20 K-mers ranked by mean

absolute SHAP value. Figure 6 shows the distribution of SHAP values on the sequences. To

determine the range of hypervariable regions, the sequence of conserved regions of *E. coli* is

first extracted according to region coordinates provided by Yarza et al. [25]. All sampled

sequences undergo BLASTN (version 2.11.0) against *E. coli* conserved sequences to determine

the range of conserved regions in each sequence. The range of hypervariable regions is thus

deduced from conserved regions. To make the figure less complicated, only 500 randomly

chosen sequences are labeled. Figure 6 indicates that ANNA16 does not simply extract

information from hypervariable regions–conserved regions also provide information. To

further illustrate the relationship between SHAP value and the information content (degree of

conservation), Figure 7 is drawn. Figure 7 plots the mean absolute SHAP value on each position

versus the degree of conservation of each position. Interestingly, the mean absolute SHAP

value reaches the peak when the degree of conservation is extremely low. This will be further

discussed in the Discussion section.

4   DISCUSSION

In summary, this study aims to use the Stacked Ensemble Model (SEM), one deep learning model, to predict 16S GCN based on 16S sequence. The performance of SEM is tested at the 16S full-length and subregions and compared with taxonomy- and phylogeny-based algorithms. Finally, ANNA16–a bioinformatic tool based on SEM–is subsequently developed and compared to existing 16S GCN correction tools, rrnDB, CopyRighter, PAPRICA, PICRUSt2, through the final test and a case study. The SHAP method is used to explain how ANNA16 finishes the task.

First and foremost, ANNA16 is also the most accurate and state-of-the-art GCN correction tools for 16S full-length, as well as for all subregions tested in this study. As shown in Figure 2, the algorithm used by ANNA16—Stacked Ensemble Model of MLP, SVM, and Ridge (SEM)—exhibits an error range that is completely lower than the error ranges of all taxonomy-based and phylogeny-based algorithms at 16S full-length. As for subregions, SEM still maintains the lowest error ranges although having overlaps with the counterparts of PIC, SA, WSCP. These results indicate SEM is capable of more accurately correcting GCN than existing algorithms at all regions tested, and its main advantage lies at 16S full-length. In addition, as Figure 4 and Table 2 shows, the RMSE of ANNA16 is the lowest among the tools at full-length and every subregion in the final test. This indicates ANNA16 has a stronger ability of predicting the GCN newly discovered species than other tools. Figure 5, Table S4, and Table S5 of the case study also confirms this indication, where the true cell fraction of both communities is more similar to those presented by ANNA16, especially for the staggered community.

Altogether, the results prove that ANNA16 is the most accurate 16S GCN correction tool for

the time being.

In addition to its superior performance, another advantage of ANNA16 is that it achieves

a fast inference speed without pre-computation. In general, existing GCN correction tools can

be classified as two types by inference strategies: pre-computation or real-time phylogenetic

placement. On the one hand, rrnDB and CopyRighter are pre-computational tools—they pre-

compute the GCN value for every taxon in the RDP database or Greengenes database respective

[5, 6]. On the other hand, PAPRICA and PICRUSt2 utilize real-time phylogenetic placement.

When a query is given, the tools first place the query sequence to its built-in phylogenetic tree

and make the prediction according to the new tree. Compared with real-time phylogenetic

placement, pre-computation strategy has a much short inference time, because the tools only

need to search the input lineages from the pre-computed GCN table, instead of computing the

value from scratch. However, this pre-computation strategy also means a pre-computed

correction tool will be bound to its database, which is a critical disadvantage of pre-computed

tools. Due to the existence of differences in nomenclature among databases (for example, the

SILVA database [58] merges *Allorhizobium*, *Neorhizobium*, *Pararhizobium*, and *Rhizobium* as

one genus, named *Allorhizobium-Neorhizobium-Pararhizobium-Rhizobium*, but in RDP these

are independent genera), increased error might be caused if a pre-computed tool is applied to a

taxonomy generated by a miscellaneous database. Fortunately, the deep learning method

implemented in this study is free of this *accuracy-or-time* dilemma. Users could predict the

GCN of each 16S sequence and assign taxonomy separately at a much shorter time than using

PAPRICA or PICRUSt2.

After proving the supremacy of ANNA16, it becomes an interesting question–how the

model perceives the complex relationship between K-mer counts and 16S GCN?

Conventionally, microbiologists believe the nine hypervariable regions are the most

informative regions on the 16S sequence that could reflect the phylogeny of one species.

Therefore, one hypothesis is that K-mers from hypervariable regions would contribute more to

prediction than those from conserved regions. However, Figure 6 shows that the distribution

of SHAP values does not completely fit in the location of hypervariable regions. Though high

SHAP values indeed tend to aggregate in V2, V3, V5, V6, V7, and V9 regions, conserved

regions between V2-V3, V4-V5, and V8-V9 also contribute considerably.

Since Figure 6 alone is not evident enough to accept or reject the hypothesis, Figure 7 is

drawn. By plotting information content against mean absolute SHAP values on each position,

we expect to see a linear relationship. However, the scatters are unexpectedly L-shaped, with

high SHAP values aggregating at positions with extremely low information content. SHAP

values are generally constant in other positions. This trend indicates extremely variable

positions or positions with insertion of extremely low frequency are most informative for

ANNA16. The other positions provide nearly the same level of information, no matter how

conserved they are. Deducing from this indication, this means ANNA16 can detect informative

positions and assign high weights to the positions. This may help explain why ANNA16 or

MLP has better performance than conventional algorithms. When implementing conventional

algorithms, variance in the sequence is converted to sequence similarity, and the sequence

similarity is to generate phylogeny or taxonomy. This approach weighs every position equally.

Therefore, informative positions can be underrepresented and non-informative regions

overrepresented in conventional algorithms. However, by weighing K-mers unequally

according to how much information they contain, ANNA16 could overcome this problem and

utilize the information contained in the 16S sequence more effectively. This finding reveals the

great potential of deep learning in genetics. On the one hand, deep learning could accurately

predict a trait based on sequencing data. On the other hand, by investigating the contribution

of each feature, scientists could discover which genes or loci are most related to the trait.

Several aspects of this study could still be improved. First, one limitation of ANNA16 is

the underestimation of species with high GCN. As can be seen in Figure 3, ANNA16 would

make underestimated prediction when the true GCN $\geq$ 14, and those predicted values can be

far from true values. This limitation could be attributed to the imbalance in the dataset. Figure

S2 shows the distribution of GCN in the preprocessed dataset. Sequences with GCN ≥ 12

account for only a small proportion of the whole dataset, and sequences with GCN > 15 are

extremely rare. This makes it difficult for the model to learn features of high GCN sequences.

The most feasible method to solve this problem is to wait for the increase in data. Thanks to

the invention of new sequencing techniques, nowadays genomic data is accumulating at an

exponential rate [59]. If more data about high GCN species could be collected, the

underestimation would be correspondingly relieved. Apart from waiting, the data science

community has developed a number of methods to relieve data imbalance, including class re-

balancing, information augmentation, and module improvement [60]. These methods could be

applied to ANNA16 and may solve the problem of underestimation. Lastly, as noted, currently

the amount of 16S GCN data is still limited. In this case, it is worth trying transfer learning.

Future studies could collect a massive amount of unlabeled 16S rRNA sequences and pre-train

a model on these data with an autoregression or autoencoder task, like the famous BERT [61]

or GPT-2/3/4 [62] models did. The pre-trained model may further improve the accuracy of 16S

GCN prediction.

5   CONCLUSIONS

In conclusion, this study developed ANNA16, a deep learning-based new bioinformatic

tool for predicting the gene copy number of 16S rRNA. The error range of ANNA16 at cross-

validation is significantly lower than the error ranges of all taxonomy-based and phylogeny-

based algorithms at 16S full-length and is partially lower at all 16S subregions. The

performance of ANNA16 in the final test and the case study is also significantly better than all

existing tools (i.e., rrnDB, CopyRighter, PICRUSt2, PAPRICA). As a deep learning tool of

simple structure, ANNA16 also possesses other advantages such as faster inference speed,

independence of pre-computation, and less demand for computing resources. SHAP analysis

implies ANNA16 could utilize the information contained in the 16S sequence more effectively

by weighing K-mers unequally according to how much information they contain. Future

studies may combine the strategy of pre-training model on unlabeled data with the strategies

for solving data imbalance to further decrease the error of copy number correction.

LIST OF ABBREVIATIONS

525   GCN: Gene Gopy Number

526   MLP: Multi-layer Perceptron

527   SEM: Stacked Ensemble Model

528   SHAP: Shapley Additive exPlanation

DECLARATIONS

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

16S rRNA sequences and the GCN data analyzed during the current study are available in the

rrnDB repository, https://rrndb.umms.med.umich.edu/. The codes of this study are available at

https://github.com/Merlinaphist/Anna16. ANNA16 is deployed on Google Colaboratory,

https://colab.research.google.com/drive/1XwpTMCHSfTmzpHyKrmiD8aC8C_1nndUV#scro

llTo=M0jLLsHC9W4M. The preprint of this study has been released on *bioRxiv* [63]:

https://www.biorxiv.org/content/10.1101/2022.11.26.518038v3.

Competing interests

This study receives funding from the Oracle Cloud Starter Award by the Oracle Corporation.

Funding

This work was supported by the Summer Research Scholars (SRS) program at Duke Kunshan

University (DKU), the startup funds of Y.L. and M.M. granted by DKU, and the Oracle Cloud

Starter Award by the Oracle Corporation.

Authors' contributions

J.M. conceived the study. J.M. and T.C. analyzed the data and implemented the models. Y.L.

and M.M. provided mentorship for the study. All authors contributed to the manuscript writing.

Acknowledgments

The authors would like to thank Dr. Jiang Long for his kind comments on algorithm design.

REFERENCES

1.   Woese CR, Fox GE: **Phylogenetic structure of the prokaryotic domain: the primary**
kingdoms. *Proc Natl Acad Sci U S A* 1977, **74**(11):5088-5090.
2.   STACKEBRANDT E, GOEBEL BM: **Taxonomic Note: A Place for DNA-DNA**
Reassociation and 16S rRNA Sequence Analysis in the Present Species Definition
in Bacteriology. *International Journal of Systematic and Evolutionary Microbiology*
1994, **44**(4):846-849.
3.   Louca S, Doebeli M, Parfrey LW: **Correcting for 16S rRNA gene copy numbers in**
microbiome surveys remains an unsolved problem. *Microbiome* 2018, **6**(1):41.
4.   Woo PC, Leung PK, Leung KW, Yuen KY: **Identification by 16S ribosomal RNA**
gene sequencing of an Enterobacteriaceae species from a bone marrow transplant
recipient. *Mol Pathol* 2000, **53**(4):211-215.
5.   Angly FE, Dennis PG, Skarshewski A, Vanwonterghem I, Hugenholtz P, Tyson GW:
CopyRighter: a rapid tool for improving the accuracy of microbial community
profiles through lineage-specific gene copy number correction. *Microbiome* 2014,
2(1):11.
6.   Stoddard SF, Smith BJ, Hein R, Roller BR, Schmidt TM: **rrnDB: improved tools for**
interpreting rRNA gene abundance in bacteria and archaea and a new foundation
for future development. *Nucleic Acids Res* 2015, **43**(Database issue):D593-598.
7.   Fogel GB, Collins CR, Li J, Brunk CF: **Mini-Review Article: Prokaryotic Genome**
Size and SSU rDNA Copy Number: Estimation of Microbial Relative Abundance
from a Mixed Population. *Microbial Ecology* 1999, **38**(2):93-113.
8.   Kembel SW, Wu M, Eisen JA, Green JL: **Incorporating 16S Gene Copy Number**
Information Improves Estimates of Microbial Diversity and Abundance. *PLOS*
Computational Biology 2012, **8**(10):e1002743.
9.   Jurtz VI, Johansen AR, Nielsen M, Almagro Armenteros JJ, Nielsen H, Sønderby CK,
Winther O, Sønderby SK: **An introduction to deep learning on biological sequence**
data: examples and solutions. *Bioinformatics* 2017, **33**(22):3685-3690.
10.   Park Y, Kellis M: **Deep learning for regulatory genomics**. *Nature Biotechnology* 2015,
33(8):825-826.
11.   Lancashire LJ, Lemetre C, Ball GR: **An introduction to artificial neural networks in**
bioinformatics—application to complex microarray and mass spectrometry
datasets in cancer studies. *Briefings in Bioinformatics* 2009, **10**(3):315-329.
12.   Schmidt B, Hildebrandt A: **Deep learning in next-generation sequencing**. *Drug*
Discov Today 2021, **26**(1):173-180.
13.   Stepniewska-Dziubinska MM, Zielenkiewicz P, Siedlecki P: **Development and**
evaluation of a deep learning model for protein–ligand binding affinity prediction.
Bioinformatics 2018, **34**(21):3666-3674.
14.   Fioravanti D, Giarratano Y, Maggio V, Agostinelli C, Chierici M, Jurman G, Furlanello
C: **Phylogenetic convolutional neural networks in metagenomics**. *BMC*
Bioinformatics 2018, **19**(2):49.

15.   Lo C, Marculescu R: **MetaNN: accurate classification of host phenotypes from**
metagenomic data using neural networks. *BMC Bioinformatics* 2019, **20**(12):314.
16.   Wang Y, Bhattacharya T, Jiang Y, Qin X, Wang Y, Liu Y, Saykin AJ, Chen L: **A novel**
deep learning method for predictive modeling of microbiome data. *Brief Bioinform*
2021, **22**(3).
17.   Zha Y, Chong H, Qiu H, Kang K, Dun Y, Chen Z, Cui X, Ning K: **Ontology-aware**
deep learning enables ultrafast and interpretable source tracking among sub-
million microbial community samples from hundreds of niches. *Genome Medicine*
2022, **14**(1):43.
18.   Arango-Argoty G, Garner E, Pruden A, Heath LS, Vikesland P, Zhang L: **DeepARG:**
a deep learning approach for predicting antibiotic resistance genes from
metagenomic data. *Microbiome* 2018, **6**(1):23.
19.   Ma Y, Guo Z, Xia B, Zhang Y, Liu X, Yu Y, Tang N, Tong X, Wang M, Ye X *et al*:
Identification of antimicrobial peptides from the human gut microbiome using
deep learning. *Nature Biotechnology* 2022, **40**(6):921-931.
20.   Chong H, Zha Y, Yu Q, Cheng M, Xiong G, Wang N, Huang X, Huang S, Sun C, Wu S
et al: **EXPERT: transfer learning-enabled context-aware microbial community**
classification. *Briefings in Bioinformatics* 2022:bbac396.
21.   Zhao Z, Woloszynek S, Agbavor F, Mell JC, Sokhansanj BA, Rosen GL: **Learning,**
visualizing and exploring 16S rRNA structure using an attention-based deep
neural network. In: *PLoS computational biology.* vol. 17; 2021: e1009345.
22.   Abellan-Schneyder I, Matchado MS, Reitmeier S, Sommer A, Sewald Z, Baumbach J,
List M, Neuhaus K: **Primer, Pipelines, Parameters: Issues in 16S rRNA Gene**
Sequencing. *mSphere* 2021, **6**(1).
23.   Woese CR, Kandler O, Wheelis ML: **Towards a natural system of organisms:**
proposal for the domains Archaea, Bacteria, and Eucarya. *Proc Natl Acad Sci U S*
A 1990, **87**(12):4576-4579.
24.   Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, Madden TL:
BLAST+: architecture and applications. *BMC Bioinformatics* 2009, **10**(1):421.
25.   Yarza P, Yilmaz P, Pruesse E, Glöckner FO, Ludwig W, Schleifer K-H, Whitman WB,
Euzéby J, Amann R, Rosselló-Móra R: **Uniting the classification of cultured and**
uncultured bacteria and archaea using 16S rRNA gene sequences. *Nature Reviews*
Microbiology 2014, **12**(9):635-645.
26.   Ebou A, Koua D, Zeze A: **HyperEx: A Tool to Extract Hypervariable Regions from**
16S rRNA Sequencing Data. *bioRxiv* 2021:2021.2009.2003.455391.
27.   Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJ, Holmes SP: **DADA2:**
High-resolution sample inference from Illumina amplicon data. *Nat Methods* 2016,
13(7):581-583.
28.   Cole JR, Wang Q, Fish JA, Chai B, McGarrell DM, Sun Y, Brown CT, Porras-Alfaro
A, Kuske CR, Tiedje JM: **Ribosomal Database Project: data and tools for high**
throughput rRNA analysis. *Nucleic Acids Research* 2013, **42**(D1):D633-D642.

29. DeSantis TZ, Hugenholtz P, Larsen N, Rojas M, Brodie EL, Keller K, Huber T, Dalevi
D, Hu P, Andersen GL: **Greengenes, a chimera-checked 16S rRNA gene database**
and workbench compatible with ARB. *Appl Environ Microbiol* 2006, **72**(7):5069-
5072.

30. Felsenstein J: **Phylogenies and the Comparative Method**. *The American Naturalist*
1985, **125**(1):1-15.

31. Sankoff D: **Minimal Mutation Trees of Sequences**. *SIAM Journal on Applied*
Mathematics 1975, **28**(1):35-42.

32. Maddison WP: **Squared-Change Parsimony Reconstructions of Ancestral States**
for Continuous-Valued Characters on a Phylogenetic Tree. *Systematic Zoology*
1991, **40**(3):304-314.

33. Louca S, Doebeli M: **Efficient comparative phylogenetics on large trees**.
Bioinformatics 2017, **34**(6):1053-1055.

34. Katoh K, Misawa K, Kuma Ki, Miyata T: **MAFFT: a novel method for rapid multiple**
sequence alignment based on fast Fourier transform. *Nucleic Acids Research* 2002,
30(14):3059-3066.

35. Price MN, Dehal PS, Arkin AP: **FastTree 2 – Approximately Maximum-Likelihood**
Trees for Large Alignments. *PLOS ONE* 2010, **5**(3):e9490.

36. Bowman JS, Ducklow HW: **Microbial Communities Can Be Described by**
Metabolic Structure: A General Framework and Application to a Seasonally
Variable, Depth-Stratified Microbial Community from the Coastal West Antarctic
Peninsula. *PLOS ONE* 2015, **10**(8):e0135868.

37. Douglas GM, Maffei VJ, Zaneveld JR, Yurgel SN, Brown JR, Taylor CM, Huttenhower
C, Langille MGI: **PICRUSt2 for prediction of metagenome functions**. *Nature*
Biotechnology 2020, **38**(6):685-688.

38. Barbera P, Kozlov AM, Czech L, Morel B, Darriba D, Flouri T, Stamatakis A: **EPA-ng:**
Massively Parallel Evolutionary Placement of Genetic Sequences. *Systematic*
Biology 2019, **68**(2):365-369.

39. Buitinck L, Louppe G, Blondel M, Pedregosa F, Mueller A, Grisel O, Niculae V,
Prettenhofer P, Gramfort A, Grobler J *et al*: **API design for machine learning software:**
experiences from the scikit-learn project. *CoRR* 2013, **abs/1309.0238**.

40. Lundberg SM, Lee S-I: **A Unified Approach to Interpreting Model Predictions**. In:
Advances in Neural Information Processing Systems: 2017: Edited by Guyon I,
Luxburg UV, Bengio S, Wallach H, Fergus R, Vishwanathan S, Garnett R. Curran
Associates, Inc. 2017.

41. Wolpert DH: **Stacked generalization**. *Neural Networks* 1992, **5**(2):241-259.

42. Breiman L: **Stacked regressions**. *Machine Learning* 1996, **24**(1):49-64.

43. Cortes C, Vapnik V: **Support-vector networks**. *Machine Learning* 1995, **20**(3):273-
297.

44. Ho TK: **Random Decision Forests**. In: *Proceedings of the Third International*
Conference on Document Analysis and Recognition (Volume 1) - Volume 1: 1995. M:
IEEE Computer Society 1995: 278-282.

45.   Cover TM, Hart PE: **Nearest neighbor pattern classification**. *IEEE Trans Inf Theory*
690   1967, **13**:21-27.

691   46.   Friedman JH: **Greedy function approximation: a gradient boosting machine**.
692   *Annals of statistics* 2001:1189-1232.

693   47.   Hoerl AE, Kennard RW: **Ridge Regression: Biased Estimation for Nonorthogonal**
694   **Problems**. *Technometrics* 1970, **12**(1):55-67.

695   48.   Tibshirani R: **Regression Shrinkage and Selection via the Lasso**. *Journal of the Royal*
696   *Statistical Society Series B (Methodological)* 1996, **58**(1):267-288.

697   49.   Lindauer M, Eggensperger K, Feurer M, Biedenkapp A, Deng D, Benjamins C,
698   Ruhkopf T, Sass R, Hutter F: **SMAC3: A Versatile Bayesian Optimization Package**
699   **for Hyperparameter Optimization**. In: *ArXiv: 210909831: 2021.*   2021.

700   50.   Loshchilov I, Hutter F: **SGDR: Stochastic Gradient Descent with Restarts**. *CoRR*
701   2016, **abs/1608.03983**.

702   51.   He K, Zhang X, Ren S, Sun J: **Deep Residual Learning for Image Recognition**. In:
703   *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR): 27-30*
704   *June 2016 2016*. 770-778.

705   52.   Moriya S: **Simple mapping-based quantification of a mock microbial community**
706   **using total RNA-seq data**. *PLoS One* 2021, **16**(7):e0254556.

707   53.   Bray JR, Curtis JT: **An Ordination of the Upland Forest Communities of Southern**
708   **Wisconsin**. *Ecological Monographs* 1957, **27**(4):325-349.

709   54.   Shapley LS: **A Value for N-Person Games**. Santa Monica, CA: RAND Corporation;
710   1952.

711   55.   Štrumbelj E, Kononenko I: **Explaining prediction models and individual predictions**
712   **with feature contributions**. *Knowledge and Information Systems* 2014, **41**(3):647-665.

713   56.   Schneider TD, Stormo GD, Gold L, Ehrenfeucht A: **Information content of binding**
714   **sites on nucleotide sequences**. *J Mol Biol* 1986, **188**(3):415-431.

715   57.   Schneider TD, Stephens RM: **Sequence logos: a new way to display consensus**
716   **sequences**. *Nucleic Acids Res* 1990, **18**(20):6097-6100.

717   58.   Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glöckner FO:
718   **The SILVA ribosomal RNA gene database project: improved data processing and**
719   **web-based tools**. *Nucleic Acids Research* 2012, **41**(D1):D590-D596.

720   59.   Navarro FCP, Mohsen H, Yan C, Li S, Gu M, Meyerson W, Gerstein M: **Genomics and**
721   **data science: an application within an umbrella**. *Genome Biology* 2019, **20**(1):109.

722   60.   Zhang Y, Kang B, Hooi B, Yan S, Feng J: **Deep Long-Tailed Learning: A Survey**.
723   *CoRR* 2021, **abs/2110.04596**.

724   61.   Devlin J, Chang M-W, Lee K, Toutanova K: **Bert: Pre-training of deep bidirectional**
725   **transformers for language understanding**. *arXiv preprint arXiv:1810 04805* 2018.

726   62.   Brown TB, Mann B, Ryder N, Subbiah M, Kaplan J, Dhariwal P, Neelakantan A, Shyam
727   P, Sastry G, Askell A *et al*: **Language Models are Few-Shot Learners**. *CoRR* 2020,
728   **abs/2005.14165**.

729   63.   Miao J, Chen T, Misir M, Lin Y: **Deep Learning for Predicting 16S rRNA Copy**
730   **Number**. *bioRxiv* 2022:2022.2011.2026.518038.

732 **TABLES**

733 **Table 1.** Performance of all algorithms at 16S full-length and subregions (Mean RMSE ± SD).

	Full Length	V1-V2	V1-V3	V3-V4	V4	V4-V5	V6-V8	V7-V9
SEM	0.685 ± 0.0379	0.751 ± 0.0285	0.727 ± 0.0301	0.730 ± 0.0450	0.774 ± 0.0453	0.746 ± 0.0364	0.733 ± 0.0368	0.737 ± 0.0423
EP	0.845 ± 0.0443	0.928 ± 0.0331	0.889 ± 0.0476	0.902 ± 0.0447	0.916 ± 0.0569	0.910 ± 0.0340	0.909 ± 0.0563	0.931 ± 0.0354
MPR	0.787 ± 0.0375	0.867 ± 0.0370	0.836 ± 0.0305	0.858 ± 0.0477	0.879 ± 0.0475	0.858 ± 0.0413	0.852 ± 0.0400	0.846 ± 0.0370
PIC	0.789 ± 0.0243	0.810 ± 0.0281	0.805 ± 0.0307	0.789 ± 0.0503	0.824 ± 0.0377	0.785 ± 0.0277	0.781 ± 0.0404	0.802 ± 0.0393
SA	0.774 ± 0.0329	0.829 ± 0.0321	0.805 ± 0.0430	0.811 ± 0.0379	0.822 ± 0.0388	0.810 ± 0.0283	0.807 ± 0.0391	0.830 ± 0.0334
WSCP	0.775 ± 0.0273	0.793 ± 0.0242	0.782 ± 0.0330	0.779 ± 0.0483	0.823 ± 0.0405	0.785 ± 0.0354	0.779 ± 0.0377	0.790 ± 0.0375
TA(RDP)	1.18 ± 0.0356	1.58 ± 0.0538	1.41 ± 0.0517	1.47 ± 0.0370	1.93 ± 0.0954	1.48 ± 0.0622	1.44 ± 0.0329	1.73 ± 0.129
TA(Greengenes)	2.52 ± 0.0388	2.08 ± 0.122	2.63 ± 0.147	1.85 ± 0.0939	2.12 ± 0.0590	2.00 ± 0.0961	2.19 ± 0.232	2.54 ± 0.434

734 EP: empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent contrast; SA: Subtree Averaging; WSCP:

735 weighted-squared-change parsimony; TA(RDP): sub-taxa averaging based on RDP database; TA(Greengenes): sub-taxa averaging based on

736 Greengenes database; SEM: Stacked Ensemble Model.

740 **Table 2.** Performance of 16S GCN Correction Tools in the Final Test (RMSE)

	Full Length	V1-V2	V1-V3	V3-V4	V4	V4-V5	V6-V8	V7-V9
CopyRighter	1.994	1.934	1.989	1.825	1.848	1.822	1.952	2.181
rrnDB5.7	1.083	1.094	1.082	1.101	1.207	1.079	1.109	1.110
ANNA16	0.683	0.711	0.710	0.716	0.780	0.715	0.720	0.713
PICRUSt2	4.198	4.353	4.175	4.393	3.807	3.459	4.731	4.677
PAPRICA	0.817	0.857	1.319	0.773	0.896	1.321	0.987	0.778

742 **FIGURES**

a) Illustration of K-merization

b) Framework of Developing ANNA16

c) Architecture of the Stacked Ensemble Learner   d) Architecture of the MLP model

744 **Figure 1.** Illustration of the Framework and Architecture of the Deep Learning Models. a) K-

745 mer strategy (K = 6). b) Framework of Designing ANNA16. c) Architecture of the Stacked

746 Ensemble Model. d) Architecture of the MLP model inside the Stacked Ensemble Model.

Figure 2. Performance of all algorithms or models at 16S full-length and subregions. EP:

empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent

contrast; SA: Subtree Averaging; WSCP: weighted-squared-change parsimony; TA(RDP): sub-

taxa averaging based on RDP database; SEM: stacked ensemble model.

Figure 3. Prediction by SEM on 16S full length and subregions in the first cycle of 5-fold

cross-validation. The red line is a diagonal line illustrating to which extent the predicted values

are derived from the true values. The density plot filled in violet shows the distribution of the

true values, and the green density plot shows the distribution of the predicted values.

Figure 4. Comparison of performance on the test dataset among CopyRighter, rrnDB, ANNA16, and PAPRICA.

Figure 5. Uncorrected copy fraction, true cell fraction, and cell fraction (microbial profiles) estimated by ANNA16, rrnDB (version 5.7), CopyRighter, and PAPRICA. The right panel shows the value of Bray-Curtis Dissimilarity of each estimated profile to the true cell fraction. Uncorrected: Uncorrected copy fraction; True: True cell fraction; ANNA16: Cell fraction estimated by ANNA16; rrnDB5.7: Cell fraction estimated by rrnDB (version 5.7); CopyRighter: Cell fraction estimated by CopyRighter; PAPRICA: Cell fraction estimated by PAPRICA.

Figure 6. Distribution of SHAP values at 16S full-length sequences. To make the figure

interpretable, only the value of the top 100 K-mers ranked by mean absolute SHAP value is

shown. Hypervariable regionsare labeled as grey shadows. V-region labels on the x-axis show

the general position of *E. coli* V-regions according to coordinates from Yarza et al. [25].

Figure 7. Relationship of mean absolute SHAP values and the information content (unit: bits)

on each position of aligned 16S full-length sequence.