Deep Learning for Predicting 16S rRNA Gene Copy Number

Jiazheng Miao[1], Tianlai Chen[1], Mustafa Misir[1, *], and Yajuan Lin[1, 2, *]

[1]*Division of Applied and Natural Sciences, Duke Kunshan University, Suzhou, China*

[2]*Deparment of Life Sciences, Texas A&M University-Corpus Christi, Corpus Christi, USA*

*Correspondence:

Mustafa Misir

mustafa.misir@dukekunshan.edu.cn

Yajuan Lin

yajuan.lin@tamucc.edu

ABSTRACT

Background

Culture-independent 16S rRNA gene metabarcoding is a commonly used method in microbiome profiling. However, this approach can only reflect the proportion of sequencing reads, rather than the actual cell fraction. To achieve more quantitative cell fraction estimates, we need to resolve the 16S gene copy numbers (GCN) for different community members. Currently, there are several bioinformatic tools available to estimate 16S GCN, either based on taxonomy assignment or phylogeny.

Method

Here we develop a novel algorithm, Stacked Ensemble Model (SEM), that estimates 16S GCN directly from the 16S rRNA gene sequence strings, without resolving taxonomy or phylogeny. For accessibility, we developed a public, end-to-end, web-based tool based on the SEM model, named Artificial Neural Network Approximator for 16S rRNA Gene Copy Number (ANNA16).

Results

Based on 27,579 16S rRNA gene sequence data (rrnDB database), we show that ANNA16 outperforms the most commonly used 16S GCN prediction algorithms. The prediction error range in the 5-fold cross validation of SEM is completely lower than all other algorithms for the 16S full-length sequence and partially lower at 16S subregions. The final test and a mock community test indicate ANNA16 is more accurate than all currently available tools (i.e.,

42   rrnDB, CopyRighter, PICRUSt2, & PAPRICA). SHAP value analysis indicates ANNA16

43   mainly learns information from rare insertions.

Conclusion

45   ANNA16 represents a deep learning based 16S GCN prediction tool. Compared to the

46   traditional GCN prediction tools, ANNA16 has a simple structure, faster inference speed

47   without precomputing, and higher accuracy. With increased 16S GCN data in the database,

48   future studies could improve the prediction errors for rare, high-GCN taxa due to current under

49   sampling.

1   INTRODUCTION

Culture-independent 16S rRNA metabarcoding is a molecular biology technique that

applies DNA sequencing technology to the prokaryotic 16S rRNA gene to identify and quantify

the microbial communities present in a sample [1]. This technique has been established as the

gold standard for inferring organismal phylogeny and microbial ecology for over 20 years [2].

However, a major limitation of 16S rRNA metabarcoding is that next-generation sequencing

estimates the proportion of 16S rRNA gene read counts, rather than the true cell counts. Since

it is typical for prokaryotes to have more than one copy of the 16S rRNA gene per cell (1 - 21

copies/genome) [3], the proportion of 16S rRNA gene read counts (also known as relative 16S

abundance) does not accurately reflect the true composition of a microbial community [4, 5].

To address this issue and accurately represent the profile of the microbiota, the proportion of

16S rRNA gene read counts needs to be weighted by the inverse of 16S gene copy number

(GCN). This step yields a corrected microbial composition that represents the proportion of

cell counts of each lineage in the community [4].

To estimate 16S GCN, researchers typically rely on experimental methods such as whole

genome sequencing [3] or competitive PCR [6]. However, these methods can be expensive

and/or culture-dependent, and thus experimental GCN estimates are only available for a limited

number of species. To overcome this limitation, several bioinformatics tools have been recently

developed to predict the GCN of unmeasured species from measured species. Although there

are exceptions [7], the basic assumption is that 16S GCN is correlated with phylogenetic

distance across species [4, 8], i.e., 16S GCN variation is relatively small among closely related

species and increases with phylogenetic distance. This allows 16S GCN to be estimated either

from taxonomy or phylogeny [4, 8, 9]. For instance, rrnDB [3] is a well-cited tool that corrects

16S GCN based on taxonomy. It calculates the mean 16S GCN of a taxon from the means of

its sub-taxa. Another example is PICRUSt2 [10], one correction tool that constructs a

phylogenetic tree of the 16S sequence and estimates the GCN of the unmeasured species from

its close measured relatives.

Deep learning, as a popular machine learning strategy, has been recently applied to learn

complex patterns from biological sequencing data [11, 12]. In this study, we explore deep

learning as a novel approach for predicting 16S GCN. Deep learning is a branch of machine

learning which uses many layers of Artificial Neural Networks (ANN) to learn complex

representations of data [13]. The concept of ANN is inspired by the way a human brain learns

and processes information through synaptic interactions between neurons [14]. An ANN is a

computational model that is constituted by multiple interconnected processing elements—

artificial neurons [14]. Neurons are utilized in groups as the layers of a network. Each artificial

neuron receives and processes input with a non-linear function, known as the activation

function [15]. Collectively, one ANN model learns to solve a specific task by capturing non-

linear trends and relationships from the presented data. Beyond these capabilities, ANNs are

even competent in disclosing relationships or mechanisms that are still unknown to scientists

[16]. Deep learning gets its name by having more than one (hidden) layer connecting the input

and output units. Having deeper networks refer to representing complex input-output

relationships while accommodating a large amount of data. In that sense, high-dimensional

biological data is a popular target for deep learning. For example, various deep learning

architectures, like the Convolutional Neural Network, and Recurrent Neural Network, have

been applied to microbiome research, including metagenomic-based taxonomy classification

[17], 16S rRNA classification [18], host phenotype prediction [19], disease prediction [20], and

microbial community predication [21]. Furthermore, deep learning algorithms have been

developed to conduct data mining for antibiotic resistance genes [22], antimicrobial peptides

[23], and microbial source [24].

With the great potential of extracting biological information from DNA sequences

demonstrated by the previous studies, this study explores the possibility of estimating GCN

directly from the 16S DNA sequence through deep learning. To the best of our knowledge, no

deep learning-based method has been utilized for 16S GCN prediction yet. A Stacked Ensemble

Model (SEM) is first trained on the 16S full-length sequences and compares the performance

to the taxonomy-based and phylogeny-based algorithms. The sequences and GCN data are

retrieved from the ribosomal RNA operon copy number database (rrnDB), a publicly available,

curated resource for copy number information for bacteria and archaea [3]. Because microbial

studies tend to target one to three adjacent hypervariable regions in 16S rRNA [25], this study

also trains deep learning models on different combinations of the adjacent hypervariable

regions in 16S rRNA and compares the performance with conventional algorithms. Finally, a

deep learning-based bioinformatic tool for 16S GCN correction is developed. The tool is

compared with existing correction tools to assess the performance. Shapley Additive

exPlanations (SHAP), a game theory-based model explanation method [26], is applied to

ANNA16 to reveal how this deep learning model understands the 16S rRNA gene sequences.

2   MATERIALS AND METHODS

2.1.   Data Source and Preprocessing

16S rRNA gene sequences and the GCN data used to train deep learning models in this

study were retrieved from rrnDB, version 5.7 [3]. The dataset includes a total of 20,277 16S

gene sequences with unique accession numbers, containing both (+) strands and (-) strands.

Firstly, the orientation for all sequences in this dataset were identified using BLASTN

algorithm (BLAST+, version 2.11.0) [27]. The first 50 bp of the *E. coli* 16S rRNA gene

sequence (+) strand (accession number: GCF_002953035.1), a conserved region on 16S rRNA

[28], were used as a template. Sequences with High-Scoring Segment Pairs (HSPs) that had

sstart (subject start) > send (subject end) and evalue < 0.01 were identified as (+) strands, and

those with sstart < send and evalue < 0.01 were identified as (-) strands. 389 sequences that did

not meet these criteria were labeled as unrecognizable and excluded from the dataset. The

reverse complement of these (-) strand sequences were then added to the (+) strand sub-dataset.

Next, in order to have uniform starting and ending positions, all 16S rRNA gene sequences

in the database were further trimmed by HyperEx [29], using the universal full-length 16S

primer 27F and primer 1492R (Table S1) [25, 30]. After that, 19,520 sequences remained in

this full-length dataset, involving 1,331 genera, with an average sequence length of 1,498.72

nucleotides and a standard deviation of 21.41 nucleotides. 16S GCN ranges from 1 to 21

copies/genome (Mean = 5.26, SD = 2.74). In addition, seven commonly targeted subregions

by metabarcoding, i.e., V1-V2, V1-V3, V3-V4, V4, V4-V5, V6-V8, and V7-V9 [25], were also

extracted by HyperEx (primers listed in Table S1) to generate subregion datasets. The full-

length and subregional datasets were used as the training datasets.

Additionally, during the course of this study, a new version rrnDB 5.8 were release on June

23rd, 2022, including 8,059 newly added sequences and their GCN. The added data involves

676 genera, and 219 of the genera that are not present in the version 5.7 dataset. The average

sequence length is 1,499.79 nucleotides (SD = 21.67), and the range of 16S GCN is 1 - 20

copies/genome (Mean = 5.72, SD = 2.85). The newly published data were also processed by

BLASTN and HyperEx and produced an independent final test dataset.

By conducting a five-fold cross-validation at each region, the initial GCN datasets were

first split into training and test sets to compare the performance of SEM and other conventional

algorithms. Data in the train datasets were used to pre-train a SEM model, and the model was

tested at each region using the test datasets. Existing GCN tools were also applied to the test

datasets and their performance were compared with that of SEM. Once an optimal GCN model

was selected, the train datasets and test datasets were combined to train the final model. Finally,

the independent final test dataset was used to evaluate the robustness and accuracy of the final

model.

2.2.   Method Comparison: Conventional GCN Algorithms and Existing Tools

There are two predominant CGN algorithms: taxonomy-based and phylogeny-based

approaches.

Taxonomic aggregation (TA) is a commonly used taxonomy-based GCN algorithm [3, 31].

The algorithm calculates the mean 16S GCN of a taxon from the GCN means of its sub-taxa.

To implement this algorithm, 16S sequences were first classified using the *assignTaxonomy*

function in the DADA2 package in R (version 1.21.0) [32]. Two well-established 16S database,

RDP (version 18) [33] and Greengenes (version 13.8) [34] were used as the reference for the

assignTaxonomy function to determine whether the choice of classification database would

impact GCN prediction performance. The algorithm was implemented in Python (version 3.8)

with an object-oriented programming approach. The algorithm took the taxonomic and GCN

data and treated every taxon as a Node object. Every Node is linked with its downstream Nodes

(taxa), so eventually the Nodes formed a hierarchical tree where the *Prokaryote domain* is the

root, and the species are the tips. Finally, the algorithm pre-computed the GCN of every Node

by taking the mean of its sub-Nodes. When a query is given, the algorithm will search the

hierarchical tree for the lowest taxon of the query lineage. If a query has unassigned taxon, it

assigns the value of the query's parent node to the query node as an estimation.

Phylogenetic algorithms were based on a pre-constructed tree of 16S rRNA gene

sequences and the GCN of each ancestral node was estimated from its daughter species through

weighing each labeled daughter node with phylogenetic distance to the parental node [35]. For

method comparison, this study employed five phylogeny-based algorithms, including

empirical probabilities (EP), subtree averaging (SA), phylogenetic independent contrasts (PIC)

[36], Sankoff's maximum-parsimony (MPR) [37], and weighted-squared-change parsimony

(WSCP) [38]. To implement these algorithms, 16S rRNA gene sequences in the dataset were

first aligned by MAFFT v7.490 [39] and then a 16S phylogenetic tree was constructed by

FastTree 2.1.10 [40]. The five phylogeny-based GCN algorithms were then executed using the

castor package in R [35], with modifications made from the R script in [9]. In particular, MPR

was   implemented   by   function   *hsp_max_parsimony*,   WSCP   by   function

hsp_squared_change_parsimony, SA by function *hsp_subtree_averaging*, EP by function

hsp_empirical_probabilities, and PIC by *hsp_independent_contrasts*, all configured to default

parameters.

Apart from conventional GCN algorithms, the existing GCN tools include rrnDB [3],

CopyRighter [4], PAPRICA [41], and PICRUSt2 [10] were also implemented for method

comparison. rrnDB is a taxonomy-based tool using taxonomic aggregation, while the latter

three are phylogeny-based tools. CopyRighter uses the PIC algorithm to pre-compute the copy

number of all taxa in the Greengenes database [34] and makes predictions by searching the

lineages of the queries in its pre-computed GCN table [4]. PAPRICA and PICRUSt2 first utilize

EPA-ng [42] to place the queries on their built-in phylogenetic tree and then use subtree-

averaging (PAPRICA) or maximum parsimony (PICRUSt2) to predict the GCN of the queries

[10, 41].

Because rrnDB and CopyRighter output GCN corrected microbial community

composition rather than 16S GCN values directly, this study extracted their precomputed tables

(rrnDB version 5.7) to generate GCN values, searching the precomputed tables for assigned

lineages. The taxonomy of full-length 16S sequences and all subregion sequences were

generated by the *assignTaxonomy* function in the DADA2 package through RDP (version 18)

and Greengenes (version 13.8, formatted by DADA2) [34] database. The assigned RDP

lineages were searched in the rrnDB precomputed table, and Greengenes lineages were

searched in CopyRighter precomputed table. As for PAPRICA and PICRUSt2, the DNA

sequences in the test dataset were directly input to the tools. For PAPRICA, *paprica-run.sh*

was called without additional parameters. For PTCRUSt2, *place_seqs.py* and *hsp.py* were

called without additional parameters.

2.3.   Development of ANNA16

2.3.1. DNA sequence K-merization

The 16S rRNA gene sequences were first preprocessed with K-merization. An example of

a set with three 6-mers is displayed in Figure 1a. The K-mers were converted into the number

of counts in the set via the *CountVectorizer* function in the scikit-learn module (version 0.23.2)

[43]. Subsequently, the K-mer counts and GCN data were used to train the SEM models.

After testing K from 3 to 7 on a prototype 3-layer Multi-layer Perceptron (MLP) model,

the model performance was found to improve with increasing K. However, a larger K value

required significantly more memory. Thus, the optimal K value was determined to be 6, striking

a balance between good performance and manageable memory requirements.

2.3.2.   Model Construction

Based on 6-mers, the Stacked Ensemble Model (SEM) was constructed for 16S GCN

prediction using the Tensorflow package (version 2.8.0) in Python (version 3.8). The initial

dataset was split for training and testing by 3:1. The SEM model training was conducted on a

Nvidia RTX 3090 GPU. This SEM method involves training multiple base models on the

available data, after which a meta-model is used to aggregate the outputs of all base-models

and make the final prediction. Typically, the stacked model performs better than any single

base model [44, 45].

The first base model of SEM is a Multi-layer Perceptron (MLP). MLP is a type of artificial

neural network that consists of layers of artificial neurons, and the input is processed layer by

layer [14]. The calculation of the output for each neuron is as follows [14]:

227
$$\nu_k = \sum_{i=0}^{n} \omega_{k,i} x_i$$

228
$$\gamma_k = \varphi(\nu_k + \nu_{k_0})$$

229   where v_k is the net output of neuron k, with x_1, x_2, . . ., x_n being the input from the last

230   layer, and $\omega_{k,1}$, $\omega_{k,2}$, . . ., $\omega_{k,n}$ being the weights on the input. γ_k is the output of the neuron,

231   where v_{k_0} represents the bias, and $\varphi(.)$ refers to the activation function. And the MLP part

232   is trained with Rooted Mean Squared Error (RMSE) loss:

233
$$\text{RMSE} = \sqrt{\frac{\sum_{i=0}^{n}(Y_{true} - Y_{pred})^2}{n}}$$

where n is the size of the input dataset, Y_{true} is the true value of copy number, Y_{pred} is the

value of the predicted copy number.

In addition to MLP, the K-mer counts data would undergo a dimension reduction by the

Principal Component Analysis (PCA) algorithm, implemented by the *PCA* function in scikit-

learn with *n_components* set to 100, and then be input to the several other machine learning

models, including Support Vector Machine (SVM) [46], Random Forest [47], K-nearest

Neighbors [48], and Gradient Boosting [49]. Linear Regression, Ridge Regression [50], and

Lasso Regression [51] were tested as meta-models which accept the output of MLP, PCA and

machine learning models and make the final prediction. All machine learning algorithms were

implemented by the scikit-learn module (version 0.23.2). After the initial testing, SVM was

selected among the base-models and Ridge Regression among the meta-models (Figure 2c).

2.3.3. Parameter Optimization

The parameter of SEM was optimized through the *SMAC4BB* function in the SMAC3

package (version 1.4.0) [52] for 500 iterations. For the MLP component, hyperparameters

including the number of dense layers, hidden layer size, activation functions, and learning rate

were tuned. The number of dense layers of the model was tested in the range of [1, 7], hidden

layer size from the range of [1, 1024], activation functions are selected among Rectified Linear

Unit (RELU), Exponential Linear Unit (ELU), Gaussian Error Linear Unit (GELU), Scaled

Exponential Linear Unit (SELU), and Linear, and the learning rate was tested in the range of

[0.00005, 0.1]. The mathematic formulae of the activation functions are demonstrated in the

Supplementary Methods.

The final MLP architecture (Figure 2d) contains a dense block of 6 hidden layers, with

neuron numbers of 489, 926, 645, 929, 582, and 82 respectively, and the activation functions

are GELU, ReLU, ReLU, ELU, GELU, and Linear respectively. For SVM, the *kernel* value

was chosen from "rbf", "sigmoid", and "linear", *gamma* was tested between "scale" and "auto",

and *C* was tested as a float in the range of [0.3, 0.9] or as an integer in the range of [1, 100].

For Ridge, the value of *alpha* was tested as a float in the range of [0.3, 0.9] or as an integer in

the range of [1, 100]. After tuning, the optimized parameters are *kernel = 'rbf'*, *gamma =*

'auto', *C = 11*, and *alpha = 49* (a complete list of parameters is shown in Table S2).

The resulted final model is named the Artificial Neural Network Approximator for 16S

rRNA Gene Copy Number (ANNA16).

2.3.4. Other Deep Learning Models Tested

In addition to SEM, this study also developed and evaluated a Transformer model and a

Residual Multi-layer Perceptron model for 16S GCN prediction. Details about these two

models are described in the Supplementary Methods and Figure S1 & S2. However, neither

model achieved perform comparable to the SEM and they were not selected.

2.4.   Mock Community Test

To assess model performance, an *in silico* test study was designed based on two

commercially available mock communities [53], one even community (ATCC, MSA-2003)

and one staggered community (ATCC, MSA-1001) (Figure 5, Table S3). Both mock

communities consist of ten common bacterial strains, but of different ratios. This study

retrieved genome sequences of the ten strains from NCBI, and copy number data from rrnDB

(version 5.7). An arbitrary total cell number (1×10^5 cells) were assigned to each community

and the cell number for each strain was calculated based on the known/targeted fraction.

To evaluate the accuracy of community profile prediction by different tools, Bray-Curtis

Dissimilarity [54] was calculated between the true cell fraction and the estimated cell fraction

using the *vegdist* function in the vegan (version 2.5-7) package.

2.5.   Model Explanation

In this study, SHAP a unified measure of feature importance that quantifies individual

feature contributions to a model prediction, was utilized to explain DNA loci's contributions

[26]. Based on collational game theory [55] and the classical Shapley method [56], SHAP

views each feature as a player. The final contribution of a feature is the sum of all the marginal

contributions across various subsets. Positive and negative SHAP values indicate positive and

negative contribution to the model's prediction, respectively. In this study, each K-mer is

considered a feature, and its SHAP value is calculated using the *KernelExplainer* function in

shap module (version 0.41.0) in Python, treating each single prediction as an independent game.

294   This study randomly sampled 10% of the whole dataset for SHAP value analysis (N =

2758). As a result, a list of 2,758 SHAP values was assigned to every K-mer to represent the

K-mer's overall contribution. These SHAP values were mapped back to the 16S rRNA gene

sequence according to the position of the corresponding K-mers to investigate if there is a

positional pattern in contribution. What is more, to study the relationship between contribution

and nucleotide conservation in a position, the rate of nucleic substitution, insertion, and

deletion of each position was calculated using aligned 16S rRNA gene sequences, with *E. coli*

(accession number: GCF_002953035.1) as the reference, to represent how conserved a position.

The upper boundary of the plot of SHAP values versus the insertion rate was fitted with the elu

function to explore how ANNA16 weighs one insertion. To represent the upper boundary, the

insertion rate was first clustered with the *KMeans* function in the scikit-learn package into 50

ranks. For each rank, the mean insertion rate and max SHAP values were calculated. Adam

optimizer in the tensorflow package were used to fit the elu function with a learning rate of

0.01 and 2000 iterations.

3   RESULTS

310   This study evaluated the performance of SEM in comparison with other algorithms for

full-length 16S GCN correction. Figure 2 and Table 1 summarize the results of 5-fold cross-

validation. Among all algorithms, taxonomic aggregation methods (TA) perform the worst. TA

based on RDP or Greengenes reference database exhibit a mean RMSE in copies/genome 1.18

(SD = 0.0356) and 2.52 (SD = 0.0388), respectively. Due to the much higher mean RMSE of

TA with Greengenes, only results from TA with RDP are shown in Figure 2. All phylogeny-

based algorithms perform better than taxonomic aggregation, with WSCP the best phylogeny-

based algorithm. SEM, the deep learning model, outperforms all other algorithms with the

lowest mean RMSE 0.685 copies/genome, with SD = 0.0379. Its error range on the 16S full-

length is significantly lower than all other algorithms ($p < 0.01$).

Furthermore, algorithm performance was evaluated and compared for commonly

amplified 16S subregions (Figure 2). Compared to the performance on full length, in general

all algorithms produce larger RMSE on subregions. SEM displays relatively consistent

performance on subregions, ranging from 0.731 (V1-V3) to 0.774 (V4) copies/genome.

Notably, except for V3-V4, V4, and V4-V5 of WSCP and V4 of SA, the error range of SEM

on subregions is significantly lower than all other algorithms in all subregions ($p < 0.05$). These

findings indicate SEM outperforms EP, MPR, PIC, and TA with RDP or Greengenes, while

partially outperforms SA, and WSCP.

The prediction results produced by SEM from the first cycle of cross-validation are

presented in Figure 3 and Figure S3. The figure shows a strong linear relationship between the

predicted values and the true values, with density plot showing similar data distribution patterns.

However, it is worth noting that SEM tends to underestimate the GCN when the true value is

greater than 14. This issue is further discussed in Section 4.

Due to SEM's superior performance, a GCN prediction tool, ANNA16, is developed based

on SEM and compared with other available tools in the final test, the newly published data in

rrnDB version 5.8 (Figure 4 and Table 2). Because PICRRUSt2 has a much higher RMSE (i.e.,

larger than 3.4 copies/genome for all regions), it is excluded from Figure 4 and the following

case study. ANNA16 achieves the lowest RMSE among all the tools examined, with the

smallest RMSE (0.683) at the full-length and the highest RMSE (0.780) at V4. In contrast, the

RMSE of CopyRighter ranges from 1.822 (V4-V5) to 2.181 (V7-V9) copies/genome, rrnDB

from 1.079 (V4-V5) to 1.207 (V4) copies/genome, PAPRICA from 0.773 (V3-V4) to 1.321

(V4-V5), and PICRUSt2 from 3.459 (V4-V5) to 4.731 (V6-V8). ANNA16 outperformed all

other tools, demonstrating superior performance at all subregions and full-length, which

indicated its superior ability to predict GCN in newly discovered species.

To demonstrate the performance of ANNA16 intuitively, a case study of *in silico* mock

communities was conducted. Figure 5, Table S4, and Table S5 show uncorrected copy fraction,

true cell fraction, and cell fraction (microbial profiles) estimated by ANNA16, rrnDB (version

5.7), CopyRighter, and PAPRICA. The difference in uncorrected copy fraction and true cell

fraction demonstrates that GCN correction is necessary for obtaining an accurate microbiome

profile. The Bray-Curtis Dissimilarity analysis shows that in general the dissimilarity values

for the even community are considerably higher than those for the staggered community. The

cell fraction estimated by ANNA16 has the smallest dissimilarity value for both even and

staggered communities. For the even community, PAPRICA and CopyRighter exhibit very

close dissimilarity values and are the second most accurate tools. For the staggered community,

PAPRICA is the second most accurate tool, followed by rrnDB, but CopyRighter is the least

accurate one. Overall, ANNA16 outperforms all the other tools in terms of similarity patterns

with the true cell fraction.

To illustrate how ANNA16 makes its predictions, the shap module in Python is used to

calculate the SHAP value of each K-mer, which represents the contribution of each K-mer to

the prediction. Figure S4 displays the top 20 K-mers ranked by mean absolute SHAP value,

while Figure 6 illustrates mean absolute SHAP values of each nucleic position across the full

length 16S rRNA gene sequences. The pattern does not fully coincide with the hypervariable

regions, which implies the distribution of high SHAP values does not strictly align with the

traditionally identified hypervariable regions. To confirm this implication, the relationship

between SHAP value and the rate of mutations (substitution, insertion, and deletion) is plotted

in Figure 7. Figure 7a and 7b shows that no non-linear pattern could be observed between

SHAP values and substitution or deletion, and the Pearson correlation coefficients indicate the

linear association is also weak (cor=0.144 or cor=0.248). However, intriguingly, the insertion

rate exhibits a non-linear relationship with SHAP values, with high SHAP values reaching its

peak when the insertion rate is extremely low. These results imply ANNA16 mainly relies on

rare insertions to predict GCN, instead of substitutions.

4   DISCUSSION

This study introduces ANNA16, a novel method for predicting 16S GCN based on 16S

DNA sequence using a deep learning model. This novel approach outperforms currently

available taxonomy- and phylogeny-based algorithms in accuracy, excelling in predicting GCN

not only for the 16S full-length sequences but also in all commonly amplified subregions.

4.1.   Strengths of ANNA16

Compared with existing GCN correction tools, the ANNA16 method owns their strengths

and meanwhile avoids the drawbacks. Existing GCN correction tools can be classified into two

categories based on their inference strategies: pre-computation or real-time phylogenetic

placement. On the one hand, pre-computational tools (i.e., rrnDB & CopyRighter) compute the

GCN value for every taxon in the database beforehand, and the tools retrieve the GCN values

from the database when a query is given. This strategy has the advantage of short inference

time, but is also heavily relay on the reference database, which can lead to errors if used with

databases having differences in nomenclature. For example, the SILVA database [57] merges

Allorhizobium, *Neorhizobium*, *Pararhizobium*, and *Rhizobium* as one genus, named

Allorhizobium-Neorhizobium-Pararhizobium-Rhizobium, but in RDP these are independent

genera.

On the other, real-time phylogenetic placement tools (i.e., PAPRICA and PICRUSt2) place

a query sequence into their built-in phylogenetic trees to predict the GCN value at runtime.

This strategy leads to better prediction performance than pre-computational tools, as shown in

Figure 2 and 4, but requires much longer inference time because phylogenetic placement can

be computationally extensive. However, the performance of ANNA16 can even be better than

real-time phylogenetic placement tools, as shown in Figure 2 and 4. Compared with these tools,

ANNA16 exhibits even better performance than real-time phylogenetic placement tools, avoids

database-dependence by predicting GCN values directly from 16S rRNA gene sequences, and

maintains a relatively short inference time because the prediction can be accelerated by GPUs.

4.2.   Explaining ANNA16

After proving the excellence of ANNA16, an intriguing question this study contemplates

is how a deep learning model interprets the intricate biological/evolutionary information

contained within the 16S DNA sequence. Interestingly, Figure 6 and Figure 7 suggest

ANNA16's approach is highly different from existing methods.

First, the peaks of high SHAP values across the 16S full-length sequence are not aligned

with the nine hypervariable regions. As shown in Figure 6, although there are peaks of high

SHAP values at the V1, V2, V4, and V5 regions, yet the conserved regions before V1 and

between V2, V3, V4, V5, and V6 also contain some loci that are significantly contributory.

Those conserved regions even seem more contributory than the remaining variable regions (i.e.,

V3 and V6-V9). These results indicate the concept of variability is not equivalent to

informativeness for ANNA16.

Second, SHAP values shows no association with nucleic substitutions. Previous studies

mainly use nucleic substitutions to infer evolutionary information. For example, the fraction of

nucleic substitutions between two sequences are commonly used as a representation for

evolutionary distance [58], or the substitution rate was used as the metric for studying the

positional variability in 16S rRNA gene [59]. However, as shown in Figure 7a, the rooted

SHAP values remain at a constant low level (about 0.05) despite the variation in the substitution

rate. This means implies that substitutions may not be so important for ANNA16, as every

substitution makes the similarly low degree of contribution regardless of the prevalence.

Given the specialty of ANNA16, SHAP values was plotted against the deletion and

insertion rate (Figure 7b & 7c) to further explore how ANNA16 perceives the information in

DNA sequences. The deletion rate demonstrates a similar pattern with SHAP values as the

substitution rate, where the rooted SHAP values also remain near 0.05. However, an intriguing

L-shaped trend emerges between the insertion rate and the rooted SHAP values. High SHAP

values aggregate at the positions with the lowest end of the insertion rate, whereas in other

areas, SHAP values also maintain the constant level of 0.05. This pattern suggests that

insertions of extremely low frequency are the most informative for ANNA16. Each rare

insertion may only exist in a limited number of taxonomic lineages, so they could serve as

identifiers of the corresponding lineages for ANNA16. What is more interesting, the upper

boundary of Figure 7c appears to be highly similar with the elu activation function used in

ANNA16. After using the elu function to fit the upper boundary, 91.17% variability in the

SHAP values could be explained (Figure 7d). In general, these results imply that ANNA16

might understand one DNA sequence by screening for rare insertions.

One potential explanation for these trends in Figure 6 and Figure 7 is that some neurons in

the MLP part of ANNA16 are differentiated for detecting the rare insertions, and they are

assigned with high weights by other neurons. Similar to biological neurons, artificial neurons

also receive input signals and fire an output to other neurons if the stimulus reaches a certain

threshold. Hypothetically, some differentiated neurons might only fire when ANNA16

encounters one insertion whose rarity reaches the threshold (roughly 10^{-2} per site according to

Figure 7d). This might result in the elu-shape of the upper boundary in Figure 7c, which places

high SHAP values at positions with rare insertions and reduces the SHAP values of the

remaining positions to a relatively low level.

These implications may explain why ANNA16 or MLP outperform conventional

algorithms. In the aspect of information extraction, traditional algorithms have two drawbacks.

First, these algorithms typically weigh every position equally by converting the variance in the

sequence-to-sequence similarity, which can underrepresent informative positions. Second,

especially for phylogeny-based algorithms, some information could be wasted while inferring

the phylogeny as most tree-building methods would ignore alignment gaps [58, 60-63].

Previous studies have proved that indels are likely to experience few homoplasy and may

produce more congruent phylogenetic trees if combined with substitutions [58, 60-63].

However, ANNA16 adopts a more nuanced approach, which not only considers the

substitutions but also pays more attention to insertions. This allows ANNA16 to more

effectively harness the information embedded in the 16S sequences, confirming the necessity

of including indels in phylogenetics. Future studies could also consider turning from classic

theory-based methods to machine learning, a data-driven and alignment-free approach, for

extracting the evolutionary information from the sequences. The effectiveness of ANNA16 also

highlights the significant potential of deep learning in genetics. Not only can deep learning

models like ANNA16 accurately predict traits based on sequencing data, but by analyzing the

contribution of each DNA feature, researchers can also establish connections between specific

genes or loci and the trait of interest. For example, by combining deep learning with the SHAP

methodology, previous studies have evaluated the contribution of genes for predicting tissue

types [64], or the pathway-level contribution for the phenotype of diffuse large B-cell

lymphoma [65].

4.3. Limitations & Future Studies

Although ANNA16 has shown great performance in 16S GCN prediction, there are several

limitations. One limitation is its tendency to underestimate the GCN of species with high GCN.

As shown in Figure 3, ANNA16's predictions become increasingly underestimated when the

true GCN is greater than or equal to 14. This limitation could be attributed to the imbalanced

distribution of GCN in the currently available dataset (Figure S5). Sequences with GCN ≥ 12

account for only a small proportion of the whole dataset, and sequences with GCN > 15 are

extremely rare. The model could be improved with more new sequence data with high GCN

species, as new sequencing techniques are rapidly generating more genomic data. Similar

implications are also discussed by [4, 9]. Alternatively, data imbalance methods, such as class

re-balancing, information augmentation, and module improvement [66] could be applied to

ANNA16 and other future models to address the issue.

Furthermore, transfer learning [67, 68] could also be explored as a potential solution. In

the framework of transfer learning, a deep learning model is first pre-trained on one or more

source tasks to capture general features or representation, and then is fine-tuned to apply the

captured knowledge to target tasks [69]. To utilize this strategy, future studies could first collect

a large amount of unlabeled 16S rRNA sequences and pre-train a model with an autoregression

or autoencoder task, similar to Large Language Models like BERT [70] or GPT [71], and then

fine-tune the model on the child task, 16S GCN prediction, which may yield more accurate

results.

5   CONCLUSIONS

In conclusion, this study developed ANNA16 as a deep learning-based new bioinformatic

tool for predicting the gene copy number of 16S rRNA. Compared to existing taxonomy-based

and phylogeny-based algorithms, ANNA16 showed significantly lower error ranges at 16S

full-length and all 16S subregions in the cross-validation. Furthermore, in the final test and

mock community case study, ANNA16 outperformed existing tools such as rrnDB,

CopyRighter, PICRUSt2, and PAPRICA. ANNA16's simple structure also offers several

advantages, including faster inference speed, independence of pre-computation, and less

demand for computing resources. The SHAP analysis implies ANNA16 could utilize the

information contained in the 16S rRNA gene sequences more effectively by not only

considering substitutions, but also paying more attention to rare insertions. Future studies could

focus on strategies such as pre-training the model on unlabeled data and addressing data

imbalance to further decrease the error of copy number correction.

LIST OF ABBREVIATIONS

ANNA16: Artificial Neural Network Approximator for 16S rRNA Gene Copy Number

ELU: Exponential Linear Unit

EP: Empirical Probabilities

GCN: Gene Copy Number

GELU: Gaussian Error Linear Unit

MLP: Multi-layer Perceptron

MPR: Sankoff's Maximum Parsimony

PIC: Phylogenetic Independent Contrasts

RELU: Rectified Linear Unit

SA: Subtree Averaging

SELU: Scaled Exponential Linear Unit

SEM: Stacked Ensemble Model

SHAP: Shapley Additive exPlanation

TA: Taxonomic Aggregation

WSCP: Weighted Squared Change Parsimony

DECLARATIONS

Ethics approval and consent to participate

Not applicable.

Consent for publication

Not applicable.

Availability of data and materials

16S rRNA sequences and the GCN data analyzed during the current study are available in the

rrnDB repository, https://rrndb.umms.med.umich.edu/. The codes and model files of ANNA16

are available at https://github.com/Merlinaphist/ANNA16. ANNA16 is deployed on Google

Colab,

https://colab.research.google.com/drive/1XwpTMCHSfTmzpHyKrmiD8aC8C_1nndUV#scro

llTo=M0jLLsHC9W4M.

Competing interests

This study receives funding from the Oracle Cloud Starter Award by the Oracle Corporation.

Funding

This work was supported by the Summer Research Scholars (SRS) program at Duke Kunshan

University (DKU), the startup funds of Y.L. and M.M. granted by DKU, and the Oracle Cloud

Starter Award by the Oracle Corporation.

Authors' contributions

J.M. conceived the study. J.M. and T.C. analyzed the data and implemented the models. Y.L.

and M.M. provided mentorship for the study. All authors contributed to the manuscript writing.

Acknowledgments

The authors would like to thank Dr. Jiang Long for his kind comments on algorithm design.

REFERENCES

1. Woese CR, Fox GE: **Phylogenetic structure of the prokaryotic domain: the primary kingdoms**. *Proc Natl Acad Sci U S A* 1977, **74**(11):5088-5090.

2. Woo PC, Leung PK, Leung KW, Yuen KY: **Identification by 16S ribosomal RNA gene sequencing of an Enterobacteriaceae species from a bone marrow transplant recipient**. *Mol Pathol* 2000, **53**(4):211-215.

3. Stoddard SF, Smith BJ, Hein R, Roller BR, Schmidt TM: **rrnDB: improved tools for interpreting rRNA gene abundance in bacteria and archaea and a new foundation for future development**. *Nucleic Acids Res* 2015, **43**(Database issue):D593-598.

4. Angly FE, Dennis PG, Skarshewski A, Vanwonterghem I, Hugenholtz P, Tyson GW: **CopyRighter: a rapid tool for improving the accuracy of microbial community profiles through lineage-specific gene copy number correction**. *Microbiome* 2014, **2**(1):11.

5. Vandeputte D, Kathagen G, D'hoe K, Vieira-Silva S, Valles-Colomer M, Sabino J, Wang J, Tito RY, De Commer L, Darzi Y *et al*: **Quantitative microbiome profiling links gut community variation to microbial load**. *Nature* 2017, **551**(7681):507-511.

6. Fogel GB, Collins CR, Li J, Brunk CF: **Mini-Review Article: Prokaryotic Genome Size and SSU rDNA Copy Number: Estimation of Microbial Relative Abundance from a Mixed Population**. *Microbial Ecology* 1999, **38**(2):93-113.

7.   Lavrinienko A, Jernfors T, Koskimäki JJ, Pirttilä AM, Watts PC: **Does Intraspecific**

Variation in rDNA Copy Number Affect Analysis of Microbial Communities?

Trends in Microbiology 2021, **29**(1):19-27.

8.   Kembel SW, Wu M, Eisen JA, Green JL: **Incorporating 16S Gene Copy Number**

Information Improves Estimates of Microbial Diversity and Abundance. *PLOS*

Computational Biology 2012, **8**(10):e1002743.

9.   Louca S, Doebeli M, Parfrey LW: **Correcting for 16S rRNA gene copy numbers in**

microbiome surveys remains an unsolved problem. *Microbiome* 2018, **6**(1):41.

10.   Douglas GM, Maffei VJ, Zaneveld JR, Yurgel SN, Brown JR, Taylor CM, Huttenhower

C, Langille MGI: **PICRUSt2 for prediction of metagenome functions**. *Nature*

Biotechnology 2020, **38**(6):685-688.

11.   Jurtz VI, Johansen AR, Nielsen M, Almagro Armenteros JJ, Nielsen H, Sønderby CK,

Winther O, Sønderby SK: **An introduction to deep learning on biological sequence**

data: examples and solutions. *Bioinformatics* 2017, **33**(22):3685-3690.

12.   Park Y, Kellis M: **Deep learning for regulatory genomics**. *Nature Biotechnology* 2015,

33(8):825-826.

13.   Dechter R: **Learning while searching in constraint-satisfaction-problems**. In:

Proceedings of the Fifth AAAI National Conference on Artificial Intelligence;

Philadelphia, Pennsylvania. AAAI Press 1986: 178–183.

14.   Lancashire LJ, Lemetre C, Ball GR: **An introduction to artificial neural networks in**

582   **bioinformatics—application to complex microarray and mass spectrometry**

583   **datasets in cancer studies**. *Briefings in Bioinformatics* 2009, **10**(3):315-329.

584   15.   Schmidt B, Hildebrandt A: **Deep learning in next-generation sequencing**. *Drug*

585   *Discov Today* 2021, **26**(1):173-180.

586   16.   Stepniewska-Dziubinska MM, Zielenkiewicz P, Siedlecki P: **Development and**

587   **evaluation of a deep learning model for protein–ligand binding affinity prediction**.

588   *Bioinformatics* 2018, **34**(21):3666-3674.

589   17.   Fioravanti D, Giarratano Y, Maggio V, Agostinelli C, Chierici M, Jurman G, Furlanello

590   C: **Phylogenetic convolutional neural networks in metagenomics**. *BMC*

591   *Bioinformatics* 2018, **19**(2):49.

592   18.   Zhao Z, Woloszynek S, Agbavor F, Mell JC, Sokhansanj BA, Rosen GL: **Learning,**

593   **visualizing and exploring 16S rRNA structure using an attention-based deep**

594   **neural network**. In: *PLoS computational biology.* vol. 17; 2021: e1009345.

595   19.   Lo C, Marculescu R: **MetaNN: accurate classification of host phenotypes from**

596   **metagenomic data using neural networks**. *BMC Bioinformatics* 2019, **20**(12):314.

597   20.   Wang Y, Bhattacharya T, Jiang Y, Qin X, Wang Y, Liu Y, Saykin AJ, Chen L: **A novel**

598   **deep learning method for predictive modeling of microbiome data**. *Brief Bioinform*

599   2021, **22**(3).

600   21.   Zha Y, Chong H, Qiu H, Kang K, Dun Y, Chen Z, Cui X, Ning K: **Ontology-aware**

601   **deep learning enables ultrafast and interpretable source tracking among sub-**

million microbial community samples from hundreds of niches. *Genome Medicine*

2022, **14**(1):43.

22.   Arango-Argoty G, Garner E, Pruden A, Heath LS, Vikesland P, Zhang L: **DeepARG:**

a deep learning approach for predicting antibiotic resistance genes from

metagenomic data. *Microbiome* 2018, **6**(1):23.

23.   Ma Y, Guo Z, Xia B, Zhang Y, Liu X, Yu Y, Tang N, Tong X, Wang M, Ye X *et al*:

Identification of antimicrobial peptides from the human gut microbiome using

deep learning. *Nature Biotechnology* 2022, **40**(6):921-931.

24.   Chong H, Zha Y, Yu Q, Cheng M, Xiong G, Wang N, Huang X, Huang S, Sun C, Wu S

et al: **EXPERT: transfer learning-enabled context-aware microbial community**

classification. *Briefings in Bioinformatics* 2022:bbac396.

25.   Abellan-Schneyder I, Matchado MS, Reitmeier S, Sommer A, Sewald Z, Baumbach J,

List M, Neuhaus K: **Primer, Pipelines, Parameters: Issues in 16S rRNA Gene**

Sequencing. *mSphere* 2021, **6**(1).

26.   Lundberg SM, Lee S-I: **A Unified Approach to Interpreting Model Predictions**. In:

Advances in Neural Information Processing Systems: 2017: Edited by Guyon I,

Luxburg UV, Bengio S, Wallach H, Fergus R, Vishwanathan S, Garnett R. Curran

Associates, Inc. 2017.

27.   Camacho C, Coulouris G, Avagyan V, Ma N, Papadopoulos J, Bealer K, Madden TL:

BLAST+: architecture and applications. *BMC Bioinformatics* 2009, **10**(1):421.

28. Yarza P, Yilmaz P, Pruesse E, Glöckner FO, Ludwig W, Schleifer K-H, Whitman WB,

Euzéby J, Amann R, Rosselló-Móra R: **Uniting the classification of cultured and**

uncultured bacteria and archaea using 16S rRNA gene sequences. *Nature Reviews*

Microbiology 2014, **12**(9):635-645.

29. Ebou A, Koua D, Zeze A: **HyperEx: A Tool to Extract Hypervariable Regions from**

16S rRNA Sequencing Data. *bioRxiv* 2021:2021.2009.2003.455391.

30. Parada AE, Needham DM, Fuhrman JA: **Every base matters: assessing small subunit**

rRNA primers for marine microbiomes with mock communities, time series and

global field samples. *Environmental Microbiology* 2016, **18**(5):1403-1414.

31. Sugihara G, Bersier LF, Schoenly K: **Effects of taxonomic and trophic aggregation**

on food web properties. *Oecologia* 1997, **112**(2):272-284.

32. Callahan BJ, McMurdie PJ, Rosen MJ, Han AW, Johnson AJ, Holmes SP: **DADA2:**

High-resolution sample inference from Illumina amplicon data. *Nat Methods* 2016,

13(7):581-583.

33. Cole JR, Wang Q, Fish JA, Chai B, McGarrell DM, Sun Y, Brown CT, Porras-Alfaro

A, Kuske CR, Tiedje JM: **Ribosomal Database Project: data and tools for high**

throughput rRNA analysis. *Nucleic Acids Research* 2013, **42**(D1):D633-D642.

34. DeSantis TZ, Hugenholtz P, Larsen N, Rojas M, Brodie EL, Keller K, Huber T, Dalevi

D, Hu P, Andersen GL: **Greengenes, a chimera-checked 16S rRNA gene database**

and workbench compatible with ARB. *Appl Environ Microbiol* 2006, **72**(7):5069-

5072.

35.   Louca S, Doebeli M: **Efficient comparative phylogenetics on large trees**.

644   *Bioinformatics* 2017, **34**(6):1053-1055.

645   36.   Felsenstein J: **Phylogenies and the Comparative Method**. *The American Naturalist*

646   1985, **125**(1):1-15.

647   37.   Sankoff D: **Minimal Mutation Trees of Sequences**. *SIAM Journal on Applied*

648   *Mathematics* 1975, **28**(1):35-42.

649   38.   Maddison WP: **Squared-Change Parsimony Reconstructions of Ancestral States**

650   **for Continuous-Valued Characters on a Phylogenetic Tree**. *Systematic Zoology*

651   1991, **40**(3):304-314.

652   39.   Katoh K, Misawa K, Kuma Ki, Miyata T: **MAFFT: a novel method for rapid multiple**

653   **sequence alignment based on fast Fourier transform**. *Nucleic Acids Research* 2002,

654   **30**(14):3059-3066.

655   40.   Price MN, Dehal PS, Arkin AP: **FastTree 2 – Approximately Maximum-Likelihood**

656   **Trees for Large Alignments**. *PLOS ONE* 2010, **5**(3):e9490.

657   41.   Bowman JS, Ducklow HW: **Microbial Communities Can Be Described by**

658   **Metabolic Structure: A General Framework and Application to a Seasonally**

659   **Variable, Depth-Stratified Microbial Community from the Coastal West Antarctic**

660   **Peninsula**. *PLOS ONE* 2015, **10**(8):e0135868.

661   42.   Barbera P, Kozlov AM, Czech L, Morel B, Darriba D, Flouri T, Stamatakis A: **EPA-ng:**

662   **Massively Parallel Evolutionary Placement of Genetic Sequences**. *Systematic*

663   *Biology* 2019, **68**(2):365-369.

43.   Buitinck L, Louppe G, Blondel M, Pedregosa F, Mueller A, Grisel O, Niculae V,

Prettenhofer P, Gramfort A, Grobler J *et al*: **API design for machine learning software:**

experiences from the scikit-learn project. *CoRR* 2013, **abs/1309.0238**.

44.   Wolpert DH: **Stacked generalization**. *Neural Networks* 1992, **5**(2):241-259.

45.   Breiman L: **Stacked regressions**. *Machine Learning* 1996, **24**(1):49-64.

46.   Cortes C, Vapnik V: **Support-vector networks**. *Machine Learning* 1995, **20**(3):273-

297.

47.   Ho TK: **Random Decision Forests**. In: *Proceedings of the Third International*

Conference on Document Analysis and Recognition (Volume 1) - Volume 1: 1995. M:

IEEE Computer Society 1995: 278-282.

48.   Cover TM, Hart PE: **Nearest neighbor pattern classification**. *IEEE Trans Inf Theory*

1967, **13**:21-27.

49.   Friedman JH: **Greedy function approximation: a gradient boosting machine**.

Annals of statistics 2001:1189-1232.

50.   Hoerl AE, Kennard RW: **Ridge Regression: Biased Estimation for Nonorthogonal**

Problems. *Technometrics* 1970, **12**(1):55-67.

51.   Tibshirani R: **Regression Shrinkage and Selection via the Lasso**. *Journal of the Royal*

Statistical Society Series B (Methodological) 1996, **58**(1):267-288.

52.   Lindauer M, Eggensperger K, Feurer M, Biedenkapp A, Deng D, Benjamins C,

Ruhkopf T, Sass R, Hutter F: **SMAC3: A Versatile Bayesian Optimization Package**

for Hyperparameter Optimization. In: *ArXiv: 210909831: 2021*.   2021.

53.   Moriya S: **Simple mapping-based quantification of a mock microbial community**

686   **using total RNA-seq data**. *PLoS One* 2021, **16**(7):e0254556.

687   54.   Bray JR, Curtis JT: **An Ordination of the Upland Forest Communities of Southern**

688   **Wisconsin**. *Ecological Monographs* 1957, **27**(4):325-349.

689   55.   Shapley LS: **A Value for N-Person Games**. Santa Monica, CA: RAND Corporation;

690   1952.

691   56.   Štrumbelj E, Kononenko I: **Explaining prediction models and individual predictions**

692   **with feature contributions**. *Knowledge and Information Systems* 2014, **41**(3):647-665.

693   57.   Quast C, Pruesse E, Yilmaz P, Gerken J, Schweer T, Yarza P, Peplies J, Glöckner FO:

694   **The SILVA ribosomal RNA gene database project: improved data processing and**

695   **web-based tools**. *Nucleic Acids Research* 2012, **41**(D1):D590-D596.

696   58.   Birth N, Dencker T, Morgenstern B: **Insertions and deletions as phylogenetic signal**

697   **in an alignment-free context**. *PLoS Comput Biol* 2022, **18**(8):e1010303.

698   59.   Van de Peer Y, Chapelle S, De Wachter R: **A quantitative map of nucleotide**

699   **substitution rates in bacterial rRNA**. *Nucleic Acids Res* 1996, **24**(17):3381-3391.

700   60.   Lloyd DG, Calder VL: **Multi-residue gaps, a class of molecular characters with**

701   **exceptional reliability for phylogenetic analyses**. *Journal of Evolutionary Biology*

702   1991, **4**(1):9-21.

703   61.   Simmons MP, Ochoterena H: **Gaps as Characters in Sequence-Based Phylogenetic**

704   **Analyses**. *Systematic Biology* 2000, **49**(2):369-381.

62. Houde P, Braun EL, Narula N, Minjares U, Mirarab S: **Phylogenetic Signal of Indels**

and the Neoavian Radiation. *Diversity* 2019, **11**(7).

63. Yuri T, Kimball RT, Harshman J, Bowie RC, Braun MJ, Chojnowski JL, Han KL,

Hackett SJ, Huddleston CJ, Moore WS *et al*: **Parsimony and model-based analyses**

of indels in avian nuclear genes reveal congruent and incongruent phylogenetic

signals. *Biology (Basel)* 2013, **2**(1):419-444.

64. Yap M, Johnston RL, Foley H, MacDonald S, Kondrashova O, Tran KA, Nones K,

Koufariotis LT, Bean C, Pearson JV *et al*: **Verifying explainability of a deep learning**

tissue classifier trained on RNA-seq data. *Scientific Reports* 2021, **11**(1):2641.

65. Hayakawa J, Seki T, Kawazoe Y, Ohe K: **Pathway importance by graph**

convolutional network and Shapley additive explanations in gene expression

phenotype of diffuse large B-cell lymphoma. *PLoS One* 2022, **17**(6):e0269570.

66. Zhang Y, Kang B, Hooi B, Yan S, Feng J: **Deep Long-Tailed Learning: A Survey**.

CoRR 2021, **abs/2110.04596**.

67. Pan SJ, Yang Q: **A Survey on Transfer Learning**. *IEEE Transactions on Knowledge*

and Data Engineering 2010, **22**(10):1345-1359.

68. Thrun S, Pratt L: **Learning to Learn: Introduction and Overview**. In: *Learning to*

Learn. Edited by Thrun S, Pratt L. Boston, MA: Springer US; 1998: 3-17.

69. Han X, Zhang Z, Ding N, Gu Y, Liu X, Huo Y, Qiu J, Yao Y, Zhang A, Zhang L *et al*:

Pre-trained models: Past, present and future. *AI Open* 2021, **2**:225-250.

70.   Devlin J, Chang M-W, Lee K, Toutanova K: **Bert: Pre-training of deep bidirectional**

transformers for language understanding. *arXiv preprint arXiv:1810 04805* 2018.

71.   Brown TB, Mann B, Ryder N, Subbiah M, Kaplan J, Dhariwal P, Neelakantan A, Shyam

P, Sastry G, Askell A *et al*: **Language Models are Few-Shot Learners**. *CoRR* 2020,

abs/2005.14165.

TABLES

Table 1. Performance of all algorithms at 16S full-length and subregions (Mean RMSE ± SD, *p*-value).

	Full Length	V1-V2	V1-V3	V3-V4	V4	V4-V5	V6-V8	V7-V9
SEM	0.685 ± 0.0379	0.751 ± 0.0285	0.727 ± 0.0301	0.730 ± 0.0450	0.774 ± 0.0453	0.746 ± 0.0364	0.733 ± 0.0368	0.737 ± 0.0423
EP	0.845 ± 0.0443	0.928 ± 0.0331	0.889 ± 0.0476	0.902 ± 0.0447	0.916 ± 0.0569	0.910 ± 0.0340	0.909 ± 0.0563	0.931 ± 0.0354
	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.01$	$p < 0.001$	$p < 0.001$	$p < 0.001$
MPR	0.787 ± 0.0375	0.867 ± 0.0370	0.836 ± 0.0305	0.858 ± 0.0477	0.879 ± 0.0475	0.858 ± 0.0413	0.852 ± 0.0400	0.846 ± 0.0370
	$p < 0.01$	$p < 0.001$	$p < 0.001$	$p < 0.01$	$p < 0.01$	$p < 0.001$	$p < 0.001$	$p < 0.01$
PIC	0.789 ± 0.0243	0.810 ± 0.0281	0.805 ± 0.0307	0.789 ± 0.0503	0.824 ± 0.0377	0.785 ± 0.0277	0.781 ± 0.0404	0.802 ± 0.0393
	$p < 0.001$	$p < 0.01$	$p < 0.01$	$p < 0.05$	$p < 0.05$	$p < 0.05$	$p < 0.05$	$p < 0.05$
SA	0.774 ± 0.0329	0.829 ± 0.0321	0.805 ± 0.0430	0.811 ± 0.0379	0.822 ± 0.0388	0.810 ± 0.0283	0.807 ± 0.0391	0.830 ± 0.0334
	$p < 0.01$	$p < 0.01$	$p < 0.01$	$p < 0.01$	$p = 0.054$	$p < 0.01$	$p < 0.01$	$p < 0.01$
WSCP	0.775 ± 0.0273	0.793 ± 0.0242	0.782 ± 0.0330	0.779 ± 0.0483	0.823 ± 0.0405	0.785 ± 0.0354	0.779 ± 0.0377	0.790 ± 0.0375
	$p < 0.05$	$p < 0.05$	$p < 0.05$	$p = 0.067$	$p = 0.054$	$p = 0.062$	$p < 0.05$	$p < 0.05$
TA(RDP)	1.18 ± 0.0356	1.58 ± 0.0538	1.41 ± 0.0517	1.47 ± 0.0370	1.93 ± 0.0954	1.48 ± 0.0622	1.44 ± 0.0329	1.73 ± 0.129
	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$
TA(Greengenes)	2.52 ± 0.0388	2.08 ± 0.122	2.63 ± 0.147	1.85 ± 0.0939	2.12 ± 0.0590	2.00 ± 0.0961	2.19 ± 0.232	2.54 ± 0.434
	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$	$p < 0.001$

733 EP: empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent contrast; SA: Subtree Averaging; WSCP:

734 weighted-squared-change parsimony; TA(RDP): taxonomic aggregation based on RDP database; TA(Greengenes): taxonomic aggregation based

735 on Greengenes database; SEM: Stacked Ensemble Model.

738 **Table 2. Performance of 16S GCN Correction Tools in the Final Test (RMSE)**

	Full Length	V1-V2	V1-V3	V3-V4	V4	V4-V5	V6-V8	V7-V9
CopyRighter	1.994	1.934	1.989	1.825	1.848	1.822	1.952	2.181
rrnDB5.7	1.083	1.094	1.082	1.101	1.207	1.079	1.109	1.110
ANNA16	0.683	0.711	0.710	0.716	0.780	0.715	0.720	0.713
PICRUSt2	4.198	4.353	4.175	4.393	3.807	3.459	4.731	4.677
PAPRICA	0.817	0.857	1.319	0.773	0.896	1.321	0.987	0.778

740   **FIGURES**

a) Illustration of K-merization

b) Framework of Developing ANNA16

c) Architecture of the Stacked Ensemble Learner   d) Architecture of the MLP model

742   **Figure 1. Illustration of the framework and architecture of the deep learning models.** a)

743   DNA sequence K-merization (K = 6). b) Framework for designing ANNA16. c) Architecture

744   of the Stacked Ensemble Model (SEM). d) Architecture of the MLP model module inside the

745   SEM.

Figure 2. Algorithm performance comparisons at 16S full-length and commonly sequenced subregions. EP: empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent contrast; SA: Subtree Averaging; WSCP: weighted-squared-change parsimony; TA(RDP): taxonomic aggregation based on RDP database; SEM: stacked ensemble model.

Full Length

Figure 3. Prediction by SEM on 16S full-length in the first cycle of 5-fold cross-validation.

The red line is a diagonal line illustrating to which extent the predicted values are derived from

the true values. The density plot filled in violet shows the distribution of the true values, and

the green density plot shows the distribution of the predicted values.

Figure 4. Comparison of performance on the final test dataset among CopyRighter,

rrnDB5.7, ANNA16, and PAPRICA.

	Bacillus cereus ATCC 10987		Enterococcus faecalis OG1RF
	Bifidobacterium adolescentis ATCC 15703		Escherichia coli str. K−12 substr. MG1655
	Cereibacter sphaeroides 2.4.1		Lactobacillus gasseri ATCC 33323
	Clostridium beijerinckii ATCC 35702		Staphylococcus epidermidis ATCC 12228
	Deinococcus radiodurans R1		Streptococcus mutans UA159

Figure 5. *In silico* test with the mock communities. Left panels: The composition of the even

community estimated by uncorrected 16S gene copy fraction, ANNA16, PAPRICA, rrnDB

(version 5.7), CopyRighter and their Bray-Curtis Dissimilarity with the cell fraction. The

Dissimilarity values are presented as the heat map. Right panel: The composition of the

staggered community estimated by the methods and their Bray-Curtis Dissimilarity with the

cell fraction. Uncorrected: Uncorrected copy fraction; True: True cell fraction; ANNA16: Cell

fraction estimated by ANNA16; rrnDB5.7: Cell fraction estimated by rrnDB (version 5.7);

CopyRighter: Cell fraction estimated by CopyRighter; PAPRICA: Cell fraction estimated by

PAPRICA. Even Community: All bacterial strains account for the same proportion. Staggered

Community: The ratio of each bacterial strains is uneven.

Figure 7. Mean absolute SHAP values across 16S rRNA gene full-length sequences. The

mean absolute SHAP values were calculated using the aligned sequences, and then converted

to *E. coli* coordinates with *E. coli* (accession number: GCF_002953035.1) as the reference.

Figure 7. Relationship of SHAP values and the rate of mutations on each position of the

aligned 16S rRNA gene sequences. (a) Log10 Substitution Rate vs. Rooted Mean Absolute

SHAP Value. (b) Log10 Deletion Rate vs. Rooted Mean Absolute SHAP Value. (c) Log10

Insertion Rate vs. Rooted Mean Absolute SHAP Value. (d) The upper boundary of Log10

Insertion Rate vs. Rooted Mean Absolute SHAP Value, fitted by the elu function.