Deep Learning for Predicting 16S rRNA Copy Number

Jiazheng Miao[1], Tianlai Chen[1], Mustafa Misir[1, *], and Yajuan Lin[1, *]

[1]*Department of Applied and Natural Science, Duke Kunshan University, Suzhou, China*

Correspondence*:

Mustafa Misir

Division of Natural and Applied Sciences, Duke Kunshan University, Duke Avenue No: 8,

Suzhou, 215316, China

mustafa.misir@dukekunshan.edu.cn

Yajuan Lin

Division of Natural and Applied Sciences, Duke Kunshan University, Duke Avenue No: 8,

Suzhou, 215316, China

linyajuan@gmail.com

ABSTRACT

16S rRNA is a commonly used technique to identify prokaryotes. However, this approach

could only reflect the proportion of sequencing reads, instead of actual cell fraction. To

accurately represent actual cell fraction, bioinformatic tools that estimate 16S gene copy

number (GCN) of unmeasured species are required. All the existing tools rely on taxonomy

or phylogeny to predict 16S GCN. The present study develops a deep learning-based method

that establishes a novel route. The proposed approach, i.e., Artificial Neural Network

Approximator for 16S rRNA Gene Copy Number (ANNA16), essentially links 16S sequence

string directly to GCN, without the construction of taxonomy or phylogeny. The

computational analysis revealed the success of the deep learning model built on 16S GCN

data retrieved from rrnDB (N = 19,520). The resulting deep learning model outperforms all

the major and state-of-the-art algorithms in the literature. Shapley Additive exPlanations

(SHAP) shows ANNA16 is capable of detecting informative positions and weighing K-mers

unequally according to their informativeness to more effectively utilize the information

contained in 16S sequence. For the accessibility of ANNA16, it will be released as a public,

an end-to-end, web-based tool that predicts copy number from 16S rRNA sequence.

1   INTRODUCTION

16S rRNA is the small subunit ribosomal RNA molecules of prokaryotic ribosomes. Since ribosome is a self-replicating system, 16S rRNA is readily isolated and its sequence changes slowly with time (Woese and Fox, 1977). This characteristic allows 16S rRNA to be highly conserved within species (STACKEBRANDT and GOEBEL, 1994) and the variance increases as inter-species relatedness decreases (Woese and Fox, 1977). Therefore, 16S rRNA is used to identity prokaryotes, or detect relatedness among distant species, through matching next-generation sequencing (NGS) data to reference database (Louca et al., 2018) such as RDP and SILVA. The relatedness may be represented as genetic distance among 16S rRNAs like mean nucleotide substitutions per site (Louca et al., 2018). This technique, named 16S rRNA metabarcoding, has been established as the gold standard to infer organismal phylogeny and microbial ecology for over 20 years (Woo et al., 2000).

One critical limitation of 16S rRNA metabarcoding is that NGS actually determines the proportion of 16S rRNA read counts, instead of cell counts. Because it is typical for prokaryotes to have more than one copy of the 16S rRNA gene, the proportion of 16S rRNA read counts (also called relative abundance) could not exactly reflect taxonomic composition of a microbial community (Angly et al., 2014). To represent the profile of a microbial community, the proportion of 16S rRNA read counts needs to be weighted by an inverse of 16S rRNA gene copy number (GCN). This step yields a corrected microbial composition as the community profile, which represents the proportion of cell counts of each lineage in the community (Angly et al., 2014). To calculate 16S GCN, scientists rely on experimental methods such as whole genome sequencing (Stoddard et al., 2015) or competitive PCR (Fogel et al., 1999). Nevertheless, experimental methods are usually costly or culture-dependent, and so far, only a limited number of species have GCN data. This situation catalyzes the development of bioinformatic tools that predict GCN of unmeasured species from measured species. Luckily, 16S GCN is correlated with relatedness across species (Angly et al., 2014, Kembel et al., 2012), which means 16S GCN variation is relatively low within species, but increases as relatedness decreases. This trait allow 16S GCN to be estimated from phylogeny or taxonomy (Kembel et

al., 2012). In fact, all current tools all rely on this kind of method (Angly et al., 2014, Louca et

al., 2018, Stoddard et al., 2015). Specifically, one correction tool could construct one taxonomy

or phylogenetic tree of the 16S sequence and estimate GCN of the unmeasured species from

its close measured relatives. For instance, rrnDB (Stoddard et al., 2015) is one well-established

tool which correct 16S GCN based on taxonomy. rrnDB calculates the mean 16S GCN of a

taxon from the means of its sub-taxa. CopyRighter (Angly et al., 2014) is one relatively novel

tool based on phylogeny. In addition to that, CopyRighter constructs a tree of 16S sequences,

and estimate GCN of each ancestral node from its daughter species (Angly et al., 2014),

weighted by the phylogenetic distance of each sequenced daughter species through

phylogenetic independent contrast (PIC) algorithm (Felsenstein, 1985).

Deep learning as a popular machine learning strategy comes with its potential of learning

complex patterns from biological sequencing data (Jurtz et al., 2017, Park and Kellis, 2015).

This aspect can be benefited as a novel approach for predicting 16S GCN. Deep learning is

essentially an Artificial Neural Network (ANN). The concept of ANN is inspired by the way

human brain learns and processes information through synaptic interactions between neurons

(Lancashire et al., 2009). An ANN is a computational model that is constituted by multiple

interconnected processing elements—artificial neurons (Lancashire et al., 2009). Neurons are

utilized in groups as the layers of a network. Each artificial neuron receives and processes input

with a non-linear function, known as the activation function (Schmidt and Hildebrandt, 2021).

Collectively, one ANN model learns to solve a specific task through capturing non-linear trends

and relationships from the presented data. Beyond these capabilities, ANN is even competent

to disclose relationships or mechanisms that are still unknown to scientists (Stepniewska-

Dziubinska et al., 2018). Deep learning gets its name by having more than one (hidden) layer

connecting the input and output units. Having deeper networks refer to representing complex

input-output relationships while accommodating large amount of data. In that sense, high-

dimensional biological data is a popular target for deep learning.

Recently, a broad spectrum of deep learning aproaches have been applied for microbiology

research. Various deep learning architectures like Convolutional Neural Network (CNN), and

Recurrent Neural Network (RNN), have been used for metagenomic-based taxonomy

classification (Fioravanti et al., 2018), host phenotype predication (Lo and Marculescu, 2019),

disease prediction (Wang et al., 2021), and microbial community predication (Zha et al., 2022).

Some other works focus on data mining for antibiotic resistance genes (Arango-Argoty et al.,

2018), antimicrobial peptides (Ma et al., 2022), microbial source (Chong et al., 2022), and raw

sequencing data (Zhao et al., 2021). All these applications show great potential of deep

Learning for microbial studies. With these present successes, it should be possible to estimate

GCN directly from 16S sequence through an ANN, without the construction of taxonomy or

phylogeny. To the best of our knowledge, there is not any deep learning-based method utilized

for the 16S rRNA-based copy number estimation.

This study undergoes three stages. In Stage 1, this study compares deep learning models

to taxonomy-based and phylogeny-based algorithms. Two ANNs are used to predict 16S rRNA

GCN from its sequence. One ANN is a classic Multi-layer Perceptron (MLP) while the other

one is a more advanced and complex Transformer architecture. These ANNs deliver superior

performance leading to the next stage. In Stage 2, a number of methods to make the deep

models compatible with different subregions of 16S rRNA, are investigated. Due to drawbacks

such as relatively high error rate or higher costs, at present it is less common for microbiologist

to sequence the full-length of 16S rRNA (Abellan-Schneyder et al., 2021). Full-length 16S

could be more commonly used only if new long sequencing methods are invented. Alternatively,

microbial studies tend to target the hypervariable regions in 16S rRNA. 16S rRNA contains

nine hypervariable regions, interspersed among conserved regions (V1-V9) (Woese et al.,

1990). Mostly, microbiologist sequence only one to three adjacent hypervariable regions by

NGS to study the microbial ecology (Abellan-Schneyder et al., 2021). This study focuses on

whether deep learning could have consistent performance on different combination of the

adjacent hypervariable regions in 16S rRNA. The performance of deep learning models on the

subregions are also compared with conventional algorithms to determine if deep learning could

outperform the latter ones. In Stage 3, a deep learning-based bioinformatic tool for 16S GCN

correction is developed. The tool is compared with existing correction tools to assess the

performance. One state-of-the-art method of model explanation is also adopted to uncover how

the deep learning model understand a 16S sequence.

Based on MLP model, the most accurate method, this study presents ANNA16 (Artificial

Neural Network Approximator for 16S rRNA Gene Copy Number), an end-to-end tool that

predicts copy number from 16S rRNA sequence.

2   MATERIALS AND METHODS

2.1.   Data Source and Preprocessing

16S rRNA sequences and GCN used to train deep learning models in this study is retrieved

from rrnDB, version 5.7 (Stoddard et al., 2015). In total, 20,277 16S genes with unique

accession number are included in the dataset, involving 1,443 genera. Average sequence length

is 1,537.32 nucleotides, with standard deviation of 31.98 nucleotides. Gene copy number

ranges from 1 copy per genome to 21 copies per genome, with mean value of 5.14 and standard

deviation of 2.77. This dataset is referred as preprocessed dataset in the following content. In

addition, to assess the performance of the deep learning-based correction tool developed in this

study, an independent dataset is prepared. This study retrieves 16S GCN data collected

independently by (Louca et al., 2018), and removes the overlap in Louca dataset with rrnDB

dataset. This yields an independent dataset of 40 sequences. This dataset is referred as

independent dataset in the following content.

Because raw 16S sequence data contains both (+) strand and (-) strand, bias may be caused

if the data is directly used for taxonomy-based and phylogeny-based algorithms. Therefore,

this study uses BLASTN algorithm in BLAST+ application, version 2.11.0 (24), with the first

50 nucleotides of *E. coli* 16S sequence (+) strand (accession number: GCF 002953035.1) being

the subject, to determine the orientation of each 16S sequence. The first 50 nucleotides of E.

coli belong to conserved region on 16S rRNA (Yarza et al., 2014), so it could serve as a template.

Returned HSPs with sstart > send and evalue < 0.01 are considered as (+) strand, and HSPs

with sstart < send and evalue < 0.01 are considered as (-) strand. Remaining sequences are

labelled as unrecognizable and dropped from dataset. Reverse complement of (-) strand

sequences are generated and added to (+) strands. In addition, 16S sequences in the dataset

have unidentical starting positions. To simulate NGS data of PCR amplicon, this study employs

HyperEx (Ebou et al., 2021), to extract full length sequence between primer 27F and primer

1492R (as listed in Table S1). This ensures all 16S sequences have uniform starting and ending

position. This preprocessing step yields a dataset of 19,520 sequences.

2.2.   Conventional Algorithms and Existing Tools

Sub-taxa averaging (TA) is one taxonomy-based algorithm. It is implemented to compare

with deep learning methods. The algorithm calculates the mean 16S GCN of a taxon from the

means of its sub-taxa. To implement this algorithm, 16S sequences are first input to

assignTaxonomy function in DADA2 package in R (version 1.21.0) (Callahan et al., 2016) and

yield three taxonomies, based on RDP (version 18, formatted by DADA2) (Cole et al., 2013),

SILVA (version 138.1, formatted by DADA2) (Quast et al., 2012), PR2 (version 4.14.0)

(Guillou et al., 2012) database respectively. The algorithm first receives taxonomy and GCN

from database and converts data structure of the taxonomy to an inheritance tree. In the tree,

every taxon is viewed as a node on the tree, and it computes the copy number of every node by

taking the mean of its sub-nodes. If an unknown query is given, it assigns the value of the

query's parent node to the query node as an estimation. This study also employs six phylogeny-

based algorithms to compare with deep learning methods: empirical probabilities (EP), subtree

averaging (SA), phylogenetic independent contrasts (PIC) (Felsenstein, 1985), Sankoff's

maximum-parsimony (MPR) (Sankoff, 1975), maximum-likelihood of fixed-rates continuous-

time Markovmodels (MK) (Pagel, 1994), and weighted-squared-change parsimony (WSCP)

(Maddison, 1991). To implement the algorithms, 16S sequences in dataset first undergoes

multiple sequence alignment by MAFFT v7.490 (Katoh et al., 2002), and is converted to

phylogenetic tree by FastTree 2.1.10 (Price et al., 2010). The algorithms are performed by

castor package in R (Louca and Doebeli, 2017), adjusted from the R script in Louca, Doebeli,

and Parfrey (2018) (Louca et al., 2018) (MK by function *hsp_mk_model*, MPR by function

hsp_max_parsimony, WSCP by function *hsp_squared_change_parsimony*, SA by function

hsp_subtree_averaging, EP by function *hsp_empirical_probabilities*, and PIC by

hsp_independent_contrasts). All functions are set on default parameters.

What is more, after the deep learning-based tool is developed, this study compares it with

two existing tools–rrnDB and CopyRighter–by applying the three tools to the independent

dataset. Because rrnDB and CopyRighter application will directly output microbial community

abundance instead of 16S GCN values, this study retrieves their precomputed tables (rrnDB

version 5.7) and predict GCN values by searching the precomputed tables for assigned lineages.

Taxonomy of full-length sequences and all subregion sequences are generated by

assignTaxonomy function in DADA2 package through RDP (version 18) and Greengenes

(version 13.8, formatted by DADA2) (DeSantis et al., 2006) database. The assigned RDP

lineages are searched in rrnDB precomputed table, and Greengenes lineages are searched in

CopyRighter precomputed table.

2.3.   Development of ANNA16

To build our own deep predictive models, we first implemented Multi-Layer Perceptron

and Transformer-based models on full-length DNA sequences in Figure 1 b). Sequences were

split into training and testing datasets by 3:1. The DNA sequences were preprocessed with K-

merization. After testing K from 3 to 7 on a three-layer MLP prototype model, we found that

the model performance would improve as K increased, but the requirement for memory size

would also expand sharply. Therefore, the value 6 appears to be the optimal length which

results in good performance and do not require extremely large memory size. 6-merization is

to decompose the DNA sequence into the set of sub-sequences of length 6. An example of a set

with three 6-mers is displayed in Figure 1 a). In MLP path, the K-mers are converted into the

number of counts in the set via scikit-learn module (version 0.23.2) CountVectorize function.

MLP takes the vector of occurrence counts and predict the gene copy number. In Transformer-

based path, K-mers are sorted by occurrence frequency in the set astoundingly and assigned

with integer values starting from 0. With a vector of integer values as input, the model then

predicts copy number. The performance of the two methods is compared with conventional

algorithms through a 5-fold cross-validation on full length DNA sequence, we selected MLP

for further training and predicting on hypervariable regions. Shapley Additive exPlanations

(SHAP) (Lundberg and Lee, 2017) is introduced here for post-hoc interpretability. The whole

study was conducted with Python 3.8 and Tensorflow 2.8.0 on Nividia RTX 3090.

2.3.1. Multi-layer Perceptron

MLP model is the most common form of ANN, in which artificial neurons are organized

into layers and the input is processed layer by layer (Lancashire et al., 2009). The calculation

of the output for each neuron is as follows (Lancashire et al., 2009):

$$v_k = \sum_{i=0}^{n} \omega_{k,i} x_i$$

$$\gamma_k = \varphi(v_k + v_{k_0})$$

where v_k is the net output of neuron k, with x_1, x_2, . . ., x_n being the input from the last

layer, and $\omega_{k,1}$, $\omega_{k,2}$, ..., $\omega_{k,n}$ being the weights on the input. γ_k is the output of the neuron,

where v_{k_0} represents the bias. In our case, $\varphi(.)$ refers to the rectified linear units (ReLU)

activation function. The model was trained with Rooted Mean Squared Error (RMSE) loss. We

performed hyper-parameter tuning on the number of dense layers, hidden layer size, and

learning rate. Layers of the model were tested in the range of [3,7], hidden layer size was

selected from the list of (128, 256, 512, 1024). Learning rate was tested from 0.001 to 0.002,

with 0.0002 being a step. The final architecture of MLP for full length DNA sequence is shown

in Figure 2 a). It contains a dense block of 6 layers with ReLU.

2.3.2. Transformer Encoder

For transformer-based model in Figure 2 b), we leveraged the original transformer encoder

architecture with cosine learning rate decay (Loshchilov and Hutter, 2016), followed by global

average pooling, and two dense layers. As shown in the Figure 2 c), the transformer encoder

takes embedding and position encoding as input. For biological sequences, a dense embedding

is considered more effective than sparse tokenization. Each sequence is thus represented as a

matrix $\mathbf{M} \in \mathbb{R}^{n \times d}$, by embedding each 6-mer into a numerical vector of dimension d via

embedding layer. Cosine positional encoded method are used to incorporate both absolute and

relative positional information by constructing the matrix **P** from **M** (40), where each position

has:

$$p(2k + 1, i) = \sin(i/1000^{2k/d})$$

$$p(2k + 2, i) = \cos(i/1000^{2k/d})$$

The encoder includes multi-head self-attention, position-wise feed-forward network,

residual connection, and layer normalization (Vaswani et al., 2017). With the combination of

these modules, the transformer encoder can process contextual information parallelly with

attention mechanism. For one single attention head, each token embedding e_i is taken as

query q_i to compute *scaled dot attention score* with all token embedding in the same input

sequence, i.e., $[e_1, e_2, ..., e_L]$, as key *k* and value *v*. Formally, the output of one attention head

is defined as follows:

$$\text{head}(\boldsymbol{q}_i, (\boldsymbol{k}_1, \boldsymbol{v}_1), ..., (\boldsymbol{k}_L, \boldsymbol{v}_L)) = \sum_{j=1}^{L} \alpha(\boldsymbol{q}_i, \boldsymbol{k}_j)\boldsymbol{v}_j$$

$$\alpha(\boldsymbol{q}_i, \boldsymbol{k}_j) = \text{softmax}(\frac{\boldsymbol{q}_i^T \boldsymbol{k}_j}{\sqrt{d}})$$

244   Thus, for the whole input sequence S, the attention score from multi-head mechanism is

$$\mathbf{M} = \text{Multihead}(S) = \text{Concat}(\text{head}_1, \text{head}_2, ..., \text{head}_n)\mathbf{W}$$

where all **W** parameters are learnable for linear transformation. By learning different linear

projection independently, it captures the combination of different representation subspaces.

The intermediate representation is passed into feed-forward network for further non-linear

transformation with ReLU activation. The Layer Normalization is used here to avoid gradient

explosion and accelerate convergence, and Dropout method to prevent over-fitting.

2.3.3.   Test of Deep Learning on Hypervariable Regions

According to Abellan-Schneyder et al. (2021) (Abellan-Schneyder et al., 2021), V1-V2,

V1-V3, V3-V4, V4, V4-V5, V6-V8, and V7-V9 are frequently targeted. This study uses

primers listed in Table S1 and HyperEx to extract these adjacent hypervariable regions from

preprocessed full-length dataset. To make deep learning model compatible with hypervariable

regions, this study test three methods to train the model. Method I extracts all nine

hypervariable regions from preprocessed full-length dataset separately with HyperEx based on

conserved markers proposed by Yang, Wang, and Qian (Yang et al., 2016), as listed in Table

S2. The markers were used as forward primers, and their reverse complements were used as

reverse primers. Extracted subregion sequences were added back to the dataset. This in fact

augments the dataset by 10 times. A new model on was trained on the augmented dataset.

Method II augments the preprocessed full-length dataset by non-overlap splitting each

sequence to fragments of 101 nucleotides. A new model will be trained on the augmented

dataset. Method III trains the model separately on the adjacent hypervariable regions. This will

produce customize models for each region. Hyperparameters of customized architecture is

shown in Table S4.

2.3.4. Case Study and Explainability

Based on the MLP method, this study presents ANNA16 (Artificial Neural Network

Approximator for 16S rRNA Gene Copy Number), an end-to-end tool that predicts copy

number from 16S rRNA sequence. In addition to independent dataset test, this study designs a

case study which simulates two mock communities in silico to demonstrate ANNA16's

performance. rrnDB and CopyRighter are also applied to estimate the mock communities'

microbial profile as a positive control. The simulated communities are two commercially

available mock communities, one even community (ATCC MSA-2003) and one staggered

community (ATCC MSA-1001). Such mock communities have been used by Moriya (2021) to

study methods of quantifying a microbial community (Moriya, 2021). Both mock communities

consist of similar 10 bacterial strains, but with different ratios. This study retrieves genome

sequences of the 10 strains from NCBI, copy number data from rrnDB (version 5.7), and

assigns a cell counts value to each strain by assuming each community have 1,000,000 cells.

Table S3 shows basic information of the mock communities. After genome sequences of the

ten strains are retrieved from NCBI, HyperEx is used to extract 16S full length sequence from

the genomes. The method is the same as described in the Data Source and Preprocessing and

Test of Deep Learning on Hypervariable Regions part.

SHAP (Lundberg and Lee, 2017) is used to further explain our model prediction. SHAP is

based on both collational game theory (Shapley, 1952) and the classical Shapley method

(Štrumbelj and Kononenko, 2014). It is a unified measure of feature importance that determines

the individual contribution of each feature to model prediction by viewing each feature as a

player in Shapley. The marginal contribution can be estimated under multiple feature subsets,

and the final contribution is the sum of all marginal contributions. A positive SHAP value

denotes that the feature contributes positively to the model's prediction over the model

expectation, whereas the negative value denotes that the feature contributes negatively. In this

study, each individual K-mer is considered as a feature. To calculate SHAP value for each K-

mer, the preprocessed dataset and ANNA16's pre-trained neural network are input to

shap.KernelExplainer function in shap module (Version 0.41.0) in Python. The function views

each prediction of every single sequence in the dataset as an independent game and calculates

SHAP values in each game. As a result, a list of 19,520 SHAP values will be assigned to every

K-mer to represent the K-mer's overall contribution. After SHAP values of K-mers are

calculated, the SHAP values are mapped back to 16S sequence to see if there is any positional

pattern in contribution. Each sequence is first transformed into an array of K-mers, and next

each K-mer is replaced by its corresponding SHAP value. As a result, the contribution of each

position in a sequence is represented as an array of SHAP values. What is more, to study the

relationship between contribution and nucleotide conservation in a position, information

content of each position is calculated. Information content is a measurement of the average

information available in a position, and it represents how conserved a position is if applied to

analyzed nucleotides (Schneider et al., 1986). This measurement has been widely used in

genetics, and one well-known application is to serve as the height of characters in sequence

logos (Schneider and Stephens, 1990). Previously aligned 16S sequences during

implementation of phylogeny-based algorithms are used to calculate information content. The

calculation is as follows:

$$H_i = -\sum f_{char,i} \times \log_2(f_{char,i}), char \in [A, T, C, G, -, N]$$

$$R'_i = \log_2(6) - H_i - (\frac{1}{\ln 2} \times \frac{s-1}{2n})$$

$$R_i = R'_i \times \sum f_{nt,i}, nt \in [A, T, C, G]$$

where H_i is the uncertainty of position i, f is the frequency of a character, $-$ represents gaps

generated in multiple sequence alignment, N = ambiguous nucleotides, $R_i{}'$ is information

content of all characters in position i, s is the number of characters (which is 6 in this

calculation), n is the number of sequences in alignment (which is 19520), R_i is the information

content of the four nucleotides, and nt represents nucleotides. R_i is used to represent degree of

conservation of the position i.

3   RESULTS

The first stage of this study tests two deep learning models against all other potential

algorithms for the task of 16S GCN correction. After tuning, the optimized hyperparameters of

MLP model are demonstrated in Table S4. MLP of full length comprises 7 layers, with 512

neurons on input layer and 1 on output layer. The model is trained with a batch size of 100, a

learning rate of 0.001 for 50 epoches. All algorithms implemented in this study undergo one 5-

fold cross-validation in Stage 1. The performance is measured in rooted mean squared error

(RMSE) as follows:

$$\text{RMSE} = \sqrt{\frac{\sum_{i=0}^{n}(Y_{true} - Y_{pred})^2}{n}}$$

where n is the size of input dataset, Y_{true} is the true value of copy number, Y_{pred} is the

value of predicted copy number.

Figure 3 and Table 1 summarize the results of 5-fold cross-validation. Sub-taxa averaging

based on PR2, RDP, and SILVA exhibit a mean RMSE of 1.26, 1.18, 1.20 copies/genome

respectively, with standard deviation of RMSE being 0.0597, 0.0356, and 0.0377. RDP proves

to be most accurate database for this task which leads to the lowest error range. Except that

MK shows particularly high RMSE (Mean = 5.76, SD = 0.112), all other phylogeny-based

algorithms perform better than sub-taxa averaging (EP: Mean = 0.845, SD = 0.0443; MPR:

Mean = 0.787, SD = 0.0375; PIC: Mean = 0.789, SD = 0.0243; SA: Mean = 0.774, SD = 0.0329;

WSCP: Mean = 0.775, SD = 0.0273). As shown in Figure 3, error range of all phylogeny-based

algorithms, except MK, is lower than those of taxonomy-based algorithms with no overlap.

With low rmse and small standard deviation, WSCP turns out to be the optimal phylogeny-

based algorithm. As for deep learning models, Transformer achieves a Mean RMSE of 0.861

copies/genome (SD = 0.0643). The error range is close to that of EP. MLP outperforms all other

algorithms with the lowest Mean RMSE (0.729 copies/genome) and a relatively small standard

deviation (0.0388). Its error range partially overlaps with WSCP, SA, PIC, MPR, and is the

lowest among all algorithms.

EP, MPR, PIC, SA, WSCP are selected as references in Stage 2 due to their relatively

superior performance. MLP is chosen between the deep learning models, and Method I, II, III

for subregions are applied to MLP. Table S5 shows the performance of Method I, II and III. It

can be seen that Method I and II performs significantly worse than Method III. Method III

achieves a maximum Mean RMSE of 0.8177 copies/genome at V4 region. However, the

minimum Mean RMSE of Method I and II is 1.034 and 1.257 copies/genome at V4 and V1-

V3 region respectively. Mean RMSE of Method I can even be as high as 4.272 copies/genome

at V6-V8 region, and Method II shows a maximum Mean RMSE of 2.239 copies/genome at

V7-V9 region. Therefore, Method I and II are abandoned and only the results of Method III are

compared with the selected phylogeny-based algorithms. Figure 4 illustrates prediction

produced by Method III in the first cycle of cross-validation. It can be seen that predicted values

possess a good linear relationship with true values. Predicted values and true values also have

similar patterns in data distribution. But one issue is that the models tend to make

underestimated prediction when true value > 12. This will be further discussed in the discussion

section. Figure 5 and Table 2 shows the performance of EP, MPR, PIC, SA, WSCP and MLP-

R (MLP by region, which is MLP on full length and MLP trained in Method III). Compared

with performance on 16 full length, all algorithms produce an increased Mean RMSE on

subregions. EP experiences the most significant increase, with Mean RMSE rising up to 0.9312

copies/genome on V7-V9 region. WSCP is the most stable phylogeny-based algorithm, with

Mean RMSE on subregions ranges from 0.7792 (V3-V4) to 0.8227 (V4) copies/genome. Mean

RMSE of MLP on subregions is relatively consistent, ranging from 0.7751 (V1-V3) to 0.8127

(V4) copies/genome. Notably, as shown in Figure 5, the error range of MLP on subregions is

lower than EP and MPR in almost all subregions, and partially lower than SA in V1-V2, V4-

V5 and V7-V9, but comparable to PIC or WSCP. This indicates the performance of MLP on

subregions is consistent with that on full length. Compared with phylogeny-based algorithms,

the performance is better than EP and MPR but indistinguishable with PIC and WSCP.

Figure 6, demonstrate the results of independent dataset test in Stage 3. Figure 6 shows

ANNA16 achieves the lowest RMSE among the three tools on full length and every subregion.

The smallest RMSE of MLP appears on full length, which is 0.7194 copies/genome, and the

highest RMSE is at V6-V8 region, being 0.8780 copies/genome. In contrast, the RMSE of

CopyRighter ranges from 1.382 (V1-V2) to 1.770 (V4) copies/genome, and rrnDB have a

stable RMSE between 1.10 and 1.20 copies/genome. Figure 7, Table S6, and Table S7 shows

uncorrected copy fraction, true cell fraction, and cell fraction (microbial profiles) estimated by

ANNA16, rrnDB (version 5.7), and CopyRighter. The different in uncorrected copy fraction

and true cell correction proves GCN correction is a necessary procedure if researchers aim to

present the accurate microbial profile. Cell fraction estimated by ANNA16 has most similar

patterns with true cell fraction compared to the counterpart of rrnDB and CopyRighter.

To illustrate how ANNA16 makes prediction, shap module in Python is used calculate

SHAP value of each K-mer. Figure S1 shows top 20 K-mers ranked by mean absolute SHAP

value. Figure 8 shows the distribution of SHAP values on the sequences and indicates that

ANNA16 does not simply extract information from hypervariable regions–conserved regions

also provide information. To further illustrate the relationship between SHAP value and

information content (degree of conservation), Figure 9 is drawn. Figure 9 plots mean absolute

SHAP value on each position versus degree of conservation of each position. Interestingly,

mean absolute SHAP value reaches the peak when degree of conservation is extremely low.

This will be further discussed in Discussion Section.

4   DISCUSSION

In summary, this study aims to use deep learning to predict 16S GCN based on 16S

sequence and consists of two stages: In Stage 1, two deep learning models, MLP and

transformer, are implemented and compared with conventional algorithms on 16S full length;

in Stage 2, sequences of different 16S subregions are generated to test if deep learning could

achieve a consistent performance on subregions; finally in Stage 3, ANNA16–a bioinformatic

tool based on MLP–is subsequently developed and compared to two existing 16S GCN

correction tools, rrnDB and CopyRighter, through a case study. SHAP method is used to

explain how MLP finishes the task.

First, the results in Stage 1 indicates MLP outperforms all other algorithms on 16S full

length. As shown in Figure 3, MLP exhibits an error range which is far lower than the error

ranges of sub-taxa averaging algorithms and considerably lower than phylogeny-based

algorithms. This indicates MLP is capable of more accurately correcting GCN than existing

algorithms if applied on 16S full length. Moreover, it is worth noting that the performance of

Transformer is unexpectedly inferior to that of MLP. As the computing cost of the self-attention

mechanism increases quadratically with sequence length, Transformer-based models are

typically incapable of modeling extended sequences (Beltagy et al., 2020). As a reference, in

natural language processing, classical models normally take inputs below 512 or 1024 (Devlin

et al., 2018). Given biological sequences are more complex than natural language and our input

length exceeds one thousand, it's plausible that Transformer-based model gives worse

performance. As MLP has simpler structure, faster inference speed, less computing

consumption, and satisfactory performance, we decided to use MLP for our final model and

other downstream tasks.

Second, Stage 2 proves ANNA16, as a state-of-the-art GCN correction tool, is more

accurate than rrnDB and CopyRighter. On the one hand, the advantage of MLP over rrnDB, is

clearly illustrated through cross-validation (Figure 3) or independent dataset test (Figure 6). It

could be safely concluded that ANNA16 turns out to be a more accurate than rrnDB. On the

other, though Figure 5 and Table 2 suggest MLP has a comparable performance to PIC (the

algorithm of CopyRighter), independent dataset test gives a different indication. As can be seen

in Figure 6, RMSE of CopyRighter is significantly higher than that of ANNA16 on all regions.

This suggests CopyRighter is actually less accurate than ANNA16. If this is the case, the

microbial profile of the two mock communities estimated by ANNA16 should be closer to true

profile than the counterpart presented by CopyRighter. Figure 7, Table S6, and Table S7

confirms this indication, where both true profiles are more similar to those presented by

ANNA16, especially for the staggered community. Independent dataset test and case study

collectively suggest ANNA16 is more accurate in 16S GCN prediction than CopyRighter. This

inconsistency in PIC and CopyRighter performance could be a result of CopyRighter's old

database. According to CopyRighter's GitHub Page, by the time this manuscript is written,

CopyRighter has not got any update for 9 years. This means the database of CopyRighter is

relatively small and out-of-date. If developers of CopyRighter could update the pre-computed

table of CopyRighter using enlarged 16S GCN dataset, its performance would probably

experience a promising improvement. But for the time being, ANNA16 turns out to be the most

accurate 16S GCN correction tool. In addition to its superior performance, another advantage

of ANNA16 is that it is taxonomy-independent. Current 16S GCN tools are dependent on pre-

computation and are bound to one specific ribosomoal database: rrnDB and CopyRighter pre-

compute the GCN value for every taxon in RDP database or Greengene database respective (4,

5). When a user submits a correction request, a pre-computed tool actually searches the input

lineages from the pre-computed GCN table, instead of computing the value from scratch. This

strategy means a pre-computed correction tool will be bound to its database. Due to the

existence of differences in nomenclature among databases (for example, SILVA merges

Allorhizobium, Neorhizobium, Pararhizobium, Rhizobium as one genus, named *Allorhizobium-*

Neorhizobium-Pararhizobium-Rhizobium, but in RDP these are separated genera), increased

error might be caused if a pre-computed tool is applied to a taxonomy generated by a

miscellaneous database. Table S8 shows the results when RDP taxonomy of preprocessed

dataset is applied to SILVA taxonomic tree, and vice versa. The RMSE will increase by 5.30%

and 4.00% respectively. On the contrary, the deep learning method implemented in this study

is free of the problem. Users could predict GCN of each 16S sequence and assign taxonomy

separately. This feature allows the deep learning method to cooperate with any 16S database in

microbial community composition analysis. After proving the supremacy of ANNA16, it

become an interesting question–how the model perceives the complex relationship between K-

mer counts and 16S GCN. Conventionally, microbiologists believe the nine hypervariable

regions are the most informative regions on 16S sequence that could reflect the phylogeny of

one species. Therefore, one hypothesis is that K-mers from hypervariable regions would

contribution more to prediction than those from conserved regions. However, Figure 8 shows

that distribution of SHAP values does not completely fit in the location of hypervariable regions.

Though high SHAP values indeed tend to aggregate in V2, V4, V6, and V8 region, conserved

regions between V2-V3, V4-V5, V8-V9 also contribute considerably. Since Figure 8 alone is

not evident enough to accept or reject the hypothesis, Figure 9 is drawn. By plotting

information content against mean absolute SHAP values on each position, we expect to see a

linear relationship. However, the scatters are actually L-shaped, with high SHAP value only

appearing on positions with extremely low information content. SHAP values is generally

constant on other positions. This trend indicates extremely variable positions or positions with

insertion of extremely low frequency are most informative for ANNA16. The other positions

provide nearly same level of information, no matter how conserved they are. Deducing from

this indication, this means ANNA16 is able to detect informative positions and assigning high

weights to the positions. This may help explain why ANNA16 or MLP has better performance

than conventional algorithms. When implementing conventional algorithms, variance in

sequence is converted to sequence similarity, and the sequence similarity is to generate

phylogeny or taxonomy. This approach in fact weighs every position equally. Therefore, it is

possible for informative positions to be underrepresented and non-informative region

overrepresented in conventional algorithms. However, by weighing K-mers unequally

according to their informativeness, ANNA16 could overcome this problem and utilize the

information contained in 16S sequence more effectively. This finding reveals the great potential

of deep learning in genetics. On the one hand, deep learning could accurately predict a trait

based on sequencing data. On the other hand, by investigating contribution of each feature,

scientists could discover which genes or loci are most related with the trait.

One limitation of ANNA16 is underestimation of species with high GCN. As can be seen

in Figure 4, ANNA16 would make underestimated prediction when true GCN $\geq$ 14 and those

predicted values can be far from true values. This limitation could be attributed to unbalance

in the dataset. Figure S2 shows the distribution of GCN in the preprocessed dataset. Sequences

with GCN $\geq$ 12 accounts for only a small proportion of the whole dataset, and sequences with

GCN > 15 is extremely rare. This makes it difficult for the model to learn features of high GCN.

The most effective method to solve this problem is to wait for increase of data. Thanks to

invention of new sequencing techniques, nowadays genomic data is accumulating at an

exponential rate (Navarro et al., 2019). If more data about high GCN species could be collected,

the underestimation would be correspondingly relieved.

CONFLICT OF INTEREST STATEMENT

The authors declare that the research was conducted in the absence of any commercial or

financial relationships that could be construed as a potential conflict of interest.

AUTHOR CONTRIBUTIONS

J.M. conceived the study. J.M. and T.C. analyzed the data and implemented the models. Y.L.

and M.M. provided mentorship for the study. All authors contributed to manuscript writing.

FUNDING

This work was supported by Duke Kunshan University (DKU) Summer Research Scholars

program and startup funds to Y.L. and M.M..

ACKNOWLEDGMENTS

The authors would like to thank Dr. Long Jiang for kind comments on algorithm design.

DATA AVAILABILITY STATEMENT

508 16S rRNA sequence and GCN data analyzed during the current study are available in the rrnDB

509 repository (https://rrndb.umms.med.umich.edu/).

510 Scripts needed to implement ANNA16 are available on

511 https://github.com/Merlinaphist/Anna16. We will soon release a notebook on Colab.

REFERENCES

ABELLAN-SCHNEYDER, I., MATCHADO, M. S., REITMEIER, S., SOMMER, A., SEWALD, Z., BAUMBACH, J., LIST, M. & NEUHAUS, K. 2021. Primer, Pipelines, Parameters: Issues in 16S rRNA Gene Sequencing. *mSphere,* 6.

ANGLY, F. E., DENNIS, P. G., SKARSHEWSKI, A., VANWONTERGHEM, I., HUGENHOLTZ, P. & TYSON, G. W. 2014. CopyRighter: a rapid tool for improving the accuracy of microbial community profiles through lineage-specific gene copy number correction. *Microbiome,* 2**,** 11.

ARANGO-ARGOTY, G., GARNER, E., PRUDEN, A., HEATH, L. S., VIKESLAND, P. & ZHANG, L. 2018. DeepARG: a deep learning approach for predicting antibiotic resistance genes from metagenomic data. *Microbiome,* 6**,** 23.

BELTAGY, I., PETERS, M. E. & COHAN, A. 2020. Longformer: The long-document transformer. *arXiv preprint arXiv:2004. 05150.*

CALLAHAN, B. J., MCMURDIE, P. J., ROSEN, M. J., HAN, A. W., JOHNSON, A. J. & HOLMES, S. P. 2016. DADA2: High-resolution sample inference from Illumina amplicon data. *Nat Methods,* 13**,** 581-3.

CHONG, H., ZHA, Y., YU, Q., CHENG, M., XIONG, G., WANG, N., HUANG, X., HUANG, S., SUN, C., WU, S., CHEN, W.-H., COELHO, L. P. & NING, K. 2022. EXPERT: transfer learning-enabled context-aware microbial community classification. *Briefings in Bioinformatics***,** bbac396.

COLE, J. R., WANG, Q., FISH, J. A., CHAI, B., MCGARRELL, D. M., SUN, Y., BROWN, C. T., PORRAS-ALFARO, A., KUSKE, C. R. & TIEDJE, J. M. 2013. Ribosomal Database Project: data and tools for high throughput rRNA analysis. *Nucleic Acids Research,* 42**,** D633-D642.

DESANTIS, T. Z., HUGENHOLTZ, P., LARSEN, N., ROJAS, M., BRODIE, E. L., KELLER, K., HUBER, T., DALEVI, D., HU, P. & ANDERSEN, G. L. 2006. Greengenes, a chimera-checked 16S rRNA gene database and workbench compatible with ARB. *Appl Environ Microbiol,* 72**,** 5069-72.

DEVLIN, J., CHANG, M.-W., LEE, K. & TOUTANOVA, K. 2018. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810. 04805.*

EBOU, A., KOUA, D. & ZEZE, A. 2021. HyperEx: A Tool to Extract Hypervariable Regions from 16S rRNA Sequencing Data. *bioRxiv***,** 2021.09.03.455391.

FELSENSTEIN, J. 1985. Phylogenies and the Comparative Method. *The American Naturalist,* 125**,** 1-15.

FIORAVANTI, D., GIARRATANO, Y., MAGGIO, V., AGOSTINELLI, C., CHIERICI, M., JURMAN, G. & FURLANELLO, C. 2018. Phylogenetic convolutional neural networks in metagenomics. *BMC Bioinformatics,* 19**,** 49.

FOGEL, G. B., COLLINS, C. R., LI, J. & BRUNK, C. F. 1999. Mini-Review Article: Prokaryotic Genome Size and SSU rDNA Copy Number: Estimation of Microbial Relative Abundance from a Mixed Population. *Microbial Ecology,* 38**,** 93-113.

GUILLOU, L., BACHAR, D., AUDIC, S., BASS, D., BERNEY, C., BITTNER, L., BOUTTE, C., BURGAUD, G., DE VARGAS, C., DECELLE, J., DEL CAMPO, J., DOLAN, J. R., DUNTHORN, M., EDVARDSEN, B., HOLZMANN, M., KOOISTRA, W. H. C. F., LARA, E., LE BESCOT, N., LOGARES, R., MAHÉ, F., MASSANA, R., MONTRESOR, M., MORARD, R., NOT, F., PAWLOWSKI, J., PROBERT, I., SAUVADET, A.-L., SIANO, R., STOECK, T., VAULOT, D., ZIMMERMANN, P. & CHRISTEN, R. 2012. The Protist Ribosomal Reference database (PR2): a catalog of unicellular eukaryote Small Sub-Unit rRNA sequences with curated taxonomy. *Nucleic Acids Research,* 41**,** D597-D604.

JURTZ, V. I., JOHANSEN, A. R., NIELSEN, M., ALMAGRO ARMENTEROS, J. J., NIELSEN, H., SØNDERBY, C. K., WINTHER, O. & SØNDERBY, S. K. 2017. An introduction to deep learning on biological sequence data: examples and solutions. *Bioinformatics,* 33**,** 3685-3690.

KATOH, K., MISAWA, K., KUMA, K. I. & MIYATA, T. 2002. MAFFT: a novel method for rapid multiple sequence alignment based on fast Fourier transform. *Nucleic Acids Research,* 30**,** 3059-3066.

KEMBEL, S. W., WU, M., EISEN, J. A. & GREEN, J. L. 2012. Incorporating 16S Gene Copy Number Information Improves Estimates of Microbial Diversity and Abundance. *PLOS Computational Biology,* 8**,** e1002743.

LANCASHIRE, L. J., LEMETRE, C. & BALL, G. R. 2009. An introduction to artificial neural networks in bioinformatics—application to complex microarray and mass spectrometry datasets in cancer studies. *Briefings in Bioinformatics,* 10**,** 315-329.

LO, C. & MARCULESCU, R. 2019. MetaNN: accurate classification of host phenotypes from metagenomic data using neural networks. *BMC Bioinformatics,* 20**,** 314.

LOSHCHILOV, I. & HUTTER, F. 2016. SGDR: Stochastic Gradient Descent with Restarts. *CoRR,* abs/1608.03983.

LOUCA, S. & DOEBELI, M. 2017. Efficient comparative phylogenetics on large trees. *Bioinformatics,* 34**,** 1053-1055.

LOUCA, S., DOEBELI, M. & PARFREY, L. W. 2018. Correcting for 16S rRNA gene copy numbers in microbiome surveys remains an unsolved problem. *Microbiome,* 6**,** 41.

LUNDBERG, S. M. & LEE, S.-I. 2017. A Unified Approach to Interpreting Model Predictions. *In:* GUYON, I., LUXBURG, U. V., BENGIO, S., WALLACH, H., FERGUS, R., VISHWANATHAN, S. & GARNETT, R. (eds.) *Advances in Neural Information Processing Systems.* Curran Associates, Inc.

MA, Y., GUO, Z., XIA, B., ZHANG, Y., LIU, X., YU, Y., TANG, N., TONG, X., WANG, M., YE, X., FENG, J., CHEN, Y. & WANG, J. 2022. Identification of antimicrobial peptides from the human gut microbiome using deep learning. *Nature Biotechnology,* 40**,** 921-931.

MADDISON, W. P. 1991. Squared-Change Parsimony Reconstructions of Ancestral States for Continuous-Valued Characters on a Phylogenetic Tree. *Systematic Zoology,* 40**,** 304-314.

MORIYA, S. 2021. Simple mapping-based quantification of a mock microbial community
using total RNA-seq data. *PLoS One,* 16**,** e0254556.
NAVARRO, F. C. P., MOHSEN, H., YAN, C., LI, S., GU, M., MEYERSON, W. & GERSTEIN,
M. 2019. Genomics and data science: an application within an umbrella. *Genome
Biology,* 20**,** 109.
PAGEL, M. 1994. Detecting correlated evolution on phylogenies: a general method for the
comparative analysis of discrete characters. *Proceedings of the Royal Society of London.
Series B: Biological Sciences,* 255**,** 37-45.
PARK, Y. & KELLIS, M. 2015. Deep learning for regulatory genomics. *Nature Biotechnology,*
33**,** 825-826.
PRICE, M. N., DEHAL, P. S. & ARKIN, A. P. 2010. FastTree 2 – Approximately Maximum-
Likelihood Trees for Large Alignments. *PLOS ONE,* 5**,** e9490.
QUAST, C., PRUESSE, E., YILMAZ, P., GERKEN, J., SCHWEER, T., YARZA, P., PEPLIES,
J. & GLÖCKNER, F. O. 2012. The SILVA ribosomal RNA gene database project:
improved data processing and web-based tools. *Nucleic Acids Research,* 41**,** D590-
D596.
SANKOFF, D. 1975. Minimal Mutation Trees of Sequences. *SIAM Journal on Applied
Mathematics,* 28**,** 35-42.
SCHMIDT, B. & HILDEBRANDT, A. 2021. Deep learning in next-generation sequencing.
Drug discovery today, 26**,** 173-180.
SCHNEIDER, T. D. & STEPHENS, R. M. 1990. Sequence logos: a new way to display
consensus sequences. *Nucleic Acids Res,* 18**,** 6097-100.
SCHNEIDER, T. D., STORMO, G. D., GOLD, L. & EHRENFEUCHT, A. 1986. Information
content of binding sites on nucleotide sequences. *J Mol Biol,* 188**,** 415-31.
SHAPLEY, L. S. 1952. *A Value for N-Person Games,* Santa Monica, CA, RAND Corporation.
STACKEBRANDT, E. & GOEBEL, B. M. 1994. Taxonomic Note: A Place for DNA-DNA
Reassociation and 16S rRNA Sequence Analysis in the Present Species Definition in
Bacteriology. *International Journal of Systematic and Evolutionary Microbiology,* 44**,**
846-849.
STEPNIEWSKA-DZIUBINSKA, M. M., ZIELENKIEWICZ, P. & SIEDLECKI, P. 2018.
Development and evaluation of a deep learning model for protein–ligand binding
affinity prediction. *Bioinformatics,* 34**,** 3666-3674.
STODDARD, S. F., SMITH, B. J., HEIN, R., ROLLER, B. R. & SCHMIDT, T. M. 2015.
rrnDB: improved tools for interpreting rRNA gene abundance in bacteria and archaea
and a new foundation for future development. *Nucleic Acids Res,* 43**,** D593-8.
ŠTRUMBELJ, E. & KONONENKO, I. 2014. Explaining prediction models and individual
predictions with feature contributions. *Knowledge and Information Systems,* 41**,** 647-
665.
VASWANI, A., SHAZEER, N., PARMAR, N., USZKOREIT, J., JONES, L., GOMEZ, A. N.,
KAISER, L. & POLOSUKHIN, I. 2017. Attention Is All You Need. *CoRR,*
abs/1706.03762.

WANG, Y., BHATTACHARYA, T., JIANG, Y., QIN, X., WANG, Y., LIU, Y., SAYKIN, A. J.
& CHEN, L. 2021. A novel deep learning method for predictive modeling of
microbiome data. *Brief Bioinform,* 22.
WOESE, C. R. & FOX, G. E. 1977. Phylogenetic structure of the prokaryotic domain: the
primary kingdoms. *Proceedings of the National Academy of Sciences of the United*
States of America, 74**,** 5088-5090.
WOESE, C. R., KANDLER, O. & WHEELIS, M. L. 1990. Towards a natural system of
organisms: proposal for the domains Archaea, Bacteria, and Eucarya. *Proc Natl Acad*
Sci U S A, 87**,** 4576-9.
WOO, P. C., LEUNG, P. K., LEUNG, K. W. & YUEN, K. Y. 2000. Identification by 16S
ribosomal RNA gene sequencing of an Enterobacteriaceae species from a bone marrow
transplant recipient. *Mol Pathol,* 53**,** 211-5.
YANG, B., WANG, Y. & QIAN, P. Y. 2016. Sensitivity and correlation of hypervariable regions
in 16S rRNA genes in phylogenetic analysis. *BMC Bioinformatics,* 17**,** 135.
YARZA, P., YILMAZ, P., PRUESSE, E., GLÖCKNER, F. O., LUDWIG, W., SCHLEIFER,
K.-H., WHITMAN, W. B., EUZÉBY, J., AMANN, R. & ROSSELLÓ-MÓRA, R. 2014.
Uniting the classification of cultured and uncultured bacteria and archaea using 16S
rRNA gene sequences. *Nature Reviews Microbiology,* 12**,** 635-645.
ZHA, Y., CHONG, H., QIU, H., KANG, K., DUN, Y., CHEN, Z., CUI, X. & NING, K. 2022.
Ontology-aware deep learning enables ultrafast and interpretable source tracking
among sub-million microbial community samples from hundreds of niches. *Genome*
Medicine, 14**,** 43.
ZHAO, Z., WOLOSZYNEK, S., AGBAVOR, F., MELL, J. C., SOKHANSANJ, B. A. &
ROSEN, G. L. 2021. Learning, visualizing and exploring 16S rRNA structure using an
attention-based deep neural network. *PLoS computational biology* [Online], 17.
Available: http://europepmc.org/abstract/MED/34550967 [Accessed 2021/09//].

TABLES

Table 1. Performance of all algorithms.

Algorithm Category	Model	SD	Mean RMSE
Phylogeny-based	EP	0.0443	0.845
	MK	0.112	5.76
	MPR	0.0375	0.787
	PIC	0.0243	0.789
	SA	0.0329	0.774
	WSCP	0.0273	0.775
Taxonomy-based	PR2+TA	0.0597	1.26
	RDP+TA	0.0356	1.18
	SILVA+TA	0.0377	1.20
Deep Learning	Transformer	0.0643	0.861
	MLP	0.0388	0.729

MK: maximum-likelihood of fixed-rates continuous-time Markov models; EP: empirical

probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent contrast;

SA: Subtree Averaging; WSCP: weighted-squared-change parsimony; RDP+TA: sub-taxa

averaging based on RDP database; SILVA+TA: sub-taxa averaging based on SILVA database;

PR2+TA: sub-taxa averaging based on PR2 database; MLP: multi-layer perceptron model;

Transformer: Transformer model.

Table 2. Performance of selected algorithms on 16S subregions.

Region	Model	SD	Mean RMSE
V1-V2	MLP-R	0.02367864	0.7978728
	EP	0.03312260	0.9276227
	MPR	0.03703488	0.8670806
	PIC	0.02811679	0.8095574
	SA	0.03205930	0.8288667
	WSCP	0.02420925	0.7927451
V1-V3	MLP-R	0.02417787	0.7751063
	EP	0.04763446	0.8889738
	MPR	0.03050384	0.8363964
	PIC	0.03068616	0.8051317
	SA	0.04302227	0.8050986
	WSCP	0.03299523	0.7824740
V3-V4	MLP-R	0.04929372	0.7811680
	EP	0.04471593	0.9018608
	MPR	0.04769014	0.8583522
	PIC	0.05032324	0.7894828
	SA	0.03785498	0.8111553
	WSCP	0.04830682	0.7791547
V4	MLP-R	0.03688014	0.8127494
	EP	0.05693514	0.9160779
	MPR	0.04745741	0.8791149
	PIC	0.03767273	0.8238156
	SA	0.03875001	0.8218996
	WSCP	0.04046582	0.8226994
V4-V5	MLP-R	0.03665258	0.7887458
	EP	0.03397454	0.9089205

	MPR	0.04128272	0.8579178
	PIC	0.02769405	0.7847597
	SA	0.02830729	0.8101834
	WSCP	0.03535666	0.7847232
V6-V8	MLP-R	0.03607741	0.7850310
	EP	0.05631475	0.9086637
	MPR	0.03998800	0.8523850
	PIC	0.04035999	0.7812806
	SA	0.03908318	0.8072924
	WSCP	0.03771673	0.7794703
V7-V9	MLP-R	0.03250365	0.7937580
	EP	0.03535698	0.9311839
	MPR	0.03702084	0.8464945
	PIC	0.03925002	0.8019705
	SA	0.03337741	0.8304700
	WSCP	0.03747741	0.7896712

675   EP: empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic

676   independent contrast; SA: Subtree Averaging; WSCP: weighted-squared-change parsimony;

677   MLP-R: multi-layer perceptron model by region.

679 **FIGURES**

a) Illustration of K-merization

b) Framework of Designing ANNA16

681 **Figure 1.** (a) K-mer strategy (K = 6). (b) Workflow of proposed MLP model.

a) Architecture of Multi-Layer Perceptron Model for
Full Length 16s DNA Sequences

c) Architecture of Transformer Encoder

b) Architecture of Transformer-based Model
for Full Length 16s DNA Sequences

684 **Figure 2.** Illustration of Architecture of Deep Learning Models.

Figure 3. Performance of all algorithms or models. MK: maximum-likelihood of fixed-rates

continuous- time Markov models; EP: empirical probabilities; MPR: Sankoff's maximum-

parsimony; PIC: phylogenetic independent contrast; SA: Subtree Averaging; WSCP: weighted-

squared-change parsimony; RDP+TA: sub-taxa averaging based on RDP database; SILVA+TA:

sub-taxa averaging based on SILVA database; PR2+TA: sub-taxa averaging based on PR2

database; MLP: multi-layer perceptron model; Transformer: Transformer model. The top panel

exhibits a global view from 0 to 6 copies/genome, and the bottom panel is a zoom-in view from

0.5 to 1.5 copies/genome.

697 **Figure 4.** Prediction by MLP on 16S full length and subregions in the first cycle of 5-fold

698 cross-validation. The red line is a diagonal line for illustrating how much predicted values

699 derive from true values. The density plot filled in violet shows the distribution of true values,

700 and the green density plot shows the distribution of predicted values.

Figure 5. Performance of selected algorithms or models on 16S full length and subregions. EP:

empirical probabilities; MPR: Sankoff's maximum-parsimony; PIC: phylogenetic independent

contrast; SA: Subtree Averaging; WSCP: weighted-squared-change parsimony; MLP-R: multi-

layer perceptron model by regions

Figure 6. Comparison of performance on independent dataset among CopyRighter, rrnDB,

and ANNA16

711 **Figure 7.** Uncorrected copy fraction, true cell fraction, and cell fraction (microbial profiles)

712 estimated by ANNA16, rrnDB (version 5.7), and CopyRighter. Uncorrected: Uncorrected

713 copy fraction; True: True cell fraction; ANNA16: Cell fraction estimated by ANNA16;

714 rrnDB5.7: Cell fraction estimated by rrnDB (version 5.7); CopyRighter: Cell fraction

715 estimated by CopyRighter.

Figure 8. Distribution of SHAP values on 16S full length sequences. To make the figure

interpretable, only the value of top 100 K-mers ranked by mean absolute SHAP value is

shown. Hypervariable regionsare labelled as grey shadows. To determine the range of

hypervariable regions, sequence of conserved regions of E. coli is first extracted according to

region coordinates provided by Yarza et al. (Yarza et al., 2014). All sequences in the

preprocessed dataset undergo BLASTN (version 2.11.0) against E. coli conserved sequences

to determine the range of conserved regions in each sequence. Range of hypervariable

regions is thus deduced from conserved regions. To make the figure less complicated, only

5,000 randomly chosen sequences are labelled. V-region labels on x-axis shows the general

position of *E. coli* V-regions according to coordinates from Yarza et al. (Yarza et al., 2014).

730 **Figure 9.** Relationship of mean absolute SHAP values and information content (unit: bits) on

731 each position of aligned 16S full length sequence.