PhosphoLingo: protein language models for phosphorylation site prediction

Jasper Zuallaert[1,2], Pathmanaban Ramasamy[1,2], Robbin Bouwmeester[1,2], Nico Callewaert[1,3], Sven Degroeve[1,2]

[1]VIB-UGent Center for Medical Biotechnology, VIB, Ghent, Belgium; [2]Department of Biomolecular Medicine, Faculty of Medicine and Health Sciences, Ghent University, Ghent, Belgium; [3]Department of Biochemistry and Microbiology, Faculty of Sciences, Ghent University, Ghent, Belgium

Abstract

Motivation: With a regulatory impact on numerous biological processes, protein phosphorylation is one of the most studied post-translational modifications. Effective computational methods that provide a sequence-based prediction of probable phosphorylation sites are desirable to guide functional experiments or constrain search spaces for proteomics-based experimental pipelines. Currently, the most successful methods train deep learning models on amino acid composition representations. However, recently proposed protein language models provide enriched sequence representations that may contain higher-level pattern information on which more performant phosphorylation site predictions may be based.

Results: We explored the applicability of protein language models to general phosphorylation site prediction. We found that training prediction models on top of protein language models yield a relative improvement of between 13.4% and 63.3% in terms of area under the precision-recall curve over the state-of-the-art predictors. Advanced model interpretation and model transferability experiments reveal that across models, protease-specific cleavage patterns give rise to a protease-specific training bias that results in an overly optimistic estimation of phosphorylation site prediction performance, an important caveat in the application of advanced machine learning approaches to protein modification prediction based on proteomics data.

Availability and implementation: PhosphoLingo code, datasets, and predictions are available at https://github.com/jasperzuallaert/PhosphoLingo.

Contact: jasper.zuallaert@vib-ugent.be, sven_degroeve@vib-ugent.be

Supplementary information: Supplementary materials are available at *bioRxiv*

1. Introduction

A post-translational modification (PTM) is a covalent and generally enzymatic modification of a protein following protein biosynthesis. The most frequently studied PTM is phosphorylation[1]. During phosphorylation, phosphate groups are transferred by enzymes from adenosine triphosphate to specific residues in a protein sequence, with serine, threonine or tyrosine residues being the most common targets. Kinases and phosphatases are involved in virtually all biological processes by targeting specific sites for modification.

The substrate preferences of kinases depend on the structural and physicochemical properties of the target substrate. Phosphorylation sites (from here onward referred to as P-sites) are most found at accessible and disordered regions of a protein[2]. In addition, the amino acid sequence and structure at the P-site are important, with for example proline-directed kinases predominantly targeting S/T residues with a neighbouring proline downstream.[3]

Proteome-wide analysis of protein phosphorylation is currently accomplished through liquid chromatography-mass spectrometry (LC-MS) experiments[4–6]. Herein, proteins are digested into peptides with a protease that cleaves the sequence at specific sites. Typically, trypsin is used, which cleaves proteins after arginine and lysine residues. This results in a positive charge at the peptide C-terminal side-chain, which is advantageous for MS and MS/MS analysis. Alternative proteases that cleave at other residues[4] are applied to increase the proportion of a proteome that can be analysed using LC-MS, which has limitations with regard to peptide length, charge states, etc.

High-throughput LC-MS comes with its limitations, as it requires expensive and laborious analysis processes using expensive specialized equipment, and it does not at all guarantee the detection of all P-sites in a proteome. In fact, sample preparation and LC-MS workflows introduce biases in terms of which P-sites are detected, which are poorly characterized. Sensitive and accurate *in-silico* P-site predictions complement LC-MS analysis, helping in down-stream MS data interpretation and further guide *in-vitro* and *in-vivo* experiments[7].

Most P-site prediction approaches use neighbouring sequence data to train machine learning models to predict which serine (S), threonine (T) or tyrosine (Y) residues are likely to be phosphorylated[7–26]. In addition to general P-site prediction, some approaches also include kinase family-specific or kinase-specific predictions[8,11,12,14,16,17,20–22,24]. Over the last two decades, different machine learning algorithms have been applied, such as random forests[9,13,23], support vector machines[8,15,23], and gradient boosting trees[8]. These classical approaches require numerical feature vector representations engineered from the amino acids surrounding a candidate P-site, which we will refer to as the receptive field. Manually crafted input features for phosphorylation prediction models include physicochemical properties[13,15,20,25], information theory features[15,17,28], as well as additional information such as structural features (e.g., secondary structure)[9,15,23], functional features[9,23], and protein-protein interactions[16,24].

Recently, deep learning based model architectures such as convolutional neural networks (CNNs)[12,16–19,21,25] and long short-term memory networks (LSTMs)[19,25] have been shown to advance P-site prediction. These models learn low-level feature representations from the

sequence input data during training, alleviating the need for preliminary manual feature
engineering.

In recent years, the success of language models in the natural language processing domain[27]
have inspired the advent of protein language models (PLMs). PLMs are pre-trained models
that yield enriched, structure-aware sequence representations, instead of merely encoding
the amino acid composition of a receptive field in a protein[28–32]. They have demonstrated
value in various tasks, such as few-shot contact map prediction[33], zero-shot mutation impact
prediction[34], or phylogenetic relationship modelling[35].

In this paper, we investigate whether the enhanced information content of different PLM
representations contributes to the prediction of P-sites and extensively compare the resulting
prediction models to the standard one-hot encoding-based representations, as well as to the
publicly available state-of-the-art implementations. Our results show that PLM
representations contain information that is highly relevant for P-site prediction, thereby
substantially increasing prediction performance. Furthermore, we applied model
interpretation methods to visualize what information was considered relevant for the
prediction of P-sites. Model interpretation reveals that these, in addition to local and global
sequence patterns, also exploit specific LC-MS protease patterns that can result in overly
optimistic prediction performance estimations. To restrain this prediction bias, we provide an
accurate PLM-based P-site predictor that is trained on a large multi-source P-site dataset, also
including data from individual protease experiments.

94 2. Methods

95 All proposed predictors consist of two main components: a representation of the receptive
96 field in the protein and a neural network that takes this representation as input. This section
97 introduces the considered representations, the neural network models, the benchmark
98 methods, and the methods to interpret the predictions computed by these models.

99 2.1 Protein representations

100 As a baseline, the receptive field was represented as a one-hot encoding of the amino acids,
101 i.e., no PLM was used. Then, multiple PLMs were considered in this study: the smallest model
102 ESM-1$_{small}$ has 43 million parameters, the larger model ESM-1b has 650 million parameters,
103 and the largest model ProtT5-XL-U50 has three billion parameters[30,31] (Suppl. Table 1).

104 2.2 Neural network architectures

We evaluated two types of architectures on top of the protein representations:

(a) A simple dense layer (i.e., a logistic regression model), with a receptive field of 1. This
means that it will only make use of the individual amino acid representation of the
candidate P-site. We refer to this setup as the **_linear_** setup.
(b) A CNN with a receptive field that is predetermined in a hyperparameter search. The
same architectural blueprint is used throughout the experiments. As shown in Figure
1, it contains a series of convolutional blocks, with each convolutional block consisting
of a convolutional layer followed by a regularization layer (either dropout or batch
normalization), and finally a max pooling layer. The resulting activations are flattened,

after which a fully-connected, a regularization layer, and an output layer are added.
Furthermore, all convolutional and fully-connected layers are followed by a rectified
linear unit (ReLU), and a sigmoid is added at the end to provide probabilities in output.
If only the CNN is trained, with the weights of the PLM fixed, we refer to this setup as
the *conv* setup. If we allow for simultaneous fine-tuning of the PLM, we refer to it as
the *full* setup.

The default one-hot encoded setup, as well as the three PLM based setups are schematically
depicted in Suppl. Figs. 1-4. Furthermore, an extensive overview of hyperparameters and
their ranges is given in Suppl. Table 2.

Figure 1. The CNN blueprint, highlighting the different components that are used throughout this study.

125 2.3 Benchmark methods
To evaluate the performance of the PLM-based predictors, we compare them to a one-hot
encoded baseline, and to three state-of-the-art predictors: MusiteDeep[17], DeepPhos[18], and
DeepPSP[12]. Code from their respective GitHub repositories was used to train their predictors
from scratch on different data sources.

MusiteDeep implements two prediction modules: a CNN module enhanced with attention
layers, and a capsule network module with dynamic routing, both built on a one-hot
encoding with a receptive field of size 33 centered around the candidate P-site. Predicted
probabilities for both modules are averaged to obtain the final P-site predictions.

In DeepPhos, three different densely connected CNN blocks are used with one-hot encoded
inputs with receptive fields of size 15, 31 and 51, where each block consists of convolutional
and intra-block concatenation layers. Blocks are combined using an inter-block
concatenation layer, followed by a final fully connected layer.

Finally, DeepPSP uses two modules, each consisting of a convolutional block, a squeeze-and-
excitation network, a bidirectional LSTM layer, and fully connected layers. The local module
takes a one-hot encoding with a receptive field of length 51 in input, centered around the
candidate P-site, while the global module uses a receptive field of length 2000 in input.
Outputs of both modules are combined using a final fully connected layer.

143 2.4 Feature importance visualization
The fitted models are interpreted by applying SHapley Additive exPlanations[36] (SHAP) to
compute importance scores for individual residues in the receptive field that estimate their
contribution to the predicted probability of a candidate P-site in an independent dataset not
used during training.

Importance scores are calculated using the DeepLiftSHAP implementation in the Captum[37]
software package, at the protein representation level. SHAP values are computed relative to
a reference baseline. For one-hot encoded models, an all-zero reference is used. For the PLM
based representations, an average embedding baseline is constructed for each protein
fragment. SHAP values are normalized on a dataset level, such that the absolute values of all
importance scores in one sequence add up to 100 on average.

The importance scores, also referred to as saliency maps, are computed on an individual base
per candidate P-site. These maps are then aggregated into an average saliency map that we
visualize as a sequence logo centered around the candidate P-site, cropped to contain ten
positions both up- and downstream.

3. Experimental Setup

3.1 Data

Prediction models were trained and evaluated on datasets that were compiled from three
sources. The *Guo21* data was employed in previous P-site prediction research and was
downloaded from the DeepPSP[12] GitHub repository. This data was compiled from
UniProtKB/SwissProt, dbPTM, Phospho.ELM[38], and PhosphoSitePlus, with negative
annotations defined as all remaining S/T/Y residues in the considered proteins. An important
caveat with this standardized way of assembling phosphorylation datasets is that the negative
set also contains S/T/Y residues for which phosphorylation can never be observed due to
limitations in the data acquisition setups via MS/MS analysis.

The *Ramasamy22* data was obtained from our in-house and publicly accessible Scop3P[2,39]
database, in which P-sites were annotated from large-scale re-processing of proteomics
experiments[40] while requiring additional evidence from PhosphoSitePlus[41] and dbPTM[42]. All
annotations were matched with protein sequences from UniProtKB/SwissProt (version
2021-11), discarding proteins when one of its annotations did not match with the sequence
data. Non-P-site annotations were defined as all remaining S/T/Y residues in the proteins for
which no evidence was found in PhosphositePlus or dbPTM.

The *Giansanti15* data was obtained from experiments that involved different proteases[4]. Next
to a multi-protease dataset containing all P-site annotations, we also compiled individual
datasets for each protease. Only S/T annotations were considered, as Y annotations were too
few. Negative labels were defined as all S/T residues in the annotated proteins that were not
positively labelled in any of the single-protease experiment, Ramasamy22, or Guo21 datasets.

A comprehensive overview of the datasets is given in Table 1. All datasets are made
available via GitHub, along with their training/validation/test splits.

dataset	residues	# of proteins	# of pos	# of neg
Ramasamy22[2]	S/T	8,759	54,408	682,214
	Y	8,588	4,884	125,331
Guo21[12]	S/T	13,599	184,375	981,620
	Y	9,710	32,213	149,501

dataset	protease	# of proteins	# of pos	# of neg
Giansanti15[4]	AspN	1,719	3,818	164,044
(S/T only)	Chymotrypsin	1,675	3,329	163,351
	GluC	1,827	4,103	178,817
	LysC	1,637	3,939	160,800
	Trypsin	3,112	8,713	290,746
	multi-protease	4,498	17,201	411,321

Table 1. An overview of datasets used in this study.

For the Guo21 data, the original data split between training and test was kept, and training
data was divided into an actual training part and a validation part. This is done for S/T (Y) by
randomly selecting 11,150 (7999) proteins in the training set for training, and 738 (743) of
all proteins for validation, while keeping the remaining 1,361 (968) proteins for testing. The
Ramasamy22 and Giansanti15 data were randomly split by dividing proteins over training,
validation and test sets via a 85/5/10 distribution. Finally, for the model transfer analysis, a
cross-validation scheme was used, where each dataset set was split up into ten folds. Then,
for each fold, the proteins included in the validation set were removed from the training set,
of which 1/10th was used for early stopping. These schemes are illustrated in Suppl. Figure
5a and 5c.

3.2 Hyperparameters

Our setup includes a couple of fixed hyperparameters (Suppl. Table 2). Prediction models
were optimized via a cross-entropy loss, using an AdamW optimizer. The loss on the held-out
validation set is measured every $1/4^{th}$ epoch, for a total of up to ten epochs. Early stopping
was applied when the loss did not increase for five times, i.e. every 1.25 epochs, and the
model with the lowest loss was used for evaluation.

In addition, for the one-hot encoding and each of the PLM + architecture setup (linear, conv
only, full) combinations, an extensive hyperparameter search was performed on the
Ramasamy22-S/T dataset. Hyperparameters were evaluated on the validation set, thus not
hampering any test set independence in the results. As such, early stopping was done using a
randomly held out $1/20^{th}$ part of the training set. This scheme is illustrated in Suppl. Figure
5b.

A Bayesian optimization was run using the Weights and Biases framework[43]. Then, for each
representation + setup combination, the top three scores were collected, and their
architectures were collected for 10 more runs. Finally, the setup with the highest average
AUPRC on the validation set was selected.

A detailed list of the hyperparameter ranges is given in Suppl. Table 2. The final
hyperparameters are listed in Suppl. Table 3.

3.3 Proteins are split into fragments

Due to computational complexity of transformer-based PLMs, all proteins were split into
fragments of at most 512 amino acids before generating the representations. Fragments of

one protein can be divided over multiple batches, but will always belong to the same training,
validation, or test set to avoid data leakage.

Furthermore, as we wanted to avoid that a candidate P-site lies at the border between two
fragments, thus implying that it can only use information from upstream or downstream
residues, we allowed for overlapping fragments. Every 256 residues, a new fragment starts,
and P-sites are coupled to the fragment with the closest centre. The full batch split setup is
illustrated in Suppl. Figure 6.

For increased efficiency, we reduced the number of times the PLMs were used to generate
representations. Per epoch, one protein fragment was forwarded through the PLM only once,
even if it holds multiple P-site candidates. As a result, optimization was performed for a
varying number of positive and negative P-sites per batch.

3.4 Hardware and software used
Programmatical frameworks used include PyTorch and PyTorch Lightning for model
development and training and evaluation logic, WandB[43] for experiment logging and
hyperparameter sweeps, and Captum[37] for calculating the SHAP values. Sequence logos were
created using LogoMaker[44].

4. Results

4.1 Fine-tuning PLMs substantially improves P-site prediction performance
Figure 2 shows the prediction performance for the different amino acid representations and
their corresponding optimized model architectures, as well as the state-of-the-art predictors.
To compare between predictors, we mainly looked at the area under the precision-recall
curve (AUPRC) as a performance measure in order to produce meaningful results on the
imbalanced datasets. More detailed results including other metrics are shown in Suppl. Table
4.

The *linear* setup performs worse than the baseline one-hot CNNs on the Ramasamy22-S/T
dataset (with a drop in performance of 4.6% for the best performing PLM). Still, it performs
around the same level on Guo21-ST (-1.1% to +0.2%) and Giansanti15 multi-protease data (-
0.6% to +2.8%), and even slightly better on the Y datasets (-1% to +12.8%). Recall that the
linear setup fits a simple logistic regression model on top of the PLM representation of only
the candidate P-site amino acid. As such, these results strongly indicate that a PLM provides
a rich source of contextual information that is particularly valuable for P-site prediction.

In the *conv* setup, training a CNN on top of a PLM representation of an extended receptive
field substantially improves performance by up to 17.6% (Ramasamy22-S/T), 45.6%
(Ramasamy22-Y), 18.6% (Guo21-S/T), 23.7% (Guo21-Y), and 16.1% (Giansanti15 multi-
protease), compared to the baseline one-hot encoded architecture. A CNN clearly benefits
from the optimized PLM representations.

Training a CNN while simultaneously fine-tuning the PLM that computes the representation
in the *full* setup further improves performance for both the ESM-1b and ProtT5-XL-U50 PLM
models on Ramasamy22-S/T and Giansanti15 multi-protease data (between +0.6% and +9.7%

compared to the *conv* setup), but underperforms slightly for the other datasets (between -
7.8% and -0.1%), with one exception where variance in results was high (ESM-1b *conv*) on
Ramasamy22-Y.

Both *conv* and *full* setups consistently outperform the state-of-the-art predictors. The top
performing PLM-based setup shows a consistent increase of the AUPRC on the Ramasamy22-
S/T data of 13.4% (compared to DeepPSP), on Ramasamy22-Y data of 63.4% (MusiteDeep),
on Guo21-S/T data of 14.2% (DeepPSP), on Guo21-Y data of 19.5% (DeepPSP), and on
Giansanti15 multi-protease data of 13.3% (DeepPSP).

To put the prediction performance gains into perspective, we looked at the precision of the
predictor that correctly classifies four out of five true P-sites (i.e., when recall equals 0.8).
Compared to the best model (DeepPSP) the precision increases by up to 13.7%, from 0.455
to 0.517 (ProtT5-XL-U50 *full*) on the Ramasamy22-S/T dataset. On the Ramasamy22-Y
dataset, an increase of up to 46.3% is observed, from 0.164 to 0.240 (ProtT5-XL-U50 *conv*).

269
270

271 *Figure 2. Precision-recall curves for the top PLM predictors per setup, a one-hot encoding, and existing predictors.*
272 *Evaluation is done for five different datasets, each split up in a training set and a hold-out evaluation set. Average*
273 *curves over 10 runs (per dataset) are depicted. In the legend, the mean AUPRC is reported.*

4.2 Feature importance analysis

Visualizations of P-site predictors show discriminative features from different kinases
We computed SHAP values to estimate the average importance of individual residues in the
proximity of candidate P-sites. Results on Ramasamy22 and Guo21 data for the ESM-1b *full*

model, the best performing PLM-based model on the Ramasamy22-S/T dataset, are visualized
in Figure 3.

For the S/T models, the most notable residue is proline (P) at position P+1, which is known to
be a strong signal towards a P-site prediction, as several kinases in the CMGC group are known
to be proline-directed kinases[3], such as those belonging to the MAPK and CDK kinase families
(Suppl. Figure 7a-b). Other favourable residues in the S/T visualization are arginine (R) at
positions P-3 and P-2, often seen for kinases in the PKa family (Suppl. Figure 7c), and aspartic
(D) and glutamic acid (E) on the first positions downstream of the candidate site, as often seen
for kinases in the CK2 family (Suppl. Figure 7d). Visualizations for the one-hot encoded
models, shown in Suppl. Fig. 8, confirm these findings.

Figure 3. Average importance scores per position, calculated using DeepLiftSHAP, for the ESM-1b full prediction
model setup, on the Ramasamy22 and Guo21 datasets. Visualizations are cropped to show the twenty positions
surrounding the candidate P-site.

CNNs trained for P-site prediction disfavour inaccessible P-sites
The average importance scores in Figure 3 suggest that the models disfavour hydrophobic
amino acids in the proximity of the candidate P-site. On average, for the one-hot encoded
model, W/C/F/Y/I/V/M/L are considered least favourable when in the proximity of a P-site,
while for the PLM, this is the case for F/Y/C/V/I/W/L. As P-sites need to be reached by kinases
for phosphorylation to take place, the majority of P-sites are found at the solvent exposed
area of the protein (more than 80%, while less than 2% are located in buried regions)[2].
Hydrophobic (A/F/I/L/M/V/Y/W) and C residues[45] are more abundant in buried regions[45],
suggesting that the models implicitly learn that P-sites occur less frequently in buried regions.

This is confirmed by considering prediction distributions for candidate P-sites in buried,
interface and accessible regions. Alphafold[46,47] was used to obtain protein structures for all
proteins in the dataset that were shorter than 2700 amino acids. Next, DSSP[48] was used to

calculate the solvent accessibility and secondary structure for all candidate P-sites. Figure 4
shows the distribution of predicted probabilities for positively labelled P-sites in the
evaluation set. Predicted scores of P-sites located in buried regions tend to be lower than
those in interface regions, and much lower than those in accessible regions. Similar
conclusions can be drawn from secondary structure analysis, where P-sites in random coil
regions generally score higher than those in helices and sheets, which is in line with statistical
analysis of phosphorylation data[2].

Figure 4. Distribution of predicted probabilities for positively labelled P-sites in the Ramasamy22-S/T test set, per
model, divided by surface accessibility and secondary structure.

Datasets from experiments with other proteases indicate biased learning

Most notably, Figure 3 shows a high sensitivity to R and K residues in the proximity of the
candidate P-sites. These residues correspond to tryptic cleavage sites. With trypsin being the
most prevalent protease in bottom-up proteomics, this observation strongly points to a
protease-related bias in phosphorylation datasets. We hypothesized that the models indeed
learn an enriched presence of tryptic cleavage sites near P-sites.

To test this hypothesis, we performed experiments on the Giansanti15 datasets, where
predictors were trained and evaluated on data compiled from experiments that applied
different proteases (Suppl. Table 5). Figure 5 shows that ESM-1b (*full*) models trained on the
single-protease datasets demonstrate consistent enrichment of their corresponding cleavage
sites. The amino acids with highest average importance within the twenty positions
surrounding the P-sites are D for AspN, F for Chymotrypsin, E for GluC, K for LysC, and R for
Trypsin, consistent with the most frequent cleavage sites of the respective proteases. Similar
results for one-hot encoded models are shown in Suppl. Fig. 9.

Figure 5. Average importance scores per position, calculated using DeepLiftSHAP, for the ESM-1b full prediction model setup, on the Giansanti15 datasets. Visualizations are cropped to show the twenty positions surrounding the candidate P-site.

4.3 Model transferability analysis

To further investigate the observed protease specific bias, we evaluated predictors that were trained on different data sources, across different test sets. Concise results for the PLM-based models are shown in Figure 6, with additional results in Suppl. Figs. 10-11.

ProtT5-XL-U90 *conv* models trained on the Ramasamy22 data are consistently outperformed by single-protease trained models with a relative AUPRC increase of 3% to 11%, except for the trypsin data. Here, the models trained on Ramasamy22 data slightly outperform the models trained on only Giansanti15 trypsin data by 2%. This is likely because the former is largely constructed from experiments using trypsin digestion, and it has more than 6 times as many positive annotations, hence more data were available in training, allowing for better prediction performance.

For the AspN, Chymotrypsin, and GluC evaluation sets, the multi-protease predictors outperform the single-protease predictors by 1% to 7%. On LysC, they reach roughly the same performance, and on Trypsin data, performance drops by 2%. Overall, this suggests that models trained on data obtained from multiple proteases generalize better. In addition, we

can expect that training on multi-protease data results in predictors that are less prone to the
protease specific bias observed before.

Figure 6. *Evaluation on Giansanti15 single-protease and multi-protease datasets (x-axis), when training on a*
different data source (legend). Predictions are computed from ten folds of the evaluation set, where training is
performed on either Ramasamy22-S/T data, Giansanti15 multi-protease data, or on the dataset matching the
data source on the x-axis. Note that proteins present in the test fold are omitted from training. The average
AUPRC over these ten test folds is shown, for ProtT5-XL-U50 conv models.

5. Discussion

With PLMs showing their potential in various structure-related prediction tasks, we applied
them to general phosphorylation prediction. We showed that PLMs compute information rich
protein representations that substantially boost P-site prediction accuracy as evaluated on
different data sources. Of the proposed training strategies, both training of the CNN (*conv*
setup) only and simultaneously fine-tuning the PLM (*full* setup) proved successful. Even for a
simple linear setup that applies logistic regression on a PLM encoding of just the candidate P-
site already compares on par with more complex CNN models with one-hot encoded
receptive fields.

Furthermore, we compared our approach to currently available state-of-the-art approaches
that apply non-standard building blocks such as squeeze-and-excitation networks in
combination with bidirectional LSTM layers (DeepPSP), capsule networks (MusiteDeep), and
densely connected CNN blocks with block concatenation (DeepPhos). Our approach
substantially outperforms these architectures. On all five datasets considered, each of the
conv and *full* setups that were trained on the two largest PLMs outperformed all considered
baselines. Overall, PLMs clearly yield richer representations that contribute towards more
effective phosphorylation prediction.

Inspecting average feature importance scores confirmed known kinase family-specific residue
patterns, such as proline at P+1, arginine at P-3 and P-2, and aspartic and glutamic acid at the
first positions downstream of the candidate P-site. Both for one-hot encoded and PLM-based
models, predicted probabilities are found to be higher on average for accessible P-sites than
for buried ones, and higher for P-sites within random coil regions than for ones in alpha
helices or beta sheets.

We also found the prediction models to favour the presence of amino acids that are targeted by proteases for cleavage, in the proximity of candidate P-sites. Rather than a biological justification for phosphorylation, this is largely a result of statistical bias in the positive and negative labels in the datasets that emerge from the nature of protein digestion in bottom-up LC-MS/MS proteomics experiments. Most P-sites are determined after MS/MS experiments where trypsin is used for digestion[3]. As more missed cleavages occur near P-sites[4,6], the set of phosphorylated peptides contains more R/K-enriched peptides that are cleaved in fragments that are too short for MS/MS analysis if they are not phosphorylated. Additionally, R/K-poor regions result in longer peptides, which suffer from lower localization scores on average (see Suppl. Figure 12), or which can be too long for MS/MS analysis.

During training, machine learning models learn to exploit these kinds of biases as a distinctive feature between positive and negative samples. Thus, general phosphorylation prediction models do not just learn P-site fingerprints to predict the likeliness of phosphorylation, but also the likeliness that they are detected with current experimental setups. We are currently only able to identify a delineated subset of all possible P-sites, as with current standard high-throughput experimental methodologies, any prediction model trained on resulting data will attempt to learn that delineation, rather than the exact boundary between actual and pseudo P-sites.

This was further illustrated by transferring prediction models between phosphorylation datasets that resulted from experiments with different proteases and showing that this was detrimental for prediction performance. Hence, the application for which P-site predictions are done steers the choice of training data. When doing *de novo* predictions, protease bias is detrimental, and the training data should be as heterogeneous as possible. However, when predicting detectable phosphorylation for LC-MS/MS data interpretation purposes, a model trained on data using the same protease should be used.

We provide an accurate PLM-based P-site predictor on our GitHub repository (https://github.com/jasperzuallaert/PhosphoLingo), trained on a large multi-source dataset that combines all annotations from the considered datasets in this paper. A user-friendly framework is released to reproduce the results in this manuscript, as well as to train and evaluate models on other phosphorylation datasets, or even for other post-translational modifications. Furthermore, we supply predictions for all S, T and Y residues in the human proteome, using an ensemble of the best prediction models discussed in this manuscript.

Acknowledgements

Funding
This work was supported by the Research Foundation – Flanders (FWO) [1274021N for J.Z.]; and the Vlaams Agentschap Innoveren en Ondernemen [HBC.2020.2205 for R.B.]. Research at our lab is core-funded by the VIB - Center for Medical Biotechnology and Ghent University.

Conflict of interest: none declared

References

1. Ramazi, S. & Zahiri, J. Post-translational modifications in proteins: resources, tools and prediction methods. *Database* **2021**, (2021).

2. Ramasamy, P., Vandermarliere, E., Vranken, W. & Martens, L. Panoramic Perspective on Human Phosphosites. *Journal of Proteome Research* **21**, 1894–1915 (2022).

3. Pinna, L. A. & Ruzzene, M. How do protein kinases recognize their substrates? *Biochimica et Biophysica Acta (BBA) - Molecular Cell Research* **1314**, 191–225 (1996).

4. Giansanti, P. *et al.* An Augmented Multiple-Protease-Based Human Phosphopeptide Atlas. *Cell Reports* **11**, 1834–1843 (2015).

5. Dephoure, N., Gould, K. L., Gygi, S. P. & Kellogg, D. R. Mapping and analysis of phosphorylation sites: A quick guide for cell biologists. *Molecular Biology of the Cell* **24**, 535–542 (2013).

6. Tsiatsiani, L., Heck, A. J. R., Heck, A. J. R. & Bijvoet, P. Proteomics beyond trypsin. *The FEBS Journal* **282**, 2612–2626 (2015).

7. Trost, B. & Kusalik, A. Computational prediction of eukaryotic phosphorylation sites. *Bioinformatics* **27**, 2927–2935 (2011).

8. Ma, R. *et al.* KinasePhos 3.0: Redesign and Expansion of the Prediction on Kinase-specific Phosphorylation Sites. *bioRxiv preprint* (2021) doi:10.1101/2021.11.02.467032.

9. Song, J. *et al.* PhosphoPredict: A bioinformatics tool for prediction of human kinase-specific phosphorylation substrates and sites by integrating heterogeneous feature selection. *Scientific Reports* **7**, (2017).

10. Xu, Y., Song, J., Wilson, C. & Whisstock, J. C. PhosContext2vec: A distributed representation of residue-level sequence contexts and its application to general and kinase-specific phosphorylation site prediction. *Scientific Reports* **8**, (2018).

11. Wang, C. *et al.* GPS 5.0: An Update on the Prediction of Kinase-specific Phosphorylation

Sites in Proteins. *Genomics, Proteomics and Bioinformatics* **18**, 72–80 (2020).

12. Guo, L. *et al.* DeepPSP: A Global-Local Information-Based Deep Neural Network for the

Prediction of Protein Phosphorylation Sites. *Journal of Proteome Research* **20**, 346–356

(2021).

13. Wei, L., Xing, P., Tang, J. & Zou, Q. PhosPred-RF: A Novel Sequence-Based Predictor for

Phosphorylation Sites Using Sequential Information only. *IEEE Transactions on*

Nanobioscience **16**, 240–247 (2017).

14. Li, F. *et al.* Quokka: A comprehensive tool for rapid and accurate prediction of kinase

family-specific phosphorylation sites in the human proteome. *Bioinformatics* **34**, 4223–

4231 (2018).

15. Dou, Y., Yao, B. & Zhang, C. PhosphoSVM: Prediction of phosphorylation sites by

integrating various protein sequence attributes with a support vector machine. *Amino*

Acids **46**, 1459–1469 (2014).

16. Yang, H., Wang, M., Liu, X., Zhao, X.-M. & Li, A. PhosIDN: an integrated deep neural

network for improving protein phosphorylation site prediction by combining sequence

and protein–protein interaction information. *Bioinformatics* **37**, 4668–4676 (2021).

17. Wang, D. *et al.* MusiteDeep: A deep-learning based webserver for protein post-

translational modification site prediction and visualization. *Nucleic Acids Research* **48**,

W140–W146 (2021).

18. Luo, F., Wang, M., Liu, Y., Zhao, X. M. & Li, A. DeepPhos: Prediction of protein

phosphorylation sites with deep learning. *Bioinformatics* **35**, 2766–2773 (2019).

19. Lv, H., Dao, F.-Y., Zulfiqar, H. & Lin, H. DeepIPs: comprehensive assessment and

computational identification of phosphorylation sites of SARS-CoV-2 infection using a

deep learning-based approach. *Briefings in Bioinformatics* (2021)

doi:10.1093/bib/bbab244.

20. Deznabi, I., Arabaci, B., Koyuturk, M. & Tastan, O. DeepKinZero: Zero-shot learning for

predicting kinase-phosphosite associations involving understudied kinases.

Bioinformatics **36**, 3652–3661 (2020).

21. Kirchoff, K. & Gomez, S. EMBER: multi-label prediction of kinase-substrate

phosphorylation events through deep learning. *Bioinformatics* **38**, (2022).

22. Blom, N., Sicheritz-Pontén, T., Gupta, R., Gammeltoft, S. & Brunak, S. Prediction of post-

translational glycosylation and phosphorylation of proteins from the amino acid

sequence. *Proteomics* **4**, 1633–1649 (2004).

23. Jamal, S., Ali, W., Nagpal, P., Grover, A. & Grover, S. Predicting phosphorylation sites

using machine learning by integrating the sequence, structure, and functional

information of proteins. *Journal of Translational Medicine* **19**, (2021).

24. Ma, H., Li, G. & Su, Z. KSP: An integrated method for predicting catalyzing kinases of

phosphorylation sites in proteins. *BMC Genomics* **21**, (2020).

25. Thapa, N. *et al.* A deep learning based approach for prediction of Chlamydomonas

reinhardtii phosphorylation sites. *Scientific Reports* **11**, (2021).

26. Ismail, H. D., Jones, A., Kim, J. H., Newman, R. H. & Kc, D. B. RF-Phos: A Novel General

Phosphorylation Site Prediction Tool Based on Random Forest. *BioMed Research*

International **2016**, (2016).

27. Brown, T. B. *et al.* Language Models are Few-Shot Learners. *Advances in Neural*

Information Processing Systems **33**, 1877--1901 (2020).

28. Alley, E. C., Khimulya, G., Biswas, S., Alquraishi, M. & Church, G. M. Unified rational

protein engineering with sequence-based deep representation learning. *Nature*

Methods **16**, 1315–1322 (2019).

29. Rao, R. *et al.* Evaluating Protein Transfer Learning with TAPE. *Advances in Neural*

Information Processing Systems **32**, 9689--9701 (2019).

30. Rives, A. *et al.* Biological structure and function emerge from scaling unsupervised

learning to 250 million protein sequences. *Proceedings of the National Academy of*

Sciences of the United States of America **118**, (2021).

31. Elnaggar, A. *et al.* ProtTrans: Towards Cracking the Language of Lifes Code Through Self-

Supervised Deep Learning and High Performance Computing. *IEEE Transactions on*

Pattern Analysis and Machine Intelligence **14**, 1–1 (2021).

32. Strodthoff, N., Wagner, P., Wenzel, M. & Samek, W. UDSMProt: universal deep

sequence models for protein classification. *Bioinformatics* **36**, 2401–2409 (2020).

33. Rao, R., Meier, J., Sercu, T., Ovchinnikov, S. & Rives, A. *Transformer protein language*

models are unsupervised structure learners.

http://biorxiv.org/lookup/doi/10.1101/2020.12.15.422761 (2020)

doi:10.1101/2020.12.15.422761.

34. Meier, J. *et al.* Language models enable zero-shot prediction of the effects of mutations

on protein function. in *Advances in Neural Information Processing Systems* vol. 34

29287–29303 (2021).

35. Detlefsen, N. S., Hauberg, S. & Boomsma, W. Learning meaningful representations of

protein sequences. *Nat Commun* **13**, 1914 (2022).

36. Lundberg, S. M. & Lee, S. A unified approach in interpreting model predictions.

Advances in Neural Information Processing Systems 4765–4774 (2017).

37. Kokhlikyan, N. *et al.* Captum: A unified and generic model interpretability library for

PyTorch. *arXiv preprint* (2020) doi:10.48550/arXiv.2009.07896.

38. Dinkel, H. *et al.* Phospho.ELM: a database of phosphorylation sites—update 2011.

Nucleic Acids Research **39**, D261–D267 (2011).

39. Ramasamy, P. *et al.* Scop3P: A Comprehensive Resource of Human Phosphosites within

Their Full Context. *Journal of Proteome Research* **19**, 3478–3486 (2020).

40. Perez-Riverol, Y. *et al.* The PRIDE database resources in 2022: a hub for mass

spectrometry-based proteomics evidences. *Nucleic Acids Research* **50**, D543–D552

(2022).

41. Hornbeck, P. V. *et al.* PhosphoSitePlus, 2014: mutations, PTMs and recalibrations.

Nucleic acids research **43**, D512–D520 (2015).

42. Li, Z. *et al.* dbPTM in 2022: an updated database for exploring regulatory networks and

functional associations of protein post-translational modifications. *Nucleic Acids*

Research **50**, D471–D479 (2022).

43. Biewald, L. Experiment Tracking with Weights and Biases. (2020).

44. Tareen, A. & Kinney, J. B. Logomaker: Beautiful sequence logos in python. *bioRxiv*

preprint (2019) doi:10.1101/635029.

45. Gowder, S. M., Chatterjee, J., Chaudhuri, T., Paul, K. & Wang, J. Prediction and Analysis

of Surface Hydrophobic Residues in Tertiary Structure of Proteins. *The Scientific World*

Journal (2014) doi:10.1155/2014/971258.

46. Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature*

2021 596:7873 **596**, 583–589 (2021).

47. Varadi, M. *et al.* AlphaFold Protein Structure Database: massively expanding the

structural coverage of protein-sequence space with high-accuracy models. *Nucleic Acids*

Research **50**, D439–D444 (2022).

48. Kabsch, W. & Sander, C. Dictionary of protein secondary structure: Pattern recognition

of hydrogen-bonded and geometrical features. *Biopolymers* **22**, 2577–2637 (1983).

535