Identifying content-invariant neural signatures of phenomenal magnitude

Benjamin O. Barnett[1,2], Lau M. Andersen[3,4,5], Stephen M. Fleming[1,2,6,*] and Nadine Dijkstra[1,*]

[1]*Wellcome Centre for Human Neuroimaging, University College London, 12 Queen Square, London WC1N 3AR, UK.*

[2]*Department of Experimental Psychology, University College London, 26 Bedford Way, London WC1H 0AP, UK.*

[3]*Aarhus Institute of Advanced Studies, Høegh-Guldbergsgade 6B, 8000 Aarhus C, Denmark*

[4]*Center of Functionally Integrative Neuroscience, Nørrebrogade 44, Building 1A, 8000 Aarhus C, Denmark*

[5]*Department for Linguistics, Cognitive Science and Semiotics, Aarhus University, Jens Chr. Skous Vej Building 1485, 8000 Aarhus C, Denmark*

[6]*Max Planck UCL Centre for Computational Psychiatry and Ageing Research, University College London, London, UK.*

[*]Joint senior authors

Correspondence: benjy.barnett.20@ucl.ac.uk

Keywords: awareness, perception, MEG, fMRI

Abstract

Some experiences are stronger than others: they have greater phenomenal magnitude. Although the phenomenal magnitude of experience is a familiar component of human consciousness, the computational scheme underpinning its encoding in the brain is unknown. In particular, it is unknown whether phenomenal magnitude is encoded in a "rich" manner, via the strengthening or broadcast of content-specific perceptual representations, or a "sparse" scheme, in which a content-invariant signal monitors the reliability or precision of first-order contents. In a reanalysis of existing MEG and fMRI data from two distinct studies, we operationalise phenomenal magnitude as subjective ratings of awareness and visibility to address this question. We find that phenomenal magnitude is associated with content-invariant neural signatures distributed across visual, parietal, and frontal cortices. Moreover, we show that these neural signatures exhibit similarities with other analogue magnitude codes such as number, with each rating being represented as being more similar to its neighbours, and less similar to more distant ratings. Our findings suggest a role for a content-invariant analogue magnitude code in determining the strength of perceptual experience.

Introduction

Humans are aware of their environment: we experience the sights and sounds of the world around us. Some experiences, however, are stronger than others. We may experience the sound of birds calling outside our window more vividly from one day to the next, for example, and the smell of wild garlic can occupy a large portion of our experience on one walk but not another. This feature of consciousness has been described as the 'force and liveliness' of an experience (Hume, 2000), its 'magnitude' (Bartoshuk et al., 1986; Marks et al., 1988), and its 'mental strength' (Morales, 2018, 2021). Put simply, these terms reflect the degree to which something takes up one's stream of consciousness: the phenomenal magnitude of experience.

An important question surrounding the neural encoding of phenomenal magnitude is its stimulus-specificity. Under a rich encoding scheme, our experience of a stimulus such as a red circle is vivid because the firing of red-representing neural populations is strengthened (driven for instance by feature-specific attention, or bottom-up stimulus strength / salience; Itti & Baldi, 2009). This rich view of phenomenal magnitude is embraced by first-order theories of consciousness, which assert that a mental state becomes conscious solely by virtue of the characteristics of its perceptual content. Local recurrency, for example, proposes that recurrent interactions between content-specific neural populations in visual cortex are responsible for generating conscious awareness (Lamme, 2006; Lamme & Roelfsema, 2000). The same holds for global workspace theory, in which the broadcast of perceptual information to a number of neural subsystems underpins changes in awareness of that content (Dehaene & Changeux, 2011; Naccache et al., 2016). In both cases, changes in stimulus visibility are associated with changes in the strength or distribution of content-specific perceptual information. In addition, some variants of higher-order theory (which suggest that perceptual representations alone are not sufficient to generate conscious awareness; Lau & Rosenthal, 2011) propose that phenomenal experience (and therefore, presumably, the magnitude of this experience)

is supported by rich meta-representations of perceptual content (Brown, 2015; Cleeremans et al., 2020). Regardless of the specific implementation of consciousness-related computation (first-order or higher-order), any version of the rich view makes a clear prediction that phenomenal magnitude should be encoded by changes in content-specific neural populations.

In contrast, under a sparse view, phenomenal magnitude is represented independently of perceptual content. Note that here rich vs. sparse refers to the neurocomputational architecture supporting phenomenal magnitude, not whether or not perceptual experience is itself rich or sparse (Block, 2011). The sparse view predicts that the phenomenal magnitude of my experience of birdsong is represented in a similar fashion to the phenomenal magnitude of my experience of smelling garlic. A number of higher-order theories of consciousness adopt this view, in which higher-order representations supported by frontoparietal regions encode the precision or reliability of first-order sensory representations (Fleming, 2020; Graziano, 2013; Lau, 2019). The drivers of such content-independent signals may include changes in attention, emotion, and other cognitive factors that go beyond stimulus-specific salience, but nevertheless also contribute to the magnitude of experiences. As such, an alternative hypothesis is that rather than being bound to content-specific representations, phenomenal magnitude is encoded in a domain-general fashion, independently of stimulus content (Morales, 2021), with higher-order brain regions responsible for generating such signals.

Related to the content-specificity of phenomenal magnitude is the question of how a putative neural substrate for phenomenal magnitude might be implemented. Beyond phenomenology, the neural basis of other analogue magnitude quantities is relatively well understood: both single neurons and neuronal populations are tuned to specific magnitudes within the domains of number, size, and time (Eiselt & Nieder, 2016; Harvey et al., 2020; Kutter et al., 2018; Piazza et al., 2004; for review: Tsouli et al., 2021). In such coding schemes, the tuning curves that are sensitive to specific magnitudes are ordered and overlapping, producing a graded representational structure. These graded representations are commonly revealed by distance effects, whereby closer magnitudes are represented as more similar than more distant magnitudes

(Dehaene et al., 1998; Tsouli et al., 2021). Recently it has been proposed that projecting neural

representations into low dimensional state-spaces may support cognition across distinct domains

(Summerfield et al., 2020) – for instance, one-dimensional magnitude codes shared between number and

reward (Luyckx et al., 2019), or two-dimensional grid-codes for mapping conceptual as well as physical

space (Behrens et al., 2018; Bellmund et al., 2018). While number and phenomenal magnitude are

psychologically distinct, perceptual vividness is also naturally low-dimensional – ranging from being

wholly unaware of content, to having a clear and vivid experience of that content. If phenomenal magnitude

codes are content-invariant, it may therefore be the case that awareness-related computations are supported

by low-dimensional and domain-general neural resources too, and as such it is an intriguing question as to

whether changes in phenomenal magnitude are supported by the graded and low-dimensional magnitude

codes often seen in other cognitive domains.

Here we reanalysed both magnetoencephalography (MEG; Andersen et al., 2016) and functional magnetic

resonance imaging (fMRI; Dijkstra et al., 2021) data to investigate how phenomenal magnitude is

represented in the human brain. We asked two questions regarding the structure of neural phenomenal

magnitude codes: (1) whether phenomenal magnitude is encoded independently of stimulus content and (2)

whether it is encoded in a graded manner like other low-dimensional magnitudes. We employed

representational similarity analysis (Flesch et al., 2022; Luyckx et al., 2019) to answer these questions,

allowing us to uncover the structure of neural representations (Kriegeskorte & Kievit, 2013). We

operationalised phenomenal magnitude as different awareness ratings and examined the extent to which

different coding schemes, instantiated as distinct representational dissimilarity matrices, predicted the

representational structure of these ratings in the brain. Finally, we used searchlight cross-condition decoding

methods (Bernardi et al., 2020; Dijkstra et al., 2018) to examine whether abstract representations of

phenomenal magnitude are found within a frontoparietal network, in line with sparse higher-order theories

of consciousness (Fleming, 2020; Lau, 2019). To anticipate our results, we found that neural representations

of phenomenal magnitude generalize over stimulus content, exhibit a graded structure, and can be identified

across visual, parietal, and frontal brain regions. Together our findings reveal a role for content-invariant

analogue magnitude codes in supporting the strength of perceptual experience.

Materials and Methods

MEG experiment

To explore the structure and dynamics of abstract representations of awareness ratings, we re-analysed an MEG dataset previously acquired at Aarhus University (Andersen et al. 2016). The data were recorded in a magnetically shielded room using an Elekta Neuromag Triux system with 102 magnetometers and 204 orthogonal planar gradiometers. Data were recorded at a frequency of 1000 Hz.

Participants

Nineteen participants took part in the experiment (Mean age = 26.6 years; SD = 4.4 years). Two participants were excluded from our analyses: one for failing to complete the experiment and the other for not using the 'almost clear experience' rating at all (see procedure details below).

Procedure

In order to obtain a range of awareness ratings from each subject, a visual masking paradigm was used (Figure 1A). First, a fixation cross was presented for either 500, 1000, or 1500 ms, followed by a target stimulus for 33.3 ms. The target stimulus was either a square or a diamond presented in white/grey on a black (RGB value 0, 0, 0) background (Figure 1B). A static random noise mask followed the target and was presented for 2000 ms. Participants were required to identify the target during these 2000 ms, before rating their awareness of the stimulus on the perceptual awareness scale (PAS) (Ramsøy & Overgaard, 2004). PAS consists of four possible responses: no experience (NE), weak glimpse (WG), almost clear experience (ACE), and clear experience (CE). Following identification of the target, participants reported their awareness of the stimulus. The response boxes used for target identification and awareness report were swapped between hands every 36 trials to minimise lateralised motor responses contributing to MEG

activity patterns. More details regarding the instructions given to participants about each PAS response can

be found in Andersen et al. (2016).

The experiment consisted of one practice block and 11 experimental blocks, each with 72 trials. A contrast

staircase was used for the target stimuli in order to obtain a sufficient number of responses for each PAS

rating. The staircase procedure had 26 contrast levels ranging from a contrast of 2% to 77%, with a step

size of 3%. In the practice block and first experimental block, the staircase increased by 1 level if a

participant made an incorrect judgement on the identification task, and decreased by 2 levels if a participant

made 2 successive correct identification judgements. For the remainder of the blocks, the staircase was

adjusted based on which PAS rating the participant had used least throughout the experiment so far.

Specifically, if NE had been used the least number of times throughout a block, 3 levels were subtracted

after 2 consecutive correct answers, and 1 added for a wrong answer. If WG was the least used response, 2

levels were subtracted and 1 added. For ACE, 1 level was subtracted and 2 added. For CE, 1 level was

subtracted and 3 added.

Figure 1. Experimental Paradigms. A: Experimental paradigm for the MEG data collected by (Andersen et al., 2016). First, a fixation cross was presented for 500, 1000 or 1500 ms. Then, either a square or a diamond was shown for 33.3 ms, followed by a static noise mask for 2000 ms. While the mask was shown, participants reported the identity of the target. Finally, they reported their awareness of the stimulus using the PAS scale. **B:** Stimuli used in Andersen et al. (2016). **C**: Experimental paradigm for the fMRI data collected by Dijkstra et al. (2021). A stimulus was presented for 17 ms, followed by a 66 ms ISI and a 400 ms mask. Participants then indicated whether the stimulus was animate or inanimate, and finally rated the visibility of the stimulus on a four-point scale. **D:** Stimuli used in Dijkstra et al. (2021).

Pre-processing

MEG data were analysed using MATLAB 2019a and FieldTrip (Oostenveld et al., 2011). The data were

pre-processed with a low pass filter at 100 Hz, as well as a Discrete Fourier Transform (DFT) and bandstop

filters at 50 Hz and its harmonics. The data were split into epochs of -200 to 2000 ms around stimulus onset

and down-sampled to 250 Hz. For baseline correction, for each trial, activity 200 ms prior to stimulus

presentation was averaged per channel and subtracted from the entire epoch. During artefact rejection, trials

with high variance were visually inspected and removed if they were judged to contain excessive artefacts.

This procedure was performed blind to the experimental condition to avoid experimenter bias and was

completed separately for the magnetometers and gradiometers in the Elekta Neuromag Triux system. We

rejected an average of 213.60 (26%) trials per participant (SD = 52.40; 6.62%). To further remove eye-

movement artefacts, an independent components analysis was carried out on the MEG data, and the

components with the highest correlation with each of the electro-oculographic (EOG) signals were

discarded after visual inspection. Components showing topographic and temporal signatures typically

associated with heart rate artefacts were also removed.

We created two additional analysis pipelines to rule out potential alternative interpretations of our results.

First, to examine whether our results were confounded by the contrast level of the stimuli, we regressed

stimulus contrast level on each trial out of the pre-processed MEG data. Second, to investigate whether

differences in pre-stimulus activity contributed to differences in phenomenal magnitude (Benwell et al.,

2017; Podvalny et al., 2019; Samaha et al., 2017), we ran our data through the same pre-processing pipeline

as above except for two adjustments: removing the baseline correction stage and lengthening the epochs to

-450 ms to 2000 ms around stimulus presentation. The omission of baseline correction allows the analysis

to be sensitive to differences in the pre-stimulus activity (in the offset or mean amplitude, for example) of

trials associated with different awareness ratings which would otherwise be removed by baseline correction

(the baseline correction procedure results in each trial's pre-stimulus window having a mean activity of

zero across all time points for each channel, such that our RSA and decoding analyses would be unable to

detect and characterise any pre-stimulus contribution to phenomenal magnitude codes).

Representational similarity analysis

Representational similarity analysis (RSA) allows us to directly compare bespoke hypotheses about the

structure of neural data (Kriegeskorte & Kievit, 2013). In RSA, hypotheses are expressed as model

representational dissimilarity matrices (RDMs), which define the predicted similarity of neural patterns

between different conditions according to each hypothesis. In our case, we defined 4 model RDMs that

make different predictions about whether or not awareness ratings generalise over perceptual content, and

whether or not each rating leads to a graded activation pattern partially shared by neighbouring ratings

(Figure 2A).

In our Abstract-Graded RDM, we model awareness ratings as being independent of perceptual content

(such that ratings of a clear experience of a square have an identical neural profile to those of a clear

experience of a diamond), as well as being graded in nature (exhibiting a distance effect such that ratings

of "no experience" are more similar to those of "weak glimpse", than of "almost clear experience"). In the

Specific-Graded RDM, awareness ratings are modelled as being graded in the same way, but they are now

represented differently depending on which specific stimulus they are related to. Conversely, the Abstract-

Discrete RDM represents PAS ratings as independent of perceptual content but with no graded

structure/distance effects (such that the neural code underpinning a report of "no experience" is equally

(dis)similar to the neural code reflecting either a "weak glimpse" or a "clear experience"). Finally, the

Specific-Discrete RDM reflects our null model, whereby there is no observable representational similarity

structure among conditions, such that neural patterns reflecting one specific awareness rating are equally

dissimilar to all other awareness ratings.

RSA involves the comparison of the model RDMs with empirical RDMs constructed from neural data. To

do this, we first ran a linear regression on the MEG data with dummy coded predictors for each of our eight

conditions (Square trials: NE, WG, ACE, CE; Diamond trials: NE, WG, ACE, CE; trial condition coded

with a 1, alternative classes coded with a 0). This resulted in coefficient weights for each condition at each

time point and sensor, with the weights representing the neural response per condition, averaged over trials.

We then computed the Pearson distance between each pair of condition weights over sensors, resulting in

an 8 x 8 neural RDM reflecting the similarity of neural patterns across different awareness ratings and

stimulus types (Luyckx et al., 2019). Neural RDMs were subsequently smoothed over time via convolution

with a 60 ms uniform kernel.

We then compared this neural RDM with our model RDMs. To compare model RDMs with the neural

RDM, we correlated the lower triangle of the model and neural RDMs using Kendall's Tau rank correlation

(Nili et al., 2014). We performed this procedure at every time point, resulting in a correlation value at each

time point for each model. Importantly, we only correlated the lower triangle of the RDMs, excluding the

diagonal to avoid spurious correlations driven by the increased similarity of on-diagonal values compared

to off-diagonal values (Ritchie et al., 2017). This precluded us from directly testing our Specific-Discrete

model, since it is represented by a uniform RDM, and as such would give identical rank correlation values

regardless of the neural RDM it was compared to. However, since this RDM reflects our null model (i.e.

that there is no observable representational structure amongst awareness ratings), this model is implicitly

compared with the other model RDMs when we examine whether the correlation of these model RDMs

with the neural RDM is greater than 0.

One concern with this approach is that the graded hypotheses may win due to the neural data itself being

noisy. In other words, if a classifier is unable to cleanly separate distinct ratings, there will be greater overlap

between all ratings in the empirical RDM, including those of close neighbours. To ensure we did not obtain

spuriously high similarity with the Abstract-Graded model in virtue of this model's low-frequency content,

we performed a shuffling and blending procedure. This procedure involved shuffling the lower triangle of

the Abstract-Discrete RDM before apportioning neighbours of the four (shuffled) high correlation cells

with graded amounts of correlation. Correlation was blurred most to immediate neighbours, and less to

diagonal neighbours, matching the format of the graded RDMs (Figure 2C). We ran this procedure 1000

times per subject, resulting in 1000 Shuffled-Discrete and 1000 Shuffled-Graded RDMs. We compared all

shuffled-discrete and shuffled-graded RDMs with subjects' neural data at each time point. Finally, we took

the average correlation value for each time point across all permutations such that we had a Kendall's Tau

value for both the Shuffled-Discrete and Shuffled-Graded RDMs across time per subject. Through this

approach, we were able to compare neural data with RDMs that shared no representational similarity with

our Abstract-Graded RDM while controlling for differences in variance and frequency profile.

Within-subject multivariate decoding analysis

To support and extend conclusions drawn from our RSA analyses, we ran an exploratory analysis using

temporal generalisation methods (King & Dehaene, 2014) to identify content-invariant and graded

representations of awareness ratings while also investigating the stability of these representations over

time. In this procedure, a separate classifier is trained on each time point (from 200 ms pre-stimulus to

2000 ms post-stimulus) and tested on all other time points. This method results in a time-by-time

decoding accuracy matrix indicating the extent to which neural representations are stable over time.

Above chance decoding at a particular point in the decoding matrix indicates that neural representations

present at the training and testing time points are similar, whilst chance decoding indicates the

representations have changed.

We ran the above temporal generalisation analysis using both a within-condition and cross-condition

decoding procedure. Within-condition decoding involved training and testing the decoder to classify PAS

ratings on trials from one stimulus type (either squares or diamonds). In cross-condition decoding, we

trained on trials from one stimulus type and tested on trials from the other (e.g. trained on square trials

and tested on diamond trials, and vice-versa). In both cases, we used a 5-fold cross validation scheme,

with a balanced number of trials per class within each fold. Cross-condition decoding, where a classifier

trained to decode multivariate neural patterns in one class of stimuli is tested on an unseen class of

stimuli, offers an empirical test of whether the neural patterns associated with each class share a similar

neural code across conditions (Albers et al., 2013; Bernardi et al., 2020; Dijkstra et al., 2018). This

analysis therefore complements the RDM analysis in being able to test for content-invariant phenomenal

magnitude codes, while also providing information about their stability over time. We performed all

multiclass decoding analyses with a multiclass Linear Discriminant Analysis (LDA) decoder using the

MVPA-light toolbox (Treder, 2020) with FieldTrip. Each of the four PAS ratings served as classes for the

decoder to classify trials into. We used L1-regularisation of the covariance matrix, with the shrinkage

parameter calculated automatically using the Ledoit-Wolf formula within each training fold (Ledoit &

Wolf, 2004).

It is important to note that cross-validation is not technically necessary during cross-condition decoding

because the test data is never seen by the classifier during training, so there is no risk of overfitting.

However, we employed a cross-validation scheme for all our decoders so that differences in their

performance would not be due to differences in training procedures (e.g. number of trials in the training or

test set). Data was smoothed over 7 samples (28ms) and classification analysis was run on individual time

points throughout the whole trial to characterise the temporal dynamics of the representations (-200 to 2000

ms post-stimulus).

Stimulus decoding

One difficulty with interpreting a content-invariant representation of phenomenal magnitude is that it may

reflect a lack of power to detect content-specific differences between conditions (e.g. square vs. diamond).

To control for this possibility, we sought to ensure that the resolution of our data was sufficiently fine-

grained to pick up differences in the neural encoding of different stimuli. To do this, we applied a binary

decoding procedure using a binary LDA decoder with the same classification parameters as above. In this

analysis, the two stimulus types (squares and diamonds) were used as classes for the decoder to classify

trials into. For this analysis we grouped trials into low (NE and WG) and high visibility (ACE and CE)

trials to ensure sufficient power, performing the decoding analysis separately in each group. Once again,

data were smoothed over 7 samples (28ms) and analysed on individual time points throughout the whole

trial (-200 to 2000 ms post-stimulus).

Statistical Inference

To determine whether our RSA and decoding results were statistically significant, we used cluster-based

permutation testing (Maris & Oostenveld, 2007) with 1000 permutations. For RSA, within each

permutation we flipped the sign of each ranked correlation value at each time point for each participant and

performed a one-sample t-test against 0. Resulting t-values associated with a p-value smaller than 0.05 were

used to form clusters across the single time dimension. For each cluster, an associated cluster statistic was

computed, the largest of which was stored per permutation to build a group-level null distribution. The

cluster statistic computed from our observed data was then compared to this chance distribution to

determine statistical significance with an alpha level of 0.05. This procedure controls for the multiple

comparisons problem by only performing one comparison at the inference stage and specifically tests the

null hypothesis that the observed data are exchangeable with data from the permuted (null) distribution

(Maris & Oostenveld, 2007). We used the same cluster-based permutation procedure to compare how well

different model RDMs predicted the neural data. In this case, we performed paired-comparisons where

ranked correlation values per RDM were randomly swapped within subjects per permutation to build up a

group-level null distribution.

For decoding results, we used the same cluster-forming parameters, but this time randomly flipped the sign

of individual subjects' accuracy scores per permutation to build up a group-level null distribution.

Additionally, we formed clusters over both time dimensions of the temporal generalisation matrices. We

used the same cluster-based permutation procedure to compare performance between cross-condition and

within-condition decoders.

It is important to note that our cluster-based permutation testing procedure does not allow for inference as

to the exact time points at which neural representations come into existence. This is because the algorithm

does not consider individual time points at the statistical inference stage, since at this point it only relies on

cluster statistics, which encompass multiple time points (Sassenhagen & Draschkow, 2019). Still, as we are

not interested in the precise onset of content-invariant representations of awareness ratings but rather their

general temporal profile, this method is sufficient for our purposes.

fMRI experiment

To help localise representations of phenomenal magnitude in the brain, we re-analysed a previously

collected fMRI dataset. It is worth noting that, while source-space decoding in MEG is certainly possible

(Andersen et al., 2016; Sandberg et al., 2013), fMRI is much better suited to answering this question at a

fine spatial scale, especially as we wish to compare the (potentially fine-grained) differences between

regions encoding either perceptual content or phenomenal magnitude.

Participants

Thirty-seven participants took part in the study. Eight participants were excluded from our analyses. One

was excluded because they quit the experiment early, and another because they failed to follow task

instructions. The final six subjects were excluded because they did not have at least 10 trials in each

visibility rating class after our grouping procedure (see *Within-subject multivariate searchlight decoding*

analysis below). Twenty-nine subjects were thus included in our final analyses (mean age = 25.35; SD =

6.31).

Stimuli

The stimuli used were taken from the POPORO stimulus data set (Kovalenko et al., 2012). The stimuli

selected were a rooster, a fish, a watering can, and a football (Figure 1D), and were selected based on

familiarity and visual difference to maximise classification performance as well as both accuracy and

visibility scores calculated in a pilot experiment run by Dijkstra et al. (2021). The mask was created by

randomly scrambling the pixel values of all stimuli combined (Figure 1C).

Procedure

The experiment consisted of two tasks: a perception task and an imagery task. Each of these tasks were

executed in interleaved blocks and were counterbalanced across participants. Our re-analysis used data only

from the perception task and thus we omit details of the imagery component of the study. The perception

task ran as follows. A stimulus was presented for only 17 ms, followed by a backward mask for 400 ms.

Participants then indicated whether the stimulus was animate or inanimate and rated the visibility of the

stimulus on a scale from 1 (not visible at all) to 4 (perfectly clear). Button response mappings were

counterbalanced across trials. The task was made up of visible and invisible trials. The difference between

these trials was the length of the interstimulus interval (ISI) between the stimulus and the mask. In the

visible trials the ISI was 66 ms, and in the invisible trials the ISI was 0 ms. In the present study, we only

analysed data from invisible trials (Figure 1C) because these were associated with the variation in the

visibility ratings that we are interested in. Choosing to focus on a single ISI also means that differences in

visibility ratings were not driven by differences in stimulus presentation characteristics. There were 184

trials in total, with 46 repetitions per stimulus divided over 4 blocks. More detailed information regarding

the study protocol can be found in (Dijkstra et al., 2021).

Acquisition

fMRI data were recorded on a Siemens 3T Skyra scanner with a Multiband 6 sequence (TR: 1 s; voxel size: 2 x 2 x 2 mm; TE: 34 ms) and a 32-channel head coil. The tilt of each participant's field of view was controlled using Siemens AutoAlign Head software, such that each participant had the same tilt relative to their head position. T1-weighted structural images (MPRAGE; voxel size: 1 x 1 x 1 mm; TR: 2.3 s) were also acquired for each participant.

Preprocessing

Data were pre-processed using SPM12 (RRID: SCR_007037). Motion correction (realignment) was performed on all functional imaging data before co-registration to the T1 structural scan. The scans were then normalised to MNI space using DARTEL normalisation and smoothed with a 6 mm Gaussian kernel, which has been shown to improve group-level decoding accuracy (Gardumi et al., 2016; Hendriks et al., 2017; Misaki et al., 2013). Slow signal drift was removed using a high pass filter of 128s.

General Linear Model

Coefficient weights were estimated per trial with a general linear model that contained a separate regressor for each trial at the onset of the stimulus convolved with the canonical HRF. Alongside nuisance regressors (average WM and CFG signals and motion parameters), the screen onset and button press of both the animacy and visibility responses were included as regressors, as well as a constant value per run to control for changes in mean signal amplitude across runs.

Within-subject multivariate searchlight decoding analysis

For decoding our fMRI data, we binarized the visibility ratings into low and high visibility classes. This is because a large number of participants failed to have enough trials reflecting each of the four visibility ratings in both animate and inanimate trials, and training a decoder on such a small number of trials would yield unreliable and noisy results. Trials were therefore sorted into low visibility and high visibility trials

on a subject-by-subject basis. This was performed as follows. The median visibility rating (from 1 to 4)

was extracted from each subject and trials with a lower visibility rating than the median were classed as

low visibility trials, and those with visibility ratings equal to or greater than the median were classed as

high visibility trials. This procedure allowed us to control for the fact that different subjects had different

distributions of visibility ratings, such that the lower 1 and 2 ratings did not always correspond to low

visibility trials, and likewise the higher 3 and 4 ratings did not always correspond to high visibility trials.

For instance, one subject may have used visibility ratings 2 and 3 in around 50% of trials, rating 4 on the

other 50%, and not used rating 1 at all. In this case, we would label ratings 2 and 3 as low visibility, and

rating 4 as high visibility.

Trials were next grouped according to whether they contained an animate or inanimate stimulus. For each

participant, if there were less than 10 trials in either the low or high visibility class for either the animate or

inanimate trials, the participant was removed. This was the case for 6 participants. The mean number of

trials per condition following this procedure were as follows (numbers in brackets denote the standard

deviation): animate-high visibility: 63.48 (11.34); animate-low visibility: 25.31 (10.38); inanimate-high

visibility: 61.10 (12.24); inanimate-low visibility: 28.86 (11.48).

We used an LDA classifier on the beta estimates per trial to decode low and high visibility ratings within

and across animate/inanimate stimulus conditions. Cross-condition decoding was performed by training the

LDA classifier on low versus high visibility ratings in animate trials and then testing it on low versus high

visibility ratings in inanimate trials, and vice versa. Cross-condition decoding was performed with the same

logic as in our MEG analysis: if we train a classifier to decode visibility ratings in animate trials and use

this classifier to successfully decode visibility ratings in inanimate trials, we can conclude the

representations of visibility ratings are similar across different perceptual content. Once again, we also

performed within-condition decoding, where the classifier was trained on low versus high ratings in one

condition (e.g., animate trials), and tested on trials in the same condition allow a direct comparison of

within- and across-condition decoding performance. This comparison allowed us to determine where

content-specific representations of phenomenal magnitude may exist in the brain. Decoding was performed

with a 5-fold cross validation scheme using L1 regularisation with a shrinkage parameter of 0.2, and, similar

to the MEG analysis, cross-validation was used for both within-condition and cross-condition decoding.

Trials were down-sampled prior to decoding, such that there was an equal number of low and high visibility

trials in each fold. To ensure that our data were sensitive enough to show content-specific codes, we

additionally ran a similar analysis that sought to decode stimulus content (animate or inanimate) rather than

visibility. This analysis was similar in structure except the classifier was trained to decode animate vs.

inanimate trials rather than visibility level.

Decoding was performed using a searchlight method. Searchlights had a radius of 4 voxels (257 voxels per

searchlight). As such, at every searchlight the classifier was trained on 257 features (one beta estimate for

each voxel in the searchlight) for each trial in every fold. The searchlights moved through the brain

according to the centre voxel, meaning that each voxel was entered into multiple searchlights. After

decoding in each searchlight, the accuracy of the classifier was averaged across folds and this value was

stored at the centre of the searchlight to produce a brain map of decoding accuracy.

Stimulus decoding in fMRI Regions of Interest (ROI)

As in the MEG analysis, we again wished to establish that findings of content-invariant awareness

representations were not due to an inability to decode content itself. We tested our ability to decode

perceptual content within two ROIs with successful visibility decoding from our searchlight results. To do

this, we created two masks, one visual and one frontal, and then selected the 200 voxels within this mask

that had the highest mean visibility decoding accuracy averaged across all four decoding directions (within

animate; within inanimate; train animate-test inanimate; train inanimate-test animate). For the frontal mask

we used a connectivity-based parcellation of the orbitofrontal cingulate cortex that spanned frontal regions

with successful visibility decoding (8m and 32d; (Neubert et al., 2015), whereas our visual mask spanned

an area with successful visibility decoding in occipital regions (VO1, VO2, PHC1, and PHC2; (Wang et

al., 2015). Using the 200 ROI voxels as features, we decoded animate (rooster and fish) versus inanimate

(watering can and football) stimuli in low and high visibility trials separately using the same 5-fold cross

validation procedure and LDA parameters as above, down-sampling trials prior to decoding to ensure an

equal number of animate and inanimate trials in each fold.

Group-level statistical inference

Distributions of accuracy values from classification of fMRI data are often non-Gaussian and asymmetric

around chance level. This means that parametric statistical comparisons, such as t-tests against chance

decoding (50%), are unable to provide valid tests of whether group-level accuracy values are significant

(Stelzer et al., 2013). Therefore, to determine where classifiers had performed significantly above chance,

we compared mean performance across all participants with a null distribution created by first permuting

the class labels 25 times prior to decoding per participant and then using bootstrapping to form a group-

level null distribution of 10,000 bootstrapping samples (Stelzer et al., 2013). We did this separately for each

decoding direction (within: train and test on animate; train and test on inanimate; cross: train on animate,

test on inanimate; train on inanimate, test on animate). To perform statistical inference on an average cross-

decoding map created by averaging the two cross-condition decoding directions, this average map was

compared to a group-level null distribution formed by averaging the two null distributions created for the

two separate maps. To compare within-condition and cross-condition classification performance, a group-

level null distribution was formed by taking the difference between cross and within decoding scores

throughout the bootstrapping procedure. To control for multiple comparisons in the searchlight analysis,

resulting p values were subsequently corrected for multiple comparisons with a false discovery rate of 0.01.

Results

Representational structure of phenomenal magnitude in whole-brain MEG data

We used RSA to test whether awareness level was encoded independently of perceptual content, and whether different awareness levels exhibited the distance effects associated with graded analogue magnitude codes (Figure 2A). A model instantiating graded and abstract representations of awareness significantly predicted the neural data throughout most of the post-stimulus period (purple line; Figure 2B). In contrast, a model with an abstract but discrete representational structure was only able to predict the neural data in an early phase of the trial between approximately 100 to 500 milliseconds after stimulus onset (green line). Paired comparisons between these two models showed that the Abstract-Graded model was significantly better at predicting the neural data than the Abstract-Discrete model throughout the majority of the trial (purple and green dots). Interestingly, the Specific-Graded model was unable to predict the neural data at any point throughout the trial (gold line), and likewise the Abstract-Graded model was found to be significantly better at predicting the neural data than the Specific-Graded model in a direct comparison (purple and yellow dots). To assess the spatial distribution of Abstract-Graded signals across sensors, we repeated the analysis for frontal and occipital sensors separately (following Hu et al., 2018), finding similar results in each case (Figure 2S1). These results indicate that neural correlates of phenomenal magnitude generalise over perceptual content and exhibit distance effects indicative of neural populations tuned to specific degrees of phenomenal magnitude with overlapping tuning curves. We found similar results when applying this RSA to data in which the contrast of the stimuli was regressed out (Figure 2S2), suggesting that our findings are unlikely to be driven by variation in bottom-up stimulus strength.

To ensure that the neural data did not exhibit spuriously high similarity with the Abstract-Graded model in virtue of its increased variance and reduced frequency when compared to the Abstract-Discrete model, we performed a shuffling and blending control analysis (Figure 2C). This procedure revealed no significant

480   prediction of the neural data for either the shuffled-discrete or shuffled-graded RDMs (Figure 2D),

481   suggesting that the Abstract-Graded model successfully captured graded and content-invariant

482   representations of awareness in neural data, and not just a frequency and variance profile that happened to

483   match that of the Abstract-Graded RDM.

Figure 2. Neural Representations of Phenomenal Magnitude are Abstract and Graded. A: *From left*
to right: Abstract-Graded model where neural correlates of awareness ratings are independent of perceptual
content and follow a graded structure; Abstract-Independent model where awareness ratings are
independent of perceptual content but do not follow a graded structure; Specific-Graded model where
awareness ratings are specific to the perceptual content to which they relate and follow a graded structure;

Specific-Discrete (Null hypothesis) model where there is no observable representational structure amongst

awareness ratings (PAS ratings, NE: No Experience, WG: Weak Glimpse, ACE: Almost Clear Experience,

CE: Clear Experience). **B**: RSA reveals that the Abstract-Graded model was the best predictor of the

representational structure of neural patterns in whole-brain sensor-level MEG data. Solid horizontal lines

represent time points significantly different from 0 for a specific RDM at $p < .05$, corrected for multiple

comparisons. Horizontal dots denote statistically significant paired comparisons between the different

models at $p < .05$, corrected for multiple comparisons. We replicated this analysis across occipital (Figure

2S1A) and frontal (Figure 2S1B) sensors separately, as well as on datasets with stimulus contrast level

regressed out (Figure 2S2) and without baseline correction (Figure 2S4). We also examined the pattern of

classifier mistakes during cross-stimulus decoding, again revealing distance-like effects in phenomenal

magnitude decoding (Figure 2S3). **C:** Shuffling and blending procedure. This analysis was performed to

control for naturally occurring low-frequency content in neural data. **D:** Results from both shuffled models

reflect the average Kendall's Tau over 1000 shuffling permutations. Purple, red, and blue lines represent

similarity of the Abstract-Graded, shuffled-discrete, and shuffled-graded models respectively with neural

data. The shuffled-discrete line varies only slightly from 0 and is thus hard to see. The Abstract-Graded

model is the only model under consideration that significantly predicted the neural data.

To further demonstrate the graded representational structure of phenomenal magnitude, we computed

confusion matrices between each rating and its neighbours. By plotting the proportion of predictions for

each awareness rating made by the multiclass classifier separately for trials of each rating, we can visualise

when our decoder makes mistakes, and which PAS ratings it most often confuses (Figure 2S3). These

confusion plots confirm the distance effects identified with the RSA model comparison, in which

neighbouring PAS ratings are most often confused with each other by the classifier, and more distant ratings

less so, suggesting that phenomenal magnitude is represented in a graded, ordinal manner.

Finally, we asked whether our model RDMs could also predict pre-stimulus neural activity. If a graded,

abstract structure for phenomenal magnitude is already evident prior to stimulus presentation, this would

suggest that trial to trial fluctuations in attention or arousal may contribute to our ability to decode content-

invariant phenomenal magnitude signals. Interpreting (a lack of) pre-stimulus decoding from our initial

RSA is not possible due to the baseline correction procedure applied during pre-processing. To address this

concern, we re-ran our analysis on data that had not been baseline corrected. We found that pre-stimulus

activity was not captured by any of the candidate RDMs, and that stimulus-triggered responses displayed

the same graded/abstract pattern of results as in our initial analysis (Figure 2S4). Together these results

indicate that pre-trial fluctuations in attention and/or arousal are unlikely to explain our findings.

Temporal profile of phenomenal magnitude codes

Next, we performed a temporal generalisation analysis to further unpack the content-invariant nature of

phenomenal magnitude codes and to characterize how and whether their patterns change from timepoint to

timepoint. Off-diagonal panels in Figure 3 (top right and bottom left) depict temporal generalisation

matrices for both directions of cross-condition decoding (top-right: train on squares-test on diamonds;

bottom-left: train on diamonds-test on squares). Within these panels, above-chance decoding on the major

diagonal indicates that representations of phenomenal magnitude begin to show content-invariance from

just after stimulus onset up until the moment of report. Contrasting cross-condition decoding with within-

condition decoding resulted in no significant differences in decoding accuracy for either comparison (train

on squares, test on diamonds vs. within squares: all $p > 0.89$; train on diamonds, test on squares vs. within

diamonds: all $p > 0.4$). In other words, there were no time points where content-specific phenomenal

magnitude information was available for classification, over and above content-invariant information.

Furthermore, the lack of off-diagonal decoding in each temporal generalisation matrix indicates that the

format of neural signatures of content-invariant magnitude change rapidly over time.

Figure 3. Abstract Representations of Phenomenal Magnitude Evolve Rapidly Over Time. Main figure: Temporal generalisation results for the classification of PAS ratings from MEG data (4 PAS responses; chance = 0.25). For each row, statistical comparisons between the two columns showed no significant differences in decoding accuracy between within- and cross-condition decoding. Non-translucent regions within solid lines highlight above chance decoding, as revealed by cluster-based permutation tests. We replicated these findings in non-baseline-corrected data (Figure 3S1).

We again replicated this analysis in a dataset that had not undergone baseline correction to test whether activity contributing to participants' awareness ratings could be decoded prior to stimulus presentation. In

line with our RSA analysis on this dataset, we could not decode awareness ratings prior to stimulus

presentation when data had not been baseline-corrected (Figure 3S1).

Content-invariant representations are found across visual, parietal, and frontal cortex

To identify the brain regions covarying with changes in phenomenal magnitude, we re-analysed an existing

fMRI dataset (Dijkstra et al., 2021). We used a searchlight approach to identify brain regions that represent

perceptual visibility in an abstract manner. Both cross-condition and within-condition decoding resulted in

above chance accuracy in a number of regions across the visual, parietal, and frontal cortex (Figure 4). We

compared cross-condition decoding to within-condition decoding in both animate and inanimate trials

(training on animate trials vs. within animate trials; training on inanimate trials vs. within inanimate trials)

to assess whether representations of perceptual visibility were stimulus-dependent in certain areas of the

brain, finding no significant differences. This suggests that there is no stimulus-specific information

encoding stimulus visibility over and above the stimulus-invariant information that is decoded by our

classifiers. See Table S1 for details of the clusters of accuracy scores found to be significantly above chance

in both cross-condition and within-condition decoding analyses.

Figure 4. Abstract Representations of visibility are found across visual, parietal, and frontal cortex.

Searchlight decoding in fMRI data revealed significantly above chance accuracy in both cross and within-

condition decoding of visibility ratings. Clusters of successful decoding were found across large regions of

the frontal, parietal, and visual cortex. Our statistical comparison of cross and within-condition decoding

accuracy revealed no significant differences anywhere in the brain. Significance was assessed at p < .05,

corrected for multiple comparisons with an FDR of 0.01. Clusters are reported in Table S1.

Stimulus content can be decoded from both MEG and fMRI data on high visibility trials

We next explored the possibility that a content-invariant magnitude code may be obtained because of

insufficient sensitivity to perceptual content in our dataset. To address this, we sought to decode stimulus

identity, rather than visibility level. Stimulus decoding was above chance in both datasets for high

visibility trials. In the MEG data, we were able to decode stimulus identity (square vs. diamond) in trials

in which participants used the upper two PAS ratings (ACE/CE), but not when participants used the lower

two PAS ratings (NE/WG; Figure 5A). Similarly, in the fMRI data, the decoding of animate vs. inanimate

stimuli was significantly above chance in a visual cortical ROI during trials reported as high visibility

(mean accuracy = 0.52; p = 0.007) but not in trials reported as low visibility (mean accuracy = 0.496; p =

0.655; Figure 5B). It was not possible to decode stimulus content from a frontal cortical ROI in either low

(mean accuracy = 0.5; p = 0.406) or high visibility trials (mean accuracy = 0.507; p = 0.159).

Stimulus Content and Visibility are Encoded in Dissociable Brain Regions

Although perceptual content could be decoded from high visibility trials (Figure 5A, 5B), it is still unclear

how these content representations relate to the abstract encoding of stimulus visibility (Figure 4). For

instance, it may be that abstract signals reflecting visibility, particularly in the visual cortex, arise from

distinct content-specific representations sharing features that co-vary with visibility.

To further probe the relationship between content representations and abstract representations of

visibility, we ran a searchlight decoding procedure to decode animate versus inanimate stimuli in our

fMRI data. Since content could only be decoded in high visibility trials in our ROI analysis (Figure 5B),

we restricted the analysis to these trials. We then compared the overlap between the content-decoding

searchlight and the content-invariant visibility searchlight maps. To do this we computed mean content

cross-decoding accuracy averaged over the two cross-decoding directions (train on animate, test on

inanimate; train on inanimate, test on animate) prior to group-level inference (see Methods).

Overall, there was minimal overlap between representations of content and abstract representations of

visibility (Figure 5C). Despite overlapping clusters being obtained in the superior and inferior lateral

occipital cortex (see Table S2 for full list of individual and overlapping clusters), a clear anatomical

distinction in occipital regions can be seen between representations of stimulus content and abstract

representations of visibility, with the former being decoded from more lateral regions of the occipital

cortex, while the latter was decoded closer to the medial surface (Figure 5C, Table S2). As expected,

stimulus content was less well decoded from frontal regions, whereas here content-invariant

representations of visibility were more abundant (Hatamimajoumerd et al., 2022). Distinct decoding

patterns for content and visibility representations further strengthens the notion that content-invariant

representations of visibility exist independently of perceptual content, even in regions typically associated

with the encoding of stimulus content such as the visual cortex (Kamitani & Tong, 2005; Kriegeskorte et

al., 2008; Mazor et al., 2022).

Figure 5. Perceptual Content Can Be Decoded in High Visibility Trials and is Encoded Separately

From Visibility. A: Decoding of perceptual content on each trial (squares or diamonds) from
participants' whole-brain sensor-level MEG data for low visibility (NE and WG) and high visibility (ACE
and CE) trials separately. Successful decoding was possible in high visibility trials up to approximately
700ms post-stimulus onset. Lines are smoothed using a Gaussian-weighted moving average with a
window of 20 ms. Shaded area denotes 95% confidence intervals. The solid horizontal line reflects above-
chance decoding, as revealed by cluster-based permutation tests. **B**: Decoding of perceptual content on
each trial (animate or inanimate) from participants' fMRI data for low visibility and high visibility trials
separately. Decoding was successful in a visual ROI in high but not low visibility trials, and unsuccessful
in a frontal ROI. Asterisks denote significance at p < .01. Error bars illustrate 95% confidence intervals.

C: Searchlight decoding accuracy for content decoding in high visibility trials (blue) and for content-

invariant visibility decoding (red). Clusters illustrate areas where content or content-invariant visibility

could be decoded significantly above chance. Content-invariant representations of visibility were more

widespread than content representations and extended into the prefrontal cortex, whereas both content and

visibility could be decoded in distinct locations of the visual cortex. Significance was assessed at $p < .05$,

corrected for multiple comparisons with an FDR of 0.01. Clusters are reported in Table S2.

Discussion

Here we explored the representational structure of phenomenal magnitude codes by applying multivariate analyses to MEG and fMRI datasets in which participants rated graded differences in their awareness of visual stimuli. Our results suggest that phenomenal magnitude is represented in a similar way across different stimulus content and exhibits signatures of an ordered and graded magnitude code, similar to that previously documented in other domains such as number. Furthermore, the neural representations of phenomenal magnitude seem to change rapidly over time and are localized across visual, parietal, and frontal cortices. Overall, our results align with recent "sparse" theories of consciousness in which low-dimensional and content-invariant representations monitor the statistical properties of first-order perceptual states (Fleming, 2020; Lau, 2019; Webb & Graziano, 2015)

The identification of content invariant representations of phenomenal magnitude (Figure 2) is in line with recent work highlighting a dissociation between neural correlates of awareness and perceptual content (Levinson et al., 2021; Mazor et al., 2022; Podvalny et al., 2019; Sanchez et al., 2020). For example, Sanchez et al. (2020) found neural patterns that indicated whether an individual was aware of a stimulus or not, irrespective of which sensory modality it was presented in. Likewise, Mazor et al. (2022) reported that, while stimulus identity was best decoded from occipital regions, stimulus visibility could be effectively decoded from a wider range of areas including the parietal and frontal cortex. Here we build on these findings by showing that the structure of awareness ratings themselves – ranging from the absence of an experience of particular content, to a clear and vivid experience – are both content-invariant and analogue-magnitude-like.

The finding that neural representations of awareness ratings display a distance effect (Figure 2; Figure 2S3) suggests that the encoding of phenomenal magnitude relies on similar schemes to those used to encode

magnitude in other domains. Specifically, our results are consistent with the notion that distributed

populations of neurons are tuned to specific phenomenal magnitudes, in the same way that specific

populations of neurons are sensitive to certain numerical magnitudes, for example (Harvey et al., 2013;

Kutter et al., 2018; Piazza et al., 2004). Such a prediction could be validated in the future by collecting

single-unit recordings from human patients while they provide subjective awareness ratings (Pereira et al.,

2021). Intriguingly, similar to our findings of content-invariant awareness codes, representations of

numerical magnitude have also been found to generalize over stimulus features (Nieder, 2012; Piazza et al.,

2007; Ramirez-Cardenas et al., 2016; Teichmann et al., 2018), as well as also extending across the visual,

parietal, and frontal cortex (Harvey & Dumoulin, 2017). Given the similarities between the encoding of

magnitude in both phenomenal and other domains, it is tempting to speculate as to the domain-generality

of such codes. A variety of magnitudes have been shown to rely on domain-general representations (Luyckx

et al., 2019; Pinel et al., 2004; Yallak & Balcı, 2021), prompting the hypothesis that a domain-general

analogue representation is responsible for encoding low-dimensional quantities in the brain (Summerfield

et al., 2020; Walsh, 2003). Therefore, an intriguing possibility is that phenomenal magnitude is represented

using a similar scheme as that used for encoding quantities in other cognitive domains. Future work could

explore this hypothesis by assessing whether phenomenal magnitude shares neural resources with other

analogue magnitude codes such as those for reward or number (Luyckx et al., 2019).

The existence of stimulus-independent representations of phenomenal magnitude in visual cortical areas

(Figure 4) was unexpected, since these areas typically encode stimulus features rather than awareness level

(Kamitani & Tong, 2005; Kriegeskorte et al., 2008; Mazor et al., 2022). One concern is that a putative

content-invariant magnitude signal in visual areas may be a consequence of insufficient power to detect

stimulus-specific effects. Specifically, neural representations of visibility ratings as revealed by decoding

analyses may look similar across stimuli if content-specific information encoded in separate neural

populations is treated as belonging to the same population (i.e. within the same voxel). Successful cross-

stimulus decoding of visibility ratings could then occur by way of decoding the amplitude of (content-

specific) neural responses in these voxels (Fisch et al., 2009; Moutoussis & Zeki, 2002). In a control

analysis, we weaken support for this alternative account by showing that stimulus-specific decoding

remains possible specifically in visual areas on high- (but not low-) visibility trials (Figure 5A; Figure 5B),

suggesting that the abstract nature of phenomenal magnitude representations in this region is not due to a

lack of power to detect stimulus-specific effects. Moreover, we show anatomical distinctions between

content and magnitude encoding (Figure 5C), again underlining that the unexpected above-chance decoding

of phenomenal magnitude in the visual cortex is unlikely to be an artefact of a failure to detect content-

specific representations.

Another possibility is that content-invariant signals of phenomenal magnitude in visual cortex reflect pre-

stimulus activations that have been shown to contribute to participants' awareness level in previous studies

(Podvalny et al., 2019). Here we were unable to decode pre-stimulus contributions to phenomenal

magnitude codes in our non-baseline-corrected MEG data (Figure 3S2), implying that the graded and

content-invariant representations we report here are largely stimulus-triggered. It remains possible that

stimulus-triggered changes in attention and/or arousal levels lead to modulations of phenomenal magnitude

and therefore awareness ratings, and that such changes contribute to the success of cross-stimulus decoding

(across visual and frontal regions). However, our results do suggest that the content-invariant signals related

to awareness level in the current data are distinct to those reported by Podvalny *et al*. in temporal profile,

and it remains to be seen how both pre- and post-stimulus neural changes contribute to fluctuations in

(content-specific and content-invariant) awareness levels.

It is worth noting that fluctuations in attention, arousal, and other psychological factors affecting the

intensity of experience (such as emotional state or motivation) should not be seen as orthogonal to, or

confounds of, phenomenal magnitude signals. Indeed, in sparse accounts of consciousness, there is a close

relationship between attention-like processes (e.g. the monitoring of the precision or reliability of first-order

perceptual content (Feldman & Friston, 2010)), and the phenomenal magnitude attached to that content

(Lau, 2019; Fleming, 2020; Graziano, 2013). Notably, however, phenomenal magnitude and attention are

related but conceptually distinct (Morales, 2018), and can be cleanly dissociated in a number of interesting

cases (Davidson et al., 2020; Kentridge et al., 2008; Wyart & Tallon-Baudry, 2008). Indeed, empirical

phenomena such as visual analgesia (Longo et al., 2009) illustrate how increased attention can sometimes

result in the magnitude of an experience being reduced, further supporting a distinction between attention

and phenomenal magnitude. As noted above, in the current study we were not able to disentangle the

contributions of attention and arousal to phenomenal magnitude fluctuations. However, the fact that neural

signatures of abstract, graded phenomenal magnitude are stimulus-triggered in the current study is at least

inconsistent with an explanation in terms of slower fluctuations in (global) attention or arousal. Instead, it

is likely that the abstract and graded phenomenal magnitude code we investigate here is a distinct

computational construct, with arousal, attention, and other cognitive and perceptual factors contributing to

its formation (Morales, 2021). Future work should seek to clarify the relationship between these constructs,

as has been done previously in distinguishing the neural basis of decision confidence and phenomenal

magnitude (Mazor et al., 2022). Such a project will be greatly aided by a precise computational definition

of both attention and phenomenal magnitude, for instance in terms of the monitoring of perceptual precision

(Whyte & Smith, 2021).

The fact that decoding of stimulus content was superior in high visibility compared to low visibility trials

(Figure 5A; Figure 5B) in both datasets is in line with previous work (Levinson et al., 2021) and is consistent

with an asymmetric factorisation between neural representations of awareness and content (Fleming, 2020).

Specifically, low-awareness states share similar content-specific neural representations (i.e., being unaware

of a square is psychologically similar to being unaware of a diamond because in both cases there is no

content), but high-awareness states are (usually, but not necessarily) accompanied by differentiation

between specific contents. In this way, classifiers should struggle to distinguish between neural

representations of low-visibility content because such representations are relatively similar in a neural state

space. In contrast, high-visibility perceptual content should be easily decodable since it is usually

represented distinctly. This asymmetry is a natural consequence of the hierarchical scheme employed by

some sparse models of consciousness, in which phenomenal magnitude is determined (in part) via the

monitoring of content-invariant features of a first-order model of perceptual content, such as signal-to-noise

level or precision (Fleming, 2020; Lau, 2019). Notably, however, stimulus-specific decoding analyses do

not shed light on how perceptual content is itself represented – only that it can be decoded. Investigating

this question will require more detailed coverage of perceptual quality spaces, in concert with subjective

ratings (Lau et al., 2022; Vishne et al., 2022).

By applying temporal generalisation analysis to our MEG data, we were also able to reveal the dynamics

of phenomenal magnitude representations over time. This analysis indicated that neural patterns covarying

with phenomenal magnitude are unstable, changing during the course of a trial (Figure 3), consistent with

a sequence of different neural populations correlating with awareness level over time (King & Dehaene,

2014). Given that we find that phenomenal magnitude is tracked across a variety of cortical regions, such

a rapidly changing temporal profile may reflect dynamic message passing between distinct neural

populations, consistent with the reverberation of predictions and prediction errors in hierarchical generative

models. Future work to directly test this hypothesis could leverage informational connectivity analyses (e.g.

Seeliger et al., 2021) to identify the direction of information flow across interacting brain regions, or use

RSA to combine M/EEG and fMRI data collected using the same task and stimuli (Cichy et al., 2014).

Here we operationalised phenomenal magnitudes as explicit reports of visual awareness (using the PAS

scale) or visibility (Dehaene & Changeux, 2011; Fleming, 2020). It is thus not possible in the current study

to dissociate neural correlates of phenomenal experience from those underpinning reporting of that

experience (Aru et al., 2012). (Although note that response button mappings were counterbalanced in the

fMRI experiment, and in both experiments discrimination decisions were elicited prior to ratings of

awareness/visibility, making it unlikely that our results reflect motor preparation effects.) An alternative

interpretation of our results is thus that abstract and graded neural representations support metacognitive

ratings *of* awareness, rather than changes in phenomenal experience per se. Such an interpretation would

bear more strongly on the neural mechanisms of introspection than those of primary experience (Michel,

2017). Note that if the neural basis of phenomenal magnitude shares resources with introspection or

perceptual metacognition (Lau, 2019), it may not be possible to cleanly dissociate such accounts, even when

employing no-report designs, as subjects may still be introspecting or reflecting on (the magnitude of) their

experience when not required to report (Fazekas & Overgaard, 2016; Tsuchiya et al., 2015). However,

under the assumption that such processes are minimised or reduced in such conditions, comparing the

within-subject neural profile of phenomenal magnitudes in report and no-report blocks could shed light on

the relative contribution of such signals to reporting requirements. Notably, a recent study employing such

an approach found that graded changes in perceptual visibility could be reliably decoded from the prefrontal

cortex in the absence of report, consistent with a contribution of this region to phenomenal magnitude

(Hatamimajoumerd et al., 2022).

In summary, we show that the neural encoding of phenomenal magnitude is supported by content-

invariant representations that exhibit graded distance effects similar to analogue magnitude codes in other

cognitive domains. These representations are spatially distributed and rapidly evolve over time, consistent

with the flow of awareness-related information across the visual, parietal, and frontal cortices. This

pattern of results is consistent with a sparse view of the neural basis of consciousness, in which abstract

higher-order representations track the precision or reliability of first-order perceptual content (Fleming,

2020; Lau, 2019; Webb & Graziano, 2015). More broadly, our results add to growing evidence for a

content-invariant neural component contributing to the strength of conscious experience, and indicate a

role for tuned neural populations supporting distinct degrees of phenomenal magnitude.

References

Albers, A. M., Kok, P., Toni, I., Dijkerman, H. C., & de Lange, F. P. (2013). Shared Representations for

Working Memory and Mental Imagery in Early Visual Cortex. *Current Biology*, *23*(15), 1427–

1431. https://doi.org/10.1016/J.CUB.2013.05.065

Andersen, L. M., Pedersen, M. N., Sandberg, K., & Overgaard, M. (2016). Occipital MEG Activity in the

Early Time Range (<300ms) Predicts Graded Changes in Perceptual Consciousness. *Cerebral*

Cortex, *26*(6), 2677–2688. https://doi.org/10.1093/cercor/bhv108

Aru, J., Bachmann, T., Singer, W., & Melloni, L. (2012). Distilling the neural correlates of consciousness.

Neuroscience and Biobehavioral Reviews, *36*(2), 737–746.

https://doi.org/10.1016/j.neubiorev.2011.12.003

Bartoshuk, L. M., Rifkin, B., Marks, L. E., & Bars, P. (1986). Taste and aging. *Journals of Gerontology*,

41(1), 51–57. https://doi.org/10.1093/geronj/41.1.51

Behrens, T. E. J., Muller, T. H., Whittington, J. C. R., Mark, S., Baram, A. B., Stachenfeld, K. L., &

Kurth-Nelson, Z. (2018). What Is a Cognitive Map? Organizing Knowledge for Flexible

Behavior. *Neuron*, *100*(2), 490–509. https://doi.org/10.1016/J.NEURON.2018.10.002

Bellmund, J. L. S., Gärdenfors, P., Moser, E. I., & Doeller, C. F. (2018). Navigating cognition: Spatial

codes for human thinking. *Science*, *362*(6415), eaat6766. https://doi.org/10.1126/science.aat6766

Benwell, C. S. Y., Tagliabue, C. F., Veniero, D., Cecere, R., Savazzi, S., & Thut, G. (2017). Prestimulus

EEG Power Predicts Conscious Awareness But Not Objective Visual Performance. *ENeuro*, *4*(6).

https://doi.org/10.1523/ENEURO.0182-17.2017

Bernardi, S., Benna, M. K., Rigotti, M., Munuera, J., Fusi, S., & Salzman, C. D. (2020). The Geometry of

Abstraction in the Hippocampus and Prefrontal Cortex. *Cell*.

https://doi.org/10.1016/j.cell.2020.09.031

Brown, R. (2015). The HOROR Theory of Phenomenal Consciousness. *Philosophical Studies*, *172*(7),

1783–1794. https://doi.org/10.1007/S11098-014-0388-7

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space and time.

Nature Neuroscience, *17*(3), 455–462. https://doi.org/10.1038/nn.3635

Cleeremans, A., Achoui, D., Beauny, A., Keuninckx, L., Martin, J. R., Muñoz-Moldes, S., Vuillaume, L.,

& de Heering, A. (2020). Learning to Be Conscious. *Trends in Cognitive Sciences*, *24*(2), 112–

123. https://doi.org/10.1016/j.tics.2019.11.011

Davidson, M. J., Mithen, W., Hogendoorn, H., van Boxtel, J. J. A., & Tsuchiya, N. (2020). The ssvep

tracks attention, not consciousness, during perceptual filling-in. *ELife*, *9*, 1–26.

https://doi.org/10.7554/eLife.60031

Dehaene, S., & Changeux, J. P. (2011). Experimental and Theoretical Approaches to Conscious

Processing. *Neuron*, *70*(2), 200–227. https://doi.org/10.1016/j.neuron.2011.03.018

Dehaene, S., Dehaene-Lambertz, G., & Cohen, L. (1998). Abstract representations of numbers in the

animal and human brain. *Trends in Neurosciences*, *21*(8), 355–361.

https://doi.org/10.1016/S0166-2236(98)01263-6

Dijkstra, N., Gaal, S. van, Geerligs, L., Bosch, S. E., & Gerven, M. A. J. van. (2021). No Evidence for

Neural Overlap between Unconsciously Processed and Imagined Stimuli. *ENeuro*, *8*(5),

ENEURO.0228-21.2021. https://doi.org/10.1523/ENEURO.0228-21.2021

Dijkstra, N., Mostert, P., de Lange, F. P., Bosch, S., & van Gerven, M. A. J. (2018). Differential temporal

dynamics during visual imagery and perception. *ELife*, *7*, 1–16.

https://doi.org/10.7554/eLife.33904

Eiselt, A. K., & Nieder, A. (2016). Single-cell coding of sensory, spatial and numerical magnitudes in

primate prefrontal, premotor and cingulate motor cortices. *Experimental Brain Research*, *234*(1),

241–254. https://doi.org/10.1007/s00221-015-4449-8

Fazekas, P., & Overgaard, M. (2016). Multidimensional Models of Degrees and Levels of Consciousness.

Trends in Cognitive Sciences, *20*(10), 715–716. https://doi.org/10.1016/j.tics.2016.06.011

Fisch, L., Privman, E., Ramot, M., Harel, M., Nir, Y., Kipervasser, S., Andelman, F., Neufeld, M. Y.,

Kramer, U., Fried, I., & Malach, R. (2009). Neural 'Ignition': Enhanced Activation Linked to

Perceptual Awareness in Human Ventral Stream Visual Cortex. *Neuron*, *64*(4), 562–574.

https://doi.org/10.1016/j.neuron.2009.11.001

Fleming, S. M. (2020). Awareness as inference in a higher-order state space. *Neuroscience of*

Consciousness, *2020*(1). https://doi.org/10.1093/nc/niz020

Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., Flesch, T., Juechems, K., Dumbalska, T., Saxe, A., &

Summerfield, C. (2022). Article Orthogonal representations for robust context- dependent task

performance in brains and neural networks Orthogonal representations for robust context-

dependent task performance in brains and neural networks. *Neuron*, 1–13.

https://doi.org/10.1016/j.neuron.2022.01.005

Gardumi, A., Ivanov, D., Hausfeld, L., Valente, G., Formisano, E., & Uludağ, K. (2016). The effect of

spatial resolution on decoding accuracy in fMRI multivariate pattern analysis. *NeuroImage*, *132*,

32–42. https://doi.org/10.1016/J.NEUROIMAGE.2016.02.033

Graziano, M. S. A. (2013). *Consciousness and the Social Brain*. Oxford University Press.

Harvey, B. M., & Dumoulin, S. O. (2017). A network of topographic numerosity maps in human

association cortex. *Nature Human Behaviour*, *1*(2). https://doi.org/10.1038/s41562-016-0036

Harvey, B. M., Dumoulin, S. O., Fracasso, A., & Paul, J. M. (2020). A Network of Topographic Maps in

Human Association Cortex Hierarchically Transforms Visual Timing-Selective Responses.

Current Biology, *30*(8), 1424-1434.e6. https://doi.org/10.1016/j.cub.2020.01.090

Harvey, B. M., Klein, B. P., Petridou, N., & Dumoulin, S. O. (2013). Topographic Representation of

Numerosity in the Human Parietal Cortex. *Science*, *341*(6150), 1123–1126.

https://doi.org/10.1126/science.1240405

Hatamimajoumerd, E., Ratan Murty, N. A., Pitts, M., & Cohen, M. A. (2022). Decoding perceptual

awareness across the brain with a no-report fMRI masking paradigm. *Current Biology*.

https://doi.org/10.1016/j.cub.2022.07.068

Hendriks, M. H. A., Daniels, N., Pegado, F., & Op de Beeck, H. P. (2017). The Effect of Spatial

Smoothing on Representational Similarity in a Simple Motor Paradigm. *Frontiers in Neurology*,

0(MAY), 222. https://doi.org/10.3389/FNEUR.2017.00222

Hu, Y., Yin, C., Zhang, J., & Wang, Y. (2018). Partial least square aided beamforming algorithm in

magnetoencephalography source imaging. *Frontiers in Neuroscience*, 616.

Hume, D. (2000). *1739. A treatise of human nature, ed. DF Norton and MJ Norton*. Oxford: Oxford

University Press.

Itti, L., & Baldi, P. (2009). Bayesian surprise attracts human attention. *Vision Research*, *49*(10), 1295–

1306. https://doi.org/10.1016/j.visres.2008.09.007

Kamitani, Y., & Tong, F. (2005). Decoding the visual and subjective contents of the human brain. *Nature

Neuroscience*, *8*(5), 679–685. https://doi.org/10.1038/nn1444

Kentridge, R. W., Nijboer, T. C. W., & Heywood, C. A. (2008). Attended but unseen: Visual attention is

not sufficient for visual awareness. *Neuropsychologia*, *46*(3), 864–869.

https://doi.org/10.1016/j.neuropsychologia.2007.11.036

King, J.-R., & Dehaene, S. (2014). Characterizing the dynamics of mental representations: The temporal

generalization method. *Trends in Cognitive Sciences*, *18*(4), 203–210.

https://doi.org/10.1016/J.TICS.2014.01.002

Kovalenko, L. Y., Chaumon, M., & Busch, N. A. (2012). A pool of pairs of related objects (POPORO)

for investigating visual semantic integration: Behavioral and electrophysiological validation.

Brain Topography, *25*(3), 272–284. https://doi.org/10.1007/S10548-011-0216-8

Kriegeskorte, N., & Kievit, R. A. (2013). Representational geometry: Integrating cognition, computation,

and the brain. *Trends in Cognitive Sciences*, *17*(8), 401–412.

https://doi.org/10.1016/J.TICS.2013.06.007

Kriegeskorte, N., Mur, M., Ruff, D. A., Kiani, R., Bodurka, J., Esteky, H., Tanaka, K., & Bandettini, P.

A. (2008). Matching Categorical Object Representations in Inferior Temporal Cortex of Man and

Monkey. *Neuron*, *60*(6), 1126–1141. https://doi.org/10.1016/j.neuron.2008.10.043

Kutter, E. F., Bostroem, J., Elger, C. E., Mormann, F., & Nieder, A. (2018). Single Neurons in the Human

Brain Encode Numbers. *Neuron*, *100*(3), 753-761.e4.

https://doi.org/10.1016/j.neuron.2018.08.036

Lamme, V. A. F. (2006). Towards a true neural stance on consciousness. *Trends in Cognitive Sciences*,

10(11), 494–501. https://doi.org/10.1016/J.TICS.2006.09.001

Lamme, V. A. F., & Roelfsema, P. R. (2000). The distinct modes of vision offered by feedforward and

recurrent processing. *Trends in Neurosciences*, *23*(11), 571–579. https://doi.org/10.1016/S0166-

2236(00)01657-X

Lau, H. C. (2019). *Consciousness, Metacognition & Perceptual Reality Monitoring*.

Lau, H., Michel, M., LeDoux, J. E., & Fleming, S. M. (2022). The mnemonic basis of subjective

experience. *Nature Reviews Psychology*. https://doi.org/10.1038/s44159-022-00068-6

Lau, H., & Rosenthal, D. (2011). Empirical support for higher-order theories of conscious awareness.

Trends in Cognitive Sciences, *15*(8), 365–373. https://doi.org/10.1016/J.TICS.2011.05.009

Ledoit, O., & Wolf, M. (2004). A well-conditioned estimator for large-dimensional covariance matrices.

Journal of Multivariate Analysis, *88*(2), 365–411. https://doi.org/10.1016/S0047-259X(03)00096-

4

Levinson, M., Podvalny, E., Baete, S. H., & He, B. J. (2021). Cortical and subcortical signatures of

conscious object recognition. *Nature Communications*, *12*(1). https://doi.org/10.1038/s41467-

021-23266-x

Longo, M. R., Betti, V., Aglioti, S. M., & Haggard, P. (2009). Visually induced analgesia: Seeing the

body reduces pain. *Journal of Neuroscience*, *29*(39), 12125–12130.

https://doi.org/10.1523/JNEUROSCI.3072-09.2009

Luyckx, F., Nili, H., Spitzer, B., & Summerfield, C. (2019). Neural structure mapping in human

probabilistic reward learning. *ELife*, *8*. https://doi.org/10.7554/eLife.42816

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data. *Journal of

Neuroscience Methods*, *164*(1), 177–190. https://doi.org/10.1016/j.jneumeth.2007.03.024

Marks, L. E., Stevens, J. C., Bartoshuk, L. M., Gent, J. F., Rifkin, B., & Stone, V. K. (1988). Magnitude-

matching: The measurement of taste and smell. *Chemical Senses*, *13*(1), 63–87.

https://doi.org/10.1093/chemse/13.1.63

Mazor, M., Dijkstra, N., & Fleming, S. M. (2022). Dissociating the Neural Correlates of Subjective

Visibility from Those of Decision Confidence. *The Journal of Neuroscience*, *42*(12), 2562–2569.

https://doi.org/10.1523/jneurosci.1220-21.2022

Michel, M. (2017). Methodological Artefacts in Consciousness Science. *Journal of Consciousness*

Studies, *24*(11–12), 94–117.

Misaki, M., Luh, W. M., & Bandettini, P. A. (2013). The effect of spatial smoothing on fMRI decoding of

columnar-level organization with linear support vector machine. *Journal of Neuroscience*

Methods, *212*(2), 355–361. https://doi.org/10.1016/J.JNEUMETH.2012.11.004

Morales, J. (2018). *The strength of the mind: Essays on consciousness and introspection*. Columbia

University.

Morales, J. (2021). Introspection Is Signal Detection. *The British Journal for the Philosophy of Science*.

https://doi.org/10.1086/715184

Moutoussis, K., & Zeki, S. (2002). The relationship between cortical activation and perception

investigated with invisible stimuli. *Proceedings of the National Academy of Sciences of the*

United States of America, *99*(14), 9527–9532. https://doi.org/10.1073/pnas.142305699

Naccache, L., Marti, S., Sitt, J. D., Trübutschek, D., & Berkovitch, L. (2016). Why the P3b is still a

plausible correlate of conscious access? A commentary on Silverstein et al., 2015. *Cortex*, *85*,

126–128. https://doi.org/10.1016/J.CORTEX.2016.04.003

Neubert, F. X., Mars, R. B., Sallet, J., & Rushworth, M. F. S. (2015). Connectivity reveals relationship of

brain areas for reward-guided learning and decision making in human and monkey frontal cortex.

Proceedings of the National Academy of Sciences of the United States of America, *112*(20),

E2695–E2704. https://doi.org/10.1073/pnas.1410767112

Nieder, A. (2012). Supramodal numerosity selectivity of neurons in primate prefrontal and posterior

parietal cortices. *Proceedings of the National Academy of Sciences of the United States of*

America, *109*(29), 11860–11865. https://doi.org/10.1073/pnas.1204580109

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N. (2014). A Toolbox

for Representational Similarity Analysis. *PLoS Computational Biology*, *10*(4).

https://doi.org/10.1371/journal.pcbi.1003553

Pereira, M., Megevand, P., Tan, M. X., Chang, W., Wang, S., Rezai, A., Seeck, M., Corniola, M.,

Momjian, S., Bernasconi, F., Blanke, O., & Faivre, N. (2021). Evidence accumulation relates to

perceptual consciousness and monitoring. *Nature Communications*, *12*(1), Article 1.

https://doi.org/10.1038/s41467-021-23540-y

Piazza, M., Izard, V., Pinel, P., Le Bihan, D., & Dehaene, S. (2004). Tuning curves for approximate

numerosity in the human intraparietal sulcus. *Neuron*, *44*(3), 547–555.

https://doi.org/10.1016/j.neuron.2004.10.014

Piazza, M., Pinel, P., Le Bihan, D., & Dehaene, S. (2007). A Magnitude Code Common to Numerosities

and Number Symbols in Human Intraparietal Cortex. *Neuron*, *53*(2), 293–305.

https://doi.org/10.1016/j.neuron.2006.11.022

Pinel, P., Piazza, M., Le Bihan, D., & Dehaene, S. (2004). Distributed and overlapping cerebral

representations of number, size, and luminance during comparative judgments. *Neuron*, *41*(6),

983–993. https://doi.org/10.1016/S0896-6273(04)00107-2

Podvalny, E., Flounders, M. W., King, L. E., Holroyd, T., & He, B. J. (2019). A dual role of prestimulus

spontaneous neural activity in visual object recognition. *Nature Communications*, *10*(1), 1–13.

https://doi.org/10.1038/s41467-019-11877-4

Ramirez-Cardenas, A., Moskaleva, M., & Nieder, A. (2016). Neuronal Representation of Numerosity

Zero in the Primate Parieto-Frontal Number Network Article Neuronal Representation of

Numerosity Zero in the Primate Parieto-Frontal Number Network. *Current Biology*, *26*, 1285–

1294. https://doi.org/10.1016/j.cub.2016.03.052

Ramsøy, T. Z., & Overgaard, M. (2004). Introspection and subliminal perception. *Phenomenology and*

the Cognitive Sciences, *3*(1), 1–23. https://doi.org/10.1023/B:PHEN.0000041900.30172.e8

Ritchie, J. B., Bracci, S., & Op de Beeck, H. (2017). Avoiding illusory effects in representational

similarity analysis: What (not) to do with the diagonal. *NeuroImage*, *148*(January), 197–200.

https://doi.org/10.1016/j.neuroimage.2016.12.079

Samaha, J., Iemi, L., & Postle, B. R. (2017). Prestimulus alpha-band power biases visual discrimination

confidence, but not accuracy. *Consciousness and Cognition*, *54*, 47–55.

https://doi.org/10.1016/j.concog.2017.02.005

Sanchez, G., Hartmann, T., Fuscà, M., Demarchi, G., & Weisz, N. (2020). Decoding across sensory

modalities reveals common supramodal signatures of conscious perception. *Proceedings of the*

National Academy of Sciences, *117*(13), 7437–7446. https://doi.org/10.1073/pnas.1912584117

Sandberg, K., Bahrami, B., Kanai, R., Barnes, G. R., Overgaard, M., & Rees, G. (2013). Early Visual

Responses Predict Conscious Face Perception within and between Subjects during Binocular

Rivalry. *Journal of Cognitive Neuroscience*, *25*(6), 969–985.

https://doi.org/10.1162/jocn_a_00353

Sassenhagen, J., & Draschkow, D. (2019). Cluster-based permutation tests of MEG/EEG data do not

establish significance of effect latency or location. *Psychophysiology*, *56*(6), 1–8.

https://doi.org/10.1111/psyp.13335

Seeliger, K., Ambrogioni, L., Gucluturk, Y., Van Den Bulk, L. M., Guclu, U., & Van Gerven, M. A. J.

(2021). End-to-end neural system identification with neural information flow. *PLoS*

Computational Biology, *17*(2), 1–22. https://doi.org/10.1371/JOURNAL.PCBI.1008558

Stelzer, J., Chen, Y., & Turner, R. (2013). Statistical inference and multiple testing correction in

classification-based multi-voxel pattern analysis (MVPA): Random permutations and cluster size

control. *NeuroImage*, *65*, 69–82. https://doi.org/10.1016/j.neuroimage.2012.09.063

Summerfield, C., Luyckx, F., & Sheahan, H. (2020). Structure learning and the posterior parietal cortex.

Progress in Neurobiology, *184*, 101717. https://doi.org/10.1016/j.pneurobio.2019.101717

Teichmann, L., Grootswagers, T., Carlson, T., & Rich, A. N. (2018). Decoding Digits and Dice with

Magnetoencephalography: Evidence for a Shared Representation of Magnitude. *Journal of*

Cognitive Neuroscience, *30*(7), 999–1010. https://doi.org/10.1162/jocn_a_01257

Treder, M. S. (2020). MVPA-Light: A Classification and Regression Toolbox for Multi-Dimensional

Data. *Frontiers in Neuroscience*, *0*, 289. https://doi.org/10.3389/FNINS.2020.00289

Tsouli, A., Harvey, B. M., Hofstetter, S., Cai, Y., van der Smagt, M. J., te Pas, S. F., & Dumoulin, S. O.

(2021). The Role of Neural Tuning in Quantity Perception. *Trends in Cognitive Sciences*, *xx*(xx),

1–14. https://doi.org/10.1016/j.tics.2021.10.004

Tsuchiya, N., Wilke, M., Frässle, S., & Lamme, V. A. F. (2015). No-Report Paradigms: Extracting the

True Neural Correlates of Consciousness. *Trends in Cognitive Sciences*, *19*(12), 757–770.

https://doi.org/10.1016/J.TICS.2015.10.002

Van Vugt, B., Dagnino, B., Vartak, D., Safaai, H., Panzeri, S., Dehaene, S., & Roelfsema, P. R. (2018).

The threshold for conscious report: Signal loss and response bias in visual and frontal cortex.

Science, *360*(6388), 537–542. https://doi.org/10.1126/science.aar7186

Vishne, G., Gerber, E. M., Knight, R. T., & Deouell, L. Y. (2022). *Representation of sustained visual*

experience by time-invariant distributed neural patterns (p. 2022.08.02.502469). bioRxiv.

https://doi.org/10.1101/2022.08.02.502469

Walsh, V. (2003). A theory of magnitude: Common cortical metrics of time, space and quantity. *Trends*

in Cognitive Sciences, *7*(11), 483–488. https://doi.org/10.1016/j.tics.2003.09.002

Wang, L., Mruczek, R. E. B., Arcaro, M. J., & Kastner, S. (2015). Probabilistic maps of visual

topography in human cortex. *Cerebral Cortex*, *25*(10), 3911–3931.

https://doi.org/10.1093/cercor/bhu277

Webb, T. W., & Graziano, M. S. A. (2015). The attention schema theory: A mechanistic account of

subjective awareness. *Frontiers in Psychology*, *6*(APR), 1–11.

https://doi.org/10.3389/fpsyg.2015.00500

Whyte, C. J., & Smith, R. (2021). The predictive global neuronal workspace: A formal active inference

model of visual consciousness. *Progress in Neurobiology*, *199*, 101918.

https://doi.org/10.1016/j.pneurobio.2020.101918

Wyart, V., & Tallon-Baudry, C. (2008). Neural dissociation between visual awareness and spatial

attention. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*,

28(10), 2667–2679. https://doi.org/10.1523/JNEUROSCI.4748-07.2008

Yallak, E., & Balcı, F. (2021). Metric error monitoring: Another generalized mechanism for magnitude

representations? *Cognition*, *210*. https://doi.org/10.1016/j.cognition.2020.104532

1021

1022

1023

1024

1025

 Supplemental Figures

Figure 2-figure supplement 1. Awareness Ratings Show Similar Representational Structure Across

Occipital and Frontal Sensors. RSA analysis performed over occipital sensors (top) and frontal sensors

(bottom) only. Purple, green, and gold lines represent similarity of the Abstract-Graded, Abstract-Discrete,

and Specific-Graded models respectively with neural data. Solid horizontal lines represent time points

significantly different from 0 for a specific RDM at $p < .05$, corrected for multiple comparisons. The

Abstract-Graded model significantly predicted the neural data throughout the majority of the trial (purple

line) across frontal sensors, and for a shorter duration when analysis was restricted occipital sensors only.

The Abstract-Discrete model was only successful at predicting the neural data across two clusters of time-

points post-stimulus when using occipital sensors, but was a significant predictor of neural data for larger

portions of the epoch when using frontal sensors. The Specific-Graded model did not significantly predict

the neural data at any time point in frontal or occipital sensors. Horizontal dots denote statistically

significant paired comparisons between the different models at $p < .05$, corrected for multiple comparisons.

Across frontal sensors, the Abstract-Graded model was a significantly better predictor of the neural data

than the Specific-Graded model, and likewise across the occipital sensors, both abstract models

significantly outperformed the Specific-Graded model. In this split-sensor analysis, the Abstract-Graded

model did not significantly outperform the Abstract-Specific model, however there was a noticeable trend

in the same direction as in the RSA performed across all sensors, where the difference in performance was

significant (Figure 2B).

1067

1068

1069

1070

1071

1072

1073

1074

Figure 2 – figure supplement 2. RSA on MEG data with stimulus contrast level regressed out. When

stimulus contrast level was regressed out of the MEG data, an RSA still produced comparable results to

the original analysis. The Abstract-Graded model still predicted the neural data better than either

alternative model. Solid horizontal lines represent time points significantly different from 0 for a specific

RDM at p <.05, corrected for multiple comparisons. Horizontal dots denote statistically significant paired

comparisons between the different models at p <.05, corrected for multiple comparisons.

1089

Figure 2 – figure supplement 3. Cross-decoding shows the graded nature of the PAS scale. For each

cross-condition decoder (A: Train on Squares; B: Train on Diamonds), the four sub-plots illustrate the

proportion of PAS ratings the classifiers decoded trials as. The subplots correspond to trials where the

true PAS rating reported by subjects were (from left to right) 'No Experience', 'Weak Glimpse', 'Almost

Clear Experience', and 'Clear Experience'. Each coloured line represents the proportion of trials

classified as each PAS rating across time. For example, in trials where participants reported No

Experience, the majority of trials were classified correctly (blue line), with the classifier most often

misclassifying these 'No Experience' trials as 'Weak Glimpse' ratings (orange line), and rarely

 misclassifying them as 'Almost Clear Experience' or 'Clear Experience' trials (gold and purple lines,

1099   respectively). Shaded areas represent 95% confidence intervals.

1100

1101   **Figure 2 – figure supplement 4. RSA analysis for MEG data without baseline correction.** None of

1102   our model RDMs significantly predicted pre-stimulus activity in non-baseline-corrected data. Instead, the

1103   predominant neural signature was stimulus triggered, as in the main analysis (Figure 2B), with the

1104   Abstract-Graded model being the best predictor of neural representations of phenomenal magnitude.

1105
1106

1107
1108

1109

1110 **Figure 3 – figure supplement 2. Temporal Generalisation matrices for MEG decoding analyses on**

1111 **data without baseline-correction.** For each row, statistical comparisons between the two columns

1112 showed no significant differences in decoding accuracy between within and cross-condition decoding.

1113 Pre-stimulus decoding of awareness ratings was not possible, even when data had not been baseline-

1114 corrected.

1115

1116

1117

1118

Decoding Type	Atlas Label	Cluster Size (voxels)	MNI Coordinates of maximum accuracy	Maximum accuracy
Cross (train animate)	Postcentral Gyrus	23,838	-46, -36, 54	0.593
Cross (train animate)	Temporal Fusiform Cortex	474	-31.5, -36.1, -25.8	0.567
Cross (train animate)	Paracingulate Gyrus	192	-8, 44, -6	0.563
Cross (train animate)	Frontal Orbital Cortex	168	-30, 34, -10	0.570
Cross (train animate)	Cingulate Gyrus, posterior division	109	4, -44, 10	0.563
Cross (train animate)	Occipital Pole	89	-22, -96, 2	0.562
Cross (train animate)	Frontal Pole	75	32, 36, -10	0.561
Cross (train animate)	Temporal Occipital Fusiform Cortex	59	20, -52, -18	0.566
Cross (train animate)	Lingual Gyrus	56	10, -38, -6	0.555
Cross (train animate)	Left Cerebral White Matter	56	-22, -38, 8	0.566
Cross (train inanimate)	Supramarginal Gyrus, anterior division	23,564	-54, -36, 30	0.593
Cross (train inanimate)	Subcallosal Cortex	512	5.85, 10.6, -6.63	0.575
Cross (train inanimate)	Left Caudate	176	-10, 2, 16	0.575

Cross (train inanimate)	Middle Temporal Gyrus, posterior division	166	-52, -42, -2	0.585
Cross (train inanimate)	Frontal Orbital Cortex	152	-32, 36, -12	0.570
Cross (train inanimate)	Left Hippocampus	106	-20, -16, -14	0.567
Cross (train inanimate)	Central Opercular Cortex	100	38, 0, 18	0.571
Cross (train inanimate)	Frontal Pole	78	22, 42, -12	0.565
Cross (train inanimate)	Insular Cortex	71	-38, -20, -4	0.564
Cross (train inanimate)	Lateral Occipital Cortex, superior division	62	32, -88, 14	0.555
Within (animate)	Cingulate Gyrus, anterior division	49,130	-2, 36, 20	0.616
Within (inanimate)	Postcentral Gyrus	32,710	62, -8, 18	0.601
Within (inanimate)	Right Caudate	79	18, 10, 16	0.565

1119

1120

1121 **Table S1. fMRI Searchlight Decoding Results.** Clusters with above chance decoding of perceptual

1122 visibility for both cross-condition and within-condition decoding. Clusters are significant at $p < .05$,

1123 corrected for multiple comparisons with an FDR of 0.01. Region names are found for the peak co-ordinate

1124 using the Harvard-Oxford Cortical and Subcortical Structural Atlas.

1125

1126

1127

Decoding Type	Atlas Label	Cluster Size (voxels)	MNI Coordinates of maximum accuracy	Maximum accuracy
Content	Inferior Lateral Occipital Cortex	2768	-48, -70, -8	0.572
Content	Cerebellum	2150	0, -48, -10	0.558
Content	Inferior Frontal Gyrus	1837	-52, 32, 6	0.556
Content	Superior Lateral Occipital Cortex	919	-40, - 58, 54	0.557
Content	Superior Lateral Occipital Cortex	907	-8, -64, 60	0.554
Content	Angular Gyrus	735	44, -52, 20	0.557
Content	Superior Parietal Lobule	626	20, -44, 62	0.548
Content	Frontal Orbital Cortex	375	38, 24, -2	0.557
Content	Paracingulate Cyrus	371	-6, 26, 34	0.547
Content	Inferior Frontal Gyrus	356	46, 20, 20	0.563
Content	Superior Frontal Gyrus	209	16, 24, 58	0.546
Content	Frontal Pole	201	-24, 42, 44	0.546

Content	Superior Temporal Gyrus	192	-54, -2, -10	0.549
Content	Postcentral Gyrus	189	-62, -22, 38	0.547
Content	Posterior Cingulate Gyrus	178	-8, -26, 44	0.547
Content	Left Cerebral White Matter	133	6, -24, 16	0.544
Content	Cerebellum	98	34, -64, -40	0.547
Content	Superior Lateral Occipital Cortex	76	20, -66, 46	0.553
Content	Anterior Cingulate Gyrus	74	6, -4, 40	0.551
Content	Parietal Operculum Cortex	56	44, -32, 20	0.546
Content	Precentral Gyrus	52	44, -16, 58	0.542
Mean Cross-Condition Visibility	Precentral Gyrus	16,638	-50, 8 32	0.584
Mean Cross-Condition Visibility	Postcentral Gyrus	2863	-50, -30, 48	0.58
Mean Cross-Condition Visibility	Right Accumbens	278	10, 14, -6	0.561

Mean Cross-Condition Visibility	Left Cerebral White Matter	167	-16, 0, 16	0.568
Mean Cross-Condition Visibility	Frontal Medial Cortex	166	-4, 48, -10	0.555
Mean Cross-Condition Visibility	Middle Temporal Gyrus	150	-52, -42, -2	0.556
Mean Cross-Condition Visibility	Central Opercular Cortex	138	-36, -10, 18	0.563
Mean Cross-Condition Visibility	Frontal Orbital Cortex	133	32, 28, 2	0.556
Mean Cross-Condition Visibility	Occipital Fusiform Gyrus	116	14, -84, -22	0.557
Mean Cross-Condition Visibility	Cerebellum	103	-28, -42, -34	0.559
Mean Cross-Condition Visibility	Frontal Orbital Cortex	95	-36, 36, -10	0.563

Mean Cross-Condition Visibility	Temporal Occipital Fusiform Cortex	91	-40, -62, -24	0.554
Mean Cross-Condition Visibility	Inferior Lateral Occipital Cortex	58	42, -80, 4	0.553
Mean Cross-Condition Visibility	Frontal Pole	58	22, 38, -12	0.557
Mean Cross-Condition Visibility	Occipital Pole	56	12, -90, -2	0.557
Mean Cross-Condition Visibility	Superior Precentral Gyrus	53	26, -12, 52	0.552
Visibility and Content Overlap	Cerebellum	1587	-6, -82, -32	N/A
Visibility and Content Overlap	Frontal Orbital Cortex	1521	-28, 16, -24	N/A
Visibility and Content Overlap	Superior Lateral Occipital Cortex	782	-32, -74, 20	N/A
Visibility and Content Overlap	Precuneous Cortex	474	-14, -58, 18	N/A
Visibility and Content Overlap	Inferior Lateral Occipital Cortex	412	46, -68, -10	N/A

Visibility and Content Overlap	Supramarginal Gyrus	383	64, -28, 34	N/A
Visibility and Content Overlap	Frontal Pole	339	40, 36, 12	N/A
Visibility and Content Overlap	Cingulate Gyrus	315	0, 36, 16	N/A
Visibility and Content Overlap	Frontal Orbital Cortex	213	36, 22, -14	N/A
Visibility and Content Overlap	Middle Frontal Gyrus	181	-24, 36, 32	N/A
Visibility and Content Overlap	Posterior Cingulate Gyrus	156	-4, -30, 36	N/A
Visibility and Content Overlap	Middle Frontal Gyrus	147	24, 28, 34	N/A
Visibility and Content Overlap	Right Cerebral Cortex	145	20, 2, -14	N/A
Visibility and Content Overlap	Cerebellum	115	26, -58, -26	N/A
Visibility and Content Overlap	Cerebellum	111	-24, -36, -38	N/A
Visibility and Content Overlap	Superior Parietal Lobule	107	34, -50, 36	N/A
Visibility and Content Overlap	Postcentral Gyrus	101	-60, -20, 24	N/A

Visibility and Content Overlap	Postcentral Gyrus	74	-36, -22, 44	N/A
Visibility and Content Overlap	Lingual Gyrus	74	-14, -56, -2	N/A
Visibility and Content Overlap	Cerebellum	63	20, -72, -32	N/A
Visibility and Content Overlap	Cerebellum	52	34, -56, -48	N/A

1128

Table S2. fMRI Searchlight Content Decoding in High Visibility Trials, Average Cross-Condition

Visibility Decoding, and Overlapping Cluster Information. *Decoding type = Content*: Clusters with

above chance decoding of perceptual content (animate vs. inanimate) in high visibility trials. *Decoding*

type = Mean Cross-Condition Visibility: Clusters with above chance decoding of perceptual visibility for

cross-condition decoding when accuracy from both decoding directions (training on animate and training

on inanimate) was averaged together. To aid the identification of individual clusters in this map,

clustering was performed at an increased accuracy threshold of 0.54. *Decoding Type = Awareness and*

Content Overlap: Clusters where decoding of content and cross-decoding of visibility were both

successful (i.e. the intersection of the Content and Mean Cross-Condition Visibility clusters). Clusters are

significant at $p < .05$, corrected for multiple comparisons with an FDR of 0.01. Region names are found

for the peak co-ordinate using the Harvard-Oxford Cortical and Subcortical Structural Atlas and the MNI

Structural Atlas.