# Visual homogeneity computations in the brain enable solving property-based visual tasks

Georgin Jacob[1,2], R. T. Pramod[1,2], and S. P. Arun[2,1]*

[1]Department of Electrical Communication Engineering & [2]Centre for Neuroscience

Indian Institute of Science, Bangalore 560012

*Correspondence to sparun@iisc.ac.in

**ABSTRACT**

Most visual tasks involve looking for specific object features. But we also often

perform property-based tasks where we look for specific property in an image, such as

finding an odd item, deciding if two items are same, or if an object has symmetry. How

do we solve such tasks? These tasks do not fit into standard models of decision making

because their underlying feature space and decision process is unclear. Using well-

known principles governing multiple object representations, we show that displays with

repeating elements can be distinguished from heterogeneous displays using a property

we define as visual homogeneity. In behavior, visual homogeneity predicted response

times on visual search, same-different and symmetry tasks. Brain imaging during visual

search and symmetry tasks revealed that visual homogeneity was localized to a region

in the object-selective cortex. Thus, property-based visual tasks are solved in a

localized region in the brain by computing visual homogeneity.

**SIGNIFICANCE STATEMENT**

Most visual tasks involve looking for specific features, like finding a face in a

crowd. But we also often look for a particular image property – such as finding an odd

item, deciding if two items are same, or judging if an object is symmetric. How does our

brain solve these disparate tasks? Here, we show that these tasks can all be solved

using a simple computation over object representations in higher visual cortex, which

we define as visual homogeneity.

 **INTRODUCTION**

Many visual tasks involve looking for specific objects or features, such as a friend

in a crowd or selecting vegetables in the market. In such tasks, which have been

studied extensively, we form a template in our brain that helps guide eye movements

and locate the target (Peelen and Kastner, 2014). This template becomes a decision

variable that can be used to solve the task: the degree of match to the template

indicates the presence or absence of the desired object (Figure 1A). However, we also

easily perform tasks that do not involve any specific feature template but rather involve

finding a property in the image. Examples of such property-based tasks are same-

different task, finding the oddball item and judging if an object has symmetry (Figure

1B). These tasks cannot be solved by looking for any particular feature, and therefore

present a major challenge for standard models of decision making since the underlying

feature space and decision variable are unknown. Even machine vision algorithms,

which are so successful at solving feature-based tasks (Serre, 2019), fail at detecting

properties like same-different and at other similar visual reasoning challenges (Fleuret

et al., 2011; Kim et al., 2018; Ricci et al., 2021; Puebla and Bowers, 2022). How do we

solve such property-based visual tasks? What are the underlying features and what is

the decision variable?

To start with, these tasks appear completely different, at least in the way we

describe them verbally. Even theoretical studies have considered visual search

(Verghese, 2001; Wolfe and Horowitz, 2017), same-different judgments (Nickerson,

1969; Petrov, 2009) and symmetry detection (Wagemans, 1997; Bertamini and Makin,

2014) as conceptually distinct tasks. However, we note that at a deeper level, these

tasks are similar because they all involve discriminating between items with repeating

features from those without repeating features. We reasoned that if images with

repeating features are somehow represented differently in the brain, this difference

could be used to solve all such tasks without requiring separate computations for each

task.

51
**Figure 1. Feature-based and property-based visual tasks**
(A) **Feature-based visual tasks.** Most visual tasks involve making decisions based
on looking at specific features. Face recognition is shown here as an example.
According to standard theories of decision making, such tasks are solved in the
brain by setting up a decision variable in a multidimensional feature space
(*arrow*), and making decisions based on whether the value of the decision
variable is larger or smaller than a decision boundary (*dashed line*).
(B) **Property-based visual tasks.** By contrast, some tasks involve detecting
properties in the image, such as a same-different task (illustrated using faces; *top*
*row*), detecting an oddball item (illustrated using *middle row*) or judging if an
object is symmetric (*bottom row*). These tasks cannot be solved by looking for
any specific feature. As a result, such tasks do not fit into standard models of
decision making since the underlying feature space and decision variable are
unknown.
66

**Key predictions**

**Key predictions**

Our key predictions are summarized in Figure 2. Consider an oddball search task

where participants have to indicate if a display contains an oddball target (Figure 2A) or

not (Figure 2B). According to the well-known principle of divisive normalization in high-

level visual cortex (Zoccolan et al., 2005; Agrawal et al., 2020; Katti and Arun, 2022),

the neural response to multiple objects is the average of the single object responses.

Accordingly, the response to an array of identical items will be the same as the

response to the single item. Similarly, the response to an array containing a target

among distractors, being a mix of images, would lie along the line joining the target and

distractor in underlying representational space. These possibilities are shown for all

possible arrays made from three objects in Figure 2C. It can be seen that the

homogeneous (target-absent) arrays naturally stand apart since they contain repeating

items, whereas the heterogeneous (target-present) arrays come closer to each other

since they contain a mixture of items. Since displays with repeating items are further

away from the center of this space, this distance can be used to discriminate them from

heterogeneous displays (Figure 2C, *inset*). While this decision process may not capture

all types of visual search, we reasoned that it could potentially guide the initial stages of

target selection.

We reasoned similarly for symmetry detection: here, participants have to decide

if an object is asymmetric (Figure 2D) or symmetric (Figure 2E). According to multiple

object normalization, objects with two different parts would lie along the line joining

objects containing the two repeated parts (Figure 2F). Indeed, both symmetric and

asymmetric objects show part summation in their neural responses (Pramod and Arun,

2018). Consequently, symmetric objects will be further away from the centre of this

space compared to asymmetric objects, and this can be the basis for discriminating

them (Figure 2F, *inset*).

We define this distance from the center for each image as its *visual homogeneity*

(VH). We made two key experimental predictions to test in behavior and brain imaging.

First, if VH is being used to solve visual search and symmetry detection tasks, then

responses should be slowest for displays with VH close to the decision boundary and

faster for displays with VH far away (Figure 2G). This predicts opposite correlations

between response time and VH: for target-present arrays and asymmetric objects, the

response time should be positively correlated with VH. By contrast, for target-absent

arrays and symmetric objects, response time should be negatively correlated with VH.

Importantly, because response times of the two choices are positively and negatively

correlated with VH, the net correlation between response time and VH will be close to

zero.

Second, if VH is encoded by a dedicated brain region, then brain activity in that

region will be positively correlated with VH (Figure 2H). Such a positive correlation

cannot be explained easily by cognitive processes linked to response time such as

attention or task difficulty, since response times will have zero correlation with the mean

activity of this region.

**Overview of this study**

The above predictions are based on computing distances in an underlying neural

representation that is the basis for other feature-based visual tasks. We drew upon the

principle that object representations in high-level visual cortex match strongly with

perceived dissimilarity measured in visual search (Sripati and Olson, 2010; Zhivago and

Arun, 2014; Agrawal et al., 2020). We therefore asked whether distance-to-center or

visual homogeneity computations, performed on object representations estimated

empirically from dissimilarity measurements, could explain the behavior and brain

imaging predictions laid out in the preceding section (Figure 2).

We performed two sets of experiments to test our key predictions. In the first set,

we measured perceptual dissimilarities on a set of grayscale natural images using

visual search (Experiment 1) and then asked whether visual homogeneity computations

on this estimated representation could explain response times as well as brain

activations during a oddball target detection task (Experiment 2). In the second set of

experiments, we measured perceptual dissimilarities between a set of silhouette images

(Experiment 3) and asked whether visual homogeneity computations on this estimated

representation could explain response times and brain activations during a symmetry

detection task (Experiment 4).

**Figure 2. Solving oddball search and symmetry tasks using visual homogeneity.**

(A) Example target-present search display, containing a single oddball target (horse) among identical distractors (dog). Participants in such tasks have to indicate whether the display contains an oddball or not, without knowing the features of the target or distractor. This means they have to perform this task by detecting some property of each display rather than some feature contained in it.

(B) Example target-absent search display containing no oddball target.

(C) Hypothesized neural computation for target present/absent judgements. According to multiple object normalization, the response to multiple items is an average of the responses to the individual items. Thus, the response to a target-absent array will be identical to the individual items, whereas the response to a target-present array will lie along the line joining the corresponding target-absent arrays. This causes the target-absent arrays to stay apart (*red lines*), and the target-present arrays to come closer due to mixing (*blue lines*). If we calculate

143 the distance (VH, for visual homogeneity) for each display, then target-absent
144 arrays will have a larger distance to the center ($VH_a$) compared to target-present
145 arrays ($VH_p$), and this distance can be used to distinguish between them. *Inset:*
146 Schematic distance from center for target-absent arrays (red) and target-present
147 arrays (blue). Note that this approach might only reflect the initial target selection
148 process involved in oddball visual search but does not capture all forms of visual
149 search.

150 (D) Example asymmetric object in a symmetry detection task. Here too, participants
151 have to indicate if the display contains a symmetric object or not, without knowing
152 the features of the object itself. This means they have to perform this task by
153 detecting some property in the display.

154 (E) Example symmetric object in a symmetry detection task.

155 (F) Hypothesized neural computations for symmetry detection. Following multiple
156 object normalization, the response to an object containing repeated parts is equal
157 the response to the individual part, whereas the response to an object containing
158 two different parts will lie along the line joining the objects with the two parts
159 repeating. This causes symmetric objects to stand apart (red lines) and
160 asymmetric objects to come closer due to mixing (*blue lines*). Thus, the visual
161 homogeneity for symmetric objects ($VH_s$) will be larger than for asymmetric
162 objects ($VH_a$). *Inset:* Schematic distance from center for symmetric objects (red)
163 and asymmetric objects (blue).

164 (G) *Behavioral predictions for VH.* If visual homogeneity (VH) is a decision variable in
165 visual search and symmetry detection tasks, then response times (RT) must be
166 largest for displays with VH close to the decision boundary. This predicts
167 opposite correlations between response time and VH for the present/absent or
168 symmetry/asymmetry judgements. It also predicts zero overall correlation
169 between VH and RT.

170 (H) *Neural predictions for VH. Left:* Correlation between brain activations and VH for
171 two hypothetical brain regions. In the VH-encoding region, brain activations
172 should be positively correlated with VH. In any region that encodes task difficulty
173 as indexed by response time, brain activity should show no correlation since VH
174 itself is uncorrelated with RT (see Panel G). *Right:* Correlation between brain
175 activations and RT. Since VH is uncorrelated with RT overall, the region VH
176 should show little or no correlation, whereas the regions encoding task difficulty
177 would show a positive correlation.

**RESULTS**

In Experiments 1-2, we investigated whether visual homogeneity computations

could explain decisions about targets being present or absent in an array. Since visual

homogeneity requires measuring distance in perceptual space, we set out to first

characterize the underlying representation of a set of natural objects using

measurements of perceptual dissimilarity.

**Measuring perceptual space for natural objects**

In Experiment 1, 16 human participants viewed arrays made from a set of 32

grayscale natural objects, with an oddball on the left or right (Figure 3A), and had to

indicate the side on which the oddball appeared using a key press. Participants were

highly accurate and consistent in their responses during this task (accuracy, mean ± sd:

98.8 ± 0.9%; correlation between mean response times of even- and odd-numbered

participants: $r = 0.91$, $p < 0.0001$ across all $^{32}C_2 = 496$ object pairs). The reciprocal of

response time is a measure of perceptual distance (or dissimilarity) between the two

images (Arun, 2012). To visualize the underlying object representation, we performed a

multidimensional scaling analysis, which embeds objects in a multidimensional space

such that their pairwise dissimilarities match the experimentally observed dissimilarities

(see Methods). The resulting two-dimensional embedding of all objects is shown in

Figure 3B. In the resulting plot, nearby objects correspond to hard searches, and far

away objects correspond to easy searches. Such representations reconstructed from

behavioural data closely match population neural responses in high-level visual areas

(Op de Beeck et al., 2001; Sripati and Olson, 2010). To capture the object

representation accurately, we took the multidimensional embedding of all objects and

treated the values along each dimension as the responses of an individual artificial

neuron. We selected the number of dimensions in the multidimensional embedding so

that the correlation between the observed and embedding dissimilarities matches the

noise ceiling in the data. Subsequently, we averaged these single object responses to

obtain responses to larger visual search arrays, as detailed below.

**Visual homogeneity predicts target present/absent judgments (Experiments 1-2)**

Having characterized the underlying perceptual representation for single objects,

we set out to investigate whether target present/absent responses during visual search

can be explained using this representation. In Experiment 2, 16 human participants

viewed an array of items on each trial, and indicated using a key press whether there

was an oddball target present or not (Figure 3C). This task was performed inside an

MRI scanner to simultaneously observe both brain activity and behaviour. Participants

were highly accurate and consistent in their responses (accuracy, mean ± sd: 95 ± 3%;

correlation between average response times of even- and odd-numbered participants: r

= 0.86, p < 0.0001 across 32 target-present searches, r = 0.63, p < 0.001 across 32

target-absent searches).

Next we set out to predict the responses to target-present and target-absent

search displays containing these objects. We first took the object coordinates returned

by multidimensional scaling in Experiment 1 as neural responses of multiple neurons.

We then used a well-known principle of object representations in high-level visual areas:

the response to multiple objects is the average of the single object responses (Zoccolan

et al., 2005; Agrawal et al., 2020). Thus, we took the response vector for a target-

present array to be the average of the response vectors of the target and distractor

(Figure 3D). Likewise, we took the response vector for a target-absent array to be equal

to the response vector of the single item. We then asked if there is any point in this

multidimensional representation such that distances from this point to the target-present

and target-absent response vectors can accurately predict the target-present and

target-absent response times with a positive and negative correlation respectively (see

Methods). Note that this model has only 5 free parameters, which are the coordinates of

this unknown point or center in multidimensional space, and this model can

simultaneously predict both target-present and target-absent judgments. We used

nonlinear optimization to find the coordinates of the center to best match the data (see

Methods).

We denoted the distance of each display to the optimized center as the visual

homogeneity. As expected, the visual homogeneity of target-present arrays was

significantly smaller than target-absent arrays (Figure 3E). The resulting model

predictions are shown in Figure 3F-G. The response times for target-present searches

were positively correlated with visual homogeneity (r = 0.68, p < 0.0001; Figure 3F). By

contrast, the response times for target-absent searches were negatively correlated with

visual homogeneity (r = -0.71, p < 0.0001; Figure 3G). This is exactly as predicted if

visual homogeneity is the underlying decision variable ( Figure 2 G). We note that the

range of visual homogeneity values for target-present and target-absent searches do

overlap, suggesting that visual homogeneity contributes but does not fully determine

task performance. Rather, we suggest that visual homogeneity provides a useful and

initial first guess at the presence or absence of a target, which can be refined further

through detailed scrutiny.

**Confirming the generality of visual homogeneity**

We performed several additional analysis to confirm the generality of our results,

and to reject alternate explanations.

First, it could be argued that our results are circular because they involve taking

oddball search times from Experiment 1 and using them to explain search response

times in Experiment 2. This is a superficial concern since we are using the search

dissimilarities from Experiment 1 only as a proxy for the underlying neural

representation, based on previous reports that neural dissimilarities closely match

oddball search dissimilarities (Sripati and Olson, 2010; Zhivago and Arun, 2014).

Nonetheless, to thoroughly refute this possibility, we reasoned that we would get similar

predictions of the target present/absent responses in Experiment using any other brain-

like object representation. To confirm this, we replaced the object representations

derived from Experiment 1 with object representations derived from deep neural

networks pretrained for object categorization, and asked if distance-to-center

computations could predict the target present/absent responses in Experiment 2. This

was indeed the case (Section S1).

Second, we wondered whether the nonlinear optimization process of finding the

best-fitting center could be yielding disparate optimal centres each time. To investigate

this, we repeated the optimization procedure with many randomly initialized starting

points, and obtained the same best-fitting center each time (see Methods).

Third, to confirm that the above model fits are not due to overfitting, we

performed a leave-one-out cross validation analysis. We left out all target-present and

target-absent searches involving a particular image, and then predicted these searches

by calculating visual homogeneity estimated from all other images. This too yielded

similar positive and negative correlations (r = 0.63, p < 0.0001 for target-present, r = -

0.63, p < 0.001  for target-absent).

Fourth, if heterogeneous displays indeed elicit similar neural responses due to

mixing, then their average distance to other objects must be related to their visual

homogeneity. We confirmed that this was indeed the case, suggesting that the average

distance of an object from all other objects in visual search can predict visual

homogeneity (Section S2).

Fifth, the above results are based on taking the neural response to oddball arrays

to be the average of the target and distractor responses. To confirm that averaging was

indeed the optimal choice, we repeated the above analysis by assuming a range of

relative weights between the target and distractor. The best correlation was obtained for

almost equal weights in the lateral occipital (LO) region, consistent with averaging and

its role in the underlying perceptual representation (Section S2).

Finally, we performed several additional experiments on a larger set of natural

objects as well as on silhouette shapes. In all cases, present/absent responses were

explained using visual homogeneity (Section S3).

**Conclusions**

These findings are non-trivial for several reasons. First, we have shown that a

specific decision variable, computed over an underlying object representation, can be

used to make target present/absent judgements, without necessarily knowing the

precise features of the target or distractor. Second, we have identified a specific image

property that explains why target-absent response times vary so systematically. If

target-distractor dissimilarity were the sole determining factor in visual search, it would

predict no systematic variation in target-absent searches since the target-distractor

dissimilarity is zero. Our results elucidate this puzzle by showing that visual

homogeneity varies systematically across images, and that this explains systematic

variation in target-absent response times. To the best of our knowledge, our model

provides for the first time a unified explanation to explain how target present/absent

judgements might be made in a generic visual search task.

In sum, we conclude that visual homogeneity can explain oddball target

present/absent judgements during visual search.

**Figure 3. Visual homogeneity predicts target present/absent responses**

(A) Example search array in an oddball search task (Experiment 1). Participants viewed an array containing identical items except for an oddball present either on the left or right side, and had to indicate using a key press which side the oddball appeared. The reciprocal of average search time was taken as the perceptual distance between the target and distractor items. We measured all possible pairwise distances for 32 grayscale natural objects in this manner.

(B) Perceptual space reconstructed using multidimensional scaling performed on the pairwise perceptual dissimilarities. In the resulting plot, nearby objects represent hard searches, and far away objects represent easy searches. Some images are shown at a small size due to space constraints; in the actual experiment, all objects were equated to have the same longer dimension. The correlation on the top right indicates the match between the distances in the 2D plot with the observed pairwise distances (**** is p < 0.00005).

(C) Example display from Experiment 2. Participants performed this task inside the scanner. On each trial, they had to indicate whether an oddball target is present or absent using a key press.

(D) Predicted response to target-present and target-absent arrays, using the principle that the neural response to multiple items is the average of the individual item responses. This predicts that target-present arrays become similar

due to mixing of responses, whereas target-absent arrays stand apart.
Consequently, these two types of displays can be distinguished using their
distance to a central point in this space. We define this distance as visual
homogeneity, and it is obtained by finding the optimum center that maximizes the
difference in correlations with response times (see Methods).

(E) Mean visual homogeneity relative to the optimum center for target-present and
target-absent displays. Error bars represent s.e.m across all displays. Asterisks
represent statistical significance (**** is $p < 0.00005$, unpaired rank-sum test
comparing visual homogeneity for 32 target-absent and 32 target-present
arrays).

(F) Response time for target-present searches in Experiment 2 plotted against visual
homogeneity calculated from Experiment 1. Asterisks represent statistical
significance of the correlation (**** is $p < 0.00005$). Note that a single model is fit
to find the optimum center in representational space that predicts the response
times for both target-present and target-absent searches.

(G) Response time for target-absent searches in Experiment 2 plotted against visual
homogeneity calculated from Experiment 1. Asterisks represent statistical
significance of the correlation (**** is $p < 0.00005$).

**Visual homogeneity predicts same/different responses**

We have proposed that visual homogeneity can be used to solve any task that requires discriminating between homogeneous and heterogeneous displays. In Experiments 1-2, we have shown that visual homogeneity predicts target present/absent responses in visual search. We performed an additional experiment to assess whether visual homogeneity can be used to solve an entirely different task, namely a same-different task. In this task, participants have to indicate whether two items are the same or different. We note that instructions to participants for the same/different task ("you have to indicate if the two items are same or different") are quite different from the visual search task ("you have to indicate whether an oddball target is present or absent"). Yet both tasks involve discriminating between homogeneous and heterogeneous displays. We therefore predicted that "same" responses would be correlated with target-absent judgements and "different" responses would be correlated with target-present judgements. Remarkably, this was indeed the case (Section S4), demonstrating that same/different responses can also be predicted using visual homogeneity.

**Visual homogeneity is independent of experimental context**

In the above analyses, visual homogeneity was calculated for each display as its distance from an optimum center in perceptual space. This raises the possibility that visual homogeneity could be modified depending on experimental context since it could depend on the set of objects relative to which the visual homogeneity is computed. We performed a number of experiments to evaluate this possibility: we found that target-

absent response times, which index visual homogeneity, are unaffected by a variety of

experimental context manipulations (Section S5).

We therefore propose that visual homogeneity is an image-computable property

that remains stable across tasks. Moreover, it can be empirically estimated as the

reciprocal of the target-absent response times in a visual search task.

**A localized brain region encodes visual homogeneity (Experiment 2)**

So far, we have found that target present/absent response times had opposite

correlations with visual homogeneity (Figure 3 F-G), suggesting that visual homogeneity

is a possible decision variable for this task. Therefore, we reasoned that visual

homogeneity may be localized to specific brain regions, such as in the visual or

prefrontal cortices. Since the task in Experiment 2 was performed by participants inside

an MRI scanner, we set out to investigate this issue by analyzing their brain activations.

We estimated brain activations in each voxel for individual target-present and

target-absent search arrays (see Methods). To identify the brain regions whose

activations correlated with visual homogeneity, we performed a whole-brain searchlight

analysis. For each voxel, we calculated the mean activity in a 3x3x3 volume centered

on that voxel (averaged across voxels and participants) for each present/absent search

display, and calculated its correlation with visual homogeneity predictions derived from

behavior (see Methods). The resulting map is shown in Figure 4A. Visual homogeneity

was encoded in a highly localized region just anterior of the lateral occipital (LO) region,

with additional weak activations in the parietal and frontal regions. To compare these

trends across key visual regions, we calculated the correlation between mean activation

and visual homogeneity for each region. This revealed visual homogeneity to be

encoded strongly in this region VH, and only weakly in other visual regions (Figure 4D).

To ensure that the high match between visual homogeneity and neural

activations in the VH region is not due to an artefact of voxel selection, we performed

subject-level analysis (Section S6). We repeated the searchlight analysis for each

subject and defined VH region for each subject. We find this VH region consistently

anterior to the LO region in each subject. Next, we divided participants into two groups,

and repeated the brain-wide searchlight analysis. Importantly, the match between mean

activation and visual homogeneity remained significant even when the VH region was

defined using one group of participants and the correlation was calculated using the

mean activations of the other group (Section S6).

To confirm that neural activations in VH region are not driven by other cognitive

processes linked to response time, such as attention, we performed a whole-brain

searchlight analysis using response times across both target-present and target-absent

searches. Proceeding as before, we calculated the correlation between mean

activations to the target-present, target-absent and all displays with the respective

response times. The resulting maps show that mean activations in the VH region are

uncorrelated with response times overall (Section S6). By contrast, activations in EVC

and LO are negatively correlated with response times, suggesting that faster responses

are driven by higher activation of these areas. Finally, mean activation of parietal and

prefrontal regions were strongly correlated with response times, consistent with their

role in attentional modulation (Section S6).

**Object representations in LO match with visual search dissimilarities**

To investigate the neural space on which visual homogeneity is being computed, we performed a dissimilarity analysis. Since target-absent displays contain multiple instances of a single item, we took the neural response to target-absent displays as a proxy for the response to single items. For each pair of objects, we took the neural activations in a 3x3x3 neighborhood centered around a given voxel and calculated the Euclidean distance between the two 27-dimensional response vectors (averaged across participants). In this manner, we calculated the neural dissimilarity for all $^{32}C_2 = 496$ pairs of objects used in the experiment, and calculated the correlation between the neural dissimilarity in each local neighborhood and the perceptual dissimilarities for the same objects measured using oddball search in Experiment 1. The resulting map is shown in Figure 4B. It can be seen that perceptual dissimilarities from visual search are best correlated in the lateral occipital region, consistent with previous studies (Figure 4E). To compare these trends across key visual regions, we performed this analysis for early visual cortex (EVC), area V4, LO and for the newly identified region VH (average MNI coordinates (x, y, z): (-48, -59, -6) with 111 voxels in the left hemisphere; (49, -56, -7) with 60 voxels in the right hemisphere). Perceptual dissimilarities matched best with neural dissimilarities in LO compared to the other visual regions (Figure 4E). We conclude that neural representations in LO match with perceptual space. This is concordant with many previous studies (Haushofer et al., 2008; Kriegeskorte et al., 2008; Agrawal et al., 2020; Storrs et al., 2021; Ayzenberg et al., 2022).

**Equal weights for target and distractor in target-present array responses**

In the preceding sections, visual homogeneity was calculated using behavioural experiments assuming a neural representation that gives equal weights to the target and distractor. We tested this assumption experimentally by asking whether neural responses to target-present displays can be predicted using the response to the target and distractor items separately. The resulting maps revealed that target-present arrays were accurately predicted as a linear sum of the constituent items, with roughly equal weights for the target and distractor (Section S6).

**Figure 4: A localized brain region encodes visual homogeneity**

A. Searchlight map showing the correlation between mean activation in each 3x3x3 voxel neighborhood and visual homogeneity.

B. Searchlight map showing the correlation between neural dissimilarity in each 3x3x3 voxel neighborhood and perceptual dissimilarity measured in visual search.

C. Key visual regions identified using standard anatomical masks: early visual cortex (EVC), area V4, lateral occipital (LO) region. The visual homogeneity (VH) region was identified using the searchlight map in Panel A.

D. Correlation between the mean activation and visual homogeneity in key visual regions EVC, V4, LO and VH. Error bars represent standard deviation of the correlation obtained using a boostrap process, by repeatedly sampling participants with replacement for 10,000 times. Asterisks represent statistical significance, estimated by calculating the fraction of bootstrap samples in which the observed trend was violated (* is p < 0.05, ** is p< 0.01, **** is p < 0.0001).

E. Correlation between neural dissimilarity in key visual regions with perceptual dissimilarity. Error bars represent the standard deviation of correlation obtained using a bootstrap process, by repeatedly sampling participants with replacement 10,000 times. Asterisks represent statistical significance, estimated by calculating the fraction of bootstrap samples in which the observed trend was violated (** is p < 0.001).

**Visual homogeneity predicts symmetry perception (Experiments 3-4)**

The preceding sections show that visual homogeneity predicts target present/absent responses as well same/different responses. We have proposed that visual homogeneity can be used to solve any task that involves discriminating homogeneous and heterogeneous displays. In Experiments 3 & 4, we extend the generality of these findings to an entirely different task, namely symmetry perception. Here, asymmetric objects are akin to heterogeneous displays whereas symmetric objects are like homogeneous displays.

In Experiment 3, we measured perceptual dissimilarities for a set of 64 objects (32 symmetric, 32 asymmetric objects) made from a common set of parts. On each trial, participants viewed a search array with identical items except for one oddball, and had to indicate the side (left/right) on which the oddball appeared using a key press. An example search array is shown in Figure 5A. Participants performed searches involving all possible $^{64}C_2$ = 2,016 pairs of objects. Participants made highly accurate and consistent responses on this task (accuracy, mean ± sd: 98.5 ± 1.33%; correlation between average response times from even- and odd-numbered subjects: r = 0.88, p < 0.0001 across 2,016 searches). As before, we took the perceptual dissimilarity between each pair of objects to be the reciprocal of the average response time for displays with either item as target and the other as distractor. To visualize the underlying object representation, we performed a multidimensional scaling analysis, which embeds objects in a multidimensional space such that their pairwise dissimilarities match the experimentally observed dissimilarities. The resulting plot for two dimensions is shown in Figure 5B, where nearby objects correspond to similar searches. It can be seen that

symmetric objects are generally more spread apart than asymmetric objects, suggesting

that visual homogeneity could discriminate between symmetric and asymmetric objects.

In Experiment 4, we tested this prediction experimentally using a symmetry

detection task that was performed by participants inside an MRI scanner. On each trial,

participants viewed a briefly presented object, and had to indicate whether the object

was symmetric or asymmetric using a key press (Figure 5C). Participants made

accurate and consistent responses in this task (accuracy, mean ± sd: 97.7 ± 1.7%;

correlation between response times of odd- and even-numbered participants: r = 0.47, p

< 0.0001).

To investigate whether visual homogeneity can be used to predict symmetry

judgements, we took the embedding of all objects from Experiment 3, and asked

whether there was a center in this multidimensional space such that the distance of

each object to this center would be oppositely correlated with response times for

symmetric and asymmetric objects (see Methods). The resulting model predictions are

shown in Figure 5E-G. As predicted, visual homogeneity was significantly larger for

symmetric compared to asymmetric objects (visual homogeneity, mean ± sd: 0.60 ±

0.24 $s^{-1}$ for asymmetric objects; 0.76 ± 0.29 $s^{-1}$ for symmetric objects; p < 0.05, rank-

sum test; Figure 5E). For asymmetric objects, symmetry detection response times were

positively correlated with visual homogeneity (r = 0.56, p < 0.001; Figure 5F). By

contrast, for symmetric objects, response times were negatively correlated with visual

homogeneity (r = -0.39, p < 0.05; Figure 5G). These patterns are exactly as expected if

visual homogeneity was the underlying decision variable for symmetry detection.

However, we note that the range of visual homogeneity values for asymmetric and

symmetric objects do overlap, suggesting that visual homogeneity contributes but does

not fully determine task performance. We therefore propose that visual homogeneity

provides a useful and initial first guess at symmetry in an image, which can be refined

further through detailed scrutiny.

To confirm that the above model fits are not due to overfitting, we performed a

leave-one-out cross validation analysis, where we left out one object at a time, and then

calculated its visual homogeneity. This too yielded similar correlations (r = 0.44 for

asymmetric, r = -0.39 for symmetric objects, p < 0.05 in both cases).

In sum, we conclude that visual homogeneity can predict symmetry perception.

Taken together, these experiments demonstrate that the same computation (distance

from a center) explains two disparate property-based visual tasks: symmetry perception

and visual search.

**Figure 5. Visual homogeneity predicts symmetry perception**

(A) Example search array in Experiment 3. Participants viewed an array containing identical items except for an oddball present either on the left or right side, and had to indicate using a key press which side the oddball appeared. The reciprocal of average search time was taken as the perceptual distance between the target and distractor items. We measured all possible pairwise distances for 64 objects (32 symmetric, 32 asymmetric) in this manner.

(B) Perceptual space reconstructed using multidimensional scaling performed on the pairwise perceptual dissimilarities. In the resulting plot, nearby objects represent hard searches, and far away objects represent easy searches. Some images are shown at a small size due to space constraints; in the actual experiment, all objects were equated to have the same longer dimension. The correlation on the *top right* indicates the match between the distances in the 2D plot with the observed pairwise distances (**** is p < 0.00005).

(C) Two example displays from Experiment 4. Participants had to indicate whether the object is symmetric or asymmetric using a key press.

(D) Using the perceptual representation of symmetric and asymmetric objects from Experiment 3, we reasoned that they can be distinguished using their distance to a center in perceptual space. The coordinates of this center are optimized to maximize the match to the observed symmetry detection times.

(E) Visual homogeneity relative to the optimum center for asymmetric and symmetric objects. Error bar represents s.e.m. across images. Asterisks represent statistical significance (* is $p < 0.05$, unpaired rank-sum test comparing visual homogeneity for 32 symmetric and 32 asymmetric objects).

(F) Response time for asymmetric objects in Experiment 4 plotted against visual homogeneity calculated from Experiment 3. Asterisks represent statistical significance of the correlation (** is $p < 0.001$).

(G) Response time for symmetric objects in Experiment 4 plotted against visual homogeneity calculated from Experiment 3. Asterisks represent statistical significance of the correlation (* is $p < 0.05$).

**Visual homogeneity is encoded by the VH region during symmetry detection**

If visual homogeneity is a decision variable for symmetry detection, it could be

localized to specific regions in the brain. To investigate this issue, we analyzed the brain

activations of participants in Experiment 4.

To investigate the neural substrates of visual homogeneity, we performed a

searchlight analysis. For each voxel, we calculated the correlation between mean

activations in a 3x3x3 voxel neighborhood and visual homogeneity. This revealed a

localized region in the visual cortex as well as some parietal regions where this

correlation attained a maximum (Figure 6A). This VH region (average MNI coordinates

(x, y, z): (-57, -56, -8) with 93 voxels in the left hemisphere; (58, -50, -8) with 73 voxels

in the right hemisphere) overlaps with VH region defined during visual search in

Experiment 3 (for a detailed comparison, see Section S8).

We note that it is not straightforward to interpret the overlap between the VH

regions identified in Experiments 2 & 4. The lack of overlap could be due to stimulus

differences (natural images in Experiment 2 vs silhouettes in Experiment 4), visual field

differences (items in the periphery in Experiment 2 vs items at the fovea in Experiment

4) and even due to different participants in the two experiments. There is evidence

supporting all these possibilities: stimulus differences (Yue et al., 2014), visual field

differences (Kravitz et al., 2013) as well as individual differences can all change the

locus of neural activations in object-selective cortex (Weiner and Grill-Spector, 2012;

Glezer and Riesenhuber, 2013). We speculate that testing the same participants on

search and symmetry tasks using similar stimuli and display properties would reveal

even larger overlap in the VH regions that drive behavior.

To confirm that neural activations in VH region are not driven by other cognitive

processes linked to response time, such as attention, we performed a whole-brain

searchlight analysis using response times across both symmetric and asymmetric

objects. This revealed that mean activations in the VH region were poorly correlated

with response times overall, whereas other parietal and prefrontal regions strongly

correlated with response times consistent with their role in attentional modulation

(Section S7).

To investigate the perceptual representation that is being used for visual

homogeneity computations, we performed a neural dissimilarity analysis. For each pair

of objects, we took the neural activations in a 3x3x3 neighborhood centered around a

given voxel and calculated the Euclidean distance between the two 27-dimensional

response vectors. In this manner, we calculated the neural dissimilarity for all $^{64}C_2 = $

2,016 pairs of objects used in the experiment, and calculated the correlation between

the neural dissimilarity in each local neighborhood and the perceptual dissimilarities for

the same objects measured using oddball search in Experiment 3. The resulting map is

shown in Figure 6B. The match between neural and perceptual dissimilarity was

maximum in the lateral occipital region (Figure 6B).

To compare these trends for key visual regions, we repeated this analysis for

anatomically defined regions of interest in the visual cortex: early visual cortex (EVC),

area V4, the lateral occipital (LO) region, and the VH region defined based on the

searchlight map in Figure 5A. These regions are depicted in Figure 6C. We then asked

how mean activations in each of these regions is correlated with visual homogeneity.

This revealed that the match with visual homogeneity is best in the VH region compared

to the other regions (Figure 6D). To further confirm that visual homogeneity is encoded

in a localized region in the symmetry task, we repeated the searchlight analysis on two

independent subgroups of participants. This revealed highly similar regions in both

groups (Section S7).

Finally, we compared neural dissimilarities and perceptual dissimilarities in each

region as before. This revealed that perceptual dissimilarities (measured from

Experiment 3, during visual search) matched best with the LO region (Figure 6E),

suggesting that object representations in LO are the basis for visual homogeneity

computations in the VH region.

In sum, our results suggest that visual homogeneity is encoded by the VH region,

using object representations present in the adjoining LO region.

**Figure 6: Brain region encoding visual homogeneity during symmetry detection**

(A) Searchlight map showing the correlation between mean activation in each 3x3x3 voxel neighborhood and visual homogeneity.

(B) Searchlight map showing the correlation between neural dissimilarity in each 3x3x3 voxel neighborhood and perceptual dissimilarity measured in visual search.

(C) Key visual regions identified using standard anatomical masks: early visual cortex (EVC), area V4, Lateral occipital (LO) region. The visual homogeneity (VH) region was identified using searchlight map in Panel A.

(D) Correlation between the mean activation and visual homogeneity in key visual regions EVC, V4, LO and VH. Error bars represent standard deviation of the correlation obtained using a boostrap process, by repeatedly sampling participants with replacement for 10,000 times. Asterisks represent statistical significance, estimated by calculating the fraction of bootstrap samples in which the observed trend was violated (* is p < 0.05, ** is p< 0.01, **** is p < 0.0001).

(E) Correlation between neural dissimilarity in key visual regions with perceptual dissimilarity. Error bars represent the standard deviation of correlation obtained using a bootstrap process, by repeatedly sampling participants with replacement 10,000 times. Asterisks represent statistical significance, estimated by calculating the fraction of bootstrap samples in which the observed trend was violated (** is p < 0.001).

**Target-absent responses predict symmetry detection**

So far, we have shown that visual homogeneity predicts target present/absent responses in visual search as well as symmetry detection responses. These results suggest a direct empirical link between these two tasks. Specifically, since target-absent response time is inversely correlated with visual homogeneity, we can take its reciprocal as an estimate of visual homogeneity. This in turn predicts opposite correlations between symmetry detection times and reciprocal of target-absent response time: in other words, we should see a positive correlation for asymmetric objects, and a negative correlation for symmetric objects. We confirmed these predictions using additional experiments (Section S9). These results reconfirm that a common decision variable, visual homogeneity, drives both target present/absent and symmetry judgements.

**Visual homogeneity explains animate categorization**

Since visual homogeneity is always calculated relative to a location in perceptual space, we reasoned that shifting this center towards a particular object category would make it a decision variable for object categorization. To test this prediction, we reanalyzed data from a previous study in which participants had to categorize images as belonging to three hierarchical categories: animals, dogs or Labradors (Mohan and Arun, 2012). By adjusting the center of the perceptual space measured using visual search, we were able to predict categorization responses for all three categories (Section S10). We further reasoned that, if the optimum center for animal/dog/Labrador categorization is close to the default center in perceptual space that predicts target present/absent judgements, then even the default visual homogeneity, as indexed by

669    the reciprocal of target-absent search time, should predict categorization responses.

670    Interestingly, this was indeed the case (Section S10). We conclude that, at least for the

671    categories tested, visual homogeneity computations can serve as a decision variable for

672    object categorization.

**DISCUSSION**

Here, we investigated three disparate visual tasks: detecting whether an oddball

is present in a search array, deciding if two items are same or different, and judging

whether an object is symmetric/asymmetric. Although these tasks are superficially

different in the way we describe them, our key insight was that they all involve

discriminating between homogeneous and heterogeneous displays. We defined a new

image property computable from the underlying perceptual representation, namely

visual homogeneity, that can be used to solve these tasks. We found that visual

homogeneity can predict response times in all three tasks. Finally we have found that

visual homogeneity estimated from behavior is best correlated with mean activations in

a region anterior to the lateral occipital cortex. This finding strongly suggests a specific

function to this part of the high-level visual cortex. Below we discuss these findings in

relation to the existing literature.

**Visual homogeneity unifies visual search, same-different and symmetry tasks**

Our main finding, that a single decision variable (visual homogeneity) can be

used to solve three disparate visual tasks (visual search, same/different and symmetry

detection) is novel to the best of our knowledge. This finding is interesting and important

because it establishes a close correspondence between all three tasks, and explains

some unresolved puzzles in each of these tasks, as detailed below.

First, with regards to visual search, theoretical accounts of search are based on

signal detection theory (Verghese, 2001; Wolfe and Horowitz, 2017), but define the

signal only for specific target-distractor pairs. By contrast, the task of detecting whether

an oddball item is present requires a more general decision rule that has not been

identified. Our results suggest that visual homogeneity is the underlying decision

variable at least for oddball visual search tasks. Of course, visual search is a far more

complex process driven by many other factors such as distractor statistics, attentional

guidance and familiarity (Wolfe and Horowitz, 2017). Our findings suggest that visual

homogeneity could also be an additional driving factor for making decisions during

visual search. Our findings also offer additional insights into visual search. Target-

absent search times have always been noted to vary systematically, but lack a clear

explanation in the literature. The slope of target-absent search times as a function of set

size are typically twice the slope of target present searches (Wolfe, 1998). However this

observation is based on averaging across many target-present searches. Since there is

only one unique item in a target-absent search array, any systematic variation in target-

absent search must be due to an intrinsic image property. Our results resolve this

puzzle by showing that this systematic variation is driven by visual homogeneity. Finally,

our findings also help explain why we sometimes know a target is present without

knowing its exact location – this is because the underlying decision variable, visual

homogeneity, arises in high-level visual areas with relatively coarse spatial information.

However, we note that visual homogeneity computations described in this study do not

completely explain all the variance observed in oddball search times in our study –

rather they offer an important quantitative model that could explain the initial phase of

target selection. We speculate that this initial phase could be shared by all forms of

visual search (e.g. searching among non-identical distractors, memory-guided search,

conjunction search), and these would be interesting possibilities for future work.

Second, with regards to same-different tasks, most theoretical accounts use

signal detection theory but usually with reference to specific stimulus pairs (Nickerson,

1969; Petrov, 2009). It has long been observed that "different" responses become faster

with increasing target-distractor dissimilarity but this trend logically predicts that "same"

responses, which have zero difference, should be the slowest (Nickerson, 1967, 1969).

But in fact, "same" responses are faster than "different" responses. This puzzle has

been resolved by assuming a separate decision rule for "same" judgements, making the

overall decision process more complex (Petrov, 2009; Goulet, 2020). Our findings

resolve this puzzle by identifying a novel variable, visual homogeneity, which can be

used to implement a simple decision rule for making same/different responses. Our

findings also explain why some images elicit faster "same" responses than others: this

is due to image-to-image differences in visual homogeneity.

Third, with regard to symmetry detection, most theoretical accounts assume that

symmetry is explicitly detected using symmetry detectors along particular axes

(Wagemans, 1997; Bertamini and Makin, 2014). By contrast, our findings indicate an

indirect mechanism for symmetry detection that does not invoke any special symmetry

computations. We show that visual homogeneity computations can easily discriminate

between symmetric and asymmetric objects. This is because symmetric objects have

high visual homogeneity since they have repeated parts, whereas asymmetric objects

have low visual homogeneity since they have disparate parts (Pramod and Arun, 2018).

In a recent study, symmetry detection was explained by the average distance of objects

relative to other objects (Pramod and Arun, 2018). This finding is consistent with ours

since visual homogeneity is correlated with the average distance to other objects

(Section S1). However, there is an important distinction between these two quantities.

Visual homogeneity is an intrinsic image property, whereas the average distance of an

object to other objects depends on the set of other objects on which the average is

being computed. Indeed, we have confirmed through additional experiments that visual

homogeneity is independent of experimental context (Section S4). We speculate that

visual homogeneity can explain many other aspects of symmetry perception, such as

the relative strength of symmetries.

**Visual homogeneity in other visual tasks**

Our finding that visual homogeneity explains property-based visual tasks has

several important implications for visual tasks in general. First, we note that visual

homogeneity can be easily extended to explain other property-based tasks such as

delayed match-to-sample tasks or n-back tasks, by taking the response to the test

stimulus as being averaged with the sample-related information in working memory. In

such tasks, visual homogeneity will be larger for sequences with repeated compared to

non-repeated stimuli, and can easily be used to solve the task. Testing these

possibilities will require comparing systematic variations in response times in these

tasks across images, and measurements of perceptual space for calculating visual

homogeneity.

Second, we note that visual homogeneity can also be extended to explain object

categorization, if one assumes that the center in perceptual space for calculating visual

homogeneity can be temporarily shifted to the center of an object category. In such

tasks, visual homogeneity relative to the category center will be small for objects

belonging to a category and large for objects outside the category, and can be used as

a decision variable to solve categorization tasks. This idea is consistent with prevalent

accounts of object categorization (Stewart and Morin, 2007; Ashby and Maddox, 2011;

Mohan and Arun, 2012). Indeed, categorization response times can be explained using

perceptual distances to category and non-category items (Mohan and Arun, 2012). By

reanalyzing data from this study, we have found that, at least for the animate categories

tested, visual homogeneity can explain categorization responses (Section S9).

However, this remains to be tested in a more general fashion across multiple object

categories.

**Neural encoding of visual homogeneity**

We have found that visual homogeneity is encoded in a specific region of the

brain, which we denote as region VH, in both visual search and symmetry detection

tasks (Figure 4D, 5D). This finding is consistent with observations of norm-based

encoding in IT neurons (Leopold et al., 2006) and in face recognition (Valentine, 1991;

Rhodes and Jeffery, 2006; Carlin and Kriegeskorte, 2017). However, our findings are

significant because they reveal a dedicated region in high-level visual cortex for solving

property-based visual tasks.

We have found that the VH region is located just anterior to the lateral occipital

(LO) region, where neural dissimilarities match closely with perceptual dissimilarities

(Figure 4E, 5E). Based on this proximity, we speculate that visual homogeneity

computations are based on object representations in LO. However, confirming this

prediction will require fine-grained recordings of neural activity in VH and LO. An

interesting possibility for future studies would be to causally perturb brain activity

separately in VH or LO using magnetic or electrical stimulation, if at all possible. A

simple prediction would be that perturbing LO would distort the underlying

representation, whereas perturbing VH would distort the underlying decision process.

We caution however that the results might not be so easily interpretable if visual

homogeneity computations in VH are based on object representations in LO.

Recent observations from neural recordings in monkeys suggest that perceptual

dissimilarities and visual homogeneity need not be encoded in separate regions. For

instance, the overall magnitude of the population neural response of monkey inferior

temporal (IT) cortex neurons was found to correlate with memorability (Jaegle et al.,

2019). These results are consistent with encoding of visual homogeneity in these

regions. However, we note that neural responses in IT cortex also predict perceptual

dissimilarities (Op de Beeck et al., 2001; Sripati and Olson, 2010; Zhivago and Arun,

2014; Agrawal et al., 2020). Taken together, these findings suggest that visual

homogeneity computations and the underlying perceptual representation could be

interleaved within a single neural population, unlike in humans where we found separate

regions. Indeed, in our study, the mean activations of the LO region were also

correlated with visual homogeneity for symmetry detection (Figure 6A), but not for target

present/absent search (Figure 4A). We speculate that perhaps visual homogeneity

might be intermingled into the object representation in monkeys but separated into a

dedicated region in humans. These are interesting possibilities for future work.

Although many previous studies have reported brain activations in the vicinity of

the VH region, we are unaware of any study that has ascribed a specific function to this

region. The localized activations in our study match closely with the location of the
recently reported ventral stream attention module in both humans and monkeys (Sani et
al., 2021). Previous studies have observed important differences in brain activations in
this region, which can be explained using visual homogeneity, as detailed below.

First, previous studies have observed larger brain activations for animate
compared to inanimate objects in high-level visual areas which have typically included
the newly defined VH region reported here (Bracci and Op de Beeck, 2015; Proklova et
al., 2016; Thorat et al., 2019). In our study, visual homogeneity, as indexed by the
reciprocal of target-absent search time, is smaller for animate objects compared to
inanimate objects (Section S9). Likewise, brain activations were weaker for animate
objects compared to inanimate objects in region VH (average VH activations, mean ± sd
across participants: 0.50 ± 0.61 for animate target-absent displays, 0.64 ± 0.59 for
inanimate target-absent displays, $p < 0.05$, sign-rank test across participants). These
discrepancies could be due to differences in stimuli or task demands. Our results do
however suggest that visual homogeneity may be an additional organizing factor in
human ventral temporal cortex. Reconciling these observations will require controlling
animate/inanimate stimuli not only for shape but also for visual homogeneity.

Second, previous studies have reported larger brain activations for symmetric
objects compared to asymmetric objects in the vicinity of this region (Sasaki et al., 2005;
Van Meel et al., 2019). This can be explained by our finding that symmetric objects
have larger visual homogeneity (Figure 5E), leading to activation of the VH region
(Figure 6A). But the increased activations in previous studies were located in the V4 &
LO regions, whereas we have found greater activations more anteriorly in the VH

region. This difference could be due to the stimulus-related differences: both previous

studies used dot patterns, which could appear more object-like when symmetric, leading

to more widespread differences in brain activation due to other visual processes like

figure-ground segmentation (Van Meel et al., 2019). By contrast, both symmetric and

asymmetric objects in our study are equally object-like. Resolving these discrepancies

will require measuring visual homogeneity as well as behavioural performance during

symmetry detection for dot patterns.

Finally, our results are consistent with the greater activity observed for objects

with shared features observed in ventral temporal cortex during naming tasks (Taylor et

al., 2012; Tyler et al., 2013). Our study extends these observations by demonstrating an

empirical measure for shared feature (target-absent times in visual search) and

encoding of this empirical measure into a localized region in object selective cortex

across many tasks. We speculate that visual homogeneity may at least partially explain

semantic concepts such as those described in these studies.

**Relation to image memorability & saliency**

We have defined a novel image property, visual homogeneity, which refers to the

distance of a visual image to a central point in the underlying perceptual representation.

It can be reliably estimated for each image as the inverse of the target-absent response

time in a visual search task (Figure 3) and seems to be an intrinsic image property that

is unaffected by the immediate experimental context (Section S4).

At the outset, the way we have defined visual homogeneity suggests that it could

be related to other empirically measured quantities such as image memorability, or

saliency. It has long been noted that faces that are rated as being distinctive or unusual

are also easier to remember (Murdock, 1960; Valentine and Bruce, 1986a, 1986b;

Valentine, 1991). Recent studies have elucidated this observation by showing that there

are specific image properties that predict image memorability (Bainbridge et al., 2017;

Lukavský and Děchtěrenko, 2017; Rust and Mehrpour, 2020). However, image

memorability, as elegantly summarized in a recent review (Rust and Mehrpour, 2020),

could be driven by a number of both intrinsic and extrinsic factors. Likewise, saliency is

empirically measured as the relative proportion of fixations towards an image, and could

be driven by top-down as well as by bottom-up factors (Eimer, 2014; Peelen and

Kastner, 2014). Since visual homogeneity, image memorability and saliency are all

empirically measured in different tasks, it would be interesting to compare how they are

related on the same set of images.

**Conclusions**

Taken together, our results show that many property-based visual tasks can be

solved using visual homogeneity as a decision variable, which is localized to a specific

region anterior to the lateral occipital cortex. While this does not explain all possible

variations of these tasks, our study represents an important first step in terms of

demonstrating a quantitative, falsifiable model and a localized neural substrate. We

propose further that visual homogeneity computations might contribute to a variety of

other visual tasks as well, and these would be interesting possibilities for future work.

 **MATERIALS AND METHODS**

All participants had a normal or corrected-to-normal vision and gave informed

consent to an experimental protocol approved by the Institutional Human Ethics

Committee of the Indian Institute of Science (IHEC # 6-15092017). Participants

provided written informed consent before each experiment and were monetarily

compensated.

**Experiment 1. Oddball detection for perceptual space (natural objects)**

*Participants.* A total of 16 participants (8 males, 22 ± 2.8 years) participated in this

experiment.

*Stimuli.* The stimulus set comprised a set of 32 grayscale natural objects (16 animate,

16 inanimate) presented against a black background.

*Procedure.* Participants performed an oddball detection task with a block of practice

trials involving unrelated stimuli followed by the main task. Each trial began with a red

fixation cross (diameter 0.5°) for 500 ms, followed by a 4 x 4 search array measuring

30° x 30° for 5 seconds or until a response was made. The search array always

contained one oddball target and 15 identical distractors, with the target appearing

equally often on the left or right. A vertical red line divided the screen equally into two

halves to facilitate responses. Participants were asked to respond as quickly and as

accurately as possible using a key press to indicate the side of the screen containing

the target ('Z' for left, M' for right). Incorrect trials were repeated later after a random

number of other trials. Each participant completed 992 correct trials ($^{32}C_2$ object pairs x

2 repetitions with either image as target). The experiment was created using PsychoPy

(Peirce et al., 2019) and ported to the online platform Pavlovia for collecting data.

Since stimulus size could vary with the monitor used by the online participants,

we equated the stimulus size across participants using the ScreenScale function

(https://doi.org/10.17605/OSF.IO/8FHQK). Each participant adjusted the size of a

rectangle on the screen such that its size matched the physical dimensions of a credit

card. All the stimuli presented were then scaled with the estimated scaling function to

obtain the desired size in degrees of visual angle, assuming an average distance to

screen of 60 cm.

*Data Analysis.* Response times faster than 0.3 seconds or slower than 3 seconds were

removed from the data. This step removed only 1.25% of the data and improved the

overall response time consistency, but did not qualitatively alter the results.

*Characterizing perceptual space using multidimensional scaling.* To characterize the

perceptual space on which present/absent decisions are made, we took the inverse of

the average response times (across trials and participants) for each image pair. This

inverse of response time (i.e. 1/RT) represents the dissimilarity between the target and

distractor (Arun, 2012), indexes the underlying salience signal in visual search (Sunder

and Arun, 2016) and combines linearly across a variety of factors (Pramod and Arun,

2014, 2016; Jacob and Arun, 2020). Since there were 32 natural objects in the

experiment and all possible ($^{32}C_2$ = 496) pairwise searches in the experiment, we

obtained 496 pairwise dissimilarities overall. To calculate target-present and target-

absent array responses, we embedded these objects into a multidimensional space

using multidimensional scaling analysis (*mdscale* function; MATLAB 2019). This

analysis finds the n-dimensional coordinates for each object such that pairwise

distances between objects best matches with the experimentally observed pairwise

distances. We then treated the activations of objects along each dimension as the

responses of a single artificial neuron, so that the response to target-present arrays

could be computed as the average of the target and distractor responses.

**Experiment 2. Target present-absent search during fMRI**

*Participants.* A total of 16 subjects (11 males; age, mean ± sd: 25 ± 2.9 years)

participated in this experiment. Participants with history of neurological or psychiatric

disorders, or with metal implants or claustrophobia were excluded through screening

questionnaires.

*Procedure.* Inside the scanner, participants performed a single run of a one-back task

for functional localizers (block design, object vs scrambled objects), eight runs of the

present-absent search task (event-related design), and an anatomical scan. The

experiment was deployed using custom MATLAB scripts written using Psychophysics

Toolbox (Brainard, 1997).

*Functional localizer runs.* Participants had to view a series of images against a black

background and press a response button whenever an item was repeated. On each

trial, 16 images were presented (0.8 s on, 0.2 s off), containing one repeat of an image

that could occur at random. Trials were combined into blocks of 16 trials each

containing either only objects or only scrambled objects. A single run of the functional

localizers contained 12 such blocks (6 object blocks & 6 scrambled-object blocks).

Stimuli in each block were chosen randomly from a larger pool of 80 naturalistic objects

with the corresponding phase-scrambled objects (created by taking the 2D Fourier

transform of each image, randomly shuffling the Fourier phase, and performing the

Fourier inverse transform). This is a widely used method for functional localization of

object-selective cortex. In practice, however, we observed no qualitative differences in

our results upon using voxels activated during these functional localizer runs to further

narrow down the voxels selected using anatomical masks. As a result, we did not use

the functional localizer data, and all the analyses presented here are based on

anatomical masks only.

*Visual search task.* In the present-absent search task, participants reported the

presence or absence of an oddball target by pressing one of two buttons using their

right hand. The response buttons were fixed for a given participant and counterbalanced

across participants. Each search array had eight items, measuring 1.5° along the longer

dimension, arranged in a 3 x 3 grid, with no central element to avoid fixation biases (as

shown in Figure 3C). The entire search array measured 6.5°, with an average inter-item

spacing of 2.5°. Item positions were jittered randomly on each trial according to a

uniform distribution with range ± 0.2°. Each trial lasted 4 s (1 s ON time and 3 s OFF

time), and participants had to respond within 4 s. Each run had 64 unique searches (32

present, 32 absent) presented in random order, using the natural objects from

Experiment 1. Target-present searches were chosen randomly from all possible

searches such that all 32 images appeared equally often. Target-absent searches

included all 32 objects. The location of the target in the target-present searches was

chosen such that all eight locations were sampled equally often. In this manner,

participants performed 8 such runs of 64 trials each.

*Data acquisition.* Participants viewed images projected on a screen through a mirror

placed above their eyes. Functional MRI (fMRI) data were acquired using a 32-channel

head coil on a 3T Skyra (Siemens, Mumbai, India) at the HealthCare Global Hospital,

Bengaluru. Functional scans were performed using a T2*-weighted gradient-echo-

planar imaging sequence with the following parameters: repetition time (TR) = 2s, echo

time (TE) = 28 ms, flip angle = 79°, voxel size = 3 × 3 × 3 mm$^3$, field of view = 192 × 192

mm$^2$, and 33 axial-oblique slices for whole-brain coverage. Anatomical scans were

performed using T1-weighted images with the following parameters: TR = 2.30 s, TE =

1.99 ms, flip angle = 9°, voxel size = 1 × 1 × 1 mm$^3$, field of view = 256 × 256 × 176

mm$^3$.

*Data preprocessing.* The raw fMRI data were preprocessed using Statistical Parametric

Mapping (SPM) software (Version12; Welcome Center for Human Neuroimaging;

https://www.fil.ion.ucl.ac.uk/spm/software_/spm12/), running on MATLAB 2019b. Raw

images were realigned, slice-time corrected, co-registered to the anatomical image,

segmented, and normalized to the Montreal Neurological Institute (MNI) 305 anatomical

template. Repeating the key analyses with voxel activations estimated from individual

subjects yielded qualitatively similar results. Smoothing was performed only on the

functional localizer blocks using a Gaussian kernel with a full-width half-maximum of 5

mm. Default SPM parameters were used, and voxel size after normalization was kept at

$3\times3\times3$ mm$^3$. The data were further processed using GLMdenoise (Kay et al., 2013).

GLMdenoise improves the signal-to-noise ratio in the data by regressing out the noise

estimated from task-unrelated voxels. The denoised time-series data were modeled

using generalized linear modeling in SPM after removing low-frequency drift using a

high-pass filter with a cutoff of 128 s. In the main experiment, the activity of each voxel

was modeled using 83 regressors (68 stimuli + 1 fixation + 6 motion regressors + 8

runs). In the localizer block, each voxel was modeled using 14 regressors (6 stimuli + 1

fixation + 6 motion regressors + 1 run).

1007

1008    *ROI definitions.* The regions of interest (ROI) of Early Visual Cortex (EVC) and Lateral

1009    Occipital (LO) regions were defined using anatomical masks from the SPM anatomy

1010    toolbox (Eickhoff et al., 2005). All brain maps were visualized on the inflated brain using

1011    Freesurfer (https://surfer.nmr.mgh.harvard.edu/fswiki/).

1012

1013    *Behavioral data analysis.* Response times faster than 0.3 seconds or slower than 3

1014    seconds were removed from the data. This step removed only 0.75% of the data and

1015    improved the overall response time consistency, but did not qualitatively alter the

1016    results.

1017

*Model fitting for visual homogeneity.*

We took the multi-dimensional embedding returned by the perceptual space

experiment (Experiment 1) in 5 dimensions as the responses of 5 artificial neurons to

the entire set of objects. For each target-present array, we calculated the neural

response as the average of the responses elicited by these 5 neurons to the target and

distractor items. Likewise, for target-absent search arrays, the neural response was

simply the response elicited by these 5 neurons to the distractor item in the search

array. To estimate the visual homogeneity of the target-present and target-absent

search arrays, we calculated the distance of each of these arrays from a single point in

the multidimensional representation. We then calculated the correlation between the

visual homogeneity calculated relative to this point and the response times for the

target-present and target-absent search arrays. The 5 coordinates of this center point

was adjusted using constrained nonlinear optimization to maximize the difference

between correlations with the target-present & target-absent response times

respectively. This optimum center remained stable across many random starting points,

and our results were qualitatively similar upon varying the number of embedding

dimensions.

Additionally, we performed a leave-one-out cross-validation analysis to validate

the number of dimensions or neurons used for the multidimensional scaling analysis in

the visual homogeneity model fits. For each choice of number of dimensions, we

estimated the optimal centre for visual homogeneity calculations while leaving out all

searches involving a single image. We then calculated the visual homogeneity for all the

target-present and target-absent searches involving the left-out image. Compiling these

predictions by leaving out all images by turn results in a leave-one-out predicted visual

homogeneity, which we correlated with the target-present and target-absent response

times. We found that the absolute sum of the correlations between visual homogeneity

and present/absent reaction times increased monotonically from 1 to 5 neurons,

remained at a steady level from 5 to 9 neurons and decreased beyond 9 neurons.

Furthermore, the visual homogeneity using the optimal center is highly correlated for 5-9

neurons. We therefore selected 5 neurons or dimensions for reporting visual

homogeneity computations.

1049

*Searchlight maps for mean activation (Figure 4A, Figure 6A)*

To characterize the brain regions that encode visual homogeneity, we performed

a whole-brain searchlight analysis. For each voxel, we took the voxels in a 3x3x3

neighborhood and calculated the mean activations across these voxels across all

participants. To avoid overall activation level differences between target-present and

target-absent searches, we z-scored the mean activations separately across target-

present and target-absent searches. Similarly, we calculated the visual homogeneity

model predictions from behaviour, and z-scored the visual homogeneity values for

target-present and target-absent searches separately. We then calculated the

correlation between the normalized mean activations and the normalized visual

homogeneity for each voxel, and displayed this as a colormap on the inflated MNI brain

template in Figures 3A & 5A.

Note that the z-scoring of mean activations and visual homogeneity removes any

artefactual correlation between mean activation and visual homogeneity arising simply

due to overall level differences in mean activation or visual homogeneity itself, but does

not alter the overall positive correlation between the visual homogeneity and mean

activation across individual search displays.

1067

*Searchlight maps for neural and behavioural dissimilarity (Figure 4B, Figure 6B)*

To characterize the brain regions that encode perceptual dissimilarity, we

performed a whole-brain searchlight analysis. For each voxel, we took the voxel

activations in a 3x3x3 neighborhood to target-absent displays as a proxy for the neural

response to the single image. For each image pair, we calculated the pair-wise

Euclidean distance between the 27-dimensional voxel activations evoked by the two

images, and averaged this distance across participants to get a single average

distance. For 32 target-absent displays in the experiment, taking all possible pairwise

distances results in $^{32}C_2$ = 496 pairwise distances. Similarly, we obtained the same 496

pairwise perceptual dissimilarities between these items from the oddball detection task

(Experiment 1). We then calculated the correlation between the mean neural

dissimilarities at each voxel with perceptual dissimilarities, and displayed this as a

colormap on the flattened MNI brain template in Figures 3B & 5B.

1081

**Experiment 3. Oddball detection for perceptual space (Symmetric/Asymmetric objects)**

*Participants.* A total of 15 participants (11 males, 22.8 ± 4.3 years) participated in this experiment.

*Paradigm.* Participants performed an oddball visual search task. Participants completed 4032 correct trials ($^{64}C_2$ shape pairs x 2 repetitions) as two sessions in two days. We used a total of 64 baton shapes (32 symmetric and 32 asymmetric), and all shapes were presented against a black background. We created 32 unique parts with the vertical line as part of the contour. We created 32 symmetric by joining the part and its mirror-filled version, and 32 asymmetric objects were created by randomly pairing the left part and mirror flipped version of another left part. All parts were occurring equally likely. All other task details are the same as Experiment 1.

**Experiment 4 Symmetry judgment task (fMRI & behavior)**

*Participants.* A total of 15 subjects participated in this study. Participants had normal or corrected to normal vision. Participants had no history of neurological or psychiatric impairment. We excluded participants with metal implants or claustrophobia from the study.

1104   *Paradigm.* Inside the scanner, participants performed two runs of one-back identity task

1105   (functional localizer), eight runs of symmetry judgment task (event-related design), and

1106   one anatomical scan. We excluded the data from one participant due to poor accuracy

1107   and long response times.

1108

*Symmetry Task.* On each trial, participants had to report whether a briefly presented

object was symmetric or not using a keypress. Objects measured 4° and were

presented against a black background. Response keys were counterbalanced across

participants. Each trial lasted 4 s, with the object displayed for 200 ms followed by a

blank period of 3800 ms. Participants could respond at any time following appearance

of the object, up to a time out of 4 s after which the next trial began. Each run had 64

unique conditions (32 symmetric and 32 asymmetric).

1116

1117   *1-back task for functional localizers.* Stimuli were presented as blocks, and participants

1118   reported repeated stimuli with a keypress. Each run had blocks of either silhouettes

1119   (asymmetric/symmetric), dot patterns (asymmetric/symmetric), combination of baton

1120   and dot patterns (asymmetric/symmetric) and natural objects (intact/scrambled).

1121

1122   **Data Analysis**

1123   *Noise Removal in RT.* Very fast (< 100 ms) reaction times were removed. We also

1124   discarded all reaction times to an object if participant's accuracy was less than 80%.

1125   This process removed 3.6% of RT data.

1126

*Model fitting for visual homogeneity.* We proceeded as before by embedding the oddball

detection response times into multidimensional space with 3 dimensions. For each

image, the visual homogeneity was defined as its distance from an optimum center. We

then calculated the correlation between the visual homogeneity calculated relative to

this optimum center and the response times for the target-present and target-absent

search arrays separately. This optimum center was estimated using a constrained

nonlinear optimization to maximize the difference between the correlations for

asymmetric object response times and symmetric object response times. Other details

were the same as in Experiment-2.

1136

## REFERENCES

Agrawal A, Hari K, Arun SP (2020) A compositional neural code in high-level visual cortex can explain jumbled word reading. eLife 9:e54846.

Arun SP (2012) Turning visual search time on its head. Vision Res 74:86–92.

Ashby FG, Maddox WT (2011) Human category learning 2.0. Ann N Y Acad Sci 1224:147–161.

Ayzenberg V, Kamps FS, Dilks DD, Lourenco SF (2022) Skeletal representations of shape in the human visual cortex. Neuropsychologia 164:108092.

Bainbridge WA, Dilks DD, Oliva A (2017) Memorability: A stimulus-driven perceptual neural signature distinctive from memory. NeuroImage 149:141–152.

Bertamini M, Makin ADJ (2014) Brain Activity in Response to Visual Symmetry. Symmetry 6:975–996.

Bracci S, Op de Beeck H (2015) Dissociations and associations between shape and category representations in the two visual pathways. J Neurosci 36:432–444.

Brainard DH (1997) The Psychophysics Toolbox. Spat Vis 10:433–436.

Carlin JD, Kriegeskorte N (2017) Adjudicating between face-coding models with individual-face fMRI responses. PLoS Comput Biol 13:e1005604.

Eickhoff SB, Stephan KE, Mohlberg H, Grefkes C, Fink GR, Amunts K, Zilles K (2005) A new SPM toolbox for combining probabilistic cytoarchitectonic maps and functional imaging data. NeuroImage 25:1325–1335.

Eimer M (2014) The neural basis of attentional control in visual search. Trends Cogn Sci 18:526–535.

Fleuret F, Li T, Dubout C, Wampler EK, Yantis S, Geman D (2011) Comparing machines and humans on a visual categorization test. Proc Natl Acad Sci U S A 108:17621–17625.

Glezer LS, Riesenhuber M (2013) Individual variability in location impacts orthographic selectivity in the "visual word form area". J Neurosci Off J Soc Neurosci 33:11221–11226.

Goulet M-A (2020) Investigation of the Cognitive Mechanisms of Same and Different Judgments. Available at: http://dx.doi.org/10.20381/ruor-24882.

Haushofer J, Livingstone MS, Kanwisher N (2008) Multivariate patterns in object-selective cortex dissociate perceptual and physical shape similarity. PLoS Biol 6:e187.

Jacob G, Arun SP (2020) How the forest interacts with the trees: Multiscale shape integration explains global and local processing. J Vis 20:20.

Jaegle A, Mehrpour V, Mohsenzadeh Y, Meyer T, Oliva A, Rust N (2019) Population response magnitude variation in inferotemporal cortex predicts image memorability. eLife 8:e47596.

Katti H, Arun SP (2022) A separable neural code in monkey IT enables perfect CAPTCHA decoding. J Neurophysiol 127:869–884.

Kay KN, Rokem A, Winawer J, Dougherty RF, Wandell BA (2013) GLMdenoise: A fast, automated technique for denoising task-based fMRI data. Front Neurosci 7:1–15.

Kim J, Ricci M, Serre T (2018) Not-So-CLEVR: Learning same-different relations strains feedforward neural networks. Interface Focus 8.

Kravitz DJ, Saleem KS, Baker CI, Ungerleider LG, Mishkin M (2013) The ventral visual
pathway: An expanded neural framework for the processing of object quality.
Trends Cogn Sci 17:26–49.
Kriegeskorte N, Mur M, Ruff DA, Kiani R, Bodurka J, Esteky H, Tanaka K, Bandettini PA
(2008) Matching categorical object representations in inferior temporal cortex of
man and monkey. Neuron 60:1126–1141.
Leopold D a, Bondar IV, Giese M a (2006) Norm-based face encoding by single
neurons in the monkey inferotemporal cortex. Nature 442:572–575.
Lukavský J, Děchtěrenko F (2017) Visual properties and memorising scenes: Effects of
image-space sparseness and uniformity. Atten Percept Psychophys 79:2044–
2054.
Mohan K, Arun SP (2012) Similarity relations in visual search predict rapid visual
categorization. J Vis 12:19–19.
Murdock BB (1960) The distinctiveness of stimuli. Psychol Rev 67:16–31.
Nickerson RS (1967) "Same"-"different" response times with multi-attribute stimulus
differences. Percept Mot Skills 24:543–554.
Nickerson RS (1969) 'Same'-'different' response times: A model and a preliminary test.
Acta Psychol (Amst) 30:257–275.
Op de Beeck H, Wagemans J, Vogels R (2001) Inferotemporal neurons represent low-
dimensional configurations of parameterized shapes. Nat Neurosci 4:1244–1252.
Peelen MV, Kastner S (2014) Attention in the real world: Toward understanding its
neural basis. Trends Cogn Sci 18:242–250.
Peirce J, Gray JR, Simpson S, MacAskill M, Höchenberger R, Sogo H, Kastman E,
Lindeløv JK (2019) PsychoPy2: Experiments in behavior made easy. Behav Res
Methods 51:195–203.
Petrov AA (2009) Symmetry-based methodology for decision-rule identification in same-
different experiments. Psychon Bull Rev 16:1011–1025.
Pramod RT, Arun SP (2014) Features in visual search combine linearly. J Vis 14:1–20.
Pramod RT, Arun SP (2016) Object attributes combine additively in visual search. J Vis
16:8.
Pramod RT, Arun SP (2018) Symmetric Objects Become Special in Perception
Because of Generic Computations in Neurons. Psychol Sci 29:95–109.
Proklova D, Kaiser D, Peelen MV (2016) Disentangling Representations of Object
Shape and Object Category in Human Visual Cortex: The Animate-Inanimate
Distinction. J Cogn Neurosci 28:680–692.
Puebla G, Bowers JS (2022) Can deep convolutional neural networks support relational
reasoning in the same-different task? J Vis 22:11.
Rhodes G, Jeffery L (2006) Adaptive norm-based coding of facial identity. Vision Res
46:2977–2987.
Ricci M, Cadène R, Serre T (2021) Same-different conceptualization: a machine vision
perspective. Curr Opin Behav Sci 37:47–55.
Rust NC, Mehrpour V (2020) Understanding Image Memorability. Trends Cogn Sci
24:557–568.
Sani I, Stemmann H, Caron B, Bullock D, Stemmler T, Fahle M, Pestilli F, Freiwald WA
(2021) The human endogenous attentional control network includes a ventro-
temporal cortical node. Nat Commun 12:360.

Sasaki Y, Vanduffel W, Knutsen T, Tyler C, Tootell R (2005) Symmetry activates
extrastriate visual cortex in human and nonhuman primates. Proc Natl Acad Sci
U S A 102:3159–3163.
Serre T (2019) Deep Learning: The Good, the Bad, and the Ugly. Annu Rev Vis Sci
5:399–426.
Sripati AP, Olson CR (2010) Global Image Dissimilarity in Macaque Inferotemporal
Cortex Predicts Human Visual Search Efficiency. J Neurosci 30:1258–1269.
Stewart N, Morin C (2007) Dissimilarity is used as evidence of category membership in
multidimensional perceptual categorization: a test of the similarity-dissimilarity
generalized context model. Q J Exp Psychol 2006 60:1337–1346.
Storrs KR, Kietzmann TC, Walther A, Mehrer J, Kriegeskorte N (2021) Diverse Deep
Neural Networks All Predict Human Inferior Temporal Cortex Well, After Training
and Fitting. J Cogn Neurosci 33:2044–2064.
Sunder S, Arun SP (2016) Look before you seek: Preview adds a fixed benefit to all
searches. J Vis 16:3.
Taylor KI, Devereux BJ, Acres K, Randall B, Tyler LK (2012) Contrasting effects of
feature-based statistics on the categorisation and basic-level identification of
visual objects. Cognition 122:363–374.
Thorat S, Proklova D, Peelen MV (2019) The nature of the animacy organization in
human       ventral       temporal       cortex.       eLife       8       Available       at:
http://www.ncbi.nlm.nih.gov/pubmed/31496518.
Tyler LK, Chiu S, Zhuang J, Randall B, Devereux BJ, Wright P, Clarke A, Taylor KI
(2013) Objects and categories: feature statistics and object processing in the
ventral stream. J Cogn Neurosci 25:1723–1735.
Valentine T (1991) A Unified Account of the Effects of Distinctiveness, Inversion, and
Race in Face Recognition. Q J Exp Psychol Sect A 43:161–204.
Valentine T, Bruce V (1986a) Recognizing familiar faces: The role of distinctiveness and
familiarity. Can J Psychol Can Psychol 40:300–305.
Valentine T, Bruce V (1986b) The Effects of Distinctiveness in Recognising and
Classifying Faces. Perception 15:525–535.
Van Meel C, Baeck A, Gillebert CR, Wagemans J, Op de Beeck HP (2019) The
representation of symmetry in multi-voxel response patterns and functional
connectivity throughout the ventral visual stream. NeuroImage Available at:
https://linkinghub.elsevier.com/retrieve/pii/S1053811919301247.
Verghese P (2001) Visual search and attention: A signal detection theory approach.
Neuron 31:523–535.
Wagemans J (1997) Characteristics and models of human symmetry detection. Trends
Cogn Sci 1:346–352.
Weiner KS, Grill-Spector K (2012) The improbable simplicity of the fusiform face area.
Trends Cogn Sci 16:251–254.
Wolfe JM (1998) What Can 1 Million Trials Tell Us About Visual Search? Psychol Sci
9:33–39.
Wolfe JM, Horowitz TS (2017) Five factors that guide attention in visual search. Nat
Hum Behav 1:0058.
Yue X, Pourladian IS, Tootell RBH, Ungerleider LG (2014) Curvature-processing
network in macaque visual cortex. Proc Natl Acad Sci U S A 111:E3467-75.

Zhivago KA, Arun SP (2014) Texture discriminability in monkey inferotemporal cortex
predicts human texture perception. J Neurophysiol 112:2745–2755.
Zoccolan D, Cox DD, DiCarlo JJ (2005) Multiple Object Response Normalization in
Monkey Inferotemporal Cortex. J Neurosci 25:8150–8164.

1277

## DATA AVAILABILITY

1279 All data and code required to reproduce the results are publicly available at
1280 https://osf.io/cvzxt/

1281

## AUTHOR CONTRIBUTIONS

1283     GJ and SPA designed the visual search experiments; GJ collected behavioral
1284 and fMRI data; GJ & SPA analyzed and interpreted the data; PRT & SPA designed the
1285 symmetry experiments; PRT collected fMRI data; GJ, PRT & SPA analyzed and
1286 interpreted the data; GJ and SPA wrote the manuscript with inputs from PRT.

1287

## ACKNOWLEDGEMENTS

1289     We thank Divya Gulati for help with data collection of Experiments S4 & S5. This
1290 research was supported by the DBT/Wellcome Trust India Alliance Senior Fellowship
1291 awarded to SPA (Grant# IA/S/17/1/503081). GJ was supported by a Senior Research
1292 Fellowship from MHRD, Government of India.

# SUPPLEMENTARY MATERIAL

## for

## Visual homogeneity computations in the brain enable solving property-based visual tasks

## Georgin Jacob, RT Pramod and SP Arun

**CONTENTS**

## SECTION S1: VISUAL HOMOGENEITY IN DEEP NETWORKS EXPLAINS SEARCH

**Introduction**

In the main text, we reconstructed the underlying object representation using oddball search in Experiment 1, and used this representation to compute visual homogeneity, and predict target present/absent searches in Expeirment 2. At first glance, this result could appear circular since we are using search data from Experiment 1 to predict search data in Experiment 2. While this is highly unlikely since we are using search dissimilarities in Experiment 1 only to reconstruct the underlying object representations, we nonetheless reasoned that this concern can also be addressed by computing visual homogeneity on any brain-like object representation.

To this end, we repeated the visual homogeneity predictions of Experiment 2 using object representations derived from deep networks whose representations are known to be brain-like.

**Methods**

We used a ResNet-50 architecture trained for object classification on the ImageNet dataset. First, we identified the layer that best matches the human representation by comparing previously observed perceptual distances (Pramod and Arun, 2020) with distances predicted by the ResNet-50 model. We then obtained the ResNet-50 representation of stimuli used in Experiment 1 specifically from layer3.5conv2. This higher dimensional stimulus representation was reduced to lower dimension using PCA. Using this reduced dimensional representation, we fitted the visual homogeneity model as before.

**Results**

To identify the layer in the ResNet-50 model that best aligns with human perceptual representation, we compared observed perceptual distances from 32 experiments in a previous study with distances predicted by each layer of the ResNet-50 model. The representations from the convolutional layer (layer3.5conv2, layer 134) demonstrated the closest match to human perceptual distances (Figure S1A). Specifically, this selected layer of the ResNet-50 model predicted the observed perceptual distances for Experiment-1 ($r = 0.66$, $p<0.0001$ across all $^{32}C_2 = 496$ object pairs).

The visual homogeneity, computed from lower-dimensional ResNet-50 model embeddings, of target-present arrays was significantly smaller than that of target-absent arrays (Figure S1B). The model's predictions are depicted in Figures S1C and S1D. Response times for target-present searches were positively correlated with visual homogeneity ($r = 0.42$, $p<0.05$; Figure S1C), while response times for target-absent searches were negatively correlated with visual homogeneity ($r = 0.56$, $p<0.0001$ across all $^{32}C_2 = 496$ object pairs). Additionally, The visual homogeneity computed using ResNet-50 is highly correlated with visual homogeneity computed using Experiments 1&2 ($r = 0.76$, $p<0.0001$).

Hence, we demonstrate that our model can predict target-present/absent search responses based on any technique to estimate the representational space, and it is not dependent on the odd-ball visual search experiment.

**Figure S1: Visual homogeneity in deep networks predicts oddball search**

(A) Correlation between perceptual dissimilarities and deep network dissimilarities across 32 oddball search experiments shown for each layer of ResNet-50 (median ± sem calculated across experiments). The layer with highest median correlation (r = 0.46) is marked with a *blue dashed line*. This layer is taken for further analyses.

(B) Predicted visual homogeneity (calculated from ResNet-50 layer 134) for target-present and target-absent searches. Error bars represent s.e.m across all displays. Asterisks represent statistical significance (**** is p < 0.00005, unpaired rank-sum test comparing visual homogeneity for 32 target-absent and 32 target-present arrays).

(C) Observed response time for target-present searches in Experiment 2 plotted against visual homogeneity calculated from ResNet-50 layer 134. Asterisks represent statistical significance of the correlation (**** is p < 0.00005). Note that a single model is fit to find the optimum center that predicts the response times for both target-present and target-absent searches.

(D) Same as (C) but for target-absent searches.

**Figure S2: Additional analysis for Experiment 1**
(E) Reaction times of target-absent searches (Experiment 2) plotted against the average dissimilarity to all other objects (Experiment 1).
(F) Visual homogeneity for each object plotted against the average distance of each object to all other objects, suggesting that visual homogeneity is closely related to the average distance of an object to all others.
(G) Correlation between predicted and observed target-present RT as a function of the weight of target relative to distractors in the search array. The analysis in the main text assumes that the responses to target-present arrays are an average of the target and distractor responses. To validate this assumption, we repeated the analysis by assuming taking target-present array response to be $r_{array} = w *$ $r_{target} + (1 - w) * r_{distractor}$ , where $r_{array}$ is the response to the target-present array, $r_{target}$ and $r_{distractor}$ are the responses to the target and distractor, and $w$ represents the weight of the target relative to the distractor. If w = 0, it means that the target does not contribute to the overall response, and w = 1 implies that the target dominates the overall response. In this plot, for each value of w, we optimized the coordinates of the center to best match the data, and plotted the correlation between predicted and observed target-present RT. It can be seen that roughly equal weighting (w = 0.52) of the target and distractor yields the best fit to the data. The gray bar represent the range of weights for which the correlation is statistically significant (p < 0.05).

# SECTION S3. GENERALIZATION TO OTHER OBJECTS

## Introduction

In the main text, using Experiments 1 & 2, we found that visual homogeneity predicts target present/absent responses, but these results were based on testing 32 natural objects. Here, we performed four additional experiments to confirm the generality of these findings. In Experiments S1 & S2, we tested 48 natural objects. In Experiments S3 & S4, we tested 49 silhouette shapes.

## Methods

All participants had a normal or corrected-to-normal vision and gave informed consent to an experimental protocol approved by the Institutional Human Ethics Committee of the Indian Institute of Science (IHEC # 6-15092017). Participants provided written informed consent before each experiment and were monetarily compensated.

## Experiment S1: Odd ball detection for perceptual space (natural objects)

This data is Experiment 1 of a previously published study (Mohan and Arun, 2012), and the salient details are reproduced here. The analysis of visual homogeneity is novel and unique to this study.

*Participants.* A total of 12 participants aged 20-30 years participated in this experiment.

*Stimuli.* The stimulus set comprised a set of 48 grayscale natural objects (24 animate, 24 inanimate) presented against a black background. Images were equated for brightness. The longer dimension was presented at a visual angle of $4.8^0$.

*Procedure.* Each participant performed a visual search task, in which a 4x4 search array was presented with one oddball. Participants had to indicate whether the oddball was on the right or left of the screen using a key press ('Z' for left, 'M' for right). Distractors were varied randomly in size to prevent low-level cues from influencing search.

*Data Analysis.* Response times faster than 0.3 seconds or slower than 4 seconds were removed from the data. This step removed only 0.76% of the data and improved the overall response time consistency but did not qualitatively alter the results.

## Experiment S2: Target-present absent search with natural objects

*Participants.* A total of 16 participants (9 males, 23.31 ± 5.24 years) participated in this experiment.

*Stimuli.* The stimuli were identical to those used in Experiment S1.

*Procedure.* Participants performed a present-absent visual search task. Each trial began by presenting a red-coloured fixation cross of size 0.5 dva for 500 ms, followed by the presentations of a circular search array measuring 13°x13° for 10 seconds or until a response, whichever was sooner. The search array contained eight elements, of

which one could be different from the others. Participants identified and reported the presence of the target with a keypress ('A' for target absence and 'P' for target presence). Participants were instructed to respond as quickly and as accurately as possible. Incorrect trials were randomly repeated later.

Each participant completed 384 correct trials (absent trials: 48 shapes x 4 repetitions = 192, present trials: 24 image pairs x 2 (AB/BA) x 4 repetitions = 192). We used a total of 48 natural images from animate and inanimate categories. All images were presented against a black background. The main experiment block explained above was preceded by an identical practice experiment block of 20 trials involving unrelated stimuli. This experiment was hosted at the Pavlovia platform (https://pavlovia.org/) using custom programs written in PyschoPy (Peirce et al., 2019).

*Data Analysis.* Image Pairs with an overall accuracy of less than 50 % were removed. One target-present search was removed based on this criterion from further analysis.

**Experiment S3: Odd ball detection for perceptual space (Silhouettes)**
This data is from Experiment 1 of a previously published study (Pramod and Arun, 2016), and the salient details are reproduced here. The analysis of visual homogeneity is novel and unique to this study.

*Participants.* A total of 8 participants (5 females, aged 20-30 years) participated in this experiment.

*Stimuli.* Each stimulus was created by joining two of the seven possible parts. The full set consisted of 49 objects formed by all possible combinations of seven parts at two locations.

*Procedure.* Participants were seated approximately 60 cm from the computer monitor that was under the control of a custom program written using Psychtoolbox in Matlab. Each trial began by presenting a fixation cross for 500 ms, followed by a 4 x 4 search array containing one oddball item among multiple identical distractors with a red vertical line down the middle. Items were jittered. Participants were asked to report the side on which the oddball target appeared as quickly and as accurately as possible using a keypress (Z for left, M for right). All images were presented against a black background.

*Data Analysis.* Response times faster than 0.3 seconds or slower than 4.5 seconds were removed from the data. This step removed 1.2% of the data and improved the overall response time consistency but did not qualitatively alter the results.

**Experiment S4: Target-present absent search with Silhouettes**

*Participants.* A total of 11 participants (6 females, aged 20-30 years) participated in this experiment.

*Stimuli.* Stimuli were identical to Experiment S3.

*Procedure.* Participants were seated approximately 60 cm from the computer monitor that was under the control of a custom program written using Psychtoolbox in Matlab. Each trial began by presenting a fixation cross for 500 ms, followed by a 4 x 4 search array containing one oddball item among multiple identical distractors. Items were jittered. Participants were asked to report the presence of an oddball target as quickly and as accurately as possible using keypress ( Y for the presence of the target, N for the absence of the target). All images were presented against a black background.

*Data Analysis.* Response times faster than 0.3 seconds or slower than 5 seconds were removed from the data. This step removed 7 % of the data and improved the overall response time consistency but did not qualitatively alter the results. We predicted the response times of target-present and target-absent search display the same approach used for experiment 2 (see main text). We used the MDS embeddings from experiment S3, and the model has 7 free parameters. To avoid overfitting, we used leave-one-out cross-validation.

**Results**

In Experiment S1, we characterized the perceptual space of 48 natural objects using a left/right oddball detection task as before. Participants were highly consistent in their responses (correlation between mean response times of even- and odd-numbered participants: $r = 0.90$, $p < 0.0001$ across all $^{48}C_2 = 1128$ object pairs). In Experiment S2, we checked if visual homogeneity predicted target present/absent responses in visual search. Participants were highly accurate and consistent in their responses (accuracy, mean ± sd: 96 ± 1.8%; correlation between mean response times of even- and odd-numbered participants: $r = 0.94$, $p < 0.0001$ across 48 target-present searches, $r = 0.93$, $p < 0.0001$ across 48 target-absent searches). We estimated the visual homogeneity using the RT data from Experiment S1&2 by fitting model with 7 free parameters. The model predictions are shown in Figure S3A. As expected, the response times of present searches were positively correlated with the visual homogeneity ($r = 0.44$, $p < 0.05$) ,and the response times of absent searches were negatively correlated with visual homogeneity ($r = -0.72$, $p < 0.0001$).

In Experiment S3, we characterized the perceptual space of 49 silhouette objects using a left/right oddball detection task as before. Participants were highly accurate and consistent in their responses (accuracy, mean ± sd: 99 ± 0.5 %; correlation between mean response times of even- and odd-numbered participants: $r = 0.80$, $p < 0.0001$ across all $^{49}C_2 = 1176$ object pairs). In Experiment S4, we checked if visual homogenity predicted target present/absent responses in visual search. Participants were highly accurate and consistent in their responses (accuracy, mean ± sd: 92.74 ± 4.27%; correlation between mean response times of even- and odd-numbered participants: $r = 0.80$, $p < 0.0001$ across 48 target-present searches, $r = 0.67$, $p < 0.0001$ across 49 target-absent searches). We estimated the visual homogeneity using the RT data from the Experiment S3&4 by fitting a model with 7 free parameters. The model predictions are shown in Figure S3B. As expected, the response times of present searches were positively correlated with the visual homogeneity ($r = 0.70$, $p < 0.0001$), and the response times of the absent searches were negatively correlated with visual homogeneity ( $r = -0.81$, $p < 0.0001$).

**Experiment S1-2 (Natural objects large set)**

**Experiment S3-4 (Silhouettes)**

**Figure S3. Generalization to other objects**

(A) Response time for target present/absent responses in Experiment S2 (involving a larger set of natural objects) plotted against visual homogeneity calculated from Experiment S1.

(B) Response time for target present/absent responses in Experiment S4 (involving silhouettes) plotted against visual homogeneity calculated from Experiment S3.

# SECTION S4. VISUAL HOMOGENEITY PREDICTS SAME/DIFFERENT RESPONSES

## Introduction

In the main text, we have shown that visual homogeneity computations can be used to solve any task that requires discriminating between homogeneous and heterogeneous displays. Having shown in Experiments 1-2 that visual homogeneity predicts target present/absent responses, we wondered whether these results would generalize to other tasks. Here, we investigated the same/different task, in which participants have to view two items and indicate whether they are same or different using a key press.

Although the exact instructions of the target present/absent visual search task and the same/different task are quite different, we predicted that "same" responses would be related to the target-absent response, while the "different" responses would be related to the target-present response. This correspondence is interesting and non-trivial since it has never been made previously to the best of our knowledge.

## Experiment S5. Same/Different task

In Experiment S5, we recruited participants to perform a same/different task involving the same natural objects as in Experiment 1. The "same" trials and "different" trials were exactly matched to the target-absent and target-present conditions in the two experiments, to enable direct comparisons.

## Methods

*Participants.* A total of 16 participants (8 males aged 23.5 ± 3.5 years) participated in this experiment.

*Stimuli.* The stimulus set comprised a set of 32 grayscale natural objects (16 animate, 16 inanimate) presented against a black background. Same as in the main experiments 1&2.

*Procedure.* Participants performed a same-different task with a block of practice trials involving unrelated stimuli followed by the main task. Each trial began with a fixation cross (width 0.6°) for 500 ms, followed by two images of size 3.5 dva presented for 500 ms on a black background. The images were presented on either side of the fixation cross along the x-axis 3 dva away from the centre. A random position jitter of 0.5 dva was added in both directions. Participants were asked to identify if two images were the same or different and respond with a keypress ('Z' for same, 'M' for different) as quickly and accurately as possible. Participants could give responses up to 3.5 s. Each participant completed 256 same trials ( 32 objects x 8 repeats) and 256 different trials (32 randomly selected image pairs x 8 repeats). The experiment was created using PsychoPy (Peirce et al., 2019) and ported to the online Pavlovia platform for collecting data. Each participant adjusted a credit card image presented on the screen with keypresses to match their credit card size, ensuring identical image presentation across participants.

**Results**

In Experiment S5, participants were highly accurate and consistent in their responses (accuracy, mean ± sd: 91.4 ± 3.4 %; correlation between mean reaction times of even- and odd-numbered participants: $r = 0.50$, $p < 0.005$ across 32 same trials, $r = 0.71$, $p < 0.0005$ across 32 diff trials). The absent search response times from Experiment 2 predicted the same response times of Experiment S5 (correlation between response times: $r = 0.67$, $p < 0.0005$; Figure S4E). The present search response time from Experiment 2 predicted the different response times of Experiment S5 (correlation between response times: $r = 0.75$, $p < 0.0005$; Figure S4F). The response times of one task predict the response times of another on the same set of image pairs is expected when identical computations can solve both tasks.

We conclude that visual homogeneity computations can explain same-different judgements.

**Figure S4. Target absent/present responses predict same/different responses.**
(A) Example target-absent trial from the visual search task (Experiment 2).
(B) Example target-present trial from the visual search task (Experiment 2).
(C) Example "same" trial from the same-different task (Experiment S5), matched exactly to the target-absent trial in panel A.
(D) Example "different" trial from the same-different task (Experiment S5), matched exactly to the target-present trial in panel B.
(E) Response time on "same" trials in Experiment S5 plotted against response time for the corresponding target-absent trials from Experiment 1.
(F) Response time on "different" trials in Experiment S5 plotted against response time for the corresponding target-present trials from Experiment 1.

In Section S1, we have shown that visual homogeneity for each image is proportional to its distance to all other images, and that it is negatively correlated with target-absent response times. This raises the question of whether target-absent response times are affected by the other objects used in the experiment. We addressed this question using two experiments.

**Experiment S6. Visual search across diverse category context**
We first investigated the possibility that target present/absent response times could vary depending on the experimental context of other searches. To this end, participants had to perform target present/absent task in three separate blocks: searches involving animate objects, searches involving silhouette objects and a mixed block containing both animate and silhouette objects.

**Methods**

*Participants.* A total of 18 participants ( 12 males, aged 23.5 ± 3.2 years) participated in this experiment.

*Stimuli.* The stimulus set comprised a set of 16 grayscale natural objects (animates) and 16 silhouettes presented against a black background.

*Procedure.*  This experiment constitutes three blocks: Animal block, Silhouettes block, and mixed block. All participants performed trials from all the blocks, and the block order was counterbalanced across participants. Each participant performed 512 correct trials (128 from animate block, 128 from silhouette block and 256 from mixed block). In the animate block, there were 32  uniques conditions (16 present searches and 16 absent searches) repeated 4 times created from 16 animate images. A similar design was repeated for the silhouette block on 16 silhouette images. The mixed block was created by combining the animate blocks and silhouette blocks. The trial presentation order was random within a block. Participants were seated approximately 60 cm from the computer monitor that was under the control of a custom program written using Psychtoolbox in Matlab. Each trial started by presenting a fixation cross for 500 ms, followed by a 4 x 4 search array containing one oddball item among multiple identical distractors. Items were randomly jittered. Participants were asked to report the presence of an oddball target as quickly and as accurately as possible using keypress ( Y for the presence of the target, N for the absence of the target). All images were presented against a black background.

**Results**
Participants were highly accurate and consistent in their responses ( accuracy, mean ± sd: 96.9 ±1.8 % for Animate block, 97.9 ±1.3 % for mixed block,  97.7  ± 1.8 for silhouette block; correlation between mean reaction times of even- and odd-numbered participants: r = 0.93, p < 0.0005  for Animate block, r = 0.94, p < 0.0005 for Mixed

block, r = 0.95, p < 0.0005 for Silhouette block). The response time to searches in the animate block shows a striking correlation with the response times to the corresponding searches in the mixed block (correlation between reaction times: r < 0.96, p < 0.0001 for present searches, r < 0.95, p < 0.0001 for absent searches). Similarly, the response time to searches in the silhouette block shows a striking correlation with the response times to the corresponding searches in the mixed block (correlation between reaction times: r < 0.96, p < 0.0001 for present searches, r < 0.91, p < 0.0001 for absent searches). Even when the animal and silhouette images have completely different image statistics, there was no significant difference between reaction times in the interleaved and separate blocks (Figure S5 A & B). Hence, we conclude that context has no effect on visual homogeneity.

**Figure S5. Target-absent responses are unaffected by mixing disparate searches**
(A) Response times in the Mixed Block plotted against the corresponding response times in the Animal Block for present searches (*blue)*, and absent searches (*red*).
(B) Response time in Mixed Block plotted against the corresponding response times in the Silhouette-only Block, with conventions as in panel A.

**Experiment S7. Objects with uncorrelated dissimilarity**

Although the results of Experiment S6 show that target-absent searches are unaffected by whether they are surrounded by similar or mixed object categories, it is still possible that the average distance of each object to other objects was unaffected by mixing with other category objects but could be influenced by the experimental context of other objects in the same category.

To this end, we constructed two sets of 29 shapes (20 unique to each set, 9 common to both sets) (Figure S5A). We chose the two sets so that the predicted visual homogeneity (i.e. average distance to other objects in that set) relative to each set is uncorrelated (Figure S5B). We then performed a present/absent visual search block in which the 9 common objects are viewed in the context of the other objects in Set 1 or Set 2 in separate blocks.

If visual homogeneity depends on the objects being seen in a given block, we predicted that the target absent response times of the common objects will be uncorrelated. If on the other hand, the visual homogeneity of an object is unaffected by experimental context, we predicted that the absent search response times will be correlated. We tested this prediction using a target present/absent search experiment.

**Methods**

*Participants.* A total of 12 participants (7 males, aged 23.5 ± 1.16 years) participated in this experiment.

*Stimuli.* This stimulus set comprised of 49 silhouette shapes. Sets 1 & 2 were constructed by selecting 29 of 49 shapes where 9 shapes were common across sets in such a manner that the average dissimilarity of the 9 common shapes relative to the other objects in the two sets were uncorrelated (Figure S5A-B).

*Procedure.* This experiment comprised two blocks. All participants completed both blocks, and the block order was counterbalanced across participants. Each participant performed 464 correct trials (232 from block 1 and 232 from block 2). In each block there were 58 unique conditions (29 absent searches, 29 present searches) and each condition was repeated 4 times. The trial presentation order was random within the block. Other details were same as experiment S6.

*Data Analysis.* Response times faster than 0.3 seconds or slower than 5 seconds were removed. We used *"isoutlier"* Matlab function to remove the outliers in the data. These steps removed 6.6 % of the data and improved the overall response time consistency but did not quantitatively alter the results.

**Results**

Participants were highly accurate and consistent in their responses (accuracy, mean ± sd: 94.8 ± 2.6% for block 1, and 95.2 ± 3.1% for block 2; correlation between mean reaction times of even- and odd-numbered participants: $r = 0.94$, $p < 0.0005$ for block 1 and $r = 0.95$, $p < 0.0005$ for block 2).

For the common objects, we computed the average dissimilarity to other objects within the set and the average dissimilarity of the common objects were not correlated across sets (r = 0.21, p  = 0.6; Figure S6 B), which is by design. Interestingly, the target-absent responses were highly correlated across sets (r = 0.83, p = 0.05; Figure S6C).

We conclude that visual homogeneity is unaffected by the experimental context regardless similar or dissimilar objects.

**Figure S6. Target-absent responses are unaffected by disparate object context**

(A) 2D embedding of the 49 silhouettes based in the pairwise dissimilarities (1/RT) measured using odd-ball visual search experiment (Experiment S3). Shapes are coloured according to the set to which they are grouped: *red* for shapes common to set 1 & set 2, *blue* for shapes only in set 1, and *green* for shapes only in set 2.

(B) Average dissimilarity of the common items relative to items in Set 2 plotted against the average dissimilarity relative to items in Set 1. If visual homogeneity depends on the average distance to other objects in the immediate experimental context, then target-absent responses for the common objects should be uncorrelated when presented in a block containing Set 1 items compared to a block containing Set 2 items.

(C) Absent search response times for the common items in Block 2 (containing Set 2 items) against the corresponding search times in Block 1 (containing Set 1 items). The strong and significant correlation indicates that target-absent search times are independent of the immediate experimental context.

**Activation difference Target-present - target-absent**

**Figure S7. Brain activations for target-present and target-absent searches.**
Whole brain colormap of activation difference between target-present and target-absent searches. The color at each voxel represents the t-statistic computed between the participant-wise mean activations for target-present minus target-absent searches (averaged across searches of each type, and across a 3x3x3 voxel neighborhood centered around that voxel).

## Figure S8. Robustness of VH region in target present/absent search

(A) Searchlight map showing the correlation between visual homogeneity and mean activation of an example subject.

(B) Colormap representing the number of subjects for which a particular voxel belonged to the localized VH region.

(C) Colormap of the correlation between visual homogeneity and mean activation across eight subjects in Group 1.

(D) VH region obtained by thresholding the searchlight map in panel C.

(E) Correlation between visual homogeneity and mean activation for participants in Group 1 for the VH region identified from Group 1, and for the VH region identified from Group 2. Asterisks indicate statistical significance of each correlation, obtained

by sampling participants with replacement 10,000 times, and calculating the fraction of times the correlation was below zero (**** is $p < 0.0005$). The significant correlation in Group 2 for the region identified using Group 1 participants suggest that the VH region is consistently localized across subjects.

(F) Searchlight map similar to panel C, but for participants in Group 2.

(G) VH region obtained by thresholding the searchlight map in panel F.

(H) Correlation between visual homogeneity and mean activation for participants in Group 2, for the VH regions identified from Group 1 and from Group 2. Asterisks indicate statistical significance of each correlation, obtained by sampling participants with replacement 1000 times, and calculating the fraction of times the correlation was below zero (***is $p < 0.005$). The significant correlation in Group 1 for the region identified using Group 2 participants suggest that the VH region is consistently localized across subjects.

**Figure S9. Searchlight maps with response times**

(A) Colormap of correlation between mean activation and response times for target-present search arrays.

(B) Colormap of correlation between mean activation and response times for target-absent search arrays.

(C) Correlation between mean activation and response times for both target-present and target-absent search arrays. To prevent image-wise correlations from being confounded by overall activation level differences, we z-scored the mean activations for each voxel within a particular search type (present/absent) and then combined the mean activations. Likewise, for similar reasons, we z-scored the response times for each particular search type.

(D) Correlation between mean activation and all response times for key visual regions.Error bars represent the standard deviation of correlation obtained using a bootstrap process by repeatedly sampling participants with replacement 10,000 times. Asterisks represent statistical significance, estimated by calculating the fraction of bootstrap samples in which the observed trend was violated (* is p < 0.05, ** is p < 0.01, **** is p < 0.0001)

**Figure S10. Relative weights of target and distractor in target-present arrays**

(A) Colormap of correlation between observed and predicted voxel activity of the linear voxel model, in which target-present search array response is modelled as a linear combination of target and distractor activity (taken from responses to target-absent arrays).

(B) Region showing good model prediction, obtained by thresholding the colormap in (A).

(C) Target and distractor model coefficients in this region. Each point corresponds to model coefficients derived from a single voxel. Model coefficients for target and distractor are equal in weight (p = 0.33, sign-rank test across weights of 222 voxels in this region).

**Activation difference
Asymmetric - Symmetric objects**

**Figure S11. Brain activations for asymmetric and symmetric objects**
Whole brain colormap of activation difference between asymmetric and symmetric objects during the symmetry task. The color at each voxel represents the t-statistic computed between the participant-wise mean activations for asymmetric minus symmetric objects (averaged across objects of each type, and across a 3x3x3 voxel neighborhood centered around that voxel).

**Figure S12. Robustness of VH region in symmetry detection**

(A) Searchlight map showing the correlation between visual homogeneity and mean activation of an example subject.

(B) Colormap representing the number of subjects for which a particular voxel belonged to the localized VH region.

(C) Colormap of the correlation between visual homogeneity and mean activation across eight subjects in Group 1.

(D) VH region obtained by thresholding the searchlight map in panel C.

(E) Correlation between visual homogeneity and mean activation for participants in Group 1 for the VH region identified from Group 1, and for the VH region identified from Group 2. Asterisks indicate statistical significance of each correlation, obtained

by sampling participants with replacement 1000 times, and calculating the fraction of times the correlation was below zero (*** is p < 0.005 ). The significant correlation in Group 2 for the region identified using Group 1 participants suggest that the VH region is consistently localized across subjects.

(F)  Searchlight map similar to panel C, but for 7 participants in Group 2.

(G)  VH region obtained by thresholding the searchlight map in panel F.

(H)  Correlation between visual homogeneity and mean activation for participants in Group 2, for the VH regions identified from Group 1 and from Group 2. Asterisks indicate statistical significance of each correlation, obtained by sampling participants with replacement 1000 times, and calculating the fraction of times the correlation was below zero (*** is p < 0.005). The significant correlation in Group 1 for the region identified using Group 2 participants suggest that the VH region is consistently localized across subjects.

**Figure S13: Searchlight maps for response time during symmetry task**

(A) Colormap of correlation between mean activation and response times for asymmetric objects.

(B) Colormap of correlation between mean activation and response times for symmetric objects.

(C) Correlation between mean activation and response times across both asymmetric and symmetric objects. To prevent image-wise correlations from being confounded by overall activation level differences, we z-scored the mean activations for each voxel within a particular object type (asymmetric/symmetric) and then combined the mean activations. Likewise, for similar reasons, we z-scored the response times for each particular object type before combining.

(D) Correlation between mean activation and all response times for key visual regions. Asterisks indicate statistical significance calculated in the same way as Figure 4D.

## SECTION S8: ENCODING OF VISUAL HOMOGENEITY IN BRAIN ACROSS EXPERIMENTS

In Experiments 1-4, we showed that visual homogeneity can be used to solve a variety of visual tasks that require discriminating between homogeneous and heterogeneous displays. We found that the region anterior to Lateral Occipital Cortex is encoding visual homogeneity signal during both present-absent search task and symmetry judgement task. We compared the spatial location of the visual homogeneity region by directly comparing the region masks derived from Experiments 2 & 4. It can be seen that the VH region localized from the present/absent visual search task in Experiment 2 overlaps reasonably well with the VH region localized from the symmetry detection task in Experiment 4 (Figure S14).

**Figure S14. Comparing the VH region from Experiments 2 & 4.** Key visual regions identified using standard anatomical masks: early visual cortex (EVC), area V4, lateral occipital (LO) region. The VH region from the present/absent search task (Experiment 2, Figure 4C) is overlaid with the VH region identified from the symmetry task (Experiment 4, Figure 6C).

# SECTION S9. RELATING TARGET-ABSENT RESPONSES AND SYMMETRY

In Experiments 1-4, we showed that visual homogeneity can be used to solve a variety of visual tasks that require discriminating between homogeneous and heterogeneous displays. These findings suggest a direct empirical link between two disparate tasks, namely visual search for a target and symmetry detection.

In particular, since target-absent response times are inversely related to visual homogeneity, we can take its reciprocal as a direct estimate of visual homogeneity. Since response times for asymmetric and symmetric objects during a symmetry detection task have opposite correlations to visual homogeneity, we predict that they will have opposite correlations with the reciprocal of target-absent response time. In Experiment S7, we tested this prediction by measuring target-absent response times for symmetric and asymmetric objects used in Experiment 4.

## Methods

### Experiment S8. Target present-absent search with Symmetric/Asymmetric objects
*Participants.* A total of 17 participants (10 females, aged 22 ± 5.3 years) participated in this experiment.
*Paradigm.* Participants performed a target-present/absent search task. Participants completed 512 correct trials (64 present conditions x 4 repetitions + 64 absent conditions x 4 repetitions). Participants reported the presence or absence of the target using the 'P' or 'A' key press. We used the same 64 baton shapes used in experiment 3. Each array had eight items arranged along a circular grid of radius 5 dva from the centre of the screen. Each item measured 2 dva. There was a random position jitter of ±0.6° in both X and Y directions. All other task details are the same as experiment 1.

## Results

An example search array from Experiment S8 is shown in Figure S15A. Likewise, an example screen from the symmetry detection task is shown in Figure S15B.

Participants were highly accurate and consistent in their responses (accuracy, mean ± sd: 97.19 ± 2%; correlation between mean reaction times of even- and odd-numbered participants: $r = 0.86$, $p < 0.0001$). As predicted, response times to asymmetric objects during the symmetry detection task in Experiment 4 were positively correlated with the inverse of the absent-search times, but this correlation was not statistically significant (Figure S15C). Likewise, response times for symmetric objects in Experiment 4 were negatively and significantly correlated with the inverse of absent-search times (Figure S15D). Thus, the reciprocal of absent search times can be taken as a decision variable for the symmetry detection task.

Thus, there is a direct and non-trivial empirical link between target-absent response times in a visual search task and response times in a symmetry detection task, because both tasks rely on the same decision variable, namely visual homogeneity.

**Figure S15. Target-absent search times predict symmetry detection**

(A) Example search array from Experiment S7.

(B) Example display containing a symmetric object from Experiment 4.

(C) Response times for asymmetric objects in Experiment 4 plotted against their target-absent response time inverse in Experiment S7.

(D) Response times for symmetric objects in Experiment 4 plotted against their target-absent response time inverse in Experiment S7.

# SECTION S10. VISUAL HOMOGENEITY EXPLAINS ANIMATE CATEGORIZATION

## Introduction

Since visual homogeneity for any image is computed as its distance to some fixed point in perceptual space, we reasoned that shifting this fixed point to the center of a particular object category would make it automatically a decision variable for this category.

To test this prediction, we analyzed data from Experiment 1 of a previous study in which participants had to categorize images as belonging to three hierarchical categories: animals, dogs or Labradors, and also performed an oddball detection task using these same images (Mohan and Arun, 2012). The oddball detection task data is already described above as Experiment S1. The categorization task is summarized below.

## Methods

*Participants.* A total of 12 participants, aged 20-30 years were recruited for the experiment.

*Stimuli.* The stimuli consisted of 48 grayscale natural objects (24 animate, 24 inanimate) presented against a black background.

*Procedure.* Participants performed three separate blocks of categorization: an animal task, a dog task and a Labrador task, with block order counterbalanced across participants. Each block began with a preview of all objects to avoid confusion regarding the category, and each trial consisted of a fixation cross displayed for 750 ms, followed by a test object for 50 ms followed by a noise mask for 250 ms. Participants had to indicate whether the object belonged to the category (animal/dog/Labrador) using a keypress ("Y" if yes, "N" if no).

*Model fitting for visual homogeneity.* We started by embedding all 48 objects into a 8-dimensional space using multidimensional scaling. For each image, visual homogeneity is calculated as its distance from a fixed point in this multidimensional space. To calculate visual homogeneity for a particular category task, we adjusted the fixed center for visual homogeneity calculations so as to maximize the difference between the correlation of visual homogeneity with objects outside vs within that category. In this manner, we calculated the correlation between visual homogeneity for all objects in the category and the corresponding categorization times, and likewise for the non-category objects.

## Results

Figure S16A shows an example screen from the animal categorization task. For this task, we estimated an optimal center for visual homogeneity computations by maximizing the difference in correlation for inanimate and animate objects. The resulting model fits are shown in Figure S16B-C. It can be seen that categorization times for are positively correlated with visual homogeneity for animate objects (Figure S16B) but

negatively correlated for inanimate objects (Figure S16C), suggesting that visual homogeneity can be used to solve the animate categorization task. We obtained similar results for the dog task (Figure S16E-G) and for the Labrador task (Figure S16I-K).

We conclude that visual homogeneity can serve as a decision variable for categorization tasks at least for the categories tested here, and provided the fixed center for the visual homogeneity computations can be shifted to the center of each category.

## Can target-absent response times explain categorization?

Since the inverse of target-absent response times is a measure of visual homogeneity, we wondered whether they would directly predict the visual homogeneity predictions of each task. To this end, we took the absent-search response times from Experiment S2 and asked whether they are correlated with the visual homogeneity optimized for each categorization task. This revealed a significant positive correlation for all three tasks (Figure S17).

**Figure S16. Visual homogeneity predicts categorization times**

(A) Example trial of the animal categorization task. Stimuli was presented for 50 ms followed by a noise mask. Subjects responded if the presented image is an animal or not with Y/N key responses.

(B) Average categorization times for animals plotted against visual homogeneity relative to an optimum center for this task, calculated from oddball detection task data (Experiment S1).

(C) Same as panel B but for inanimate objects.

(D) Example trial of the dog categorization task.

(E) Average categorization times for dogs plotted against visual homogeneity relative to an optimum center for this task, calculated from oddball detection task data (Experiment S1).

(F) Same as panel E but for non-dogs.

(G) Example trial of the Labrador categorization task.

(H) Average categorization times for dogs plotted against visual homogeneity relative to an optimum center for this task, calculated from oddball detection task data (Experiment S1).

(I) Same as panel H but for non-Labradors.

**Figure S17. Target-absent search predicts visual homogeneity for each category.**

(A) Inverse of target-absent search times from Experiment S2 plotted against the optimized visual homogeneity from the animate task.

(B) Inverse of target-absent search times from Experiment S2 but now plotted against the optimized visual homogeneity from the dog task.

(C) Inverse of target-absent search times from Experiment S2 but now plotted against the optimized visual homogeneity from the Labrador task.

# SUPPLEMENTARY REFERENCES

Mohan K, Arun SP (2012) Similarity relations in visual search predict rapid visual categorization. J Vis 12:19–19.

Peirce J, Gray JR, Simpson S, MacAskill M, Höchenberger R, Sogo H, Kastman E, Lindeløv JK (2019) PsychoPy2: Experiments in behavior made easy. Behav Res Methods 51:195–203.

Pramod RT, Arun SP (2016) Object attributes combine additively in visual search. J Vis 16:8.

Pramod RT, Arun SP (2020) Improving Machine Vision using Human Perceptual Representations: The Case of Planar Reflection Symmetry for Object Classification. IEEE Trans Pattern Anal Mach Intell in press Available at: https://pubmed.ncbi.nlm.nih.gov/32750809/ [Accessed September 16, 2020].