Title: Structural pre-training improves physical accuracy of antibody structure prediction using deep learning.

Authors: Jarosław Kończak[1], Bartosz Janusz[1], Jakub Młokosiewicz[1], Tadeusz Satława[1], Sonia Wróbel[1], Paweł Dudzic[1], Konrad Krawczyk[1]*

1. NaturalAntibody, Kraków, Poland

Correspondence: konrad@naturalantibody.com

Abstract: Protein folding problem obtained a practical solution recently, owing to advances in deep learning. There are classes of proteins though, such as antibodies, that are structurally unique, where the general solution still lacks. In particular, the prediction of the CDR-H3 loop, which is an instrumental part of an antibody in its antigen recognition abilities, remains a challenge. Antibody-specific deep learning frameworks were proposed to tackle this problem noting great progress, both on accuracy and speed fronts. Oftentimes though, the original networks produce physically implausible bond geometries that then need to undergo a time-consuming energy minimization process. Here we hypothesized that pre-training the network on a large, augmented set of models with correct physical geometries, rather than a small set of real antibody X-ray structures, would allow the network to learn better bond geometries. We show that fine-tuning such a pre-trained network on a task of shape prediction on real X-ray structures improves the number of correct peptide bond distances. We further demonstrate that pre-training allows the network to produce physically plausible shapes on an artificial set of CDR-H3s, showing the ability to generalize to the vast antibody sequence space. We hope that our strategy will benefit the development of deep learning antibody models that rapidly generate physically plausible geometries, without the burden of time-consuming energy minimization.

Introduction

Antibodies are the largest group of biologics (Kaplon et al. 2022), recently reaching hundred approved molecules (Mullard 2021) with more forecasted to come to clinical use (Krawczyk, Buchanan, and Marcatili 2021). Because of their therapeutic role, there is much interest in the development of computational methods addressing these molecules (Wilman et al. 2022).

One of the crucial properties of an antibody to be predicted is its structure (Kovaltsuk et al. 2017). The antigen-recognizing variable domain has an immunoglobulin fold, with a largely conserved framework region and three complementarity-determining

region loops (CDRs) defining the antigen-recognizing paratope. Of the three loops the third CDR of the heavy chain (CDR-H3) is particularly problematic for structure prediction (Marks et al. 2017; Ruffolo et al. 2020; Abanades, Georges, et al. 2022; Almagro et al. 2014). Methods such as AlphaFold2 (Jumper et al. 2021) have made great progress in general protein structure prediction, however, some of its applications lack in face of antibodies whose CDRs undergo a different evolutionary process (evolving in days rather than millions of years), and thus are structurally unique (Regep et al. 2017).

To address this issue, but also to draw from AlphaFold2 and its derivatives (Ahdritz et al. 2022; Lin et al. 2022), many antibody-specific deep learning structure prediction methods have been introduced (Wilman et al. 2022; Lin et al. 2022). The algorithms started by addressing CDR-H3 loop prediction such as DeepH3 (Ruffolo et al. 2020) and AbLooper (Abanades, Georges, et al. 2022), after extending these to the entire variable domain via NanoNet (Cohen, Halfon, and Schneidman-Duhovny 2022) and the entire Fv molecule by DeepAb (Ruffolo, Sulam, and Gray 2022), IgFold (Ruffolo et al. 2022), AbodyBuilder2 (Abanades, Wong, et al. 2022), EquiFold (Lee et al. 2022) and tFold-Ab (Wu et al. 2022). As opposed to the homology methods that reported CDR-H3 root mean squared deviation (RMSD) accuracies in the region of 3-4Å (Almagro et al. 2014), the deep learning methods achieve an RMSD of 2-3Å RMSD. The methods are also faster - achieving predictions in seconds, rather than in minutes, as was the case with best homology modeling tools (Leem et al. 2016; Weitzner et al. 2014) and tens of minutes in case of AlphaFold2.

The methods introduced a variety of architectures such as residual convolutional networks (Ruffolo, Sulam, and Gray 2022), graph neural networks (Abanades, Georges, et al. 2022) or drawing from the structure of AlphaFold2 (Ruffolo et al. 2022; Abanades, Wong, et al. 2022). In certain guises, large-scale sequence information from the Observed Antibody Space (Olsen, Boyles, and Deane 2022; Kovaltsuk et al. 2018) was introduced to provide a sequence pre-training basis for the models (Ruffolo et al. 2022). The methods achieve similar accuracies to each other and the original AlphaFold, perhaps with a minor advantage from focusing on the antibody datasets.

Though in statistical terms the methods do not provide an order of magnitude improvement in antibody prediction accuracy with respect to AlphaFold2, they have a great advantage in terms of faster running time. Coordinates can be generated in seconds, rather than in minutes or even hours as is the case with AlphaFold2. Though the networks produce the results fast, they are afflicted by problems relating to the physical plausibility of the generated structures (Fernández-Quintero et al. 2022). The problem was highlighted by methods such as Ablooper, IgFold, and AbodyBuilder2, as

they can produce the coordinates rapidly, but then the final structure needs to be energy minimized (Ruffolo et al. 2022; Abanades, Georges, et al. 2022; Eastman et al. 2017).

One can address such issues in coordinate generation by employing special loss functions such as the Frame Aligned Point Error (FAPE), or the distogram prediction loss in AlphaFold2 (Jumper et al. 2021). One can also introduce physical priors to improve the quality of generated coordinates (Eguchi, Choe, and Huang 2022). In place of employing explicit energy calculator programs such as OpenMM, one can attempt to train a neural network to approximate such functions (Yang, Xiong, and Zonta 2022).

Here we address the problem of improving antibody structure prediction by generating more physically plausible structures directly from the network. An important aspect that impacts model performance is the availability of data that can be used in the training process. With antibody diversity estimated to be 10^{18} unique molecules, the publicly available 6,500 of redundant experimentally resolved antibody structures are a relatively small sample. Most of the models that attempted antibody structure prediction were trained on such a small publicly available dataset of antibody structures, and to the best of our knowledge only IgFold employed AlphaFold to augment its input dataset. Such a small dataset of antibodies is clearly powerful enough to teach the broad features of an immunoglobulin shape but falls short of making the structures physically plausible out-of-the-network. To address this issue, one might attempt to augment input dataset to expose the network to larger amount of correct bond geometries. Here we demonstrate that pre-training a network on a large, augmented dataset of antibody model structures allows it to learn such physical features.

Results

Problem setup.

We test the hypothesis that pre-training on a large set of model structures allows the network to learn physically plausible conformations that can then be fine-tuned on the real dataset of crystal structures. For this effort, we focus on the distances of the peptide bond, simplified to the distance between consecutive $C\alpha$ carbons. In crystal structures, the distribution of such distances is firmly centered on 3.8Å, with a small standard deviation in the order of 0.1Å. Current deep learning models are trained to have the distribution of $C\alpha$ distances centered on 3.8, however, with a much larger standard deviation. This results from the models oftentimes producing peptide bonds

that are implausibly far away or close together (Figure 1) - though they are close enough in RMSD space to the template that they aim to reproduce.

AbLooper 3mxw unrefined CDR-H3   IgFold 3lmj unrefined CDR-H3

Figure 1. Example of CDR-H3 predictions with consecutive Cα distances requiring refinement. Distances outside of the range of [3.6Å 3.9Å] range are circled. The two structures are outputs from the neural networks of AbLooper and IgFold, without applying refinement post-processing. After energy refinement using OpenMM and Rosetta respectively for each method, the distances become physically plausible, however at a high computational cost.

As the basis architecture, we aimed for the simplest deep learning model that would not rely on improvements such as problem-specific loss functions or all-atom predictions. For this purpose, we re-created the architecture of NanoNet (Cohen, Halfon, and Schneidman-Duhovny 2022). The model is a small residual neural network (seven blocks, 1.9m parameters) predicting coordinates directly, in comparison to other networks using more advanced architectures and training regimes. In its published form NanoNet predicts all the backbone atoms, however, we implemented a version only predicting Cα to make sure we provide the model with minimal information.

For training & testing the network, we employed two augmented sets of homology models for pre-training, a set of crystal structures for fine-tuning and the Rosetta test set as the hold-out. The Rosetta test set was previously used to benchmark several models (Abanades, Georges, et al. 2022; Ruffolo et al. 2020), but we reduced it to 45 structures due issues such as incomplete chains. The crystal structure dataset was obtained from the PDB by identifying antibodies therein (Dunbar et al. 2014; Ferdous and Martin 2018). Here we have three datasets, CrystalHeavy, consisting of heavy

chain structures, CrystalLight, consisting of light chain structures and CrystalCombined, where we merged the two previous datasets. We used two pre-training datasets, 'Natural' and 'Homology'. The Homology dataset results from homology modeling a subset of approximately 40,000 paired structures available in OAS (Kovaltsuk et al. 2018; Olsen, Boyles, and Deane 2022). To control whether the results we obtain are the function of the dataset we chose and the homology method we implemented, we also employed the Natural dataset that was created independently of NaturalAntibody. This consisted of the public-response structures, carefully curated from naturally occurring antibodies in NGS datasets (Raybould et al. 2021). We also created a combined pre-training dataset consisting of all heavy and light chains in the Natural and Homology datasets, termed PretrainingCombined. All the datasets employed are briefly described in Table 1, with details in Methods.

Table 1. Datasets employed in this study. For details please refer to Methods.

Dataset	Size (#structures)	Comment
Rosetta test set	45	Employed as hold-out for testing.
CrystalHeavy	1,813	Heavy chain structures from the PDB
CrystalLight	1,451	Light chain structures from the PDB
CrystalCombined	3,264	Heavy and light chain structures from the PDB
Natural	23,697	Homology models of the public response structures, containing heavy and light chains
Homology	47,090	Homology models of a subset of OAS paired data, containing heavy and light chains.
PretrainingCombined	135,914	Combination of all the heavy and light chains from Homology and Natural datasets.

Structural and sequence similarities between pre-training data and real crystal structures - controlling for data leaks.

There exists a risk of data leakage between the pre-training and crystal structure datasets. The similarities could arise from 1) data leakage of templates between pre-training and crystal structure datasets 2) close sequence identity between pre-training and crystal structure datasets as well as 3) close data leakage as a result of test templates being employed in generating the datasets.

In our Homology pre-trained dataset, we ensured that no templates were being used that were in the Rosetta test set, judging by identical CDR-H3/L3 sequences. No such control was possible for the Natural dataset as it was pre-prepared. Attempting a conservative approach, we purged the Homology and Natural datasets from sequences that had a close resemblance to those in the entire crystal structure dataset as judged by identical CDR-H3 or CDR-L3.

Even after removing all the non-identical CDR-H3s and CDR-L3s, the pre-training datasets still had structures within 1Å RMSD of one in the Rosetta training set, which were subsequently removed. A total of 4761 structures were removed from the Homology dataset and 339 from the Natural dataset. Afterwards, the Homology dataset had an average CDR-H3 RMSD of 2.8Å to the closest CDR-H3 in the Rosetta test set with the corresponding figure for the Natural dataset being 3.2Å. In total, 146 structures in the crystal dataset had an RMSD of less than 1Å to the closest one in the Rosetta test set, indicating that diverse sequences of CDR-H3 can still adopt similar folds.

Finally, we also checked the overlap between the structural training set 'purged' of identical CDR-H3s, with that of the Rosetta test set, given in Table 1. Overall, we did not note radical closeness of the pre-training datasets to that of the Rosetta test set.

Table 1. CDR-H3 Sequence overlaps between the CrystalHeavy and the pre-training datasets. The alignments were computed for length-matched IMGT CDR-H3s using the biopython pairwise alignment function.

	Rosetta Test Set (n=45)			Crystal Structures (CrystalHeavy) (n=1,813)		
	μ	Max	Min	μ	Max	Min
Crystal Structures (CrystalHeavy)	57%	92%	25%	n/a		
Natural pre-training	54%	77%	33%	46%	88%	0%
Homology pre-training	66%	91%	38%	59%	92%	0%

Effect of structural pre-training on the number of incorrect peptide bonds in heavy chain prediction.

Equipped with two pre-training sets, Natural and Homology, we used our interpretation of the NanoNet model to see whether pre-training has any effect on the number of incorrect peptide bonds. We defined the 'incorrect' peptide bonds as those falling outside of the range [3.6Å,3.9Å].

For training, we employed a simplistic loss function that consisted of the Mean Squared Error in Cα of the predicted vs template positions, together with the consecutive Cα distance loss parameter. The Cα distance loss component is weighted, with higher weights incurring a larger penalty for consecutive Cα's distance being different from 3.8Å. For training, we checked the effect of the Cα loss weight of 1, 5, 10, 15, 20.

For each value of the Cα loss weight, we trained six models to predict the heavy chain. Three models without any benefit of pre-training, each for Natural, Homology, and CrystalHeavy with a learning rate of 10^{-3}. Such models were named after the dataset and the Cα weight, e.g. CrystalHeavy model with the Cα weight of 5 would be called CrystalHeavy5. Then, each of the three models served as a pre-training basis for training on the CrystalHeavy structure dataset with a learning rate of 10^{-5}. In each case of fine-tuning the Cα weight was the same as in pre-training. A fine-tuned model would be called by combining its pre-trained name with CrystalHeavy and the Cα parameter. For instance, a model pre-trained on Homology with the Cα weight of 10

would be Homology10CrystalHeavy10. Using the Crystal dataset for both pre-training and fine-tuning was supposed to contrast the effects of using the Natural and Homology pre-training datasets. Each of the models was benchmarked on the Rosetta test set, noting the number of peptide bonds outside of the [3.6,3.9] range, median and standard deviation of the peptide bond distribution as well as the $C\alpha$ RMSD of the CDR-H3 (after aligning the entire V-region). All the results are compiled in Table 2.

Though there are discrepancies between CDR-H3 modeling quality, all the models appear to end up within a quality range, rather than specific models being better than others by an order of magnitude.

In each case reported in Table 2, models that had the benefit of pre-training using either the Homology or Natural dataset produced better peptide bond lengths than base models without pre-training. In contrast, pre-training on the CrystalHeavy structure dataset led to worse peptide bond lengths than pre-training on either Natural or Homology dataset, showing the benefit of the different base models. The number of incorrect peptide bonds is lower with pre-training without a significant effect on the quality of CDR-H3 prediction.

As expected, the higher the weight for the $C\alpha$ penalty, the lower the number of peptide bonds falling outside of our predefined erroneous range. Note, however, that even the highest values for the loss penalty we employed in Table 2 (20), did not approach the crystal structure number of bad bonds on the same dataset which is 26. To test the limits of the $C\alpha$ penalty, we employed a radically higher weight of 100. The resulting CrystalHeavy100 model achieved a radically worse number of peptide bonds, than models with lower penalties (3,910). By contrast the Natural100Crystal100 model achieved 138 incorrect bonds. This suggests that there are limits to biasing the loss function that can be overcome by the benefit of a larger pre-training test set.

Altogether, these results demonstrate that using structural pre-training, appears to reduce the number of incorrect peptide bonds independently of the weight of $C\alpha$ and the training regime, without the detriment to the CDR-H3 RMSD accuracy.

Table 2. Structural pre-training improves the peptide bond length quality of the model. We checked to what extent increasing the weight on the Cα bond in the loss function improves the matters vs pretraining. In each case, increasing the Cα bond weight in loss reduces the number of bad bonds. However in each case, consistently, the models that had been pre-trained achieved the best results, on both pre-training datasets. For contrast, the very bottom row shows the peptide bond Cα distances from the crystal structures in the Rosetta test dataset. The results in the table are grouped by their Cα loss penalty weights.

Model	Cα weight	#d < 3.6Å	#d>3.9Å	Sum bad bonds	σ	μ	Mean IMGT H3 RMSD
CrystalHeavy1	1	1330	1176	2506	.26	3.73	2.11
Natural1	1	665	501	1166	.19	3.73	2.79
Homology1	1	976	372	1348	.19	3.70	2.06
CrystalHeavy 1 CrystalHeavy 1	1	1091	974	2065	.23	3.72	2.09
Natural1 CrystalHeavy 1	1	477	597	**1074**	.16	3.75	2.20
Homology1 CrystalHeavy 1	1	603	634	1237	.16	3.75	2.04
CrystalHeavy 5	5	328	978	1306	.13	3.79	2.15
Natural5	5	426	843	1269	.16	2.77	2.26
Homology5	5	702	529	1231	.18	3.72	2.02
CrystalHeavy 5 CrystalHeavy 5	5	503	493	996	.12	3.75	2.17
Natural5 CrystalHeavy 5	5	208	641	849	.11	3.79	2.16
Homology5 CrystalHeavy 5	5	209	563	**772**	.11	3.78	2.10
CrystalHeavy 10	10	345	546	891	.11	3.76	2.19
Natural10	10	334	352	686	.13	3.75	2.26
Homology10	10	238	741	979	.12	3.78	2.14
CrystalHeavy 10 CrystalHeavy 10	10	300	396	696	.10	3.75	2.20

Natural10 CrystalHeavy 10	10	117	316	433	.08	3.78	2.21
Homology10Crystal Heavy10	10	182	238	**420**	.08	3.76	2.22
CrystalHeavy15	15	272	835	1107	.14	3.78	2.10
Natural15	15	296	444	740	.11	3.77	2.34
Homology15	15	310	292	602	.13	3.75	2.20
CrystalHeavy15Cryst alHeavy15	15	135	408	543	.9	3.78	2.10
Natural15CrystalHea vy15	15	126	362	488	.8	3.78	2.27
Homology15Crystal Heavy15	15	122	189	**311**	.7	3.77	2.16
CrystalHeavy20	20	265	600	865	.13	3.77	2.19
Natural20	20	271	185	456	.10	3.75	2.19
Homology20	20	298	394	692	.12	3.76	2.25
CrystalHeavy20Cryst alHeavy20	20	111	396	507	.08	3.78	2.26
Natural20CrystalHea vy20	20	83	358	441	.07	3.79	2.19
Homology20Crystal Heavy20	20	50	349	**399**	.07	3.79	2.14
Rosetta test set crystal structures	n/a	1	25	26	.05	3.8	n/a

Effect of mixing heavy and light chain predictions

The previous experiment consisted entirely of the heavy chain predictions. We, therefore, tested a hypothesis that creating a combined predictor of heavy and light chains would offer better results on the constraints of peptide bonds, by the same virtue of using a larger dataset.

We employed three training datasets/regimes - heavy chain only (CrystalHeavy), light chain only (CrystalLight), and combining the heavy and light prediction (CrystalCombined). Each model was trained in three copies to test the reproducibility. We employed the $C\alpha$ penalty of 3.0, so as not to give it too much bias but also so as not to leave the model too reliant on the template MSE loss as well. The heavy models were tested on the CDR-H3 structures from the Rosetta test, the light ones on the CDR-L3 from the Rosetta test, and the combined set on both. The results are compiled in Table 3.

Judging by RMSD accuracy in Table 3, predicting the CDR-L3 chain is a much easier task for the network than CDR-H3 prediction - except for 3mlr which is an outlier with a shifted beta sheet (Figure 2). We do not note any observable benefit or detriment to the prediction of CDR-H3 or CDR-L3 by combining the predictions. However, it appears that having access to more structures allowed the combined model to reduce the number of incorrect peptide bonds across heavy and light chains. This provides supplementary evidence that augmenting the datasets in antibody modeling appears to have a favorable effect on the basic physical plausibility of produced structures without significant detriment, nor benefit to the quality of the estimated backbone shape.

Figure 2. 3mlr outlier in light chain modeling. Our prediction (pink) has been overlaid on the native structure (green). One beta strand appears to shift with respect to where it would normally be expected in the immunoglobulin fold. Our modeling consistently failed in that case and produced CDR-L3 RMSD in the region of 10Å.

Table 3. Contrasting of CDR-H3/CDR-L3 modeling between chain-specific models and the combined model. We trained three different models on a different train/validation split on the CrystalHeavy, CrystalLight and CrystalCombined datasets. We used the Rosetta test set to verify the CDR-H3 and CDR-L3 predictions only. It appears that combining heavy and light chain predictions does not improve the accuracy of CDR3 prediction based on RMSD. However, it appears to contribute to a smaller number of bad peptide bonds (<3.6Å or >3.9Å) in the resulting structures.

	Heavy-only Model		Light-only Model		Combined Heavy/Light Model	
	#Bad Bonds	CDR3 RMSD	#Bad Bonds	CDR3 RMSD	#Bad Bonds	CDR3 RMSD
CrystalHeavy	1802 1832 1808	2.09 2.11 2.15	N/A		1506 1383 1429	2.16 2.08 2.07
CrystalLight	N/A		1419 1795 1402	0.88 0.96 1.13	1231 1047 1162	0.9 0.86 0.96

Benchmarking antibody structure prediction methods for their ability to produce plausible physical peptide bond lengths.

We aimed to establish how the effects of CDR-H3 and peptide bond length accuracies are placed in the context of other available methods. For this reason, we tested those that were freely available for download & academic purposes. These criteria were satisfied by AbLooper, IgFold, AbodyBuilder2, and ESMFold.

All the methods except for AbLooper produce full antibody structures. Ablooper requires the framework to be modeled and predicts the CDRs only. We supplied the real crystal structures of our Rosetta test set as a basis for AbLooper. IgFold, AbodyBuilder2, and AbLooper produce excellent peptide bond lengths when allowed the refinement step of the structure produced by the network. Therefore, for the analysis here, we employed the unrefined structures produced by these methods straight from the network. The ESMFold models were used directly as produced by the network.

Given the findings from previous sections, we created a combined heavy/light chain pre-trained model, by merging the Homology and Natural datasets together (PretrainedCombined). We employed $C\alpha$ loss penalty of 100 and thus called the model PretrainedCombined100. This model was designed to be a radical version that reduces the number of bad peptide bonds. For contrast we also employed CrystalHeavy1 and CrystalHeavy100 models, to demonstrate the effects of no-pretraining and high $C\alpha$ penalty loss.

We only focused on the prediction of $C\alpha$ CDR-H3 accuracy, as the methods produce different outputs from the network - AbLooper only does CDRs, NanoNet and IgFold only backbone and ESMFold and AbodyBuilder2 produce side-chains as well. The CDR-H3 predictions are aligned to the original crystal structures and the RMSDs for each method are given in Figure 3. Even though RosettaAntibody was not a test set for all methods, (validation set for AbodyBuilder2 and no control for ESMFold), all the methods appear to produce a similar distribution of their predictions (Figure 3). This could be indicative of the limits of current deep learning methods in backbone shape prediction. This is of course notwithstanding producing supplementary output, such as additional backbone atoms to $C\alpha$, side chains, or the physical plausibility of the structures.

In Table 4 we summarize the number of bad peptide bond distances according to our definition that all the methods in Figure 3 achieved. Unlike in Table 2 where we calculated the total number of bad $C\alpha$ distances, here we only calculated the peptide bonds in the IMGT-Defined CDR-H3 region. Our pre-trained network achieved the least number of bad peptide bond distances, followed by ESMFold and IgFold. The

training regimen that did benefit from pre-training (CrystalHeavy100), obtained a notably worse number of bad peptide bond distances, 527 vs 20 in PretrainedCombined100. Furthermore, the predictions of the PretrainedCombined100 are well centered on 3.8Å (Figure 4), with similar distribution shape in ESMFold. Other methods appear to produce distances even in the range below 3Å.

These results suggest that the pre-training strategy we introduced could have an effect on the number of correct peptide bonds, without notable detriment to CDR-H3 prediction accuracy with respect to other methods, despite simplistic model and training regimen.

Table 4. **Number of bad peptide bonds on the Rosetta test benchmark**. The peptide bond distances were calculated on IMGT-defined CDR-H3 only.

Model	#Cα–Cα <3.6Å, Cα–Cα >3.9Å
PretrainedCombined100	20
CrystalHeavy1	357
CrystalHeavy100	527
NanoNet	278
AbLooper	369
IgFold	110
AbodyBuilder2	297
ESMFold	65

Figure 3. Accuracy of the benchmarked models on the Rosetta dataset. The CDR–H3 were structurally aligned and consecutive Cα distances and RMSD were calculated. The Rosetta test set was also a test set for IgFold and AbLooper. It was a validation set in the case of AbodyBuilder2 and there was no control possible in the case of ESMFold. Despite no proper control for test in such cases, all the methods appear to be in a similar range for their predictions, suggesting that the deep learning predictions of CDR–H3 converge in their accuracy. The error of such CDR–H3 prediction was calculated to be 0.25Å, as the RMSD of H3s of the same length resolved multiple times.

Figure 4. The distribution of Cα distances in the CDR-H3 predictions on the Rosetta test set. The red lines indicate the region of [3.6Å 3.9Å]. The distributions correspond to the predictions presented in Figure 3. Please note that the histograms have different bin sizes to fit the same axes in each image.

Effect of predicting out-of-distribution CDR-H3 structures.

Antibody structural modeling tools need to be able to generalize to the vast number of conformations these molecules can adopt (Briney et al. 2019). Therefore, we checked to what extent different networks can produce physically plausible out-of-distribution sequences. For this purpose, we randomly generated ten CDR-H3s, between lengths [10-19] for each of the sequences in the Rosetta test set. This was supposed to be a the most extreme case of introducing the diversity, as opposed to following the natural substitution profiles (Młokosiewicz et al. 2022) or sampling novel sequences from the OAS (Olsen, Boyles, and Deane 2022; Kovaltsuk et al. 2018). It was checked that none of the generated CDR-H3s were in the crystal structure or the pre-training datasets. This resulted in 450 sequences.

We ran the predictions on our pre-trained model PretrainedCombined100, those without the benefit of pre-training, CrystalHeavy1 and CrystalHeavy100 as well as on IgFold, ESMFold, AbLooper and AbodyBuilder2. The AbodyBuilder2 predictions (final refined models) were used by AbLooper for remodeling the CDRs.

For each model, we calculated the number of bad Cα values (<3.6Å and >3.9Å). The number of CDR-H3 bad Cα distances for each model is given in Table 5. It is evident that in their unrefined form, IgFold, AbodyBuilder2 and AbLooper produce a large number of Cα-Cα distances falling outside of [3.6Å, 3.9Å] range. As on the proper Rosetta test-set, IgFold appears to produce a smaller amount of distances that would

need to be refined as compared to AbLooper, AbodyBuilder2 or our not pre-trained models. From the previously developed methods, ESMFold does the best job of rapidly producing a low (509) number of incorrect bonds. Note that though the 509 values fall outside our range of [3.6Å, 3.9Å], the distribution is not too wide, not venturing below 2Å, which is not the case for other methods other than our pre-trained model (Figure 5). Note however that ESMFold achieves such performance without the benefit of costly refinement and produces full atom models, as opposed to simplistic Cα-only residual networks, trained here.

Most importantly from the point of view of pre-training, CrystalHeavy100 model, which did not get the benefit of pre-training but a very large Cα parameter, produces the largest amount of bad distances, at 5,740. The model with a small Cα parameter but also without pre-training (CrystalHeavy1), also achieves a bad result in terms of number of peptide bonds (4,686). By contrast, the pre-trained model produces only 517 incorrect contacts. Since the only difference between the methods was the benefit of pretraining, we venture a statement that the network benefited from learning more correct physical bonds from a large pre-trained dataset that is able to generalize to physically plausible shapes of unseen (though perhaps unrealistic) CDR-H3s.

Table 5. **Number of bad bonds in the artificial CDR-H3s.** We generated 100 random CDR-H3s in the length range between 10-20 residues. Each of the structures was modeled by IgFold, AbodyBuilder2, ESMFold, NanoNet, our pre-trained model PretrainedCombyined100 and the not-pretrained varieties (CrystalHeavy100 and CrystalHeavy1). We report the number of Cα bonds that fall outside of the [3.6Å, 3.9Å] range for the CDR-H3.

Model	#Cα-Cα <3.6Å, Cα-Cα >3.9Å
PretrainedCombined100	517
CrystalHeavy1	4,686
CrystalHeavy100	5,837
NanoNet	4,005
AbLooper	5,035
IgFold	2,554
AbodyBuilder2	4,097

ESMFold	509

Figure 5. The distribution of Cα distances in the CDR-H3 predictions of the CDR-H3s randomized on the Rosetta test set. For each of the 45 structures in the Rosetta test set, we generated 10 random IMGT CDR-H3s in the length range [10 20] and we plot the histograms of the consecutive Cα distances in these. The red lines indicate the region of [3.6Å 3.9Å]. Please note that the histograms have different bins sizes to fit the same axes in each image.

Discussion

We addressed the issue of generating structural antibody models of better physical quality without detriment to prediction of the backbone Cα. We trained a very simplistic deep learning model with a rudimentary loss function to minimize the risk of better peptide bond distances being the result of ingenious model architectures (Lee et al. 2022; Ruffolo et al. 2022; Abanades, Wong, et al. 2022). We demonstrated that even such simple models can learn better quality peptide bonds if given the benefit of pre-training on a large augmented set of refined antibody structures.

Producing good quality antibody models fast is crucial for practical applications of such methods in therapeutic development. During a phage-display or animal immunization campaigns, it is not uncommon to produce a number of sequences in the region of 10^5–10^6 or even 10^{11} (Alfaleh et al. 2020). Current methods such as IgFold, AbodyBuilder2, and ESMFold produce results of comparable quality in matter of seconds, which is an order of magnitude improvement versus the pioneer, AlphaFold2. However, even assuming an optimistic scenario that with refinement such methods would take only one second, 10^6 sequences would still take approximately 11 days on a powerful GPU.

This could be a further hindrance when one wishes to study the entire space of antibodies, of which there is estimated to be 10^{18} unique molecules (Briney et al. 2019). A relatively tiny snapshot of this space in the form of Observed Antibody Space, currently holds 2,426,036,223 unique antibody sequences (Olsen, Boyles, and Deane 2022; Kovaltsuk et al. 2018). Assuming an optimistic running time of 1s per model, covering all of these sequences on a powerful GPU would take approximately 673,898 hours or around 75 years. Producing physically accurate predictions without the need for energy refinement can reduce the running time, and thus make large-scale annotation of the antibody space within reach.

Nevertheless, the current efforts to model the available antibody space are not in vain as it was demonstrated that this could be done using even very rudimentary methods (Krawczyk et al. 2018). We are employing such a natural dataset for pre-training obtained from public response structures. The authors of IgFold and AbodyBuilder2 also make available snapshots of more than 100,000 paired sequences available in OAS. Since snapshots provided by IgFold and AbodyBuilder2 use more advanced tools that we employed for pre-training here, we think that in the future they might provide an even better basis for structural pre-training. This raises the question of whether the structures in such pre-training datasets need to be only 'physically accurate' or be models that closely resemble the real structures that they model.

Furthermore, the proof of concept demonstrated here only took into account the peptide bond. It is not unreasonable to imagine that overall plausibility of the structure produced by the network might improve in other areas, such as side chains, the number of amino acids with D-stereochemistry or clashes (Fernández-Quintero et al. 2022). All such considerations hinge on presenting the network with a large, augmented dataset so it can develop a basis of inference of correct physical geometries that can be generalized to the vast space of antibody molecules.

As we demonstrated with the artificial CDR-H3 exercise, many networks show unstable behavior (non-physical peptide bond lengths) when predicting novel sequences, suggesting limited generalizability. Developing plausible novel antibodies is not only the domain of structure prediction but also generative modeling (Melnyk et al. 2021; Eguchi, Choe, and Huang 2022). While our approach of introducing augmented dataset for model pre-training improved model stability in CDR-H3 prediction, it might also be applicable to producing novel physically plausible structures using generative modeling regimes.

Altogether, employing a large, augmented dataset for structural pre-training appears to produce physically plausible predictions for known structures as well as randomly generated ones. Therefore we hope that our presented strategy for structural pre-

training would benefit the many antibody structural modeling tools available currently.

Methods

Datasets

Rosetta test set. We employed the 'Rosetta' test set introduced previously as multiple methods employed it subsequently for benchmarking. The original Rosetta test set consisted of 48 Fvs. We removed three of them because of low quality, for instance incomplete chains. The final dataset consisted of the following 45 PDBs : 3gnm, 2xwt, 2vxv, 3i9g, 2d7t, 2ypv, 1mlb, 2w60, 1gig, 3g5y, 2adf, 3liz, 3poy, 3hnt, 3e8u, 3mxw, 2fbj, 1nlb, 3go1, 2fb4, 3mlr, 1jfq, 3nps, 2e27, 1fns, 2v17, 1seq, 4nzu, 1mqk, 4f57, 4hpy, 2r8s, 1mfa, 3oz9, 3hc4, 1jpt, 3t65, 1oaq, 3vow, 3lmj, 3m80, 4h20, 1dlf, 3e09, 3giz.

Crystal datasets. We downloaded the antibodies from the Protein Data Bank on March 13th 2022. We removed the structures with identical CDR-H3 or CDR-L3 loops. Only X-ray structures with resolution better than 3Å were left in. We removed all the structures that had the same CDR-H3 or CDR-L3 as in the Rosetta test set. The final dataset consisted of 1,628 training and 185 validation heavy chain structures that we term as CrystalHeavy. The CrystalLight dataset consisted of 1,302 training and 149 validation light chain structures. The CrystalCombined dataset was created by taking the intersection of the two datasets resulting in 2966 training and 298 validation structures.

Pre-training datasets. We employed two pre-training datasets 'Natural' and 'Homology'. The Natural dataset was created externally as the sample of the public response structures (Raybould et al. 2021). We created the Homology dataset by reproducing the homology modeling protocol introduced by AbodyBuilder (Leem et al. 2016) via: 1) selecting the closest template framework from the PDB (Krawczyk et al. 2018), 2) orientating the chains by closest matching pair 3) modeling the loops by FREAD (Choi and Deane 2010) and refining the predictions by PEARS (Leem et al. 2018). In both the Natural and Homology datasets, we removed all the structures where CDR-H3 or CDR-L3 matched this in the CrystalHeavy or CrystalLight datasets. We further removed structures that had more than 1Å RMSD to CDR-H3 or CDR-L3 in the Rosetta test set. This resulted in 18,959 training, 2369 validation and 2369 test structures in the natural dataset. Likewise, the Homology dataset consisted of 37,672 training, 4709 validation and 4709 test structures. Since we demonstrated that combining heavy and light chains for prediction appears to improve the peptide bond length without detriment to shape prediction quality we created a PretrainCombined dataset by merging the heavy and light chains in the Homology and Natural datasets. This resulted in 113,262 structures for training 11,326 for validation and 11,326 for test.

Models

Model for pre-training. We employed the simplest deep learning architecture we could identify that reported heavy chain modeling of antibodies, which was NanoNet (Cohen, Halfon, and Schneidman-Duhovny 2022). In brief it consists of seven convolutional residual blocks. It has 1.9m parameters which puts it on the lower spectrum with respect to models trained on the basis of 15B parameters language models (ESMFold) or on the basis of AlPhaFold (AbodyBuilder2). The lightweight architecture ensured that we could do multiple iterations and variations of the models to test the effects of the structural pre-training strategy (e.g. AbodyBuilder achieves very good results but it takes several weeks to train on a powerful GPU). Furthermore, the lightweight architecture reduced the risk that any effects we might observe of better peptide bond distances, would be accounted for by ingenious architectures or training regimes. The method does not come with a training loop so the architecture and training functions had to be reimplemented from scratch. For the training loss we employ the Mean Squared Error together with a loss on the consecutive distances of $C\alpha$. The $C\alpha$ loss was parameterized with weight, biasing the predictions towards putting more attention to $C\alpha$ distances.

Models for benchmarking. We employed five models for benchmarking, AbodyBuilder2, AbLooper, IgFold, ESMFold and NanoNet. The choice was motivated by the availability of the methods and the fact that they are state-of-the art. The models coming from AbodyBuilder2, AbLooper and IgFold did not undergo refinement, which is the full protocol in each case. This was to compare the results of predictions coming straight from the network. All the methods are freely available and they were obtained from the repositories advertised in the corresponding publications.

Quality Metrics

$C\alpha$-$C\alpha$ peptide bond distances. We calculated the $C\alpha$-$C\alpha$ distances between the consecutive atoms as the simple euclidean distance of the coordinates. Our datasets were not allowed to have structures with missing amino acids, resulting in incorrectly large $C\alpha$-$C\alpha$ distances as a result of a missing residue or a stretch of these in between. All the $C\alpha$-$C\alpha$ distances that were falling outside of the [3.6 3.9] range we considered as incorrect, which was an arbitrary choice based on observation of the distance in the crystal structures.

RMSD. Whenever we report the Root Mean Square Deviation between prediction and native structures we only take $C\alpha$ into account. The RMSDs for the H3s were calculated in two modes – by Fv alignment (Employed in Table 2) and by CDR-H3 alignment (employed in Figure 3). In the Fv alignment, the $C\alpha$ coordinates of the entire variable region are aligned using the KABSCH algorithm in the python *rmsd* module and the

RMSD is calculated on the IMGT-defined CDR-H3 only. In the CDR-H3 alignment, the CDR-H3 Cα only are aligned and the RMSD calculated. Clearly, the CDR-H3 alignment should typically produce lower numbers.

References

Abanades, Brennan, Guy Georges, Alexander Bujotzek, and Charlotte M. Deane. 2022. "ABlooper: Fast Accurate Antibody CDR Loop Structure Prediction with Accuracy Estimation." *Bioinformatics* , January. https://doi.org/10.1093/bioinformatics/btac016.

Abanades, Brennan, Wing Ki Wong, Fergus Boyles, Guy Georges, Alexander Bujotzek, and Charlotte M. Deane. 2022. "ImmuneBuilder: Deep-Learning Models for Predicting the Structures of Immune Proteins." *bioRxiv*. https://doi.org/10.1101/2022.11.04.514231.

Ahdritz, Gustaf, Nazim Bouatta, Sachin Kadyan, Qinghui Xia, William Gerecke, Timothy J. O'Donnell, Daniel Berenberg, et al. 2022. "OpenFold: Retraining AlphaFold2 Yields New Insights into Its Learning Mechanisms and Capacity for Generalization." *bioRxiv*. https://doi.org/10.1101/2022.11.20.517210.

Alfaleh, Mohamed A., Hashem O. Alsaab, Ahmad Bakur Mahmoud, Almohanad A. Alkayyal, Martina L. Jones, Stephen M. Mahler, and Anwar M. Hashem. 2020. "Phage Display Derived Monoclonal Antibodies: From Bench to Bedside." *Frontiers in Immunology* 11 (August): 1986.

Almagro, Juan C., Alexey Teplyakov, Jinquan Luo, Raymond W. Sweet, Sreekumar Kodangattil, Francisco Hernandez-Guzman, and Gary L. Gilliland. 2014. "Second Antibody Modeling Assessment (AMA-II)." *Proteins* 82 (8): 1553–62.

Briney, Bryan, Anne Inderbitzin, Collin Joyce, and Dennis R. Burton. 2019. "Commonality despite Exceptional Diversity in the Baseline Human Antibody Repertoire." *Nature* 566 (7744): 393–97.

Choi, Yoonjoo, and Charlotte M. Deane. 2010. "FREAD Revisited: Accurate Loop Structure Prediction Using a Database Search Algorithm." *Proteins* 78 (6): 1431–40.

Cohen, Tomer, Matan Halfon, and Dina Schneidman-Duhovny. 2022. "NanoNet: Rapid and Accurate End-to-End Nanobody Modeling by Deep Learning." *Frontiers in Immunology* 13 (August): 958584.

Dunbar, James, Konrad Krawczyk, Jinwoo Leem, Terry Baker, Angelika Fuchs, Guy Georges, Jiye Shi, and Charlotte M. Deane. 2014. "SAbDab: The Structural Antibody Database." *Nucleic Acids Research* 42 (Database issue): D1140–46.

Eastman, Peter, Jason Swails, John D. Chodera, Robert T. McGibbon, Yutong Zhao, Kyle A. Beauchamp, Lee-Ping Wang, et al. 2017. "OpenMM 7: Rapid Development of High Performance Algorithms for Molecular Dynamics." *PLoS Computational Biology* 13 (7): e1005659.

Eguchi, Raphael R., Christian A. Choe, and Po-Ssu Huang. 2022. "Ig-VAE: Generative Modeling of Protein Structure by Direct 3D Coordinate Generation." *PLoS Computational Biology* 18 (6): e1010271.

Ferdous, Saba, and Andrew C. R. Martin. 2018. "AbDb: Antibody Structure Database–a Database of PDB-Derived Antibody Structures." *Database: The Journal of Biological Databases and Curation* 2018 (January). https://doi.org/10.1093/database/bay040.

Fernández-Quintero, Monica L., Janik Kokot, Franz Waibl, Anna-Lena M. Fischer, Patrick K. Quoika, Charlotte M. Deane, and Klaus R. Liedl. 2022. "Challenges in Antibody Structure Prediction." *bioRxiv*. https://doi.org/10.1101/2022.11.09.515600.

Jumper, John, Richard Evans, Alexander Pritzel, Tim Green, Michael Figurnov, Olaf Ronneberger, Kathryn Tunyasuvunakool, et al. 2021. "Highly Accurate Protein Structure Prediction with AlphaFold." *Nature* 596 (7873): 583–89.

Kaplon, Hélène, Alicia Chenoweth, Silvia Crescioli, and Janice M. Reichert. 2022. "Antibodies to Watch in 2022." *mAbs* 14 (1): 2014296.

Kovaltsuk, Aleksandr, Konrad Krawczyk, Jacob D. Galson, Dominic F. Kelly, Charlotte M. Deane, and Johannes Trück. 2017. "How B-Cell Receptor Repertoire Sequencing Can Be Enriched with Structural Antibody Data." *Frontiers in Immunology* 8 (December): 1753.

Kovaltsuk, Aleksandr, Jinwoo Leem, Sebastian Kelm, James Snowden, Charlotte M. Deane, and Konrad Krawczyk. 2018. "Observed Antibody Space: A Resource for Data Mining Next-Generation Sequencing of Antibody Repertoires." *Journal of Immunology* 201 (8): 2502–9.

Krawczyk, Konrad, Andrew Buchanan, and Paolo Marcatili. 2021. "Data Mining Patented Antibody Sequences." *mAbs* 13 (1): 1892366.

Krawczyk, Konrad, Sebastian Kelm, Aleksandr Kovaltsuk, Jacob D. Galson, Dominic Kelly, Johannes Trück, Cristian Regep, et al. 2018. "Structurally Mapping Antibody Repertoires." *Frontiers in Immunology* 9 (July): 1698.

Lee, Jae Hyeon, Payman Yadollahpour, Andrew Watkins, Nathan C. Frey, Andrew Leaver-Fay, Stephen Ra, Kyunghyun Cho, Vladimir Gligorijevic, Aviv Regev, and Richard Bonneau. 2022. "EquiFold: Protein Structure Prediction with a Novel Coarse-Grained Structure Representation." *bioRxiv*. https://doi.org/10.1101/2022.10.07.511322.

Leem, Jinwoo, James Dunbar, Guy Georges, Jiye Shi, and Charlotte M. Deane. 2016. "ABodyBuilder: Automated Antibody Structure Prediction with Data–driven Accuracy Estimation." *mAbs* 8 (7): 1259–68.

Leem, Jinwoo, Guy Georges, Jiye Shi, and Charlotte M. Deane. 2018. "Antibody Side Chain Conformations Are Position-Dependent." *Proteins* 86 (4): 383–92.

Lin, Zeming, Halil Akin, Roshan Rao, Brian Hie, Zhongkai Zhu, Wenting Lu, Nikita Smetanin, et al. 2022. "Evolutionary-Scale Prediction of Atomic Level Protein Structure with a Language Model." *bioRxiv*. https://doi.org/10.1101/2022.07.20.500902.

Marks, Claire, Jaroslaw Nowak, Stefan Klostermann, Guy Georges, James Dunbar, Jiye Shi, Sebastian Kelm, and Charlotte M. Deane. 2017. "Sphinx: Merging Knowledge-Based and Ab Initio Approaches to Improve Protein Loop Prediction." *Bioinformatics* 33 (9): 1346–53.

Melnyk, Igor, Payel Das, Vijil Chenthamarakshan, and Aurelie Lozano. 2021. "Benchmarking Deep Generative Models for Diverse Antibody Sequence Design." *arXiv [q-bio.BM]*. arXiv. http://arxiv.org/abs/2111.06801.

Młokosiewicz, Jakub, Piotr Deszyński, Wiktoria Wilman, Igor Jaszczyszyn, Rajkumar Ganesan, Aleksandr Kovaltsuk, Jinwoo Leem, Jacob D. Galson, and Konrad Krawczyk. 2022. "AbDiver: A Tool to Explore the Natural Antibody Landscape to Aid Therapeutic Design." *Bioinformatics* 38 (9): 2628–30.

Mullard, Asher. 2021. "FDA Approves 100th Monoclonal Antibody Product." *Nature Reviews. Drug Discovery* 20 (7): 491–95.

Olsen, Tobias H., Fergus Boyles, and Charlotte M. Deane. 2022. "Observed Antibody Space: A Diverse Database of Cleaned, Annotated, and Translated Unpaired and Paired Antibody Sequences." *Protein Science: A Publication of the Protein Society* 31 (1): 141–46.

Raybould, Matthew I. J., Claire Marks, Aleksandr Kovaltsuk, Alan P. Lewis, Jiye Shi, and Charlotte M. Deane. 2021. "Public Baseline and Shared Response Structures Support the Theory of Antibody Repertoire Functional Commonality." *PLoS Computational Biology* 17 (3): e1008781.

Regep, Cristian, Guy Georges, Jiye Shi, Bojana Popovic, and Charlotte M. Deane. 2017. "The H3 Loop of Antibodies Shows Unique Structural Characteristics." *Proteins* 85 (7): 1311–18.

Ruffolo, Jeffrey A., Lee-Shin Chu, Sai Pooja Mahajan, and Jeffrey J. Gray. 2022. "Fast, Accurate Antibody Structure Prediction from Deep Learning on Massive Set of Natural Antibodies." *bioRxiv*. https://doi.org/10.1101/2022.04.20.488972.

Ruffolo, Jeffrey A., Carlos Guerra, Sai Pooja Mahajan, Jeremias Sulam, and Jeffrey J. Gray. 2020. "Geometric Potentials from Deep Learning Improve Prediction of CDR H3 Loop Structures." *Bioinformatics* 36 (Suppl_1): i268–75.

Ruffolo, Jeffrey A., Jeremias Sulam, and Jeffrey J. Gray. 2022. "Antibody Structure Prediction Using Interpretable Deep Learning." *Patterns (New York, N.Y.)* 3 (2): 100406.

Weitzner, Brian D., Daisuke Kuroda, Nicholas Marze, Jianqing Xu, and Jeffrey J. Gray. 2014. "Blind Prediction Performance of RosettaAntibody 3.0: Grafting, Relaxation, Kinematic Loop Modeling, and Full CDR Optimization." *Proteins* 82 (8): 1611–23.

Wilman, Wiktoria, Sonia Wróbel, Weronika Bielska, Piotr Deszynski, Paweł Dudzic, Igor Jaszczyszyn, Jędrzej Kaniewski, et al. 2022. "Machine-Designed Biotherapeutics: Opportunities, Feasibility and Advantages of Deep Learning in Computational Antibody Discovery." *Briefings in Bioinformatics* 23 (4). https://doi.org/10.1093/bib/bbac267.

Wu, Jiaxiang, Fandi Wu, Biaobin Jiang, Wei Liu, and Peilin Zhao. 2022. "tFold-Ab: Fast and Accurate Antibody Structure Prediction without Sequence Homologs." *bioRxiv*. https://doi.org/10.1101/2022.11.10.515918.

Yang, Huan, Zhaoping Xiong, and Francesco Zonta. 2022. "Construction of a Deep Neural Network Energy Function for Protein Physics." *Journal of Chemical Theory and Computation* 18 (9): 5649–58.