A Versatile Deep Graph Contrastive Learning Framework for Single-cell Proteomics Embedding

Abstract

The advance of single-cell proteomics sequencing technology sheds light on the research in revealing the protein-protein interactions, the post-translational modifications, and the proteoform dynamics of proteins in a cell. However, the uncertainty estimation for peptide quantification, data missingness, severe batch effects and high noise hinder the analysis of single-cell proteomic data. It is a significant challenge to solve this set of tangled problems together, where existing methods tailored for single-cell transcriptome do not address. Here, we proposed a novel versatile framework scPROTEIN, composed of peptide uncertainty estimation based on a multi-task heteroscedastic regression model and cell embedding learning based on graph contrastive learning designed for single-cell proteomic data analysis. scPROTEIN estimated the uncertainty of peptide quantification, denoised the protein data, removed batch effects and encoded single-cell proteomic-specific embeddings in a unified framework. We demonstrate that our method is efficient for cell clustering, batch correction, cell-type annotation and clinical analysis. Furthermore, our method can be easily plugged into single-cell resolved spatial proteomic data, laying the foundation for encoding spatial proteomic data for tumor microenvironment analysis.

Introduction

In the past, the application of single-cell sequencing technologies mainly focused on detecting the level of single-cell transcriptome[1], while recent single-cell proteomic technologies are also advancing[2–13]. Although the mRNA level of genes was considered as a proxy of the protein level in the past decades[14,15], the transcriptional level of genes and the content of proteins that ultimately perform functions have low consistency, indicating that single-cell transcriptome alone is insufficient to derive cellular protein levels[16,17]. Proteins are the ultimate executors of cellular function, and proteomics provides knowledge on deciphering cellular mechanisms through enzyme activity and post-translational modifications[10]. Single-

cell proteomics enables the identification of activated pathways in therapy-resistant cells and therefore

provides biomarkers for cancer diagnosis and prognosis[18]. In recent years, improvements in the sensitivity

of mass spectrometry and innovations in single-cell proteomic technologies have made it possible to

quantify a range of proteins at the single-cell resolution [4,13].

Despite the above advantages, single-cell proteomic data have several serious problems such as

uncertainty of peptides quantification, data missingness, batch effects and data noise due to the limitations

in current sample preparation, data acquisition, and isotopic labelling, etc[19,20]. First, current single-cell

proteomic technologies use diverse sample preparation approaches (i.e., TEAB solution, DMSO solution,

or water solution), data acquisition strategies (i.e., data-dependent acquisition or data-independent

acquisition), and labelling strategies (i.e., label-free or isotopic labelling), resulting in severe batch

effects[4,6,11]. Second, not all the constituting peptides' contents are delivered to the mass spectrometry

instrument due to the sample loss during sample preparation, which is a significant issue for single-cell

proteomics. After the peptides are injected to the mass spec, their signal intensity would be influenced by

their ionization efficiencies and peak selection of precursors for fragmentation in the DDA mode[19], which

will potentially lead to severe noise in single-cell proteomic data. Third, as for the bottom-up single-cell

proteomics, the core quantification lies in the peptide level and a protein's content is always obtained

based on the simple average or median of its constituting peptides intensity detected in the mass

spectrometry instrument. However, in practice, the current sequencing technologies are imperfect in

quantifying peptide levels. It would be inaccurate to calculate the protein content only based on the

average or median intensity of its peptides without considering the uncertainty of the measurement of the

peptide intensities[8] .Therefore, a more accurate way to construct the protein-level expression data is to

assign uncertainty weights to peptides to compensate the measurement inaccuracy.

The existing single-cell proteomic data processing methods are mainly migrated from pipelines for

scRNA-seq processing such as routine imputation (i.e., KNN imputation), batch correction (ComBat), and

normalization[19,21,22]. However, those pipelines could not address the unique problems of data analysis on

single-cell proteomic data[19]. First, KNN imputation could introduce big artifacts under severe batch

effects in single-cell proteomic data. On the other hand, batch effect correction methods (ComBat) could

not handle missing data without conducting imputation first. Hence, it would be problematic to conduct

imputation and batch correction separately if the influence between them is ignored. Therefore, it is a

significant challenge to consider the influence and interaction between these problems including data

denoising simultaneously[19] . Second, current batch correction methods assume that there are the same sets

of cells between two batches which might not be true when the cell types or cell states are unknown

before the experiment. Third, single-cell proteomics exhibits a hierarchical structure that the proteins are

constituted by peptides, and the protein contents are calculated based on the detected peptides' signals.

However, existing data analysis methods ignore the hierarchical information and the uncertainty of

peptide quantification. In this regard, we developed a novel deep graph contrastive learning framework

for *single-c*ell PROTeomics EmbeddINg (scPROTEIN) to tackle the uncertainty of peptide quantification,

data missingness, batch effects and high noise in a unified framework by providing versatile cell

embeddings. For the datasets provided with raw peptide signal intensities, we proposed a multi-task

heteroscedastic regression model to estimate the uncertainty of peptide quantification and then aggregate

the peptide content to the protein level in an uncertainty-guided manner. Then, we built a graph structure

to characterize the single-cell proteomic data where the message-passing process considering co-

expression patterns can help alleviate the data missingness problem and recover the missing values for

low-abundance proteins. Graph contrastive learning model together with a designed alternated topology-

attribute denoising module was developed, which can denoise the proteomic data and lead to an accurate

representation. The discriminative property of contrastive learning and the well-denoised cell embedding

can together alleviate the severe batch effect implicitly without knowing the prior knowledge of the

dataset. Finally, the learned versatile cell embedding could be applied in various downstream tasks (i.e.,

cell clustering, batch correction and cell type annotation). We also performed experiments on antibody-

based single-cell proteomic data to evaluate the effectiveness on clinical analysis. Moreover, scPROTEIN

could be easily generalized to learn from spatial-resolved single-cell proteomic data.

Results

The overall architecture of versatile deep graph contrastive learning framework for single-cell proteomics embedding

The overall framework is illustrated in Figure 1. For datasets provided with raw peptide-level profile, scPROTEIN starts from *stage 1* to learn the peptide uncertainty and obtain the protein-level expression profile in an uncertainty-guided manner. The protein-level data is then fed into *stage 2* and *stage 3* to learn the cell embedding by graph contrastive learning together with a data denoising module. The learned cell embedding can then be applied in a variety of downstream tasks.

The first stage is to aggregate the peptide-level intensities to determine the protein-level content guided by the uncertainty of peptide abundance quantification of mass spectrometry in single-cell proteomic data. We designed a multi-task heteroscedastic regression model to estimate the uncertainty of each peptide signal in each cell, which can partially reflect the quality of the signal (i.e., the amount of noise). Heteroscedastic regression model assumes that the uncertainty varies with different peptides. By considering the uncertainty estimation for all peptides in one cell as one specific task, our multi-task learning takes the estimation for all cells into consideration at the same time. The combination of Heteroscedastic regression model and multi-task learning enables adaptively learning the uncertainty of each peptide across different cells. Based on the estimated uncertainty, we can then construct a weight for each peptide and perform uncertainty-guided aggregation over peptide-level data to obtain the protein-level data. By this way, peptide with higher quality can pose larger impact on the cell embedding and this process would benefit the model's reliability and accuracy. Then we utilized the protein-level data to learn comprehensive cell embeddings in *stage 2*. For datasets provided directly with the reconstructed protein-level profile, scPROTEIN will start from *stage2*.

The topological structure of graph can help impute the missing data of single-cell proteomic data and

improve the quality of learned embedding. Specifically, each node in the graph has specific semantic

pattern which can be used to compensate each other during the graph learning process. To this end, in the

second stage a cell graph is built where each node represents a cell and the initial node feature represents

the proteomic data within the cell. There are three characteristics of our proposed graph: 1) in the

contrastive learning framework, two different perturbed views are generated respectively and the mutual

information of the same node between these two views is maximized, which can lead to robust

representations to noise. 2) Besides, when dealing with data from different sources, the shared proteins

are utilized to build a shared cell graph. Therefore, the batch effect between different sources can be

implicitly alleviated by aligning the semantic information of the same cell type through contrastive loss.

3) Moreover, two denoising modules (attribute and topology) are alternated to mitigate the noise problem

in the proteomic profile. During this *stage 2*, data missingness is alleviated, batch effect is implicitly

corrected and the severe noise in proteomic data is largely removed.

In *stage 3*, the obtained topology-refined cell graph in *stage 2* and the single-cell protein-level data are fed

into the trained GCN encoder in *stage 2*. Then the cell embedding is learned, which can be applied to

various downstream tasks including cell clustering, batch correction, cell type annotation and clinical

analysis. Moreover, our proposed methods can be easily extended to single-cell spatial proteomic data by

constructing a cell graph based on the spatial cell proximity and learn a spatial informative embedding. A

detailed description of the proposed method is in the Method Section.

To comprehensively evaluate the performance, we applied scPROTEIN in nine single-cell proteomic

datasets (detailed in Supplementary Table 1). We first showed the overall learning workflow from *stage 1*

to *stage 3* by taking a representative single-cell proteomic dataset SCoPE2_Specht as a concrete example.

We qualitatively and quantitatively compared the cell clustering performance of scPROTEIN with other

methods and showed the learned peptide uncertainty. Then we benchmarked five independent batch

correction tasks across six single-cell datasets with different cutting-edge sequencing techniques (Scope2,

pScope, plexDIA, N2, nanoPOTS, etc) and species (mouse and human cell lines). Besides, we

investigated the application of scPROTEIN for single-cell clinical proteomic data in ECCITE-seq dataset,

which is a antibody-based single-cell proteomic dataset and collected from the patient with cutaneous T-

cell lymphoma (CTCL). Furthermore, BaselTMA dataset which is consisted of spatially resolved

proteomic data from breast cancer tumor biopsy slices was utilized to validate the scalability of

scPROTEIN on single-cell spatial proteomics. Finally, a systematic analysis for hyperparameter

sensitivity of our scPROTEIN model is presented in Extended Data Figure 1 and Extended Data Figure 2.

Evaluation of cell clustering and the uncertainty of peptide quantification

We first evaluated the cell embedding learned by our proposed method on the cell clustering task and

illustrated how scPROTEIN works from stage1 to stage3. We applied scPROTEIN in SCoPE2_Specht

dataset[23], which quantifies 3042 proteins in 1490 cells via SCoPE2 sequencing technique. The existing

single-cell proteomic data analysis pipeline[19] employed KNN-based imputation and ComBat based batch

correction (termed KNN-ComBat) for the routine data preprocessing. Beyond that, Markov affinity-based

graph imputation of cells (MAGIC)[24] is a manifold learning-based algorithm for denoising high-

dimensional data which is most commonly applied to single-cell RNA sequencing data. In this study, we

used these two representative data processing methods as comparison method[19]. From the clustering

results in Figure 2a-b, we can see that our graph-based embedding achieved the best performance on all

the evaluation metrics on the SCoPE2_Specht dataset. Besides, we illustrated a concrete example of

embedding learning process in Extended Data Figure 3a.

Furthermore, the entire framework is tailored for analysing the hierarchical data structure of single-cell

proteomics where the expression of a protein can be aggregated by the levels of its digested peptides. The

estimated peptide-level uncertainty reflects the data noise varied across samples and is visualized in

Figure 2c. As the digested peptides from different samples are pooled together after isotopic labelling and

then detected in the mass spectrometry with consistent ionic behavior[4], the peptides from the same run of

experiments display similar uncertainty patterns. We can observe four distinct heatmap blocks along with

the batch ID in Figure 2c. While in the same proteins, the measurement uncertainties of different peptides

vary due to their different behaviours in ionization, co-isolation, fragmentation, and sampler preparation

loss[20,25]. For instance, "AYSSFGGGR_2" and "DDFNSGFR_2" are two constituting peptides of the same

protein "Q15056" (in the red box), while they show quite different uncertainty patterns across batches and

samples.

In addition, the ablation study in Figure 2d displays the results of our method on SCoPE2_Specht dataset

with and without uncertainty estimation in *stage 1*. It can be seen scPROTEIN performs significantly

better after uncertainty adjustment. Besides, we compared the average signal to noise ratio within each

cell type with other methods (Extended Data Figure 3b), and the results prove the effectiveness of

scPROTEIN in data denoising.

Evaluation of batch correction with cell embeddings and label transfer.

Due to the systematic biases in sample preparation, data acquisition, and labelling strategy, single-cell

proteomic data faces more severe batch effects than scRNA-seq data. Therefore, we evaluated the

robustness of our method to batch effect compared with existing methods on five independent

experiments where the batch effects from different single-cell proteomic platforms hamper the clustering

results of different cell types with the original protein level (Figure 3a, c, Extended Data Figure 4 a,

Extended Data Figure 5 a, c). We used different shapes to represent various cell types and the same colour

in different shades to represent the same cell type from different sources. We first applied scPROTEIN to

integrate two mouse cell datasets: N2 (108 cells and 1068 proteins) and nanoPOTS (61 cells and 1225

proteins). The shared proteins (762 proteins) were used as the raw protein profile to build a shared cell

graph. In Figure 3a, the visualization of the raw data and processed data from comparison methods show

a clear separation of the same cell type from both batches. After processed by scPROTEIN, cells within

each cell type are pulled closer whilst those of different cell types remain properly separated. This

indicates that scPROTEIN preserves the batch-invariant biodiversity. In addition, we show the

comparison of raw protein data and the learned embedding by scPROTEIN in Extended Data Figure 3c,

which indicates that scPROTEIN can largely alleviate the batch effect.

For SCoPE2_Leduc (163 cells and 1647 proteins) and plexDIA (164 cells and 1242 proteins), the batch

correction is more challenging since the two datasets have different sets of cell types. It can be seen from

Figure 3c that scPROTEIN still obtains a promising performance. Using scPROTEIN embedding, U-937

Cells from both sources were closely clustered while other cell types remained separable.

Notably, batch correction methods based on ComBat or other conventional methods may cause the

problem of overcorrection for batch effects by removing the biodiversity of different cell types. To

evaluate the performance of batch correction as well as the ability to preserve biodiversity within different

cell types, we used cell-type-level metrics (ASW-cell, ARI-cell, NMI-cell, and PS-cell) to measure the

cell type separation, and 1 - batch level metrics (1-ASW-batch, 1-ARI-batch, 1-NMI-batch, and 1-PS-

batch) to measure the clustering of the same cell type between batches, similar to the metrics used in Tran

et al[26] and Li et al[27]. Results in Figure 3b and 3d show the excellent balance of our method on correcting

batch effect (1-batch level metrics) and maintaining the batch-invariant biodiversity of cells (cell type

level metrics) compared to the comparison methods (Figure 3b, d, Extended Data Figure 4b and Extended

Data Figure 5b, d).

We further performed label transfer to annotate cell types across N2 and nanoPOTs datasets which

contain the same set of cell types. The label transfer was implemented by K- Nearest Neighbor (KNN)

algorithm based on the batch correction results (Figure 3e). The performance of label transfer is highly

dependent on the effectiveness of batch corrections. Only when the batch effect is well corrected and the

biodiversity is properly preserved, cells of unknown types can be moved closer to the correct cluster, thus

enabling correct label transfer. As shown in Figure 3f, when we take N2 as the reference set and

nanoPOTS as the query set, the results indicate that the performance for cell type annotation of our

method clearly outperforms other comparison methods on both accuracy (Acc=0.967) and macro-f1 score

(macro-f1 score=0.966). Besides, our method can label all query cells correctly when transferring labels

from nanoPOTS to N2 dataset (Acc=1.00, macro-f1=1.00).

Application on clinical proteomic data.

In this study, we briefly explored the application of our method on antibody-based single-cell proteomic

data from clinical tissues in ECCITE-seq dataset[28], which quantifies 49 marker proteins across 6500 cells

from a healthy donor and 6500 cells from a patient with cutaneous T-cell lymphoma (CTCL). We

visualized the UMAP of raw data and the learned representations in Figure 4a and Figure 4b, with cells

from healthy donor in green and from cutaneous CTCL patient in red. The samples could be further

grouped in 25 clusters with the embedding learned by scPROTEIN (Figure 4c). The high expressed

proteins of each cluster are shown in Figure 4d. In addition, from Figure 4e we can observe the proportion

of cells from CTCL donor and from healthy donor varies in different subgroups. We selected three

representative clusters and conducted detailed analysis for subgroups in Figure 4f-n and more results can

be found in Extended Data Figure 6, in which pie plot indicates the proportion of CTCL samples and

healthy samples (4f, 4i, 4l), volcano plot depicts the differential expression proteins (4g, 4j, 4m) and

enrichment analysis indicates the gene ontology (GO) function for identified up-regulated proteins for

CTCL cells (4h, 4k, 4n). Based on the clustering results and corresponding subgroup analysis, we found

several differential expressed proteins of the malignant CTCL cells[28]. For instance, CD62L (Fig 4g) is the

functional marker for circulating innate lymphoid cell precursors and correlates with the extent of

lymphadenopathy, which could be applied as the diagnostic marker in inflammatory disorders[29,30]. For

cluster 5 which overrepresents in CTCL sample, the volcano plot both indicates that CD62L is a potential

functional and diagnostic marker for CTCL. As for cluster 6 which underrepresents in the CTCL sample,

programmed death-1 (PD-1) is significantly upregulated in the cells from CTCL sample. The increased

PD-1 level has been detected in various immune cells in CTCL patients and functioned in the attenuation

of the immune response and anti-tumor immunity in the CTCL progression[31,32,33]. We also analysed the

clusters which do not have significant variation between CTCL cells and control cells (i.e., cluster 2, Fig

4l). CD2 is a fundamental gene that expresses on the surface of 80-90% of human peripheral blood

lymphocytes, subtypes of NK cells and all mature T cells and those CD2+ cells within cluster 2 function

as lymphocyte activation, immune system process and so on. Note that CD62L, the potential functional

and diagnostic marker identified by our proposed method cannot be discovered by routine analysis

employed on raw expression data in the original research on this dataset[28].

Application on spatial proteomic data

Spatial proteomic technologies are maturing and provide an increasing number of resources for the tumor

microenvironment. We applied our method to single-cell resolved spatial proteomic datasets BaselTMA

dataset[32] by constructing a cell graph based on the spatial distance (Figure 5a). As cells of the same cell

types may locate in close proximity in the tissue, our method could enhance the cell embedding with the

help of its spatial neighbor's proteome. In this way, we can fully utilize both the spatial information and

the protein profiling of the spatial proteomic data. The advantage of spatial proteomics is that it can reveal

the spatial cell-cell interaction in the tumor microenvironment. Therefore, we analyze the tumor

microenvironment with the learned embedding by scPROTEIN. Besides, the constructed spatial

informative cell graph can be naturally used to quantify the spatial heterogeneity degree, which is utilized

to estimate the spatial heterogeneity of the tumor microenvironment. In particular, a metric *shd* is defined

to quantify the spatial heterogeneity degree and the detailed definition can be found in Evaluation Metrics

in Methods. A high *shd* represents a highly compartmentalized phenotype and the tissue tends to be

block-like. On the contrary, a low *shd* denotes a high level of spatial mixing.

Here the cell clusters identified by scPROTEIN from tumor slices shown in Figure 5b indicate the highly

compartmentalized phenotype and exhibit high *shd* scores (range from 0.880 to 0.908). In the contrary,

the spatial proteomic data from the normal slices retains relatively low *shd* scores (0.501 and 0.577),

which indicates the high levels of inter-cell-type mixing (Figure 5d). The *shd* scores indicate two types of

samples showing different spatial heterogeneity signatures (p-value = 0.0015, two-sided Mann–Whitney

test). The observation is consistent with the previous clinical study on breast tumor[32,33].

Besides, in Figure 5c and Figure 5e, we depict the results by directly clustering on raw single-cell protein

data for tumor slices and normal slices, respectively. It can be seen that for two different types of slices,

the results do not show any distinct signatures. We further show the density plot of *shd* scores across

different slices for both scPROTEIN and raw expression data in Figure 5f. For scPROTEIN the *shd* for

tumor slices and non-tumor slices show different ranges, while in raw data the ranges for both types are

overlapped. This confirms the effectiveness of scPROTEIN to discriminate the compartmentalized and

highly mixed spatial phenotypes in spatial resolved single-cell proteomic data. More results are shown in

Extended Data Figure 7 a, b.

Discussion

Although the current widely used CITE-seq technology facilitates the detection of cell surface proteins at

scale, it suffers from the limitation of detectable protein numbers and types. The mass-spec based

proteomics provides complementary advantages in detectable protein numbers and types (1000-3000

intracellular proteins) which are critical for analysing cellular function and disease progression. However,

at the same time, it is a significant challenge to simultaneously address the peptide uncertainty estimation,

data missingness, batch effect and data noise problem in mass-spec based single-cell proteomic data.

Most of the existing methods only address one or two problems, but generally speaking, because these

problems are often tangled each other, previous methods are not effective to be used alone or simply

combined.

To this end, we presented a versatile deep graph contrastive learning model scPROTEIN that is tailored

for single-cell proteomics embedding and solved the whole set of problems in a unified framework. First,

with the uncertainty of peptide signals estimated by the multi-task heteroscedastic regression model, our

method could aggregate peptide-level content to protein content. In this way, we could fully utilize and

explore the available hierarchical information of single-cell proteomic data. The nascent design of

uncertainty estimation in peptide intensity exactly meets the urgent need of the single-cell proteomics

community[8]. Then, the cell graph constructed by cellular expression of proteomic displayed the cell's

similarity and the data missingness problem could be implicitly alleviated by propagating information

from neighbour cells. scPROTEIN was trained based on contrastive learning, which can lead to a

perturbation-resistant cell embedding. To further obtain a more robust representation, we designed a

alternated topology-attribute denoising module. The noisy raw expression profile could be largely cleaned,

and the initial constructed cell graph topology was enhanced. Moreover, contrastive learning is capable of

pull the cells with similar pattern closer and push quite different cells apart, which yields a discriminative

ability for batch correction and promotes data completion as well as denoising. To the best of our

knowledge, it is the first time to establish the cell embeddings of single-cell proteomic data to address all

above problems, providing a novel insight into exploring the embedding of single-cell proteomic data in a

data-driven manner.

Extensive experiments proved the versatile application and superior performance of the embeddings

learned by our method on both mass-spec-based and antibody-based proteomics. Benefiting from the

compact embedding, scPROTEIN demonstrates a promising performance compared with the existing

single-cell proteomic data processing pipeline and other comparison methods in cell clustering, batch

correction and cell type annotation on a large number of single-cell proteomic datasets. Moreover,

scPROTEIN exhibits wide applicability such as clinical analysis and single-cell spatial resolved

proteomics data analysis. The application of our method on clinical single-cell proteomic data would be

further explored as the exploration of the single-cell proteomics application in clinical practice. In terms

of the generalization capability, scPROTEIN could be easily extended to spatial-resolved single-cell

proteomic data. Building cell graph based on cell proximity yielded a spatial-informative embedding and

the constructed graph could be naturally used to quantify the spatial heterogeneity degree. It could be

foreseen that with the rapid development and application of single-cell proteomic technologies, our

method would play an increasingly important role in various scenarios of single-cell proteomic data

analysis.

Despite the above advantages, there still exist some limitations in our investigation. First, some

sequencing platforms provided raw profile data directly from the protein-level, in which *stage 1* tailored

for the hierarchical proteome structure cannot be employed. Second, since there is no ground truth for

peptide uncertainty, the performance of peptide uncertainty estimation is evaluated indirectly by

downstream tasks. Third, the existing pipelines for single-cell proteomic data are scarce, and therefore

few baseline methods can be used for comparison. In addition, with the rapid development of graph

model, there will emerge more informative graph construction manners in the future, which could further

enrich our scPROTEIN model.

Methods

The proposed method

Estimation of the uncertainty of the peptide-level intensity.

In the previous study[4,23], the detection of peptide sequence is considered to be deterministic. However, it

has been shown there is a probability that the detected signal is not accurate[8]. Therefore, it is necessary to

estimate uncertainties of peptide-level signal and obtain a more informative protein-level data.

To this end, we develop an uncertainty-aware framework in scPROTEIN *stage 1* to provide a measure for

peptide uncertainty estimation via multi-task heteroscedastic regression motivated by previous

researches[34]. As shown in Figure 1 a, the model takes the original peptide sequences as input and outputs

the estimated uncertainty. We employ Convolutional Neural Network (CNN) as the backbone framework.

Specifically, for each certain detected peptide sequence, we first use one-hot encoding to generate a

matrix of size $20 \times peptide\_length$, where 20 is the total number of common amino acid types and

$peptide\_length$ is the length of the input sequence. Besides, since the sequence lengths are variable, we

perform a padding operation to align all the one-hot matrices to the maximum sequence length, which

facilitates the subsequent encoding process.

The one-hot encoded matrices then go through three convolutional blocks as shown in Figure 1a, where

each block consists of one-dimensional convolution layer, batch normalization layer, Rectified Linear

Unit (ReLU) activation function and max-pooling layer. The outputs are then flattened and pass through

two fully connected layers. Finally, we design two independent dense layers to obtain the predicted

expression vector μ and estimated uncertainty σ respectively, and the loss function for training the whole

peptide uncertainty estimation framework is:

327
$$L_{unc} = \frac{1}{N \times P} \sum_{n=1}^{N} \sum_{p=1}^{P} \frac{1}{2\sigma_{pn}^2} \parallel Pep_{pn} - \mu_{pn} \parallel^2 + \frac{1}{2} \log \sigma_{pn}^2, \tag{1}$$

where μ_{pn} and Pep_{pn} represent the predicted and observed expression value of peptide sequence p in cell

n, respectively. σ_{pn} represents the uncertainty for peptide sequence p in cell n . It can be seen that this

loss function is composed of two terms and each term involves σ_{pn}, which measures the data uncertainty

and also plays the role as a balance factor. Specifically, to reduce the loss, the model cannot output an

overly small σ_{pn} value since the term $\frac{1}{2\sigma_{pn}^2}$ will explode. On the other hand, the model cannot predict an

extremely large σ_{pn} either since the second term will increase. Hence, the model will output a reasonable

uncertainty estimation to balance both terms in the loss function. Besides, $\| y_{pn} - \mu_{pn} \|^2$ term is the

Mean Square Error (MSE) loss between the predicted and the observed expression values. Only when this

term is small enough, scPROTEIN can offer a small uncertainty prediction σ_{pn}, which indicates that the

model is confident about the current prediction of peptide expression value.

Protein-level expression matrix aggregated from peptide estimation.

Once the peptide uncertainty is estimated, we can compute the protein-level data in an uncertainty-guided

manner as shown in the right side of Figure 1 a. A peptide signal with higher uncertainty estimation value

indicates a noisy signal and should be assigned a smaller weight. In contrast, a peptide signal with lower

uncertainty tends to be a highly confident signal and should be given a larger weight. Therefore, we can

obtain the protein-level expression matrix X with its each entry as:

$$X_{fn} = \sum_{pep_p \in Pro_f} Pep_{pn} \cdot \frac{1}{\sigma_{pn}}, \tag{2}$$

where X_{fn} represents the aggregated expression value of protein f in cell n and $pep_p \in Pro_f$ denotes

peptide sequence p from protein f. The obtained expression protein-level expression matrix is then fed

into the *stage 2* of the scPROTEIN framework as the initial feature matrix.

Graph construction.

To make full use of the single-cell proteomic data, we convert the expression matrix into an undirected

and unweighted cell-cell graph $G = (V, E, X)$. $V = \{v_1, v_2, \dots, v_N\}$ is the set of cell nodes and N denotes

the number of cells. $E = \{e_{ij}\} \subseteq V \times V$ represents the set of all edges. We take the protein-level

expression data as the feature matrix $X = \{x_1, x_2, \ldots, x_N\} \in \mathbb{R}^{N \times F}$, and F denotes the dimension of feature

vectors which is also the number of proteins.

To obtain the cell graph topology, we first calculate the cell-wise similarity matrix S by Pearson

correlation coefficient (PCC) based on the expression feature vectors. S is formally stated as:

$$S_{ij} = PCC(v_i, v_j) = \frac{cov(x_i, x_j)}{\sigma_{x_i} \sigma_{x_j}},$$ (3)

where cov and σ denote the covariance and the standard deviation respectively. Then we set a threshold h

to construct the cell graph and the topological structure of cell graph G can be specified by a symmetric

adjacency matrix $A \in \mathbb{R}^{N \times N}$:

$$A_{ij} = \begin{cases} 1, & if\ S_{ij} > h \\ 0, & else \end{cases}.$$ (4)

The obtained binary adjacency matrix is then used to perform the following graph learning. Besides, our

scPROTEIN method can also be easily extended to single-cell spatial proteomics. With the provided

spatial location information, scPROTEIN can construct cell graph based on spatial proximity. Specifically,

the similarity matrix S now will be calculated based on the Euclidean distance computed from the spatial

coordinates as:

$$S_{ij} = Euc\_dist(coordinate_i, coordinate_j),$$ (5)

and we can similarly obtain the spatial informative cell graph topology by setting the threshold as

mentioned above. Noteworthy, our constructed spatial informative cell graph can subsequently be used to

quantify the spatial heterogeneity degree.

As the protein profile data are noisy, the constructed cell graph cannot be completely accurate. Therefore,

we apply two data augmentation strategies and a special denoising module to solve this problem and learn

robust embeddings.

Graph contrastive learning for accurate cell embedding

Model architecture.

Since label information is always scarce and task-specific, we propose to learn embeddings in an

unsupervised manner for better model generalizability. Motivated by the previous study[35], we propose a

deep graph contrastive learning framework to learn the comprehensive low-dimensional cell embeddings,

which receives the cell graph G and expression feature matrix X as input. Specially, in order to deal with

the noisy single-cell proteomic data caused by limitations of sequencing technology, we design a novel

alternated topology-attribute denoising module, which yields a more informative and noise-resistant cell

embedding. Overall, scPROTEIN contains four major components as shown in Figure 1b: 1) Data

augmentation, 2) GCN-based graph encoder, 3) Node-level graph contrastive learning and 4) Alternated

topology-attribute denoising module. Next, we will delve into the details.

Data augmentation.

Contrastive learning aims to learn the invariant representation between similar and dissimilar data pairs.

To produce the similar pairs, we employ the data augmentation to generate different views of the data.

Here we adopt two types of graph augmentation techniques: drop-edge[36] and mask-feature.

For drop-edge, we randomly remove existing edges from E with a given ratio p_{de}. In particular, we

sample an indicator matrix $R \in \mathbb{R}^{N \times N}$ to decide which edges will be removed. R_{ij} can be expressed as:

$$R_{ij} \sim Bernoulli(1 - p_{de}) \text{ if } A_{ij} = 1 \text{ else } R_{ij} = 0. \tag{6}$$

The perturbed adjacency matrix can be obtained by:

$$\tilde{A} = A \odot R, \tag{7}$$

where $\odot$ represents the Hadamard product operator.

For mask-feature, an indicator vector $M \in \mathbb{R}^{N \times 1}$ is generated with each entry $M_i \sim Bernoulli(1 - p_{mf})$,

where p_{mf} is a given mask-feature probability. The masked feature matrix is expressed as:

$$\tilde{X} = [x_1 \odot M; x_2 \odot M; ...; x_N \odot M]^T. \tag{8}$$

$[\cdot \, ; \cdot]$ represents the vector concatenation operator. In each training iteration, we employ the data

augmentation to generate two different but correlated graph views $G_1 = (V, \tilde{E}_1, \tilde{X}_1), G_2 = (V, \tilde{E}_2, \tilde{X}_2)$ as

shown in Figure 1b step 1.

GCN-based graph encoder

After the augmented graph views G_1 and G_2 are prepared, we learn the cell embedding based on node-

level graph contrastive learning. Since Graph Convolutional Network (GCN)[37] provides a powerful

learning model and is able to extract comprehensive embeddings for graph-structured data, we adopt

GCN as the feature extractor to learn the latent pattern for cell nodes. Concretely, GCN performs

convolution operation on the graph and iteratively updates the node representations by message passing

among the neighbourhoods. Taking the graph topology structure and the feature matrix as input, the low-

dimensional node representation can be learned by a L-layer GCN as:

$$Z^{l+1} = \delta(\hat{D}^{-\frac{1}{2}} \hat{A} \hat{D}^{-\frac{1}{2}} Z^l W^l), \tag{9}$$

where $\hat{A} = A + I$ and I is the identity matrix. $\hat{D}$ is the degree matrix of $\hat{A}$ with $\hat{D}_{ii} = \sum_i \hat{A}_{ij}$. W^l is the

layer-specific trainable weight parameter and Z^l represents the embedding matrix obtained by layer l. We

use ReLU as the non-linear activation function $\delta(\cdot)$. For two augmented graph views, we adopt a weight-

sharing GCN encoder to generate the embedding matrix Z_1 and Z_2 for each view respectively.

We set the dimension of all GCN layers d and the dimension of output embedding matrix is $\mathbb{R}^{N \times d}$.

Node-level graph contrastive learning

The obtained output Z_1 and Z_2 are then fed into a weight-sharing projection head g, which is used to

project the embeddings from two views into a common latent feature space where the contrastive loss is

constructed. g is implemented by a two-layer Multiple Layer Perceptron (MLP). By calculating the

contrastive loss in the projected latent space, scPROTEIN can obtain a better representation ability[38,39].

Then we try to maximize the agreement of the representations between two generated views of the same

node. Taking node i as an example, its embedding z_{1i} from view G_1 can be regarded as an anchor and

embedding z_{2i} from another view G_2 will be treated as a positive sample. Naturally, the embeddings of

other cell nodes will be taken as negative samples. We want to maximize the agreement between positive

pairs (anchor and its positive sample) and minimize the agreement between negative pairs (anchor and its

negative samples). Here we adopt the cosine similarity function $\cos(\cdot)$ to measure the similarity between

samples and we can arrive at the modified infoNCE loss[40] for positive pair (z_{1i}, z_{2i}) as:

429
$$l(z_{1i}, z_{2i}) = -\log \frac{e^{\cos(z_{1i},z_{2i})/\tau}}{e^{\cos(z_{1i},z_{2i})/\tau} + \sum_{j=1}^{N} \mathbb{1}_{[j \neq i]}\left(e^{\cos(z_{1i},z_{1j})/\tau} + e^{\cos(z_{1i},z_{2j})/\tau}\right)}, \tag{10}$$

430   where τ is the temperature parameter and $\mathbb{1}_{[j \neq i]}$ denotes the indicator function. (z_{1i}, z_{1j}) is the negative

431   pair from the same augmented view and (z_{1i}, z_{2j}) is the negative pair from different views. Since the two

432   generated views can be switched, we can finally obtain the overall contrastive loss expressed as:

433
$$L_{cont\_node} = \frac{1}{2N} \sum_{i=1}^{N} [l(z_{1i}, z_{2i}) + l(z_{2i}, z_{1i})]. \tag{11}$$

By minimizing this node-level contrastive loss, positive node pairs are drawn closer and negative node

pairs are pushed apart. The biodiversity of each cell node can be well preserved and the batch effect can

be implicitly corrected, which results in a more robust embedding.

Alternated Topology-attribute denoising module

Compared to single-cell transcriptomic data, proteomic data has a more severe noise problem due to its

specific sample preparation process. Therefore, in order to obtain a noise-resistant cell embedding, we

design an alternated attribute-topology denoising module, which can be decoupled into the following two

alternated major steps.

Attribute denoising.

To alleviate the severe noise problem in the single-cell proteomic profile, we develop an attribute

denoising module based on prototype contrastive learning. As investigated in the previous study[41], the

prototypes[30] which are far away from the cluster boundaries are not vulnerable to noise compared to those

near the boundary. Based on this observation, we propose to exploit the away-from-boundary prototypes

to update other noisy samples.

As shown in Figure 1b *step2*, at each training epoch, we perform subpopulation detection via K-means

algorithm[42] based on the current learned embeddings with a pre-defined cluster number K. After K-means

algorithm converges, we can assign each node with its cluster label $cluster_i$. Then we naturally take K

cluster centers $\{c_1, c_2, ..., c_K\}$ as the prototype representation since these centers are usually far away from

the cluster boundary and more confident about their cluster label. Formally, cluster center c_k is calculated

by the average of samples with cluster label k:

454
$$c_k = \frac{1}{Num_k}\sum_{cluster_i=k} z_i, \tag{12}$$

455   where Num_k denotes the total number of samples with cluster label k. z_i is the learned cell embedding

456   for node i without data augmentation. This noise-resistant knowledge is then exploited to update the

457   whole node representation matrix by the designed prototype contrastive loss as:

458
$$L_{cont\_proto} = -\frac{1}{N}\sum_{i=1}^{N} \log \frac{\mathbb{1}_{[cluster_i=k]}\exp(z_i \cdot c_k/\tau)}{\sum_{k=1}^{K}\exp(z_i \cdot c_k/\tau)}. \tag{13}$$

By minimizing this objective function, the similarity between each node and its cluster center will be

enlarged. Each prototype is used to enhance the information of its surrounding samples. Finally, we can

obtain a denoised cell representation after an iterative training process. Besides, we further confirm that

our scPROTEIN model is robust to the choice of the cluster number K in Extended Data Figure 2.

Topology denoising.

To fix the existing inaccurate edges and further enhance the graph topology, we develop a topology

denoising module. The graph learning process is highly dependent on the graph structure. Hence the noise

exists in the graph topology can seriously degrade the model performance. In the initial cell graph, there

may be some vital edges that have not been mined. On the other hand, some established edges may be

pseudo edges which may bring in noisy information. With the learning of the network and the process of

attribute denoising, the characteristics of the nodes are continuously enhanced and cleaned, and the

semantic information of each cell node becomes clearer. Therefore, the edges in the network should also

be alternately updated accordingly.

To this end, we design a link predictor to alternately denoise the topology structure, and in turn improve

the quality of the learned embeddings. Considering the embedding matrix in iteration t as $Z^{(t)}$, we can

obtain the corresponding similarity matrix $S_{ij}{}^{(t)}$ based on pair-wise Pearson correlation coefficient. Then

we choose M edges with the highest probability in $S_{ij}{}^{(t)}$ as the set $Edge\_add^{(t)}$, and M edges with the

lowest probability score as the set $Edge\_remove^{(t)}$. The current adjacency matrix $A_{ij}{}^{(t)}$ can be refined

based on these two sets. We suggest that high probability edges should be added to enhance the graph

representation ability, while low probability edges should be removed to eliminate the topological noise.

Thus, we can obtain the updated adjacency matrix in iteration t as:

480
$$A_{ij}{}^{(t)} = \begin{cases} 1 & if\ e_{ij} \in Edge\_add^{(t)} \\ 0 & if\ e_{ij} \in Edge\_remove^{(t)} \\ A_{ij}{}^{(t-1)} & else \end{cases} \tag{14}$$

As shown in Figure 1b *step 2*, the updated adjacency matrix will pass through the next training iteration

for data augmentation and attribute denoising. Then the denoised node representation will in turn be used

to update the topological structure. Through such an alternated update mechanism, we largely relieve the

impacts of noise problem in single-cell proteomic data and derive a more robust cell representation.

Overall loss function.

The overall loss function of scPROTEIN model consists of two parts, which is expressed as:

$$L = L_{cont\_node} + \alpha L_{cont\_proto},$$ (15)

where α is a balance factor which is 0.05 used in the experiments. We minimize this loss function to train

the model parameters. Adam[43] is used as the optimizer with a learning rate 0.001.

Generation of cell embedding.

After the model achieves convergence, we can obtain the trained GCN encoder and the refined cell graph.

As shown in Figure 1c, the learned cell embedding Z is generated on the refined graph topology in *stage*

2 with the informative trained GCN encoder. The obtained embedding has largely mitigated this set of

tangled problems, including the data missingness, batch effects and noise problem. Therefore, it can be

used in a variety of applications, such as cell clustering, batch correction, label transfer, clinical analysis

and spatial analysis. It is worth noting that data augmentation is only used during the training process.

During the inference process, none of the data augmentation techniques is exploited.

Datasets

The single-cell proteomic datasets.

SCoPE2_Specht

SCoPE2_Specht is a representative single-cell proteomic dataset which quantifies 3042 proteins in 1490

cells via SCoPE2 sequencing technique. It contains two cell types: Monocyte and Macrophage cells.

Noteworthy, since Monocyte cells can be differentiated into Macrophage-like cells when polarizing

cytokines are absent, the characteristics of these two cell types can be quite similar and result in a more

difficult cell clustering task. We downloaded the data from https://scp.slavovlab.net/Specht_et_al_2019.

nanoPOTS

nanoPOTS dataset was prepared by nanoPOTS technology (nanodroplet processing in one-pot for trace

samples). It quantifies 1225 proteins in 61 cells which are composed of C10 cell, RAW cell and SVEC

cell. Data was downloaded at MassIVE data repository with ID: MSV000084110.

N2

N2 dataset sampled from mouse blood contains 108 cells and 1068 proteins. In N2 dataset, there are three

cell types (C10 cell, RAW cell and SVEC cell) as well. We downloaded the data from MassIVE data

repository with ID: MSV000086809.

SCoPE2_Leduc

The SCoPE2_Leduc dataset was downloaded from https://scp.slavovlab.net/Leduc_et_al_2021. It

contains 163 cells over 1647 proteins which is generated by SCoPE2. In SCoPE2_Leduc dataset, there are

two cell types: Hela cell and U-937 cell.

plexDIA

We downloaded plexDIA dataset from https://scp.slavovlab.net/Derks_et_al_2022. It contains three cell

types, which are Melanoma cell, U-937 cell，PDAC (HPAFII) cell.

pSCoPE_Huffman

We obtained the pSCoPE_Huffman dataset from https://scp.slavovlab.net/Huffman_et_al_2022. This

dataset is sampled by pSCoPE and consists of 163 cells and 1647 proteins. It contains three cell lines of

PDAC cell: CFPACI, HPAFII and BxPC3.

pSCoPE_Leduc

pSCoPE_Leduc dataset was downloaded from https://scp.slavovlab.net/Leduc_et_al_2022. It is generated

by pSCoPE technique and 1543 cells over 2844 different proteins are quantified. Melanoma cell and U-

937 cell are two cell types of pSCoPE_Leduc dataset.

The single-cell clinical proteomics datasets.

ECCITE-seq

The ECCITE-seq dataset was downloaded from Gene Expression Omnibus (accession number:

GSE126310). It contains 49 surface protein markers which is detected by cellular indexing of

transcriptomes and epitopes by sequencing (CITE-seq). The human peripheral blood mononuclear cells

(PBMC) in ECCITE-seq are from a healthy control donor or a patient with cutaneous T-cell lymphoma

(CTCL). After removing cell doublets, there remain 2767 cells from the control donor and 2634 cells

from the CTCL donor which are then used for exploration of downstream clinical analysis based on

single-cell proteomic data.

The spatial proteomics datasets.

BaselTMA

The BaselTMA dataset was downloaded at Zenodo (https://doi.org/10.5281/zenodo.3518284) and

includes 281 patients with breast cancer. The imaging mass cytometry technique was used to quantify 38

marker proteins and spatial tissue image at the same time. This results in that each TMA is equipped with

spatially resolved single-cell location information together with the protein quantification matrix. Each

tissue slice contains a 0.8-mm tumor core or a corresponding healthy breast tissue.

Data preprocessing.

547   The raw single-cell proteomic data is firstly normalized to the library size and then log2 transformed with

548   pseudo count 1. This process is implemented via SCANPY (https://pypi.org/project/scanpy/) package.

549   Besides, for ECcite_seq dataset, we remove the cell doublets as the authors suggested by a python

550   package scrublet[44] (https://github.com/swolock/scrublet).

Baseline methods

KNN-ComBat[19]

The imputation step with KNN is implemented by python package sklearn (https://scikit-learn.org/stable/)

and ComBat for batch correction is implemented by scanpy.pp.combat module via SCANPY

(https://pypi.org/project/scanpy/) package.

MAGIC[24]

MAGIC is downloaded from https://github.com/KrishnaswamyLab/MAGIC.

Evaluation experiments

Performance on the cell clustering.

We conducted cell clustering experiment on SCoPE2_Specht, which is a representative single-cell

proteomic dataset. We first exploited scPROTEIN *stage 1* to estimate the uncertainty of the peptide signal.

The obtained uncertainty estimation matrix together with the original peptide-level expression data were

then combined to produce the protein-level expression data, which was then fed into scPROTEIN *stage 2*

and *stage 3* to learn the informative cell embeddings. The embedding dimension was reduced by using

top 50 principle components selected by PCA (Principal Component Analysis) and we then used tSNE (t-

distributed stochastic neighbor embedding) algorithm to further reduce the dimension to 2 for 2-

dimensional visualization similar to Li et al[27]. The PCA and tSNE function were both implemented via

python package sklearn.manifold. Furthermore, to assess how well scPROTEIN performs by the aid of

the uncertainty-guided aggregation for protein-level data, we conducted an ablation study to compare the

performance of scPROTEIN with and without *Stage 1* (Figure 2d).

Performance on the batch correction.

To evaluate the ability of our proposed methods on cross-cohort data with batch effects from various

single-cell proteomic sequencing techniques and platforms, we conducted five different experiments in

two levels. In the first level, we performed experiments on N2 and nanoPOTS datasets with exactly the

same set of cell types (Figure 3a, b). In these two datasets, both have three cell types: C10 cell, RAW cell,

and SVEC cell. In the second level, we test the model's ability to reconcile the same cell type (cell line)

from different sources while maintaining the biodiversity of different cell types. Specifically, we

corrected the batch effect of SCoPE2_Leduc and plexDIA in Figure 3c, d (merging U-937 cell),

pSCoPE_Huffman and plexDIA in Extended Data Figure 3a, b (merging PDAC (HPAFII) cell),

pSCoPE_Leduc & plexDIA in Extended Data Figure 4a, b (merging Melanoma cell and U-937 cell), and

pSCoPE_Leduc & SCoPE2_Leduc in Extended Data Figure 4 c, d (merging U-937 cell). In each batch

correction experiment and for all comparison methods, the shared proteins were exploited for analysis.

We reported the mean values of each metric across 10 runs in each experiment.

Performance on the cell type annotation.

The cell type annotation (label transfer) task was conducted on N2 and nanoPOTS dataset. After

correcting the batch effect via scPROTEIN, the cell labels from one dataset can be naturally transferred to

another (Figure 3e, f). KNN algorithm was employed to inference the labels of query set from reference

set in the learned latent space.

Application

Performance on clinical single-cell proteomic data.

Samples from ECCITE-seq data were clustered based on the learned embeddings by Leiden algorithm

(resolution=0.6), which was implemented via scanpy.tl.leiden. Samples were clustered into 25 subgroups.

We can observe the different sample proportions and distinct protein signatures in various clusters using

the cell embedding. The Differential expression protein analysis was carried out using rank_gene_groups

function in SCANPY package with the t-test statistical method. The Functional profiling of Gene

Ontology (GO) for each subpopulation was performed by the gProfiler[45]

(https://biit.cs.ut.ee/gprofiler/gost).

Performance on spatial single-cell proteomic data.

BaselTMA dataset was exploited to confirm the scalability for scPROTEIN on single-cell spatial

proteomics. In each TMA slice, we constructed the cell graph, where node attributes are the expression

profile and edges between cells are established based on spatial cell location. Then the spatial informative

embedding can be naturally obtained via scPROTEIN model. The learned embedding was then clustered

via Leiden algorithm (resolution=0.6).

Evaluation Metrics

ARI[46] (Adjusted Rand Index), ASW[47] (Average Silhouette Width), NMI[48] (Normalized Mutual

Information) and PS[49] (Purity Score) were used for the evaluation of cell clustering and 1 - batch wise

metrics (1-ASW, 1-ARI, 1-NMI, and 1-PS) were used to measure the performance on batch correction of

same cell type. Similar to [26,27], we applied these metrics on the transformed data by tSNE. Accuracy and

macro-f1 score were applied in cell type annotation experiments. Average signal to noise ratio was

exploited to evaluate the data quality and quantify the data noise within each cell type. For all metrics,

higher score represents better performance. Metrics are defined as follows:

ARI[46]

$$ARI = \frac{\sum_{ij}\binom{n_{ij}}{2} - [\sum_i\binom{a_i}{2}\sum_j\binom{b_j}{2}]/\binom{n}{2}}{\frac{1}{2}[\sum_i\binom{a_i}{2} + \sum_j\binom{b_j}{2}] - [\sum_i\binom{a_i}{2}\sum_j\binom{b_j}{2}]/\binom{n}{2}}$$

614   where n_{ij} denotes the number of cells which are assigned to cluster i and j based on the true labels and the

615   clustering labels respectively. a_i is the number of cells from cluster i based on the true labels and b_j is the

616   number of cells assigned to cluster j according to the clustering labels.

617   *ASW*[47]

$$ASW = \frac{1}{N}\sum_i \frac{p(i) - q(i)}{max\{q(i), p(i)\}}$$

618     $q(i)$ represents the average distance of cell i to other cells in the same cluster and $p(i)$ is the average

619   distance between cell i and other cells in the nearest cluster. N is the total number of cells.

620   *NMI*[48]

$$NMI = \frac{MI(\hat{Y};Y)}{\sqrt{H(\hat{Y})H(Y)}}$$

621     $MI(\hat{Y};Y)$ denotes the mutual entropy between the predicted categorical distributions $\hat{Y}$ and the true

622   clustering categorical distributions Y. H is the Shannon entropy.

623   *PS*[49]

$$PS = \frac{1}{N}\sum_i max_j(n_{ij})$$

624   n_{ij} denotes the number of cells assigned to cluster i whose ground-truth label belongs to partition j. The

625   purity score quantifies the extent to which a cluster contains cells from only one partition.

626   *Acc*

$$Acc = \frac{1}{N} \sum_i I(\hat{Y}_i = Y_i)$$

$I(\cdot)$ denotes the indicator function.

macro-f1

The macro-f1 score was calculated by the function f1_score with average="macro" in the scikit-learn

package in Python.

average signal to noise ratio

The average signal to noise ratio was calculated within each cell type. Take $X_s \in \mathbb{R}^{N_s \times F}$ as a subset of

raw expression profile $X \in \mathbb{R}^{N \times F}$, where each cell has the same cell type. The average signal to noise

ratio is expressed as:

$$average\ signal\ to\ noise\ ratio = \frac{1}{F} \sum_f \frac{mean(X_s[:,f])}{sd(X_s[:,f])}$$

$X_s[:,f]$ denotes the column data for protein f. $mean(\cdot)$ and $sd(\cdot)$ represent the mean value and the

standard deviation. For other methods, X_s in this calculation process will be replaced by the processed

expression matrix or embedding matrix.

shd

In addition, we defined a spatial heterogeneity degree (*shd*) based on the built cell graph to quantify the

spatial heterogeneity. We first compared the cluster assignment of each cell with its spatial neighbouring

cells, which were identified by the constructed spatial informative graph. Then the proportion of

neighbouring cells with same cluster labels was used as the measure and can be expressed as:

$$shd = \frac{\sum_i \sum_{j \in Neigh(i)} I(cluster_i = cluster_j)}{\sum_i \sum_{j \in Neigh(i)} 1}$$

where $j \in Neigh(i)\ if\ e_{ij} \in E$ and $I(\cdot)$ denotes the indicator function. A high *shd* denotes a highly

compartmentalized phenotype while a low *shd* denotes a high level of inter-cell type mixing.

Statistical analysis

The two-sided Mann–Whitney test was utilized for the significance test and was implemented via

scipy.stats.mannwhitneyu package.

Data Availability

All data used in this study are publicly available and the usages were fully illustrated in the Method

section.

Code Availability

The codes are implemented in Python and released on https://github.tencentailab/scPROTEIN with

detailed instruction.

Acknowledgements

We thank Dr. Peilin Zhao for the suggestion of the project.

Author Contributions

F.Y. and J.Y. conceived and designed the project. W.L. and H.Z. developed the method. W.L. performed

research and conducted experiments under the supervision of F.Y. , H.Z. and J.Y.. W.L. and F.Y.

analysed the results. W.L. and F.Y. write the manuscript. W.L. finish the figure under the guidance of F.Y.

and J.Y.. F.W. helped to polish the manuscript and figure. H.Z. and J.Y. revised the manuscript. Y.R.

gave suggestion for the graph model building and the improvement of the manuscript. B.W. gave

suggestion for trustworthy AI and the improvement of the manuscript. All authors reviewed and approved

the manuscript.

Competing Interests

668   The authors declare no competing interests.

Figure Legends

Figure 1. The architecture of our proposed method.
a, The multi-task heteroscedastic regression model for peptide uncertainty estimation. The hierarchical
structure for cells, proteins, peptides, and amino acids is shown in the sub diagram. The uncertainty of
peptide measurement is estimated in this stage and used to guide the aggregation of peptide levels for the
corresponding protein. The network takes multiple peptide sequences as input in each iteration with a
mini-batch training strategy. One peptide sequence is shown to illustrate the learning process. In the right
panel, we show the aggregation process of using the learned uncertainty to get the protein-level content.

b, The unsupervised cell embedding model based on deep contrastive learning. A cell graph is
constructed using single-cell proteomic data where cells with similar protein content patterns are
connected. Contrastive learning scheme where different views of the graph are compared is employed to
generate cell embeddings. Attribute denoising and topology denoising are alternated to further improve
the embedding.

c, The inference of the pre-trained graph encoder to generate cell embedding, which is then applied to
various downstream tasks.

Figure 2. Cell clustering and peptide uncertainty estimation.
a, The tSNE plot displaying the cell distribution with the embedding of our proposed method and
comparison methods (KNN-ComBat and MAGIC) on SCoPE2_Specht dataset. The plots are colored by
the cell types. RAW denotes the results of raw protein-level expression data.

b, The ARI, ASW, NMI, and PS of our proposed method and comparison methods (KNN-ComBat and
MAGIC) on cell clustering on SCoPE2_Specht dataset. RAW means the metric evaluated on the raw
protein levels. The lower and upper hinges denote the first and third quartiles, with the whiskers in the
range of 1.5-times the interquartile.

c, The heatmap showing the estimated uncertainties of each peptide signal across cells, colored by the
estimated uncertainty. The batch information and protein information are shown below the heatmap and
on the right hand side of the heatmap, respectively.

d, The ablation experiment on clustering performance based on our method with and without performing
the uncertainty estimation of peptides in *stage 1* on SCoPE2_Specht dataset. Our method without
uncertainty means that the protein content is obtained simply based on the average of its constituting
peptides intensity. All data are given as means$\pm$sd. *, **, *** and **** indicate p-value<0.05, p-
value<0.01, p-value<0.001 and p-value<0.0001 respectively in a two-sided Mann–Whitney test.

Figure 3. Batch effect correction and label transfer.

a, The tSNE plot showing cells of N2 and nanoPOTS datasets, colored by data source and cell types.

b, The ARI-cell, ASW-cell, NMI-cell, and PS-cell of our proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with cell type labels as ground truth (x-axis) and 1-metrics of our proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with batch labels as ground truth (y-axis) on N2 and nanoPOTs datasets.

c, The tSNE plot showing cells of SCoPE2_Leduc and plexDIA datasets, colored by data source and cell types. U-937 is the shared cell type in the two datasets.

d, The ARI-cell, ASW-cell, NMI-cell, and PS-cell of our proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with cell type labels as ground truth (x-axis) and 1-metrics of our proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with batch labels as ground truth (y-axis) on SCoPE2_Leduc and plexDIA datasets. The result which is closest to the top right corner achieves the best performance.

e, The diagram showing the label transfer process based on the learned embedding. In the left panel, the gray dots represent cells with unknown labels from query set, and the other colored dots represent cells with known labels from reference set. When the batch effect is well removed (right panel), the gray cells can be annotated accurately by KNN.

f, The histogram showing the accuracy and macro-f1 score of our proposed method and the comparison methods (RAW, KNN-ComBat, and MAGIC) on transferring labels from N2 to nanoPOTS (left panel) and from nanoPOTS to N2 (right panel). All data are given as means±sd.

Figure 4. Application of learned embedding on clinical proteomic dataset.

a, The UMAP for raw data showing the cells from healthy donor in green and cutaneous T-cell lymphoma (CTCL) patient in red.

b, The UMAP for scPROTEIN showing the cells from healthy donor in green and cutaneous T-cell lymphoma (CTCL) patient in red.

c, The UMAP for scPROTEIN showing the cells colored by clustering results.

d, The heatmap showing the level of protein markers across clusters.

e, The count numbers of cells from the control donor in green and CTCL donor in red for different clusters.

f, The detailed ratio of cluster 5 cells in control donor and CTCL donor.

g, The volcano plot showing the differential expression proteins found by contrasting healthy cells and CTCL cells in cluster 5. The dots in red and green represent the identified up-regulated and down-regulated proteins for CTCL cells, respectively. We used p-value□= 0.05 and Fold Change = 1.5 as thresholds.

h, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster 5.

i, The detailed ratio of cluster 6 cells in control donor and CTCL donor.

j, The volcano plot showing the differential expression proteins found by contrasting healthy cells and
CTCL cells in cluster 6. The dots in red and green represent the identified up-regulated and down-
regulated proteins for CTCL cells, respectively.

k, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster
6.

l, The detailed ratio of cluster 2 cells in control donor and CTCL donor.

m, The volcano plot showing the differential expression proteins found by contrasting healthy cells and
CTCL cells in cluster 2. The dots in red and green represent the identified up-regulated and down-
regulated proteins for CTCL cells, respectively.

n, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster
2.

Figure 5. Application of our proposed method on spatial proteomic data.
a, The diagram showing the application of our proposed method on spatial proteomic data. The spatial
proteomic data is used to construct the spatial informative graph and then to infer spatial informative
embedding for tumor microenvironment analysis and spatial heterogeneity degree quantification.

b, The visualization of clusters on learned spatial informative embedding and the estimated index of
spatial heterogeneity within tumor samples. Representative samples with high *shd* indicating a highly
compartmentalized phenotype.

c, The visualization of clusters on raw protein expression data and the estimated index of spatial
heterogeneity within tumor samples. *shd* was calculated based on the graph built in scPROTEIN.

d, The visualization of learned spatial informative embedding and the estimated index of spatial
heterogeneity within non-tumor samples. Representative samples with low *shd* indicating a high level of
mixing between different cells.

e, The visualization of clusters on raw protein expression data and the estimated index of spatial
heterogeneity within non-tumor samples. *shd* was calculated based on the graph built in scPROTEIN.

f, The density plot of *shd* for scPROTEIN and raw expression data. The *shd* of scPROTEIN for tumor and
non-tumor slices show different ranges, while in raw expression data the ranges are overlapped.

Extended Data Figure 1. Systematical analysis on the sensitivity of hyperparameter d.

a, The influence of hyperparameter d on ASW and ARI in the clustering task using SCoPE2_Specht
dataset. d is the dimension of learned graph latent embedding of our proposed method.

b, The influence of hyperparameter d on ASW-cell and ARI-cell with cell type labels as ground truth in
the batch effect correction task using N2 and nanoPOTS dataset (top panel). The influence of
hyperparameters k on 1-ASW-batch and 1-ARI-batch with batch labels as ground truth in the batch effect
correction task using N2 and nanoPOTS dataset (bottom panel).

c, The influence of hyperparameter d on accuracy and macro-f1 score in the label transfer task (transfer from N2 to nanoPOTS).

Extended Data Figure 2. Systematical analysis on the sensitivity of hyperparameter K.

a, The influence of hyperparameter K on ASW and ARI in the clustering task using SCoPE2_Specht dataset. K is the number of prototypes in *Stage 2* of our proposed method.

b, The influence of hyperparameter K on ASW-cell and ARI-cell with cell type labels as ground truth in the batch effect correction task using N2 and nanoPOTS dataset (top panel). The influence of hyperparameters K on 1-ASW-batch and 1-ARI-batch with batch labels as ground truth in the batch effect correction task using N2 and nanoPOTS dataset (bottom panel).

c, The influence of hyperparameter K on accuracy and macro-f1 score in the label transfer task (transfer from N2 to nanoPOTS).

Extended Data Figure 3. Embedding visualization for SCoPE2_Specht, N2 and nanoPOTS.

a, The embedding learning process in SCoPE2_Specht dataset. From left to right, we depict the learning process from raw peptide level, learned peptide uncertainty for corresponding peptide, aggregated protein level after uncertainty adjustment and the final learned cell embedding.

b, The average signal to noise ratio within each cell type of scPROTEIN and comparison methods in SCoPE2_Specht dataset. Higher value indicates better data quality.

c, The visualization for part of the raw protein expression profile and learned embedding by scPROTEIN in N2 and nanoPOTS datasets. In the left panel, we can observe that the batch effect exhibits in the same cell type across two datasets. In the right panel, scPROTEIN can greatly mitigate the batch effect and the same cell type tend to show similar patterns.

Extended Data Figure 4. The batch effect correction on cell lines across different datasets.

a, The tSNE plot showing cells of pSCoPE_Huffman and plexDIA datasets, colored by data source and cell lines. HPAFII is the shared cell line in the two datasets.

b, The ARI-cell, ASW-cell, NMI-cell, and PS-cell of our proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with cell line labels as ground truth (x-axis) and 1-metrics of our proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with batch labels as ground truth (y-axis) on pSCoPE_Huffman and plexDIA datasets.

c, The heatmap showing the estimated uncertainties of each peptide signal across cells, colored by the estimated uncertainty on pSCoPE_Huffman dataset. The batch information and protein information are shown below the heatmap and on the right hand of the heatmap, respectively.

Extended Data Figure 5. The batch effect correction on cell types across different datasets.

a, The tSNE plot showing cells of pSCoPE_Leduc and plexDIA datasets, colored by data source and cell lines. Melanoma and U-937 are the shared cell types in the two datasets.

b, The ARI-cell, ASW-cell, NMI-cell, and PS-cell of our proposed method and comparison methods
(RAW, KNN-ComBat, and MAGIC) with cell line labels as ground truth (x-axis) and 1-metrics of our
proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with batch labels as
ground truth (y-axis) on pSCoPE_Leduc and plexDIA datasets.

c, The tSNE plot showing cells of pSCoPE_Leduc and SCoPE2_Leduc datasets, colored by data source
and cell lines. U-937 is the shared cell type in the two datasets.

d, The ARI-cell, ASW-cell, NMI-cell, and PS-cell of our proposed method and comparison methods
(RAW, KNN-ComBat, and MAGIC) with cell line labels as ground truth (x-axis) and 1-metrics of our
proposed method and comparison methods (RAW, KNN-ComBat, and MAGIC) with batch labels as
ground truth (y-axis) on pSCoPE_Leduc and SCoPE2_Leduc datasets.

Extended Data Figure 6. Application of learned embedding on clinical proteomic dataset
822

a, The detailed ratio of cluster 0 cells in control donor and CTCL donor.

b, The volcano plot showing the differential expression proteins found by contrasting healthy cells and
CTCL cells in cluster 0.

c, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster
0.

d, The detailed ratio of cluster 3 cells in control donor and CTCL donor.

e, The volcano plot showing the differential expression proteins found by contrasting healthy cells and
CTCL cells in cluster 3.

f, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster
3.

g, The detailed ratio of cluster 4 cells in control donor and CTCL donor.

h, The volcano plot showing the differential expression proteins found by contrasting healthy cells and
CTCL cells in cluster 4.

i, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster
4.

j, The detailed ratio of cluster 17 cells in control donor and CTCL donor.

k, The volcano plot showing the differential expression proteins found by contrasting healthy cells and
CTCL cells in cluster 17.

l, Top GO terms in Biological Process (BP) for identified up-regulated proteins for CTCL cells in cluster
17.

Extended Data Figure 7. Application of scPROTEIN on spatial proteomic data.
a, The visualization of learned spatial informative embedding and the estimated index of spatial
heterogeneity within tumor samples.

b, The visualization of learned spatial informative embedding and the estimated index of spatial
heterogeneity within non-tumor samples.

References

1. Svensson, V., Vento-Tormo, R. & Teichmann, S. A. Exponential
scaling of single-cell RNA-seq in the past decade. *Nature Protocols*
2018 13:4 **13**, 599–604 (2018).

2. Slavov, N. Unpicking the proteome in single cells:: Single-cell mass
spectrometry will help reveal mechanisms that underpin health and
disease. *Science* **367**, 512 (2020).

3. Leduc, A., Huffman, R. G. & Slavov, N. Droplet sample preparation
for single-cell proteomics applied to the cell cycle.
doi:10.1101/2021.04.24.441211.

4. Petelski, A. A. *et al.* Multiplexed single-cell proteomics using SCoPE2.
Nature Protocols 2021 16:12 **16**, 5398–5425 (2021).

5. Derks, J. *et al.* Increasing the throughput of sensitive proteomics by
plexDIA. *Nature Biotechnology 2022* 1–10 (2022)
doi:10.1038/s41587-022-01389-w.

6. Huffman, R. G. *et al.* Prioritized single-cell proteomics reveals
molecular and functional polarization across primary macrophages.
bioRxiv 2022.03.16.484655 (2022) doi:10.1101/2022.03.16.484655.

7. Doerr, A. Single-cell proteomics. *Nature Methods 2018 16:1* **16**, 20–
20 (2018).

8. Marx, V. A dream of single-cell proteomics. *Nature Methods 2019*
16:9 **16**, 809–812 (2019).

9. Perkel, J. M. Single-cell proteomics takes centre stage. *Nature* **597**,
580–582 (2021).

10. Schoof, E. M. *et al.* Quantitative single-cell proteomics as a tool to
characterize cellular hierarchies. *Nature Communications 2021 12:1*
12, 1–15 (2021).

11. Furtwängler, B. *et al.* Real-Time Search-Assisted Acquisition on a
Tribrid Mass Spectrometer Improves Coverage in Multiplexed Single-
Cell Proteomics. *Molecular and Cellular Proteomics* **21**, 100219
(2022).

12.   Dou, M. *et al.* High-Throughput Single Cell Proteomics Enabled by
882   Multiplex Isobaric Labeling in a Nanodroplet Sample Preparation
883   Platform. *Anal Chem* **91**, 13119–13127 (2019).

884   13.   Woo, J. *et al.* High-throughput and high-efficiency sample
885   preparation for single-cell proteomics using a nested nanowell chip.
886   *Nature Communications 2021 12:1* **12**, 1–11 (2021).

887   14.   Khan, Z. *et al.* Primate transcript and protein expression levels
888   evolve under compensatory selection pressures. *Science (1979)* **342**,
889   1100–1104 (2013).

890   15.   Vogel, C. & Marcotte, E. M. Insights into the regulation of protein
891   abundance from proteomic and transcriptomic analyses. *Nature*
892   *Reviews Genetics 2012 13:4* **13**, 227–232 (2012).

893   16.   Gygi, S. P., Rochon, Y., Franza, B. R. & Aebersold, R. Correlation
894   between Protein and mRNA Abundance in Yeast. *Mol Cell Biol* **19**,
895   1720–1730 (1999).

896   17.   Marguerat, S. *et al.* Quantitative Analysis of Fission Yeast
897   Transcriptomes and Proteomes in Proliferating and Quiescent Cells.
898   *Cell* **151**, 671–683 (2012).

899   18.   Irish, J. M., Kotecha, N. & Nolan, G. P. Mapping normal and cancer
900   cell signalling networks: towards single-cell proteomics. *Nature*
901   *Reviews Cancer 2006 6:2* **6**, 146–155 (2006).

902   19.   Vanderaa, C. & Gatto, L. Replication of single-cell proteomics data
903   reveals important computational challenges.
904   *https://doi.org/10.1080/14789450.2021.1988571* **18**, 835–843
905   (2021).

906   20.   Cheung, T. K. *et al.* Defining the carrier proteome limit for single-cell
907   proteomics. *Nature Methods 2020 18:1* **18**, 76–83 (2020).

908   21.   Mund, A. *et al.* Deep Visual Proteomics defines single-cell identity
909   and heterogeneity. *Nature Biotechnology 2022 40:8* **40**, 1231–1240
910   (2022).

911   22.   Brunner, A.-D. *et al.* Ultra-high sensitivity mass spectrometry
912   quantifies single-cell proteome changes upon perturbation. *Mol Syst*
913   *Biol* **18**, e10798 (2022).

914   23.   Specht, H. *et al.* Single-cell proteomic and transcriptomic analysis of
915   macrophage heterogeneity using SCoPE2. *Genome Biol* **22**, 1–27
916   (2021).

917   24.   van Dijk, D. *et al.* Recovering Gene Interactions from Single-Cell Data
918   Using Data Diffusion. *Cell* **174**, 716-729.e27 (2018).

25. Boekweg, H. *et al.* Features of Peptide Fragmentation Spectra in Single-Cell Proteomics. *J Proteome Res* **21**, 182–188 (2022).

26. Tran, H. T. N. *et al.* A benchmark of batch-effect correction methods for single-cell RNA sequencing data. *Genome Biol* **21**, 1–32 (2020).

27. Li, H., Brouwer, C. R. & Luo, W. A universal deep neural network for in-depth cleaning of single-cell RNA-Seq data. *Nature Communications 2022 13:1* **13**, 1–11 (2022).

28. Mimitou, E. P. *et al.* Multiplexed detection of proteins, transcriptomes, clonotypes and CRISPR perturbations in single cells. *Nature Methods 2019 16:5* **16**, 409–412 (2019).

29. Capriotti, E., Vonderheid, E. C., Thoburn, C. J., Bright, E. C. & Hess, A. D. Chemokine Receptor Expression by Leukemic T Cells of Cutaneous T-Cell Lymphoma: Clinical and Histopathological Correlations. *Journal of Investigative Dermatology* **127**, 2882–2892 (2007).

30. Bar-Ephraim, Y. E. *et al.* CD62L Is a Functional and Phenotypic Marker for Circulating Innate Lymphoid Cell Precursors. *The Journal of Immunology* **202**, 171–182 (2019).

31. Samimi, S. *et al.* Increased Programmed Death-1 Expression on CD4+ T Cells in Cutaneous T-Cell Lymphoma: Implications for Immune Suppression. *Arch Dermatol* **146**, 1382–1388 (2010).

32. Jackson, H. W. *et al.* The single-cell pathology landscape of breast cancer. *Nature 2020 578:7796* **578**, 615–620 (2020).

33. Keren, L. *et al.* A Structured Tumor-Immune Microenvironment in Triple Negative Breast Cancer Revealed by Multiplexed Ion Beam Imaging. *Cell* **174**, 1373-1387.e19 (2018).

34. Kendall, A. & Gal, Y. What Uncertainties Do We Need in Bayesian Deep Learning for Computer Vision? *Adv Neural Inf Process Syst* **30**, (2017).

35. Zhu, Y. *et al.* Deep Graph Contrastive Representation Learning. (2020) doi:10.48550/arxiv.2006.04131.

36. Rong, Y., Huang, W., Xu, T. & Huang, J. DropEdge: Towards Deep Graph Convolutional Networks on Node Classification. (2019) doi:10.48550/arxiv.1907.10903.

37. Kipf, T. N. & Welling, M. Semi-Supervised Classification with Graph Convolutional Networks. *5th International Conference on Learning Representations, ICLR 2017 - Conference Track Proceedings* (2016) doi:10.48550/arxiv.1609.02907.

38.   Tschannen, M., Djolonga, J., Rubenstein, P. K., Gelly, S. & Lucic, M.
On Mutual Information Maximization for Representation Learning.
(2019) doi:10.48550/arxiv.1907.13625.

39.   Chen, T., Kornblith, S., Norouzi, M. & Hinton, G. A Simple Framework
for Contrastive Learning of Visual Representations. 1597–1607
Preprint at https://proceedings.mlr.press/v119/chen20j.html (2020).

40.   van den Oord DeepMind, A., Li DeepMind, Y. & Vinyals DeepMind,
O. Representation Learning with Contrastive Predictive Coding.
(2018) doi:10.48550/arxiv.1807.03748.

41.   Wang, Y. & Yang, Y. Bayesian Robust Graph Contrastive Learning.
(2022) doi:10.48550/arxiv.2205.14109.

42.   Ahmed, M., Seraj, R. & Islam, S. M. S. The k-means Algorithm: A
Comprehensive Survey and Performance Evaluation. *Electronics*
2020, Vol. 9, Page 1295 **9**, 1295 (2020).

43.   Kingma, D. P. & Ba, J. L. Adam: A Method for Stochastic
Optimization. *3rd International Conference on Learning*
Representations, ICLR 2015 - Conference Track Proceedings (2014)
doi:10.48550/arxiv.1412.6980.

44.   Wolock, S. L., Lopez, R. & Klein, A. M. Scrublet: Computational
Identification of Cell Doublets in Single-Cell Transcriptomic Data. *Cell*
Syst **8**, 281-291.e9 (2019).

45.   Reimand, J. *et al.* g:Profiler—a web server for functional
interpretation of gene lists (2016 update). *Nucleic Acids Res* **44**,
W83–W89 (2016).

46.   Hubert, L. & Arabie, P. Comparing partitions. *Journal of Classification*
1985 2:1 **2**, 193–218 (1985).

47.   Rousseeuw, P. J. Silhouettes: A graphical aid to the interpretation
and validation of cluster analysis. *J Comput Appl Math* **20**, 53–65
(1987).

48.   Estévez, P. A., Tesmer, M., Perez, C. A. & Zurada, J. M. Normalized
mutual information feature selection. *IEEE Trans Neural Netw* **20**,
189–201 (2009).

49.   Mogotsi, I. C. Christopher D. Manning, Prabhakar Raghavan, and
Hinrich Schütze: Introduction to information retrieval. *Information*
Retrieval 2009 13:2 **13**, 192–195 (2009).

Figure 1

a

Stage1：peptide uncertainty estimation

b

Stage2：unsupervised cell embedding learning based on deep contrastive learning

c

stage3：perform a variety of analyses with learned embedding

Figure 2

Figure 3

Figure 4

Figure 5

EDFigure 1

EDFigure 2

a Cell clustering (SCoPE2)

b Cell clustering (N2&nanoPOTS)

Batch correction (N2&nanoPOTS)

c Label transfer (N2&nanoPOTS)

EDFigure 3

EDFigure 4

EDFigure 5

EDFigure 6

EDFigure 7

a

BaselTMA_SP41_38_X4Y7

shd = 0.838

BaselTMA_SP41_33_X14Y6

shd = 0.810

BaselTMA_SP41_63_X4Y9

shd = 0.806

BaselTMA_SP41_58_X15Y1

shd = 0.828

BaselTMA_SP41_31_X15Y2

shd = 0.782

BaselTMA_SP41_11_X13Y7

shd = 0.779

- 0
- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20

b

BaselTMA_SP41_58_X16Y1

shd = 0.517

BaselTMA_SP41_104_X8Y4_233

shd = 0.583

BaselTMA_SP41_24_X6Y2

shd = 0.619