CAAStools: a toolbox to identify and test Convergent Amino Acid Substitutions.

Fabio Barteri* [a,d], Alejandro Valenzuela* [a], Xavier Farré [g], David de Juan [a], Gerard Muntané [a,e,f],

Borja Esteve-Altava [h] and Arcadi Navarro [a,b,c,d].

Authors affiliations

a. *IBE, Institute of Evolutionary Biology (UPF-CSIC), Department of Medicine and Life Sciences, Universitat Pompeu Fabra. PRBB, C. Doctor Aiguader N88, 08003 Barcelona, Spain*

b. *Institució Catalana de Recerca i Estudis Avançats (ICREA) and Universitat Pompeu Fabra. Pg. Lluís Companys 23, 08010, Barcelona, Spain*

c. *Center for Genomic Regulation (CRG), The Barcelona Institute of Science and Technology, Av. Doctor Aiguader, N88, 08003 Barcelona, Spain*

d. *BarcelonaBeta Brain Research Center, Pasqual Maragall Foundation, C. Wellington 30, 08005, Barcelona, Spain*

e. *Hospital Universitari Institut Pere Mata, Institut d'Investigació Sanitària Pere Virgili (IISPV), Universitat Rovira i Virgili, Reus, Spain.*

f. *Centro de investigación biomédica en red en salud mental (CIBERSAM), Spain.*

g. *Genomes for Life-GCAT lab. Germans Trias i Pujol Research Institute (IGTP), Badalona, Spain*

h. *European Molecular Biology Laboratory. Meyerhofstraße 1, 69117 Heidelberg, Germany*

* Equal contribution

Abstract.

Background.

Coincidence of Convergent Amino Acid Substitutions (CAAS) with phenotypic convergences allow pinpointing genes and even individual mutations that are likely to be associated with trait variation within their phylogenetic context. Such findings can provide useful insights into the genetic architecture of complex phenotypes. Here we introduce CAAStools, a set of bioinformatics tools to identify and validate CAAS in orthologous protein alignments for pre-defined groups of species representing the phenotypic values targeted by the user.

Implementation and availability

CAAStools source code is available at http://github.com/linudz/caastools, along with documentation and examples.

Supplementary information

Supplementary data are available.

Introduction.

Convergent Amino Acid Substitutions (CAAS) provide important insights into the genetic changes

underlying phenotypic variation (Zhang and Kumar, 1997; Ray *et al.*, 2015). Recent examples

include the identification of genes potentially involved in marine adaptation in mammals (Foote

et al., 2015) and the convergent evolution of mitochondrial genes in deep-sea fish species (Sheng

et al., 2019). Notably, in 2018, Muntané *et al.* identified a set of 25 genes involved in longevity in

primates (Muntané *et al.*, 2018). A few years later, a similar analysis for a wider phylogeny

retrieved 996 genes associated with lifespan determination in mammals (Farré *et al.*, 2021). While

these analyses often need to be tailored for each particular phenotype and phylogeny, all CAAS

detection and validation strategies reported in the literature share some common steps (Rey *et al.*,

2019). First, researchers select the species to compare for CAAS analysis and split them into two

or more groups according to the phenotype of interest. The criteria to select these groups can be

quite diverse: for instance, groups can be formed by species having diverging values of a given

continuous trait, or by species sharing different adaptations, like terrestrial and marine mammals

(Foote *et al.*, 2015). The second step consists in linking amino acid substitutions with each group.

Here, different approaches can be used, such as identifying identical substitutions for the same

amino acid (Besnard *et al.*, 2009; Chabrol *et al.*, 2018), detecting topological incongruencies (Li

et al., 2008), variations in amino acid profiles (Rodrigue *et al.*, 2010; Rey *et al.*, 2018), or relying

on consistent patterns of groups of amino acids in different groups of species (Zhang et al, 2014;

Muntané *et al.*, 2018; Farré *et al.*, 2021). The third step consists in testing the significance of the

results. Molecular convergence is a noisy process because spurious CAAS may occur at random

in the absence of relationships with phenotypes or selective forces (Shahoua *et al.*, 2017). To

overcome this, researchers have adopted different strategies, mostly based on the idea that adaptive

CAAS tend to exceed convergent noise. The delta Site-Specific log-Likelihood Score (ΔSSLS),

for instance, is a method that consists in comparing the CAAS likelihood for different phylogenetic

topologies (Castoe *et al.*, 2009; Wang, Susko and Roger, 2012; Parker *et al.*, 2013). Another

approach uses bootstrap resampling tests to evaluate whether the number of detected CAAS is

larger than expected by chance (Muntané *et al.*, 2018; Farré *et al.*, 2021). Alternatively, some

authors have adopted a strategy that consists in quantifying the convergent noise and focus on the

detection of Convergence on Conservative Sites (CCS) (Xu *et al.*, 2017; He *et al.*, 2020). In spite

of all these contributions, there is still no consensus approach. Some authors question whether

phenotypic convergence matches genome-wide molecular convergence (Zou and Zhang, 2015b),

or whether adaptive substitutions outnumber random CAAS (Zou and Zhang, 2015a; Gregg *et al.*,

2015). Access to free software tools that are specifically designed to retrieve CAAS will allow the

wider research community to compare and validate different strategies, boosting future

methodological developments in the field of phylogenetic analysis.

Here we present CAAStools, a toolbox to identify and validate CAAS in a phylogenetic context.

CAAStools is based on the strategy applied in our previous studies (Muntané et al., 2018; Farré et

al., 2021) and implements different testing strategies through bootstrap analysis. CAAStools is

designed to be included in parallel workflows and is optimized to allow scalability at proteome

level.

Implementation.

CAAStools is a multi-modular python application organized into three tools. The outline of the suite is presented in **Figure 1**. The discovery tool is based on the protocol described in Muntané *et al.*, 2018 and Farré *et al.*, 2021. This approach identifies CAAS between two groups of species in an amino-acid Multiple Sequence Alignment (MSA) of orthologous proteins. These groups are named Foreground Group (FG) and Background Group (BG). Collectively, the two groups are called Discovery Groups (DG), as they represent the base for CAAS discovery. The CAAS identification algorithm scans each MSA and returns those positions that meet the following conditions: First, the FG and the BG species must share no amino acids in that position. Second, all the species in at least one of the two discovery groups (FG or BG) must share the same amino acid. The combination of these two conditions determines a set of different mutation patterns that the tool identifies as CAAS. Details on these patterns are provided in Supplementary Table 1.

Finally, CAAStools calculates the probability of obtaining a CAAS in a given position compared to randomized DGs, corresponding to the empirical p-value of the predicted CAAS in that position. This p-value represents a quantification of the convergent noise (Shahoua *et al.*, 2017) that is associated with a specific position. The details of this calculation are presented in Supplementary section 3. The Resample tool sorts species into *n* virtual DGs (resamplings) for bootstrap analysis according to different combination strategies. This tool enables bootstrap analyses based on CAAS excess or likelihood (Muntané et al., 2018; Farré et al., 2021; Castoe *et al.*, 2009). In a *Naive* modality, the probability of every species being included in a DG is considered identical and independent. This feature allows for bootstrap analyses aimed at quantifying convergent noise. However, species are phylogenetically related, biasing their probability of sharing a phenotype or amino acid. To address these phylogenetic dependencies CAAStools includes two other testing strategies. In the *Phylogeny-restricted* modality, the randomization can be restricted to some taxonomic orders or defined clades. These clades will match the ones of the species included in the DGs. In the *Brownian motion* modality, resampling is based on Brownian Motion simulations. The latter builds on the "permulation" strategy for trait randomization (Saputra et al., 2021) and its implementation relies on the *simpervec()* function from the RERconverge package (Kowalczyk *et al.*, 2019). Finally, the *bootstrap* tool determines the iterations returning a CAAS for each

115   position in a MSA to establish the corresponding empirical p-value for the detection of a CAAS
116   in that position. Both the discovery and the bootstrap tools are designed to be launched on single
117   MSAs, in order to allow the user to parallelize the workflow for large protein sets.

118   Usage and testing.

CAAStools users should take special care when designing the analysis and interpreting the results.
The comparison should be made between species with diverging values of a convergent phenotype.
Each DG should include species with comparable phenotype values from different lineages. The
values between the two DGs must diverge, ideally representing the extreme top and bottom values
in a continuous distribution or different binary conditions. The resulting output will consist of a
list of positions where at least one DG shares the same amino acid, which differs from those found
in the other DG. Depending on the DGs selected (often limited by the available phenotypic and
genetic information), this outcome may be influenced by various uninformative sources of
sequence variability, such as convergent noise and identity-by-descent. Therefore, it is advisable
to complement the CAAS analysis with other approaches that have different limitations, such as
ancestral state reconstruction (Royer-Carenzi and Didier, 2016), selection studies (Kosakovsky
Pond et al., 2020), or dN/dS analysis (Yang, 1997). For e.g., we tested CAAStools on the dataset
from Farré *et al.*, (2021). The details of this test are reported in Supplementary 3. The full dataset
is available in the /test folder within the CAAStools repository.

Figures

Figure 1. CAAStools layout. The three tools of the CAAStools suite rely on three pieces of information; a phylogenetic tree, the trait information, and an amino acid MSA. The discovery tool (A) detects the CAAS between two groups of species that are defined by the user on the basis of trait values. The resample tool (B) performs *n* trait resamplings in different modalities, on the bases of the phylogeny and the trait value distributions. The output of this resampling is processed by the bootstrap tool (C) that elaborates a bootstrap distribution from the MSA. All the tools can be executed independently.

Acknowledgements

We would like to thank our collaborators at the Institute of Evolutionary Biology of Pompeu Fabra University for supporting us and sharing their ideas in scientific discussions, with particular mention of Dr. Tomas Marques Bonet and members of his group. This work was supported by the I+D+i project PID2021-127792NB-I00 funded by MCIN/AEI/10.13039/501100011033 (FEDER Una manera de hacer Europa)" and by "Unidad de Excelencia María de Maeztu", funded by the AEI (CEX2018-000792-M) and Departament de Recerca i Universitats de la Generalitat de Catalunya (GRC 2021 SGR 0467).

Author Contributions

Fabio Barteri (FB) has been in charge of the development of CAAStools. Alejandro Valenzuela (AV) carried on the beta-testing and code debugging. FB and AV have contributed equally to this manuscript. Xavi Farré (XF), Gerard Muntané (GM) and Arcadi Navarro (AN) designed the CAAS identification and validation protocol. XF wrote a set of scripts to identify CAAS that served as template for CAAStools implementation. AN and GM conceptualized the method. AN, David de Juan (DJ) and Borja Esteve-Altava (BEA) - along with GM - participated in the scientific discussion and supervision of this project. DJ's contribution was particularly helpful for the optimization of CAAStools code.

Bibliography

Besnard, Guillaume, A. Muthama Muasya, Flavien Russier, Eric H. Roalson, Nicolas Salamin, y Pascal-Antoine Christin. «Phylogenomics of C4 Photosynthesis in Sedges (Cyperaceae): Multiple Appearances and Genetic Convergence». *Molecular Biology and Evolution* 26, n.º 8 (1 de agosto de 2009): 1909-19. https://doi.org/10.1093/molbev/msp103.

Castoe, Todd A., A. P. Jason de Koning, Hyun-Min Kim, Wanjun Gu, Brice P. Noonan, Gavin Naylor, Zhi J. Jiang, Christopher L. Parkinson, y David D. Pollock. «Evidence for an ancient adaptive episode of convergent molecular evolution». *Proceedings of the National Academy of Sciences* 106, n.º 22 (2 de junio de 2009): 8986-91. https://doi.org/10.1073/pnas.0900233106.

Chabrol, Olivier, Manuela Royer-Carenzi, Pierre Pontarotti, y Gilles Didier. «Detecting the Molecular Basis of Phenotypic Convergence». *Methods in Ecology and Evolution* 9, n.º 11 (2018): 2170-80. https://doi.org/10.1111/2041-210X.13071.

Farré, Xavier, Ruben Molina, Fabio Barteri, Paul R H J Timmers, Peter K Joshi, Baldomero Oliva, Sandra Acosta, Borja Esteve-Altava, Arcadi Navarro, y Gerard Muntané. «Comparative Analysis of Mammal Genomes Unveils Key Genomic Variability for Human Life Span». *Molecular Biology and Evolution* 38, n.º 11 (1 de noviembre de 2021): 4948-61. https://doi.org/10.1093/molbev/msab219.

Foote, Andrew D., Yue Liu, Gregg W. C. Thomas, Tomáš Vinař, Jessica Alföldi, Jixin Deng, Shannon Dugan, et al. «Convergent Evolution of the Genomes of Marine Mammals». *Nature Genetics* 47, n.º 3 (marzo de 2015): 272-75. https://doi.org/10.1038/ng.3198.

He, Ziwen, Shaohua Xu, Zhang Zhang, Wuxia Guo, Haomin Lyu, Cairong Zhong, David E Boufford, Norman C Duke, The International Mangrove Consortium, y Suhua Shi. «Convergent adaptation of the genomes of woody plants at the land–sea interface». *National Science Review* 7, n.º 6 (1 de junio de 2020): 978-93. https://doi.org/10.1093/nsr/nwaa027.

Kosakovsky Pond, Sergei L, Art F Y Poon, Ryan Velazquez, Steven Weaver, N Lance Hepler, Ben Murrell, Stephen D Shank, et al. «HyPhy 2.5—A Customizable Platform for Evolutionary Hypothesis Testing Using Phylogenies». *Molecular Biology and Evolution* 37, n.º 1 (1 de enero de 2020): 295-99. https://doi.org/10.1093/molbev/msz197.

Kowalczyk, Amanda, Wynn K Meyer, Raghavendran Partha, Weiguang Mao, Nathan L Clark, y Maria Chikina. «RERconverge: an R package for associating evolutionary rates with convergent traits». *Bioinformatics* 35, n.º 22 (1 de noviembre de 2019): 4815-17. https://doi.org/10.1093/bioinformatics/btz468.

Li, Gang, Jinhong Wang, Stephen J. Rossiter, Gareth Jones, James A. Cotton, y Shuyi Zhang. «The hearing gene Prestin reunites echolocating bats». *Proceedings of the National Academy of Sciences* 105, n.º 37 (16 de septiembre de 2008): 13959-64. https://doi.org/10.1073/pnas.0802097105.

Muntané, Gerard, Xavier Farré, Juan Antonio Rodríguez, Cinta Pegueroles, David A. Hughes, João Pedro de Magalhães, Toni Gabaldón, y Arcadi Navarro. «Biological Processes Modulating Longevity across Primates: A Phylogenetic Genome-Phenome Analysis». *Molecular Biology and Evolution* 35, n.º 8 (1 de agosto de 2018): 1990-2004. https://doi.org/10.1093/molbev/msy105.

Parker, Joe, Georgia Tsagkogeorga, James A. Cotton, Yuan Liu, Paolo Provero, Elia Stupka, y Stephen J. Rossiter. «Genome-Wide Signatures of Convergent Evolution in Echolocating Mammals». *Nature* 502, n.º 7470 (octubre de 2013): 228-31. https://doi.org/10.1038/nature12511.

Rey, Carine, Laurent Guéguen, Marie Sémon, y Bastien Boussau. «Accurate Detection of Convergent Amino-Acid Evolution with PCOC». *Molecular Biology and Evolution* 35, n.º 9 (1 de septiembre de 2018): 2296-2306. https://doi.org/10.1093/molbev/msy114.

Rey, Carine, Vincent Lanore, Philippe Veber, Laurent Guéguen, Nicolas Lartillot, Marie Sémon, y Bastien Boussau. «Detecting adaptive convergent amino acid evolution». *Philosophical Transactions of the Royal Society B: Biological Sciences* 374, n.º 1777 (22 de julio de 2019): 20180234. https://doi.org/10.1098/rstb.2018.0234.

Rodrigue, Nicolas, Hervé Philippe, y Nicolas Lartillot. «Mutation-selection models of coding sequence evolution with site-heterogeneous amino acid fitness profiles». *Proceedings of the National Academy of Sciences* 107, n.º 10 (9 de marzo de 2010): 4629-34. https://doi.org/10.1073/pnas.0910915107.

Royer-Carenzi, Manuela, y Gilles Didier. «A Comparison of Ancestral State Reconstruction Methods for Quantitative Characters». *Journal of Theoretical Biology* 404 (7 de septiembre de 2016): 126-42. https://doi.org/10.1016/j.jtbi.2016.05.029.

Saputra, Elysia, Amanda Kowalczyk, Luisa Cusick, Nathan Clark, y Maria Chikina. «Phylogenetic Permulations: A Statistically Rigorous Approach to Measure Confidence in Associations in a Phylogenetic Context». *Molecular Biology and Evolution* 38, n.º 7 (1 de julio de 2021): 3004-21. https://doi.org/10.1093/molbev/msab068.

Shen, Xuejuan, Zhiqing Pu, Xiao Chen, Robert W. Murphy, y Yongyi Shen. «Convergent Evolution of Mitochondrial Genes in Deep-Sea Fishes». *Frontiers in Genetics* 10 (2019). https://www.frontiersin.org/articles/10.3389/fgene.2019.00925.

Wang, Huai-Chun, Edward Susko, y Andrew J. Roger. «The Site-Wise Log-Likelihood Score Is a Good Predictor of Genes under Positive Selection». *Journal of Molecular Evolution* 76, n.º 5 (mayo de 2013): 280-94. https://doi.org/10.1007/s00239-013-9557-0.

Xu, Shaohua, Ziwen He, Zixiao Guo, Zhang Zhang, Gerald J. Wyckoff, Anthony Greenberg, Chung-I. Wu, y Suhua Shi. «Genome-Wide Convergence during Evolution of Mangroves from Woody Plants». *Molecular Biology and Evolution* 34, n.º 4 (1 de abril de 2017): 1008-15. https://doi.org/10.1093/molbev/msw277.

Yang, Z. «PAML: A Program Package for Phylogenetic Analysis by Maximum Likelihood». *Computer Applications in the Biosciences: CABIOS* 13, n.º 5 (octubre de 1997): 555-56. https://doi.org/10.1093/bioinformatics/13.5.555.

Zhang, Guojie, Cai Li, Qiye Li, Bo Li, Denis M. Larkin, Chul Lee, Jay F. Storz, et al. «Comparative genomics reveals insights into avian genome evolution and adaptation». *Science* 346, n.º 6215 (12 de diciembre de 2014): 1311-20. https://doi.org/10.1126/science.1251385.

Zhang, J., y S. Kumar. «Detection of Convergent and Parallel Evolution at the Amino Acid Sequence Level». *Molecular Biology and Evolution* 14, n.º 5 (mayo de 1997): 527-36. https://doi.org/10.1093/oxfordjournals.molbev.a025789.

Zou, Zhengting, y Jianzhi Zhang. «Are Convergent and Parallel Amino Acid Substitutions in Protein Evolution More Prevalent Than Neutral Expectations?» *Molecular Biology and*

249   *Evolution* 32, n.º 8 (1 de agosto de 2015): 2085-96.
250   https://doi.org/10.1093/molbev/msv091.

251   ———. «No Genome-Wide Protein Sequence Convergence for Echolocation». *Molecular*
252   *Biology and Evolution* 32, n.º 5 (1 de mayo de 2015): 1237-41.
253   https://doi.org/10.1093/molbev/msv014.

1 # CAAStools, a toolbox to identify and test Convergent
2 # Amino Acid Substitutions.
3
4 # Supplementary information.
5
6
7 ## Supplementary 1. CAAS Discovery algorithm.
8
Given two Discovery Groups (DGs, Foreground and Background groups, FG and BG,
respectively), the discovery tool recognizes as CAAS all those substitutions that meet two
requirements. Let A be an MSA of q sequences of length t. We can describe A as an array
of t positions [1]. Each position (pos_i) will consist of a set of N different amino acids, a,
with absolute frequency (or count), f, where NS is the total number of symbols in the
alignment [1].
15

16 [1] $A = (pos_1 \ pos_2 \ ... \ pos_t) \ ; \ pos_i = a_1 \ f_1 \ a_2 \ f_2 \ ... \ a_{NS} \ ... \ f_{NS} \ ; \ \sum_1^{NS} \ f =$
17 q
18

19 The FG and the BG are formalized as sets of different species s_{FG} and s_{BG}, with no
20 intersection and size l_{FG} and l_{BG} [2].
21

22 [2] $s_{FG} = (s_1 \ s_2 \ ... \ s_{l_{FG}}) \ ; \ s_{BG} = (s_1 \ s_2 \ ... \ s_{l_{BG}})$
23

24 $s_{FG} \cap s_{BG} = \emptyset$
25

26 In each alignment position, s_{FG} and s_{BG} are associated with two sets of amino acids,
27 $fg(pos_i)$ and $bg(pos_i)$, with length w_{FG} and w_{BG}.
28

29 [3] $fg(pos_i) = a_1 \ f_1 \ a_2 \ f_2 \ ... \ a_{w_{FG}} \ ... \ f_{w_{FG}} \ ; \ bg(pos_i) =$
30 $a_1 \ f_1 \ a_2 \ f_2 \ ... \ a_{w_{BG}} \ ... \ f_{w_{BG}}$
31
32

33 CAAStools identifies a CAAS when three conditions are met [4]. First, the two groups
34 must share no amino acids. This means that all the species in the FG need to have different
35 AAs than the species in the BG. Second, at least one of the two DGs must share (or
36 "converge to") the same amino acid. Also, the CAAS is detected if at least one amino
37 acid is associated to both DGs
38

39 [4] $CAAS_i \{ fg(pos_i) \cap bg(pos_i) = \emptyset \ w_{FG} == 1 \ or \ w_{BG} == 1 \ w_{FG} >$
40 $0 \ and \ w_{BG} > 0$
41

The combination of these three rules defines 3 different mutation *patterns*. We define
pattern 1 when the DGs converge to two different amino acids ($w_{FG} = 1; \ w_{BG} = 1$).
The *pattern 2* will be verified as the FG converges to one amino acid, but the BG will be
associated with different amino acids ($w_{FG} = 1; \ w_{BG} > 1$). *Pattern 3* will consist in the
opposite situation, or else when the FG is associated with different amino acids, whilst

the BG converges to a single amino acid ($w_{FG} > 1$; $w_{BG} = 1$). **Supplementary Table**
1 summarizes the different mutation patterns and the meeting of requirements for CAAS
identification.
50
51 ***Supplementary Table 1.*** *Mutation patterns and associated program decisions on CAAS*
52 *assignment.*

Discovery Groups		Difference between DGs	Convergence in		Pattern
FG	BG		FG	BG	
KV	K	NO	NO	YES	Not a CAAS (No difference)
M	TM	NO	YES	NO	Not a CAAS (No difference)
MK	VE	YES	NO	NO	Not a CAAS (No convergence)
K	V	YES	YES	YES	**Pattern 1** (Both convergent)
K	VM	YES	YES	NO	**Pattern 2** (FG convergent, BG multiple)
KE	W	YES	NO	YES	**Pattern 3** (FG multiple, BG convergent)

53
54

Supplementary 2. CAAS discovery statistical testing

56
CAAStools calculates an empirical p-value for each CAAS prediction. This p-value is
equal to the probability of obtaining a CAAS with random species, and under the same
conditions as the CAAS discovery (size of the DGs, maximum permitted gaps and
missing species). Following the MSA description in [1], we'll consider a couple of DG
(FG and BG) of size l_{FG} and l_{BG}, as formalized in [2]. The probability to obtain a CAAS
from random species is calculated as the probability of extracting concomitantly k_{FG}
and k_{BG} objects from a population of size N over a number of extractions *n*, provided the
conditions in [4], i.e. $k_{FG} \cap k_{BG} = \emptyset$ and $wk_{FG} == 1\ or\ wk_{BG} == 1$ where *wk* is the
number of symbols in the resampling *k*. This probability can be calculated through the
probability mass function from the hypergeometric distribution [5].
67

68 [5] $P(k) = \frac{\binom{K}{k}\binom{N-k}{n-k}}{\binom{N}{n}} = Hyp(N, K, k, n)$

69 $P(CAAS) = P(FG) * P(BG)$
70

71 $\{P(FG) = Hyp(N_{FG}, K_{FG}, k_{FG}, n_{FG})\ N_{FG} = q\ ;\quad k_{FG} = l_{FG} - null_{FG}\ n_{FG} =$
72 k_{FG}
73

74 $\{P(BG) = Hyp(N_{BG}, K_{BG}, k_{BG}, n_{NG})\ N_{BG} = q - l_{FG}\ k_{BG} = l_{BG} -$
75 $null_{BG}\ n_{BG} = k_{BG}$
76

Note that the size of the population N in *P(FG)* differs from the one considered in *P(BG)*.
In the first case, the probability of obtaining a convergence in the *FG* is calculated on the
total number of sequences in the alignment. In *BG*, the size considered is the difference
between the total number of sequences in the alignment *q* and the size of the other group
$(q - l_{BG})$, $(q - l_{FG})$, as the two events are concomitant but not independent. The
number of extractions k_{FG} and k_{BG} are equal to the number of the difference between the
size of the DGs and the number of indels and missing species allowed by the user (*null*).
The terms K_{FG} and K_{BG} represent the number of successes in the population. In [6], [7]
and [8], we see how this value can be calculated considering all the possible combinations
of amino acid symbols that meet the requirements for CAAS detection [4].

[6] $C_{P1,2} = \{K_{FG} = [f_j]; K_{BG} = [q - f_j] \ \forall \ a_j \in pos_i\}$

$C_{P1,2} = [(K_{FG_1}; K_{BG_1}), (K_{FG_2}; K_{BG_2}) \dots (K_{FG_z}; K_{BG_z})]$

[7] $C_{P1,3} = \{K_{FG} = [q - f_j]; K_{BG} = [f_j] \ \forall \ a_j \in pos_i\}$

$C_{P1,3} = [(K_{FG_1}; K_{BG_1}), (K_{FG_2}; K_{BG_2}) \dots (K_{FG_z}; K_{BG_z})]$

[8] $C_{P1} = \{K_{FG} = [f_j]; K_{BG} = [f_h] \ \forall \ a_j, a_k \in pos_i\}$

$C_{P1} = [(K_{FG_1}; K_{BG_1}), (K_{FG_2}; K_{BG_2}) \dots (K_{FG_z}; K_{BG_z})]$

These combinations are based on patterns (P). Note that $C_{P1,2}$ and $C_{P1,3}$ overlap, and
that the intersection coincides with C_{P1}. We can now calculate the CAAS probability
separately for each pattern [9].

[9] $P(CAAS_{P1,3}) = \sum_{x=1}^{z} Hyp(N_{FG}, K_{FG_x}, k_{FG}, n_{FG}) *$
$Hyp(N_{BG}, K_{BG_x}, k_{BG}, n_{NG})$

$P(CAAS_{P1,2}) = \sum_{x=1}^{z} Hyp(N_{FG}, K_{FG_x}, k_{FG}, n_{FG}) *$
$Hyp(N_{BG}, K_{BG_x}, k_{BG}, n_{NG})$

$P(CAAS_{P1}) = \sum_{x=1}^{z} Hyp(N_{FG}, K_{FG_x}, k_{FG}, n_{FG}) *$
$Hyp(N_{BG}, K_{BG_x}, k_{BG}, n_{NG})$

The probability to obtain a CAAS in position pos_i is hence calculated as it follows:

[10] $pvalue_{pos_i} = P(CAAS_{pos_i}) = P(CAAS_{P1,3}) + P(CAAS_{P1,2}) - P(CAAS_{P1})$

2.1 Correction for discovery groups of equal size.

If the species found in the alignment are the same for FG and BG sizes ($l_{FG} = l_{BG}$), the
probability of retrieving pattern 2 and pattern 3 are equal. In this case, the p-value is
equal to the $P(CAAS_{P1,2})$.

[11] $\{pvalue_{pos_i} = P(CAAS_{pos_i}) = P(CAAS_{P1,2})$ if $l_{FG} = l_{BG}$

Supplementary 3. CAAS discovery from Farré et al., 2021.

As a test run for CAAStools, we repeated the CAAS discovery from the results published
by Farré et al., in 2021 and entitled "*Comparative Analysis of Mammal Genomes Unveils*
Key Genomic Variability for Human Life Span" (DOI: 10.1093/molbev/msab219). In this
work, 13,035 MSA from UCSC public database (https://genome.ucsc.edu/, accessed
August, 2019) were scanned to find CAAS between two groups of species with divergent
maximum lifespan. The "long lived" group is formed by *Homo sapiens* (hg38), *Nomascus*
leucogenys (nomLeu3), *Heterocephalus glaber* (hetGla2), *Myotis davidii* (myoDav1),
Myotis lucifugus (myoLuc2), *Eptesicus fuscus* (eptFus1). The "short lived" group is
formed by *Mesocricetus auratus* (mesAur1), *Rattus norvegicus* (rn6), *Pantholops*
hodgsonii (panHod1), *Sorex araneus* (sorAra2), *Condylura cristata* (conCri1),

Monodelphis domestica (monDom5). Farré et al., filtered the results from CAAS
discovery to those CAAS having no gaps or missing species, and focused their analysis
on the CAAS of scenarios 1 and 2, which correspond to patter 1 and 2 in CAAStools
terminology.
137
138 We have repeated this analysis under the same conditions, filtering for pattern 1 and 2
139 and for no gaps in foreground (*short-lived* group) and background (*long-lived* group). The
140 results (*Supplementary dataset 1*) and the phenotype configuration (*Supplementary
141 dataset 2*) are available in the supplementary.material.xls spreadsheet. Our analysis
142 confirmed the identification of 2737 mutations in 2004 MSA.
143

144 ## Supplementary 4. An example of p-value calculation and correction via
145 ## bootstrap from *Farré et al. 2021* dataset.
146
The gene BRCA2 (RefSeq code: *NM_000059*) is part of the results published by Farré
et al. in 2021. In that analysis, authors selected only those positions that were associated
with no gaps in both Foreground and Background, obtaining 7 CAAS from this gene.
Here, we repeated the CAAS detection without any filtering for gaps or missing species
on the BRCA2 gene. Then, we used the simulation tool to generate 1,000 simulated
traits for each simulation mode (random, random with phylogeny restriction and
Brownian motion). We finally ran a bootstrap for each strategy and compared the
resulting p-values with the one calculated by the discovery tool. The result is shown in
Supplementary Table 2, whilst the extended CAAStools discovery output can be found
in *Supplementary Dataset 3*.
157
158 **Supplementary Table 2.** *P-value comparison on CAAS found on BRCA2.*
159

Gene	Position in MSA	Substitution	p-value			
			Hypergeometric	Random	Phylogeny-restricted	Brownian motion
NM_000059	46	A/PSV	0.00111290839	0.002	0.086	0.016
NM_000059	258	R/GKQT	0.0001146674319	0	0.033	0.022
NM_000059	481	L/IMPT	0.0002223201488	0	0.016	0.006
NM_000059	483	V/GILT	0.0002482399421	0.001	0.154	0.01
NM_000059	631	AIL/T	0.0003309226089	0.001	0.013	0.024
NM_000059	953	E/DK	0.02510771161	0.003	0.014	0.055
NM_000059	979	D/EGN	0.0037519556	0	0.421	0.071
NM_000059	1172	I/ALPTV	0.007452886308	0.001	0.144	0.026
NM_000059	1216	R/GKS	0.0001084014692	0	0.059	0.009
NM_000059	1297	I/AFKNTV	0.0002223401233	0	0.011	0.002
NM_000059	1361	H/CGQRY	0.000565102993	0.002	0.076	0.004
NM_000059	1548	K/ET	0.002094076584	0.006	0.355	0.061
NM_000059	1585	T/N	0.1699568024	0.038	0.383	0.159

NM_000059	1858	I/V	0.01704761083	0.047	0.226	0.106
NM_000059	1935	M/IKV	0.0002880415021	0.002	0.058	0.004
NM_000059	2012	K/EMRT	0.0009116846684	0.001	0.013	0.01
NM_000059	2039	I/L	0.1171992697	0.089	0.254	0.167
NM_000059	2261	M/ART	0.006530180592	0.007	0.082	0.069
NM_000059	3418	Z/QS	0.006622240227	0.001	0.037	0.039

160
The random resampling returns p-values that compare to those calculated by the
hypergeometric function from the discovery tool (*hypergeometric*). Besides, the
hypergeometric p-value reflects the probability to find a CAAS in a certain position
with random species. The difference between hypergeometric and random bootstrap
relies on the sets of species that are considered for resampling. Whilst the
hypergeometric function p-value is calculated on the species that are present in the
alignment, the random sampling is based on the species that are present in the
phylogenetic tree. The user might be motivated to choose the random resampling if the
number of species in the alignment differs remarkably from the number of species in the
phylogeny. Note that in our example, the number of species in the alignment equals the
number of species in the phylogeny (Farré et al., 2021).
172
As we apply phylogenetic constraints to random re-samplings, we observe a radical
increase of the p-values. This strategy, indicated as "*phylogeny-restricted*", is still based
on the random selection of species. Differently from the "*random*" resampling,
however, the *phylogeny-restricted* strategy limits the species extraction to some specific
clades. These clades correspond to the ones that are present in the DGs used in the
discovery tool that serve as "template". This limitation corresponds to a radical
reduction of the probability space and to an increase of the p-values (Supplementary
Table 2). In this case, the p-values reflect the probability to find aleatory convergences
in the clades used for CAAS discovery.
182
Finally, the resampling tool allows to simulate DGs through a Brownian-motion
stochastic process (Supplementary Table 2). In this case, the program will simulate a
neutral phenotype distribution over the phylogeny, to form the DGs by selecting species
with top and bottom values. With this approach, phylogenetically closer species tend to
exhibit similar phenotype values (Saputra et al., 2021). The simulated traits will hence
compare close species from different partitions of the phylogeny. This represents an
obvious reduction of the probability space, as not all the species combinations are
equiprobable. Also, it tends to compare species that come from different lineages and
that are more prone to share different amino-acids. The p-values are hence higher than
those calculated by both the discovery tool (using the hypergeometric method) and the
p-values simulated in the 'random' strategy. Conversely, the p-values simulated through
the "phylogeny-restricted" strategy – which reduces dramatically the probability space-
are tendentially higher.
Further details on the statistical testing are provided in CAAStools documentation
(https://github.com/linudz/caastools/blob/main/README.md).

Phylogeny

Trait values

Alignment(s)

A.

```
ct discovery \
  -a $alignment \
  -t $trait_values \
  -o $output
```

List of CAAS associations

B.

```
ct resample \
  -m $mode
  -p $phylogeny \
  --bytemp $trait_values \
  -o $output
```

Trait re-samplings

RS_01
RS_02
(...)
RS_1000

C.

```
ct bootstrap \
  -s $resamplings
  -a $alignment \
  -o $output
```

Bootstrap distribution

Inputs

Outputs