Reconstructing Spatio-Temporal Trajectories of Visual Object Memories in the Human Brain

Julia Lifanov[1*], Benjamin J. Griffiths[1], Juan Linde-Domingo[2,3,4], Catarina S. Ferreira[1], Martin Wilson[1], Stephen D. Mayhew[1], Ian Charest[5] & Maria Wimber[1,6*]

1) School of Psychology and Centre for Human Brain Health (CHBH), University of Birmingham, Birmingham, United Kingdom.
2) Research Group Adaptive Memory and Decision Making, Max Planck Institute for Human Development, Berlin, Germany
3) Center for Adaptive Rationality, Max Planck Institute for Human Development, Berlin, Germany
4) Max Planck Dahlem Campus of Cognition, Max Planck Institute for Human Development, Berlin, Germany
5) Département de Psychologie, Université de Montréal, Montréal, Quebec, Canada
6) School of Psychology & Neuroscience and Centre for Cognitive Neuroimaging (CCNi), University of Glasgow, Glasgow, United Kingdom.

Main text: 6032
Online methods: 17041

*Contact Information / Corresponding Authors
Maria Wimber, Julia Lifanov
maria.wimber@glasgow.ac.uk
jxl1118@alumni.bham.ac.uk

Abstract

Our understanding of how information unfolds when we recall events from memory remains limited. In this study, we investigate whether the reconstruction of visual object memories follows a backward trajectory along the ventral visual stream with respect to perception, such that their neural feature representations are gradually reinstated from late areas close to the hippocampus backwards to lower-level sensory areas. We use multivariate analyses of fMRI activation patterns to map the constituent features of the object memories onto the brain during retrieval, and EEG-fMRI fusion to track the temporal evolution of the reactivated patterns. Participants studied new associations between verbs and randomly paired object images in an encoding phase, and subsequently recalled the objects when presented with the corresponding verb cue. Decoding reactivated memory features from fMRI activity revealed that retrieval patterns were dominated by conceptual features, represented in comparatively late visual and parietal areas. Representational-similarity-based fusion then allowed us to map the EEG patterns that emerged at each given time point of a trial onto the spatially resolved fMRI patterns. This fusion suggests that memory reconstruction proceeds backwards along the ventral visual stream from anterior fronto-temporal to posterior occipital and parietal regions, in line with a semantic-to-perceptual gradient. A linear regression on the peak time points of reactivated brain regions statistically confirms that the temporal progression is reversed with respect to encoding. Together, the results shed light onto the spatio-temporal trajectories along which memories are reconstructed during associative retrieval, and which features of an image are reconstructed when in time and where in the brain.

Introduction

In contrast to the substantial scientific literature on visual perception, relatively little is known about how the human brain reconstructs content that is retrieved from memory. We here investigated which features of a visual memory are preferentially reactivated when objects are recalled from episodic memory, and where in the brain and when in time such feature reactivation occurs. We used multivariate pattern analyses combined with an experimental design where the perceptual and conceptual attributes of visual object stimuli were manipulated experimentally. Multivariate similarity-based EEG-fMRI fusion was then used to resolve these spatial patterns in time to recover the dynamic information flow during memory reconstruction. Together, the multivariate analyses of fMRI patterns and the EEG-fMRI fusion offer complementary insight into the reconstruction stream of low- and high-level features of episodic memories.

Visual perception of a realistic object triggers an information processing cascade along the ventral visual stream that follows a gradient of increasing abstraction. While early processing stages are dominated by low-level perceptual representations, later stages along the ventral visual stream increasingly code for conceptual features of the perceived object (T. Carlson et al., 2013; Cichy et al., 2014; Kolb et al., 1995; Martin et al., 2018). After approximately 250 ms, the information reaches the hippocampus, where one cell type, referred to as concept cell, represents an object as a highly abstract and individual concept (Clarke & Tyler, 2015; Quiroga, 2012). This final processing stage within the hippocampus also binds together information from different sources (including the dorsal stream) and serves the longer-term storage of associative information (Danker et al., 2017; Eichenbaum, 2001; Horner et al., 2015; Rolls, 2010).

Computational models then assume that once stored, the hippocampus can use a partial reminder to recover the missing, associatively linked information, a process termed pattern completion (Marr, 1971; O'Reilly & McClelland, 1994; O'Reilly & Norman, 2002; Teyler & DiScenna, 1986). Pattern completion in turn dictates the reactivation of neocortical brain regions that re-instantiate the various features of the previously encoded episode (Marr, 1971; Teyler & Rudy, 2007; Moscovitch, 2008). Such neocortical reinstatement presumably leads to the subjective re-experiencing of a past event (Tulving et al., 1983).

These computational models have provided the dominant framework for studying hippocampal-neocortical interactions during memory recall. One of their central characteristics is that they describe memory reinstatement as an all-or-none process and assume that during recall, neocortical information contained in a memory trace is re-established the way it was represented during initial perception. Indeed, indices for such copy-like encoding-retrieval-similarities (ERS) have been found by various neuroimaging studies using similarity- or classification-based multivariate analyses (Danker & Anderson, 2010; Rissman & Wagner, 2012; Staresina et al., 2012). ERS has been found in activation patterns for a variety of memory features, e.g., individual episodes, semantic category, sensory modality, or task context during learning (Wing et al., 2014; Ferreira et al., 2019; Griffiths et al., 2019; Jiang et al., 2020; Polyn et al., 2005). Further, evidence for pattern reinstatement has been found all along the sensory processing pathways activated during the initial perception of an event, including areas most proximal to the hippocampus (Staresina et al., 2012) as well as more distant neocortical structures (Polyn et al., 2005; Wing et al., 2014). Numerous studies additionally showed that successful retrieval is associated with the interplay between hippocampal activity and cortical reinstatement of encoding patterns during retrieval (Bosch et al., 2014; Horner et al., 2015; Staresina et al., 2012). Together, the previous findings support the central premise of the aforementioned computational models that hippocampal pattern completion is associated with a more or less truthful reinstatement of the encoding patterns. In the present study, our first goal is to decompose visual object memories into perceptual and conceptual components, and to test if both types of features are equally reinstated, in the same areas representing these features during memory encoding. The latter question is particularly interesting in the light of recent evidence that information reactivated from memory is not necessarily decodable from the same regions during encoding and retrieval (Favila et al., 2020; Xue, 2022).

While the above-mentioned classical theories and neuroimaging studies focus on the spatial localization of reactivated memory representations, less focus has been placed on the temporal progression of the reactivation processes. We therefore asked next how this spatial mapping of the retrieved contents unfolds over time. While the finding of encoding-retrieval similarity suggests at least a degree of copy-like reinstatement, it is well possible that different features of a memory are reactivated with different

temporal priority. Such prioritisation could naturally emerge from the hippocampus' differential connectivity with neocortical regions during retrieval. Once pattern completion is initiated, most information is relayed via the subiculum to the entorhinal cortex which in turn has back-projections to other cortical areas (Chrobak et al., 2000; Rolls, 2013; Staresina & Wimber, 2019). A majority of direct hippocampal and entorhinal efferents terminate in late areas of the visual processing hierarchy where representations cluster in abstract-semantic categories, while there are few connections to low-level sensory areas (Dalton et al., 2022; Insausti & Muñoz, 2001). We therefore expect that memories are initially reinstated on a conceptual level, and information coded in lower-level visual areas can only be reached at later stages of memory reconstruction (Insausti & Muñoz, 2001; Linde-Domingo et al., 2019). Indeed recent studies using EEG decoding and behavioural responses demonstrated a temporal prioritization of high-level conceptual over perceptual features during memory retrieval (Linde-Domingo et al., 2019; Lifanov et al., 2021). Where in the brain these different memory features are reinstated, and whether the conceptual-to-perceptual gradient truly maps onto a sensory backpropagation stream, remains an open question that is central to our study.

In the present work, we used an associative recall paradigm with visual object stimuli that allowed us to differentiate between their low-level perceptual and high-level conceptual features. First, using multivariate analysis of the fMRI patterns only, we investigated the spatial location of these low- and high-level feature representations, that is, where in the brain the different object dimensions can be decoded during retrieval compared to the initial encoding. Second, we asked whether the object information reconstructed during retrieval propagates backwards along the ventral visual stream, from high-level semantic to low-level visual areas, using EEG-fMRI fusion to resolve spatial activation patterns in time.

Results

In our memory paradigm, based on Linde-Domingo et al. (2019), participants first encoded novel associations between objects and action verbs, and at a later recall stage retrieved the object in as much detail as possible when presented with the verb. Participants were asked to indicate the time point of subjective recall with a button

press and to continue holding the retrieved image in mind. Importantly, images varied
along a perceptual (photographs versus line drawings) and a conceptual (animate
versus inanimate) dimension, and participants had to answer either a perceptual (Was
the object a photograph/drawing?) or conceptual (Was the object animate/inanimate?)
question after each recall. Using this paradigm in an fMRI environment, we aimed at
pinpointing the retrieval-related reinstatement of different object features in the brain.
A searchlight classification approach was used to spatially locate perceptual
(photograph versus drawing) and conceptual (animate versus inanimate)
representations during image encoding and retrieval. The next aim was to map spatial
representations onto a precise timeline preceding the subjective recall button press on
a trial-by-trial basis within subjects, using simultaneous EEG-fMRI data acquisition.
Since the within-scanner data turned out to be too noisy to decode the relevant object
features (see 'Analyses that did not work'), we instead used a previously acquired out-
of-scanner EEG dataset (Linde-Domingo et al., 2019) to map the spatial
representations onto the memory reconstruction timeline. This was done by means of
an EEG-fMRI data fusion, using a second-order representational similarity analysis
(RSA).

Figure 1. Overview of stimuli and task. a) Design of the stimuli. The 128 pictures used in any given
participant were orthogonally split into 64 drawings and 64 photographs, out of which 32 were animate
and 32 inanimate objects, respectively. Each object could thus be classified along a perceptual
(photo/drawing, cyan) or conceptual (animate-inanimate, magenta) dimension. b) One prototypical task
block of the paradigm. At encoding, participants were asked to associate verb-object pairings, and
indicate the successful formation of an association by button press. After a 20 s distractor task,
participants did a memory test where on each trial, they recalled the previously associated object upon
presentation of a verb cue and indicated successful subjective recollection by button press (referred to
as retrieval button press). Then participants were asked to hold the mental image of the object in mind
for a further 3 seconds, before answering a perceptual or conceptual catch question. Each association
was tested twice during retrieval, once with a perceptual, once with a conceptual question, with several
intervening test trials in between repetitions of the same association. Participants performed 16 task
blocks overall, with eight novel associations per block. Stimuli illustrated are chosen from the BOSS
database   (https://sites.google.com/site/bosstimuli/home,   https://creativecommons.org/licenses/by-
sa/3.0/) and customized with free and open source GNU image manipulation software (www.gimp.org;
see Linde-Domingo et al., 2019). Figure adapted from Lifanov et al. (2021) and Linde-Domingo et al.
(2019). c-e) Behavioural data acquired within (EEG-fMRI group) and out of scanner (EEG only group).
c) Subjective retrieval reaction times (RTs), d) RTs for each type of catch question, and e) catch

Behaviour

We first analysed the behaviour of participants who completed the fMRI study and
descriptively compared their performance with the participants who took part in the
out-of-scanner EEG study (Linde-Domingo et al., 2019). The encoding RTs and
accuracy rates between the in- and out-of-scanner data showed comparable results
(Table 1). However, looking at the retrieval RTs (Fig. 1d), participants in the fMRI study
were 1.24 s faster on average to indicate subjective retrieval than participants in the
EEG study. This RT difference was not only a result of the repeated retrievals in the
fMRI group, since RTs of both the first ($M1$ = 1.93 s; $SD1$ = 0.67 s) and second ($M2$ =
1.58 s, $SD2$ = 0.66 s) retrieval repetition of the fMRI group were substantially shorter
than those of the EEG group. Participants in the fMRI sample might thus have tended
to indicate subjective retrieval prematurely, and this may have had knock-on effect on
the catch question RTs discussed in the next paragraph.

	In-scanner	Out-of-scanner
Encoding RT	M = 3.01 s; SD = 0.91 s	M = 2.82 s, SD = 1.56 s
Retrieval RT	M = 1.75 s; SD = 0.66 s	M = 2.99 s; SD = .81s
Retrieval accuracy	M = 84.65 %, SD = .07	M = 86.75 %; SD = .06

Table 2. Means (M) and Standard deviations (SD) of encoding and subjective retrieval reaction times
(RTs) and accuracies of in- and out-of-scanner data.

After an explorative inspection of the behavioural data, we compared accuracies and
RTs between perceptual and conceptual catch questions using paired-sample t-tests
(Table 2). Note that, different from our previous behavioural work (Linde-Domingo et
al., 2019; Lifanov et al., 2021), the paradigm used here was not designed for

measuring differential conceptual and perceptual reaction times. After verb cue onset, participants were instructed to mentally reinstate the object and indicate this by button press. At this stage, we expected participants to have a fully reconstructed image of the recalled object in mind, such that answering the perceptual and conceptual catch question afterwards should take equally long. In the EEG study (also see Linde-Domingo et al., 2019), participants indeed answered conceptual and perceptual questions equally fast (t(23) = .5, p = .62 (uncorr.)) and accurately (t(23) = -1.80, p = .09 (uncorr.)). Participants in the fMRI study, however, performed more accurately (t(30) = -6.63, p < .01 (uncorr.)) and faster (t (30) = 8.31, p < .01 (uncorr.)) when answering conceptual compared to perceptual questions. The discrepancy between the EEG and fMRI samples, together with the difference in subjective retrieval time, suggests that participants in the fMRI study often pressed the subjective retrieval button before recall was complete, such that the reconstruction process carried over into the catch question period (Linde-Domingo et al., 2019; Lifanov et al., 2021).

a) In-scanner	RTs	Accuracy
Perceptual	M = 1.30 s, SD = 0.35 s;	M = 0.82, SD= 0.08
Conceptual	M = 1.06 s, SD = 0.25 s;	M = 0.88, SD = 0.07
t-test	t (30) = 8.31, p < .01 (uncorr.)	t(30) = -6.63, p < .01 (uncorr.)

b) Out-of-scanner	RTs	Accuracy
Perceptual	M = 1.38 s, SD = 0.35 s;	M = 0.86, SD = 0.07
Conceptual	M = 1.36 s, SD = 0.30 s;	M = 0.88, SD = 0.07
t-test	t(23) = .5, p = .62 (uncorr.)	t(23) = -1.80, p = .09 (uncorr.)

Table 2. Means (M) and Standard deviations (SD) of reaction times (RTs) and accuracies for perceptual and conceptual questions separately of in- and out-of-scanner data.

Despite these noticeable differences, accuracies were comparably high in the two samples. Moreover, in the EEG-fMRI fusion analyses reported further below, the fMRI

data is mainly used to derive the spatial representational patterns, while the precise
time resolution is provided by the EEG data. Considering the sluggishness of the
hemodynamic response (Friston et al., 1994; Kruggel & von Cramon, 1999), the faster
button presses in the fMRI sample should thus only have minimal effects on the fusion
results.

fMRI multivariate results

fMRI searchlight LDA

Previous work suggests that during memory recall, conceptual information becomes
accessible earlier than perceptual information, as evidenced in neural pattern
decodability (Linde-Domingo et al., 2019) and behaviour (Lifanov et al., 2021; Linde-
Domingo et al., 2019, and Fig. 1d). The first aim of the present study was to determine
the locus of these perceptual and conceptual representations both during encoding
and retrieval. We thus performed a searchlight-based, linear discriminant analysis
(LDA). Two separate classifiers were trained to distinguish between the different
perceptual (photographs versus drawings) and the different conceptual (animate
versus inanimate) classes of our visual objects (see methods for details). During
encoding (Fig. 2a), when the object was present on the screen, perceptual class could
be decoded in posterior regions along the ventral visual stream including V1, V2,
lingual and fusiform gyrus ($t(30) = 4.92$, $p < .05$ (FWE)). Conceptual class was
decodable from more anterior lateral temporal lobe areas, including inferior, mid and
superior temporal gyrus; and from precuneus, and inferior and dorsolateral prefrontal
cortex ($t(30) = 4.76$, $p < .05$ (FWE)). Together, this mapping generally reflects a
posterior-to-anterior perceptual-to-conceptual processing gradient. The results largely
mirror the univariate analyses reported in the supplemental materials (Suppl. Fig. 1,
supporting Fig. 2) and complement them by showing additional content decoding in
frontal and parietal regions, suggesting that these areas code information in fine-
grained multi-voxel patterns that univariate analyses are unable to capture.

During retrieval (Fig. 2b), perceptual features were most strongly decodable in the
precentral gyrus (i.e. premotor cortex), but also in V2, precuneus, mid and inferior
temporal lobe, parahippocampal gyrus, cingulate gyrus and middle frontal gyrus ($t(30)$
$= 4.74$, $p < .05$ (FWE)). Conceptual category membership was classified with the

highest accuracy from fusiform gyrus, precuneus, angular gyrus, and dorsolateral
prefrontal cortex, inferior and middle frontal gyrus, and temporal pole (t(30) = 4.54, p
< .05 (FWE)). Hence, in addition to the ventral visual areas dominating
encoding/perception, we also found extensive frontal and parietal areas in our retrieval
searchlight, in line with previous work suggesting that mnemonic as opposed to
sensory content can often be decoded from these areas (Favila et al., 2018, 2020;
Ferreira et al., 2019; Kuhl & Chun, 2014). Together, the fMRI-based classification of
the two dimensions that we explicitly manipulated demonstrates that brain activity
patterns during the retrieval of object images carry information about perceptual format
and semantic content, with the latter dominating the recall patterns. Reinstatement
was present in some of the areas seen at encoding, but additionally comprised regions
in fronto-parietal networks.

a fMRI searchlight results for encoding

b fMRI searchlight results for retrieval

- perceptual
- conceptual

$p < .05$ (FWE)

Figure 2. Searchlight LDA results. a) Encoding and b) retrieval accuracies significantly higher than the
50% chance level when classifying perceptual (cyan) and conceptual (magenta) object features. All
contrasts are thresholded at p < .05 (FWE-corrected). N = 31 independent subjects. Figure made using
MRIcron (https://www.nitrc.org/projects/mricron, www.mricro.com, Rorden & Brett, 2000) and a colin 27
average brain template (http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27, Holmes et al., 1998;
Copyright (C) 1993–2009 Louis Collins, McConnell Brain Imaging Centre, Montreal Neurological
Institute, McGill University).

EEG-fMRI data fusion

EEG multivariate analysis

The next goal of this study was to map the spatial patterns in a given brain area onto
the EEG patterns present at each time point of a trial, to reveal how content
representations evolve over the time course of encoding and retrieval. For this data
fusion, we first needed to obtain a meaningful EEG matrix representing object-to-
object similarities for each time point of encoding and retrieval, which we could then
compare to the fMRI-based matrices. Correlation-based RDMs for the EEG data were
too noisy to see a meaningful match between modalities (see section 'Analyses that
did not work'). We thus created a classification-based matrix representing the
dissimilarities between each pair of objects, in each EEG time bin, based on a cross-

participant classifier. Amplitudes over the 128 electrodes at a given time point served as classification features, and our 24 participants provided the repetitions of each object. The pairwise classification accuracies were entered in a single, time resolved RDM structure representing the dissimilarity between individual objects of our stimulus pool collapsed across participants (Fig. 3a). For all fusion analyses, we investigated encoding timelines from image onset, and retrieval timelines leading up to the subjective button press.

ROI fusion

Having obtained this EEG-based similarity time courses, we performed a similarity-based fusion of the EEG and fMRI data, probing what brain regions (in the fMRI data) most closely matched the similarity structures contained in the EEG data at any given time point during encoding and retrieval. For a first fusion step, we used the representational geometries (i.e., the RDMs) from an anatomically pre-defined set of regions of interest (ROIs). We then calculated the correlation between these ROIs' representational geometries and the geometries obtained from the EEG data for each time bin (Fig. 3a), and statistically compared the correlations against zero using cluster-basted permutation testing.

To statistically evaluate whether the information flow is primarily forward or backward along ventral visual stream areas, we used a linear regression on the cumulative sums of the correlation time courses of the corresponding ROIs, a method previously established for MEG analyses (Michelmann et al., 2019). The intuition of this method is that if region A starts accumulating information before region B, and region B before region C, the cumulative sums will line up sequentially to reflect this systematic delay in information accumulation (see simulation in Fig. 3b-d). In our case, we expected forward progressing latencies along the ventral visual stream during encoding and backwards progressing latencies during retrieval (Fig. 3b-d).

Figure 3. a) Overview of ROI and searchlight fusion. First, brain activity patterns are extracted from

fMRI and EEG to create representational dissimilarity matrices (RDMs) in the spatial and temporal

domain, respectively. Then, second-order correlations of the RDMs from the two imaging modalities

are computed for the data fusion. The EEG RDMs are classification-based, derived from binary

classifiers trained and tested to distinguish each pair of objects across participants. FMRI RDMs are

computed within participants and are correlation-based. FMRI RDMs can be computed at each voxel

centre (v) including voxels within a specific radius, or for larger regions of interest (ROI). Depending on

this choice, the data fusion will be searchlight- or ROI-based, respectively. b-c) Linear regression

approach on ROI time courses in a forward stream simulation. b) Normalized cumulative sum of each

ROI time course of the ventral visual stream. At time point 0.5 s, earlier visual regions show a higher

cumulative sum than later regions along the ventral visual stream. c) A linear regression is fitted across

ROI values at 0.5 s and results in a negative slope. d) Average slopes and standard errors are illustrated

for each time point across the window 0-1.5 s and tested against zero. Significant time points are

Our predefined set of ROIs included regions along the ventral visual stream (V1/V2,
hIT, temporal pole, and MTL), and regions along the dorsal stream (superior parietal
lobe, lateral inferior parietal cortex, and medial parietal cortex; see section ROIs).
Since many computational models propose that the role of the hippocampus is related
to association or indexing rather than feature representation (Eichenbaum, 2001;
McClelland et al., 1995; Teyler & DiScenna, 1986), we excluded the hippocampus
from the MTL regions. In Fig. 4, correlation time courses are plotted for each individual
ROI as t-values resulting from t-tests against zero, with clusters resulting from a
cluster-based permutation test (see section 'Analyses'). The figure shows ventral
visual regions in panel a, and dorsal regions in panel b. Following the object onset at
encoding (Fig. 4a-b), posterior regions including V1 and V2 show an increasing
correlation with the EEG representations from approximately 130 ms ($p < .01$
(uncorr.)). A significant cluster is seen at 240 ms ($p < .05$ (cluster)), followed by a
correlation increase of later ventral visual areas (human inferior temporal cortex (hIT))
around 300 ms ($p < .01$ (uncorr.)), reaching a significant peak at 430 ms ($p < .05$
(cluster)). Later lateral and medial temporal as well as parietal regions do not show a
significant correlation with the EEG time series during encoding.

As a proof of principle, we then tested for a forward processing stream in the encoding
data across ventral visual areas. Performing a linear regression on the cumulative
sums of all ventral ROI time courses at each time point (see Methods and Fig. 3b-c),
we found negative slopes reaching significance 500 ms after stimulus onset ($p < .05$
(cluster)). This finding statistically corroborates the observation that earlier ventral
visual regions code relevant information before later regions, supporting the well-
established forward stream (Fig. 4e). It should be noted, however, that evidence for
such feed-forward processing was only present relatively late in the trial, likely since
the strongest peaks of object identity decoding also fell in this late time window (see
Suppl. Fig. 2, supporting Fig. 4).

When performing the same analysis for ventral visual ROIs during retrieval (Fig. 4c), we find a significant cluster in early visual regions (V1/V2) preceding the subjective button press by 1.20 s ($p < .05$ (cluster)). Further, a number of regions peak below the threshold of cluster significance: MTL regions show a peak correlation with the EEG representational geometries -2.17 s prior to the retrieval button press ($p < .01$ (uncorr.)). Shortly after, correlation peaks are found for early visual regions (V1/V2), -1.90 s ($p < .01$ (uncorr.)) and again around -1.32 s before button press, slightly before the significant peak at -1.20 s ($p < .05$ (cluster)). At the latter peak, hIT also showed a peak correlation with the EEG geometry at -1.24 s ($p < .01$ (uncorr.)).

Within the dorsal set of ROIs (Fig. 4d), the medial parietal lobe showed a correlation peak in a similar time window, at -1.25 s and -1.13 s before button press ($p < .01$ (uncorr.)), however not surviving the cluster correction. This peak in the inferior parietal, but no other parietal regions, coincided with the peak times of posterior ventral visual areas (V1/V2/hIT).

Our main aim of the data fusion was to test if memory reactivation followed a backward processing hierarchy along the ventral visual stream. We therefore also performed a linear regression on cumulative sums of ventral visual regions within retrieval. This analysis revealed a significant positive slope from -2.1 to -1.2 s before button press ($p < .05$ (cluster)), speaking in favour of a backward stream and thus confirming our main hypothesis (Fig. 4f).

Searchlight fusion

Next, in a more explorative but also spatially better resolved approach, we conducted a whole-brain searchlight fusion to inspect where across the brain the fMRI-based representational geometries matched the EEG geometries over time. Figure 5 depicts spatial t-maps representing significant EEG-fMRI correlations in each searchlight radius for a given time bin, separately at encoding (Fig. 5a) and retrieval (Fig. 5b). The maps only show time points where significant spatial clusters emerged. During encoding, the searchlight fusion revealed a significant cluster in early visual regions from 300 to 800 ms after stimulus onset. Around 400 ms, significant clusters of EEG-fMRI similarity also extended to more ventral and lateral areas, including fusiform and inferior temporal gyrus. Correlations in brain regions along the ventral visual stream from early visual cortex to inferior temporal gyrus were sustained until approximately 700 ms, after which they gradually decreased. For the encoding data, the results of the searchlight approach thus overlap with the ROI fusion results, and mainly reveal ventral visual stream activation progressing in a forward manner. The missing engagement of early visual regions within the first 300 ms is most likely attributable to

the cross-subject classification approach used here, where the perceptual format of the perceived objects (photo vs drawing version) could differ between subjects, while object identity (i.e., semantics) was always matched.

During retrieval, the earliest cluster of significant EEG-fMRI correlation was found in the temporal pole, preceding the subjective retrieval button press by 2.97 s. This region re-emerged at -2.13 s, together with clusters in the precentral and inferior frontal gyrus. Then, from -1.9 s prior to the retrieval button press, ventral regions including fusiform and lingual gyrus, and early visual regions showed significant correlation peaks. Posterior visual regions also emerged again between approximately -1.35 s and -1.15 s before the retrieval button press. At -1.24 s, a large set of frontal and parietal regions showed significant correlations with the EEG representations, followed by another cluster of largely posterior visual areas at -1.15 s before button press. Together, the retrieval data shows strong convergence between the ROI- and searchlight fusion approach. It shows a progression of the peak correlations from fronto-temporal to posterior sensory regions, generally in line with a backward propagation hierarchy. This pattern of results is in line with previous work showing a conceptual-to-perceptual gradient in the same EEG dataset (Linde-Domingo et al., 2019). The present results additionally suggest that closest to the time point of subjective recollection (approximately 1.1-1.3 s preceding the button press), content information is most prominently represented in fronto-parietal and low-level visual areas.

Figure 5. T-maps of EEG-fMRI correlations at a) encoding and b) retrieval showing time points in the
trial time course where significant spatial clusters ($p_{cluster}$ < .05 for encoding and $p_{cluster}$ <.1 for retrieval,
see Methods for details on cluster correction) emerged. At encoding, time point 0 s would mark the
object onset. At retrieval, time point 0 s marks the button press, however, both zero time points are not
included in figure as no clusters emerged. N = 31 independent subjects. Brain figures made using
MRIcron (https://www.nitrc.org/projects/mricron, www.mricro.com, Rorden & Brett, 2000) and a colin 27
average brain template (http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27, Holmes et al., 1998;
Copyright (C) 1993–2009 Louis Collins, McConnell Brain Imaging Centre, Montreal Neurological
Institute, McGill University).

Discussion

A plethora of work on object recognition has shown that neural processing of a visually
perceived object progresses along the ventral visual stream following a feed-forward
gradient with increasing levels of information abstraction (T. Carlson et al., 2013; Cichy
et al., 2014; Martin et al., 2018). Recent memory research suggests that the
information processing hierarchy is reversed during the recall of an object from
episodic memory (Linde-Domingo et al., 2019; Lifanov et al., 2020; Mirjalili et al.,
2021). Here, we investigated whether this presumed reversed information processing
cascade during memory reconstruction maps onto the same ventral visual stream
areas that carry the information forward during perception, but now following a
backward trajectory. Our study shows that the reinstatement of visual object memories

follows a largely backward trajectory along ventral visual object processing pathways
and involves an additional information relay to parietal and frontal regions.

We first used uni- and multivariate analyses on the fMRI data alone to map out the
regions processing perceptual and conceptual object dimensions that were the built
into the stimulus set. As expected, during encoding when the object was visible on the
screen, these features largely mapped onto the ventral visual pathway, where early
visual areas processed the perceptual features (coloured photos versus black-and-
white line drawings), whereas later visual areas processed the higher order,
conceptual information (animate versus inanimate objects). This general perceptual-
to-conceptual gradient is in line with a multitude of findings in the basic object
recognition literature (T. Carlson et al., 2013; Cichy et al., 2014; Kravitz et al., 2013).

Univariate analyses were not powerful enough to detect differential activations
between perceptual and conceptual categories when objects were reconstructed from
memory. Activity patterns at the finer-grained multi-voxel level, however, carried
information about the categorical features of the retrieved images. Memory-related
reactivation of these features comprised some regions also found during object
encoding, particularly in late visual areas. This overlap confirms a body of previous
work showing that posterior visual areas are not only involved in visual perception but
also in internally generated processes, such as mental imagery (Dijkstra et al., 2021;
Kosslyn et al., 1993) or episodic memory. The reinstatement of encoding-related
patterns is a basic assumption of many computational models (O'Reilly & Norman,
2002), and has been reported in a wealth of empirical studies (for reviews, see Danker
& Anderson, 2010; Rissman & Wagner, 2012). While most studies find reactivation in
late visual areas (e.g., Griffiths et al., 2019; Polyn et al., 2005; Staresina et al., 2012),
others have reported areas as early as V1 (Bosch et al., 2014). It is also commonly
observed that stronger reinstatement is associated with memory success and strength
(e.g. Huijbers et al., 2011; Ritchey et al., 2013; Staresina et al., 2012; Thakral et al.,
2015; Wing et al., 2014) and the vividness and detail of remembering (Bone et al.,
2020; Simons et al., 2022; St-Laurent et al., 2015; Wheeler et al., 2000), suggesting
an important functional role of sensory reactivation.

Although the spatial locations of feature-specific patterns during recall partly
overlapped with those found during encoding, they also encompassed regions outside

the ventral visual object processing pathways. Most notably, during recall we were able to decode conceptual information from frontal and parietal regions. This shift from sensory to multimodal fronto-parietal areas between perception and memory, respectively, has recently gained attention, and has been described as a representational transformation of memories compared to their original representations during the actual experience (Favila et al., 2020; Xue, 2022). It has been suggested that depending on a bias in functional networks towards an encoding or retrieval state, content representations are preferentially expressed in sensory or parietal cortices, respectively, and mediated by differential connectivity with the hippocampus (Long & Kuhl, 2021; Ritchey & Cooper, 2020). Why reconstructed information is primarily represented in frontal and parietal cortex is currently debated (Favila et al., 2018; Humphreys et al., 2021; Levy, 2012; Staresina & Wimber, 2019). Previous work showed a retrieval-related semanticization and integration of memory patterns in those areas (Ferreira et al., 2019; Jonker et al., 2018), and more flexibility in parietal representations adjusted to recall goals (Favila et al., 2018), underlining the constructive nature of the reactivated memories (Xiao et al., 2017; Favila et al., 2020). Our findings support this encoding-retrieval distinction. They also suggest that it is primarily conceptual information (Fig. 2b) that is represented in these regions during retrieval, in line with previous work showing strong object identity, and even abstract concept coding in parietal cortex (Jeong & Xu, 2016; Kaiser et al., 2022). The involvement of parietal networks is also discussed further below in relation to the timing of the reactivation.

Going beyond a purely spatial mapping of perceptual and conceptual representations, fusing the EEG and fMRI data allowed us to inject time information into these spatial maps, and to ask how the memory reconstruction stream evolves, building up to the time of subjective recollection. We used two complementary approaches for data fusion, both comparing the representational geometries found in the EEG patterns at each time point with the fMRI geometries found in a given brain region. Both the ROI-based and searchlight-based approach showed a mainly feedforward sweep of information processing during the first few hundred milliseconds of encoding, starting within early visual regions approximately 120 ms after image onset (ROI fusion), and spreading to more ventral visual regions within the next 200 ms (ROI and searchlight fusion). Importantly, a formal regression analysis allowed us to statistically corroborate

the temporal direction of information flow, by modelling the information accumulation
rate across the hierarchy of ventral visual stream regions (Michelmann et al., 2019).
This regression analysis also showed a clear forward, posterior-visual to anterior-
temporal progression of the correlation patterns during encoding.

The EEG-fMRI fusion and sequence analysis applied to the retrieval data revealed a
largely backward information processing trajectory. Specifically, the data shows an
information flow from medial temporal lobe (see ROI fusion) and temporal pole (see
searchlight fusion) to more posterior visual regions (both fusion approaches). The
earliest significant searchlight cluster indicating a correspondence between EEG and
fMRI representations was found 2.97 s prior to the retrieval button press (Fig. 5b) and
was confined to the anterior temporal lobe. Caution is needed when interpreting this
earliest time point, since some participants had response times shorter than 3 sec,
where this time point would overlap with cue presentation. Reassuringly, however,
later time points preceding subjective recollection by approximately 2.2 to 2.1 s show
the same match with anterior temporal geometries (Fig. 5b) together with MTL
structures close to the hippocampus (Fig. 4c). The temporal pole has previously been
associated with the modality-independent processing of semantic information on the
level of basic-level categories (Clarke, 2020), and semantic retrieval in particular
(McClelland & Rogers, 2003; Noppeney & Price, 2002; Patterson et al., 2007; Rice et
al., 2018; Visser et al., 2010). Moreover, temporal pole reactivation around -2.1 s
before button press was close to the time point when objects from two different
conceptual classes were decoded with significantly higher accuracy than objects from
two similar conceptual classes based on the EEG classification alone (see Suppl. Fig.
2b, supporting Fig. 4). Together, these findings indicate that conceptual object features
in semantic networks are among the first to be reactivated during memory retrieval.

More posterior areas including inferior temporal, inferior parietal and visual cortices,
as well as frontal regions, reached their representational correlation peaks
considerably later, at the earliest around -1.9 s and most prominently at -1.2 s, the
latest time window in which we found significant reactivations leading up to subjective
recollection (Fig. 4c-d & 5b). While visual activations can be assumed to represent the
perceptual content of the reactivated memories, the role of fronto-parietal regions, as
mentioned before, is still a matter of debate (Barry & Maguire, 2019). In addition to the
literature discussed above, parietal areas have been shown to play a role in contextual

processing and memory-related imagery and scene construction (Lundstrom et al., 2005; Fletcher et al., 1995; Chrastil, 2018). The latest reactivations might thus be indicative of a final stage of reinstatement leading up to subjective recollection, likely involving working memory and memory-related imagery, and hence, preparation for the upcoming categorisation task (Christophel et al., 2012, 2017; Ganis et al., 2004). In summary, contrary to encoding, we find that retrieval follows a backward propagating stream along the ventral visual stream indicative of a conceptual-to-perceptual reconstruction gradient. Moreover, the backward reconstruction flow is not limited to ventral visual brain areas that dominate the encoding patterns, but instead involves frontal and parietal regions likely serving as an episodic memory or imagery buffer for the retrieved representations (Baddeley, 1998; Levy, 2012; Wagner et al., 2005).

To construct the EEG-based similarity structure for our data fusion, we used a cross-subject classification of object identity. This method differs from previously used EEG classification methods (Linde-Domingo et al., 2019; Mirjalili et al., 2021), which mainly served to find the peak times of categorical feature decoding. The different classification approaches might contribute to some timing differences between the present and previously published data. The present study revealed a reinstatement timeline where anterior temporal and posterior visual areas showed a representational match with the object-by-object similarities approximately -2.2 s and 1.9 s before subjective recall. Previously published analyses of the same EEG data (Linde-Domingo et al., 2019) found categorical decoding peaks considerably later, preceding subjective recollection by 1.8 s for conceptual and at 1.6 s for perceptual information. This timing difference could indicate that object-level information (e.g., elephant) is retrieved even earlier than conceptual class-level information (e.g., animate). Indeed, it has been shown that exemplar-level information is coded at very late stages of visual processing, in close proximity to the hippocampus, and might hence be the first to reactivate during retrieval (Clarke & Tyler, 2015). Importantly, the findings do agree on the reversed reconstruction aspect of memory retrieval, and our present results add the missing information about the spatial loci of reconstructed content. Together these results imply an information reactivation cascade during memory retrieval that starts with late semantic regions closely connected to the hippocampus, coding unified concepts and abstract object features, and then back-propagates to early visual

regions representing perceptual surface features of an object, while potentially
maintaining a unified memory representation in multisensory parietal areas.

The fMRI classification and the RSA-based EEG-fMRI data fusion in this study offer
complementary information. RSA is a highly useful tool to enable the comparison of
brain activity representations measured by different neuroimaging modalities
(Kriegeskorte & Kievit, 2013). By creating similarity structures from both EEG and fMRI
activity patterns in the same format, it becomes possible to directly correlate the
representational geometries emerging in neural space and time. However, RSA is in
itself blind to the informational content that is driving the match in representations
(Schyns et al., 2020). Classification-based approaches on fMRI (or EEG) data can
pinpoint categorical representations, however, these methods are limited to the very
few categories (e.g. colour, animacy) that can be explicitly built into an experimental
design. The methods thus offer complementary insights, and this is the likely reason
why in our study, some correlation peaks in the searchlight fusion maps during
retrieval did not overlap with the localisation of either perceptual or conceptual
features. Similarly, some individual stimulus classification peaks in the EEG data do
not coincide in time with the ROI fusion peaks. Richer study designs with more
stimulus variations on a trial-by-trial basis (Schyns et al., 2020) are a promising avenue
for revealing what type of content representations are contained in, and dominate,
reactivated memories.

An exciting recent development is the use of deep neural networks (DNNs) trained on
image categorization, and to compare the networks' layer patterns to the
representational patterns that emerge in the real brain (E. J. Allen et al., 2022; Cichy
et al., 2019). Some recent work has employed this approach to shed light onto the
nature of reactivated memory representations. For example, the method was used to
investigate what level of feature reactivation strongly predicts the vividness and
distinctiveness of a memory (Bone et al., 2020). Others have used DNNs in
comparison with intracranial EEG to reveal memory transformations over time and
across different processing stages (Liu et al., 2020). Finally, different types of models,
including word embedding models, have been used successfully to uncover the
temporal and content structure of recall narratives, and how it compares to the original
encoding (Heusser et al., 2021). In contrast to the relative black box of DNN layers,
the latter models offer more transparency and interpretability of the dimensions

contained in a memory, and a route to understanding how the recall of naturalistic, continuous events unfolds in time.

Finally, reaction times and accuracies have previously been shown to be strongly related to neuroimaging-based classification and thus indicative of the timing of the underlying brain processes (T. A. Carlson et al., 2013; Cichy et al., 2017; Linde-Domingo et al., 2019; Ritchie et al., 2015; ter Wal et al., 2021). Our reaction time results also reflected a backward neural processing stream, in line with previous studies designed explicitly to measure the speed of feature access during perception and memory using RTs (Linde-Domingo et al., 2019; Lifanov et al., 2021). The fMRI-based categorical decoding analyses support such a prioritization (Fig. 2b), showing that memory patterns are dominated by conceptual information. These findings may reflect functional anatomy, where closer reciprocal connections from the hippocampus to semantic than to perceptual regions shorten the processing time and thereby favour the reactivation of conceptual features during retrieval, which ultimately leads to a stronger retention of conceptual features, and possibly to a semanticization of memories over repeated retrievals (Linde-Domingo et al., 2019; Lifanov et al., 2021; Ferreira et al., 2019). The behavioural results therefore complement the spatial and temporal prioritisation of conceptual over perceptual representations during retrieval, as seen in the fMRI and EEG patterns, respectively.

In summary, our study supports the idea of a conceptual-to-perceptual information processing gradient that is reversed with respect to encoding along ventral visual stream regions processing object identity. Additionally, we show that the backward trajectory of memory reconstruction is not limited to ventral visual stream regions involved during encoding, engaging multisensory fronto-parietal areas at distinct stages of retrieval processing. The present findings demonstrate how the fusion of temporally and spatially resolved methods can further our understanding of memory retrieval as a staged feature reconstruction process, tracking how the reconstruction of a memory trace unfolds in time and space.

Methods

Participants

We acquired fMRI data of 37 right-handed, fluent English-speaking participants at the University of Birmingham (26 females, 11 males, mean age (M_{age}) = 23.33, standard deviation (SD_{age}) = 3.89, one participant did not indicate their age). The a priori planned sample size for the full EEG-fMRI dataset was $n = 24$ subjects. However, due to poor data quality and technical failures in 13 of the simultaneous EEG datasets, additional subjects were recorded leading to a larger sample size for the fMRI data alone. Three subjects were excluded from the fMRI analysis due to failed scanning sequences, and three additional subjects were excluded due to extensive motion within the scanner, exceeding the functional voxel size, such that 31 fMRI datasets remained for analysis. All participants were informed about the experimental procedure, underwent imaging safety screening and signed an informed consent. The research was approved by the STEM ethics committee of the University of Birmingham.

For the fusion analyses, we also included a previously published EEG dataset including the same stimulus set and a nearly identical associative learning and retrieval paradigm (Linde-Domingo et al., 2019). This additional dataset included 24 further participants with a clean, out-of-scanner EEG. For further information on the EEG data sample and the related ethical procedures, we refer to previous work (Linde-Domingo et al., 2019).

Material

The paradigm was a visual verb-object association task (Linde-Domingo et al., 2019) adapted for fMRI in terms of timing. Stimuli included 128 action verbs and 128 pictures of everyday objects (Linde-Domingo et al., 2019). Importantly, all object images existed in two perceptual categories, a coloured photograph from the BOSS database (Brodeur et al., 2010, available on https://sites.google.com/site/bosstimuli/home) or a black line drawing version of a respective photograph created by Linde-Domingo et al. (2019) by means of the free and open source GNU image manipulation software (www.gimp.org). Further each object belonged to one of two conceptual categories, i.e. animate vs inanimate. We selected 128 images per participant according to a fully

balanced scheme, such that each combination of perceptual and conceptual categories included the same number of pictures (32 animate-photographs, 32 animate-drawings, 32 inanimate-photographs, 32 inanimate-drawings; Fig. 1a). With respect to the later fusion with the out-of-scanner EEG data, it is important to note that while both experiments used the same set of 128 objects, the same object could appear in different perceptual versions between participants, due to the pseudo-randomised image selection. For example, an image of a camel could be shown as a photograph to one participant, and as a line drawing to another. Action verbs were randomly assigned to images in each participant and were presented together with pictures centrally overlaid on a white background.

Procedure

Before the session, participants were informed about the experimental procedure and asked to perform a training task block in front of the computer. After completion of the training, the experimental session in the fMRI scanner included four runs with four task blocks each, summing up to a total of 16 task blocks. A typical block in the training and experimental task included the encoding of eight novel associations, a 20 s distractor task, and 16 retrieval trials (two repetitions per association). A 3 min break was included after each fMRI run, in which participants were asked to rest and close their eyes. In total, it took participants approximately 70 min to perform the entire task.

Encoding

In the encoding phases (Fig. 1b), participants were instructed to study eight novel verb-object pairings in random order. A trial started with a fixation cross presented for a jittered period between 500 and 1500 ms. The action verb was presented for 500 ms before an object was shown for a maximum duration of 5 s. To facilitate learning, participants were instructed to form a vivid visual mental image using the verb-object pairing, and once formed, to press a button with their thumb, which moved the presentation on to the next trial.

Distractor

After each encoding phase, participants performed a self-paced distractor task for 20
s, indicating as fast as possible whether each of the consecutively presented numbers
on the screen was odd or even, pressing a button with their index or middle finger,
respectively. Feedback on the percentage of correct responses was provided at the
end of each distractor phase.

Retrieval

In the retrieval phases, participants were instructed to recall the previously associated
objects upon presentation of the corresponding verb (Fig. 1b). Trials started with the
presentation of a fixation cross, jittered between 500 and 1500 ms and followed by a
previously encoded action verb, presented for 500 ms. Cued with the verb, participants
were instructed to recall the paired object within a maximum of 5 s, while a black
fixation cross was presented on screen. Note that this maximum duration was shorter
than in the original task (Linde-Domingo et al., 2019), which might have caused
participants to react faster and possibly explains RT differences between the in-
scanner and out-of-scanner datasets (Fig. 1d). Participants were asked to indicate the
time point of image recall by button press with their thumb, at which point the black
fixation cross turned grey and was presented for an additional 3 s. This retrieval button
press was meant to mark the time point of subjective recollection. During the remaining
3 s participants were asked to hold the mental image of the object in mind as vividly
as possible. Last, they were asked about the perceptual (Was the object a photograph
or a line drawing?) or conceptual (Was the object animate or inanimate?) features of
the recalled object, answering with their index or middle finger within a maximum
response period of 5 s. During the presentation of the catch question, participants also
had the option to indicate with their ring finger that they forgot the features of the
corresponding object. Importantly, each encoded stimulus was retrieved twice, once
with a perceptual and once with a conceptual question. Trial order was pseudo-
random within the first and second set of repetitions, with a minimum of two intervening
trials before a specific object was recalled for the second time. The order of catch
questions was counterbalanced across repetitions such that half of the associations
were first probed with a perceptual question, and the other half was first probed with
a conceptual question.

fMRI data acquisition

FMRI scanning was performed in a 3 Tesla Philips Achieva MRI scanner with a 32-channel SENSE head coil at the Birmingham University Imaging Centre (BUIC, now the Centre for Human Brain Health, CHBH). Slices covered the whole head. T1-weighted anatomical scans were collected with an MP-RAGE sequence (1 mm isotropic voxels, 256 x 256 matrix, 176 slices, no inter-slice gap, repetition time (TR) = 7.5 ms, field of view (FOV) = 256 x 256 x 176 mm, flip angle (FA) = 7°, echo time (TE) = 3.5 ms). T2*-weighted functional images were acquired by a dual-echo EPI pulse sequence with a low specific absorption rate (SAR) to optimize the image quality in regions highly susceptible for distortions by a long readout gradient (3 x 3 x 3.5 mm, 64 x 64 matrix, 34 slices, no inter-slice gap, TR = 2.2 s, full head coverage, FOV = 192 x 192 x 119 mm, FA = 80°, TE1 = 12 ms, TE2 = 34 ms (for dual-echo information see also Halai et al., 2014, 2015; Kirilina et al., 2016). Slices were acquired in a continuous descending fashion. Furthermore, we collected 200 resting state volumes, 50 after each of the four task runs, used for the later combining of dual-echo images with the short and long TEs. During the acquisition of the functional scans, the helium pump was switched off to prevent contamination of the EEG by the compressor artifact at about 20-30 Hz. Stimulus timings were jittered in relation to the acquired scans. The task was presented to participants through a mirror system in the scanner and a JVC SX 21e projector with resolution 1280x1024 at 60 Hz (https://de.jvc.com/). Participants´ heads were extra padded to minimize movement artefacts. The stimulus presentation, and the collection of timing and accuracy information, was controlled by scripts written in Matlab 2016a (www.mathworks.com) and Psychophysics Toolbox Version 3 (Brainard, 1997; Kleiner et al., 2007; Pelli, 1997). Responses were logged by NATA response boxes (https://natatech.com/).

Out-of-scanner EEG data acquisition

As previously stated, a simultaneous EEG dataset was acquired during the fMRI session, but this EEG dataset was too noisy to decode retrieval-related information. We therefore decided to instead use an out-of-scanner EEG dataset for data fusion. This out-of-scanner data, used for all analyses reported here, originated from a previous publication (Linde-Domingo et al., 2019). We give a short description of the

EEG data acquisition in the following and of the EEG preprocessing further below.
More details can be found in the original publication.

For EEG data collection, 128 electrodes of silver metal and silver chloride were used.
Further, an Active-Two amplifier system and the ActiView acquisition software aided
data recording (BioSemi, Amsterdam, the Netherlands). Psychophysics Toolbox
Version 3 and MATLAB 2014b (www.mathworks.com) were used for task presentation
and response collection (Linde-Domingo et al., 2019).

801 Analyses

802 Behaviour

Behavioural data was analysed by MATLAB R2017b (www.mathworks.com). For the
inspection of RTs and accuracies, the behavioural data were preprocessed as follows.
For the RT analysis, all trials with incorrect responses to the catch question were
removed first. Additionally, catch question RTs of correct trials were removed if they
were faster than 200 ms or exceeding the average RT of a participant in a given set
of repetitions (first or second cycle) by more than three times the standard deviation
(Lifanov et al., 2021; Linde-Domingo et al., 2019). For the analysis of the accuracy
data, trials faster than 200 ms and objects with a missing response for either of the
two questions were excluded in the corresponding cycle (Lifanov et al., 2021). The
same procedures were applied to the data of the out-of-scanner EEG participants,
who performed a nearly identical task. However, note that out-of-scanner EEG
participants only went through one cycle of retrieval.

816 FMRI data preprocessing

We used MATLAB R2017b (www.mathworks.com) and SPM 12 (*Statistical Parametric*
Mapping, 2007; http://store.elsevier.com/product.jsp?isbn=9780123725608) for the
preprocessing and the analysis of fMRI data. All functional images were first realigned
based on three motion and three rotation parameters, unwarped, and slice time
corrected to the middle slice in time.

After these initial preprocessing steps, images obtained during the task at two echo
times were combined as a weighted average (Poser et al., 2006). Importantly, the
relative weights were obtained from the SNR of 200 resting state volumes per echo
and its corresponding *TE*

$$w(CNR)_n = \frac{SNR_n{}^*TE_n}{\sum_n SNR_n{}^*TE_n}$$ (1) (equation from Poser et al., 2006)

where *w* is the weight for an individual voxel, SNR_n is the signal to noise ratio here
calculated as ratio of mean to standard deviation of the given voxel calculated over
time at the *n*th echo, and *TE* is the readout time of the *n*th echo.

Weights obtained from the resting state were then used to combine task volumes from
both echoes.

$$S = w_1{}^*S_1 + w_2{}^*S_2$$ (2) (as described by Poser et al., 2006)

where S is the final signal of an individual voxel over time, calculated by summing the
weighted signals of both echoes. These methods and equations were applied as
described in work on BOLD contrast optimization by multi-echo sequences (Poser et
al., 2006). Combined image structures were written to NIFTI files by Tools for NIfTI
and ANALYZE image (https://www.mathworks.com/matlabcentral/fileexchange/8797-
tools-for-nifti-and-analyze-image retrieved December 8, 2017, by Shen, 2021).

Anatomical images were segmented, co-registered with the functional images and
normalized into a standard MNI template in SPM. Then, after the combination of
functional images, the T2* images were also normalized into MNI space, using the T1-
based normalization parameters. Finally, EPI images were smoothed for the univariate
GLM analysis with a gaussian spatial filter of 8 mm full width at half maximum (FWHM).
Note that multivariate analyses were performed on unsmoothed data in native space
(Weaverdyck et al., 2020).

ROIs
ROIs were created from templates in MNI space as available in the WFU PickAtlas
(Lancaster et al., 1997, 2000; Maldjian et al., 2003, 2004; Tzourio-Mazoyer et al.,
2002). These ROIs were then fitted to individual brains by applying the reversed T1-

based normalization parameters (see previous section) to the ROI masks (as in Chang
& Glover, 2010). The anatomical masks used for our analyses included: an early visual
mask, consisting of Brodmann areas (BAs, Brodmann, 1909, as from the Talairach
Daemon database atlases Lancaster et al., 1997, 2000) 17 and 18; a human inferior
temporal (hIT) mask, consisting of BAs 19 and 37; a temporal pole mask, consisting
of superior and middle temporal pole regions as defined by automated anatomical
labelling (AAL, Tzourio-Mazoyer et al., 2002); an MTL mask, consisting of BAs 28, 34,
35, 36 and AAL rhinal sulcus and parahippocampal gyrus; a superior parietal lobe
mask, consisting of BA 7; a lateral inferior parietal lobe mask, consisting of BA 39 and
40; and a medial parietal lobe mask, consisting of BA 29 and 30.

EEG data preprocessing

EEG data (from Linde-Domingo et al., 2019, also available on
https://doi.org/10.17605/OSF.IO/327EK) were preprocessed in MATLAB
(www.mathworks.com) and the Fieldtrip toolbox (Oostenveld et al., 2010; Donders
Institute for Brain, Cognition and Behaviour, Radboud University Nijmegen, the
Netherlands. See http://www.ru.nl/neuroimaging/fieldtrip). During epoching, different
temporal references were used for encoding and retrieval. Encoding epochs were
stimulus locked to the onset of the object image, while retrieval timelines were locked
to the subjective retrieval button press, in order to observe the reactivation stream
leading up to the subjective experience of recollection. These epochs were created
with a length of 2 s (-500 before to 1500 ms after object onset) for encoding and 4.5 s
(-4 s before to 500 ms after retrieval button press) for retrieval. Line noise was removed
by a FIR filter with a band-stop between 48 and 52 Hz. A high-pass filter with a cut-off
frequency of 0.1 Hz was applied to remove slow temporal drifts, and a low-pass filter
with a cut-off frequency of 100 Hz to remove high-frequency noise. Individual
artifactual trials and bad electrodes were rejected manually. Remaining artifacts were
removed by independent component analysis (ICA), after which any excluded
electrodes were re-introduced by interpolation. The referencing of the data was set to
the average across all scalp channels.

After this step, we implemented additional preprocessing steps using MATLAB
R2017b (www.mathworks.com) and the Fieldtrip toolbox the Fieldtrip toolbox

(Oostenveld et al., 2010; Donders Institute for Brain, Cognition and Behaviour,
Radboud University Nijmegen, the Netherlands. See
http://www.ru.nl/neuroimaging/fieldtrip, version from 16th November, 2017) to prepare
data for the specific fusion analyses of this paper. The encoding data was baseline
corrected by subtracting the average signal in the pre-stimulus period (-0.2 to -0.1 s)
for all post-stimulus time points, separately per electrode. The retrieval data was
baseline corrected by whole trial demeaning, since retrieval trials had no obvious,
uncontaminated baseline period. The EEG time series data was then downsampled
to 128 Hz and temporally smoothed with a moving average with a time window of 40
ms.

fMRI multivariate analyses

As preparation for the multivariate analyses, we performed a GLM, modelling
individual object-specific regressors for encoding, and for each of the two retrieval
repetitions separately, adding regressors of no interest for the presentation of verbs,
button presses, and catch question onsets, as well as nuisance regressors for head
motion, scanner drift and run means (one regressor per variable containing all onsets,
see also (Griffiths et al., 2019). We used stick functions locked to the object onset to
model the onset of encoding trials and boxcar functions with a duration of 2.5 s locked
to the cue onset to model the onset of retrieval trials. The resulting beta weights were
transformed into t-values for all subsequent multivariate analyses (Misaki et al., 2010).

fMRI searchlight LDA
To investigate where in the brain activity patterns differentiated between the two
perceptual and the two conceptual categories, we performed a volumetric LDA
searchlight analysis on the non-normalized and unsmoothed fMRI data of each
participant individually using the searchlight function of the RSA toolbox (Kriegeskorte,
2009; Kriegeskorte et al., 2006, 2008; Kriegeskorte & Kievit, 2013; Nili et al., 2014;
https://www.mrc-cbu.cam.ac.uk/methods-and-resources/toolboxes/). The LDA was
calculated using the MVPA-Light toolbox (Treder, 2020;
https://github.com/treder/MVPA-Light). This was done at each centre voxel of a
sphere, where object-specific t-values of the voxels within a 3D searchlight radius of

12 mm were used as feature vectors. Using these feature vectors, we classified
perceptual (photo vs drawing) and conceptual (animate vs inanimate) categories by a
5-fold LDA with 5 repetitions, preserving class proportions, separately for encoding
and retrieval using all trials. Individual accuracy maps were normalized to MNI space
and spatially smoothed with a 10 mm FWHM Gaussian kernel, before second-level t-
tests were performed to statistically compare voxel-specific classification accuracies
against 50% chance performance. Finally, the results were plotted on an MNI surface
template brain.

fMRI correlation-based RSA
As preparation for the fusion of EEG and fMRI data, we performed a representational
similarity analysis (RSA, Kriegeskorte, 2009; Kriegeskorte et al., 2006, 2008;
Kriegeskorte & Kievit, 2013; Nili et al., 2014; https://www.mrc-cbu.cam.ac.uk/methods-
and-resources/toolboxes/) on the non-normalized and unsmoothed fMRI data. FMRI-
based t-maps corresponding to unique objects were arranged in the same order for all
participants. As mentioned earlier, object correspondence across participants was
only given on the level of object identity (and thus also conceptual category), but not
perceptual format. In other words, all participants saw an image of a camel (i.e., an
animate object) at some point in the experiment, but the camel could be presented as
a photograph to some participants, and as a line drawing to others. For each voxel
and its surrounding neighbours within a radius of 12 mm, we extracted object-specific
t-value patterns resulting from the appropriate GLM and arranged these as one-
dimensional feature vectors. Using these feature vectors, we calculated the Pearson
correlation distance (1-r) between each pair of objects at each voxel location,
separately for encoding and retrieval. The resulting RDM maps were saved and used
at a later stage for the searchlight fusion with the EEG data.

In a similar fashion to the searchlight approach, RDMs were also calculated for the
pre-defined set of anatomical regions of interest in the non-normalized and
unsmoothed individual functional datasets (see section ROIs). The resulting ROI
RDMs were used at a later stage for the ROI fusion.

EEG multivariate analyses

EEG cross-subjects classifier-based RSA

Our next step was to construct a representational dissimilarity matrix (RDM) for each time point of the EEG recordings, resulting in one timeline representing the similarity structure of our object dataset across all subjects. Cells of the RDM represented the pair-wise discriminability of object pairs, based on a cross-subjects classification of object identity using the MVPA-Light toolbox (Treder, 2020; https://github.com/treder/MVPA-Light). To compute this matrix, we arranged object-specific trials in the same order between all participants, independent of their perceptual format, and the 24 repetitions of each individual object across participants were used for the pairwise classification. Specifically, we performed a time resolved LDA using as feature vectors the EEG amplitude values from the 128 electrodes, at a given time bin, and participants as repetitions of the same object. To tackle problems of overfitting we used automatic shrinkage regularization as implemented in the MVPA-Light toolbox (Treder, 2020). We used the LDA to classify object identity among each pair of objects at each time bin, again with a 5-fold cross validation, preserving class proportions. The resulting discrimination accuracies were entered in a single time resolved RDM structure representing the dissimilarity between individual objects of our stimulus pool across participants over time. This classification procedure was performed independently for encoding and retrieval.

Before using the EEG-based RDMs for our data fusion, we also wanted to assess statistically how much information about object identity can be decoded from the EEG signals themselves (see Supplements). We therefore first calculated the average classification performance across all pairwise accuracies as a descriptive measure. We then tested if the pairwise accuracies resulting from the 'real' classification with correct object labels were significantly larger than the pairwise accuracies that resulted from a classification with permuted object labels. This test was performed in two steps. First, we created 25 classification-based RDMs (same classification procedure as for the 'real' RDM time course) but each one with randomly permuted object labels, keeping a given label permutation consistent across time in order to preserve the autocorrelation of the EEG time series. The 25 permutations were averaged to form a single 'baseline' RDM time course.

As a second step, we used a cluster-based permutation test to find clusters with
temporally extended above-chance decoding accuracy. This cluster-based
permutation test compared the t-statistic of each time point resulting from a 'real
matrix' versus 'baseline matrix' t-test, with the t-statistics computed from a 'real matrix'
versus 'baseline matrix' comparison, this time shuffling the 'real' and 'baseline' cells
between the two matrices (again keeping a consistent shuffling across time, 1000
permutations, cluster-definition threshold of p < .05, as used in previous publications
(Cichy et al., 2019; Cichy & Pantazis, 2017; Dobs et al., 2019). Note that the variance
in the t-tests for each time bin comes from the pair-wise accuracies contained in the
cells of the two ('real' and 'baseline') classification matrices. All remaining analyses
were performed using the ('real') classification matrix with the correct object labels.

Next, we tested whether object discriminability systematically differs between objects
coming from the same or different conceptual classes (i.e. animate and inanimate
objects) within the classification with correct labels. We thus calculated the average
accuracies of pairwise classes within and between conceptual categories as a
descriptive measure. Using another cluster-based permutation test (1000
permutations, cluster-definition threshold of p < .05), we statistically tested for
differences of within- against between-category accuracies over time. This analysis
was conducted for conceptual classes only, since there was no correspondence of
perceptual class between subjects. The retrieval analyses focused on the time period
from -3 s to -1 s before retrieval button press. We based this time window of interest
on previous findings (Linde-Domingo et al., 2019) which indicated perceptual and
conceptual decoding peaks prior to -1 s before button press. All cluster permutation
tests were implemented by means of the permutest toolbox
(https://www.mathworks.com/matlabcentral/fileexchange/71737-permutest retrieved
February 16, 2021, by Gerber, 2021; also see Maris & Oostenveld, 2007).

1006

1007 ## EEG-fMRI data fusion

1008 ### ROI fusion

1009 Two distinct approaches were used for the fusion analyses, with either the fMRI data
1010 or the EEG data serving as starting point. The first approach used the fMRI patterns

from a given ROI as a starting point, and we thus refer to it as ROI fusion. One RDM was created per participant per ROI, representing the similarity structure (i.e., RDM) in a given anatomical brain region. This ROI RDM was then correlated with the RDM from each time bin of the single, EEG-based RDM time course that represents the pooled similarity structure across subjects (see cross-subject classification of described above and in supplements). Correlations and classification accuracies were Fisher's z-transformed before the data fusion (as in Griffiths et al., 2019). This analysis resulted in one correlation time course per individual ROI per subject who took part in the fMRI experiment (n = 31). The EEG-fMRI correlations were only computed for those cells of the matrix that an individual participant from the fMRI study remembered correctly. To test for statistical significance, we then contrasted the 31 correlation time courses against zero, using a cluster-based permutation test with 1000 permutations and a cluster-definition threshold of p < .05, correcting for multiple comparisons in time as in previous studies (Cichy et al., 2019; Cichy & Pantazis, 2017; Dobs et al., 2019).

To test for a sequential information progression over the ventral visual stream regions, we implemented a linear regression on the cumulative sums of the ROI time courses (based on Michelmann et al., 2019). To do so, we first calculated the cumulative sum of the ROI time courses over the time period from 0 to 1.5 s after image onset for encoding, and from -3 to -1 s before button press for retrieval. For an easier comparison, the cumulative sum of each ROI time course was normalized to an area under the curve that equals 1. For each time point, a linear regression was fitted across the cumulative correlation values of the ROIs within subjects. The resulting slopes of all subjects were then tested against zero in a one-sided cluster-based permutation test (with 1000 permutations and a cluster-definition threshold of p < .05). This method enabled us to test for a forward stream during encoding and a backward stream during retrieval (Fig. 4e-f). An example of the rationale is illustrated in figure 4. In the case of a forward stream, the ROIs along the ventral visual stream activate sequentially from early towards late regions. Therefore, earlier regions (e.g. V1-hIT) show a higher cumulative sum than later regions (e.g. temporal pole - MTL) at 0.5 s after stimulus onset (and other time points). A linear fit across ROIs at 0.5 s will therefore show a significant negative slope. According to this rationale, a backward stream across the same regions would result in a significant positive slope. Since we expected a forward stream at encoding and a backward stream at retrieval, we used one-sided tests to

1044 confirm if the slope differs from zero (< 0 at encoding, > 0 at retrieval). The sequential
1045 ordering of our ROIs was based on the extensive literature describing the hierarchical
1046 organisation of the ventral visual stream in anatomical and functional neuroimaging
1047 studies (e.g. Cichy et al., 2016, 2017; Felleman & Essen, 1991).

1048

Searchlight fusion
The second, complementary fusion approach offers higher spatial resolution and a
whole-brain perspective on how encoding and retrieval patterns emerge over time.
Here, we used the EEG-based RDMs from each time point as starting point, and then
searched for matching similarity structures across the entire brain, using a volumetric
searchlight analysis on each individual's fMRI data (Kriegeskorte, 2009; Kriegeskorte
et al., 2006, 2008; Kriegeskorte & Kievit, 2013; Nili et al., 2014). We refer to this
method as a (time-resolved) searchlight fusion. A second-order correlation was
computed between the (classification-based) EEG RDM from each time bin and the
(correlation-based) fMRI RDMs for each centre voxel and its neighbours within a
searchlight radius of 3 voxels, separately for encoding and retrieval. This analysis
results in a "fusion movie" (i.e., a time-resolved brain map) for each participant who
took part in the fMRI experiment. The searchlight fusion for retrieval data was
performed for correct trials within the fMRI data only (same as above). The fused data
was Fisher's z-transformed. The searchlight fusion was performed using the
rsatoolbox   (https://rsatoolbox.readthedocs.io/en/latest/,
https://github.com/rsagroup/rsatoolbox) which works on Python (van Rossum, 1995),
using the sys and os module, SciPy (Virtanen et al., 2020), NumPy (Harris et al., 2020),
and nibabel (https://github.com/nipy/nibabel/releases).

To test for significant EEG-fMRI pattern similarity at individual voxels, we normalized
the correlation maps to MNI space, smoothed them with a 10 mm FWHM Gaussian
kernel and then tested them in a one-sample t-test against zero at each single time
bin. The t-test included a spatial maximal permuted statistic correction combined with
a threshold free cluster enhancement (Nichols & Holmes, 2002; Smith & Nichols,
2009). This cluster-based analysis was performed using the toolbox MatlabTFCE
(http://markallenthornton.com/blog/matlab-tfce/) with 1000 permutations, a height
exponent of 2, an extent exponent of 0.5, a connectivity parameter of 26 and a step

number for cluster formation of .1 as suggested by Smith & Nichols (2009). The

analysis resulted in time-resolved spatial t-maps, depicting clusters of significant EEG-

fMRI correlations, created by Tools for NIfTI and ANALYZE image

([https://www.mathworks.com/matlabcentral/fileexchange/8797-tools-for-nifti-and-](https://www.mathworks.com/matlabcentral/fileexchange/8797-tools-for-nifti-and-analyze-image)

[analyze-image](https://www.mathworks.com/matlabcentral/fileexchange/8797-tools-for-nifti-and-analyze-image) retrieved December 8, 2017, by Shen, 2021).

 Figures

Figures were created using the RainCloud plots Version 1.1 (https://github.com/RainCloudPlots/RainCloudPlots, M. Allen et al., 2019; Whitaker et al., 2019), Inkscape 1.0.1 (https://inkscape.org/), WFU PickAtlas v3.0 (Maldjian et al., 2003, 2004), MRIcron (https://www.nitrc.org/projects/mricron, www.mricro.com, Rorden & Brett, 2000) and a colin 27 average brain template (http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27, Holmes et al., 1998).

Analyses that did not work

1) Data fusion with the in-scanner EEG

The initial plan for this project was to fuse the fMRI data with the EEG data acquired during scanning. Using the simultaneous EEG data for fusion, the spatio-temporal mapping could then have been performed on a trial-by-trial basis within participants. However, neither a time-resolved RSA nor a perceptual or conceptual LDA classification on the EEG data showed interpretable results, likely due to extensive noise in the in-scanner EEG data.

2) Data fusion with correlation-based EEG RDMs

Having decided to use the out-of-scanner EEG dataset for the data fusion, we first attempted to perform the fMRI-EEG fusion using correlation-based RDMs calculated from the EEG data (see Cichy & Oliva, 2020). To compute these RDMs, we arranged object-specific trials in the same order between all participants, independent of their perceptual format, identical to the arrangement in the fMRI data. We then performed a time-resolved RSA using EEG amplitude values from the 128 electrodes, at a given time bin, as feature vectors. Specifically, we calculated the pairwise distance (1-Pearson correlation (r)) between each pair of objects. However, inspecting the average overall similarity and contrasting the average similarity within versus between conceptual classes did not show interpretable results. This is most likely due to too unreliable and time-varying single-trial estimates from the EEG data. Following this initial analysis, we thus used the cross-subject, classification-based RDMs that produced more stable results on the EEG data itself.

Code availability

The custom code used in this study is available on the Open Science Framework with the identifier https://doi.org/10.17605/OSF.IO/2T7SN.

Acknowledgements

We thank, Simrandeep Cheema, Dagmar Fraser, and Nina Salman for help with the data collection. Further we thank Karen Mullinger for useful analytical advice. This work was supported by a European Research Council (ERC) Starting Grant StG-2016-715714 awarded to Maria Wimber, and a scholarship from the Midlands Integrative Biosciences Training Partnership (MIBTP) awarded to Juan Linde-Domingo.

Author contributions

J.L., J.L.D. and M. Wimber designed the experiments. J.L. and J.L.D. conducted the experiments. B.G. and C.F. helped with the EEG-fMRI acquisition. J.L. and J.L.D preprocessed the data. J.L. analysed the data. All authors contributed to the analyses. J.L. wrote the first version of the manuscript under the supervision of M. Wimber. All authors contributed to reviewing and editing.

Competing interests

The authors declare no competing interests.

References

Allen, E. J., St-Yves, G., Wu, Y., Breedlove, J. L., Prince, J. S., Dowdle, L. T., Nau, M.,
Caron, B., Pestilli, F., Charest, I., Hutchinson, J. B., Naselaris, T., & Kay, K. (2022).
A massive 7T fMRI dataset to bridge cognitive neuroscience and artificial
intelligence. *Nature Neuroscience*, *25*(1), 1. https://doi.org/10.1038/s41593-021-
00962-x

Allen, M., Poggiali, D., Whitaker, K., Marshall, T. R., & Kievit, R. A. (2019). Raincloud
plots: A multi-platform tool for robust data visualization. *Wellcome Open Research*,
4, 63. https://doi.org/10.12688/wellcomeopenres.15191.1

Baddeley, A. (1998). Recent developments in working memory. *Current Opinion in
Neurobiology*, *8*(2), 234–238. https://doi.org/10.1016/S0959-4388(98)80145-1

Barry, D. N., & Maguire, E. A. (2019). Remote Memory and the Hippocampus: A
Constructive Critique. *Trends in Cognitive Sciences*, *23*(2), 128–142.
https://doi.org/10.1016/j.tics.2018.11.005

Bone, M. B., Ahmad, F., & Buchsbaum, B. R. (2020). Feature-specific neural reactivation
during episodic memory. *Nature Communications, 11*(1).
https://doi.org/10.1038/s41467-020-15763-2

Bosch, S. E., Jehee, J. F. M., Fernández, G., & Doeller, C. F. (2014). Reinstatement of
Associative Memories in Early Visual Cortex Is Signaled by the Hippocampus.
Journal of Neuroscience, *34*(22), 7493–7500.
https://doi.org/10.1523/JNEUROSCI.0805-14.2014

Brainard, D. H. (1997). The Psychophysics Toolbox. *Spatial Vision*, *10*(4), 433–436.
https://doi.org/10.1163/156856897X00357

Brodeur, M. B., Dionne-Dostie, E., Montreuil, T., & Lepage, M. (2010). The Bank of
Standardized Stimuli (BOSS), a New Set of 480 Normative Photos of Objects to Be

Used as Visual Stimuli in Cognitive Research. *PLOS ONE*, *5*(5), e10773.

https://doi.org/10.1371/journal.pone.0010773

Brodmann, K. (1909). *Vergleichende Lokalisationslehre der Grosshirnrinde in ihren Prinzipien dargestellt auf Grund des Zellenbaues von Dr. K. Brodmann* ... J.A. Barth.

Carlson, T. A., Ritchie, J. B., Kriegeskorte, N., Durvasula, S., & Ma, J. (2013). Reaction Time for Object Categorization Is Predicted by Representational Distance. *Journal of Cognitive Neuroscience*, *26*(1), 132–142. https://doi.org/10.1162/jocn_a_00476

Carlson, T., Tovar, D. A., Alink, A., & Kriegeskorte, N. (2013). Representational dynamics of object vision: The first 1000 ms. *Journal of Vision*, *13*(10), 1–1. https://doi.org/10.1167/13.10.1

Chang, C., & Glover, G. H. (2010). Time–frequency dynamics of resting-state brain connectivity measured with fMRI. *NeuroImage*, *50*(1), 81–98. https://doi.org/10.1016/j.neuroimage.2009.12.011

Chrastil, E. R. (2018). Heterogeneity in human retrosplenial cortex: A review of function and connectivity. *Behavioral Neuroscience*, *132*(5), 317–338. https://doi.org/10.1037/bne0000261

Christophel, T. B., Hebart, M. N., & Haynes, J.-D. (2012). Decoding the Contents of Visual Short-Term Memory from Human Visual and Parietal Cortex. *Journal of Neuroscience*, *32*(38), 12983–12989. https://doi.org/10.1523/JNEUROSCI.0184-12.2012

Christophel, T. B., Klink, P. C., Spitzer, B., Roelfsema, P. R., & Haynes, J.-D. (2017). The Distributed Nature of Working Memory. *Trends in Cognitive Sciences*, *21*(2), 111–124. https://doi.org/10.1016/j.tics.2016.12.007

Chrobak, J. J., Lörincz, A., & Buzsáki, G. (2000). Physiological patterns in the hippocampo-

entorhinal cortex system. *Hippocampus*, *10*(4), 457–465.

https://doi.org/10.1002/1098-1063(2000)10:4<457::AID-HIPO12>3.0.CO;2-Z

Cichy, R. M., Kriegeskorte, N., Jozwik, K. M., Bosch, J. J. F. van den, & Charest, I. (2017).

Neural dynamics of real-world object vision that guide behaviour. *BioRxiv*, 147298.

https://doi.org/10.1101/147298

Cichy, R. M., Kriegeskorte, N., Jozwik, K. M., van den Bosch, J. J. F., & Charest, I. (2019).

The spatiotemporal neural dynamics underlying perceived similarity for real-world

objects. *NeuroImage, 194*, 12–24. https://doi.org/10.1016/j.neuroimage.2019.03.031

Cichy, R. M., & Oliva, A. (2020). A M/EEG-fMRI Fusion Primer: Resolving Human Brain

Responses in Space and Time. *Neuron*, *107*(5), 772–781.

https://doi.org/10.1016/j.neuron.2020.07.001

Cichy, R. M., & Pantazis, D. (2017). Multivariate pattern analysis of MEG and EEG: A

comparison of representational structure in time and space. *NeuroImage*, *158*, 441–

454. https://doi.org/10.1016/j.neuroimage.2017.07.023

Cichy, R. M., Pantazis, D., & Oliva, A. (2014). Resolving human object recognition in space

and time. *Nature Neuroscience, 17*(3), 455–462. https://doi.org/10.1038/nn.3635

Cichy, R. M., Pantazis, D., & Oliva, A. (2016). Similarity-Based Fusion of MEG and fMRI

Reveals Spatio-Temporal Dynamics in Human Cortex During Visual Object

Recognition. *Cerebral Cortex*, *26*(8), 3563–3579.

https://doi.org/10.1093/cercor/bhw135

Clarke, A. (2020). Dynamic activity patterns in the anterior temporal lobe represents object

semantics. *Cognitive Neuroscience, 11*(3), 111–121.

https://doi.org/10.1080/17588928.2020.1742678

Clarke, A., & Tyler, L. K. (2015). Understanding What We See: How We Derive Meaning

From Vision. *Trends in Cognitive Sciences*, *19*(11), 677–687.

https://doi.org/10.1016/j.tics.2015.08.008

Dalton, M. A., D'Souza, A., Lv, J., & Calamante, F. (2022). New insights into anatomical

connectivity along the anterior–posterior axis of the human hippocampus using in

vivo quantitative fibre tracking. *ELife, 11*, e76143.

https://doi.org/10.7554/eLife.76143

Danker, J. F., & Anderson, J. R. (2010). The ghosts of brain states past: Remembering

reactivates the brain regions engaged during encoding. *Psychological Bulletin, 136*(1),

87–102. https://doi.org/10.1037/a0017937

Danker, J. F., Tompary, A., & Davachi, L. (2017). Trial-by-Trial Hippocampal Encoding

Activation Predicts the Fidelity of Cortical Reinstatement During Subsequent

Retrieval. *Cerebral Cortex, 27*(7), 3515–3524. https://doi.org/10.1093/cercor/bhw146

Dijkstra, N., Gaal, S. van, Geerligs, L., Bosch, S., & Gerven, M. van. (2021). *No overlap*

between unconscious and imagined representations. PsyArXiv.

https://doi.org/10.31234/osf.io/ctdmk

Dobs, K., Isik, L., Pantazis, D., & Kanwisher, N. (2019). How face perception unfolds over

time. *Nature Communications, 10*(1), 1258. https://doi.org/10.1038/s41467-019-

09239-1

Eichenbaum, H. (2001). The hippocampus and declarative memory: Cognitive mechanisms

and neural codes. *Behavioural Brain Research, 127*(1), 199–207.

https://doi.org/10.1016/S0166-4328(01)00365-5

Favila, S. E., Lee, H., & Kuhl, B. A. (2020). Transforming the Concept of Memory

Reactivation. *Trends in Neurosciences, 43*(12), 939–950.

https://doi.org/10.1016/j.tins.2020.09.006

Favila, S. E., Samide, R., Sweigart, S. C., & Kuhl, B. A. (2018). Parietal Representations of

Stimulus Features Are Amplified during Memory Retrieval and Flexibly Aligned with

Top-Down Goals. *Journal of Neuroscience*, *38*(36), 7809–7821.

https://doi.org/10.1523/JNEUROSCI.0564-18.2018

Felleman, D. J., & Essen, D. C. V. (1991). Distributed hierarchical processing in the primate

cerebral cortex. *Cereb Cortex*, 1–47.

Ferreira, C. S., Charest, I., & Wimber, M. (2019). Retrieval aids the creation of a generalised

memory trace and strengthens episode-unique information. *NeuroImage*, *201*, 115996.

https://doi.org/10.1016/j.neuroimage.2019.07.009

Fletcher, P. C., Frith, C. D., Baker, S. C., Shallice, T., Frackowiak, R. S. J., & Dolan, R. J.

(1995). The Mind's Eye—Precuneus Activation in Memory-Related Imagery.

NeuroImage, *2*(3), 195–200. https://doi.org/10.1006/nimg.1995.1025

Friston, K. J., Jezzard, P., & Turner, R. (1994). Analysis of functional MRI time-series.

Human Brain Mapping, *1*(2), 153–171. https://doi.org/10.1002/hbm.460010207

Ganis, G., Thompson, W. L., & Kosslyn, S. M. (2004). Brain areas underlying visual mental

imagery and visual perception: An fMRI study. *Cognitive Brain Research*, *20*(2),

226–241. https://doi.org/10.1016/j.cogbrainres.2004.02.012

Griffiths, B. J., Mayhew, S. D., Mullinger, K. J., Jorge, J., Charest, I., Wimber, M., &

Hanslmayr, S. (2019). Alpha/beta power decreases track the fidelity of stimulus-

specific information. *ELife*, *8*, 49562. https://doi.org/10.7554/eLife.49562

Halai, A. D., Parkes, L. M., & Welbourne, S. R. (2015). Dual-echo fMRI can detect

activations in inferior temporal lobe during intelligible speech comprehension.

NeuroImage, *122*, 214–221. https://doi.org/10.1016/j.neuroimage.2015.05.067

Halai, A. D., Welbourne, S. R., Embleton, K., & Parkes, L. M. (2014). A comparison of dual

gradient-echo and spin-echo fMRI of the inferior temporal lobe. *Human Brain*

Mapping, *35*(8), 4118–4128. https://doi.org/10.1002/hbm.22463

Harris, C. R., Millman, K. J., van der Walt, S. J., Gommers, R., Virtanen, P., Cournapeau, D.,

Wieser, E., Taylor, J., Berg, S., Smith, N. J., Kern, R., Picus, M., Hoyer, S., van

Kerkwijk, M. H., Brett, M., Haldane, A., del Río, J. F., Wiebe, M., Peterson, P., …

Oliphant, T. E. (2020). Array programming with NumPy. *Nature*, *585*(7825), 7825.

https://doi.org/10.1038/s41586-020-2649-2

Heusser, A. C., Fitzpatrick, P. C., & Manning, J. R. (2021). Geometric models reveal

behavioural and neural signatures of transforming experiences into memories. *Nature*

Human Behaviour, *5*(7), 7. https://doi.org/10.1038/s41562-021-01051-6

Holmes, C. J., Hoge, R., Collins, L., Woods, R., Toga, A. W., & Evans, A. C. (1998).

Enhancement of MR Images Using Registration for Signal Averaging. *Journal of*

Computer Assisted Tomography, *22*(2), 324–333.

Horner, A. J., Bisby, J. A., Bush, D., Lin, W.-J., & Burgess, N. (2015). Evidence for holistic

episodic recollection via hippocampal pattern completion. *Nature Communications*, *6*,

7462. https://doi.org/10.1038/ncomms8462

Huijbers, W., Pennartz, C. M. A., Rubin, D. C., & Daselaar, S. M. (2011). Imagery and

retrieval of auditory and visual information: Neural correlates of successful and

unsuccessful performance. *Neuropsychologia*, *49*(7), 1730–1740.

https://doi.org/10.1016/j.neuropsychologia.2011.02.051

Humphreys, G. F., Lambon Ralph, M. A., & Simons, J. S. (2021). A Unifying Account of

Angular Gyrus Contributions to Episodic and Semantic Cognition. *Trends in*

Neurosciences, *44*(6), 452–463. https://doi.org/10.1016/j.tins.2021.01.006

Insausti, R., & Muñoz, M. (2001). Cortical projections of the non-entorhinal hippocampal formation in the cynomolgus monkey (Macaca fascicularis). *European Journal of Neuroscience*, *14*(3), 435–451. https://doi.org/10.1046/j.0953-816x.2001.01662.x

Jeong, S. K., & Xu, Y. (2016). Behaviorally Relevant Abstract Object Identity Representation in the Human Parietal Cortex. *Journal of Neuroscience*, *36*(5), 1607–1619. https://doi.org/10.1523/JNEUROSCI.1016-15.2016

Jiang, J., Wang, S.-F., Guo, W., Fernandez, C., & Wagner, A. D. (2020). Prefrontal reinstatement of contextual task demand is predicted by separable hippocampal patterns. *Nature Communications*, *11*(1), 1. https://doi.org/10.1038/s41467-020-15928-z

Jonker, T. R., Dimsdale-Zucker, H., Ritchey, M., Clarke, A., & Ranganath, C. (2018). Neural reactivation in parietal cortex enhances memory for episodically linked information. *Proceedings of the National Academy of Sciences*, *115*(43), 11084–11089. https://doi.org/10.1073/pnas.1800006115

Kaiser, D., Jacobs, A. M., & Cichy, R. M. (2022). Modelling brain representations of abstract concepts. *PLoS Computational Biology*, *18*(2), e1009837. https://doi.org/10.1371/journal.pcbi.1009837

Kirilina, E., Lutti, A., Poser, B. A., Blankenburg, F., & Weiskopf, N. (2016). The quest for the best: The impact of different EPI sequences on the sensitivity of random effect fMRI group analyses. *NeuroImage*, *126*, 49–59. https://doi.org/10.1016/j.neuroimage.2015.10.071

Kleiner, M., Brainard, D., Pelli, D., Ingling, A., Murray, R., & Broussard, C. (2007). What's new in psychtoolbox-3. *Perception*, *36*(14), 1–16.

Kolb, H., Fernandez, E., & Nelson, R. (Eds.). (1995). *Webvision: The Organization of the*

Retina and Visual System. University of Utah Health Sciences Center.

http://www.ncbi.nlm.nih.gov/books/NBK11530/

Kosslyn, S. M., Alpert, N. M., Thompson, W. L., Maljkovic, V., Weise, S. B., Chabris, C. F.,

Hamilton, S. E., Rauch, S. L., & Buonanno, F. S. (1993). Visual Mental Imagery

Activates Topographically Organized Visual Cortex: PET Investigations. *Journal of*

Cognitive Neuroscience, *5*(3), 263–287. https://doi.org/10.1162/jocn.1993.5.3.263

Kravitz, D. J., Saleem, K. S., Baker, C. I., Ungerleider, L. G., & Mishkin, M. (2013). The

ventral visual pathway: An expanded neural framework for the processing of object

quality. *Trends in Cognitive Sciences*, *17*(1), 26–49.

https://doi.org/10.1016/j.tics.2012.10.011

Kriegeskorte, N. (2009). Relating population-code representations between man, monkey,

and computational models. *Frontiers in Neuroscience*, *3*.

https://doi.org/10.3389/neuro.01.035.2009

Kriegeskorte, N., Goebel, R., & Bandettini, P. (2006). Information-based functional brain

mapping. *Proceedings of the National Academy of Sciences*, *103*(10), 3863–3868.

https://doi.org/10.1073/pnas.0600244103

Kriegeskorte, N., & Kievit, R. A. (2013). Representational geometry: Integrating cognition,

computation, and the brain. *Trends in Cognitive Sciences*, *17*(8), 401–412.

https://doi.org/10.1016/j.tics.2013.06.007

Kriegeskorte, N., Mur, M., & Bandettini, P. A. (2008). Representational similarity analysis—

Connecting the branches of systems neuroscience. *Frontiers in Systems Neuroscience*,

2. https://doi.org/10.3389/neuro.06.004.2008

Kruggel, F., & von Cramon, D. y. (1999). Temporal properties of the hemodynamic response

in functional MRI. *Human Brain Mapping*, *8*(4), 259–271.

https://doi.org/10.1002/(SICI)1097-0193(1999)8:4<259::AID-HBM9>3.0.CO;2-K

Kuhl, B. A., & Chun, M. M. (2014). Successful Remembering Elicits Event-Specific Activity

Patterns in Lateral Parietal Cortex. *Journal of Neuroscience*, *34*(23), 8051–8060.

https://doi.org/10.1523/JNEUROSCI.4328-13.2014

Lancaster, J. L., Summerlin, J. L., Rainey, L., Freitas, C. S., & Fox, P. T. (1997). The

Talairach Daemon a database server for talairach atlas labels. *NeuroImage*, *5*(4 PART

II), S633.

Lancaster, J. L., Woldorff, M. G., Parsons, L. M., Liotti, M., Freitas, C. S., Rainey, L.,

Kochunov, P. V., Nickerson, D., Mikiten, S. A., & Fox, P. T. (2000). Automated

Talairach Atlas labels for functional brain mapping. *Human Brain Mapping*, *10*(3),

120–131. https://doi.org/10.1002/1097-0193(200007)10:3<120::AID-

HBM30>3.0.CO;2-8

Levy, D. A. (2012). Towards an understanding of parietal mnemonic processes: Some

conceptual guideposts. *Frontiers in Integrative Neuroscience, 0*.

https://doi.org/10.3389/fnint.2012.00041

Lifanov, J., Linde-Domingo, J., & Wimber, M. (2020). Feature-specific reaction times reveal

a semanticisation of memories over time and with repeated remembering. *BioRxiv*,

2020.09.11.292813. https://doi.org/10.1101/2020.09.11.292813

Lifanov, J., Linde-Domingo, J., & Wimber, M. (2021). Feature-specific reaction times reveal

a semanticisation of memories over time and with repeated remembering. *Nature*

Communications, *12*(1), 1. https://doi.org/10.1038/s41467-021-23288-5

Linde-Domingo, J., Treder, M. S., Kerrén, C., & Wimber, M. (2019). Evidence that neural

information flow is reversed between object perception and object reconstruction

from memory. *Nature Communications*, *10*(1), 1. https://doi.org/10.1038/s41467-018-

08080-2

Liu, J., Zhang, H., Yu, T., Ni, D., Ren, L., Yang, Q., Lu, B., Wang, D., Heinen, R.,

Axmacher, N., & Xue, G. (2020). Stable maintenance of multiple representational

formats in human visual short-term memory. *Proceedings of the National Academy of*

Sciences, *117*(51), 32329–32339. https://doi.org/10.1073/pnas.2006752117

Long, N. M., & Kuhl, B. A. (2021). Cortical Representations of Visual Stimuli Shift

Locations with Changes in Memory States. *Current Biology*, *31*(5), 1119-1126.e5.

https://doi.org/10.1016/j.cub.2021.01.004

Lundstrom, B. N., Ingvar, M., & Petersson, K. M. (2005). The role of precuneus and left

inferior frontal cortex during source memory episodic retrieval. *NeuroImage*, *27*(4),

824–834. https://doi.org/10.1016/j.neuroimage.2005.05.008

Maldjian, J. A., Laurienti, P. J., & Burdette, J. H. (2004). Precentral gyrus discrepancy in

electronic versions of the Talairach atlas. *NeuroImage*, *21*(1), 450–455.

https://doi.org/10.1016/j.neuroimage.2003.09.032

Maldjian, J. A., Laurienti, P. J., Kraft, R. A., & Burdette, J. H. (2003). An automated method

for neuroanatomic and cytoarchitectonic atlas-based interrogation of fMRI data sets.

NeuroImage, *19*(3), 1233–1239. https://doi.org/10.1016/S1053-8119(03)00169-1

Maris, E., & Oostenveld, R. (2007). Nonparametric statistical testing of EEG- and MEG-data.

Journal of Neuroscience Methods, *164*(1), 177–190.

https://doi.org/10.1016/j.jneumeth.2007.03.024

Marr, D. (1971). Simple Memory: A Theory for Archicortex. *Philosophical Transactions of*

the Royal Society of London. Series B, Biological Sciences, *262*(841), 23–81.

Martin, C. B., Douglas, D., Newsome, R. N., Man, L. L., & Barense, M. D. (2018).

Integrative and distinctive coding of visual and conceptual object features in the

ventral visual stream. *ELife*, *7*, e31873. https://doi.org/10.7554/eLife.31873

McClelland, J. L., McNaughton, B. L., & O'Reilly, R. C. (1995). Why there are

complementary learning systems in the hippocampus and neocortex: Insights from the

successes and failures of connectionist models of learning and memory.

Psychological Review, *102*(3), 419–457. https://doi.org/10.1037/0033-

295X.102.3.419

McClelland, J. L., & Rogers, T. T. (2003). The parallel distributed processing approach to

semantic cognition. *Nature Reviews. Neuroscience*, *4*(4), 310–322.

https://doi.org/10.1038/nrn1076

Michelmann, S., Staresina, B. P., Bowman, H., & Hanslmayr, S. (2019). Speed of time-

compressed forward replay flexibly changes in human episodic memory. *Nature*

Human Behaviour, *3*(2), 143–154. https://doi.org/10.1038/s41562-018-0491-4

Mirjalili, S., Powell, P., Strunk, J., James, T., & Duarte, A. (2021). Context Memory

Encoding and Retrieval Temporal Dynamics are Modulated by Attention across the

Adult Lifespan. *ENeuro*, *8*(1), ENEURO.0387-20.2020.

https://doi.org/10.1523/ENEURO.0387-20.2020

Misaki, M., Kim, Y., Bandettini, P. A., & Kriegeskorte, N. (2010). Comparison of

multivariate classifiers and response normalizations for pattern-information fMRI.

NeuroImage, *53*(1), 103–118. https://doi.org/10.1016/j.neuroimage.2010.05.051

Moscovitch, M. (2008). The hippocampus as a 'stupid,' domain-specific module:

Implications for theories of recent and remote memory, and of imagination. *Canadian*

Journal of Experimental Psychology/Revue Canadienne de Psychologie

Expérimentale, *62*(1), 62–79. https://doi.org/10.1037/1196-1961.62.1.62

Nichols, T. E., & Holmes, A. P. (2002). Nonparametric permutation tests for functional

neuroimaging: A primer with examples. *Human Brain Mapping*, *15*(1), 1–25.

https://doi.org/10.1002/hbm.1058

Nili, H., Wingfield, C., Walther, A., Su, L., Marslen-Wilson, W., & Kriegeskorte, N. (2014).

A Toolbox for Representational Similarity Analysis. *PLOS Computational Biology*,

10(4), e1003553. https://doi.org/10.1371/journal.pcbi.1003553

Noppeney, U., & Price, C. J. (2002). A PET study of stimulus- and task-induced semantic

processing. *NeuroImage*, *15*(4), 927–935. https://doi.org/10.1006/nimg.2001.1015

Oostenveld, R., Fries, P., Maris, E., & Schoffelen, J.-M. (2010). FieldTrip: Open Source

Software for Advanced Analysis of MEG, EEG, and Invasive Electrophysiological

Data. *Computational Intelligence and Neuroscience*, *2011*, e156869.

https://doi.org/10.1155/2011/156869

O'Reilly, R. C., & McClelland, J. L. (1994). Hippocampal conjunctive encoding, storage, and

recall: Avoiding a trade-off. *Hippocampus*, *4*(6), 661–682.

https://doi.org/10.1002/hipo.450040605

O'Reilly, R. C., & Norman, K. A. (2002). Hippocampal and neocortical contributions to

memory: Advances in the complementary learning systems framework. *Trends in*

Cognitive Sciences, *6*(12), 505–510. https://doi.org/10.1016/S1364-6613(02)02005-3

Patterson, K., Nestor, P. J., & Rogers, T. T. (2007). Where do you know what you know? The

representation of semantic knowledge in the human brain. *Nature Reviews.*

Neuroscience, *8*(12), 976–987. https://doi.org/10.1038/nrn2277

Pelli, D. G. (1997). The VideoToolbox software for visual psychophysics: Transforming

numbers into movies. *Spatial Vision*, *10*(4), 437–442.

Polyn, S. M., Natu, V. S., Cohen, J. D., & Norman, K. A. (2005). Category-Specific Cortical Activity Precedes Retrieval During Memory Search. *Science*, *310*(5756), 1963–1966. https://doi.org/10.1126/science.1117645

Poser, B. A., Versluis, M. J., Hoogduin, J. M., & Norris, D. G. (2006). BOLD contrast sensitivity enhancement and artifact reduction with multiecho EPI: Parallel-acquired inhomogeneity-desensitized fMRI. *Magnetic Resonance in Medicine*, *55*(6), 1227–1235. https://doi.org/10.1002/mrm.20900

Quiroga, R. Q. (2012). Concept cells: The building blocks of declarative memory functions. *Nature Reviews. Neuroscience, 13*(8), 587–597. https://doi.org/10.1038/nrn3251

Rice, G. E., Caswell, H., Moore, P., Hoffman, P., & Lambon Ralph, M. A. (2018). The Roles of Left Versus Right Anterior Temporal Lobes in Semantic Memory: A Neuropsychological Comparison of Postsurgical Temporal Lobe Epilepsy Patients. *Cerebral Cortex, 28*(4), 1487–1501. https://doi.org/10.1093/cercor/bhx362

Rissman, J., & Wagner, A. D. (2012). Distributed Representations in Memory: Insights from Functional Brain Imaging. *Annual Review of Psychology*, *63*(1), 101–128. https://doi.org/10.1146/annurev-psych-120710-100344

Ritchey, M., & Cooper, R. A. (2020). Deconstructing the Posterior Medial Episodic Network. *Trends in Cognitive Sciences*, *24*(6), 451–465. https://doi.org/10.1016/j.tics.2020.03.006

Ritchey, M., Wing, E. A., LaBar, K. S., & Cabeza, R. (2013). Neural Similarity Between Encoding and Retrieval is Related to Memory Via Hippocampal Interactions. *Cerebral Cortex, 23*(12), 2818–2828. https://doi.org/10.1093/cercor/bhs258

Ritchie, J. B., Tovar, D. A., & Carlson, T. A. (2015). Emerging Object Representations in the Visual System Predict Reaction Times for Categorization. *PLoS Computational Biology, 11*(6). https://doi.org/10.1371/journal.pcbi.1004316

Rolls, E. T. (2010). A computational theory of episodic memory formation in the hippocampus. *Behavioural Brain Research*, *215*(2), 180–196. https://doi.org/10.1016/j.bbr.2010.03.027

Rolls, E. T. (2013). The mechanisms for pattern completion and pattern separation in the hippocampus. *Frontiers in Systems Neuroscience, 7*.

Rorden, C., & Brett, M. (2000). Stereotaxic display of brain lesions. *Behavioural Neurology*, *12*(4), 191–200. https://doi.org/10.1155/2000/421719

Schyns, P. G., Zhan, J., Jack, R. E., & Ince, R. A. A. (2020). Revealing the information contents of memory within the stimulus information representation framework. *Philosophical Transactions of the Royal Society B: Biological Sciences*, *375*(1799), 20190705. https://doi.org/10.1098/rstb.2019.0705

Simons, J. S., Ritchey, M., & Fernyhough, C. (2022). Brain Mechanisms Underlying the Subjective Experience of Remembering. *Annual Review of Psychology*, *73*, 159–186. https://doi.org/10.1146/annurev-psych-030221-025439

Smith, S. M., & Nichols, T. E. (2009). Threshold-free cluster enhancement: Addressing problems of smoothing, threshold dependence and localisation in cluster inference. *NeuroImage*, *44*(1), 83–98. https://doi.org/10.1016/j.neuroimage.2008.03.061

Staresina, B. P., Henson, R. N. A., Kriegeskorte, N., & Alink, A. (2012). Episodic Reinstatement in the Medial Temporal Lobe. *Journal of Neuroscience*, *32*(50), 18150–18156. https://doi.org/10.1523/JNEUROSCI.4156-12.2012

Staresina, B. P., & Wimber, M. (2019). A Neural Chronometry of Memory Recall. *Trends in Cognitive Sciences*, *23*(12), 1071–1085. https://doi.org/10.1016/j.tics.2019.09.011

Statistical Parametric Mapping. (2007). Elsevier. https://doi.org/10.1016/B978-0-12-372560-8.X5000-1

St-Laurent, M., Abdi, H., & Buchsbaum, B. R. (2015). Distributed Patterns of Reactivation

Predict Vividness of Recollection. *Journal of Cognitive Neuroscience*, *27*(10), 2000–

2018. https://doi.org/10.1162/jocn_a_00839

ter Wal, M., Linde-Domingo, J., Lifanov, J., Roux, F., Kolibius, L. D., Gollwitzer, S., Lang,

J., Hamer, H., Rollings, D., Sawlani, V., Chelvarajah, R., Staresina, B., Hanslmayr,

S., & Wimber, M. (2021). Theta rhythmicity governs human behavior and

hippocampal signals during memory-dependent tasks. *Nature Communications*, *12*(1),

1. https://doi.org/10.1038/s41467-021-27323-3

Teyler, T. J., & DiScenna, P. (1986). The hippocampal memory indexing theory. *Behavioral*

Neuroscience, *100*(2), 147–154. https://doi.org/10.1037//0735-7044.100.2.147

Teyler, T. J., & Rudy, J. W. (2007). The hippocampal indexing theory and episodic memory:

Updating the index. *Hippocampus*, *17*(12), 1158–1169.

https://doi.org/10.1002/hipo.20350

Thakral, P. P., Wang, T. H., & Rugg, M. D. (2015). Cortical reinstatement and the confidence

and accuracy of source memory. *NeuroImage*, *109*, 118–129.

https://doi.org/10.1016/j.neuroimage.2015.01.003

Tools for NIfTI and ANALYZE image. (n.d.). Retrieved 28 May 2021, from

https://uk.mathworks.com/matlabcentral/fileexchange/8797-tools-for-nifti-and-

analyze-image

Treder, M. S. (2020). MVPA-Light: A Classification and Regression Toolbox for Multi-

Dimensional Data. *Frontiers in Neuroscience*, *14*.

https://doi.org/10.3389/fnins.2020.00289

Tulving, E., Le Voi, M. E., Routh, D. A., Loftus, E., & Broadbent, D. E. (1983). Ecphoric

processes in episodic memory. *Philosophical Transactions of the Royal Society of*

London. B, Biological Sciences, *302*(1110), 361–371.

https://doi.org/10.1098/rstb.1983.0060

Tzourio-Mazoyer, N., Landeau, B., Papathanassiou, D., Crivello, F., Etard, O., Delcroix, N.,

Mazoyer, B., & Joliot, M. (2002). Automated Anatomical Labeling of Activations in

SPM Using a Macroscopic Anatomical Parcellation of the MNI MRI Single-Subject

Brain. *NeuroImage*, *15*(1), 273–289. https://doi.org/10.1006/nimg.2001.0978

van Rossum, G. (1995). *Python tutorial* (R 9526). R 9526. https://ir.cwi.nl/pub/5007

Virtanen, P., Gommers, R., Oliphant, T. E., Haberland, M., Reddy, T., Cournapeau, D.,

Burovski, E., Peterson, P., Weckesser, W., Bright, J., van der Walt, S. J., Brett, M.,

Wilson, J., Millman, K. J., Mayorov, N., Nelson, A. R. J., Jones, E., Kern, R., Larson,

E., … SciPy 1.0 Contributors. (2020). Author Correction: SciPy 1.0: fundamental

algorithms for scientific computing in Python. *Nature Methods*, *17*(3), 352.

https://doi.org/10.1038/s41592-020-0772-5

Visser, M., Jefferies, E., & Lambon Ralph, M. A. (2010). Semantic Processing in the

Anterior Temporal Lobes: A Meta-analysis of the Functional Neuroimaging

Literature. *Journal of Cognitive Neuroscience, 22*(6), 1083–1094.

https://doi.org/10.1162/jocn.2009.21309

Wagner, A. D., Shannon, B. J., Kahn, I., & Buckner, R. L. (2005). Parietal lobe contributions

to episodic memory retrieval. *Trends in Cognitive Sciences*, *9*(9), 445–453.

https://doi.org/10.1016/j.tics.2005.07.001

Weaverdyck, M. E., Lieberman, M. D., & Parkinson, C. (2020). Tools of the Trade

Multivoxel pattern analysis in fMRI: A practical introduction for social and affective

neuroscientists. *Social Cognitive and Affective Neuroscience, 15*(4), 487–509.

https://doi.org/10.1093/scan/nsaa057

Wheeler, M. E., Petersen, S. E., & Buckner, R. L. (2000). Memory's echo: Vivid

remembering reactivates sensory-specific cortex. *Proceedings of the National*

Academy of Sciences of the United States of America, *97*(20), 11125–11129.

https://doi.org/10.1073/pnas.97.20.11125

Whitaker, K., TomRhysMarshall, Mourik, T. van, Martinez, P. A., poggiali, davide, Ye, H.,

& MariusKlug. (2019). *RainCloudPlots/RainCloudPlots: WellcomeOpenResearch*.

Zenodo. https://doi.org/10.5281/zenodo.3368186

Wing, E. A., Ritchey, M., & Cabeza, R. (2014). Reinstatement of Individual Past Events

Revealed by the Similarity of Distributed Activation Patterns during Encoding and

Retrieval. *Journal of Cognitive Neuroscience*, *27*(4), 679–691.

https://doi.org/10.1162/jocn_a_00740

Xiao, X., Dong, Q., Gao, J., Men, W., Poldrack, R. A., & Xue, G. (2017). Transformed

Neural Pattern Reinstatement during Episodic Memory Retrieval. *Journal of*

Neuroscience, *37*(11), 2986–2998. https://doi.org/10.1523/JNEUROSCI.2324-

16.2017

Xue, G. (2022). From remembering to reconstruction: The transformative neural

representation of episodic memory. *Progress in Neurobiology*, *219*, 102351.

https://doi.org/10.1016/j.pneurobio.2022.102351

Supplements

fMRI univariate analyses

We first performed a univariate GLM analysis and subsequent t-contrasts on the fMRI data to reveal activation differences between the two perceptual and the two conceptual categories (Suppl. Fig. 1, supporting Fig. 2). The GLM included the four main regressors (drawing-animate, photograph-animate, drawing-inanimate, and photograph-inanimate), with separate regressors for encoding, first retrieval, and second retrieval, using all trials. We used stick functions locked to the object onset to model the onset of encoding trials and boxcar functions with a duration of 2.5 s locked to the cue onset to model the onset of retrieval trials. We added one regressor each for the presentation of verbs, button presses, and perceptual and conceptual catch questions as well as nuisance regressors for head motion, scanner drift and run means. After computing the GLM for each subject, a sample-level ANOVA was computed with the perceptual (photograph versus line drawing) and conceptual (animate versus inanimate) dimensions as within-subjects factors. Planned comparisons contrasting photographs versus drawings and animate versus inanimate objects were carried out in subsequent t-contrasts separately at encoding and retrieval for all trials. The t-contrasts for retrieval trials were performed using both the first and second retrieval trials together.

fMRI univariate results

At encoding, photographs and line-drawings showed average activity differences primarily in ventral visual regions (see Suppl. Fig. 1, supporting Fig. 2). Photographs elicited significantly higher BOLD responses in V1, V2 and fusiform gyrus, ($t(30) = 4.56$, $p < .05$ (FWE)). Drawings only triggered slightly stronger activity in the middle and inferior occipital gyrus ($t(30) = 3.11$; $p < .001$ (unc.)). When contrasting conceptual categories, animate objects were associated with significantly higher activity in the lingual gyrus, middle occipital gyrus, fusiform gyrus and inferior temporal gyrus ($t(30) = 4.56$; $p < .05$ (FWE)), while inanimate objects showed a stronger signal in middle occipital gyrus and fusiform gyrus ($t(30) = 4.56$; $p < .05$ (FWE)). These contrasts thus show the expected tendency that perceptual categories differed in regions earlier

1564 along the ventral visual stream than conceptual categories, in line with the multivariate

1565 results reported in the main results.

1566 During retrieval, no voxels survived family-wise error correction or even a very liberal

1567 threshold of $p_{uncorr} < .01$ when contrasting perceptual or conceptual categories.

1568

a fMRI univariate results for encoding

1569

Supplemental Figure 1. Univariate t-contrasts for encoding. a) Cyan: Photograph > drawing, green:

drawing > photograph. b) Magenta: animate > inanimate, yellow: animate< inanimate. All contrasts

are thresholded at t(30) = 4.56, p < .05 (FWE). N = 31 independent subjects. Figure made using

MRIcron (https://www.nitrc.org/projects/mricron, www.mricro.com, Rorden & Brett, 2000) and a colin

27 average brain template (http://www.bic.mni.mcgill.ca/ServicesAtlases/Colin27, Holmes et al., 1998;

Copyright (C) 1993–2009 Louis Collins, McConnell Brain Imaging Centre, Montreal Neurological Institute,

McGill University*).*

1577

1578 ## EEG multivariate results

1579 EEG cross-subjects classifier-based RSA

1580 Plots below show the time-resolved decoding accuracy from the cross-subjects

1581 classifier, once in grey averaged across all object pairings in the RDM, and in magenta

split into the pairings belonging to the same (within) or different (between) conceptual classes, all with corresponding statistics (see methods).

During encoding, individual object decoding accuracy gradually increased from approximately 60 ms after stimulus onset, with a first smaller peak around 127 ms ($p < .05$ (cluster)), and a second temporally extended cluster from 224 ms until the end of the trial ($p < .05$ (cluster)). Moreover, objects from conceptually different classes (animate vs inanimate) were classified significantly better than objects from the same class, starting from 222 ms after stimulus onset until 1.3 s ($p < .05$ (cluster)). Given the object recognition literature (Cichy et al., 2014), it was surprising that the accuracy of object-identity decoding was comparatively low (though still significant) within the first 100 ms compared to the time period after 200 ms. This might reflect the fact that across participants, the objects corresponded in terms of image content but not perceptual format, potentially suppressing some low-level similarities and thus making classification on early visual features more difficult. Having said that, the photographic and drawn object versions overlapped in shape, orientation and disparity, preserving at least some low-level features, and a classifier should be able to use the neural signals corresponding to these features to discriminate individual objects. In fact, the searchlight fusion shows major correlation clusters during encoding in early visual areas (Fig. 5), indicating that some low-level features contribute to decoding performance at these early time points.

During retrieval, overall cross-subject classification accuracies remained relatively low in comparison to encoding, showing a peak decoding accuracy of 51 % approximately -2.8 s before the retrieval button press. Five significant accuracy clusters were found with peaks located at times -2.74 s, -2.63 s, -2.54 s, -2.16 s and -1.46 s relative to the time of subjective recollection (all $p < .05$ (cluster)). When comparing classification accuracy for conceptually different, between-class object pairs to within-class pairs, at no time point did this comparison survive cluster correction. The maximum between- versus within-class difference was identified -2.5 s before the retrieval button press, though at a very liberal threshold ($p < .01$ (uncorr.)).

a

b

1611

Supplemental Figure 2. Average accuracy of EEG-based classification of object identity over time

(grey), and average classification accuracy within- versus between conceptual classes (magenta)

during a) encoding and b) retrieval. At encoding, time point 0 s marks the object onset. At retrieval,

time point 0 s marks the button press, but is not included in figure as it does not lie within the time

window of interest (see methods). Solid grey line represents average accuracy across the entire

RDM, dashed grey line represents baseline average, and grey markers indicate significant overall

classification accuracy against chance through random label permutation. Solid magenta line

represents the average accuracy within conceptual categories, dashed magenta line represents

average accuracy between conceptual categories, and magenta markers indicate significant between-

versus within conceptual classes with correct labels. Significant decoding accuracy is indicated by

points (p < .01 uncorrected) and asterisk (p < .05 cluster). See Methods for details on cluster

correction. N = 24 independent subjects.