MultiGML: Multimodal Graph Machine Learning for Prediction of Adverse Drug Events

Sophia Krix[+,1,2,3], Lauren Nicole DeLong[+,1,4], Sumit Madan[1,5], Daniel Domingo-Fernández[1,3,6], Ashar Ahmad[2,7], Sheraz Gul[8,9], Andrea Zaliani[8,9], Holger Fröhlich[1,2,*]

[1] Department of Bioinformatics, Fraunhofer Institute for Algorithms and Scientific Computing (SCAI), Schloss Birlinghoven, 53757 Sankt Augustin, Germany

[2] Bonn-Aachen International Center for Information Technology (B-IT), University of Bonn, 53115 Bonn, Germany

[3] Fraunhofer Center for Machine Learning, Germany

[4] Artificial Intelligence and its Applications Institute, School of Informatics, University of Edinburgh, 10 Crichton Street, EH8 9AB, UK

[5] Department of Computer Science, University of Bonn, 53115 Bonn, Germany

[6] Enveda Biosciences, Boulder, CO 80301, USA

[7] Grünenthal GmbH, 52099 Aachen, Germany

[8] Fraunhofer Institute for Translational Medicine and Pharmacology ITMP, Schnackenburgallee 114, 22525 Hamburg, Germany

[9] Fraunhofer Cluster of Excellence for Immune-Mediated Diseases CIMD, Schnackenburgallee 114, 22525 Hamburg, Germany

[+] Shared first-authorship

[*] Correspondence: holger.froehlich@scai.fraunhofer.de

Summary

Adverse drug events constitute a major challenge for the success of clinical trials. Several computational strategies have been suggested to estimate the risk of adverse drug events in preclinical drug development. While these approaches have demonstrated high utility in practice, they are at the same time limited to specific information sources and thus neglect a wealth of information that is uncovered by fusion of different data sources, including biological protein function, gene expression, chemical compound structure, cell-based imaging, etc. In this work we propose an integrative and explainable Graph Machine Learning approach (MultiGML), which fuses knowledge graphs with multiple further data modalities to predict drug related adverse events. MultiGML demonstrates excellent prediction performance compared to alternative algorithms, including various knowledge graph embedding techniques. MultiGML distinguishes itself from alternative techniques by providing in-depth explanations of model predictions, which point towards biological mechanisms associated with predictions of an adverse drug event.

Keywords: Machine Learning, Knowledge Graph, Adverse Event, Graph Neural Network, Graph Attention Network, Graph Convolutional Network

Motivation

Adverse drug events are a major risk for failure of late-stage clinical trials. Attempts to prevent adverse drug events in preclinical drug development include experimental procedures for measuring liver-toxicity, cardio-toxicity, etc. Yet these procedures are costly and cannot fully guarantee success in later clinical studies, specifically in situations without a reliable animal model. Computational approaches developed for adverse event prediction have shown to be valuable, but are mostly limited to single data sources. Our approach successfully integrates various data sources on protein functions, gene expression, chemical compound structures and more, into the prediction of adverse events. A main distinguishing characteristic is the explainability of our model predictions which allow further insight into biological mechanisms.

1. Introduction

Adverse drug events (ADEs) are defined as an injury resulting from the use of a drug, including harm caused by the drug (adverse drug reactions and overdoses) and harm from the use of the drug (including dose reductions and discontinuations of drug therapy) (Nebeker et al., 2004). Experimental approaches to address potential ADEs (e.g. liver-toxicity) based on animal and tissue models are well established in pharma research. Yet, results obtained in such model systems may not always reflect the situation in humans. Furthermore, reliable model systems do not even exist for all indication areas. Computational approaches reflective of human biology could bridge this gap and provide supportive information regarding potential ADE prediction. Hence, there is a strong in interest in computational strategies: ADE prediction has been tackled via statistical methods based on human genetics (Carss et al., 2022; Duffy et al., 2020; Nguyen et al., 2019), chemical structure-based approaches (Liu et al., 2014; Niu & Zhang, 2017; Pauwels et al., 2011; Yamanishi et al., 2012; Zhang et al., 2015; Zhao et al., 2018), approaches using high-throughput literature mining (Deftereos et al., 2011), gene expression data (Cakir et al., 2021; Z. Wang et al., 2016), protein sequences (Takarabe et al., 2012) and electronic health records (Vilar et al., 2012) and data from electronic pharmacovigilance systems such as the FDA Adverse Event Reporting System (Schotland et al., 2021). While each of these approaches have their own merits, they also come along with unavoidable limitations: For example, genetic variants associated with a certain phenotype may not be identifiable in genome-wide association studies due to lack of statistical power. Chemical compound structure can inform about binding affinity to a given target, but does not cover the question whether the choice of a specific target should per se raise safety concerns due to the expected biological downstream consequences. Electronic health records can inform about real-world post-marketing aspects of drugs, but have limited utility in the preclinical drug development phase due to the lack of quantitative biological data.

An alternative strategy is to use biological networks, which represent a rich resource of relational information. In this context knowledge graphs (KGs) have become popular due to their ability to accurately represent multiple types of relationships between different entities (Barabási & Oltvai, 2004; Rebele et al., 2016; Vrandečić & Krötzsch, 2014). That means KGs are multi-relational graphs with entities as nodes and their relations as edges. Relations are represented as triples of (source entity, relation type, target entity). KGs often incorporate a variety of heterogeneous information in the form of different node and edge types. In recent years, numerous knowledge graphs have been published such as OpenBioLink (Breit et al., 2020), Hetionet (D. S. Himmelstein et al., 2017), PharmKG (Zheng et al., 2020) or CTKG (Chen et al., 2021), a knowledge graph on clinical trials. These comprehensive KGs contain

a variety of entity types and relation types which model biology as accurately as possible and can be applied to multiple tasks due to their versatile design.

From a network-perspective, ADE prediction can be formulated as a link prediction task in a KG. Earlier approaches extracted manually crafted features of the topology of the KG by using the neighborhood information of each node (Lin et al., 2013) or by extracting local information indexes and path information (Luo et al., 2014). Other authors used an enrichment test of known causes of ADEs to construct features that were subsequently employed in a machine learning algorithm (Bean et al., 2017). Another network-based approach used structural information of the drug molecules for a logistic regression model (Cami et al., 2011). As interactions between co-prescribed drugs are a major cause of ADEs (Aronson, 2015), predicting these by using similarity measures (Fokoue et al., 2016) or by using an approach which generates representative KG embeddings with a convolutional Long short-term memory (LSTM) network (Karim et al., 2019) have been proposed. Another embedding-based approach using node2vec along with a deep neural network was recently developed for predicting ADEs (Joshi et al., 2022). In order to model possible inaccuracies in the KG, Dasgupta *et al.* used confidence scores from natural language processing (NLP) inference for clinical concepts and for edges in the KG during representation learning (Dasgupta et al., 2021).

From a methodological point of view, link prediction in KGs can be addressed by first learning an embedding of the graph structure in Euclidean space. Essentially, the KG embedding is a low-dimensional representation which captures key information about entities and their relations. Typically, entities with similar embeddings are also similar in the original space. Hence, we can assess the likelihood that two entities should be connected by a relation type. In addition to established network representation learning methods such as TransE (Bordes et al., 2013), ComplEx (Trouillon et al., 2016), DistMult (Yang et al., 2014), RotatE (Sun et al., 2019), DeepWalk (Perozzi et al., 2014) and node2vec (Grover & Leskovec, 2016), graph neural networks (GNNs) have emerged as an efficient machine learning method. GNNs were first introduced by Scarselli et al. (2009). Subsequently, graph convolutional neural networks (GCNs) (Kipf & Welling, 2017) and graph attention networks (GATs) (Veličković et al., 2017) were developed as variants of GNNs. GNNs have been successfully applied to various tasks in network analytics, including clustering (Wang et al., 2017) and disease classification (Rhee et al., 2018), prediction of molecular fingerprints (Duvenaud et al., 2015) and protein interfaces (Fout, 2016), as well as prediction of drug-protein interactions (Wu et al., 2022) and poly-pharmacological side effects (Zitnik et al., 2018). A GNN has also been used on a drug-disease graph for ADE prediction (Kwak et al., 2020). This approach has been further developed by combining two GNNs for graph and node embedding in a hybrid approach to predict ADEs via a matrix completion process (Yu et al., 2022). Finally, a graph convolutional autoencoder approach coupled with an attention mechanism has been suggested, leveraging the pairwise attributes for drug-related ADE prediction in a heterogeneous graph (Xuan et al., 2022).

A limitation of these existing KG focused approaches is that they neglect any orthogonal information, including genetic associations, chemical compound structure, gene expression signatures and cell morphology changes. The aim of this paper is thus to address limitations of previous work by developing a Graph Machine Learning approach, which integrates biological networks, genetic variant to phenotype association, gene expression, cell based imaging, protein sequence information, clinical concept embeddings as well as chemical compound fingerprints into one end-to-end trainable algorithm. The idea is thus to integrate a large number of potentially relevant sources of evidence to predict potential ADEs that could occur during clinical trials and therefore reduce the risk of late and costly failures

(Schuster et al., 2005). To do so, we built a dedicated KG and designed a novel GNN architecture tailored for ADE prediction. The KG consists of multi-relational and heterogeneous information collected from 14 different databases and is enriched with multi-modal features for each node in order to capture various relevant biomedical data in addition to graph topology. As opposed to state-of-the-art approaches, our proposed MultiGML model is thus designed to integrate multi-modal and in particular also quantitative input data (e.g. gene expression). We demonstrate the superior prediction performance of our approach by comparing it with several state-of-the-art models. Moreover, we introduce a technique to make model predictions explainable, which is crucial in the context of an application in the early phases of drug development. Based on a number of examples we show that our method in this way allows for pointing towards the biological mechanisms associated with a given ADE prediction. Finally, we provide literature evidence for some of the predictions made by our GNN method. The source code and the Python package of MultiGML is available on [GitHub](https://github.com/SCAI-BIO/MultiGML) (https://github.com/SCAI-BIO/MultiGML).

2.   Results

2.1.   Link Prediction Results

In the following, we show the prediction performance of our MultiGML models compared to various competing methods for link prediction in KGs. We first evaluated MultiGML for the task of predicting any link in the KG and second for the more specific task of adverse drug event prediction. Regarding the first task, our MultiGML-RGCN model reached a performance of 0.808 area under precision recall curve (AUPR), and the MultiGML-RGAT model reached an AUPR of 0.798, both outperforming all competing methods (Table 1) by at least ~5%. At the same time precision@1000 was about 0.9 for both variants. When omitting the multi-modal feature embedding (i.e. only learning from the graph topology) the Precision@k of both MultiGML models dropped by 1-2%.

We focused subsequently on the task of predicting links between compounds and ADEs. For that purpose we employed a version of our MultiGML model for which we specifically optimized hyperparameters on the validation set with respect to the loss for this specific relation type. Once again, all MultiGML variants performed better than all competing methods with AUROC, AUPR and precision@30 all close to 1 (Table 2). Compared to the Random Forest approach by Wang et al. performance gains were highly significant. Notably reported performance measures were based on the negative sampling scheme explained in section 3.3.1. When increasing the ratio of negative samples in the test set from 1:1 to 1000:1 AUROC and AUPR remained stable, and precision@30 was stable for ratios from 1:1 to 100:1 (see Suppl. Figure 1).

We next evaluated the performance for predicting links between genes and phenotypes, which would be of relevance in the context of target selection. For this purpose we used our MultiGML models which were optimized for general link prediction. Once again all variants of the MultiGML model outperformed competing methods with AUROC ~0.89, AUPR ~0.83 and precision@100 ~0.84 (Table 3).

We explored which feature modalities contributed most to our model's predictions. Notably, in both MultiGML variants, available protein and drug features played an important role, i.e. were selected during the hyperparameter optimization (see Suppl. Figure 2). More specifically, the molecular fingerprint of the drugs as well as the gene ontology fingerprint of the proteins were found to be the best choices of node features for the prediction of ADEs

with our MultiGML models. Additionally, gene expression signatures of drugs were identified as relevant by the MultiGML-RGCN model.

Model	AUROC	AUPR	Precision@1000
TransE	0.667	0.633	0.715
RotatE	0.793	0.759	0.909
ComplEx	0.757	0.699	0.622
DistMult	0.765	0.696	0.656
DeepWalk	0.648	0.622	0.773
MultiGML-RGCN (basic)	0.847	0.787	0.881
MultiGML-RGAT (basic)	0.843	0.793	0.902
MultiGML-RGCN (multimodal)	**0.859**	**0.808**	0.901
MultiGML-RGAT (multimodal)	0.845	0.798	**0.916**

Table 1. Model performance results for general relation prediction. The table shows the test results of several competing KG embedding methods, including TransE, RotatE, ComplEx, DistMult and DeepWalk, as well as our two tested MultiGML model variants. Best results are marked in bold. Both RGCN and RGAT variants of the MultiGML model were tested with two types of input features. Basic features are vectors initialized with the Xavier-Glorot method and are unimodal features. Multimodal features refer to the representative features of several modalities for each node type described in section 3.1.2.

Model	AUROC	AUPR	Precision@30
TransE	0.293	0.389	0.233
RotatE	0.943	0.915	0.967
ComplEx	0.884	0.934	**1.0**
DistMult	0.963	0.966	**1.0**
DeepWalk	0.575	0.604	0.567
Random Forest	0.512	0.164	0.464
MultiGML-RGCN (basic)	**1.0**	**1.0**	**1.0**
MultiGML-RGAT (basic)	**1.0**	**1.0**	**1.0**
MultiGML-RGCN (multimodal)	**1.0**	**1.0**	**1.0**
MultiGML-RGAT (multimodal)	0.980	0.982	**1.0**

Table 2. Model performance results for predicting a novel relation between a drug and an ADE. Test results of competing KG embedding methods, including TransE, RotatE, ComplEx, DistMult, DeepWalk, and additionally Random Forest for adverse drug event prediction in comparison to our MultiGML models. Best results are marked in bold. Both MultiGML-RGCN and -RGAT variants were tested with basic and multimodal input features. Basic features are vectors initialized with the Xavier-Glorot method and are unimodal features.

Multimodal features refer to the representative features of several modalities for each node type described in section 3.1.2.

Model	AUROC	AUPR	Precision@100
TransE	0.735	0.674	0.533
RotatE	0.723	0.680	0.710
ComplEx	0.843	0.770	0.790
DistMult	0.848	0.767	0.776
DeepWalk	0.654	0.630	0.761
MultiGML-RGCN (basic)	**0.898**	**0.832**	**0.850**
MultiGML-RGAT (basic)	0.897	0.831	0.841
MultiGML-RGCN (multimodal)	0.897	**0.832**	0.846
MultiGML-RGAT (multimodal)	0.892	0.826	0.827

Table 3. Model performance results for predicting a novel gene - phenotype association. Test results of competing KG embedding methods, including TransE, RotatE, ComplEx, DistMult and DeepWalk for prediction of a gene - phenotype association in comparison to our MultiGML models. Both MultiGML-RGCN and -RGAT variants were tested with basic and multimodal input features. Basic features are vectors initialized with the Xavier-Glorot method and are unimodal features. Multimodal features refer to the representative features of several modalities for each node type described in section 3.1.2.

2.2. Use cases

To illustrate the practical use of our MultiGML method we further explored two newly predicted links between drugs and ADEs that were not part of the KG. Furthermore, we show an example of a newly predicted gene - phenotype association. All links have been predicted with probability >70% by MultiGML-RGAT.

2.2.1. Acute Liver Failure As A Predicted Adverse Drug Event of Alendronic Acid

MultiGML predicted a link between alendronic acid (DRUGBANK:DB00630), a bisphosphonate, and acute liver failure (UMLS:C0162557). Alendronic acid is used to prevent and treat osteoporosis (Wishart et al., 2018), and was found to cause liver damage in a patient that was in treatment for osteoporosis (Halabe et al., 2000). Alendronic acid is also listed in the NIH LiverTox lexicon as a "rare cause of clinically apparent liver injury" (Hoofnagle et al., 2013).

We extracted the attention weights for all relations involving acute liver failure and alendronic acid of the MultiGML-RGAT model of the last graph attention layer (see Figure 1 A). Several relations between alendronic acid and proteins, including two tyrosine phosphatases, PTPRS and PTPN4, and the phenotype Paget's Disease (UMLS:C0029401), were weighted higher than all other direct relations by the MultiGML-RGAT model. Indeed, alendronic acid is used to treat Paget's Disease of bone, also known as Osteitis Deformans (Reid & Siris, 1999) by inhibiting tyrosine-protein phosphatases (Wishart et al., 2018). Protein tyrosine phosphatase receptor type S (PTPRS) acts as a metastatic suppressor in hepatocellular

carcinoma (Z.-C. Wang et al., 2015) and was found dysregulated in cirrhotic liver (Chan et al., 2016). PTPN4 belongs to the same family of proteins and has accordingly been reported as a prognostic marker for hepatocellular carcinoma (Zhangyuan et al., 2018).

To better understand the prediction by our MultiGML model, we investigated the importances of the gene expression signature of the drug alendronic acid in the prediction. More specifically, we identified the top 100 influential genes of the L1000 gene expression signature of alendronic acid according to the integrated gradients methods and performed a Gene Ontology (GO) overrepresentation analysis via a hypergeometric test. After multiple testing correction according to the Benjamini-Hochberg method and choosing a false discovery rate cutoff of 5% we found that regulation of the cytoskeleton organization and protein stability were important for the prediction of acute liver failure as an adverse drug event of alendronic acid (see Figure 1 B, Supp. Table 1). A comprehensive list of the top 100 positively and negatively attributed genes can be found in the Supplementary Material (Suppl. Table 2).

2.2.2. Paralysis As A Predicted Adverse Drug Event of Kanamycin

Kanamycin (DRUGBANK:DB01172), which is an aminoglycoside bactericidal antibiotic (Wishart et al., 2018), was predicted to be associated with a paralytic side effect (UMLS:C0522224) (Figure 2 A iii). Kanamycin is used to treat a wide variety of bacterial infections (Wishart et al., 2018). In several studies, Kanamycin was reported to be neurotoxic and induce neuromuscular paralysis or blockades (Freemon, 1967; Naiman et al., 1965; Pittinger et al., 1970). More recent studies with organoids suggested a damaging effect on early postnatal but not on adult ganglion neurons (Gao et al., 2017). Indeed, ototoxicity of kanamycin is a significant dose-limiting side effect (Heysell et al., 2018).

As done previously, we extracted the attention weights for all relations involving kanamycin and paralysis of the MultiGML-RGAT model of the last graph attention layer (see Figure 2 A). Of all direct relations, the relation between the drug cyclopentolate and the phenotype paralysis was weighted higher than all other direct relations by the MultiGML-RGAT model. Cyclopentolate (DRUGBANK:DB00979) is an anticholinergic agent used to dilate the eye for diagnostic and examination purposes (Wishart et al., 2018). Additionally to inducing mydriasis - the dilation of the pupil - , cyclopentolate also causes reversible paralysis of the ciliary muscle by blocking muscarinic receptors (Bartlett & Jaanus, 2008).

We investigated which genes from the gene expression signature of kanamycin were found to be important by the integrated gradient analysis. We performed a GO overrepresentation analysis of the top 100 genes via a hypergeometric test (see Figure 2 B, Suppl. Table 3), reporting the Benjamin-Hochberg adjusted p-value (q-value) for multiple testing, and found that biological processes involved in metabolism and responses to stimuli were significantly overrepresented. Altogether, this demonstrates the ability of our method to point towards biological mechanisms associated with ADEs. A comprehensive list of the top 100 genes can be found in the Supplementary Material (Suppl. Table 4).

2.2.3. Association of WNT3 with Thrombophlebitis

WNT3 (HGNC:12782) is a gene that is part of the Wnt signaling pathway (KEGG:hsa04310) in humans. Wnt proteins are secreted morphogens that are required for basic developmental processes, such as cell-fate specification, progenitor-cell proliferation and the control of asymmetric cell division, in many different species and organs (Kanehisa et al., 2016). Our MultiGML-RGAT model predicted an association between WNT3 and Thrombophlebitis (UMLS:C0040046). Thrombophlebitis is an inflammation of a vein associated with a blood

clot (Bodenreider, 2004). Several studies suggest that WNT signaling has a regulatory role in inflammation (George, 2008), is involved in the calcification of vascular smooth muscle cells (Bundy et al., 2021), and that it is a key player in the development of vascular disease, including thrombosis (Foulquier et al., 2018). A recent study on endothelial injury has shown protective effects of Wnt signaling (Y. Wang et al., 2021). More specifically, attenuated apoptosis and exfoliation of vascular endothelial cells and infiltration of inflammatory cells was observed upon activation of the Wnt/beta-catenin pathway.

In Figure 3, we display the novel link of WNT3 to thrombophlebitis in the knowledge graph together with the attention weights learned by our MultiGML-RGAT model. Several relations between WNT3 and other proteins were attributed a high attention weight, including insulin (INS), LRP6, as well as their relations with other proteins, FZD4, FZD7, FZD9, SFRP2 with INS and FZD10 with LRP6. Betamethasone and its relation to thrombophlebitis as an ADE was also attributed with a high attention weight. Associations between the phenotypes essential thrombocythemia (UMLS:C0040028) and rare diabetes mellitus (UMLS:C5681799) with insulin were also much attended by the model. The association between thrombosis, vascular inflammation and diabetes in relation with insulin resistance has been observed in many studies (Pechlivani & Ajjan, 2018; Piazza et al., 2012). A modulation of the interaction of the insulin and Wnt signaling has even been proposed as an attractive target in treating diabetes (Abiola et al., 2009), and could potentially have a role in mediating the effect of inflammatory conditions affecting the vascular system, such as thrombophlebitis.

Figure 1. Prediction of acute liver failure as an ADE for alendronic acid. A) Novel prediction of acute liver failure (UMLS:C0162557) as a potential ADE of alendronic acid (DRUGBANK:DB00630) in the KG, colored in red. The attention weight for every edge from the last MultiGML-RGAT graph attention layer is indicated by the edge strength. **B)** GO overrepresentation analysis of the top 100 genes from the L1000 drug signature identified via the integrated gradients method. Top 10 enriched terms (one per cluster) created with Metascape. $-Log_{10}(q)$ -values are reported and color coded for each term.

Figure 2. Prediction of paralysis as an ADE for kanamycin. A) Novel prediction of paralysis (UMLS:C0522224) as potential ADE of kanamycin (DRUGBANK:DB01172) in the KG, colored in red. The attention weight for every edge from the last MultiGML-RGAT graph attention layer is indicated by the edge strength. **B)** GO overrepresentation analysis of the top 100 genes from the L1000 drug signature identified via the integrated gradients method. Top enriched terms created with Metascape. $-Log_{10}(q)$ - values are reported and color coded for each term.

Figure 3. Prediction of thrombophlebitis as a phenotype associated with WNT3. Novel prediction of thrombophlebitis (UMLS:C0040046) associated with WNT3 (HGNC:12782) in the KG, colored in red. The attention weight for every edge from the last MultiGML-RGAT graph attention layer is indicated by the edge strength.

3. Materials and Methods

3.1. Multi-modal Knowledge Graph Generation

3.1.1. Integration of Biomedical Knowledge from Databases

We integrated information from 14 well-established databases to generate an heterogeneous KG. Our KG contains information about interactions and associations between drugs, proteins, and phenotypes. We introduce the node type 'phenotype' to resolve the ambiguity between ADEs and diagnoses. That means ADEs and diagnoses are both subsumed as 'phenotype'. As a result, we generated a heterogeneous and multi-relational KG with 3 different entity types and 8 different relation types (see Figure 4A). The relation types that occur in the KG are drug-protein, protein-phenotype, genetic variant-phenotype, drug-adverse drug event and 3 different types of protein-protein interactions (physical interaction, functional interaction and signaling interaction) (see Suppl. Table 5). The knowledge graph is formally defined as $G = (N, R)$, with N as entities, and R as relations.

Interaction information between approved drugs and their protein targets was taken from DrugBank (Wishart et al., 2018) and IUPHAR (Harding et al., 2018). Associations between proteins and indications (here: phenotypes) with a high confidence score > 0.6 were extracted from DisGeNet (Piñero González et al., 2020) and specific gene-phenotype associations from PheWAS (Denny et al., 2010), with an odds-ratio > 1. Drug indications for diseases were obtained from OpenTargets (Ochoa et al., 2021) and ClinicalTrials (Zarin et al., 2011). Protein-protein interactions were gathered from renowned databases, including KEGG (Kanehisa et al., 2016; Kanehisa & Goto, 2000), Reactome (Jassal et al., 2020), BioGRID (Oughtred et al., 2021), IntAct (Kerrien et al., 2012), PathwayCommons (Cerami et

al., 2011) and STRINGDB (Szklarczyk et al., 2019), where interactions from the latter were filtered for genetic associations with a homology score > 600. The OFFSIDES database (Tatonetti et al., 2012) as well as the renowned SIDER database (Kuhn et al., 2016) were used to extract known ADEs of drugs (see Suppl. Table 6).

Because more severe ADEs tend to increase the risk for a drug to fail in clinical trials or be withdrawn from the market, the following heuristic was employed to filter out more severe ADEs from the information contained in the aforementioned databases: first, we designed a novel metric called the *failure ratio*, which we computed for each phenotype in the graph which served as a target node in an "adverse drug event" edge. The *failure ratio* is defined in Equation 1. Given the number of trials in which a given phenotype is listed as an "adverse drug event" on *ClinicalTrials.gov*, the *failure ratio* is equal to the proportion of these trials which were suspended, terminated, or withdrawn. All phenotypes with a failure ratio greater than 0.75 among at least 3 trials were chosen to be used for the graph. This resulted in nearly two hundred ADE relations, approximately 0.1% of the unique ADE between SIDER and OFFSIDES, which were subsequently added to the KG. All identifiers and interaction types were harmonized across all databases (Figure 4 A). A complete overview about the entity and relation types in the KG is provided in Table 4 and Table 5.

$$\text{Failure ratio} = \frac{\text{Trials with condition as "adverse event" AND suspended, terminated, or withdrawn}}{\text{Total trials with condition as "adverse event"}}$$

<div align="right">Equation 1</div>

Knowledge Graph Generation

Feature Modality Annotation

Adverse Drug Event Prediction

Figure 4. Overview of workflow. A) Knowledge Graph compilation. In the first step of data processing, interaction information from 14 biomedical databases was parsed with data on drug-drug interactions, drug-target interactions, protein-protein interactions, indication, drug-ADE and gene-phenotype associations. The data was harmonized across all databases and a comprehensive, heterogeneous, multi-relational knowledge graph was generated. B) Feature definition. Descriptive data modalities were selected to annotate entities in the knowledge graph. Drugs were annotated with their molecular fingerprint, the gene expression profile they cause, and the morphological profile of cells they induce. Proteins were annotated with their protein sequence embedding and a gene ontology fingerprint. Phenotypes, comprising indications and ADEs, were annotated by their clinical concept embedding. C) Proposed MultiGML approach. The heterogeneous Knowledge Graph with its feature annotations is used as the input for our graph neural network approach, the MultiGML. For each node entity, a multi-modal embedding layer learns a low dimensional representation of entity features. These embeddings are then used as input for either the RGCN or RGAT of the encoder (see section 3.2.1), which learns an embedding for each entity in the KG. A bilinear decoder takes a source and a destination node, drug X and phenotype Y in the example here, and produces a score for the probability of their connection, considering their relation type with each other.

Entity Type	Count
phenotype	16,560
drug	2,378
protein	12,953

Table 4. Overview of entities in the knowledge graph.

Relation Type	Count
drug-adverse drug event	197
functional protein-protein association	1,761
protein-phenotype	5,448
physical protein-protein interaction	6,087
drug-protein	12,451
drug-indication	12,848
genetic variant-phenotype	159,202
protein-protein signaling interaction	222,078

Table 5. Overview of relation types in the knowledge graph.

3.1.2.   Definition of Entity Related Features

Due to the increasing availability of descriptive data modalities for drugs, proteins, and phenotypes, we decided to incorporate multiple feature modalities in our dataset (see Figure 4 B). We chose modalities that were descriptive for the individual entity type, and generated features for each entity type as described below:

- **DRUGS:** Transcriptomics data are informative about the effect of a drug on biological processes in a defined system of a cell culture experiment. A molecular signature can therefore be generated for each drug, measuring the gene expression fold change of selected transcripts. We chose the LINCS L1000 dataset (Duan et al.,

2014) to annotate the drugs with gene expression profile information. More specifically, we retrieved the consensus signatures calculated by Himmelstein et al. (D. Himmelstein et al., 2016; D. S. Himmelstein et al., 2017). The background is that each LINCS compound may have been assayed across multiple cell lines, dosages and replicates. Himmelstein et al. thus estimated a single consensus transcriptional profile across multiple signatures (Himmelstein, Daniel, 2015)

The effects of a drug perturbation in a cell culture experiment can not only be seen in the gene expression fold change, but also in the change in morphology of the treated cells. Therefore, we additionally annotate the drug with the Cell Painting morphological profiling assay information from the LINCS Data Portal (LDG-1192: LDS-1195) (Schreiber, 2014).

Furthermore, the molecular structure of the drugs was also taken into account by generating the molecular fingerprints. We here took the Morgan count fingerprint (Rogers & Hahn, 2010) with a radius = 2, generated with the RDKit (Landrum, 2010).

- **PROTEINS:** We used structural information of proteins by utilizing the protein sequence embeddings. We generated the embeddings for each protein with the ESM-1b Transformer (Rives et al., 2021), a recently published pre-trained deep learning model for protein sequences.

  In addition, we generated a binary Gene Ontology (GO) fingerprint for biological processes for each protein using data from the Gene Ontology Resource (Ashburner et al., 2000; Gene Ontology Consortium, 2021). A total of 12,226 human GO terms of Biological Processes were retrieved and their respective parent terms obtained. This resulted in a 1,298 dimensional binary fingerprint for each protein, with each index either set to 1, if the protein was annotated with the respective GO term or 0 if not.

- **PHENOTYPES:** Medical concept embeddings from Beam et al. (Beam et al., 2020) were used to annotate phenotypes including ADEs and indications. The so-called *cui2vec* embeddings were generated on the basis of clinical notes, insurance claims, and biomedical full text articles for each clinical concept. Briefly, the authors mapped ICD-9 codes in claims data to UMLS concepts and then counted co-occurence of concept pairs. After decomposing the co-occurrence matrix via singular value decomposition, they used the popular word2vec approach to obtain concept embeddings in the Euclidean space. We refer to Beam et al. for more details.

3.2. Graph Neural Network Architecture

MultiGML consists of two main structures, an encoder and a decoder. The encoder has two main components which create a low-dimensional embedding of each node in the KG (see section 3.2.1.). Due to its design, the encoder can handle multimodal input data. The second part of the model decodes edges from node embeddings with a bilinear form (see section 3.2.2.). The entire model architecture is shown in Figure 4C and discussed in more detail in the subsequent paragraphs.

3.2.1. Encoder
3.2.1.1. Multi-modal Embedding of Node Features

Due to the multi-modal character of our KG, we require a model that can integrate input features of multiple modalities for one node into the message passing. To do so, we implemented a specific architecture based on the work by (Lemsara et al., 2020) that combines representations from different data modalities (Figure 5).

In a nutshell, this multimodal embedding learns hidden representations of each modality separately in the first densely connected layer. The hidden feature representations are then concatenated and passed to a second densely connected layer to generate a shared multimodal embedding for each entity v in the KG: Let x_1, x_2,..., x_k denote the k feature vectors of dimensions d_1, d_2, ..., d_k associated to entity v. The embedding H_{shared} is therefore learned as follows:

$$H_{shared} = \sigma \left(W_{multi}(\sigma(W_1(x_1)||\sigma(W_2(x_2))||...||\sigma(W_k(x_k))))) \right)$$ Equation 2,

where σ is the tanh activation function and || denotes a concatenation.

We use dropout units in each layer with a dropout ratio that is adjusted during Bayesian hyperparameter optimization. This is followed by a batch normalization with a tanh activation function.

Figure 5. Multi-modal embedding (example of drug input): Each drug is represented by f different feature modalities, which are fed into a multi-modal neural network with bottleneck architecture. That means $H_{molecular}, H_{gene}, H_{morph}$ are the output of dense feed-forward layers, each having $k_r/2$ hidden units, where k_r is the number of original input features for data modality r. $H_{shared} = (H_{molecular}||H_{gene}||H_{morph})$ represents the multi-modal embedding.

3.2.1.2. Relational Graph Convolutional Neural Network (RGCN)

KGs often incorporate a variety of heterogeneous information in the form of different node and edge types. In the following, we will refer to the prominent Relational Graph Convolutional Neural Network (RGCN) that was proposed by Schlichtkrull et al. (2018) to deal with the multirelational data characteristic of KGs. The RGCN includes information from the neighborhood of a node into the message passing by differentiating between the relation types. Due to this characteristic, the model is able to learn the inherent relationships between the entities in the KG.

The RGCN takes as input a heterogeneous multi-relational knowledge graph G with features $x \in \mathbb{R}^q$ and learns an embedding h_i of each entity $v_i \in N$ in the KG. The architecture of the implemented model has three consequent RGCN layers (Schlichtkrull et al., 2018)l:

- **input to hidden layer:** input feature vectors $x_i \in \mathbb{R}^q$ are transformed into their hidden representation $h_i \in \mathbb{R}^{k'}$

- **hidden to hidden layer**: convolution of hidden feature vectors $h_i \in \mathbb{R}^{k'}$, maintaining their shape
- **hidden to output layer**: hidden feature vectors $h_i \in \mathbb{R}^{k'}$ are transformed into their latent representation $h_i \in \mathbb{R}^l$

The message passing for node i is given by:

$$h_i^{(l+1)} = \sigma \left(\sum_{r \epsilon R} \sum_{j \epsilon N_i^r} \frac{1}{c_{i,r}} W_r^{(l)} h_j^{(l)} + W_0^{(l)} h_i^{(l)} \right)$$ Equation 3,

The updated hidden representation h_i of entity v_i at layer $l + 1$ is a non-linear combination of the hidden representations of neighboring entities with index $j \in N_i^r$ weighted by the learnable relation type specific weight matrix $W_r^{(l)}$. Here, N_r is the set of neighbors of node v_i of relation type r. A self-loop is defined by adding the node's own hidden representation h_i, multiplied by the weight matrix W_0. $c_{i,r}$ is a normalization constant that is task-dependent and can either be learned or chosen in advance, such as $c_{i,r} = \left| N_i^r \right|$. We refer to this variant of our MultiGML model as MultiGML-RGCN.

3.2.1.3.   Relational Graph Attention Network (RGAT)

Alternatively to the RGCN we considered a relational graph attention network (Veličković et al., 2017) as part of the encoder. The input is a set of entity features $h = \{h_1, h_2, h_3, ..., h_N\}$, $h_i \epsilon R^q$ with N being the number of entities and q being the number of features of each entity. Self-attention is performed on the entities, whereby a shared attention mechanism a computes attention coefficients (Veličković et al., 2017) for each relation type (Equation 4)

$$E_{i,j}^{(r)} = a(W^{(r)} h_i, W^{(r)} h_j)$$ Equation 4,

The attention mechanism a is a single-layer feedforward neural network feeding into a Leaky ReLU unit (angle of negative slope = 0.2). The attention coefficients are normalized across all choices of j via the softmax function (Busbridge et al., 2019; Veličković et al., 2017),

$$\alpha_{i,j}^{(r)} = softmax_j \left(E_{i,j}^{(r)} \right) = \frac{exp\left(E_{i,j}^{(r)} \right)}{\sum_{k \epsilon N_i^{(r)}} exp\left(E_{i,k}^{(r)} \right)}, \forall i, r : \sum_{j \epsilon N_i^{(r)}} \alpha_{i,j}^{(r)} = 1$$ Equation 5,

leading to the propagation model for a single node update in a multi-relational graph of the following form (Equation 6):

$$h_i^{(l+1)} = \sigma \left(\sum_{r \epsilon R} \sum_{j \epsilon N_i^r} \alpha_{i,j}^{(r)} h_i (W^{(r)})^T \right)$$

Equation 6

The graph attention layer allows assigning different importances to nodes of a same neighborhood which can be analyzed to interpret the model predictions (Veličković et al., 2017). We refer to this variant of our MultiGML model as MultiGML-RGAT.

3.2.2. Bilinear Decoder

The decoder structure in our model uses the entity embeddings to decode relations in the KG. We calculate a score for a given triple of entities v_i and v_j connected by relation r. We use a bilinear form on the embeddings h_i and h_j with a trainable matrix M_r representing the relation type and apply a sigmoid function σ to the result as in equation 7:

$$score_{i,j}^{(r)} = score(v_i, r, v_j) = \sigma(h_i^T M_r h_j)$$

Equation 7,

3.3. Empirical Evaluation

3.3.1. Model Training Strategy

We trained our MultiGML model on the KG described in section 3.1. The binary cross-entropy loss was applied to supervise the model. We performed a stratified random split of all relations into a 70% train, 20% test and 10% validation set. The stratification was done such that each data subset contained the same fraction of each relation type. The number of relations amounted to 604,903 in the training set, 67,212 in the validation set and 168,029 in the test set. Note that all those real existing relations provide positive examples. An important question in Graph Machine Learning is, how to generate negative samples for non-existing relations. In this work we performed negative sampling where for each positive relation one negative relation was generated by randomly exchanging the target for each source entity according to a uniform distribution (uniform sampling). We employed a hyperparameter optimization with the Optuna package (Akiba et al., 2019), with a customized search space for each hyperparameter (see Suppl. Table 7). Notably, hyperparameter optimization also included the selection of node feature modalities. That means we allowed entire data modalities to be dropped from the model during training. The Tree Parzen Estimator (Bergstra et al., 2011), an independent sampling algorithm, was used for an efficient exploration of the search space. Each hyperparameter optimization for both the RGCN and RGAT model consisted of 50 trials. Models within each trial were trained for 100 epochs unless the hyperband pruner (Li et al., 2016) determined that a trial should be pruned. After each training epoch the model was evaluated on the validation test. After the best set of hyperparameters was found, we trained a final model for 100 epochs with the selected hyperparameters (see Suppl. Table 7), unless early stopping was triggered by a stagnation in the loss calculation for 10 epochs, and then tested the model on the unseen test set.

3.3.2. Comparison against competing methods

We benchmarked MultiGML against several competing approaches for both general link prediction and adverse drug event prediction. All methods were evaluated using the same data splits. We compared our models against four well-established KG embedding approaches, namely TransE (Bordes et al., 2013), RotatE (Sun et al., 2019), DistMult (Yang et al., 2014) and ComplEx (Trouillon et al., 2016) and DeepWalk (Perozzi et al., 2014). Deep Walk is a KG embedding technique based on random walks. DeepWalk creates a mapping of entities to a low-dimensional space of features using a random walk strategy. The entity embeddings and the scores for all samples were generated using the implementation by (Hu et al., 2020), which incorporates a multi-layer perceptron with three layers as a predictor. We also compared our models to a Random Forest (RF) based machine learning approach for ADE prediction (Zhao et al., 2018), which uses gene expression as data as well as compound fingerprints.

3.4. Making Models Explainable

From an application perspective it is important to be able to explain which features of a compound influence the model's predictions in each single instance. For this purpose we build on the integrated gradients method (Sundararajan et al., 2017) as implemented in captum.ai (Kokhlikyan et al., 2020). Integrated gradients is an axiomatic attribution method which represents the integral of gradients with respect to inputs along the path from a given baseline to input (Sundararajan et al., 2017). The integrated gradient along the i^{th} dimension from baseline x_0 to input x is defined as

$$\text{IntegratedGrads}_i(x)^{\text{approx}} := (x_i - x_i') \times \int_{k=1}^{m} \frac{\partial F(x' + \frac{k}{m} \times (x - x'))}{\partial x_i} \partial \alpha$$

Equation 8,

with α as a scaling coefficient, m as the number of steps, and F as a function $F\colon R^p \Rightarrow (0,1)$ which represents our MultiGML model. For each predicted link between a drug and a side effect, we calculated the integrated gradients to receive the importances of the individual features. We used n = 500 steps for the approximation method. For the baseline x_0, we used a vector of zeros in case of the drug molecular fingerprint. For the drug morphological (i.e. cell painting assay) as well as gene expression features we employed the overall mean vector as baseline. In a further step, the attributions of the Integrated Gradient analysis were evaluated. For the molecular fingerprint of the drugs we decoded the most important molecular moieties from the bits of the molecular fingerprint using RDKit (Landrum, 2010). A gene ontology enrichment analysis of biological processes was performed on the top 100 positively and negatively attributed genes from the molecular gene expression signature of the drugs using Metascape (Zhou et al., 2019). For the enrichment analysis, all genes in the human genome were used as background, and a *q*-value cut-off of 0.05, a minimum count of 3 and an enrichment factor > 1.5 were chosen. A hypergeometric test was performed and q-values were calculated using the Benjamini-Hochberg procedure (Hochberg & Benjamini, 1990) to account for multiple testing.

3.5. Performance Metrics

We evaluate our models on the independent test set according to area under the ROC curve (AUROC), area under the precision-recall curve (AUPR) and precision among the top k predictions (precision@k). Precision@k were calculated based on a ranking of the models' predicted link probabilities. Due to drastic differences in the number of relation types in the test set, we here report precision@k with k = 1000 for evaluating general link prediction performance, k = 30 for drug - ADE, and k = 100 for gene - phenotype predictions.

4. Discussion

We proposed a novel Graph Machine Learning neural network approach for adverse drug event prediction that combines multi-modal quantitative data with a heterogeneous, multi-relational KG. MultiGML demonstrated excellent prediction performance in comparison to a broad set of competing approaches. Furthermore, we demonstrated that predictions made by our MultiGML method can be explained via the method of integrated gradients and visualization of attention weights. We showed that in this way it is possible to identify biologically plausible mechanisms associated with predicted ADEs. Therefore, our approach could provide valuable information during the early phases of drug development, where it is important to lower the failure risk of later clinical trials. Getting insights into relevant biological mechanisms associated with a high risk could support selection of safe targets. We thus see the value of integrating multimodal data into MultiGML not so much in terms of increase in link prediction performance, but much more with regard to the far better interpretability compared to purely graph topology based techniques.

5. Limitations

Of course, MultiGML is not without limitations: for example, specific feature modalities may be unavailable for some of the entities in the KG. The neighborhood aggregation approach of MultiGML in such a case provides a way to mitigate this issue, because it essentially smoothens features over the neighborhood of a given entity, but that can not perfectly replace missing information. Furthermore, ADEs are in reality also dependent on pharmacodynamic (PD) properties of a compound, including dose, which are currently not considered in our model. Finally, model explanations can only disentangle model predictions, but they do not always point to the right biological cause of an ADE. Due to the versatile model design, MultiGML offers the perspective of applications of link prediction tasks other than the one discussed in this paper, including drug repositioning. Moreover, MultiGML could be used to integrate other or additional data modalities, for example protein and tissue expression and pathology imaging slides. Altogether, we thus see MultiGML as a flexible approach to support important decisions in early drug discovery.

Acknowledgements

We thank Bruce Schultz and Aliaksandr Masny for their support during the project. This work was supported by the Research Center Machine Learning (FZML) of the Fraunhofer Cluster of Excellence Cognitive Internet Technologies CCIT.

Author Contributions

Designed the project: HF, AZ; supervised the work: HF, SM, DDF, AZ, SG; SK and DDF compiled the knowledge graph; SK implemented the models with the help of SM, DDF and AA; SK trained the models with the help of SM; LdL implemented the Random Forest model and SK trained and evaluated the model; SK benchmarked the models; SK, HF, AZ and SG interpreted the results. All authors have read and approved the current version of the manuscript.

Declaration of Interests

DDF received salaries from Enveda Biosciences, and AA from Grünenthal GmbH.

References

Abiola, M., Favier, M., Christodoulou-Vafeiadou, E., Pichard, A.-L., Martelly, I., & Guillet-Deniau, I. (2009). Activation of Wnt/β-Catenin Signaling Increases Insulin Sensitivity through a Reciprocal Regulation of Wnt10b and SREBP-1c in Skeletal Muscle Cells. *PLoS ONE*, *4*(12), e8509. https://doi.org/10.1371/journal.pone.0008509

Akiba, T., Sano, S., Yanase, T., Ohta, T., & Koyama, M. (2019). Optuna: A Next-generation Hyperparameter Optimization Framework. *Proceedings of the 25th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining - KDD '19*, 2623–2631. https://doi.org/10.1145/3292500.3330701

Aronson, J. K. (2015). *Meyler's Side Effects of Drugs: The International Encyclopedia of Adverse Drug Reactions and Interactions*. Elsevier.

Ashburner, M., Ball, C. A., Blake, J. A., Botstein, D., Butler, H., Cherry, J. M., Davis, A. P., Dolinski, K., Dwight, S. S., Eppig, J. T., Harris, M. A., Hill, D. P., Issel-Tarver, L., Kasarskis, A., Lewis, S., Matese, J. C., Richardson, J. E., Ringwald, M., Rubin, G. M., & Sherlock, G. (2000). Gene Ontology: Tool for the unification of biology. *Nature Genetics*, *25*(1), 25–29. https://doi.org/10.1038/75556

Barabási, A.-L., & Oltvai, Z. N. (2004). Network biology: Understanding the cell's functional organization. *Nature Reviews. Genetics*, *5*(2), 101–113. https://doi.org/10.1038/nrg1272

Bartlett, J. D., & Jaanus, S. D. (Eds.). (2008). *Clinical ocular pharmacology* (5th ed). Butterworth-Heinemann/Elsevier.

Beam, A. L., Kompa, B., Schmaltz, A., Fried, I., Weber, G., Palmer, N., Shi, X., Cai, T., & Kohane, I. S. (2020). Clinical Concept Embeddings Learned from Massive Sources of Multimodal Medical Data. *Pacific Symposium on Biocomputing. Pacific Symposium on Biocomputing*, *25*, 295–306.

Bean, D. M., Wu, H., Iqbal, E., Dzahini, O., Ibrahim, Z. M., Broadbent, M., Stewart, R., & Dobson, R. J. B. (2017). Knowledge graph prediction of unknown adverse drug reactions and validation in electronic health records. *Scientific Reports*, *7*(1), Article 1. https://doi.org/10.1038/s41598-017-16674-x

Bergstra, J., Bardenet, R., Bengio, Y., & Kégl, B. (2011). Algorithms for hyper-parameter optimization. *25th Annual Conference on Neural Information Processing Systems (NIPS 2011)*, *24*.

Bodenreider, O. (2004). The Unified Medical Language System (UMLS): Integrating biomedical terminology. *Nucleic Acids Research*, *32*(Database issue), D267–D270. https://doi.org/10.1093/nar/gkh061

Bordes, A., Usunier, N., Garcia-Duran, A., Weston, J., & Yakhnenko, O. (2013). Translating Embeddings for Modeling Multi-relational Data. *Advances in Neural Information Processing Systems*. https://proceedings.neurips.cc/paper/2013/hash/1cecc7a77928ca8133fa24680a88d2f9-Abstract.html

Breit, A., Ott, S., Agibetov, A., & Samwald, M. (2020). OpenBioLink: A benchmarking framework for large-scale biomedical link prediction. *Bioinformatics*, *36*(13), 4097–4098. https://doi.org/10.1093/bioinformatics/btaa274

Bundy, K., Boone, J., & Simpson, C. L. (2021). Wnt Signaling in Vascular Calcification. *Frontiers in Cardiovascular Medicine*, *8*. https://www.frontiersin.org/articles/10.3389/fcvm.2021.708470

Busbridge, D., Sherburn, D., Cavallo, P., & Hammerla, N. Y. (2019). Relational Graph Attention Networks. *ArXiv*. https://doi.org/10.48550/arxiv.1904.05811

Cakir, A., Tuncer, M., Taymaz-Nikerel, H., & Ulucan, O. (2021). Side effect prediction based on drug-induced gene expression profiles and random forest with iterative feature selection. *The Pharmacogenomics Journal*, *21*(6), Article 6. https://doi.org/10.1038/s41397-021-00246-4

Cami, A., Arnold, A., Manzi, S., & Reis, B. (2011). Predicting adverse drug events using pharmacological network models. *Science Translational Medicine*, *3*(114), 114ra127. https://doi.org/10.1126/scitranslmed.3002774

Carss, K. J., Deaton, A. M., Del Rio-Espinola, A., Diogo, D., Fielden, M., Kulkarni, D. A., Moggs, J., Newham, P., Nelson, M. R., Sistare, F. D., Ward, L. D., & Yuan, J. (2022). Using human genetics to improve safety assessment of therapeutics. *Nature Reviews Drug Discovery*, 1–18. https://doi.org/10.1038/s41573-022-00561-w

Cerami, E. G., Gross, B. E., Demir, E., Rodchenkov, I., Babur, O., Anwar, N., Schultz, N., Bader, G. D., & Sander, C. (2011). Pathway Commons, a web resource for biological pathway data. *Nucleic Acids Research*, *39*(Database issue), D685-690. https://doi.org/10.1093/nar/gkq1039

Chan, K.-M., Wu, T.-H., Wu, T.-J., Chou, H.-S., Yu, M.-C., & Lee, W.-C. (2016). Bioinformatics microarray analysis and identification of gene expression profiles associated with cirrhotic liver. *The Kaohsiung Journal of Medical Sciences*, *32*(4), 165–176. https://doi.org/10.1016/j.kjms.2016.03.008

Chen, Z., Peng, B., Ioannidis, V. N., Li, M., Karypis, G., & Ning, X. (2021). *CTKG: A Knowledge Graph for Clinical Trials* (p. 2021.11.04.21265952). medRxiv. https://doi.org/10.1101/2021.11.04.21265952

Dasgupta, S., Jayagopal, A., Hong, A. L. J., Mariappan, R., & Rajan, V. (2021). Adverse Drug Event Prediction Using Noisy Literature-Derived Knowledge Graphs: Algorithm Development and Validation. *JMIR Medical Informatics*, *9*(10), e32730. https://doi.org/10.2196/32730

Deftereos, S. N., Andronis, C., Friedla, E. J., Persidis, A., & Persidis, A. (2011). Drug repurposing and adverse event prediction using high-throughput literature analysis. *Wiley Interdisciplinary Reviews. Systems Biology and Medicine*, *3*(3), 323–334. https://doi.org/10.1002/wsbm.147

Denny, J. C., Ritchie, M. D., Basford, M. A., Pulley, J. M., Bastarache, L., Brown-Gentry, K., Wang, D., Masys, D. R., Roden, D. M., & Crawford, D. C. (2010). PheWAS: demonstrating the feasibility of a phenome-wide scan to discover gene-disease associations. *Bioinformatics*, *26*(9), 1205–1210. https://doi.org/10.1093/bioinformatics/btq126

Duan, Q., Flynn, C., Niepel, M., Hafner, M., Muhlich, J. L., Fernandez, N. F., Rouillard, A. D., Tan, C. M., Chen, E. Y., Golub, T. R., Sorger, P. K., Subramanian, A., & Ma'ayan, A. (2014). LINCS Canvas Browser: Interactive web app to query, browse and interrogate LINCS L1000 gene expression signatures. *Nucleic Acids Research*, *42*(Web Server issue), W449–W460. https://doi.org/10.1093/nar/gku476

Duffy, Á., Verbanck, M., Dobbyn, A., Won, H.-H., Rein, J. L., Forrest, I. S., Nadkarni, G., Rocheleau, G., & Do, R. (2020). Tissue-specific genetic features inform prediction of drug side effects in clinical trials. *Science Advances*, *6*(37), eabb6242. https://doi.org/10.1126/sciadv.abb6242

Duvenaud, D., Maclaurin, D., Aguilera-Iparraguirre, J., Gómez-Bombarelli, R., Hirzel, T., Aspuru-Guzik, A., & Adams, R. P. (2015). Convolutional Networks on Graphs for Learning Molecular Fingerprints. *ArXiv*. https://doi.org/10.48550/arxiv.1509.09292

Fokoue, A., Sadoghi, M., Hassanzadeh, O., & Zhang, P. (2016). Predicting Drug-Drug Interactions Through Large-Scale Similarity-Based Link Prediction. In H. Sack, E. Blomqvist, M. d'Aquin, C. Ghidini, S. P. Ponzetto, & C. Lange (Eds.), *The Semantic Web. Latest Advances and New Domains* (pp. 774–789). Springer International Publishing. https://doi.org/10.1007/978-3-319-34129-3_47

Foulquier, S., Daskalopoulos, E. P., Lluri, G., Hermans, K. C. M., Deb, A., & Blankesteijn, W. M. (2018). WNT Signaling in Cardiac and Vascular Disease. *Pharmacological Reviews*, *70*(1), 68–141. https://doi.org/10.1124/pr.117.013896

Fout, A. M. (2016). *Protein interface prediction using graph convolutional networks* [THESIS.DOCTORAL]. Colorado State University. Libraries.

Freemon, F. R. (1967). Unusual neurotoxicity of kanamycin. *JAMA*, *200*(5), 410. https://doi.org/10.1001/jama.1967.03120180098021

Gao, K., Ding, D., Sun, H., Roth, J., & Salvi, R. (2017). Kanamycin damages early postnatal, but not adult spiral ganglion neurons. *Neurotoxicity Research*, *32*(4), 603–613. https://doi.org/10.1007/s12640-017-9773-2

Gene Ontology Consortium. (2021). The Gene Ontology resource: Enriching a GOld mine. *Nucleic Acids Research*, *49*(D1), D325–D334. https://doi.org/10.1093/nar/gkaa1113

George, S. J. (2008). Wnt Pathway. *Arteriosclerosis, Thrombosis, and Vascular Biology*, *28*(3), 400–402. https://doi.org/10.1161/ATVBAHA.107.160952

Grover, A., & Leskovec, J. (2016). *Node2vec*.

Halabe, A., Lifschitz, B. M., & Azuri, J. (2000). Liver damage due to alendronate. *The New England Journal of Medicine*, *343*(5), 365–366. https://doi.org/10.1056/NEJM200008033430512

Harding, S. D., Sharman, J. L., Faccenda, E., Southan, C., Pawson, A. J., Ireland, S., Gray, A. J. G., Bruce, L., Alexander, S. P. H., Anderton, S., Bryant, C., Davenport, A. P., Doerig, C., Fabbro, D., Levi-Schaffer, F., Spedding, M., Davies, J. A., & NC-IUPHAR. (2018). The IUPHAR/BPS Guide to PHARMACOLOGY in 2018: Updates and expansion to encompass the new guide to IMMUNOPHARMACOLOGY. *Nucleic Acids Research*, *46*(D1), D1091–D1106. https://doi.org/10.1093/nar/gkx1121

Heysell, S. K., Ahmed, S., Rahman, M. T., Akhanda, M. W., Gleason, A. T., Ebers, A., Houpt, E. R., & Banu, S. (2018). Hearing loss with kanamycin treatment for multidrug-resistant tuberculosis in Bangladesh. *European Respiratory Journal*, *51*(3). https://doi.org/10.1183/13993003.01778-2017

Himmelstein, D., Brueggeman, L., & Baranzini, S. (2016). *Consensus signatures for LINCS L1000 perturbations*.

https://doi.org/f3mqvs

Himmelstein, D. S., Lizee, A., Hessler, C., Brueggeman, L., Chen, S. L., Hadley, D., Green, A., Khankhanian, P., & Baranzini, S. E. (2017). Systematic integration of biomedical knowledge prioritizes drugs for repurposing. *ELife*, *6*. https://doi.org/10.7554/eLife.26726

Himmelstein, Daniel, C., Caty. (2015, March 26). Computing consensus transcriptional profiles for LINCS L1000 perturbations. *ThinkLab*. https://doi.org/f3mqwc

Hochberg, Y., & Benjamini, Y. (1990). More powerful procedures for multiple significance testing. *Statistics in Medicine*, *9*(7), 811–818. https://doi.org/10.1002/sim.4780090710

Hoofnagle, J. H., Serrano, J., Knoben, J. E., & Navarro, V. J. (2013). LiverTox: A website on drug-induced liver injury. *Hepatology*, *57*(3), 873–874. https://doi.org/10.1002/hep.26175

Hu, W., Fey, M., Zitnik, M., Dong, Y., Ren, H., Liu, B., Catasta, M., & Leskovec, J. (2020). Open Graph Benchmark: Datasets for Machine Learning on Graphs. *ArXiv*. https://doi.org/10.48550/arxiv.2005.00687

Jassal, B., Matthews, L., Viteri, G., Gong, C., Lorente, P., Fabregat, A., Sidiropoulos, K., Cook, J., Gillespie, M., Haw, R., Loney, F., May, B., Milacic, M., Rothfels, K., Sevilla, C., Shamovsky, V., Shorser, S., Varusai, T., Weiser, J., … D'Eustachio, P. (2020). The reactome pathway knowledgebase. *Nucleic Acids Research*, *48*(D1), D498–D503. https://doi.org/10.1093/nar/gkz1031

Joshi, P., V, M., & Mukherjee, A. (2022). A knowledge graph embedding based approach to predict the adverse drug reactions using a deep neural network. *Journal of Biomedical Informatics*, *132*, 104122. https://doi.org/10.1016/j.jbi.2022.104122

Kanehisa, M., & Goto, S. (2000). KEGG: Kyoto encyclopedia of genes and genomes. *Nucleic Acids Research*, *28*(1), 27–30. https://doi.org/10.1093/nar/28.1.27

Kanehisa, M., Sato, Y., Kawashima, M., Furumichi, M., & Tanabe, M. (2016). KEGG as a reference resource for gene and protein annotation. *Nucleic Acids Research*, *44*(D1), D457–D462. https://doi.org/10.1093/nar/gkv1070

Karim, Md. R., Cochez, M., Jares, J. B., Uddin, M., Beyan, O., & Decker, S. (2019). Drug-Drug Interaction Prediction Based on Knowledge Graph Embeddings and Convolutional-LSTM Network. *Proceedings of the 10th ACM International Conference on Bioinformatics, Computational Biology and Health Informatics*, 113–123. https://doi.org/10.1145/3307339.3342161

Kerrien, S., Aranda, B., Breuza, L., Bridge, A., Broackes-Carter, F., Chen, C., Duesbury, M., Dumousseau, M., Feuermann, M., Hinz, U., Jandrasits, C., Jimenez, R. C., Khadake, J., Mahadevan, U., Masson, P., Pedruzzi, I., Pfeiffenberger, E., Porras, P., Raghunath, A., … Hermjakob, H. (2012). The IntAct molecular interaction database in 2012. *Nucleic Acids Research*, *40*(D1), D841–D846. https://doi.org/10.1093/nar/gkr1088

Kipf, T. N., & Welling, M. (2017). *Semi-Supervised Classification with Graph Convolutional Networks* (arXiv:1609.02907). arXiv. https://doi.org/10.48550/arXiv.1609.02907

Kokhlikyan, N., Miglani, V., Martin, M., Wang, E., Alsallakh, B., Reynolds, J., Melnikov, A., Kliushkina, N., Araya, C., Yan, S., & Reblitz-Richardson, O. (2020). Captum: A unified and generic model interpretability library for PyTorch. *ArXiv*. https://doi.org/10.48550/arxiv.2009.07896

Kuhn, M., Letunic, I., Jensen, L. J., & Bork, P. (2016). The SIDER database of drugs and side effects. *Nucleic Acids Research*, *44*(D1), D1075-9. https://doi.org/10.1093/nar/gkv1075

Kwak, H., Lee, M., Yoon, S., Chang, J., Park, S., & Jung, K. (2020). *Drug-disease Graph: Predicting Adverse Drug Reaction Signals via Graph Neural Network with Clinical Data* (arXiv:2004.00407). arXiv. http://arxiv.org/abs/2004.00407

Landrum, G. (2010). *RDKit: Open-source cheminformatics*. https://www.rdkit.org/

Lemsara, A., Ouadfel, S., & Fröhlich, H. (2020). PathME: Pathway based multi-modal sparse autoencoders for clustering of patient-level multi-omics data. *BMC Bioinformatics*, *21*(1), 146. https://doi.org/10.1186/s12859-020-3465-2

Li, L., Jamieson, K., DeSalvo, G., Rostamizadeh, A., & Talwalkar, A. (2016). Hyperband: A Novel Bandit-Based Approach to Hyperparameter Optimization. *ArXiv*. https://doi.org/10.48550/arxiv.1603.06560

Lin, J., Kuang, Q., Li, Y., Zhang, Y., Sun, J., Ding, Z., & Li, M. (2013). Prediction of adverse drug reactions by a network based external link prediction method. *Analytical Methods*, *5*(21), 6120–6127. https://doi.org/10.1039/C3AY41290C

Liu, M., Cai, R., Hu, Y., Matheny, M. E., Sun, J., Hu, J., & Xu, H. (2014). Determining molecular predictors of adverse drug reactions with causality analysis based on structure learning. *Journal of the American Medical Informatics Association*, *21*(2), 245–251. https://doi.org/10.1136/amiajnl-2013-002051

Luo, Y., Liu, Q., Wu, W., Li, F., & Bo, X. (2014). Predicting drug side effects based on link prediction in bipartite network. *2014 7th International Conference on Biomedical Engineering and Informatics*, 729–733. https://doi.org/10.1109/BMEI.2014.7002869

Naiman, J. G., Sakurai, K., & Martin, J. D. (1965). The antagonism of calcium and neostigmine to kanamycin-induced neuromuscular paralysis. *Journal of Surgical Research*, *5*(7), 323–328. https://doi.org/10.1016/S0022-4804(65)80077-4

Nebeker, J. R., Barach, P., & Samore, M. H. (2004). Clarifying adverse drug events: A clinician's guide to terminology, documentation, and reporting. *Annals of Internal Medicine*, *140*(10), 795–801. https://doi.org/10.7326/0003-4819-140-10-200405180-00009

Nguyen, P. A., Born, D. A., Deaton, A. M., Nioi, P., & Ward, L. D. (2019). Phenotypes associated with genes encoding drug targets are predictive of clinical trial side effects. *Nature Communications*, *10*(1), 1579.

https://doi.org/10.1038/s41467-019-09407-3

Niu, Y., & Zhang, W. (2017). Quantitative prediction of drug side effects based on drug-related features. *Interdiscip. Sci.*, *9*(3), 434–444.

Ochoa, D., Hercules, A., Carmona, M., Suveges, D., Gonzalez-Uriarte, A., Malangone, C., Miranda, A., Fumis, L., Carvalho-Silva, D., Spitzer, M., Baker, J., Ferrer, J., Raies, A., Razuvayevskaya, O., Faulconbridge, A., Petsalaki, E., Mutowo, P., Machlitt-Northen, S., Peat, G., … McDonagh, E. M. (2021). Open Targets Platform: Supporting systematic drug–target identification and prioritisation. *Nucleic Acids Research*, *49*(D1), D1302–D1310. https://doi.org/10.1093/nar/gkaa1027

Oughtred, R., Rust, J., Chang, C., Breitkreutz, B.-J., Stark, C., Willems, A., Boucher, L., Leung, G., Kolas, N., Zhang, F., Dolma, S., Coulombe-Huntington, J., Chatr-Aryamontri, A., Dolinski, K., & Tyers, M. (2021). The BioGRID database: A comprehensive biomedical resource of curated protein, genetic, and chemical interactions. *Protein Science: A Publication of the Protein Society*, *30*(1), 187–200. https://doi.org/10.1002/pro.3978

Pauwels, E., Stoven, V., & Yamanishi, Y. (2011). Predicting drug side-effect profiles: A chemical fragment-based approach. *BMC Bioinformatics*, *12*, 169. https://doi.org/10.1186/1471-2105-12-169

Pechlivani, N., & Ajjan, R. A. (2018). Thrombosis and Vascular Inflammation in Diabetes: Mechanisms and Potential Therapeutic Targets. *Frontiers in Cardiovascular Medicine*, *5*. https://doi.org/10.3389/fcvm.2018.00001

Perozzi, B., Al-Rfou, R., & Skiena, S. (2014). DeepWalk: Online learning of social representations. *Proceedings of the 20th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining - KDD '14*, 701–710. https://doi.org/10.1145/2623330.2623732

Piazza, G., Goldhaber, S. Z., Kroll, A., Goldberg, R. J., Emery, C., & Spencer, F. A. (2012). Venous Thromboembolism in Patients with Diabetes Mellitus. *The American Journal of Medicine*, *125*(7), 709–716. https://doi.org/10.1016/j.amjmed.2011.12.004

Piñero González, J., Ramírez Anguita, J. M., Saüch Pitarch, J., Ronzano, F., Centeno, E., Sanz, F., & Furlong, L. I. (2020). *The DisGeNET knowledge platform for disease genomics: 2019 update*. https://doi.org/10.1093/nar/gkz1021

Pittinger, C. B., Eryasa, Y., & Adamson, R. (1970). Antibiotic-induced paralysis. *Anesthesia and Analgesia*, *49*(3), 487–501.

Rebele, T., Suchanek, F., Hoffart, J., Biega, J., Kuzey, E., & Weikum, G. (2016). YAGO: A Multilingual Knowledge Base from Wikipedia, Wordnet, and Geonames. In P. Groth, E. Simperl, A. Gray, M. Sabou, M. Krötzsch, F. Lecue, F. Flöck, & Y. Gil (Eds.), *The semantic web – ISWC 2016* (Vol. 9982, pp. 177–185). Springer International Publishing. https://doi.org/10.1007/978-3-319-46547-0_19

Reid, I. R., & Siris, E. (1999). Alendronate in the treatment of Paget's disease of bone. *International Journal of Clinical Practice. Supplement*, *101*, 62–66.

Rhee, S., Seo, S., & Kim, S. (2018). Hybrid approach of relation network and localized graph convolutional filtering for breast cancer subtype classification. In J. Lang (Ed.), *Proceedings of the Twenty-Seventh International Joint Conference on Artificial Intelligence* (pp. 3527–3534). International Joint Conferences on Artificial Intelligence Organization. https://doi.org/10.24963/ijcai.2018/490

Rives, A., Meier, J., Sercu, T., Goyal, S., Lin, Z., Liu, J., Guo, D., Ott, M., Zitnick, C. L., Ma, J., & Fergus, R. (2021). Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *Proceedings of the National Academy of Sciences of the United States of America*, *118*(15). https://doi.org/10.1073/pnas.2016239118

Rogers, D., & Hahn, M. (2010). Extended-connectivity fingerprints. *Journal of Chemical Information and Modeling*, *50*(5), 742–754. https://doi.org/10.1021/ci100050t

Scarselli, F., Gori, M., Tsoi, A. C., Hagenbuchner, M., & Monfardini, G. (2009). The graph neural network model. *IEEE Transactions on Neural Networks*, *20*(1), 61–80. https://doi.org/10.1109/TNN.2008.2005605

Schlichtkrull, M., Kipf, T. N., Bloem, P., van den Berg, R., Titov, I., & Welling, M. (2018). Modeling Relational Data with Graph Convolutional Networks. In A. Gangemi, R. Navigli, M.-E. Vidal, P. Hitzler, R. Troncy, L. Hollink, A. Tordai, & M. Alam (Eds.), *The Semantic Web* (pp. 593–607). Springer International Publishing. https://doi.org/10.1007/978-3-319-93417-4_38

Schotland, P., Racz, R., Jackson, D. B., Soldatos, T. G., Levin, R., Strauss, D. G., & Burkhart, K. (2021). Target Adverse Event Profiles for Predictive Safety in the Postmarket Setting. *Clinical Pharmacology & Therapeutics*, *109*(5), 1232–1243. https://doi.org/10.1002/cpt.2074

Schreiber, S. (2014). *Cell Painting morphological profiling assay*. http://identifiers.org/lincs.data/LDS-1195

Schuster, D., Laggner, C., & Langer, T. (2005). Why drugs fail—A study on side effects in new chemical entities. *Current Pharmaceutical Design*, *11*(27), 3545–3559. https://doi.org/10.2174/138161205774414510

Sun, Z., Deng, Z.-H., Nie, J.-Y., & Tang, J. (2019). RotatE: Knowledge Graph Embedding by Relational Rotation in Complex Space. *ArXiv*. https://doi.org/10.48550/arxiv.1902.10197

Sundararajan, M., Taly, A., & Yan, Q. (2017). *Axiomatic Attribution for Deep Networks* (arXiv:1703.01365). arXiv. http://arxiv.org/abs/1703.01365

Szklarczyk, D., Gable, A. L., Lyon, D., Junge, A., Wyder, S., Huerta-Cepas, J., Simonovic, M., Doncheva, N. T., Morris, J. H., Bork, P., Jensen, L. J., & Mering, C. von. (2019). STRING v11: Protein-protein association networks with increased coverage, supporting functional discovery in genome-wide experimental datasets. *Nucleic Acids Research*, *47*(D1), D607–D613. https://doi.org/10.1093/nar/gky1131

Takarabe, M., Kotera, M., Nishimura, Y., Goto, S., & Yamanishi, Y. (2012). Drug target prediction using adverse

event report systems: A pharmacogenomic approach. *Bioinformatics*, *28*(18), i611–i618. https://doi.org/10.1093/bioinformatics/bts413

Tatonetti, N. P., Ye, P. P., Daneshjou, R., & Altman, R. B. (2012). Data-driven prediction of drug effects and interactions. *Science Translational Medicine*, *4*(125), 125ra31. https://doi.org/10.1126/scitranslmed.3003377

Trouillon, T., Welbl, J., Riedel, S., Gaussier, É., & Bouchard, G. (2016). Complex Embeddings for Simple Link Prediction. *ArXiv*. https://doi.org/10.48550/arxiv.1606.06357

Veličković, P., Cucurull, G., Casanova, A., Romero, A., Liò, P., & Bengio, Y. (2017). Graph Attention Networks. *ArXiv*. https://doi.org/10.48550/arxiv.1710.10903

Vilar, S., Harpaz, R., Santana, L., Uriarte, E., & Friedman, C. (2012). Enhancing Adverse Drug Event Detection in Electronic Health Records Using Molecular Structure Similarity: Application to Pancreatitis. *PLOS ONE*, *7*(7), e41471. https://doi.org/10.1371/journal.pone.0041471

Vrandečić, D., & Krötzsch, M. (2014). Wikidata: A Free Collaborative Knowledgebase. *Communications of the ACM*, *57*(10), 78–85. https://doi.org/10.1145/2629489

Wang, C., Pan, S., Long, G., Zhu, X., & Jiang, J. (2017). MGAE: marginalized graph autoencoder for graph clustering. *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management - CIKM '17*, 889–898. https://doi.org/10.1145/3132847.3132967

Wang, Y., Wang, J., Yang, J., Kang, J., Xue, F., Chang, S., Ji, H., Zang, H., Zhou, X., Wang, G., Fan, W., Yan, X., Guo, J., Ren, X., & Tian, J. (2021). Study on Protection of Human Umbilical Vein Endothelial Cells from Amiodarone-Induced Damage by Intermedin through Activation of Wnt/β-Catenin Signaling Pathway. *Oxidative Medicine and Cellular Longevity*, *2021*, 8889408. https://doi.org/10.1155/2021/8889408

Wang, Z., Clark, N. R., & Ma'ayan, A. (2016). Drug-induced adverse events prediction with the LINCS L1000 data. *Bioinformatics*, *32*(15), 2338–2345. https://doi.org/10.1093/bioinformatics/btw168

Wang, Z.-C., Gao, Q., Shi, J.-Y., Guo, W.-J., Yang, L.-X., Liu, X.-Y., Liu, L.-Z., Ma, L.-J., Duan, M., Zhao, Y.-J., Wu, Y.-N., Gao, D.-M., Wang, X.-Y., Shi, G.-M., Ding, Z.-B., Ke, A.-W., Tang, Q.-Q., Cao, Y., Zhou, J., & Fan, J. (2015). Protein tyrosine phosphatase receptor S acts as a metastatic suppressor in hepatocellular carcinoma by control of epithermal growth factor receptor–induced epithelial-mesenchymal transition. *Hepatology*, *62*(4), 1201–1214. https://doi.org/10.1002/hep.27911

Wishart, D. S., Feunang, Y. D., Guo, A. C., Lo, E. J., Marcu, A., Grant, J. R., Sajed, T., Johnson, D., Li, C., Sayeeda, Z., Assempour, N., Iynkkaran, I., Liu, Y., Maciejewski, A., Gale, N., Wilson, A., Chin, L., Cummings, R., Le, D., … Wilson, M. (2018). DrugBank 5.0: A major update to the DrugBank database for 2018. *Nucleic Acids Research*, *46*(D1), D1074–D1082. https://doi.org/10.1093/nar/gkx1037

Wu, Y., Gao, M., Zeng, M., Zhang, J., & Li, M. (2022). BridgeDPI: A Novel Graph Neural Network for Predicting Drug-Protein Interactions. *Bioinformatics*. https://doi.org/10.1093/bioinformatics/btac155

Xuan, P., Wang, M., Liu, Y., Wang, D., Zhang, T., & Nakaguchi, T. (2022). Integrating specific and common topologies of heterogeneous graphs and pairwise attributes for drug-related side effect prediction. *Briefings in Bioinformatics*, *23*(3), bbac126. https://doi.org/10.1093/bib/bbac126

Yamanishi, Y., Pauwels, E., & Kotera, M. (2012). Drug side-effect prediction based on the integration of chemical and biological spaces. *Journal of Chemical Information and Modeling*, *52*(12), 3284–3292. https://doi.org/10.1021/ci2005548

Yang, B., Yih, W., He, X., Gao, J., & Deng, L. (2014). Embedding Entities and Relations for Learning and Inference in Knowledge Bases. In *ArXiv e-prints*. https://ui.adsabs.harvard.edu/abs/2014arXiv1412.6575Y

Yu, L., Cheng, M., Qiu, W., Xiao, X., & Lin, W. (2022). idse-HE: Hybrid embedding graph neural network for drug side effects prediction. *Journal of Biomedical Informatics*, *131*, 104098. https://doi.org/10.1016/j.jbi.2022.104098

Zarin, D. A., Tse, T., Williams, R. J., Califf, R. M., & Ide, N. C. (2011). The ClinicalTrials.gov Results Database—Update and Key Issues. *The New England Journal of Medicine*, *364*(9), 852–860. https://doi.org/10.1056/NEJMsa1012065

Zhang, W., Liu, F., Luo, L., & Zhang, J. (2015). Predicting drug side effects by multi-label learning and ensemble learning. *BMC Bioinformatics*, *16*, 365. https://doi.org/10.1186/s12859-015-0774-y

Zhangyuan, G., Yin, Y., Zhang, W., Yu, W., Jin, K., Wang, F., Huang, R., Shen, H., Wang, X., & Sun, B. (2018). Prognostic Value of Phosphotyrosine Phosphatases in Hepatocellular Carcinoma. *Cellular Physiology and Biochemistry*, *46*(6), 2335–2346. https://doi.org/10.1159/000489625

Zhao, X., Chen, L., & Lu, J. (2018). A similarity-based method for prediction of drug side effects with heterogeneous information. *Mathematical Biosciences*, *306*, 136–144. https://doi.org/10.1016/j.mbs.2018.09.010

Zheng, S., Rao, J., Song, Y., Zhang, J., Xiao, X., Fang, E. F., Yang, Y., & Niu, Z. (2020). PharmKG: a dedicated knowledge graph benchmark for bomedical data mining. *Brief. Bioinform.*

Zhou, Y., Zhou, B., Pache, L., Chang, M., Khodabakhshi, A. H., Tanaseichuk, O., Benner, C., & Chanda, S. K. (2019). Metascape provides a biologist-oriented resource for the analysis of systems-level datasets. *Nature Communications*, *10*(1), 1523. https://doi.org/10.1038/s41467-019-09234-6

Zitnik, M., Agrawal, M., & Leskovec, J. (2018). Modeling polypharmacy side effects with graph convolutional networks. *Bioinformatics*, *34*(13), i457–i466. https://doi.org/10.1093/bioinformatics/bty294