# A stochastic world model on gravity for stability inference

**Authors: Taicheng Huang[1], Jia Liu[1*]**

[1]Department of Psychology and Tsinghua Laboratory of Brain & Intelligence,

Tsinghua University, Beijing, China.

* Correspondence to: liujiathu@tsinghua.edu.cn (J. Liu).

## Abstract

The fact that objects without proper support will fall to the ground is not only a
natural phenomenon, but also common sense in mind. Previous studies suggest that
humans may infer objects' stability through a world model that performs mental
simulations with *a priori* knowledge of gravity acting upon the objects. Here we
measured participants' sensitivity to gravity to investigate how the world model
works. We found that the world model on gravity was not a faithful replica of the
physical laws, but instead encoded gravity's vertical direction as a Gaussian
distribution. The world model with this stochastic feature fit nicely with participants'
subjective sense of objects' stability and explained the illusion that taller objects are
perceived as more likely to fall. Furthermore, a computational model with
reinforcement learning revealed that the stochastic characteristic likely originated
from experience-dependent comparisons between predictions formed by internal
simulations and the realities observed in the external world, which illustrated the
ecological advantage of stochastic representation in balancing accuracy and speed for
efficient stability inference. The stochastic world model on gravity provides an
example of how *a priori* knowledge of the physical world is implemented in mind that
helps humans operate flexibly in open-ended environments.

## Significance Statement

Humans possess an exceptional capacity for inferring the stability of objects, a skill
that has been crucial to the survival of our predecessors and continues to facilitate our
daily interactions with the natural world. The present study elucidates that our
representation of gravitational direction adheres to a Gaussian distribution, with the

vertical orientation as the maximum likelihood. This stochastic representation is likely to have originated from our interactions with the physical world, conferring an ecological advantage of balancing accuracy with speed. Therefore, the world model on gravity in the mind is a distorted replica of the natural world, enabling adaptive functionality in open-ended environments and thus shedding light on developing machines imbued with embodied intelligence.

## Introduction

About two thousand years ago, Confucius warned his disciples that a wise man should not stand next to a collapsing wall. We, wise or not, can easily judge whether a wall is stable or collapsing in a fraction of a second (Battaglia et al., 2013; Kubricht et al., 2017; McCloskey, 1983). This astonishing performance is unlikely to have been achieved by previous visual experience alone. Taking a stack consisting of ten blocks as an example (Fig. 1), we can quickly report its stability with a satisfactory accuracy of 70% on average (Bear et al., 2021; Zhang et al., 2016), but the universal cardinality of possible configurations is at least $1.14 \times 10^{50}$ (Supplementary Figure 1), which is much larger than the total number of sand grains on Earth (est. $7.5 \times 10^{18}$) (Blatner, 2013). Contrary to this intuition, four-month-old infants, who have little visual experience of the physical world, expect a box to fall if it loses contact with a support platform (Baillargeon, 2004, 1994). Our minds may therefore have devised a mechanism that differs from the widely used discriminative approach in artificial neural networks, which relies on the extensive visual experience of objects and feedback about their stability (Bear et al., 2021; Li et al., 2016; Zhang et al., 2016).

Indeed, both behavioral and neuroimaging studies have suggested that humans possess *a priori* knowledge of Newton's law of physics in the mind. For example, infants as young as seven months expect a downward-moving object to accelerate and an upward-moving object to decelerate (Friedman, 2002; Kim and Spelke, 1999), and adults can estimate the remaining time to catch a moving ball (McIntyre et al., 2001; Zago and Lacquaniti, 2005) even in the absence of visual information (Lacquaniti and Maioli, 1989; Zago et al., 2009). Further fMRI studies have revealed the parieto-insular vestibular cortex in the brain as the neural basis for gravity-based stability inference, suggesting that this knowledge is encapsulated as a cognitive module (Fischer et al., 2016; Indovina et al., 2005; Pramod et al., 2022). Accordingly, our brain is proposed as a set of generative machines that actively predict future events of the ever-changing physical world through mental simulation with *a priori* knowledge acting upon the world (Battaglia et al., 2013; Hegarty, 2004; Huang and Rao, 2011; Tenenbaum et al., 2011; Ullman et al., 2017). For this reason, the generative machine is also called the world model (Land, 2014; Tenenbaum et al., 2011).

Recently, the idea of the world model has become popular to explain the predictive nature of the brain (Friston et al., 2021) and to improve the generality and

robustness of the artificial neural networks (Matsuo et al., 2022). However, how *a*
*priori* knowledge is implemented in the world model remains to be determined. A
prevailing theory suggests that the world model in the brain accurately mirrors the
physical laws of the world (Allen et al., 2020; Battaglia et al., 2013; Zhou et al., 2022).
For example, the direction of gravity encoded in the world model, a critical factor in
stability inference, is assumed to be straight downward, aligning with its
manifestation in the physical world. To explain the phenomenon that tall and thin
objects are subjectively perceived as more unstable compared to short and fat ones
(Supplementary Figure 2), external noise, such as imperfect perception and assumed
external forces, is introduced to influence the output of the model. However, when the
brain actively transforms sensory data into cognitive understanding, these data can
become distorted (Kriegeskorte and Douglas, 2019; Naselaris et al., 2011), hereby
introducing uncertainty into the representation of gravity's direction. In this scenario,
the world model inherently incorporates uncertainty, eliminating the need for
additional external noise to explain the inconsistency between subjective perceptions
of stability and the actual stability of objects. Note that this distinction of these two
theories is nontrivial: the former model implies a deterministic representation of the
external world, while the latter suggests a stochastic approach. Here, we investigated
these two alternative hypotheses regarding the construction of the world model in the
brain by examining how gravity's direction is represented in the world model when
participants judged object stability. Here, we investigated these two alternative
hypotheses for the construction of the world model in the brain by examining how
gravity's direction was represented in the world model when participants judged the
stability of objects.

To do this, we measured participants' sensitivity to gravity's direction in a
stability inference task (Battaglia et al., 2013) and found that gravity's direction was
encoded in a Gaussian distribution, with the vertical direction as the maximum
likelihood. This stochastic parameter was then built into the world model to simulate
the displacement of blocks in a stack under the force of gravity, and the simulation
result fits nicely with participants' judgment of stacks' stability and explains the daily
illusion that taller objects are perceived as more likely to fall. A computational model
with a reinforcement learning algorithm was devised to reveal its origin through
interactions with the physical world. Finally, we explored the ecological advantage of
the stochastic feature of the world model.

110
111

112
113

## Results

## The direction of gravity in the world model

The direction of gravity is perpendicular to the ground surface. Here, we first tested humans' sensitivity to gravity's direction to investigate how faithfully our gravity is represented in the world model compared to gravity in the physical world. To do this, we used Pybullet (Coumans and Bai, 2016), a forward physics simulator, to manipulate gravity's direction. Then, we asked the participants to judge whether the collapse trajectories of unstable stacks were normal (Fig 1a, Supplementary Movie S1). The direction of simulated gravity was measured by a parameter pair $(\theta, \varphi)$ (Fig 1b), which determines the deviation of the direction of simulated gravity from the direction of gravity in the physical world. Specifically, $\theta$ is the vertical component of the direction that affects the degree of collapse, and $\varphi$ is the horizontal component that determines the orientation of collapse. We collected participants' judgment of the normality of collapse trajectories while varying $\theta$ from 0 to 45$^\text{o}$ and $\varphi$ from 0$^\text{o}$ to 360$^\text{o}$ across the force space, and the confidence level of the judgment for each angle pair was used to index participants' sensitivity to gravity's direction (Fig 1c). As expected, when $\theta$ is equal to 0 (i.e., the direction of the simulated gravity is the direction of the natural gravity), the participants were likely to report that the collapse trajectory was normal (accuracy: 91.0%, STD: 8.0%). Then, the critical question is how participants' subjective sense of the normal degree of collapse trajectories changes as a function of $\theta$. If our world model on gravity is a faithful replica of the physical reality, we should expect the immediate detection of abnormality when $\theta$ is away from 0.

**Fig 1. Gravity's direction in the world model.** a) The design of the behavioral experiment. Left: A

rotating camera was used to rotate a stack 360° to display the 3-dimensional appearance of the

configuration. Middle: Gravity's direction was randomly sampled from a spherical surface. Right: The

physics simulator simulated the collapse trajectory of the stack under this selected direction, and

participants reported whether the collapse trajectory was normal. b) The spherical surface of gravity's

direction was determined by two parameters    and    . c) The procedure of calculating participants'

confidence level about normal trajectory as the function of angle pairs. Left: Each cell represents the

response of normal trajectory for an angle pair within a run. Middle: Responses for unsampled pairs

were interpolated with the averaged responses along    . Right:  The confidence level for each angle pair

was calculated by averaging responses across runs and participants. d) Left: Gravity's direction

encoded in the world model follows a Gaussian distribution with the vertical direction as the maximum

likelihood. Note that the confidence level for    > 0 was sampled from                    , and for    < 0

was sampled from                    . Right: The sphere represents the space of gravity's direction, with

two poles pointing upward and downward, respectively. Each dot in the sphere represents one angle

pair, and the color on a dot indicates the likelihood that the collapse trajectory under this gravity

direction was judged normal. e) In a new setting, gravity's direction is reversed. Left: An example

collapse trajectory when gravity's direction was upward. Right: A trajectory when the direction was

away from the vertical upward. f) Gravity's direction encoded in the world model when gravity's

direction in the physical world was reversed. Error bar: standard error.

Contrary to this intuition, the subjective sense of the abnormality was not

immediately apparent as $\theta$ moved away from 0; instead, the confidence level of

reporting normal trajectories decreased gradually as a function of $\theta$, which was the

best fit by a Gaussian function with $\sigma = 19.9$ (Fig. 1d left). That is, the participants

were 50.9% confident in reporting a normal collapse trajectory when the vertical

offset of $\theta$ was 19.9°. In addition, accuracy in detecting the abnormality was not

affected by $\varphi$ (Supplementary Figure 3), consistent with the uniformly distributed

gravitational field in the physical world. This pattern was observed for all participants

tested, with $\sigma$ varying from 11.1 to 37.1 (Supplementary Figure 3), and remained

unchanged with the addition of a wall on one side to block potential external

disturbances from wind (Supplementary Figure 4). Therefore, the world model on

gravity is unlikely to be a faithful replica of the physical world; instead, it encodes

gravity's direction as a Gaussian distribution with the vertical direction as the

maximum likelihood (Fig 1d right).

To further test whether the world model on gravity, once established, is

encapsulated from visual experience and task context, we inverted the virtual

environment upside down with gravity's direction pointing upward, and then asked

the same group of participants to judge whether collapse trajectories were normal (Fig

1e, see Supplementary Movie S2). We found that the confidence level also decreased

gradually as a function of $\theta$ (Fig. 1f, $\sigma = 17.2$; Supplementary Figure 5 for each

participant), which was not significantly different from that in the environment with

gravity pointing downward. Indeed, each participant's $\sigma$ in the upright condition was

in high agreement with the $\sigma$ in the upside-down condition (r = 0.91, p < 0.01). That

is, the visual experience and task context apparently did not cognitively penetrate

humans' world model on gravity, suggesting that it is likely encapsulated as a

cognitive module.

How does the stochastic gravity's direction in the world model affect our

inference on objects' stability? To answer this question, we recruited an independent

group of participants to estimate the stability of 60 stacks of different configurations

(Fig 2a), half of which were stable. During the experiment, the participants were

required to judge how stable each stack was on a 0-7 scale without feedback, which

was used to index their subjective sense about stacks' stability. Two world models

were constructed for comparison. One world model was equipped with a vertically

downward direction of gravity without any stochastic variance. This deterministic

model is intended to simulate how the stacks fell in the real world, and is therefore

called a natural gravity simulator (NGS) (Fig 2b top). The other model is the same as

the NGS, except that the deterministic direction of gravity in the NGS was replaced

by the stochastic direction obtained from the previous psychophysical experiment.

This model is thus called the mental gravity simulator (MGS, Fig 2c top). Both

models were used to quantify the degree of stability by measuring the proportion of

unmoved blocks after the collapse, where the proportion of unmoved blocks after the

simulation was used to estimate the stability of the stacks.

NGS-estimated stability was significantly correlated with participants'

subjective sense (Fig 2b bottom; $r = 0.70$, $p < 0.01$), consistent with previous findings

(Battaglia et al., 2013). However, the participants showed an obvious bias towards

predicting a collapse for stacks regardless of their actual stability, as the dots in Fig 2b

are more concentrated on the lower side of the diagonal line. This phenomenon is

referred to as the inference bias, which was indexed as the difference in stability

estimates between the participants and the NGS (inference bias = -0.31, $p < 0.01$) (see

Methods). In other words, the participants were unlikely to infer stacks' stability from

simulations with a deterministic direction of gravity pointing vertically downward. In

contrast, the MGS randomly sampled pairs of ($\theta_s$, $\varphi_s$) from the Gaussian distribution

as gravity's directions 100 times, and the estimated stability of a stack was the

averaged stability of simulations with different angle pairs. Aside from a similar

magnitude of the correlation in the stability estimates between the participants and the

MGS (Fig 2c bottom; $r = 0.75$, $p < 0.01$), the MGS, in contrast to the NGS, more

precisely reflected participants' judgments of stability because the points were evenly

distributed along the diagonal line (inference bias = 0.04, $p > 0.05$; see Supplementary

Figure 6 for the agreement when the MGS was implemented with different Gaussian

functions). In other words, the magnitude of the correlation coefficients is not the only

indicator to evaluate the model's fitness. In short, the world model that represents

gravity's direction as a Gaussian distribution around the vertical direction properly

explains our tendency to judge stacks as more prone to collapse.

Fig 2. Stability inference by the world model on gravity. a) An experiment to rate the stability of

stacks, half of which were stable and the other half unstable. b) Top: The procedure of the NGS to

estimate the actual stability of stacks by simulation, and for unstable stacks the stability was indexed by

the proportion of displaced blocks. Bottom: The correlation between the stability estimates of the

participant and those of the NGS. Each dot represents one stack, and the lines denote the standard

errors. c) Top: The procedure of the MGS, where the stability of a stack was estimated by averaging

the estimated stabilities from multiple simulations with different gravity directions sampled from the

Gaussian distribution. Bottom: The correlation between the stability estimates of the participant and

those of the MGS. d) Left: The illusion that taller objects are perceived as more unstable than shorter

ones. Right: The inference bias was indexed by the difference between the stability estimated by the

MGS and that estimated by the NGS. The larger the negative values, the more likely stacks were

234 unstable. The x-axis denotes the height of a stack containing ten blocks, where the height, length, and
235 width of each block were 1.2, 0.4, and 0.4, respectively. IB: inference bias. Error bar: standard error.
236

The stochastic world model illustrated by the MGS that led to participants'
inference bias may explain the daily illusion that we perceive taller objects to be more
unstable than shorter ones (Fig 2d left). An intuitive explanation from physics is that a
tall object has a higher center of gravity, and thus an external perturbation makes it
more likely to collapse. Our stochastic world model, on the other hand, provides an
alternative explanation without introducing external perturbations, because the center
of gravity in taller objects is more susceptible to influence when gravity deviates
slightly from a strictly downward direction during humans' internal simulations. To
test this conjecture, we constructed a set of stacks with different heights, and
estimated the degree of stacks' stability with the MGS and the NGS, respectively.
Because the MGS was considered to be the world model implemented in the brain,
the inference bias here was calculated as the difference in stability estimates between
the MGS and the NGS, with negative values indicating a tendency to judge a stable
stack as an unstable one. Consistent with the inference bias found in humans, the
MGS found stacks of all heights to be more prone to collapse (Fig 2d right; inference
bias $< 0$, $p < 0.01$ for all heights). Critically, the bias increased monotonically with
increasing height, consistent with the illusion that taller objects are considered more
prone to collapse (see Supplementary Figure 7 for the inference bias when the MGS
was equipped with different levels of deviation). In short, the stochastic world model
on gravity provides a more concise explanation for the daily illusion that taller objects
are perceived as more likely to collapse, without assuming external perturbations.
258

**The origin of the stochastic feature of the world model**
A deterministic model that combines gravity's veridical direction with external
perturbations, such as an external force or perceptual uncertainty (Allen et al., 2020;
Battaglia et al., 2013; Lake et al., 2017; Smith and Vul, 2013), is theoretically
equivalent to our stochastic model that represents gravity's direction in a Gaussian
distribution; therefore, it also fits well with humans' inference on stability by fine-
tuning the parameters of external perturbations. While the cognitive impenetrability
and the self-consistency observed in this study, without resorting to an external

perturbation, favor the stochastic model over the deterministic one, the origin of this

stochastic feature of the world model is unclear.

Here we used a reinforcement learning (RL) framework to unveil this origin,

because our intelligence emerges and evolves under the constraints of the physical

world. Therefore, the stochastic feature may emerge as a biological agent interacts

with the environment, where the mismatches between external feedback from the

environment and internal expectations from the world model are in turn used to fine-

tune the world model (Friston et al., 2021; MacKay, 1956; Matsuo et al., 2022). Note

that a key aspect of the framework is determining whether the stochastic nature of the

world model on gravity emerges through this interaction, even in the absence of

external noise. To simulate this process, here we designed a reinforcement learning

(RL) framework to model this interactive process to illustrate how the world model on

gravity evolves (Fig 3a). Specifically, an agent perceived a stack in the environment,

which was then acted upon by a simulated gravity with direction parameters (i.e., $\theta$

and $\varphi$) sampled from a spherical direction space. The initial probabilities for the

sampling directions were identical (Fig 3b, left). The final state of the stack served as

the agent's expectation under the effect of the simulated gravity. The mismatch

between the expectation and the observed final state of the stack under the natural

gravity was used to update the sampling probability of the direction space, with a

larger discrepancy leading to a larger decrease in probabilities through RL. Within

this RL framework, we constructed abundant stacks of 2 to 15 blocks to train the

world model on gravity. As the training progressed, the probabilities of the direction

space gradually converged downward (Fig 3b, middle; see Supplementary Figure 8

for the training trajectory). Although gravity's direction in the environment was

vertical, the distribution of updated probabilities in the direction space was

gradational ($\sigma = 21.6$; Fig 3b, right), which is close to gravity's direction represented

in the world model derived from the psychophysics experiment on human participants.

Therefore, the world model representing gravity's direction in a Gaussian distribution

can emerge automatically as the agent interacts with the environment, without the

need for any external perturbation.

**Fig 3. The origin of the stochastic feature of gravity's direction.** a) The reinforcement learning

framework, which updated gravity's direction        of the world model by minimizing the difference

between the expectation from the internal simulation (i.e., simulated states) and the observation from

the physical world (i.e., actual states). b) Gravity's directions, which were uniformly distributed on the

spherical surface, gradually converged downward as the training progressed, and eventually stabilized

in a Gaussian distribution with the vertical direction as the maximum likelihood. Color denotes the

probability of a parameter pair being adopted as gravity's direction. c) Left: World models constructed

by reinforcement learning when stacks in the physical world were composed of different numbers of

blocks ranging from 2 to 15. Right: The variance of the Gaussian distribution, illustrated by the width

of the distribution of gravity's direction on a spherical surface, monotonically decreased as the number

of blocks in the stacks increased.

To further illustrate the idea that the environment constrains the form of

intelligence, we systematically manipulated the appearance of the physical world

while holding the natural gravity constant. Specifically, we constructed 14 worlds,

each containing stacks of the same number of blocks, but with different

configurations. The number of blocks ranged from 2 to 15. We trained the world

model on gravity under the same RL framework for each world, and found that all

world models represented gravity's direction in a Gaussian distribution (Fig 3c left;

see Supplementary Figure 9 for all world models). However, the width of the

distribution, indexed by the parameter of $\sigma$, decreased monotonically as the number of

blocks increased (Fig 3c right). This phenomenon was shown because in general

stacks containing more blocks were more likely to be affected by forces whose

directions were not perpendicular to the ground surface, which provided more

information about gravity, and thus resulted in a more accurate representation of

gravity's direction in the world model. In short, the world model on gravity resonates

with not only the physical law governing the environment, but also the specific

regularities of the environment the agent encountered.

**The ecological advantage of the stochastic world model**

When passing a cliff face, we have to be constantly aware of the stability of the rocks

on the cliff. The ideal response would be both accurate and fast, but accuracy and

speed are often difficult to achieve simultaneously. Here we investigated how the

world model on gravity balances these two factors with its stochastic feature. To

answer this question, we used a linear classifier (i.e., logistic regression) to model

humans' decision-making behavior at different stages of the mental simulation.

Specifically, we collected all the position coordinates of a stack's blocks at different

stages of the simulation. The position difference between the intermediate states of

the stack and the initial state provides information about the stability of the stack. For

example, a stable stack should have no difference in the positions of the component

blocks at all simulation stages, and an unstable stack should have a gradually

increasing position difference. If the linear classifier detected the difference in

positions sufficient for the classification at any stage, it classified the stack as unstable,

otherwise stable (Fig 4a). The classification accuracy gradually increased as the

simulation progressed until it reached the asymptote.

As expected, for the NGS (i.e., the world model with the deterministic

direction of gravity), the accuracy at the plateau was close to 100% (95.3% on

average, Fig 4b top red box), significantly higher than that for the MGS (80.1% on

average, Fig 4b top blue box) (t = 19.59, p<0.001), simply because of the stochastic

feature of gravity's direction. However, while the initial growth rates of both models

were comparable, the MGS reached the plateau crucial for decision-making sooner

than the NGS (response time, indexed by the ratio between the time to reach the

plateau and the time to reach the final stage: 27.1% vs. 75.2%, t = 15.58, p < 0.001)

(Fig 4b middle). The same pattern was also observed with different variances of the

Gaussian distribution (Supplementary Figure 10). That is, the stochastic world model

prioritized speed over accuracy, echoing the basic principle of survival: fleeing

potential danger as quickly as possible, rather than making a perfect decision with a

dreadful delay. In addition, by integrating the prediction accuracy and the response

time as a measure of efficiency, we found that the stochastic world model provided a

better balance between accuracy and speed, with an efficiency significantly higher

than that provided by the NGS (3.49 vs. 1.32, t = 9.12, p < 0.001; Fig 4b bottom).

**Fig 4. The ecological advantage of the stochastic feature.** a) Illustration that modeled humans'

decision-making behavior at different stages of the mental simulation using the NGS and MGS. b) The

decision of the linear classifier based on the simulation of the MGS was less accurate than that of the

NGS (top), but the decision was made faster in the MGS than in the NGS (middle). The MGS was

more efficient than the NGS in combining accuracy and speed (bottom). c) The relationship between

the number of simulations and the variance of the estimated stability. d) The difference in the variance

of the estimated stability between the participants and the MGS. The difference was minimal when the

MGS ran the simulation three times. Error bar: standard error.

On the other hand, if time permits, multiple simulations with the MGS can

significantly reduce the variance introduced by the stochastic representation of

gravity's direction (Fig 4c). To explore whether humans adopted this strategy of

performing multiple simulations before making a decision, we ran simulations with

the MGS at different numbers of times and then matched them with humans'

performance. We found that the variance of humans' inference on stability best

matched that of the MGS after three simulations (Fig 4d; see Supplementary Figure

11 for the model-behavior correspondence under different numbers of simulations).

Therefore, humans are likely to run simulations a limited number of times to infer

stacks' stability.

381
382
383
384

## Discussion

In this study, we investigated how the physical law of gravity is embodied in the brain as a world model that guides inferences on objects' stability. A series of psychophysics experiments showed that the world model on gravity is not a faithful replica of the physical world, but rather a stochastic model that captures the essence of the vertically downward direction of gravity as the maximum likelihood of a Gaussian distribution. The stochastic feature of the world model not only fits humans' stability inference behavior better than the deterministic model, but also provides new insight into the daily illusion that taller objects are perceived as more likely to collapse. We further illustrated how the stochastic feature evolved through interactions with the environment using reinforcement learning, and well-balanced accuracy and speed to produce a unique ecological advantage for our survival in the physical world.

About 300 years ago, the philosopher Immanuel Kant proposed the intuition of space and time as *a priori* knowledge in the mind for us to understand the physical world (Kant, 1781), but only until recently have researchers investigated how the intuition is implemented in the brain as intuitive physics (Kubricht et al., 2017; McCloskey, 1983). In the Noisy Newtonian Framework, intuitive physics is depicted as a combination of Newtonian physics and uncertainty generated by noise (Battaglia et al., 2013; Kubricht et al., 2017; Sanborn et al., 2013). The introduction of uncertainty helps to reconcile the misconception occurring under unfavorable conditions, such as unfamiliar events or static scenes (Kaiser et al., 1992, 1986; Kim and Spelke, 1999; McCloskey, 1983; Smith and Vul, 2013), which was once thought to support Aristotelian physics (DiSessa, 1982; Halloun and Hestenes, 1985). The noise in previous studies was thought to originate from sources such as perceptual uncertainty or external perturbations of forces, rather than from the intuitive physical engine itself, which is thought to be a deterministic system. Our study extends these deterministic models by showing a stochastic world model that the noise instead came from the representation of gravity's direction under Gaussian distribution. The inherent stochastic feature of gravity's direction did not need to rely on external noise to explain the illusory instability of taller objects. In addition, it was also confirmed by the cognitive impenetrability of the Gaussian distribution of gravity's direction when gravity's direction in the physical world was reversed (Pylyshyn, 1980).

With a reinforcement learning framework, we further proposed a possible

origin of the stochastic feature of the world model through interactions with the

physical world. In contrast to summarizing statistical patterns from experience (Bear

et al., 2021; Li et al., 2016; Zhang et al., 2016), this framework was designed to

simulate how an agent constructed the world model on gravity through agent-

environment interactions. Specifically, a world model with undifferentiated directions

of gravity generated a prediction on the stability of an object, and the mismatches

between the prediction and the observation of the object from the physical world were

used to fine-tune the distribution of the directions in the world model. This process is

similar to how humans update their internal knowledge by comparing simulated

expectations (Hegarty, 2004; Ullman et al., 2017) with actual observations

(Baillargeon, 2004, 1994; Kotovsky and Baillargeon, 2000). After several generations

of error minimization, a Gaussian distribution of gravity's direction with the vertically

downward direction as the maximum likelihood was similar to that observed in the

human world model. Interestingly, when the physical worlds that the agent interacted

with changed their appearance with stacks of different heights, the world models

maintained their general patterns, but the stochastic representation of gravity's

direction changed accordingly. This finding not only supports the robustness of the

active inference (Hegarty, 2004; Ullman et al., 2017), which efficiently encodes

critical features under different physical worlds, but also resonates with the idea that

intelligence develops under the constraints of the physical world. Taken together, the

finding from the RL framework implies that the world model on gravity in humans

may also be constructed in the same way, possibly through the mechanism of the

predictive coding in a generative process (Friston, 2018; Huang and Rao, 2011).

Our world model on gravity provides an example of the world model theory

that emphasizes the predictive nature of generative neural networks implemented with

*a priori* knowledge of the physical world (Friston et al., 2021; Land, 2014; Matsuo et

al., 2022). In contrast to traditional discriminative neural networks that learn statistical

patterns for stability from gigantic amounts of labeled stacks, generative models

equipped with the physics laws governing the physical world rely much less on

experience. Importantly, the stochastic feature of the model further enhances the

efficiency by balancing accuracy and speed, which improves our chances of better

survival (Cosmides and Tooby, 1997) and adaptation to novel environments (e.g.,

astronauts in outer space (Wang et al., 2022)). Indeed, the close link between human

cognition and the physical world through interaction may shed light on the

development of a new generation of AI with human-like intelligence that can work

flexibly in open-ended environments (Marcus, 2020, 2018).

## Methods
### Creating stacks with different configurations

We designed a block-stacking procedure in a physical simulation platform (PyBullet) to generate stacks with different configurations. All stacks used in this study were generated using this procedure with the same parameters listed below.

The block-stacking procedure includes three steps (Supplementary Figure 1a): (1) defining the designated area, (2) stacking blocks, and (3) fine-tuning block positions. The first step is to designate a restricted place area. All blocks of a stack were required to be placed within the designated area. The designated area controls the aggregation level of blocks, with a small area clustering blocks closer than a large area. The designated area is determined by two horizontal parameters $x$ and $y$, which separately represent the size of the area in two horizontal directions. Therefore, when the block number is fixed, a smaller area in general constructs a higher stack. After designating the area, in step two we stacked blocks in random horizontal positions within the area one by one. If no block was positioned under a new block, the new block would be directly placed on the ground; otherwise, it would stack on the positioned block. The horizontal position of each block was independently sampled from a uniform distribution, with lower and upper bounds being $-x$ and $+x$, or $-y$ and $+y$ separately ($x$ and $y$ were all independently sampled from a uniform distribution $U(0.2, 2.0)$). The first two steps allow us to generate a large number of configurations within the designated area, which is the only restriction of the block-stacking procedure. To better control the physical stability of each stack, in step three we fine-tuned blocks in the stack by adjusting overlaps between every neighboring one, which was randomly sampled from a uniform distribution $U(0.2, 0.8)$. Smaller overlap between neighboring blocks is more likely to construct unstable stacks, whereas more extensive overlap results in more stable stacks. The overlap of neighboring blocks without contact is set to 0. Note that the overlap between neighboring blocks is not the only factor determining a stack's stability, and step three is used to generate stacks without consuming too many computational resources.

The size of each block has a 3D aspect ratio of 3:1:1 (length: width: height), with an arbitrary unit of 1.2:0.4:0.4. This constitutes three types of blocks (length, width, or height is 1.2, respectively, see Supplementary Figure 1b). Each block of a stack was randomly selected as one of the three types of blocks. The mass of each

493 block is set to 0.2 kg, and the friction coefficients and the coefficients of restitution

494 between blocks are set to 1 and 0, respectively.

## **Estimating the stability of a stack**

The stability of a stack was obtained by a rigid-body forward simulation under the

natural gravity environment (i.e., natural gravity simulator, NGS). The direction of the

natural gravity points downward (i.e., $\vec{G} = (0, 0, -9.8)$), and all blocks of a stack are

affected by the same gravity. Gravity is the only factor for changing the state of each

block, and no external force is added during the simulation. Within each simulation,

we recorded 500 simulation stages. In each stage, the center position of each block

was collected to measure the stability of the stack. If the position of any block does

not change during the simulation, the stack is considered stable, otherwise unstable.

We formulate the stack's state according to the below criteria:

$$Stable: \forall t \wedge \forall m, |P_{tm} - P_{0m}| < \varepsilon$$
$$Unstable: \exists t \vee \exists m, |P_{tm} - P_{0m}| > \varepsilon \tag{1}$$

506 Where $t$ is a simulation stage, m is the block number of a stack, $P_{tm}$ is the position of

507 the block m at stage t, and $\varepsilon$ is the just noticeable difference (i.e., j.n.d) of the

508 perception, which is set to 0.01.

509        The stability of a stack is further calculated by measuring the proportion of

510 displaced blocks, which is formulated as the following,

$$Stability = \frac{\sum_{m=1}^{M} \mathbb{I}(|P_{Tm} - P_{0m}| < \varepsilon)}{M} \tag{2}$$

511 Where M is the total number of blocks of a stack, and T is the final stage of the

512 simulation (i.e., T = 500). $\mathbb{I}(\cdot) = 1$ when $|P_{Tb} - P_{0b}| < \varepsilon$, which denotes that the

513 stack is stable.

## **Measuring participants' sensitivity to gravity's direction**

516 We decomposed gravity's direction into three independent components (Fig. 1b).

$$G_x = g \sin \theta \cos \varphi$$
$$G_y = g \sin \theta \sin \varphi \tag{3}$$
$$G_z = g \cos \theta$$

Where g is the magnitude of gravity (g = 9.8), which was fixed in this study. $\theta$

represents the vertical component, $\varphi$ represents the horizontal component, and x, y,

and z are three mutually perpendicular axes. The direction of the gravity was

determined by the angle pair $(\theta, \varphi)$, where $\theta$ affects the extent of the collapse, and $\varphi$

affects the orientation of the collapse. When $\theta$ is 0, gravity's direction is vertical.

We performed a psychophysics experiment to measure humans' sensitivity to

gravity's direction. In this experiment, 10 participants (5 female, age range: 21-28)

from Tsinghua University were recruited to finish four runs of the behavioral

experiment, which measured their ability to detect the abnormality of stacks' collapse

trajectories. The experiment was approved by the Institutional Review Board of

Tsinghua University (2022 No. 34), and informed consent was obtained from all

participants before the experiment.

The collapse trajectory of a stack was solely determined by gravity with

different directions, where larger values of $\theta$ and $\varphi$ made the trajectories more

abnormal. A pilot experiment showed that almost all $\theta_s$ greater than 45 degrees made

the collapse trajectory abnormal to most participants, and therefore in the experiment,

$\theta$ ranges from 0 to 45 degrees with a step of 3 degrees. $\varphi$ ranges from 0 to 360

degrees with a step of 24 degrees. Therefore, $\theta$ and $\varphi$ consists of 16 values,

respectively, which were randomly combined into 96 pairs of $(\theta, \varphi)$ with each value

repeating 6 times in each run. In a trial, an unstable stack was constructed, and then

the camera rotated one circle to show the 3D configuration of the stack to participants

(Supplementary Movie S1). The configuration was randomly selected from a dataset

with more than 2,000 unstable stacks, which was generated with the block-stacking

procedure before the experiment. Each stack in the database was constructed with 10

blocks, and the color of each block was randomly rendered. There was a 1-sec delay

after the rotation, during which the participants were instructed to infer the collapse

trajectory based on the configuration. Then, simulated gravity with a direction

determined by an angle pair $(\theta, \varphi)$ was applied to the stack, and the stack started to

collapse. If the collapse trajectory met participants' expectations, they were instructed

to choose 'Normal,' otherwise 'Abnormal'. Once the judgment was made, the

subsequent trial started immediately. Each trial lasts about 10 seconds, taking 16

minutes for a run.

In addition, to test if participants' sensitivity to gravity's direction is

encapsulated from visual experience and task context, we flipped gravity's direction

upside down by inverting the camera's view, and the rest procedure remained the
same.

To calculate participants' sensitivity to gravity's direction, we converted their
behavioral judgment into confidence levels about the normal trajectory, which is the
percentage that a trajectory was judged as normal, which was calculated as below:

$$Ratio_{\theta,\varphi} = \frac{n_{\theta,\varphi}}{N_{\theta,\varphi}} \tag{4}$$

Where $n_{\theta,\varphi}$ is the number of trajectories that were judged as 'Normal' with the angle
pair $(\theta, \varphi)$, $N_{\theta,\varphi}$ is the total number of trajectories with the same angle pair. Because
the angle pairs tested were a subset of all possible angle pairs, we used the average
ratio along $\varphi$ as the ratio of angle pairs untested (Fig. 1c) to acquire each participant's
tuning curve. Finally, we calculated participants' sensitivity by fitting their confidence
levels at different $\theta$ to a Gaussian distribution.

$$Ratio_{\theta} = Ae^{-\frac{\theta^2}{2\sigma^2}} \tag{5}$$

562 Where $Ratio_{\theta}$ is the confidence level of $\theta$, which was calculated by averaging the
563 confidence level along all $\varphi_s$, A is the magnitude of the Gaussian curve, $\sigma$ is the
564 variance of the Gaussian curve. The best-fitted $\sigma$ was used to index participants'
565 sensitivity to gravity's direction, and a larger $\sigma$ indicates a lower sensitivity.

**567 Measuring participants' ability on stability inference**

Another group of 11 participants (5 female, age range: 21-32) from Tsinghua
University completed a behavioral experiment for judging the stability of 60 stacks.
The experiment was approved by the Institutional Review Board of Tsinghua
University, and informed consent was obtained from all participants before the
experiment. One male participant (age: 25) was excluded from further analyses
because his judgment showed an extremely weak correlation with the actual stability
of stacks ($r_s < 0.30$ for all experimental runs), as compared to the rest of the
participants.

The stacks contained 26 unstable and 34 stable stacks, which were randomly
interleaved in each run. The participants were instructed to judge stacks' stability on
an 8-point Likert scale, with 0 referring to 'definitely unstable' and 7 to 'definitely
stable.' There was no feedback after each judgment. The participants completed six
runs, within which the same group of stacks was presented but the sequence, blocks'

colors, and camera's perspective were all randomized. After the experiment, only two

participants reported that they suspected a few stacks were repeated in different runs,

but they could not locate the stacks they suspected. Besides, their behavioral

performance was not significantly different from other participants.

Participants' stability judgment was rescaled to 0 and 1 to match the scale of

the stacks' stability. The participants' inference bias (IB) was indexed as the

difference in stability judgment between the participants and the NGS, shown as

$$IB = Stability_{human} - Stability_{NGS} \qquad (6)$$

Negative IB indicates that participants tended to consider a stable stack as an unstable

one.

**Estimating the stability of stacks based on the stochastic world model**

**on gravity**

The actual stability of a stack can be calculated with a one-time simulation of NGS ($\vec{G}$

= (0, 0, -9.8)). In contrast, the stochastic nature of mental gravity requires a multiple-

time simulation with different gravity's directions. Specifically, we first randomly

sampled several angle pairs $(\theta_s, \varphi_s)$ from the Gaussian distribution of gravity's

directions in humans. The distribution was the average of two distributions acquired

from the real world (i.e., gravity's direction is downward) and the inverted world (the

direction is upward), with angles having larger confidence levels more likely being

sampled. We then applied the simulated gravity with these sampled directions to the

stack, and used the averaged stability with these directions as the stability of the stack

estimated by the MGS. Similar to the IB between the participants and the NGS, the IB

between the MGS and NGS was calculated as

$$IB = Stability_{MGS} - Stability_{NGS} \qquad (7)$$

Stacks of different heights were created to investigate whether the stochastic

world model on gravity results in the illusion that tall objects are considered less

stable than short ones. The height of a stack was correlated with the size of the

designated area, with a smaller area size corresponding to taller stacks. Therefore, we

designated several square areas with different sizes. The side length of the squares

ranged from 0.2 to 2.0, with an increase of 0.1. For each square, we used the block-

stacking procedure to generate 100 stable and 100 unstable stacks consisting of 10

blocks. The height of each stack was the height of the highest block.

### Investigating the origin of the stochastic world model on gravity

A reinforcement learning (RL) framework was used to simulate the development of

the stochastic nature of the world model on gravity. To do this, we first created stacks

whose block number ranged from 2 to 15 with the block-stacking procedure, and

initialized a spherical force space, where $\theta$ ranged from 0 to 180 degrees and $\varphi$ from

0 to 360 degrees, separately divided them into 61 sampling angles across the spherical

force space (i.e., the angle density). The spherical space covered all possible force

directions, with the initial probability of being sampled by the MGS identical. During

the training, three angle pairs $(\theta_s, \varphi_s)$ were sampled according to the probability of

the spherical space, and then applied to a stack for simulating its collapse trajectory,

which was divided into 500 stages. We optimized the sampling probability of

gravity's direction by comparing the estimated stability (i.e., expectation) with the

actual stability (i.e., observation) as a Q value, with a higher Q value suggesting that

the sampled gravity's direction more likely mismatched the actual gravity's direction.

The Q value was calculated as

$$Q = \frac{\sum_{m=1}^{M} \mathbb{I}(|P_{m,(\theta,\varphi)} - P_m| < \varepsilon)}{M} \tag{8}$$

628     Where $P_{m,(\theta,\varphi)}$ is the final position of block m with gravity's direction $(\theta, \varphi)$, $P_m$ is

629     the final position of block m with NGS, M is the block number of the stack, and the

630     j.n.d. $\varepsilon$ is set to 0.01. The mismatch between the expectation and the observation was

631     used to update the sampling probability of the angle pair using a temporal difference

632     optimization

$$W_{\theta,\varphi} \leftarrow W_{\theta,\varphi} + \gamma(Q - W_{\theta,\varphi}) \tag{9}$$

Where $\gamma = 0.15$ is the learning rate. This process was iterated to update the sample

probability of angle pairs $(\theta_s, \varphi_s)$ until the training stopped. The angle density and

learning rate are two factors that affect the learning speed. A larger angle density

prolongs the time to reach convergence but enables a more detailed force space; a

higher learning rate accelerates convergence but incurs larger variance during training.

To balance speed and convergence, we utilized 100,000 configurations for the

training.

### Evaluating the ecological advantage of the model

To investigate how the world model on gravity balances response accuracy and speed,
we trained a linear classifier (i.e., logistic regression) to model humans' decision-
making process at different simulation stages. During the simulation, the same stack
was separately simulated using the NGS and MGS, and we collected the position
coordinates of all blocks at each stage. Differences in the positions of the blocks
between the intermediate stage and the initial stage provided information about the
stability of a stack, with more displaced blocks suggesting the lower stack's stability.
As the simulation proceeded, differences in position gradually accumulated for
unstable stacks, otherwise unchanged for stable stacks. The linear classifier was
trained to judge whether a stack is stable with differences in position as inputs.

We used the block-stacking procedure to create stacks consisting of 2 to 10
blocks, and estimated their stabilities with the NGS for simulation in 500 stages. For
each block number, there were 100 stable and 100 unstable stacks to train the linear
classifier, and its prediction accuracy was measured with another group of 100 stable
and 100 unstable stacks at every simulation stage.

The difference in positions of each block between the intermediate and initial
stages was used as the input of the linear classifier. Specifically, we collected all
vertex positions of a block during the simulation to acquire the difference in position,
which included 8 coordinate points for each block in each stage. We did not collect
the central position as previously used in the stability estimation, simply because it
did not provide information on the shape and size of the block. We separately
performed the simulation using the MGS and NGS, calculated the difference in
position between the intermediate stage and the initial stage, and then flattened the
difference to generate 24 position features for each block (i.e., eight positions per
block in three-dimensional space). Therefore, for a 10-block stack as an example,
there were 240 position features were prepared as the input of the linear classifier.

Prediction accuracy at each stage was estimated by evaluating whether a stack
tested was stable with the MGS or with the NGS. The highest accuracy in the whole
simulation stages was used as the prediction accuracy. Accordingly, the first
simulation stage to reach the maximum accuracy provided information on response
speed: reaching the maximum accuracy with a smaller number of stages indicates the
classifier model accomplishes stability inference in a shorter amount of time (i.e.,
quick response). Therefore, we measured the response speed by estimating the steps
to reach the accuracy plateau.

$$Time = \frac{\hat{t}}{T}$$

(10)

$$\hat{t} = arg \max_{t} Accuracy_t$$

676    Where $Accuracy_t$ is the accuracy of stage t. $\hat{t}$ is the stage that a linear classifier

677    acquires the maximum accuracy for the first time, T is the total stage number of each

678    simulation (T = 500). Higher values indicate longer response time (i.e., slower

679    response). Finally, the efficiency of the stability inference, which is the balance

680    between accuracy and speed, by dividing the prediction accuracy by the response time.

$$Efficiency = \frac{Accuracy}{Time}$$

(11)

# References

Allen KR, Smith KA, Tenenbaum JB. 2020. Rapid trial-and-error learning with simulation supports flexible tool use and physical reasoning. *Proceedings of the National Academy of Sciences* **117**:29302–29310.

Baillargeon R. 2004. Infants' physical world. *Current directions in psychological science* **13**:89–94.

Baillargeon R. 1994. How do infants learn about the physical world? *Current Directions in Psychological Science* **3**:133–140.

Battaglia PW, Hamrick JB, Tenenbaum JB. 2013. Simulation as an engine of physical scene understanding. *Proceedings of the National Academy of Sciences* **110**:18327–18332.

Bear DM, Wang E, Mrowca D, Binder FJ, Tung H-YF, Pramod R, Holdaway C, Tao S, Smith K, Sun F-Y, others. 2021. Physion: Evaluating physical prediction from vision in humans and machines. *arXiv preprint arXiv:210608261*.

Blatner D. 2013. Spectrums: our mind-boggling universe from infinitesimal to infinity. A&C Black.

Cosmides L, Tooby J. 1997. Evolutionary psychology: A primer.

Coumans E, Bai Y. 2016. Pybullet, a python module for physics simulation for games, robotics and machine learning.

Dabney W, Kurth-Nelson Z, Uchida N, Starkweather CK, Hassabis D, Munos R, Botvinick M. 2020. A distributional code for value in dopamine-based reinforcement learning. *Nature* **577**:671–675.

DiSessa AA. 1982. Unlearning Aristotelian physics: A study of knowledge-based learning. *Cognitive science* **6**:37–75.

Fischer J, Mikhael JG, Tenenbaum JB, Kanwisher N. 2016. Functional neuroanatomy of intuitive physical inference. *Proceedings of the national academy of sciences* **113**:E5072–E5081.

Friedman WJ. 2002. Arrows of time in Infancy: The representation of temporal–causal invariances. *Cognitive Psychology* **44**:252–296.

Friston K. 2018. Does predictive coding have a future? *Nature neuroscience* **21**:1019–1021.

Friston K, Moran RJ, Nagai Y, Taniguchi T, Gomi H, Tenenbaum J. 2021. World model learning and inference. *Neural Networks* **144**:573–590.

Halloun IA, Hestenes D. 1985. Common sense concepts about motion. *American journal of physics* **53**:1056–1065.

Hegarty M. 2004. Mechanical reasoning by mental simulation. *Trends in cognitive sciences* **8**:280–285.

Huang Y, Rao RP. 2011. Predictive coding. *Wiley Interdisciplinary Reviews: Cognitive Science* **2**:580–593.

Indovina I, Maffei V, Bosco G, Zago M, Macaluso E, Lacquaniti F. 2005. Representation of visual gravitational motion in the human vestibular cortex. *Science* **308**:416–419.

Kaiser MK, Jonides J, Alexander J. 1986. Intuitive reasoning about abstract and familiar physics problems. *Memory & Cognition* **14**:308–312.

Kaiser MK, Proffitt DR, Whelan SM, Hecht H. 1992. Influence of animation on dynamical judgments. *Journal of experimental Psychology: Human Perception and performance* **18**:669.

Kant I. 1781. The Critique of Pure Reason.

Kim I-K, Spelke ES. 1999. Perception and understanding of effects of gravity and inertia on object motion. *Developmental Science* **2**:339–362.

Kotovsky L, Baillargeon R. 2000. Reasoning about collisions involving inert objects
in 7.5-month-old infants. *Developmental Science* **3**:344–359.
Kriegeskorte N, Douglas PK. 2019. Interpreting encoding and decoding models.
*Current opinion in neurobiology* **55**:167–179.
Kubricht JR, Holyoak KJ, Lu H. 2017. Intuitive physics: Current research and
controversies. *Trends in cognitive sciences* **21**:749–759.
Lacquaniti F, Maioli C. 1989. Adaptation to suppression of visual information during
catching. *Journal of Neuroscience* **9**:149–159.
Lake BM, Ullman TD, Tenenbaum JB, Gershman SJ. 2017. Building machines that
learn and think like people. *Behavioral and brain sciences* **40**.
Land MF. 2014. Do we have an internal model of the outside world? *Philosophical
Transactions of the Royal Society B: Biological Sciences* **369**:20130045.
Li W, Azimi S, Leonardis A, Fritz M. 2016. To fall or not to fall: A visual approach
to physical stability prediction. *arXiv preprint arXiv:160400066*.
MacKay DM. 1956. The epistemological problem for automataAutomata
Studies.(AM-34), Volume 34. Princeton University Press. pp. 235–252.
Marcus G. 2020. The next decade in ai: four steps towards robust artificial
intelligence. *arXiv preprint arXiv:200206177*.
Marcus G. 2018. Deep Learning: A Critical Appraisal.
Matsuo Y, LeCun Y, Sahani M, Precup D, Silver D, Sugiyama M, Uchibe E,
Morimoto J. 2022. Deep learning, reinforcement learning, and world models.
*Neural Networks*.
McCloskey M. 1983. Intuitive physics. *Scientific american* **248**:122–131.
McIntyre J, Zago M, Berthoz A, Lacquaniti F. 2001. Does the brain model Newton's
laws? *Nature neuroscience* **4**:693–694.
Naselaris T, Kay KN, Nishimoto S, Gallant JL. 2011. Encoding and decoding in fMRI.
*Neuroimage* **56**:400–410.
Pessiglione M, Seymour B, Flandin G, Dolan RJ, Frith CD. 2006. Dopamine-
dependent prediction errors underpin reward-seeking behaviour in humans.
*Nature* **442**:1042–1045.
Pramod R, Cohen MA, Tenenbaum JB, Kanwisher N. 2022. Invariant representation
of physical stability in the human brain. *eLife* **11**:e71736.
Pylyshyn ZW. 1980. Computation and cognition: Issues in the foundations of
cognitive science. *Behavioral and Brain sciences* **3**:111–132.
Sanborn AN, Mansinghka VK, Griffiths TL. 2013. Reconciling intuitive physics and
Newtonian mechanics for colliding objects. *Psychological review* **120**:411.
Smith KA, Vul E. 2013. Sources of uncertainty in intuitive physics. *Topics in
cognitive science* **5**:185–199.
Tenenbaum JB, Kemp C, Griffiths TL, Goodman ND. 2011. How to grow a mind:
Statistics, structure, and abstraction. *science* **331**:1279–1285.
Ullman TD, Spelke E, Battaglia P, Tenenbaum JB. 2017. Mind games: Game engines
as an architecture for intuitive physics. *Trends in cognitive sciences* **21**:649–
665.
Wang Y, Zhang X, Wang C, Huang W, Xu Q, Liu D, Zhou W, Chen S, Jiang Y. 2022.
Modulation of biological motion perception in humans by gravity. *Nature
Communications* **13**:1–10.
Zago M, Lacquaniti F. 2005. Visual perception and interception of falling objects: a
review of evidence for an internal model of gravity. *Journal of Neural
Engineering* **2**:S198.

Zago M, McIntyre J, Senot P, Lacquaniti F. 2009. Visuo-motor coordination and
internal models for object interception. *Experimental Brain Research*
**192**:571–604.
Zhang R, Wu J, Zhang C, Freeman WT, Tenenbaum JB. 2016. A comparative
evaluation of approximate probabilistic simulation and deep neural networks
as accounts of human physical scene understanding. *arXiv preprint*
*arXiv:160501138*.
Zhou L, Smith K, Tenenbaum J, Gerstenberg T. 2022. Mental Jenga: A counterfactual
simulation model of physical support.
801
802

**Acknowledgments**

We thank all members of the Liu Lab for their valuable comments.

**Funding:** This study was funded by the Beijing Municipal Science & Technology Commission and Administrative Commission of Zhongguancun Science Park (Z221100002722012), the Shuimu Tsinghua Scholar Program (T.H.), Tsinghua University Guoqiang Institute (2020GQG1016), Tsinghua University Qiyuan Laboratory, and Beijing Academy of Artificial Intelligence (BAAI).

**Author contributions**: J.L. conceptualized the study. T.H. designed and conducted the experiments. T.H. analyzed data. T.H. and J.L. wrote the manuscript.

**Competing interests**: Authors declare no competing interests.

**Data and materials availability**: All code and data underlying our study and necessary to reproduce the results are available on Github: https://github.com/helloTC/GravityWorldModel.

**Supplementary Figure 1**

Supplementary Figure 1 **Construction of stacks with different configurations.** a) Illustration of the

block-stacking procedure to create stacks in different configurations. A configuration was constructed

by placing multiple blocks within a designated area. If there was no positioned block in the area, a new

block was placed on the ground; otherwise, it was placed on top of the positioned block. b) Three types

of blocks with an aspect ratio of 3:1:1. c) This procedure can create a large number of stacks with

different configurations within designated areas. Note that in small areas, the height of stacks was taller.

d) The lower bound of configurations' possible number and the number of blocks in a stack followed

an exponential relationship with a base of 10. The procedure can create at least $1.14 \times 10^{50}$

configurations for stacks consisting of 10 blocks. See the appendix for the estimation.

**Supplementary Figure 2**

a

Are they consistent in their stability?
If no, choose the most stable one.

b

Are they consistent in their stability?
If no, choose the most stable one.

Supplementary Figure 2 **Differentiating Subjectivity from Objectivity.** In both **Experiment 1 (a)**

and **Experiment 2 (b),** participants were instructed to determine which shape appeared most stable.

Objectively, in the absence of external forces, all shapes possess equal stability. Yet, participants

typically perceived the shape on the left as the most stable because of its larger base area. The

discrepancy between objective realities and subjective feelings, as we propose, is attributed to the

human mind representing gravity's direction as a Gaussian distribution, rather than as a singular value

pointing directly downward.

## Supplementary Figure 3

Supplementary Figure 3 **The stochastic world model on gravity of each participant.** Participants'
confidence level about normal trajectory in θ angles followed a Gaussian distribution, with the
variance ranging from 11.1 to 37.1. No stochastic characteristic was observed in φ.

**Supplementary Figure 4**

Supplementary Figure 4 **Wall experiment to test the impact of external forces on the measurement**

**of stochastic gravity.** (a) **Experimental setting.** We replicated the original setup with the addition of a

wall implemented on one side. Left: the overall experimental scene; Right, the scene shown to

participants. (b) **Human behaviors.** Three participants conducted this experiment, and their responses

consistently showed normal distributions without any skewness, suggesting that their judgments were

not affected by the presence of the wall. These results support our claim that humans' judgments on

stability were not affected by potential concerns regarding external forces.

**Supplementary Figure 5**

Supplementary Figure 5 **The stochastic world model on gravity of each participant when gravity's**

**direction was inverted.** Participants' confidence level about normal trajectory in    angles also

followed a Gaussian distribution, with the variance ranging from 9.1 to 28.4, and no stochastic

characteristic was observed along   .

**868**   **Supplementary Figure 6**

**870**   Supplementary Figure 6 **Relation between the stability estimated by the MGS stability and that by**

**871**   **participants when the world model was implemented with different Gaussian functions.** Only

**872**   when the world model embodied Gaussian functions with intermediate variance (i.e.,                ) did

**873**   the stability estimated by the MGS match participants' stability inference. On the other hand, when the

**874**   variance was small, most points were positioned below the diagonal line, indicating the model

**875**   considered stacks more stable in general as compared to participants' judgment. When the variance was

**876**   large, the model considered stacks less stable. Note that all models showed high correlation coefficients

**877**   regardless of the bias. In other words, the magnitude of the correlation is not the sole indicator to

**878**   evaluate the fitness of the model. IB: inference bias.

**879**

**880**

881    **Supplementary Figure 7**

882
883    Supplementary Figure 7 **Height illusion of stability inference when the world model was**
884    **implemented with different Gaussian functions.** The illusion that tall objects are considered more
885    unstable than short ones manifests at all levels of variances of Gaussian functions, with larger variance
886    leading to a stronger illusion.
887

**Supplementary Figure 8**

891 Supplementary Figure 8 **The developmental trajectory of   (Top) and    (Bottom) angles.** Sampling

892 probabilities of   angles gradually decreased during reinforcement learning, with the probabilities from

893 smaller   angles having a lower decrement tendency. The probability of   without any deviation (i.e.,

894        ) keeps unchanged. Probabilities of all   angles finally reached convergence after about 50%

895 training progress. Different from   angles, sampling probabilities of the   angles dropped evenly.

 **Supplementary Figure 9**

Supplementary Figure 9 **The world models developed in the world containing stacks with different numbers of blocks.** The number of blocks ranged from 2 to 15, and in all the worlds gravity's direction was in Gaussian distributions with the vertical direction as the maximum likelihood. Note that the world with stacks consisting of more block numbers led to smaller variances in the Gaussian function.

**Supplementary Figure 10**

Supplementary Figure 10 **Ecological advantage of the world model embodied with different**

**Gaussian functions.** a) Prediction accuracy decreased when the variance of the Gaussian function

increased, and reached an asymptote of 0.75. b) Response time decreased as the variance increased, and

reached an asymptote of 0.20. c) The prediction accuracy and response time were combined as a

measurement for efficiency, which gradually increased monotonically as the function of the variance

until an asymptote of 4. Red box: the world model embodied no stochastic characteristic (i.e., the

deterministic model); Blue box: the world model with different levels of variances. Error bar: standard

error.

**Supplementary Figure 11**

Supplementary Figure 11 **The relation between the number of simulations and the variance of**

**stability inference.** The simulation showed that the variance of stability inference decreased with the

number of simulations. Note that the variance in the world model observed in participants best matched

the variance when the simulation of the MGS was conducted three times.

## Appendix: Estimate the lower bound of the possible number of configurations

A configuration is a structure composed of several contact blocks. To simplify the computation of estimating the number of possible configurations, here we constrained the shape of blocks and the position where the blocks were placed.

**The shape constraint**: *the blocks used to form a configuration are all uniform rectangular blocks with the same aspect ratio.*

**The position constraint**: *only one block is allowed to be placed on the same layer of the configuration.*

Thus, the problem is then simplified to estimate the possible number of configurations when only one rectangular block with the aspect ratio of ___ (i.e., **the shape constraint**) is allowed to place in one layer (i.e., **the position constraint**). Note that the constraints significantly reduce the number of estimated configurations.

We illustrated our solution by starting with a simple case: the aspect ratio of blocks is ___ .

**Appendix Fig 1.** An illustration of the procedure to estimate the possible number of configurations when blocks have an aspect ratio of ___ . (a) the cubic block with the length, width and height are ___ . (b) Constructing a configuration by stacking two cubic blocks. The upper block could only be placed within a ___ area to guarantee contact with the lower block. (c) A three-block configuration can be viewed as stacking a cubic block on a two-block configuration.

**The condition when the aspect ratio of blocks is ___**

The block with the aspect ratio of ___ is a cube (Appendix Fig 1a). The side length of the cube is defined as ___ . Consider a configuration with two stacking blocks, the upper block needs to be placed in a ___ area to ensure contact with the bottom block (Appendix Fig 1b). To estimate the possible number of this simple situation, we defined a visual acuity ___ , which is the minimum resolution to distinguish two stacks (i.e., j.n.d.). Note that ___ is a small value and here we set it as ___ to match the minimal position difference for stability estimation in the simulation platform (please see Methods). Therefore, the possible number of the configuration containing two cubic blocks is

$$\qquad \qquad \qquad \tag{1}$$

Where ____ indicates the possible number of configurations containing two cubic
blocks.
We further consider the situation with more cubic blocks. For a stack that
contains three cubic blocks, it can be viewed as placing a cubic block on a two-block
stack (Appendix Fig 1c). Therefore, the total possible number of configurations is the
multiplication of two two-block configurations, which is formulated as

Similarly, the possible number of configurations for stacks containing four cubic
blocks is

Accordingly, the possible number of configurations with M cubic blocks is

$$ \overline{\phantom{xxx}} \tag{2}$$

967      Now, we have introduced the basic idea of calculating the number of
968 configurations using a block with an   :   :   aspect ratio as a special case. Then we
969 generalized the idea to estimate the possible number when the block is rectangular
970 with the aspect ratio as ____ .
971

972
**Appendix Fig 2.** An illustration of the procedure to estimate the possible number of configurations
when blocks have the aspect ratio of ____ . (a) Three types of rectangular blocks with an aspect ratio
of ____ . (b) There are nine possible two-block configurations when combining blocks with an aspect
ratio of ____ . (c) A three-block configuration could be viewed as stacking a cubic block on a two-
block configuration.

**The condition when the aspect ratio of blocks is**
A block with the aspect ratio of ____ has three types, corresponding to the
sides of length, width and height are ____ and the rest sides are   (   ,     , and
____ ; see Appendix Fig 2a). For simplicity, we label the three basic blocks as A, B
and C. The three types of blocks can generate 9 (i.e., $3^2$) two-block configurations in
total (Appendix Fig 2b). We calculate each of the possible numbers of two-block
configurations below.

$$N_{R2} = \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} \\ N_{BA} & N_{BB} & N_{BC} \\ N_{CA} & N_{CB} & N_{CC} \end{bmatrix}$$

$$= \frac{1}{v^2} \begin{bmatrix} 4\alpha\beta & (\alpha+\beta)^2 & 2\beta(\alpha+\beta) \\ (\alpha+\beta)^2 & 4\alpha\beta & 2\beta(\alpha+\beta) \\ 2\beta(\alpha+\beta) & 2\beta(\alpha+\beta) & 4\beta^2 \end{bmatrix}$$

(3)

The possible number of configurations for stacks containing two rectangular blocks with the aspect ratio of $\alpha:\beta:\beta$ is

$$N_{R2} = \sum N_{R2}$$

(4)

For a configuration containing three blocks, it can be viewed as a block stacked on a two-block stack (Appendix Fig 2c). Therefore,

$$N_{R3} = N_{..A} + N_{..B} + N_{..C}$$

(5)

Where $N_{..A}$ indicates the possible number when block A stacked at the upper layer, and each term can be expanded as below.

$$N_{..A} = N_{.A} \times N_{AA} + N_{.B} \times N_{BA} + N_{.C} \times N_{CA}$$
$$N_{..B} = N_{.A} \times N_{AB} + N_{.B} \times N_{BB} + N_{.C} \times N_{CB}$$
$$N_{..C} = N_{.A} \times N_{AC} + N_{.B} \times N_{BC} + N_{.C} \times N_{CC}$$

(6)

Combining equations (4), (5) and (6), we have

$$N_{R3} = \sum \left( [N_{.A} \quad N_{.B} \quad N_{.C}] \times \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} \\ N_{BA} & N_{BB} & N_{BC} \\ N_{CA} & N_{CB} & N_{CC} \end{bmatrix} \right)$$

And

$$[N_{.A} \quad N_{.B} \quad N_{.C}] = [1 \quad 1 \quad 1] \times \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} \\ N_{BA} & N_{BB} & N_{BC} \\ N_{CA} & N_{CB} & N_{CC} \end{bmatrix}$$

Therefore,

$$N_{R3} = \sum \left( N_{R2}^2 \right)$$

(7)

Following a similar logic, the possible number of configurations containing M blocks with an aspect ratio of $\alpha:\beta:\beta$ is

$$N_{RM} = \sum \left( N_{R2}^{M-1} \right), M \geq 2$$

(8)

**The aspect ratio of blocks is $\alpha:\beta:\gamma$**

We further generalize the problem by considering the aspect ratio of blocks as $\alpha:\beta:\gamma$. This forms six different types: $\alpha:\beta:\gamma$, $\alpha:\gamma:\beta$, $\beta:\alpha:\gamma$, $\beta:\gamma:\alpha$, $\gamma:\alpha:\beta$, $\gamma:\beta:\alpha$, for each type the three proportional values corresponding to length, width and height, respectively. We label the six types of blocks as A, B, C, D, E, F, and G for simplicity.

Following the similar logic as above, different types of blocks generated 36 (i.e., $6^2$) two-block configurations in total, and the possible number of each two-block configuration is

$$N_{R2} = \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} & N_{AD} & N_{AE} & N_{AF} \\ N_{BA} & N_{BB} & N_{BC} & N_{BD} & N_{BE} & N_{BF} \\ N_{CA} & N_{CB} & N_{CC} & N_{CD} & N_{CE} & N_{CF} \\ N_{DA} & N_{DB} & N_{DC} & N_{DD} & N_{DE} & N_{DF} \\ N_{EA} & N_{EB} & N_{EC} & N_{ED} & N_{EE} & N_{EF} \\ N_{FA} & N_{FB} & N_{FC} & N_{FD} & N_{FE} & N_{FF} \end{bmatrix}$$

(9)

$$= \frac{1}{v^2} \begin{bmatrix}
4\alpha\beta & 2\alpha(\beta+\gamma) & (\alpha+\beta)^2 & (\alpha+\beta)(\beta+\gamma) & (\alpha+\gamma)(\alpha+\beta) & 2\beta(\alpha+\gamma) \\
2\alpha(\beta+\gamma) & 4\alpha\gamma & (\alpha+\beta)(\alpha+\gamma) & 2\gamma(\alpha+\beta) & (\alpha+\gamma)^2 & (\alpha+\gamma)(\beta+\gamma) \\
(\alpha+\beta)^2 & (\alpha+\beta)(\alpha+\gamma) & 4\alpha\beta & 2\beta(\alpha+\gamma) & 2\alpha(\beta+\gamma) & (\alpha+\beta)(\beta+\gamma) \\
(\alpha+\beta)(\beta+\gamma) & 2\gamma(\alpha+\beta) & 2\beta(\alpha+\gamma) & 4\beta\gamma & (\beta+\gamma)(\alpha+\gamma) & (\beta+\gamma)^2 \\
(\alpha+\beta)(\alpha+\gamma) & (\alpha+\gamma)^2 & 2\alpha(\beta+\gamma) & (\alpha+\gamma)(\beta+\gamma) & 4\alpha\gamma & 2\gamma(\alpha+\beta) \\
2\beta(\alpha+\gamma) & (\alpha+\gamma)(\beta+\gamma) & (\alpha+\beta)(\beta+\gamma) & (\beta+\gamma)^2 & 2\gamma(\alpha+\beta) & 4\beta\gamma
\end{bmatrix}$$

The possible number of configurations for stacks with M blocks with an aspect ratio $\alpha:\beta:\gamma$ is

$$N_{RM} = \sum \left(N_{R2}^{M-1}\right), M \geq 2 \tag{10}$$

Therefore, we can estimate the possible number of configurations when only one rectangular block with the aspect ratio of $\alpha:\beta:\gamma$ is allowed to place in each layer using the formula (9) and (10).

Finally, in this study we chose blocks with an aspect ratio of 3:1:1 as building blocks for stacks whose stability was evaluated. Specifically, for stacks consisting of 10 blocks and j.n.d. of $v = 0.01$, the number of configurations can be estimated with formula (9), which is $1.14 \times 10^{50}$.