A stochastic world model on gravity for stability inference

Authors: Taicheng Huang[1], Jia Liu[1*].

[1]Department of Psychology and Tsinghua Laboratory of Brain & Intelligence, Tsinghua University, Beijing, China.

* Correspondence to: liujiathu@tsinghua.edu.cn (J. Liu).

Abstract

The fact that objects without proper support will fall to the ground is not only a natural phenomenon, but also common sense in humans' minds. Previous studies have found that humans develop a world model on gravity in the mind to infer the stability of objects. However, its characteristics are less clear, especially how it benefits our rapid response with satisfactory accuracy. Here we measure participants' sensitivity to the direction of gravity in a stability inference task by directly manipulating gravity's direction in a game engine. We find that the world model is not a faithful copy of Newtonian Laws on gravity, but encodes gravity's direction as a Gaussian distribution with the vertical direction as the maximum likelihood of gravity's direction. The stochastic nature of the world model fits nicely with participants' subjective assessment on the stability of stacks and explains the illusion that taller objects are considered more prone to collapse. Further, a computational model with reinforcement learning reveals that the stochastic nature originated from agents' interaction with the real world, and simulations from the game engine illustrate its ecological advantage of balancing accuracy and speed for efficient stability inference. In sum, our stochastic world model on gravity provides an example of the predictive nature of neural networks implemented with *a priori* knowledge about the physical world, which may shed light on developing AI with human-like intelligence that can flexibly operate in open-ended environments.

Introduction

About two thousand years ago, Confucius warned his disciples that a wise man shall not stand beside a collapsing wall. We, wise or not, can easily judge whether a wall is stable or collapsing in a fraction of a second (Battaglia et al., 2013; Kubricht et al., 2017; McCloskey et al., 1983). However, the computation of judging the stability based on the configurations of stacks alone is largely intractable. For example, the universal cardinality of possible configurations constructed by ten blocks with an aspect ratio of 3:1:1 (length: width: height) is at least 3.72×10^{19} (Extended Data Fig. 1), which is much greater than the total number of sand grains on earth. Yet for any configuration in this category (Fig. 1a), we can quickly report its stability at a satisfactory accuracy of 70% on average (Bear et al., 2021; Zhang et al., 2016). This staggering achievement is unlikely from visual experience during development, because infants at four months old start to expect a box to fall if it loses contact with a support platform (Baillargeon, 1994, 2004). Therefore, our brain likely devises a mechanism different from discriminative approaches adopted by artificial neural networks that rely on extensive visual experiences and feedback for stability inference (Bear et al., 2021; Li et al., 2016; Zhang et al., 2016).

Indeed, both behavioral and neuroimaging studies have suggested that humans have built-in knowledge of gravity in the mind. For instance, infants at the age of seven months old expect a downwardly moving object to accelerate and an upwardly moving object to decelerate (Friedman, 2002; Kim & Spelke, 1999), and adults can estimate the remaining time for catching a moving ball (McIntyre et al., 2001; Zago & Lacquaniti, 2005) even without visual information (Lacquaniti & Maioli, 1989; Zago et al., 2009). Further fMRI studies have revealed the parieto-insular vestibular cortex in the brain as a neural basis for the gravity-based stability inference (Fischer et al., 2016; Indovina et al., 2005). In sum, humans seem to accomplish stability inference by performing simulations (Hegarty, 2004; Ullman et al., 2017) with the built-in knowledge of gravity.

Incorporating the knowledge of gravity as a prior in the mind is not surprising, because our intelligence emerges and develops under the constraints of the physical world, thus it may well possess the characteristics of Newtonian Laws that govern the world. Indeed, building Newtonian Laws into the mind as models on the world, coined as the world model (Land, 2014; Tenenbaum et al., 2011), not only bestows

newborns with *a prior* knowledge as foundations for developing cognitive functions, but also enables the mind as a generative model to predict future events (Clark, 1998; Land, 2014; Tenenbaum et al., 2011). This idea is realized in a computational model (a.k.a., the intuitive physical engine), whose behavioral pattern of stability inference is similar to humans' (Battaglia et al., 2013). Recently, the concept of the world model has been introduced to computational neuroscience to explain how the brain works (Friston et al., 2021) to inspire artificial intelligence to improve generality and robustness (Matsuo et al., 2022), but its characteristics have not been systematically investigated. Here we used the paradigm of the stability inference (Battaglia et al., 2013) to explore how the human mind constructs the world model on gravity.

To do this, we first characterized the world model on gravity by measuring humans' sensitivity to the direction of gravity in stability inference with a game engine as a simulation platform. We found that the world model is not a faithful copy of Newtonian Laws on gravity; instead, it encodes gravity's direction as a Gaussian distribution with the vertical direction as the maximum likelihood of gravity's direction. The stochastic character of the world model on gravity fits nicely with humans' behaviors in evaluating the stability of stacks and explains the daily illusion that taller objects are considered more prone to collapse. A reinforcement learning framework was then devised to illustrate the origin of the world model on gravity through interaction with the real world. Finally, the ecological advantage of the world model on gravity was revealed to balance the accuracy and speed for making stability inference more efficient.

Results

The characteristics of the world model on gravity

The direction of gravity is perpendicular to the ground surface. Here, we first tested humans' sensitivity to gravity's direction to investigate how faithful our world model on gravity is to the gravity in the physical world. To do this, we used Pybullet (Coumans & Bai, 2016), a forward physics simulator, to manipulate gravity's direction, and asked the participants to judge whether collapse trajectories of unstable stacks were normal (Fig 1a, Supplementary Movie S1). The direction of simulated gravity was measured by a parameter pair (θ, φ) (Fig 1b), which determines the deviation of the direction of simulated gravity from the direction of gravity in the

physical world. Specifically, θ is the vertical component of the direction that

influences the degree of collapse, and φ is the horizontal component that determines

the orientation of collapse. We collected subjects' judgment on the normality of the

collapse while varying θ from 0 to 45º and φ from 0º to 360º of the whole force

space, and the normality ratio of the judgment on each angle pair was used to index

participants' sensitivity on the direction of gravity (Fig 1c). As expected, when θ

equals 0 (i.e., the direction of the simulated gravity is the direction of the natural

gravity), the participants likely reported the collapse trajectory was normal (accuracy:

91.0%, STD: 8.0%). The critical question is how participants' subjective feelings

about the normality of the collapse trajectory change as a function of θ. If our world

model on gravity is a faithful copy of the physical reality, we expect the immediate

detection of abnormality when θ is away from 0.

Fig 1. The characteristics of the world model on gravity. a) The design of the behavioral experiment. Left: with a rotating camera, a stack was rotated 360° for displaying the 3-dimensional appearance of the configuration. Middle: gravity's direction was randomly sampled from a spherical surface. Right: the physics simulator simulated the collapse trajectory of the stack under this selected direction, and the participants reported whether the collapse was normal. b) The spherical surface of gravity's direction was determined by two parameters θ and φ. c) The procedure of calculating the normality ratio as the function of the parameter pairs. Left: each cell represents the response of normality for a parameter pair within a run. Middle: responses for unsampled pairs were interpolated with the averaged responses along φ. Right: the normality ratio for each parameter pair was finally calculated by averaging responses across runs and across participants. d) Left: Gravity's direction encoded in the world model follows a Gaussian distribution with the vertical direction as the maximum likelihood. Note that the normality ratios for $\theta > 0$ were sampled from $\varphi \in (0°, 180°)$, and for $\theta < 0$ were sampled from $\varphi \in (180°, 360°)$. Right: The sphere represents the space of gravity's direction, with two poles showing upward and downward. Each dot in the sphere represents one parameter pair, and the color on a dot indicates the likelihood of the collapse trajectory under this gravity direction being judged normal. e) In a new world setting, gravity's direction is flipped upside down. Left: an exemplar collapse trajectory when gravity's direction was pointed upward. Right: a trajectory when the direction was away from the vertical upward. f) Gravity's direction was encoded in the world model when the gravity direction in the physical world was flipped. Error bar: standard error.

Contrary to this intuition, the subjective feeling of the abnormality did not become evident immediately when θ moved away from 0; instead, the ratio of reporting normality of collapse trajectory decreased gradually as the function of θ, which was the best fit with a Gaussian function with $\sigma = 19.9$ (Fig. 1d left). That is, the participants were 50.9% confident in reporting a collapse trajectory normal when the vertical offset of θ was 19.9°. In addition, the accuracy in detecting the abnormality was not affected by φ (Extended Data Fig. 2), consistent with the equally distributed gravity field in the physical world. This pattern is observed in all participants tested with σ varying from 11.1 to 37.1 (Extended Data Fig. 2). Therefore, the world model on gravity is unlikely a faithful copy of physical reality; instead, it encodes gravity's direction as a Gaussian distribution with the vertical direction as the maximum likelihood of gravity's direction (Fig 1d right)

To further test whether the world model on gravity, once established, is encapsulated from visual experience and task context, we inverted the virtual world upright down with gravity's direction pointing upward, and then asked the same group of participants to judge whether collapse trajectories were normal (Fig 1e, see Supplementary Movie S2). We found that the normality ratio also decreased gradually

as the function of θ (Fig. 1f, $\sigma = 17.2$; Extended Data Fig 3 for each participant),

which was not significantly different from that in the world when gravity pointed

downward. In fact, the σ of each participant in the upward condition was in high

agreement with the σ in the upside-down condition ($r = 0.91$, $p < 0.01$). That is, the

visual experience and task context apparently did not cognitively penetrate humans'

world model on gravity, suggesting that it is likely encapsulated as a cognitive

module.

How does the stochastic nature of the world model on gravity affect our

stability inference on objects? To answer this question, we recruited an independent

group of participants to estimate the stability of 60 stacks with different

configurations (Fig 2a), half of which were stable. For the other half of the unstable

configurations, a natural gravity simulator (NGS) (Fig 2b Top) was used to quantify

the degree of stability by measuring the proportion of unmoved blocks after the

collapse. During the experiment, the participants were required to judge how stable

each configuration was on a 0-7 scale without feedback, which was used to compare

with the stability estimated by the NGS. We found that there was a significant

correlation between the two estimates of stability (Fig 2b Bottom; $r = 0.70$, $p < 0.01$),

consistent with the previous finding (Battaglia et al., 2013). However, the participants

were more inclined to judge stacks as being more prone to collapse, as the points in

Fig 2b are more concentrated on the lower side of the diagonal line, which was

indexed by the inference bias (see Method) (inference bias = -0.31, $p < 0.01$). In other

words, the NGS did not accurately capture participants' inference bias on stability.

Therefore, we tested whether the world model on gravity better matches participants'

inference bias by constructing a mental gravity simulator (MGS) based on the

Gaussian distribution identified above. Specifically, in the simulation, a pair of (θ, φ)

was randomly sampled from the Gaussian distribution as gravity's direction (Fig 2c

Top), and the degree of stability was then quantified in the same way as the NGS. The

simulation was performed 100 times for each stack and the averaged stability was

used as the estimated stability by the MGS. Similarly, there was a significant

correlation between the estimates of stability between the participants and the MGS

(Fig 2c Bottom; $r = 0.75$, $p < 0.01$). Although the correlation was not significantly

increased by adopting the world model, the MGS perfectly captured participants'

judgment on stability as the points were evenly distributed along the diagonal line

(inference bias = 0.04, p > 0.05; see Extended Data Fig. 4 for the correspondence

when the MGS was implemented with different Gaussian functions). In other words,

the magnitude of correlation coefficients is not the sole indicator to evaluate the

fitness of the model. In short, the world model that represents gravity's direction as a

Gaussian distribution around the vertical direction properly explains our inclination of

judging stacks more prone to collapse.

Fig 2. Stability inference with the world model on gravity. a) An experiment to rate the stability of

stacks, where half of them is stable and the other half unstable. b) Top: the procedure of the natural

gravity simulator (NGS) in estimating the actual stability of stacks through simulation, and for unstable

stacks the stability is indexed by the proportion of displaced blocks. Bottom: the correlation between

the participants' stability inference and the actual stability by the NGS. Each dot represents one stack, and the lines denote the standard errors. c) Top: the procedure of the mental gravity simulator (MGS), where the stability of a stack was estimated by averaging estimated stabilities from multiple simulations with different gravity directions sampled from the world model. Bottom: the correlation between the participants' stability inference and the stability estimated by the MGS. d) Left: Illusion that taller objects are more unstable than shorter ones. Right: the stability bias is indexed by the difference between the stability estimated by the MGS and that by the NGS, and the larger the negative value, the more likely stacks are considered unstable. The x-axis denotes the height of a stack, which contained 10 blocks with each block's height, length and width being 1.2, 0.4 and 0.4. IB: inference bias. Error bar: standard error.

The world model that leads to participants' inference bias may explain the daily illusion that we consider taller objects are more unstable than shorter ones (i.e., inference bias, Fig 2d Left). An intuitive explanation from physics is that a tall object has a higher center of gravity, and thus external disturbance makes it more likely to collapse. Our world model on gravity, on the other hand, provides an alternative explanation without introducing external disturbance, simply because deviations from gravity's veridical direction likely accumulate with the height of the objects. To examine this conjecture, we constructed a set of configurations with different heights, and estimated the degree of configurations' stability with the MGS and NGS respectively. The inference bias was calculated by the difference between the stability estimated from the MGS and NGS, with negative values indicating the inclination of judging a stable stack as an unstable one. Consistent with the inference bias found in humans, the MGS found objects with all heights are more prone to collapse (Fig 2d Right; inference bias < 0, p < 0.01 for all heights). Critically, the bias increased monotonically with the increase of heights, consistent with the illusion that taller objects are more prone to collapse (Fig 2d Right; see Extended Data Fig. 5 for the inference bias when the MGS was equipped with different levels of deviance). In short, the world model on gravity provides a more concise explanation of the daily illusion that taller objects are more prone to collapse without assuming external disturbance.

The origin of the stochastic world model on gravity

A deterministic model that combines gravity's veridical direction with external disturbance, such as external force or perceptual uncertainty (Battaglia et al., 2013), is

theoretically equivalent to our stochastic model that represents gravity's direction in a

Gaussian distribution; therefore, it also fits nicely with humans' judgment on stability

by fine-tuning the parameters of external disturbance. Although both the cognitive

impenetrability and the self-consistency without resorting to external disturbance

found in our study favor the stochastic model over the deterministic model, more

direct evidence comes from the origin of the world model on gravity.

Previous studies suggest that a world model likely emerges when a biological

agent interacts with the environment during evolution, where the mismatch between

external feedback from the environment and internal expectation from the world

model is used in turn to fine-tune the world model (Friston et al., 2021; MacKay,

1956; Matsuo et al., 2022). Here we designed a reinforcement learning (RL)

framework to model this interactive process to illustrate how the world model on

gravity evolves (Fig 3a). Specifically, an agent perceives a stack in the environment,

which is then acted upon by a simulated gravity with the direction parameters (i.e., θ

and φ) sampled from a spheric direction space. The initial weights for directions are

identical (Fig 3b, left). The final state of the stack serves as the agent's expectation

under the effect of the simulated gravity. The mismatch between the expectation and

the observed final state of the stack under the natural gravity is used to update the

sampling probability of the direction space, where a larger difference leads to a larger

drop in probabilities through RL. Within this RL framework, we constructed 100,000

configurations consisting of 2 to 15 blocks to train the world model on gravity. As the

training proceeded, the probabilities of the direction space gradually converged

downwardly (Fig 3b, middle). Although gravity's direction in the environment is

vertical, the distribution of updated probabilities in the direction space was

gradational ($\sigma = 21.6$; Fig 3b, right), which is close to the world model on gravity

derived from the psychophysics experiment on human participants. That is, the

probabilities' gradients only occurred along the parameter of θ, not along the

parameter of φ. Therefore, the world model that represents gravity in a Gaussian

distribution can emerge automatically during the interaction between the agent and

the environment without the interference of any external disturbance.

Fig 3. The origin of the world model on gravity. a) The reinforcement learning framework to update

gravity's direction (θ, φ) of the world model by minimizing the difference between the expectation

from internal simulation (i.e., simulated states) and the observation from the physical world (i.e., actual

states). b) Gravity direction equally distributed in the spherical surface gradually converged downward

as the training proceeded, and finally stabilized in a gaussian distribution with the vertical direction as

the maximum likelihood of gravity's direction. Color denotes the probability of a parameter pair being

adopted as gravity's direction. c) Left: World models constructed by reinforcement learning when

stacks in the physical world are composed of different numbers of blocks ranging from 2 to 15. Right:

The variance of the Gaussian distribution, illustrated by the width of the distribution of gravity's

direction in a spherical surface, monotonically decreased as the number of blocks in stacks increased.

To further illustrate the idea that biological intelligence emerges under the

constraint of the physical world, we then systematically manipulated the appearance

of the physical world while keeping the natural gravity constant. Specifically, we

constructed 14 worlds, which contained stacks with a variety of configurations but

were constructed by the same number of blocks ranging from 2 to 15 blocks. That is,

the world consisting of 2-block stacks is more stable than the world consisting of 15-

block stacks in general. We respectively trained the world model on gravity under the

same RL framework for each world, and found that all world models represented

gravity's direction in a Gaussian distribution (Fig 5c Left; see Extended Data Fig. 6

for all world models). However, the width of the distribution, indexed by the

parameter of σ, decreased monotonically as the number of blocks increased (Fig 5c

Right), showing that the representation of the gravity's direction becomes more

accurate when the agent learned the gravity in a less stable world. Therefore, the

world model on gravity echoes not only the physical law governing the environment

but also the properties of the environment the agent encountered.

The ecological advantage of the stochastic world model on gravity

When we pass by a cliff face, we have to be constantly aware of the stability of the

rocks on the cliff. The ideal response would be both accurate and fast, but accuracy

and speed are often difficult to achieve simultaneously. Here we examined how the

world model on gravity balances these two factors. To answer this question, we used a

linear classifier (i.e., logistic regression) to simply model humans' decision-making

behavior at different stages of the mental simulation. Specifically, we collected all

position coordinates of a stack's blocks at different stages of the simulation. The

position difference between the intermediate states of the stack and the original state

provides information about the stability of the stack. For example, a stable stack shall

show no difference in the positions of component blocks at all stages of the

simulation, and the difference in positions for an unstable stack shall gradually

increase. If the linear classifier detected the difference in positions at any stage, it

classified the stack as unstable, otherwise stable (Fig 4a). The classification accuracy

increased gradually as the simulation proceeded, until it reached the asymptote. As

expected, with the NGS, the accuracy at the plateau was close to 100% (95.3% on

average, Fig 4b Top red box), significantly higher than that with MGS (80.1% on

average, Fig 4b Top blue box) (t = 19.59, p<0.001), simply because the MGS did not

accurately represent gravity's veridical direction. However, the MGS reached the

plateau of decision accuracy much faster than the NGS (response time, indexed by the

ratio between the time to reach the plateau and that to reach the final stage: 27.1% vs.

75.2%, t = 15.58, p < 0.001) (Fig 4b Middle). The same pattern was also observed

with different variances of the Gaussian distribution (Extended Data Fig. 7). That is,

the world model on gravity prioritizes speed over accuracy, echoing the basic

principle of survival: fleeing potential danger as quickly as possible, rather than

making a perfect decision with a dreadful delay. In addition, by integrating the

prediction accuracy and the response time as the measurement of efficiency, we found

the world model provides a better balance of accuracy and speed, with an efficiency

significantly higher than that provided by the NGS (3.49 vs. 1.32, $t = 9.12$, $p < 0.001$;

Fig 4d).

Fig 4. The balance of accuracy and speed of the world model on gravity. a) Illustration to model

humans' decision-making behavior at different stages of the mental simulation using the NGS and

MGS. b) The decision of the linear classifier based on the simulation of the MGS was less accurate

than that of the NGS (top), but the decision was made more quickly in the MGS than in the NGS

(middle). When combining both accuracy and speed, the MGS showed better efficiency than the NGS

(bottom). c) The relation between the times of simulations and the variance of estimated stability. d)

The difference in the variance of estimated stability between the participants and the MGS. The

difference was minimal when the MGS performed the simulation three times. Error bar: standard error.

On the other hand, when time permits, multiple simulations by the MGS can

greatly reduce the variance led by stochastic representations on gravity's direction

(Fig 4c). To explore whether humans adopt this strategy of performing multiple simulations before decision, we ran simulations with the MGS at various times, and then matched them with humans' performance. We found that the variance of humans' judgment on stability was best matched with that of the MGS after simulating three times (Fig 4d; see Extended Data Fig. 8 for the model-behavior correspondences under different numbers of simulations). Therefore, humans are likely to use MGS simulations a limited number of times to infer the stability of stacks.

Discussion

In this study, we investigated how the physical law of gravity is embodied in the mind as a world model to guide the inference of the stability of objects. A series of psychophysics experiments showed that the world model on gravity is not a faithful copy of the physical world; instead, it is a stochastic model on gravity's direction that captures the essence of the vertically downward direction of gravity as the maximum likelihood of a Gaussian distribution. The stochastic nature of the world model not only fits more nicely with humans' behaviors on stability inference than the discriminative model, but also provides new insight into a daily illusion that taller objects are more prone to collapse. Finally, we constructed a framework of reinforcement learning to reveal a possible way for the stochastic nature of the world model to evolve through the interaction with the physical world, and it is likely through the nature of the interaction between humans and the environment that the world model well balances the accuracy and speed to produce a unique ecological advantage for our survival in the physical world.

About 300 years ago, the philosopher Immanuel Kant proposed the intuition of space and time as *a priori* knowledge in the mind for us to understand the physical world (Kant, 1781), but only until recently researchers investigate how the intuition is implemented in the mind as the intuitive physics (Kubricht et al., 2017; McCloskey, 1983; McCloskey et al., 1983). Under the Noisy Newtonian Framework, intuitive physics is depicted as a combination between Newtonian Physics and uncertainty generated by the noises (Battaglia et al., 2013; Kubricht et al., 2017; Sanborn et al., 2013). The introduction of uncertainty helps to reconcile the misconception occurring under unfavorable conditions, including unfamiliar events or static scenes (Kaiser et

al., 1986, 1992; Kim & Spelke, 1999; McCloskey et al., 1980; Smith & Vul, 2013), which was once thought as supporting evidence for Aristotelian Physics (DiSessa, 1982; Halloun & Hestenes, 1985). The noise in previous studies supposedly originated from sources such as perceptual uncertainty or external disturbance of forces, rather than the intuitive physical engine that is thought of as a deterministic system. Our study extends these deterministic models by showing a stochastic model that the noise instead came from the representation of gravity's direction under Gaussian distribution. The inherent stochastic nature of the world model on gravity does not need to rely on external noises to explain humans' unstable illusion of taller objects, and is also confirmed by the cognitive impenetrability of the Gaussian distribution of gravity's direction when the gravity's direction in the physical world was inverted upside down (Pylyshyn, 1980).

With a reinforcement learning framework, we further demonstrated a possible origin of the stochastic nature of the world model through interaction with the physical world. In contrast to summarizing statistical patterns from experiences (Bear et al., 2021; Li et al., 2016; Zhang et al., 2016), this framework is designed to simulate how a biological agent acquires knowledge on gravity through evolution. Specifically, a world model with undifferentiated directions of gravity generates a prediction on the stability of an object, and the error from the mismatch between the prediction and the observation on the object from the physical world is used to fine-tune the distribution of the directions in the world model. This process is similar to the fact that humans update their internal knowledge by comparing simulated expectations (Hegarty, 2004; Ullman et al., 2017) with actual observations (Baillargeon, 1994, 2004; Kotovsky & Baillargeon, 2000). After several generations of minimizing errors, a Gaussian distribution of gravity's direction with the vertically downward direction as the maximum likelihood is similar to that observed in the world model of humans. Interestingly, when physical worlds that the agent interacted with changed their appearance with configurations consisting of different numbers of blocks, the world models maintained their general patterns but the stochastic representation of gravity's direction changed accordingly, as the representation becomes more faithful to the physical world when the variety of configurations increased. This finding not only shows the robustness of the active inference (Hegarty, 2004; Ullman et al., 2017) that efficiently encodes critical features under various physical worlds, but also echoes the idea that intelligence develops under the

constraint of the physical world. Taken together, the findings from the RL framework imply that the world model on gravity in humans may also be constructed in the same way possible through the mechanism of the predictive coding (Friston, 2018; Huang & Rao, 2011).

Our world model on gravity provides an example of the world model theory that emphasizes the predictive nature of neural networks implemented with *a priori* knowledge about the physical world (Friston et al., 2021; Land, 2014; Matsuo et al., 2022). In contrast to traditional discriminative neural networks that learn statistical patterns for stability from gigantic amounts of labeled configurations, the world model equipped with the Noisy Newtonian Framework relies much less on experiences. The stochastic nature of the model further increases the efficiency by balancing accuracy and speed, which promotes our chances of better survival (Cosmides & Tooby, 1997) and adaptation to new environments (e.g., astronauts in outer space (Wang et al., 2022)). Indeed, the close link between human cognition and the physical world through interaction may shed light on developing a new generation of AI with human-like intelligence that can flexibly work in open-ended environments (Marcus, 2018, 2020).

Methods
Creating stacks with different configurations

We designed a block-stacking procedure in a physical simulation platform (PyBullet) to generate stacks with different configurations. All stacks used in this study were generated using this procedure with the same parameters listed below.

The block-stacking procedure includes three steps (Extended Data Fig. 1a): (1) defining the designated area, (2) stacking blocks, and (3) fine-tuning block positions. The first step is to designate a restricted place area. All blocks of a stack were required to place within the designated area. The designated area controls the aggregation level of blocks, with a small area clustering blocks closer than a large area. The designated area is determined by two horizontal parameters x and y, which separately represent the size of the area in two horizontal directions. Therefore, when the block number is fixed, a smaller area in general constructs a higher stack. After designating the area, in step two we stacked blocks in random horizontal positions within the area one by one. If no block was positioned under a new block, the new

block would be directly placed on the ground, otherwise it would stack on the

positioned block. The horizontal position of each block was independently sampled

from a uniform distribution, with lower and upper bounds being -*x* and +*x*, or -*y* and

+*y* separately (*x* and *y* were all independently sampled from a uniform distribution

$U(0.2, 2.0)$). The first two steps allow us to generate a large number of configurations

within the designated area, which is the only restriction of the block-stacking

procedure. To better control the physical stability of each stack, in step three we fine-

tuned blocks in the stack by adjusting overlaps between every neighboring one, which

was randomly sampled from a uniform distribution $U(0.2, 0.8)$. Smaller overlap

between neighboring blocks is more likely to construct unstable stacks, whereas

bigger overlap results in more stable stacks. The overlap of neighboring blocks

without contact is set to 0. Note that the overlap between neighboring blocks is not the

only factor to determine the stability of a stack, and step three is used to generate

stacks without consuming too many computational resources.

The size of each block has a 3D aspect ratio of 3:1:1 (length: width: height),

with an arbitrary unit of 1.2:0.4:0.4. This constitutes three types of blocks (length,

width or height is 1.2, respectively, see Extended Data Fig. 1b). Each block of a stack

was randomly selected as one of the three types of blocks. The mass of each block is

set to 0.2 kg, and the friction coefficients and the coefficients of restitution between

blocks are set to 1 and 0, respectively.

Estimating the stability of a stack

The stability of a stack was obtained by a rigid-body forward simulation under the

natural gravity environment (i.e., natural gravity simulator, NGS). The direction of the

natural gravity points downward (i.e., $\vec{G} = (0, 0, -9.8)$), and all blocks of a stack are

affected by the same gravity. Gravity is the only factor for changing the state of each

block, and no external force is added during the simulation. Within each simulation,

we recorded 500 simulation stages. In each stage, the center position of each block

was collected to measure the stability of the stack. If the position of any block does

not change during the simulation, the stack is considered as stable, otherwise unstable.

We formulate the stack's state according to the below criteria:

$$Stable: \forall t \land \forall m, |P_{tm} - P_{0m}| < \varepsilon$$
$$Unstable: \exists t \lor \exists m, |P_{tm} - P_{0m}| > \varepsilon \qquad (1)$$

464   Where t is a simulation stage, m is the block number of a stack, P_{tm} is the position of

465   the block m at stage t, and ε is the just noticeable difference (i.e., j.n.d) of the

466   perception, which is set to 0.01.

467   The stability of a stack is further calculated by measuring the proportion of

468   displaced blocks, which is formulated as the following,

$$Stability = \frac{\sum_{m=1}^{M} \mathbb{I}(|P_{Tm} - P_{0m}| < \varepsilon)}{M} \tag{2}$$

469   Where M is the total number of blocks of a stack, and T is the final stage of the

470   simulation (i.e., T = 500). $\mathbb{I}(\cdot) = 1$ when $|P_{Tb} - P_{0b}| < \varepsilon$, which denotes that the

471   stack is stable.

Measuring participants' sensitivity to gravity's direction

474   We decomposed gravity's direction into three independent components (Fig. 1b).

$$G_x = g \sin \theta \cos \varphi$$
$$G_y = g \sin \theta \sin \varphi \tag{3}$$
$$G_z = g \cos \theta$$

Where g is the magnitude of the gravity (g = 9.8), which was fixed in this study. θ

represents the vertical component, and φ represents the horizontal component. The

direction of the gravity was determined by the angle pair (θ, φ), where θ affects the

extent of the collapse, and φ affects the orientation of the collapse. When θ is 0,

gravity's direction is vertical.

We performed a psychophysics experiment to measure humans' sensitivity to

gravity's direction. In this experiment, 10 participants (5 female, age range: 21-28)

from Tsinghua University were recruited to finish four runs of the behavioral

experiment, which measured their ability to detect the abnormality of stacks' collapse

trajectories. The experiment was approved by the Institutional Review Board of

Tsinghua University, and informed consent was obtained from all participants before

the experiment.

The collapse trajectory of a stack was solely determined by gravity with

different directions, where larger values of θ and φ made the trajectories more

abnormal. A pilot experiment showed that θ greater than 45 degrees made the

collapse trajectory abnormal to most participants, and therefore in the experiment, θ

ranges from 0 to 45 degrees with a step of 3 degrees. φ ranges from 0 to 360 degrees

with a step of 24 degrees. Therefore, θ and φ consists of 16 values respectively,

which were randomly combined into 96 pairs of (θ, φ) with each value repeating 6

times in each run. In a trial, an unstable stack was constructed, and then the camera

rotated one circle to show the 3D configuration of the stack to participants

(Supplementary Movie S1). The configuration was randomly selected from a dataset

that contains more than 2,000 unstable stacks, which was generated with the block-

stacking procedure before the experiment. Each stack in the database was constructed

with 10 blocks, and the color of each block was randomly rendered. There was a 1-sec

delay after the rotation, during which the participants were instructed to infer the

collapse trajectory based on the configuration. Then, simulated gravity with a

direction determined by an angle pair (θ, φ) was applied to the stack, and the stack

started to collapse. If the collapse trajectory met participants' expectations, they were

instructed to choose 'Normal', otherwise 'Abnormal'. Once the judgment was made,

the next trial started immediately. Each trial lasts about 10 seconds, making a total of

16 minutes for a run.

In addition, to test if participants' sensitivity to gravity's direction is

encapsulated from visual experience and task context, we flipped gravity's direction

upside down by inverting the camera's view, and the rest procedure remained the

same.

To calculate participants' sensitivity to gravity's direction, we converted their

behavioral judgment into normality ratio, which is the percentage that a trajectory was

judged as normal, which was calculated as below:

$$Ratio_{\theta,\varphi} = \frac{n_{\theta,\varphi}}{N_{\theta,\varphi}} \tag{4}$$

Where $n_{\theta,\varphi}$ is the number of trajectories that were judged as 'Normal' with the angle

pair (θ, φ), $N_{\theta,\varphi}$ is the total number of trajectories with the same angle pair. Because

the angle pairs tested were a subset of all possible angle pairs, we used the average

ratio along φ as the ratio of angle pairs untested (Fig. 1c). Finally, we calculated

participants' sensitivity by fitting their normality ratios at different θ to a Gaussian

distribution.

$$Ratio_{\theta} = Ae^{-\frac{\theta^2}{2\sigma^2}} \tag{5}$$

520   Where $Ratio_{\theta}$ is the normality ratio of θ, which was calculated by averaging the

521   normality ratio along all φ_s, A is the magnitude of the gaussian curve, σ is the

522 variance of the Gaussian curve. The best-fitted σ was used to index participants'

523 sensitivity to gravity's direction, and a larger σ indicates a lower sensitivity.

Measuring participants' ability on stability inference

Another group of 11 participants (5 female, age range: 21-32) from Tsinghua

University completed a behavioral experiment for judging the stability of 60 stacks.

The experiment was approved by the Institutional Review Board of Tsinghua

University, and informed consent was obtained from all participants before the

experiment. One male participant (age: 25) was excluded from further analyses

because his judgment showed an extremely weak correlation with the actual stability

of stacks (r_s < 0.30 for all experimental runs), as compared to the rest of the

participants.

The stacks contained 26 unstable stacks and 34 stable stacks, which were

randomly interleaved in each run. The participants were instructed to judge stacks'

stability on an 8-point Likert scale, with 0 referring to 'definitely unstable' and 7 to

'definitely stable'. There was no feedback after each judgment. The participants

completed six runs, within which the same group of stacks was presented but the

sequence, blocks' colors and camera's perspective were all randomized. After the

experiment, only two participants reported that they suspected a few stacks were

repeated in different runs, but they were unable to locate the stacks that they

suspected. Besides, their behavioral performance was not significantly different from

other participants.

Participants' stability judgment was rescaled to 0 and 1 to match the scale of

the stacks' stability. The participants' inference bias (IB) was indexed as the

difference in stability judgment between the participants and the NGS, shown as

$$IB = Stability_{human} - Stability_{NGS} \qquad (6)$$

547 Negative IB indicates participants had a tendency of considering a stable stack as an

548 unstable one.

Estimating the stability of stacks based on the stochastic world model on gravity

The actual stability of a stack can be calculated with a one-time simulation of NGS ($\vec{G}$

= (0, 0, -9.8)). In contrast, the stochastic nature of mental gravity requires a multiple-

time simulation with different gravity's direction. Specifically, we first randomly

sampled several angle pairs (θ_s, φ_s) from the Gaussian distribution of gravity's

directions in humans. The distribution was the average of two distributions acquired

from the real world (i.e., gravity's direction is downward) and the inverted world (the

direction is upward), with angles having larger normality ratios more likely being

sampled. We then applied the simulated gravity with these sampled directions to the

stack and used the averaged stability with these directions as the stability of the stack

estimated by the MGS. Similar to the IB between the participants and the NGS, the IB

between the MGS and NGS was calculated as

$$IB = Stability_{MGS} - Stability_{NGS} \tag{7}$$

Stacks of different heights were created to investigate whether the stochastic

world model on gravity results in the illusion that tall objects are considered less

stable than short ones. The height of a stack was correlated with the size of the

designated area, with a smaller area size corresponding to taller stacks. Therefore, we

designated several square areas with different sizes. The side length of the squares

ranged from 0.2 to 2.0, with an increase of 0.1. For each square, we used the block-

stacking procedure to generate 100 stable and 100 unstable stacks consisting of 10

blocks. The height of each stack was the height of the highest block.

Investigating the origin of the stochastic world model on gravity

A reinforcement learning (RL) framework was used to simulate the development of

the stochastic nature of the world model on gravity. To do this, we first created stacks

whose block number ranged from 2 to 15 with the block-stacking procedure, and

initialized a spherical force space, where θ ranged from 0 to 180 degrees and φ from

0 to 360 degrees. The spherical space covered all possible force directions, with the

initial probability of being sampled by the MGS identical. During the training, three

angle pairs (θ_s, φ_s) were sampled according to the probability of the spherical space,

and then applied to a stack for simulating its collapse trajectory, which was divided

into 500 stages. We optimized the sampling probability of gravity's direction by

comparing the estimated stability (i.e., expectation) with the actual stability (i.e.,

observation) as a Q value, with a higher Q value suggesting that the sampled gravity's

direction more likely mismatched the actual gravity's direction. The Q value was

calculated as

$$Q = \frac{\sum_{m=1}^{M} \mathbb{I}(|P_{m,(\theta,\varphi)} - P_m| < \varepsilon)}{M} \tag{8}$$

586   Where $P_{m,(\theta,\varphi)}$ is the final position of block m with gravity's direction (θ, φ), P_m is

587   the final position of block m with NGS, M is the block number of the stack, and the

588   j.n.d. ε is set to 0.01. The mismatch between the expectation and the observation was

589   used to update the sampling probability of the angle pair using a temporal difference

590   optimization

$$W_{\theta,\varphi} \leftarrow W_{\theta,\varphi} + \gamma(Q - W_{\theta,\varphi}) \tag{9}$$

591   Where $\gamma = 0.15$ as the learning rate. This process was iterated to update the sample

592   probability of angle pairs (θ_s, φ_s) until the training stopped. We prepared 100,000

593   configurations for the training.

Evaluating the ecological advantage of the model

To investigate how the world model on gravity balances response accuracy and speed,

we trained a linear classifier (i.e., logistic regression) to model humans' decision-

making process at different stages of the simulation. During the simulation, the same

stack was separately simulated using the NGS and MGS, and we collected the

position coordinates of all blocks at each stage. Differences in the positions of the

blocks between the intermediate stage and the original stage provided information

about the stability of a stack, with more displaced blocks suggesting the lower stack's

stability. As the simulation proceeded, differences in position gradually accumulated

for unstable stacks, otherwise unchanged for stable stacks. The linear classifier was

trained to judge whether a stack is stable with differences in position as inputs.

We used the block-stacking procedure to create stacks consisting of 2 to 10

blocks, and estimated their stabilities with the NGS for simulation in 500 stages. For

each block number, there were 100 stable and 100 unstable stacks to train the linear

classifier, and its prediction accuracy was measured with another group of 100 stable

and 100 unstable stacks at every simulation stage.

The difference in positions of each block between the intermediate stage and

the original stage was used as the input of the linear classifier. Specifically, we

collected all vertex positions of a block during the simulation to acquire the difference

in position, which included 8 coordinate points for each block in each stage. We did

not collect the central position as previously used in the stability estimation, simply

because it did not provide information on the shape and size of the block. We

separately performed the simulation using the MGS and NGS, and calculated the

difference in position between the intermediate stage and the original stage, then

flattened the difference to generate 24 position features for each block (i.e., 8

positions per block in three-dimensional space). Therefore, for a 10-block stack, for

example, there were 240 position features were prepared as the input of the linear

classifier.

Prediction accuracy at each stage was estimated by evaluating whether a stack

tested is stable with the MGS or with the NGS. The highest accuracy in the whole

simulation stages was used as the prediction accuracy. Accordingly, the first

simulation stage to reach the maximum accuracy provided information on response

speed: reaching the maximum accuracy with a smaller number of stages indicates the

classifier model accomplishes stability inference in a shorter amount of time (i.e.,

quick response). Therefore, we measured the response speed by estimating the steps

to reach the accuracy plateau.

$$Time = \frac{\hat{t}}{T}$$

$$\hat{t} = arg \max_{t} Accuracy_t \qquad (10)$$

Where $Accuracy_t$ is the accuracy of stage t. $\hat{t}$ is the stage that a linear classifier

acquires the maximum accuracy for the first time, T is the total stage number of each

simulation (T = 500). Higher values indicate longer response time (i.e., slower

response). Finally, the efficiency of the stability inference, which is the balance

between accuracy and speed, by dividing the prediction accuracy by the response

time.

$$Efficiency = \frac{Accuracy}{Time} \qquad (11)$$

References

640   Baillargeon, R. (1994). How do infants learn about the physical world? *Current*

641   *Directions in Psychological Science, 3*(5), 133–140.

642   Baillargeon, R. (2004). Infants' physical world. *Current Directions in Psychological*

643   *Science, 13*(3), 89–94.

Battaglia, P. W., Hamrick, J. B., & Tenenbaum, J. B. (2013). Simulation as an engine of physical scene understanding. *Proceedings of the National Academy of Sciences*, *110*(45), 18327–18332.

Bear, D. M., Wang, E., Mrowca, D., Binder, F. J., Tung, H.-Y. F., Pramod, R., Holdaway, C., Tao, S., Smith, K., Sun, F.-Y., & others. (2021). Physion: Evaluating physical prediction from vision in humans and machines. *ArXiv Preprint ArXiv:2106.08261*.

Clark, A. (1998). Embodiment and the philosophy of mind. *Royal Institute of Philosophy Supplements*, *43*, 35–51.

Cosmides, L., & Tooby, J. (1997). *Evolutionary psychology: A primer*.

Coumans, E., & Bai, Y. (2016). *Pybullet, a python module for physics simulation for games, robotics and machine learning*. https://pybullet.org

DiSessa, A. A. (1982). Unlearning Aristotelian physics: A study of knowledge-based learning. *Cognitive Science*, *6*(1), 37–75.

Fischer, J., Mikhael, J. G., Tenenbaum, J. B., & Kanwisher, N. (2016). Functional neuroanatomy of intuitive physical inference. *Proceedings of the National Academy of Sciences*, *113*(34), E5072–E5081.

Friedman, W. J. (2002). Arrows of time in Infancy: The representation of temporal–causal invariances. *Cognitive Psychology*, *44*(3), 252–296.

Friston, K. (2018). Does predictive coding have a future? *Nature Neuroscience*, *21*(8), 1019–1021.

Friston, K., Moran, R. J., Nagai, Y., Taniguchi, T., Gomi, H., & Tenenbaum, J. (2021). World model learning and inference. *Neural Networks*, *144*, 573–590.

Halloun, I. A., & Hestenes, D. (1985). Common sense concepts about motion. *American Journal of Physics*, *53*(11), 1056–1065.

Hegarty, M. (2004). Mechanical reasoning by mental simulation. *Trends in Cognitive Sciences*, *8*(6), 280–285.

Huang, Y., & Rao, R. P. (2011). Predictive coding. *Wiley Interdisciplinary Reviews: Cognitive Science*, *2*(5), 580–593.

Indovina, I., Maffei, V., Bosco, G., Zago, M., Macaluso, E., & Lacquaniti, F. (2005). Representation of visual gravitational motion in the human vestibular cortex. *Science*, *308*(5720), 416–419.

Kaiser, M. K., Jonides, J., & Alexander, J. (1986). Intuitive reasoning about abstract and familiar physics problems. *Memory & Cognition*, *14*(4), 308–312.

Kaiser, M. K., Proffitt, D. R., Whelan, S. M., & Hecht, H. (1992). Influence of

animation on dynamical judgments. *Journal of Experimental Psychology: Human*

Perception and Performance, *18*(3), 669.

Kant, I. (1781). *The Critique of Pure Reason*.

Kim, I.-K., & Spelke, E. S. (1999). Perception and understanding of effects of gravity

and inertia on object motion. *Developmental Science*, *2*(3), 339–362.

Kotovsky, L., & Baillargeon, R. (2000). Reasoning about collisions involving inert

objects in 7.5-month-old infants. *Developmental Science*, *3*(3), 344–359.

Kubricht, J. R., Holyoak, K. J., & Lu, H. (2017). Intuitive physics: Current research

and controversies. *Trends in Cognitive Sciences*, *21*(10), 749–759.

Lacquaniti, F., & Maioli, C. (1989). Adaptation to suppression of visual information

during catching. *Journal of Neuroscience*, *9*(1), 149–159.

Land, M. F. (2014). Do we have an internal model of the outside world?

Philosophical Transactions of the Royal Society B: Biological Sciences, *369*(1636),

20130045.

Li, W., Azimi, S., Leonardis, A., & Fritz, M. (2016). To fall or not to fall: A visual

approach to physical stability prediction. *ArXiv Preprint ArXiv:1604.00066*.

MacKay, D. M. (1956). The epistemological problem for automata. In *Automata*

Studies.(AM-34), Volume 34 (pp. 235–252). Princeton University Press.

Marcus, G. (2018). Deep learning: A critical appraisal. *ArXiv Preprint*

ArXiv:1801.00631.

Marcus, G. (2020). The next decade in ai: Four steps towards robust artificial

intelligence. *ArXiv Preprint ArXiv:2002.06177*.

Matsuo, Y., LeCun, Y., Sahani, M., Precup, D., Silver, D., Sugiyama, M., Uchibe, E.,

& Morimoto, J. (2022). Deep learning, reinforcement learning, and world models.

Neural Networks.

McCloskey, M. (1983). Intuitive physics. *Scientific American*, *248*(4), 122–131.

McCloskey, M., Caramazza, A., & Green, B. (1980). Curvilinear motion in the

absence of external forces: Naive beliefs about the motion of objects. *Science*,

210(4474), 1139–1141.

McCloskey, M., Washburn, A., & Felch, L. (1983). Intuitive physics: The straight-

down belief and its origin. *Journal of Experimental Psychology: Learning, Memory,*

and Cognition, *9*(4), 636.

McIntyre, J., Zago, M., Berthoz, A., & Lacquaniti, F. (2001). Does the brain model

Newton's laws? *Nature Neuroscience*, *4*(7), 693–694.

Pylyshyn, Z. W. (1980). Computation and cognition: Issues in the foundations of

cognitive science. *Behavioral and Brain Sciences*, *3*(1), 111–132.

Sanborn, A. N., Mansinghka, V. K., & Griffiths, T. L. (2013). Reconciling intuitive

physics and Newtonian mechanics for colliding objects. *Psychological Review*,

120(2), 411.

Smith, K. A., & Vul, E. (2013). Sources of uncertainty in intuitive physics. *Topics in*

Cognitive Science, *5*(1), 185–199.

Tenenbaum, J. B., Kemp, C., Griffiths, T. L., & Goodman, N. D. (2011). How to

grow a mind: Statistics, structure, and abstraction. *Science*, *331*(6022), 1279–1285.

Ullman, T. D., Spelke, E., Battaglia, P., & Tenenbaum, J. B. (2017). Mind games:

Game engines as an architecture for intuitive physics. *Trends in Cognitive Sciences*,

21(9), 649–665.

Wang, Y., Zhang, X., Wang, C., Huang, W., Xu, Q., Liu, D., Zhou, W., Chen, S., &

Jiang, Y. (2022). Modulation of biological motion perception in humans by gravity.

Nature Communications, *13*(1), 1–10.

Zago, M., & Lacquaniti, F. (2005). Visual perception and interception of falling

objects: A review of evidence for an internal model of gravity. *Journal of Neural*

Engineering, *2*(3), S198.

Zago, M., McIntyre, J., Senot, P., & Lacquaniti, F. (2009). Visuo-motor coordination

and internal models for object interception. *Experimental Brain Research*, *192*(4),

571–604.

Zhang, R., Wu, J., Zhang, C., Freeman, W. T., & Tenenbaum, J. B. (2016). A

comparative evaluation of approximate probabilistic simulation and deep neural

networks as accounts of human physical scene understanding. *ArXiv Preprint*

ArXiv:1605.01138.

740
741
742

Acknowledgments

Funding: This study was funded by Beijing Municipal Science & Technology Commission, Administrative Commission of Zhongguancun Science Park (Z221100002722012), the Shuimu Tsinghua Scholar Program (T.H.), Tsinghua University Guoqiang Institute (2020GQG1016), Tsinghua University Qiyuan Laboratory, and Beijing Academy of Artificial Intelligence (BAAI).

Author contributions: J.L. conceptualized the study. T.H. designed and conducted the experiments. T.H. analyzed data. T.H. and J.L. wrote the manuscript.

Competing interests: Authors declare no competing interests.

Data and materials availability: All code and data underlying our study and necessary to reproduce the results are available on Github: https://github.com/helloTC/GravityWorldModel.

757 **Extended Data Fig.1**

758
Extended Data Fig. 1 **Construction of stacks with different configurations.** a) Illustration of the

block-stacking procedure to create stacks in different configurations. A configuration was constructed

by placing multiple blocks within a designated area. If there was no positioned block in the area, a new

block was placed on the ground; otherwise, it was placed on the top of the positioned block. b) Three

types of blocks with an aspect ratio of 3:1:1. c) This procedure can create a large number stacks with

different configurations within designated areas. Note that in small areas, the height of stacks was

taller. d) The lower bound of configurations' possible number showed an exponential relation with the

number of blocks in a stack. The procedure can create at least 3.72×10^{19} configurations for stacks

consisting of 10 blocks. See the appendix for the estimation.

768
769
770
771

Extended Data Fig.2

Extended Data Fig. 2 **The stochastic world model on gravity of each participant.** The normality
ratios of θ followed a Gaussian distribution, with the variance ranging from 11.1 to 37.1. No stochastic
characteristic was observed in φ.

Extended Data Fig. 3

Extended Data Fig. 2 **The stochastic world model on gravity of each participant when gravity's**

direction was inverted. The normality ratios of θ also followed a Gaussian distribution, with the

variance ranging from 9.1 to 28.4, and no stochastic characteristic was observed along φ.

Extended Data Fig. 4

Extended Data Fig. 4 **Relation between the stability estimated by the MGS stability and that by**

participants when the world model was implemented with different Gaussian functions. Only

when the world model embodied Gaussian functions with intermediate variance (i.e., $\sigma \in (15,20)$) did

the stability estimated by the MGS match participants' stability inference. On the other hand, when the

variance was small, most points were positioned below the diagonal line, indicating the model

considered stacks more stable in general as compared to participants' judgment. When the variance was

large, the model considered stacks less stable. Note that all models showed high correlation coefficients

regardless the bias. In other words, the magnitude of correlation is not a sole indicator to evaluate the

fitness of the model. IB: inference bias.

Extended Data Fig. 5

Extended Data Fig. 5 **Height illusion of stability inference when the world model was implemented with different Gaussian functions.** The illusion that tall objects are considered more unstable than short ones manifests at all levels of variances of Gaussian functions, with larger variance leading to a stronger illusion.

Extended Data Fig. 6

Extended Data Fig. 6 **The world models evolved in the world containing stacks with different numbers of blocks.** The number of blocks ranged from 2 to 15, and in all the worlds gravity's direction was in Gaussian distributions with the vertical direction as the maximum likelihood. Note that the world with stacks consisting of more block numbers led to smaller variances in the Gaussian function.

Extended Data Fig. 7

Extended Data Fig. 7 **Ecological advantage of the world model embodied with different Gaussian**

functions. a) Prediction accuracy decreased when the variance of the Gaussian function increased, and

reaches an asymptote of 0.75. b) Response time decreased as the variance increased, and reached an

asymptote of 0.20. c) The prediction accuracy and response time was combined as a measurement for

efficiency, which gradually increased monotonically as the function of the variance until an asymptote

of 4. Red box: the world model embodied no stochastic characteristic (i.e., the deterministic model);

Blue box: the world model with different levels of variances. Error bar: standard error.

Extended Data Fig.8

Extended Data Fig. 8 **The relation between the number of simulations and the variance of stability**

inference. The simulation showed that the variance of stability inference decreased with the number of

simulations. Note that the variance in the world model observed in participants best matched the

variance when the simulation of the MGS was conducted three times.

Appendix: Estimation of the lower bound of the possible number of
configurations
A configuration is a structure composed of several contact blocks. To simplify the
computation of estimating the number of possible configurations, here we constrained
the shape of blocks and the position where the blocks were placed.
The shape constraint: the blocks used to form a configuration are all uniform
rectangular blocks with the same aspect ratio.
The position constraint: only one block is allowed to be placed on the same
layer of the configuration.
Thus, the problem is then simplified to estimate the possible number of
configurations when only one rectangular block with the aspect ratio of $\alpha:\beta:\gamma$ (i.e.,
the shape constraint) is allowed to place in one layer (i.e., **the position constraint**).
Note that the constraints significantly reduce the number of estimated configurations.
We illustrated our solution by starting with a simple case: the aspect ratio of
blocks is $\alpha:\alpha:\alpha$.
845

846
847 **Appendix Fig 1.** An illustration of the procedure to estimate the possible number of configurations
848 when blocks have an aspect ratio of $\alpha:\alpha:\alpha$. (a) the cubic block with the length, width and height are α.
849 (b) Constructing a configuration by stacking two cubic blocks. The upper block could only be placed
850 within a $3\alpha \times 3\alpha$ area to guarantee contact with the lower block. (c) A three-block configuration can
851 be viewed as stacking a cubic block on a two-block configuration.
852

The condition when the aspect ratio of blocks is $\alpha:\alpha:\alpha$
The block with the aspect ratio of $\alpha:\alpha:\alpha$ is a cube (Appendix Fig 1a). The
side length of the cube is defined as α. Consider a configuration with two stacking
blocks, the upper block needs to be placed in a $3\alpha \times 3\alpha$ area to ensure contact with
the bottom block (Appendix Fig 1b). To estimate the possible number of this simple
situation, we defined a visual acuity v, which is the minimum resolution to distinguish
two stacks (i.e., j.n.d.). Note that v is a small value and here we set it as $v = 0.01$ to
match the minimal position difference for stability estimation in the simulation
platform (please see Methods). Therefore, the possible number of the configuration
containing two cubic blocks is

$$N_{C2} = (\frac{2\alpha}{v})^2 \tag{1}$$

Where N_{C2} indicates the possible number of configurations containing two cubic
blocks.
We further consider the situation with more cubic blocks. For a stack that
contains three cubic blocks, it can be viewed as placing a cubic block on a two-block
stack (Appendix Fig 1c). Therefore, the total possible number of configurations is the
multiplication of two two-block configurations, which is formulated as

$$N_{C3} = N_{C2} \times N_{C2} = N_{C2}{}^2$$

869 Similarly, the possible number of configurations for stacks containing four cubic
870 blocks is

$$N_{C4} = N_{C3} \times N_{C2} = N_{C2}{}^3$$

871 Accordingly, the possible number of configurations with M cubic blocks is

$$N_{CM} = N_{C(M-1)} \times N_{C2} = \cdots = N_{C2}{}^{M-1} = \left(\frac{2\alpha}{v}\right)^{2M-2}, M \geq 2 \qquad (2)$$

872   Now, we have introduced the basic idea of calculating the number of
873 configurations using a block with an $\alpha: \alpha: \alpha$ aspect ratio as a special case. Then we
874 generalized the idea to estimate the possible number when the block is rectangular
875 with the aspect ratio as $\alpha: \beta: \beta$.
876

877
878 **Appendix Fig 2.** An illustration of the procedure to estimate the possible number of configurations
879 when blocks have the aspect ratio of $\alpha: \beta: \beta$. (a) Three types of rectangular blocks with an aspect ratio
880 of $\alpha: \beta: \beta$. (b) There are nine possible two-block configurations when combining blocks with an aspect
881 ratio of $\alpha: \beta: \beta$. (c) A three-block configuration could be viewed as stacking a cubic block on a two-
882 block configuration.
883

The condition when the aspect ratio of blocks is $\alpha: \beta: \beta$
A block with the aspect ratio of $\alpha: \beta: \beta$ has three types, corresponding to the
sides of length, width and height are α and the rest sides are β ($\alpha: \beta: \beta$, $\beta: \alpha: \beta$, and
$\beta: \beta: \alpha$; see Appendix Fig 2a). For simplicity, we label the three basic blocks as A, B
and C. The three types of blocks can generate 9 (i.e., 3^2) two-block configurations in
total (Appendix Fig 2b). We calculate each of the possible numbers of two-block
configurations below.

$$N_{R2} = \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} \\ N_{BA} & N_{BB} & N_{BC} \\ N_{CA} & N_{CB} & N_{CC} \end{bmatrix}$$

(3)

$$= \frac{1}{v^2} \begin{bmatrix} 4\alpha\beta & (\alpha+\beta)^2 & 2\beta(\alpha+\beta) \\ (\alpha+\beta)^2 & 4\alpha\beta & 2\beta(\alpha+\beta) \\ 2\beta(\alpha+\beta) & 2\beta(\alpha+\beta) & 4\beta^2 \end{bmatrix}$$

The possible number of configurations for stacks containing two rectangular blocks with the aspect ratio of $\alpha:\beta:\beta$ is

$$N_{R2} = \sum N_{R2}$$

(4)

For a configuration containing three blocks, it can be viewed as a block stacked on a two-block stack (Appendix Fig 2c). Therefore,

$$N_{R3} = N_{..A} + N_{..B} + N_{..C}$$

(5)

Where $N_{..A}$ indicates the possible number when block A stacked at the upper layer, and each term can be expanded as below.

$$N_{..A} = N_{.A} \times N_{AA} + N_{.B} \times N_{BA} + N_{.C} \times N_{CA}$$
$$N_{..B} = N_{.A} \times N_{AB} + N_{.B} \times N_{BB} + N_{.C} \times N_{CB}$$
$$N_{..C} = N_{.A} \times N_{AC} + N_{.B} \times N_{BC} + N_{.C} \times N_{CC}$$

(6)

Combining equations (4), (5) and (6), we have

$$N_{R3} = \sum \left(\begin{bmatrix} N_{.A} & N_{.B} & N_{.C} \end{bmatrix} \times \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} \\ N_{BA} & N_{BB} & N_{BC} \\ N_{CA} & N_{CB} & N_{CC} \end{bmatrix} \right)$$

And

$$\begin{bmatrix} N_{.A} & N_{.B} & N_{.C} \end{bmatrix} = \begin{bmatrix} 1 & 1 & 1 \end{bmatrix} \times \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} \\ N_{BA} & N_{BB} & N_{BC} \\ N_{CA} & N_{CB} & N_{CC} \end{bmatrix}$$

Therefore,

$$N_{R3} = \sum (N_{R2}^2)$$

(7)

Following a similar logic, the possible number of configurations containing M blocks with an aspect ratio of $\alpha:\beta:\beta$ is

$$N_{RM} = \sum (N_{R2}^{M-1}), M \geq 2$$

(8)

The aspect ratio of blocks is $\alpha:\beta:\gamma$

We further generalize the problem by considering the aspect ratio of blocks as $\alpha:\beta:\gamma$. This forms six different types: $\alpha:\beta:\gamma, \alpha:\gamma:\beta, \beta:\alpha:\gamma, \beta:\gamma:\alpha, \gamma:\alpha:\beta, \gamma:\beta:\alpha$, for each type the three proportional values corresponding to length, width and height, respectively. We label the six types of blocks as A, B, C, D, E, F, and G for simplicity.

Following the similar logic as above, different types of blocks generated 36 (i.e., 6^2) two-block configurations in total, and the possible number of each two-block configuration is

$$N_{R2} = \begin{bmatrix} N_{AA} & N_{AB} & N_{AC} & N_{AD} & N_{AE} & N_{AF} \\ N_{BA} & N_{BB} & N_{BC} & N_{BD} & N_{BE} & N_{BF} \\ N_{CA} & N_{CB} & N_{CC} & N_{CD} & N_{CE} & N_{CF} \\ N_{DA} & N_{DB} & N_{DC} & N_{DD} & N_{DE} & N_{DF} \\ N_{EA} & N_{EB} & N_{EC} & N_{ED} & N_{EE} & N_{EF} \\ N_{FA} & N_{FB} & N_{FC} & N_{FD} & N_{FE} & N_{FF} \end{bmatrix}$$

(9)

$$= \frac{1}{v^2} \begin{bmatrix} 4\alpha\beta & 2\alpha(\beta+\gamma) & (\alpha+\beta)^2 & (\alpha+\beta)(\beta+\gamma) & (\alpha+\gamma)(\alpha+\beta) & 2\beta(\alpha+\gamma) \\ 2\alpha(\beta+\gamma) & 4\alpha\gamma & (\alpha+\beta)(\alpha+\gamma) & 2\gamma(\alpha+\beta) & (\alpha+\gamma)^2 & (\alpha+\gamma)(\beta+\gamma) \\ (\alpha+\beta)^2 & (\alpha+\beta)(\alpha+\gamma) & 4\alpha\beta & 2\beta(\alpha+\gamma) & 2\alpha(\beta+\gamma) & (\alpha+\beta)(\beta+\gamma) \\ (\alpha+\beta)(\beta+\gamma) & 2\gamma(\alpha+\beta) & 2\beta(\alpha+\gamma) & 4\beta\gamma & (\beta+\gamma)(\alpha+\gamma) & (\beta+\gamma)^2 \\ (\alpha+\beta)(\alpha+\gamma) & (\alpha+\gamma)^2 & 2\alpha(\beta+\gamma) & (\alpha+\gamma)(\beta+\gamma) & 4\alpha\gamma & 2\gamma(\alpha+\beta) \\ 2\beta(\alpha+\gamma) & (\alpha+\gamma)(\beta+\gamma) & (\alpha+\beta)(\beta+\gamma) & (\beta+\gamma)^2 & 2\gamma(\alpha+\beta) & 4\beta\gamma \end{bmatrix}$$

The possible number of configurations for stacks with M blocks with an aspect ratio $\alpha:\beta:\gamma$ is

$$N_{RM} = \sum (N_{R2}^{M-1}), M \geq 2 \tag{10}$$

Therefore, we can estimate the possible number of configurations when only one rectangular block with the aspect ratio of $\alpha:\beta:\gamma$ is allowed to place in each layer using the formula (9) and (10).

Finally, in this study we chose blocks with an aspect ratio of 3:1:1 as building blocks for stacks whose stability was evaluated. Specifically, for stacks consisting of 10 blocks and j.n.d of $v = 0.01$, the number of configurations can be estimated with formula (9), which is 3.72×10^{19}.