Mechanostat parameters estimated from time-lapsed *in vivo* micro-computed tomography data of mechanically driven bone adaptation are logarithmically dependent on loading frequency

Francisco C. Marques[1], Daniele Boaretti[1], Matthias Walle[1], Ariane C. Scheuren[1], Friederike A.
Schulte[1], Ralph Müller*[1]

[1]Institute for Biomechanics, ETH Zurich, Zurich, Switzerland

* Correspondence:
Ralph Müller
ram@ethz.ch

Keywords: Bone remodeling, mechanical loading, high-performance computing, frequency
dependency, micro-finite element analysis, mechanostat theory, mechanoregulation, mouse
caudal vertebra

Abstract

Mechanical loading is a key factor governing bone adaptation. Both preclinical and clinical studies
have demonstrated its effects on bone tissue, which were also notably predicted in the mechanostat
theory. Indeed, existing methods to quantify bone mechanoregulation have successfully associated
the frequency of (re)modeling events with local mechanical signals, combining time-lapsed *in vivo*
micro-computed tomography (micro-CT) imaging and micro-finite element (micro-FE) analysis.
However, a correlation between the local surface velocity of (re)modeling events and mechanical
signals has not been shown. As many degenerative bone diseases have also been linked to impaired
bone (re)modeling, this relationship could provide an advantage in detecting the effects of such
conditions and advance our understanding of the underlying mechanisms. Therefore, in this study, we
introduce a novel method to estimate (re)modeling velocity curves from time-lapsed *in vivo* mouse
caudal vertebrae data under static and cyclic mechanical loading. These curves can be fitted with
piecewise linear functions as proposed in the mechanostat theory. Accordingly, new (re)modeling
parameters can be derived from such data, including formation saturation levels, resorption velocity
modulus, and (re)modeling thresholds. Our results revealed that the norm of the gradient of strain
energy density yielded the highest accuracy in quantifying mechanoregulation data using micro-FE
analysis with homogeneous material properties, while effective strain was the best predictor for
micro-FE analysis with heterogeneous material properties. Furthermore, (re)modeling velocity curves
could be accurately described with piecewise linear and hyperbola functions (root mean square error
below 0.2 μm/day for weekly analysis), and several (re)modeling parameters determined from these
curves followed a logarithmic relationship with loading frequency. Crucially, (re)modeling velocity
curves and derived parameters could detect differences in mechanically driven bone adaptation,
which complemented previous results showing a logarithmic relationship between loading frequency
and net change in bone volume fraction over four weeks. Together, we expect this data to support the
calibration of *in silico* models of bone adaptation and the characterization of the effects of
mechanical loading and pharmaceutical treatment interventions *in vivo*.

Introduction

Bone is a dynamic organ capable of adapting to its mechanical environment (Burr et al. 2002).
Through a multiscale process, loads are transferred from the organ to the cellular level, eliciting
highly coordinated biological responses that adapt its architecture (Wolff 1986, Lanyon 1992, Turner
1998). This process of continuous bone formation and resorption comprises both bone modeling and
remodeling events, collectively referred to as (re)modeling (Huiskes et al. 2000). Indeed, several
studies have successfully shown the influence of mechanical loading in bone adaptation, especially in
trabecular bone, highlighting how mechanical cues guide the bone structure towards an optimal load
transfer (Lanyon 1992, Rubin and McLeod 1994, Huiskes et al. 2000, De Souza et al. 2005, Lambers
et al. 2011). From a mathematical modeling perspective, the mechanostat theory (Frost 1987) is a
widely known proposal for the regulatory mechanism driving tissue-level bone adaptation. Mirroring
the function of a thermostat, a system to maintain the temperature within a predefined interval
through heating and cooling, Frost argued that bone physiology also embodies processes to maintain
bone mass within an adapted window for optimal mechanical usage. Specifically, Frost postulated
the existence of key set-points or thresholds that bound this adapted window such that bone would
modulate states of disuse-remodeling, i.e., when mechanical demands are lower than normal named
"disuse", or bone modeling, i.e., when mechanical demands are higher than normal termed "mild
overload", where bone mass is predominantly added or removed, accordingly. This fine balance
would eventually normalize the mechanical demands perceived on the structure to the adapted
window. Additionally, Frost reflected on the mechanostat theory in the context of disease states, such
as osteoporosis and osteogenesis imperfecta, space orbit, or in the presence of circulating agents, like
growth factors or medications, and proposed how these would interfere with the physiological
mechanoregulation of the adapted window. Briefly, he associated some disease states with a
desensitization of response mechanisms, which would raise bone modeling thresholds, hence
reducing the adaptive response when the mechanical usage increased, while high mechanically
demanding conditions would lower such thresholds, making the system overreactive and triggering
strong anabolic reactions. Crucially, the mechanostat theory has been successfully incorporated into
in silico models of bone adaptation capable of approximating the trends observed *in vivo* in response
to various interventions (Levchuk et al. 2014) and loading frequencies (Kameo et al. 2011). Such
models can leverage time-lapsed *in vivo* micro-computed tomography (micro-CT) data, which has
also enabled tracking structural changes in response to externally applied loading in preclinical
animal studies, contributing to a comprehensive description of both morphometric changes and
mechanoregulation information of bone adaptation (Schulte et al. 2013, Birkhold et al. 2017, Albiol
et al. 2020, San Cheong et al. 2020).

Notably, with aging and in specific disease contexts, this (re)modeling process becomes unbalanced
(Rubin et al. 1992, Bassey et al. 1998), often leading to other degenerative conditions such as
osteoporosis, which precede an increased risk of fractures and culminate in considerable health and
economic costs for society (Gabriel et al. 2002, Becker et al. 2010). In agreement with Frost's
assumptions, impaired bone mechanoregulation has been suggested as a possible cause of this
problem. Therefore, advancing our ability to retrieve mechanoregulation information from time-
lapsed *in vivo* micro-CT data can help better understand the underlying mechanisms and, with that,
develop more effective treatments for these degenerative conditions.

In this regard, preclinical models, such as the mouse caudal vertebrae or tibia loading model, have
been foundational to explore bone adaptation processes by enabling controllable experimental
settings that can also mimic clinical pathological conditions (Rubin and McLeod 1994, Robling and
Turner 2002, Webster et al. 2008, Vandamme 2014, Razi et al. 2015, Roberts et al. 2019). As a

result, existing methods to investigate mechanoregulation have successfully linked (re)modeling
events with tissue strains obtained from micro-finite element (micro-FE) analysis, showing strong
associations between formation/resorption and high/low tissue strains, respectively (Schulte et al.
2013, Razi et al. 2015, Scheuren et al. 2020), which were summarized in conditional probability
curves defined over a continuous range of tissue strains. To this end, several mathematical quantities
have been proposed to describe the local mechanical signal: strain energy density (SED), effective
strain (Pistoia et al. 2002), and norm of the gradient of SED (∇SED). Deformation can be quantified
using SED or effective strain, a derived quantity from SED that accounts for differences in tissue
Young's modulus. Likewise, it is hypothesized that load-induced bone adaptation arises from
mechanical deformation perceived by osteocytes, the mechanosensitive cells in bone (direct cell
strain), and interstitial fluid flow (shear stress) in the lacunar-canalicular network (Klein-Nulend et al.
1995, Fritton and Weinbaum 2009, Weinbaum et al. 2011). Mathematically, ∇SED represents spatial
differences in tissue deformation, which are believed to induce fluid flow (Huiskes 2000). From this
perspective, it is unclear which mechanical signal shows the best association with bone (re)modeling
events.

Furthermore, conditional probability-based approaches lack quantitative information describing the
expected change in bone material for a given strain value. This dependency has been considered *in*
silico (Adachi et al. 2001, Levchuk et al. 2014, Goda et al. 2016, Louna et al. 2019) by defining the
normal surface velocity in response to the perceived mechanical signals guiding (re)modeling events.
This formulation based on surface velocity deviates from the original mechanostat theory by Frost,
which focused on changes in bone mass with the mechanical signal. Nonetheless, this shift was vital
for the development of such high-resolution *in silico* models based on micro-CT images driven by
surface advection (Adachi et al. 2001, Levchuk et al. 2014), where new bone material is added along
the gradient of the surface.

Besides, previous work has shown a dose-dependent effect of this mechanical stimulus (Mosley and
Lanyon 1998, Sugiyama et al. 2012, Scheuren et al. 2020, Walle et al. 2021), but an association of
surface velocity with mechanical signal has not been investigated at the tissue level *in vivo*. On the
one hand, it hinders more detailed comparisons of degenerative conditions that may conserve the
mechanosensation ability of bone cells, associated with mechanical signal thresholds that regulate
(re)modeling events but influence the magnitude of the response to the mechanical stimuli and the
overall bone turnover. On the other hand, from a computational modeling perspective, retrieving such
information from *in vivo* data can provide valuable calibration data for the mechanoregulation
mechanisms implemented in such models to achieve more realistic bone adaptation representations.

Therefore, the present study had two aims. First, we sought to identify which mechanical signal
showed the best association with bone (re)modeling events using conditional probability curves and
quantified with the correct classification rate (CCR) (Tourolle né Betts et al. 2020). Second, we
aimed to propose a method to retrieve mechanoregulation information from time-lapsed *in vivo*
micro-CT data that associates the surface (re)modeling velocity (RmV) with the local mechanical
signal. We express this relationship in RmV curves from which several biologically meaningful
parameters can be derived, such as formation/resorption thresholds and saturation levels. Notably, a
consistent nomenclature of these parameters is proposed and formalized in alignment with the current
understanding of the mechanostat theory. Furthermore, we applied our novel method to an *in vivo*
mouse caudal vertebrae dataset (Scheuren et al. 2020) and quantified the local dynamic response of
trabecular bone adaptation to static and cyclic loading of varying frequencies. We hypothesized that
the effect of increased loading frequencies could be measured with our new analysis and compared
through the parameters derived from these RmV curves. Finally, we investigated if there was a

relationship between these parameters and loading frequency, analogous to the logarithmic
relationship observed between loading frequency and net change in bone volume fraction over the 4-
week observation period (Scheuren et al. 2020).

Materials and Methods

Time-lapsed *in vivo* micro-CT mouse caudal vertebrae dataset

The experimental data used for this study was collected in a previous longitudinal murine *in vivo*
loading study (Scheuren et al. 2020), supporting 3R principles. Briefly, 11-week-old female
C57BL/6J mice received surgery to allow mechanical loading of the sixth caudal vertebrae (CV6) via
stainless steel pins (Fine Science Tools, Heidelberg, Germany) inserted into the fifth and seventh
vertebrae following the protocol by Webster et al. (2008). After surgery and recovery, the 15-week-
old mice were split into five groups: sham loading (0 N, 8 mice), 8 N static (8 mice), or 8 N cyclic
loading with the frequencies of 2 Hz (7 mice), 5 Hz (5 mice), or 10 Hz (8 mice). The loading regime
was performed for five minutes, three times per week, over four weeks, as previously described by
Lambers et al. (2011). Cyclic loading aimed at recreating supraphysiological loading conditions, that
is, which surpass the loading perceived with typical physiological activity of the mice (Frost 2003).
With the start of loading, the animals were scanned weekly using *in vivo* micro-CT (vivaCT 40,
Scanco Medical AG, Switzerland), with an isotropic voxel size of 10.5 μm. All mouse experiments
described in the present study were carried out in strict accordance with the recommendations and
regulations in the Welfare Ordinance (TSchV 455.1) of the Swiss Federal Food Safety and
Veterinary Office (license number 262/2016).

Automated compartmental analysis of the mouse caudal vertebrae

Consecutive time-points of the micro-CT scans were initially registered to each other using the Image
Processing Language (IPL Version 5.04c; Scanco Medical AG, Switzerland). For the identification
of the trabecular and cortical compartments in the structure, the images were filtered with a Gaussian
filter (sigma: 1.2, truncate: 1) as implemented in (Virtanen et al. 2020), binarized with a threshold of
580 mgHA/cm^3 (Scheuren et al. 2020), followed by automatic identification of the relevant
compartments following the protocol proposed by Lambers et al. (2011). This approach was
implemented in Python (version 3.9.9) and validated against the existing pipeline in IPL
(Supplementary Material 1.1.1 and Supplementary Figure 1).

Micro-finite element analysis

Micro-CT images were analyzed with micro-finite element analysis (micro-FE) to estimate the local
mechanical signal. Image voxels were converted to 8-node hexahedral elements (approximately 20
million elements in total), and bone was assumed to behave within the linear elastic regime. The
nodes at the proximal end of the micro-FE mesh were constrained in all directions, while the nodes at
the distal end were displaced by 1% of the length in the z-axis (longitudinal axis of the sample). Two
sets of simulations were performed for each sample: with homogeneous and heterogeneous material
properties based on the binary and grayscale images of the samples. The former considered a
Young's modulus value of 14.8 GPa for bone and 2 MPa for marrow (defined as non-bone voxels in
the trabecular region) and a Poisson's ratio of 0.3 (Webster et al. 2008) (see Supplementary Figure 2
for a sensitivity analysis of the effect of the Young's modulus value assigned to bone and marrow
voxels on the ability to quantify mechanoregulation information). Conversely, the latter applied a
linear relationship between bone mineral density and Young's modulus (Mulder et al. 2007) for all
voxels within the outer mask of the vertebrae (closed mask that contains all voxels within the

external surface of the vertebrae), also using a Poisson's ratio of 0.3. In this case, the minimum value
allowed for Young's modulus was also 2 MPa. Two cylindrical discs were added at the proximal and
distal ends of the vertebra model (Webster et al. 2008), mimicking the role of the intervertebral discs.
Disc settings were calibrated for micro-FE with homogeneous and heterogeneous material properties
(Supplementary Material 1.2). The simulations computed strain energy density (SED, in MPa) in the
vertebrae, from which all derived quantities were determined after linear rescaling to match the
forces applied in vivo: 8 N for loaded groups and 4 N (physiological loading) for the sham-loaded
group (0 N) (Christen et al. 2012). The pipeline was also implemented in Python, and the simulations
ran on the Euler cluster operated by Scientific IT Services at ETH Zurich, using the micro-FE solver
ParOSol (Flaig and Arbenz 2011) on Intel Xeon Gold 6150 processors (2.7-3.7 GHz).

Mechanoregulation analysis based on conditional probability curves

The mechanoregulation analysis performed in this study considered three mathematical quantities
representing the local mechanical signal: strain energy density (SED), effective strain (Pistoia et al.
2002), and the norm of the gradient of SED (∇SED). In this context, the gradient was computed
using the central difference scheme, and the norm was used as a proxy for the fluid flow in each
voxel. For SED and effective strain, the values were collected on the voxels on the bone side of the
surface interface between bone and marrow, while the values for ∇SED were collected on the
marrow side. The latter was motivated by previous results showing that fluid flow velocity
surrounding osteocytes was most influential close to the bone surfaces (Kameo et al. 2008) and,
similarly, that fluid flow affected the activity of osteoblasts and mesenchymal stem cells (Riehl et al.
2015, Riehl et al. 2017), which are also primarily found on the bone surfaces. The analysis only
considered the surface voxels and mechanical signal values inside the trabecular compartment
identified with the algorithm described in a previous section.

The conditional probabilities of a (re)modeling event (formation, quiescence, resorption) to occur at
each value of mechanical signal were calculated as described previously by Schulte et al. (2013), for
weekly intervals (e.g., weeks 1-2 considered the micro-CT images from weeks 1 and 2 and the micro-
FE from week 1) and the 4-week observation period (using the micro-CT images from weeks 0 and 4
and micro-FE data from week 0). Briefly, for each (re)modeling event, the values of the mechanical
signal at the surface voxels were collected and normalized by the 99[th] percentile of all observed
values, defining a normalized mechanical signal (%). These values were binned at 1% of the 99[th]
percentile determined, and a normalization of the total number of counts per (re)modeling event was
applied to rule out any dependence on the imbalance between these events before calculating
conditional probabilities. A conditional probability of 0.33 indicates an equal probability of any
(re)modeling event occurring.

The quantification of the amount of mechanoregulation information recovered in the analysis relied
on the CCR, using an implementation proposed by Tourolle né Betts et al. (2020). This metric
summarizes in a single number the accuracy of this ternary classification problem that categorizes
(re)modeling events (formation, quiescence, and resorption) within the range of observed local
mechanical signal values. In short, two thresholds (t_r and t_f) define three intervals, one per
(re)modeling event: resorption (mechanical signal < t_r), quiescence (t_r < mechanical signal < t_f), and
formation (t_f < mechanical signal). A 3-by-3 confusion matrix is filled with the sum of the
conditional probabilities of each event within the intervals: diagonal entries (e.g., the sum of the
conditional probability values of formation within the formation interval) represent true positive
entries, while off-diagonal are false negatives and positives. The normalized trace of the confusion
matrix yields the CCR value (optimal thresholds are found by sweeping the range of mechanical

signal values until the highest CCR is obtained). A value of 1 represents perfect accuracy, and 0.33
describes the accuracy of a random classification, given the presence of three classes. In this context,
CCR values above 0.33 indicate that the mechanical signal descriptor considered can predict
(re)modeling events with better accuracy than a random classifier.

Mechanostat (re)modeling velocity curve and parameter derivation

Here, we introduce a novel method to estimate sample-specific (re)modeling velocity curves and
their corresponding mechanostat parameters based on time-lapsed micro-CT data. The proposed
method considers the scans from two time-points: baseline and follow-up images. Note that only the
trabecular compartment is considered for this analysis. First, the follow-up image is registered to the
baseline, revealing volumes of formed, quiescent, and resorbed clusters. Next, these clusters are used
to classify surface voxels of the baseline image: formation surfaces consist of the overlap between
dilated formed clusters and the baseline surface (von Neumann neighborhood), resorption surfaces
refer to the overlap between resorbed clusters and the baseline surface, and quiescent surfaces contain
the remaining surface voxels. A distance transform (DT) algorithm (taxicab metric) is applied to the
follow-up image and the inverse of the follow-up image and masked with the formation and
resorption surfaces identified before, yielding the distance of each surface voxel to the surface of the
follow-up scan. It is assumed that the distance transform of the follow-up reveals the amount of
formed bone, while the inverted follow-up identifies the depth of resorption per surface voxel. The
values assigned to formation surfaces are obtained by gray-dilating (von Neumann neighborhood) the
distance transform values of the formed clusters into the neighboring formation surface voxels
identified. A gray-dilation operation is needed since the remodeling distance values are no longer
binary (in comparison to the identification of remodeling surfaces performed initially) and to ensure
an accurate distance calculation (e.g., if a 1-voxel thick is added on the surface, the surface voxels
underneath will contain a remodeling distance value of 2, despite a single layer of voxels being
added; with the gray dilation, the value of distance one computed by the distance transform on the
added layer can be accurately projected to the surface voxels). Further, these are linearly scaled in a
cluster-specific fashion to match the volume of the corresponding cluster (Supplementary Figure 3).
Next, the mechanical signal (ms) computed from the micro-FE analysis of the baseline image is
collected using the same (re)modeling surface masks. For this application, the micro-FE analysis
considered the homogeneous material properties described previously. Furthermore, we selected
effective strain in microstrain ($\mu\varepsilon$) as the mechanical signal descriptor, although an alternative signal
would also be suitable (e.g., SED or ∇SED).

Given that each surface voxel contains information on the amount of surface change and the
estimated mechanical signal, a 2D histogram is computed, considering the mechanical signal on the
horizontal axis and the estimated distance on the vertical axis. The mechanical signal is capped at the
99[th] percentile to eliminate very high (unphysiological) values and binned at 1% of this value. In the
vertical axis, all values are considered and binned at 1% of the maximum value observed. A weighted
average of the distance values is computed using the number of counts in the 2D histogram as
weights, providing a value for each mechanical signal bin and considering a value of 0 for the
quiescent surface voxels. The last step converts the estimated distance to a (re)modeling velocity
magnitude by multiplying and dividing by the voxel size of the images and the interval between the
time-points analyzed, respectively. For consistency with other dynamic morphometry quantities
(such as mineral apposition and resorption rates), we chose to express (re)modeling velocity in
μm/day. In this context, (re)modeling velocity aims to describe the surface movement along the
normal surface direction (Adachi et al. 2001, Levchuk et al. 2014, Goda et al. 2016, Louna et al.
2019).

Finally, mathematical functions are fitted to the curves obtained, yielding their quantitative
parametric description, namely: piecewise linear (Equation 1), as proposed in the original
mechanostat theory, and a continuous hyperbola function (Equation 2), both illustrated in Figure 1,
and which enable quantifying new (re)modeling parameters *in vivo*. The piecewise linear function is
defined by formation and resorption saturation levels (FSL and RSL, µm/day), which determine the
maximum and minimum (re)modeling velocities observed, formation and resorption thresholds (FT
and RT, µε) which determine the minimum and maximum mechanical signal value from which
formation and resorption events are observed, and formation and resorption velocity modulus (FVM
and RVM, µm/day / µε) which determine the change in (re)modeling velocity resulting from a
change in mechanical signal, defined between FSL, RSL and FT, RT, respectively. Specifically, we
highlight the proposal to define FVM and RVM as a modulus because the values are also
proportional to mechanical strain. Comparably, the hyperbola function comprises similar FSL and
RSL parameters, a (re)modeling threshold (RmT, µm/day) corresponding to the mechanical signal
value at which the RmV curve is zero and a (re)modeling velocity modulus (RmVM, µm/day x µε),
which is defined as the scale factor determining the rate of change in (re)modeling velocity resulting
from a change in mechanical signal. A summary of these parameters is also presented in Table 1.

Piecewise linear:

$$RmV\,(ms) = \begin{cases} RSL,\ ms < RT - \dfrac{RSL}{RVM} \\ -RT \times RVM + RVM \times ms,\ RT - \dfrac{RSL}{RVM} < ms < RT \\ 0,\ RT < ms < FT \\ -FT \times FVM + FVM \times ms,\ FT < ms < FT + \dfrac{FSL}{FVM} \\ FSL,\ FT + \dfrac{FSL}{FVM} < ms \end{cases}$$ (Equation 1)

Hyperbola function:

$$RmV\,(ms) = FSL - \dfrac{RmVM}{RmT + ms}$$ (Equation 2)

Note that for the hyperbola function, RSL is defined as the value of the RmV function at the
minimum mechanical signal value observed.

The quality of the fits was assessed using the root mean squared error (RMSE) between the fitted
curve and the corresponding velocity value at each mechanical signal value. The curve fitting was
done with Scipy 1.7.3 (Virtanen et al. 2020) and Curve-fit annealing (Reinhardt 2019). Similar to the
mechanoregulation analysis using conditional probabilities, the mechanostat (re)modeling velocity
curves and associated parameters were estimated for weekly intervals and the 4-week observation
period.

We implemented a balanced bootstrapping approach (Dvison et al. 1986) to characterize the
distribution of the parameters estimated from the mathematical functions fitted to the (re)modeling
velocity curves. Samples were randomly resampled 2500 times per group to generate a synthetic
group of the same size, and the corresponding (re)modeling velocity curves were determined and
fitted with the piecewise linear and hyperbola functions, yielding the estimations of the mechanostat
parameters.

Frequency dependency of estimated mechanostat parameters

The logarithmic function used previously by Scheuren et al. (2020) was considered here to evaluate
the dependency of mechanostat parameters with cyclic loading frequency. Specifically, the median
values of the parameter distributions generated with the balanced bootstrapping approach were
plotted for each loading frequency and fitted with a logarithmic regression curve (Equation 3). The
quality of the fit was assessed with the Pseudo-R^2 (Schabenberger and Pierce 2001), which enables
comparing the quality of fitted relationships for parameters with different magnitudes.

$y = y_0 + a \times \ln (f)$, f represents the loading frequency (Equation 3).

Statistical analysis

Statistical analysis was performed with Python 3.10.5, using the packages SciPy 1.7.3 (Virtanen et al.
2020) and Scikit_posthocs 0.7.0 (Terpilowski 2019), and in R (R Core Team 2022). Longitudinal
measurements of bone structural parameters were also analyzed through repeated measurements
ANOVA (Scheuren et al. 2020), implemented as a linear mixed model from the lmerTEST package
(Kuznetsova et al. 2017) after inspection of linear regression diagnostics plots. As described by
Scheuren et al. (2020), the between-subjects effect was allocated to the groups, while within-subjects
effects were allocated to time and time-group interactions. Random effects were allocated to the
animal to account for the natural differences in bone morphometry in different mice. In instances
where a significant interaction effect (group∗time) was found, a Tukey post-hoc multiple
comparisons test was performed. All other parameters were first checked for normality using the
Shapiro-Wilk test. Non-normally distributed parameters (CCR values) were presented with their
median and inter-quartile range (IQR). Estimated mechanostat parameters were presented with the
value of the fitted curve for each case and the IQR of the parameter distribution estimated with the
balanced bootstrapping approach. Subsequently, non-parametric tests (Mann-Whitney U-test;
Kruskal-Wallis followed by Conover-Iman test for multiple comparisons, corrected by Bonferroni-
Holm method) were chosen based on the result of the normality test and indicated accordingly for
each comparison in the corresponding figure or table caption. Differences between the conditional
probability curves were assessed with Mann-Whitney U-test, for normalized mechanical signal
values above 95%. Correlation between (re)modeling velocity curves from different groups was
assessed with Pearson Correlation Coefficient. Correlations of static and dynamic morphometry
parameters obtained with the IPL and Python compartmental analysis methods (Supplementary
Figure 1) and between estimated and ground truth (re)modeling clusters' volume estimation
(Supplementary Figure 3) were determined with Spearman's correlation coefficient. Significance was
set at $p < 0.05$ in all experiments; otherwise, significance levels are reported.

Results

Performance comparison of mechanical signal descriptors for mechanoregulation analysis

First, we extended previous results (Scheuren et al. 2020) by comparing SED, effective strain, and
∇SED and their ability to quantify mechanoregulation information from time-lapsed *in vivo* micro-
CT data. Figure 2A illustrates the conditional probability curves for each combination of mechanical
signal and group between weeks 0-4. This qualitative evaluation highlighted that, for all mechanical
signal descriptors, resorption was confined within a small interval of low mechanical signal values
(normalized mechanical signal < 10% for SED and ∇SED and normalized mechanical signal < 29%
for effective strain), where it was associated with a higher conditional probability of occurrence.
Furthermore, for higher magnitudes of the mechanical signal, the conditional probability curves
displayed a more stochastic pattern oscillating around the random probability of 0.33 for SED and

∇SED and stabilizing below this value for effective strain. ∇SED provided the best discriminative
ability for formation and quiescence events for all groups, supported by statistically significant
differences when comparing the difference between the conditional probability associated with
formation and quiescence between the mechanical signal descriptors (p<0.001 for ∇SED-
SED, ∇SED-effective strain, and SED-effective strain). For completeness, these comparisons
focused on normalized mechanical signal values above 95%, which comprised a median (IQR)
number of voxels per normalized mechanical signal value of 26 (21 – 32) formation voxels, 2 (1 – 3)
quiescence voxels and 11 (8 – 16) resorption voxels for SED; 57 (46 – 69) formation voxels, 5 (3 –
7) quiescence voxels and 25 (17 – 35) resorption voxels for effective strain; 27 (22 – 32) formation
voxels, 1 (0 – 2) quiescence voxels, and 15 (10 – 19) resorption voxels for ∇SED. These results were
also substantiated by the increasing separation between both curves with increased mechanical signal
magnitude (Figure 2A). The 10 Hz group achieved the widest difference between these events with
38% for ∇SED, in comparison to 33% for SED and 20% for effective strain, respectively, while the
sham-loaded group showed a maximum difference of 33%, 24% and 12% for ∇SED, SED, and
effective strain, respectively. Conversely, effective strain showed the best association with resorption
events based on the sharp increase in the conditional probability for this event within the interval of
low mechanical signal values (normalized mechanical signal < 29%), reaching its maximum
conditional probability value between 64% (2 Hz group) and 80% (static and 5 Hz groups),
contrasting with values ranging between 47% (sham-loaded group) and 52% (5 Hz group) for ∇SED.

CCR was computed from the conditional probability curves as a proxy of the amount of
mechanoregulation information retrieved, quantifying the number of (re)modeling events correctly
classified. Our analysis showed that ∇SED consistently achieved the best performance for the micro-
FE analysis with homogeneous material properties, followed by effective strain and SED (Figure
2B). Across all groups and all time-points, CCR values for ∇SED were significantly higher than
those of SED (Figure 2B). A similar result was observed for ∇SED and effective strain, although no
statistical differences were found for the groups with loading frequencies of 5 Hz and 10 Hz after
week 2 (Figure 2B). For the interval of 0-4 weeks, CCR values for ∇SED were also significantly
higher than those from SED (p<0.001) and effective strain (p<0.05) for all groups except for the 10
Hz group (Table 2). The effect of increasing loading frequencies was also noticeable in the
corresponding increase in CCR values in the same period (Table 2). Conversely, for the micro-FE
analysis with heterogeneous material properties, effective strain showed the best association with
(re)modeling events, followed by SED and ∇SED, albeit the accuracy was lower than what was
observed for micro-FE with homogeneous material properties, both in the weekly analysis (Figure
2B) and between 0-4 weeks (Table 2). Furthermore, there was a weaker increasing trend of CCR
values with increasing loading frequencies (Table 2) in comparison to the micro-FE analysis with
homogeneous material properties.

Quantification of (re)modeling velocity curves and mechanostat parameters

Next, we investigated bone mechanoregulation from time-lapsed *in vivo* micro-CT data by deriving
(re)modeling velocity curves and fitting piecewise linear and hyperbola functions to estimate the
corresponding mechanostat parameters, namely formation and resorption saturation levels (FSL and
RSL), velocity modulus (FVM and RVM) and thresholds (FT and RT) for the piecewise linear
function and FSL and RSL, (re)modeling velocity modulus (RmVM) and (re)modeling thresholds
(RmT) for the hyperbola function, respectively. We analyzed consecutive pairs of scans (Figure 3,
Supplementary Table 1) one week apart and summarized the group differences over the four-week
period of the study (Table 3).

The raw net response curves shown in Figure 3 resemble the shape of the mechanostat schematic
proposed by Frost (1987) from the disuse to the adapted and mild overload windows, providing a
qualitative validation of the output, which evaluated supraphysiological cyclic loads applied to the
mouse vertebrae. Furthermore, increasing loading frequency led to a linear translation of the derived
curves towards higher RmV values, with formation events starting from lower mechanical signal
threshold values (Figure 3). Quantitatively, the parameters derived from the fitted curves showed a
significant increase in the FSL and decreased RT and RmT values with increasing loading frequency
for both the weekly and the 0-4 weeks analysis (Table 3, Supplementary Table 1). Conversely, the
RSL values decreased significantly for increasing loading frequencies (Supplementary Table 1),
especially for weeks 3-4. Reinforcing the effects of different loading frequencies on bone adaptation,
statistically significant differences were observed between estimated parameters between groups and
time-points (Supplementary Figures 3-6).

The RmV curves also allowed characterizing time-lapsed bone adaptation for each group, where the
range of RmV values decreased weekly (Figure 3) and converged towards comparable values
between groups. Overall, this result indicated that the magnitude of the mechanical signal in weeks 3
and 4 no longer induced the same strong (re)modeling responses observed in the first two weeks.
FSL values followed a similar pattern for each group over the four weeks (Supplementary Table 1).
In the first week, the RmV curves highlighted the acute response to supraphysiological loading since
most loaded groups did not reach a plateau at their FSL value, which only occurred in subsequent
time-points. This progression was visible in the raw net response curves and the fitted mathematical
functions (Figure 3). Concurrently, RVM and FVM values (Supplementary Table 1) increased
significantly over time such that, at weeks 0-1, only regions of either high or low effective strain
could elicit the strongest response associated with the estimated formation and resorption saturation
levels, respectively. Over time, as the bone structure adapted to supraphysiological loading, the
extent of regions of either high or low effective strain decreased, also visible in the decrease in the
range of mechanical signal values (except for the sham-loaded group), and FSL were reached for
lower mechanical signal values (Figure 3, Supplementary Table 1, Supplementary Figures 3-6). The
RmV curves showed that even groups loaded with higher frequencies (5 Hz and 10 Hz) evolved from
a state of predominant formation in the first two weeks towards physiological (re)modeling
conditions, where resorption was tightly regulated within an interval of low mechanical signals and
in agreement with the conditional probability curves shown previously (Figure 2). These
observations were also corroborated by increased Pearson correlation coefficients between
(re)modeling velocity curves of 5 Hz and 10 Hz loaded groups and the sham-loaded group.
Specifically, these increased from 0.828 and 0.822 (p<0.0001) for weeks 0-1 to 0.908 and 0.883
(p<0.0001) in weeks 3-4, for the 5 Hz and 10 Hz groups, respectively, supporting comparable bone
(re)modeling responses between these groups except for their mechanosensitivity, as seen in the
differences between FT and RT values. Comparably, the RmV curves between loaded groups also
evolved towards a more uniform bone (re)modeling response based on the increase in the Pearson
correlation coefficients between the 2 Hz and 10 Hz groups and the 5 Hz and 10 Hz, from 0.872 and
0.874 to 0.899 and 0.925, respectively.

Regarding the effects of static and dynamic loads, we observed that static loading still induced an
anabolic response in the first week, characterized by a higher FSL than the sham-loaded group
(Figure 3). However, in weeks 1-2 and 2-3, the static group already matched the FSL values of the
sham-loaded group suggesting a return to a physiological (re)modeling condition, and eventually
reached a lower FSL in weeks 3-4. RT and FT were significantly higher in the static group than in the
sham-loaded group across all weeks, indicating that this loading condition still produced high strains
in the structure. Likewise, RmV curves also reflected net bone volume changes by integrating them

with respect to time and the mechanical signal. While the sham and static groups showed a negative
volume change over four weeks, cyclically loaded groups showed increasing net positive changes
with increasing loading frequency for the same interval.

Comparing the piecewise linear and hyperbola functions, the RMSE of the fitted curves indicated
that these could be determined reliably and accurately, with an average RMSE of 0.357 and 0.314
μm/day for the former and latter, respectively, over the 4-week interval (Table 3) and yielding even
lower RMSE values for the weekly analysis (Supplementary Table 1), partially given the lower
magnitude of (re)modeling velocities observed. Additionally, lower RMSE values coupled with a
wider range of (re)modeling velocities obtained with the fitting of the hyperbola function suggested
more accurate curve fits than with the piecewise linear function, which is especially crucial for the
quantification of (re)modeling thresholds in the region where the (re)modeling velocity is zero
(Figure 4A, Supplementary Table 1).

Finally, our analysis also investigated the trend followed by the mechanostat parameters derived from
the fitted (re)modeling velocity curves with loading frequency. A logarithmic function was suitable
for several parameters estimated from the piecewise linear and hyperbolic fits (Figure 4B,
Supplementary Table 2). For the piecewise linear function, FSL was accurately modeled by a
logarithmic function across all time-points (Supplementary Table 2, Figure 4B for the interval 1-2),
especially from week 1 onwards and for the analysis over the 4-week observational period (weeks 0-
4). FT values also followed the same trend for weeks 0-1 and 1-2, while RT showed the same
behavior for all weekly time-points between weeks 1 and 4 (Supplementary Table 2). Similarly, for
the hyperbola function, FSL was also accurately modeled by a logarithmic function across all weekly
time-points and between weeks 0-4 (Supplementary Table 2, Figure 4B for the interval 1-2). Besides,
RmT followed a logarithmic relationship until week 2, analogous to the FT estimated with the
piecewise linear function.

Discussion

The present study evaluated mechanoregulation in trabecular bone adaptation and quantitatively
characterized the effects of loading frequencies on bone adaptation using a novel method to estimate
(re)modeling velocity curves and their mechanostat parameters from time-lapsed *in vivo* mouse
vertebra micro-CT data. Crucially, we showed that such RmV curves could be accurately determined
and that several parameters obtained from them followed a logarithmic relationship with loading
frequency, further supporting the trend observed previously for the change in bone volume fraction
over the 4-week observation period (Scheuren et al. 2020).

First, we consolidated key factors that yield the best association between mechanical stimuli and
local bone (re)modeling using existing methods for mechanoregulation analysis. Our results revealed
that micro-FE analysis with homogeneous material properties achieved the best performance in
recovering mechanoregulation information. These homogeneous material properties were determined
from *in vivo* experiments using strain gauges attached to the cortical walls of the murine vertebrae,
such that the strains computed with micro-FE would correlate best with the *in vivo* measurements
(Webster et al. 2008). Conversely, the mathematical relationship relating bone mineral density and
Young's Modulus for the micro-FE analysis with heterogeneous material properties was derived
from nanoindentation experiments on the mandibular condyles of pigs (Mulder et al. 2007). Given
the differences in animal models and anatomical sites, it is plausible that this relationship could
influence the accuracy of the Young's Modulus conversion and, ultimately, the strain distribution
obtained from micro-FE with heterogeneous material properties. Indeed, we observed that this

relationship led to a higher average Young's Modulus value than the value used for homogeneous
material properties (Supplementary Material 1.2). In alignment with our results, previous work on the
murine tibia (Oliviero et al. 2021) has shown that micro-FE analysis with homogeneous material
properties achieved the highest correlation between experimental and estimated material properties,
while micro-FE with heterogeneous material properties of the lumbar vertebra L6 did not improve
the prediction of failure force in comparison to homogeneous material properties (Harris et al. 2020).
In any case, other applications where more significant changes in bone mineralization are expected,
such as during fracture healing of cortical bone in the mouse femur (Tourolle né Betts et al. 2020),
were more accurately modeled with heterogeneous material properties. Still, in the context of load-
induced trabecular bone adaptation as explored in this work, the micro-CT images did not show large
dynamic ranges in bone mineralization and changes in bone volume (Lambers et al. 2011, Oliviero et
al. 2021), suggesting that the use of homogeneous material properties in micro-FE analysis is
appropriate to model mechanically driven bone adaptation.

From a mathematical modeling perspective, the mechanostat theory (Frost 1987) is an established
paradigm to describe bone adaptation in response to mechanical loading that has also been
successfully applied in preclinical *in silico* models (Levchuk et al. 2014, Pereira et al. 2015, San
Cheong et al. 2020, San Cheong et al. 2020). The analysis proposed in this work enables a direct
estimation of such a relationship from time-lapsed *in vivo* micro-CT data and can be applied in a
sample-specific or group-wise fashion and for an arbitrary time interval between the input images.
We also proposed a nomenclature of mechanostat parameters, unifying the descriptions used in
previous studies. For instance, the change in bone material in response to mechanical loading was
originally named bone turnover and bone growth by Frost (1987) and later adapted to growth
velocity using a detailed mathematical framework *in silico* (Levchuk et al. 2014, Goda et al. 2016,
Louna et al. 2019). In agreement with these studies and with potential relevance for future *in silico*
models, we chose to also focus our analysis on velocity rather than change in bone mass, spatially
resolving the displacement of surface voxels between time-points. In fact, recent advances in the
context of *in silico* single-cell mechanomics (Boaretti et al. 2023) have associated positive and
negative velocities with the activity of osteoblasts and osteoclasts, respectively. Still, converting the
output to other units of interest, including a change in bone volume as originally proposed, is equally
possible. Furthermore, we opted for (re)modeling velocity as it fits the context of bone adaptation
where there can be negative and positive growth (Hadjidakis and Androulakis 2006). Conversely,
formation/resorption thresholds and saturation levels were consistent with previous approaches
(Levchuk et al. 2014, San Cheong et al. 2020). Regarding the change of RmV with mechanical
signal, it was appropriate to align this term with the naming structure of the remaining parameters
and provide an intuitive, succinct description integrating a modulus terminology:
formation/resorption/(re)modeling velocity modulus. In this way, we aimed to strengthen the
association of these terms with the mechanical signals, as modulus is inherently linked with other
mechanical terms that relate a change in a quantity with a change in mechanical strain, such as
Young's modulus, describing the relationship between stress and strain for a given material.

Focusing on the effects of mechanical loading, we observed statistically different FT, RT, and RmT
per group. These observations align with the original predictions by Frost (1987), who argued that
disease states (leading to long periods of physical inactivity) or increased mechanical demands could
increase or decrease these parameters, respectively. In our approach, at the micrometer scale, these
thresholds reflect the transition between an interval of lower strains where resorption is
predominantly observed and an interval of higher strains where formation is, on average, more
frequent and with higher magnitude. As cyclic loading groups with increasing frequency showed
more formation events, (re)modeling velocity curves were shifted towards higher velocity values,

yielding progressively lower thresholds. Conversely, sham and static groups showed a slight bone
loss in the observation period, concordant with higher thresholds. Focusing on mild-overload
examples, Rubin and Lanyon (1985) had already noted that the thresholds for bone formation would
vary depending on the loading characteristics. Although Frost (1987) could only anticipate the
existence of such thresholds, technological advances have enabled identifying possible biological
agents that realize them at the cellular level. For instance, the absence of Connexin 43 (Cx43)
membrane protein in osteocytes enhanced the responsiveness to mechanical force in mice (Bivi et al.
2013). Similarly, the activation of the Wnt/β-catenin pathway increased the sensitivity of osteoblasts
and osteocytes to mechanical loading (Gerbaix et al. 2015, Gerbaix et al. 2021). Conversely, high-
magnitude mechanical stress was observed to inhibit canonical Wnt signaling-induced osteoblastic
differentiation (Song et al. 2017). These examples highlight adjustable responses to external
mechanical loading events by cells implicated in bone (re)modeling events.

On a similar note, Skerry (2006) stated that different loading conditions, such as those induced *in*
vivo through varying loading frequencies, produce deviations from the habitual strain stimuli of the
structure. Furthermore, he argued that different anatomical sites have specific "customary strain
stimulus (CSS)" values to which the structure adapts. Our results align with these beliefs, where
different loading frequencies produced significantly different responses (Scheuren et al. 2020), and
the RmV curves evolved towards a state where (re)modeling thresholds were very close, suggesting a
return to the habitual mechanostat rule and its local CSS value. For this reason, it is understandable
that FT and RmT were no longer logarithmic dependent on loading frequency at week 4. Conversely,
RT conserved a logarithmic trend with loading frequency for all weeks, which aligns with the tight
regulation of resorption events observed in conditional probability and RmV curves. Crucially, an
accurate derivation of the mechanostat curve required calibrating the volume estimated for each
(re)modeling cluster (Supplementary Figure 3A). For instance, the volume of smaller clusters with a
high surface-to-volume ratio was expectedly overestimated by the distance transform operation. This
artifact is particularly noticeable for formation clusters where the identification of the neighboring
surface from which they emerged required a morphological dilation operation, leading to an increase
in the number of surface voxels related to this event. While previous studies (Schulte et al. 2013,
Razi et al. 2015, Scheuren et al. 2020) assessing bone mechanoregulation focused exclusively on
conditional probabilities, which only consider the frequency of mechanical signal values per
(re)modeling event, this volume correction becomes of significant importance in our proposed
method, where a new axis focusing on the (re)modeling velocity at each voxel is considered.
Ultimately, this observation sustains two key aspects. First, in agreement with previous studies
(Lanyon and Rubin 1984, Turner et al. 1995, Robling et al. 2001) that showed that dynamic but not
static loads induce an adaptive response, also our estimated RmV curves conserve this hallmark
previously observed in the dataset analyzed here (Scheuren et al. 2020). Second, an accurate volume
estimation enables the identification of critical setpoints, such as formation and resorption thresholds,
where the RmV curve approaches zero. Notably, the interval defined by these thresholds is typically
described as a lazy zone, i.e., a range of strains where bone formation and resorption balance each
other, analogous to the adapted window proposed by Frost (1987).

In this regard, and in agreement with previous findings in preclinical mouse (Sugiyama et al. 2012,
Schulte et al. 2013, Razi et al. 2015, San Cheong et al. 2020) and clinical (Christen et al. 2014) data,
our results provided no evidence of the existence of a lazy zone. This was further supported by the
lower RMSE values associated with the fitted hyperbola mathematical functions which, by definition,
cannot accommodate such an interval. Regardless, the estimated (re)modeling velocity curves agree
with previous publications (Schulte et al. 2013, Razi et al. 2015), where resorption seems to be more
tightly regulated than formation, based on the width of the interval of mechanical signal values

allocated to each (re)modeling event, consistent for all groups and loading frequencies. Furthermore,
the estimated (re)modeling rates, ranging between 0 and 3 μm/day, agree with the corresponding
mineral apposition and resorption rates previously reported for this dataset (Scheuren et al. 2020) at
around 2 μm/day, averaged across all (re)modeling clusters identified. Besides, the decreasing RSL
values for increasing loading frequencies observed (Supplementary Table 1), especially for weeks 3-
4, also align with previous work on the mouse tibia that showed an increase in the depth of resorption
cavities with loading (Birkhold et al. 2017). Given the correction in the curve estimation that ensures
accurate volumes, established dynamic morphometry indices characterizing bone formation and
resorption rates in a single value can now be expanded into a range of mechanical signals.

On a different note, previous studies (Rubin and Lanyon 1985, Turner et al. 1994) identified a strain
threshold of around 1000 με from which formation events were observed. This estimate seemingly
contradicts the conditional probabilities and (re)modeling velocity curves presented (Figure 2A),
where formation had a non-zero probability of being observed over the entire range of mechanical
signals and positive velocity values started from 200 με, respectively. However, those studies
focused primarily on the effects of the supraphysiological loading applied to the animal models,
offsetting effects resulting from physiological activity (e.g., by subtracting reference measurements
from the control leg to the loaded leg and defining relative measures). Conversely, our analysis
considered all (re)modeling events observed, that is, from both modeling and remodeling processes
occurring concurrently. In agreement with previous studies (Burr 2002) describing other non-
deterministic processes driving formation and resorption events, it is reasonable that these can occur
in locations that a purely mechanically driven system would not favor. Indeed, Lanyon et al. (1982)
had already observed bone formation in a sheep model in regions with "functional strains lower than
normal values. Furthermore, previously reported values refer to peak strains determined on the
external cortical wall of each bone, while our analysis considers local effective strain inside the
trabecular compartment, making a direct comparison of magnitudes challenging. Still, notably,
Webster et al. (2008) originally reported peak strains measured with strain gauges on the external
cortical wall of caudal vertebrae of the same mouse model considered in our work within the same
range as those obtained in previous studies.

Nonetheless, there are some limitations to consider in this study. First, although the estimation of
RmV curves can be determined in a sample-specific fashion, we observed that the analysis of group
average curves was more reliable. These naturally contained more data points which were also
filtered such that at least three samples were considered per mechanical signal value. Eventually,
these factors were vital to producing relatively smooth RmV curves and enabling consistent and
plausible piecewise linear, and hyperbola fits. In any case, as previous work has focused on group
average results both *in vivo* (Schulte et al. 2013, Razi et al. 2015, San Cheong et al. 2020) and *in*
silico (Levchuk et al. 2014, San Cheong et al. 2020, Boaretti et al. 2023), our analysis still aligns with
such standard practices. Second, contrasting with conditional probability-based approaches,
(re)modeling events are no longer characterized separately since our approach yields a single curve
representing the average RmV describing the net effect of (re)modeling events for a given
mechanical signal. Effectively, this feature prevents our method from capturing more subtle trends
observed in the conditional probability curves (e.g., the slight increase in the conditional probability
of resorption for higher mechanical signal values). Nonetheless, our goal was to derive a relationship
in alignment with the mechanostat theory which, by definition, also does not describe (re)modeling
events independently. Although conditional probability curves showed that these events could occur
across the entire range of mechanical signals and highlight the interrelated effect of mechanical and
biological cues governing targeted and non-targeted bone (re)modeling (Burr 2002, Parfitt 2002,
Schulte et al. 2013), we consider our approach complementary to this probability-based method. Still,

as different mechanical signal quantities performed differently for formation and resorption events
(Figure 2A), future approaches can attempt to combine both methods and derive separate RmV
curves for formation and resorption using the mechanical signal that best associates with each event.

Likewise, our approach was not designed to investigate the spatial and temporal links between
surface (re)modeling events (i.e., analysis of the spatial/temporal distribution of formation, quiescent
and resorption regions), analogous to previously proposed methods (Birkhold et al. 2015). Indeed, in
the mouse bone and with the resolution of the micro-CT used here, one cannot distinguish between
pure remodeling and modeling events, which we collectively refer to as (re)modeling (Huiskes et al.
2000, Schulte et al. 2013). Therefore, it is expected that physiological (re)modeling also took place
during the 4-week observation period. One can argue that such events are continuously happening
and would not be as mechanically driven, yielding flatter (re)modeling velocity curves. Accordingly,
our observations of the sham group, where (re)modeling events should be most noticeable, feature
lower FSL, FVM, and RmVM values while conserving a tighter regulation of resorption events. With
potential applications for clinical data focusing on disease states, this observation would be
particularly impactful as current *in vivo* clinical imaging modalities are still affected by noise and
motion artifacts, such that reliably identifying (re)modeling events is challenging (Christen et al.
2018). Eventually, longer intervals between scans would be required to produce time-lapsed data
with sufficient changes that could yield RmV curves depicting a more explicit relationship with
mechanical signals computed from micro-FE.

It should be noted that the current micro-CT image resolution also challenges an accurate
identification of sub-voxel phenomena. Indeed, such information would help to elucidate the
assumption considered in our (re)modeling velocity estimation that the (re)modeling distance
measured for each voxel surrounding a (re)modeling cluster can be linearly scaled to match the
calculated volume of the cluster. For the same reason, this factor also implies that the proposed
method cannot recover single-cell behavior. Nonetheless, loading frequency was positively correlated
with the number of osteocytes recruited in response to an increase in applied strain (Lewis et al.
2017), with a particular focus on bone formation in a murine metatarsal model. Additionally, in a rat
tibia model, increasing loading frequency was associated with a decrease in the estimated peak
microstrain triggering periosteal bone formation and an increase in the rate of bone formation per
microstrain (Hsieh and Turner 2001). Combined, these results would emerge as an increase in FVM
and a decrease in FT values with increasing frequency, which is what our RmV curves show until
week 3. Furthermore, the decreased anabolic response observed in the RmV curves for high strains
may also be linked to a decrease in mechanosensitivity resulting from increased cell stiffness, as
previously reported for such high strain values (Nawaz et al. 2012). Therefore, the trends estimated
with the mechanostat (re)modeling velocity curves could be leveraged by *in silico* simulations that
also rely on time-lapsed *in vivo* micro-CT data as input, such as novel agent-based models that
simulate individual cell populations in 3D (Tourolle 2019, Boaretti et al. 2023) and, with that,
improve the accuracy of their predictions with respect to *in vivo* data. For this reason, we chose to
express RmV curves using effective strain, as this signal has already been implemented successfully
in such *in silico* models. Still, our approach is compatible with any voxel-based mechanical signal
descriptor, including ∇SED which showed the best association with (re)modeling events (Figure 2)
or other signals implemented in *in silico* models of trabecular bone remodeling. Furthermore, our
results demonstrating that several parameters estimated from the mechanostat also follow a
logarithmic relationship with loading frequency can help to calibrate such models and investigate
loading frequency-dependent responses *in silico*. With the advent of more powerful imaging
methods, cell populations may soon be efficiently measured from *in vivo* samples and compared with
the results of these *in silico* models. Additionally, our approach can support preclinical *in vivo* studies

focusing on bone mechanoregulation. Previous work exploring the effects of aging and degenerative
conditions described changes in conditional probabilities between young and aged groups (Razi et al.
2015), while studies focusing on pharmaceutical interventions characterized changes in global
morphometry indices and micro-FE properties (Roberts et al. 2020), and also reported synergistic
effects between specific treatments and mechanical loading in a mouse model of osteoporosis
(Levchuk et al. 2014). Therefore, as Frost (1987) had already anticipated the effects of medications
on the thresholds bounding the adapted window, our approach provides a quantitative framework to
support this analysis. Interventions leading to changes in (re)modeling thresholds (FT, RT, RmT)
could suggest changes in the sensitivity to loading while varying (re)modeling modulus (FVM,
RVM, RmVM) would relate to changes in the magnitude of the response. Ultimately, it could be
possible to identify which intervention would help to counter such disruptions in bone
mechanoregulation that follow degenerative conditions.

In conclusion, we have presented a novel method to estimate (re)modeling velocity curves and their
parameters from time-lapsed *in vivo* micro-CT data. Furthermore, we applied this approach to
evaluate the effects of different loading frequencies on time-lapsed changes in bone
microarchitecture by quantifying critical parameters describing bone mechanoregulation, such as
formation saturation levels and (re)modeling thresholds. Crucially, we reinforced previous results
that revealed a logarithmic relationship of bone volume change with loading frequency by showing
that mechanostat parameters estimated from RmV curves, such as (re)modeling thresholds and
formation and resorption saturation levels, are also logarithmically dependent on loading frequency.
Altogether, we expect these results to support future *in silico* and *in vivo* studies comparing the
effects of mechanical loading and pharmaceutical treatment interventions on bone mechanoregulation
and bone adaptation and, ultimately, identify more effective treatment plans that can be translated
into clinical settings.

Conflict of Interest

691 The authors declare that the research was conducted in the absence of any commercial or financial
692 relationships that could be construed as a potential conflict of interest.

Author Contributions

694 **Study design**: FM, AS, RM. **Study conduct**: FM, DB, MW. **Data collection**: FM. **Data analysis**:
695 FM. **Data interpretation**: FM, DB, FS, RM. **Drafting manuscript**: FM. **Revising manuscript**
696 **content**: FM, DB, MW, AS, FS, RM. **Approving final version of manuscript**: FM, DB, MW, AS,
697 FS, RM. RM takes responsibility for the integrity of the data analysis.

Funding

699 This manuscript was based upon work supported by the European Research Council (ERC Advanced
700 MechAGE ERC-2016-ADG-741883).

Acknowledgments

This manuscript was released as a preprint at bioRxiv (C. Marques et al. 2023).

1   Data Availability Statement

Data and code will be made available upon reasonable request.

References

Adachi, T., K. Tsubota, Y. Tomita and S. J. Hollister (2001). "Trabecular surface remodeling
simulation for cancellous bone using microstructural voxel finite element models." Journal of
Biomechanical Engineering-Transactions of the Asme 123(5): 403-409.

Albiol, L., A. Buttner, D. Pflanz, N. Mikolajewicz, A. I. Birkhold, I. Kramer, M. Kneissel, G. N.
Duda, S. Checa and B. M. Willie (2020). "Effects of Long-Term Sclerostin Deficiency on Trabecular
Bone Mass and Adaption to Limb Loading Differ in Male and Female Mice." Calcif Tissue Int
106(4): 415-430.

Bassey, E. J., M. C. Rothwell, J. J. Littlewood and D. W. Pye (1998). "Pre- and postmenopausal
women have different bone mineral density responses to the same high-impact exercise." J Bone
Miner Res 13(12): 1805-1813.

Becker, D. J., M. L. Kilgore and M. A. Morrisey (2010). "The societal burden of osteoporosis." Curr
Rheumatol Rep 12(3): 186-191.

Birkhold, A. I., H. Razi, G. N. Duda, S. Checa and B. M. Willie (2017). "Tomography-Based
Quantification of Regional Differences in Cortical Bone Surface Remodeling and Mechano-
Response." Calcif Tissue Int 100(3): 255-270.

Birkhold, A. I., H. Razi, R. Weinkamer, G. N. Duda, S. Checa and B. M. Willie (2015). "Monitoring
in vivo (re)modeling: a computational approach using 4D microCT data to quantify bone surface
movements." Bone 75: 210-221.

Bivi, N., R. Pacheco-Costa, L. R. Brun, T. R. Murphy, N. R. Farlow, A. G. Robling, T. Bellido and
L. I. Plotkin (2013). "Absence of Cx43 selectively from osteocytes enhances responsiveness to
mechanical force in mice." J Orthop Res 31(7): 1075-1081.

Boaretti, D., F. C. Marques, C. Ledoux, A. Singh, J. J. Kendall, E. Wehrle, G. A. Kuhn, Y. D.
Bansod, F. A. Schulte and R. Müller (2023). "Trabecular bone remodeling in the ageing mouse: a
micro-multiphysics agent-based in silico model using single-cell mechanomics." Frontiers in
Bioengineering and Biotechnology 11 - 2023.

Burr, D. B. (2002). "Targeted and nontargeted remodeling." Bone 30(1): 2-4.

Burr, D. B., A. G. Robling and C. H. Turner (2002). "Effects of biomechanical stress on bones in
animals." Bone 30(5): 781-786.

C. Marques, F., D. Boaretti, M. Walle, A. C. Scheuren, F. A. Schulte and R. Müller (2023).
"Mechanostat parameters estimated from time-lapsed *in vivo* micro-computed tomography data of
mechanically driven bone adaptation are logarithmically dependent on loading frequency." bioRxiv:
2023.2001.2007.523082.

Christen, P., S. Boutroy, R. Ellouz, R. Chapurlat and B. van Rietbergen (2018). "Least-detectable and
age-related local in vivo bone remodelling assessed by time-lapse HR-pQCT." Plos One 13(1):
e0191369.

Christen, P., K. Ito, R. Ellouz, S. Boutroy, E. Sornay-Rendu, R. D. Chapurlat and B. van Rietbergen
(2014). "Bone remodelling in humans is load-driven but not lazy." Nature Communications 5(1):
4855.

Christen, P., B. van Rietbergen, F. M. Lambers, R. Muller and K. Ito (2012). "Bone morphology
allows estimation of loading history in a murine model of bone adaptation." Biomech Model
Mechanobiol 11(3-4): 483-492.

De Souza, R. L., M. Matsuura, F. Eckstein, S. C. Rawlinson, L. E. Lanyon and A. A. Pitsillides
(2005). "Non-invasive axial loading of mouse tibiae increases cortical bone formation and modifies
trabecular organization: a new model to study cortical and cancellous compartments in a single
loaded element." Bone 37(6): 810-818.

Dvison, A. C., D. V. Hinkley and E. Schechtman (1986). "Efficient bootstrap simulation."
Biometrika 73(3): 555-566.

Flaig, C. and P. Arbenz (2011). "A scalable memory efficient multigrid solver for micro-finite
element analyses based on CT images." Parallel Computing 37(12): 846-854.

Fritton, S. P. and S. Weinbaum (2009). "Fluid and Solute Transport in Bone: Flow-Induced
Mechanotransduction." Annu Rev Fluid Mech 41: 347-374.

Frost, H. M. (1987). "The mechanostat: a proposed pathogenic mechanism of osteoporoses and the
bone mass effects of mechanical and nonmechanical agents." Bone and mineral 2(2): 73-85.

Frost, H. M. (2003). "Bone's mechanostat: a 2003 update." Anat Rec A Discov Mol Cell Evol Biol
275(2): 1081-1101.

Gabriel, S. E., A. N. Tosteson, C. L. Leibson, C. S. Crowson, G. R. Pond, C. S. Hammond and L. J.
Melton, 3rd (2002). "Direct medical costs attributable to osteoporotic fractures." Osteoporos Int
13(4): 323-330.

Gerbaix, M., P. Ammann and S. Ferrari (2021). "Mechanically Driven Counter-Regulation of
Cortical Bone Formation in Response to Sclerostin-Neutralizing Antibodies." J Bone Miner Res
36(2): 385-399.

Gerbaix, M., L. Vico, S. L. Ferrari and N. Bonnet (2015). "Periostin expression contributes to cortical
bone loss during unloading." Bone 71: 94-100.

Goda, I., J.-F. Ganghoffer and G. Maurice (2016). "Combined bone internal and external remodeling
based on Eshelby stress." International Journal of Solids and Structures 94-95: 138-157.

Hadjidakis, D. J. and Androulakis, II (2006). "Bone remodeling." Ann N Y Acad Sci 1092: 385-396.

Harris, D., K. Garrett, S. Uppuganti, A. Creecy and J. S. Nyman (2020). "The BALB/c mouse as a
preclinical model of the age-related deterioration in the lumbar vertebra." Bone 137.

Hsieh, Y. F. and C. H. Turner (2001). "Effects of loading frequency on mechanically induced bone
formation." Journal of Bone and Mineral Research 16(5): 918-924.

Huiskes, R. (2000). "If bone is the answer, then what is the question?" Journal of Anatomy 197: 145-
156.

Huiskes, R., R. Ruimerman, G. H. van Lenthe and J. D. Janssen (2000). "Effects of mechanical
forces on maintenance and adaptation of form in trabecular bone." Nature 405(6787): 704-706.

Kameo, Y., T. Adachi and M. Hojo (2008). "Transient response of fluid pressure in a poroelastic
material under uniaxial cyclic loading." Journal of the Mechanics and Physics of Solids 56(5): 1794-
1805.

Kameo, Y., T. Adachi and M. Hojo (2011). "Effects of loading frequency on the functional
adaptation of trabeculae predicted by bone remodeling simulation." J Mech Behav Biomed Mater
4(6): 900-908.

Klein-Nulend, J., A. van der Plas, C. M. Semeins, N. E. Ajubi, J. A. Frangos, P. J. Nijweide and E.
H. Burger (1995). "Sensitivity of osteocytes to biomechanical stress in vitro." FASEB J 9(5): 441-
445.

Kuznetsova, A., P. B. Brockhoff and R. H. B. Christensen (2017). "lmerTest Package: Tests in Linear
Mixed Effects Models." Journal of Statistical Software 82(13): 1-26.

Lambers, F. M., F. A. Schulte, G. Kuhn, D. J. Webster and R. Muller (2011). "Mouse tail vertebrae
adapt to cyclic mechanical loading by increasing bone formation rate and decreasing bone resorption
rate as shown by time-lapsed in vivo imaging of dynamic bone morphometry." Bone 49(6): 1340-
1350.

Lanyon, L. E. (1992). "Control of bone architecture by functional load bearing." J Bone Miner Res 7
Suppl 2: S369-375.

Lanyon, L. E., A. E. Goodship, C. J. Pye and J. H. Macfie (1982). "Mechanically Adaptive Bone
Remodeling." Journal of Biomechanics 15(3): 141-154.

Lanyon, L. E. and C. T. Rubin (1984). "Static Vs Dynamic Loads as an Influence on Bone
Remodeling." Journal of Biomechanics 17(12): 897-905.

Levchuk, A., A. Zwahlen, C. Weigt, F. M. Lambers, S. D. Badilatti, F. A. Schulte, G. Kuhn and R.
Muller (2014). "The Clinical Biomechanics Award 2012 - presented by the European Society of
Biomechanics: large scale simulations of trabecular bone adaptation to loading and treatment." Clin
Biomech (Bristol, Avon) 29(4): 355-362.

Lewis, K. J., D. Frikha-Benayed, J. Louie, S. Stephen, D. C. Spray, M. M. Thi, Z. Seref-Ferlengez,
R. J. Majeska, S. Weinbaum and M. B. Schaffler (2017). "Osteocyte calcium signals encode strain
magnitude and loading frequency in vivo." Proceedings of the National Academy of Sciences of the
United States of America 114(44): 11775-11780.

Louna, Z., I. Goda and J.-F. Ganghoffer (2019). "Homogenized strain gradient remodeling model for
trabecular bone microstructures." Continuum Mechanics and Thermodynamics 31(5): 1339-1367.

Mosley, J. R. and L. E. Lanyon (1998). "Strain rate as a controlling influence on adaptive modeling
in response to dynamic loading of the ulna in growing male rats." Bone 23(4): 313-318.

Mulder, L., J. H. Koolstra, J. M. den Toonder and T. M. van Eijden (2007). "Intratrabecular
distribution of tissue stiffness and mineralization in developing trabecular bone." Bone 41(2): 256-
265.

Nawaz, S., P. Sanchez, K. Bodensiek, S. Li, M. Simons and I. A. T. Schaap (2012). "Cell Visco-
Elasticity Measured with AFM and Optical Trapping at Sub-Micrometer Deformations." Plos One
7(9).

Oliviero, S., M. Roberts, R. Owen, G. C. Reilly, I. Bellantuono and E. Dall'Ara (2021). "Non-
invasive prediction of the mouse tibia mechanical properties from microCT images: comparison
between different finite element models." Biomech Model Mechanobiol 20(3): 941-955.

Parfitt, A. M. (2002). "Targeted and nontargeted bone remodeling: relationship to basic multicellular
unit origination and progression." Bone 30(1): 5-7.

Pereira, A. F., B. Javaheri, A. A. Pitsillides and S. J. Shefelbine (2015). "Predicting cortical bone
adaptation to axial loading in the mouse tibia." Journal of the Royal Society Interface 12(110).

Pistoia, W., B. van Rietbergen, E. M. Lochmuller, C. A. Lill, F. Eckstein and P. Ruegsegger (2002).
"Estimation of distal radius failure load with micro-finite element analysis models based on three-
dimensional peripheral quantitative computed tomography images." Bone 30(6): 842-848.

R Core Team (2022). R: A Language and Environment for Statistical Computing, R Foundation for
Statistical Computing.

Razi, H., A. I. Birkhold, R. Weinkamer, G. N. Duda, B. M. Willie and S. Checa (2015). "Aging
Leads to a Dysregulation in Mechanically Driven Bone Formation and Resorption." J Bone Miner
Res 30(10): 1864-1873.

Reinhardt, S. (2019). "Curve fit annealing." Retrieved 11/08/2022, from
https://github.com/amba/curve_fit.annealing.

Riehl, B. D., J. S. Lee, L. Ha, I. K. Kwon and J. Y. Lim (2017). "Flowtaxis of osteoblast migration
under fluid shear and the effect of RhoA kinase silencing." Plos One 12(2).

Riehl, B. D., J. S. Lee, L. Ha and J. Y. Lim (2015). "Fluid-flow-induced mesenchymal stem cell
migration: role of focal adhesion kinase and RhoA kinase sensors." Journal of the Royal Society
Interface 12(104).

Roberts, B. C., M. Giorgi, S. Oliviero, N. Wang, M. Boudiffa and E. Dall'Ara (2019). "The
longitudinal effects of ovariectomy on the morphometric, densitometric and mechanical properties in
the murine tibia: A comparison between two mouse strains." Bone 127: 260-270.

Robling, A. G., K. M. Duijvelaar, J. V. Geevers, N. Ohashi and C. H. Turner (2001). "Modulation of
appositional and longitudinal bone growth in the rat ulna by applied static and dynamic force." Bone
29(2): 105-113.

Robling, A. G. and C. H. Turner (2002). "Mechanotransduction in bone: genetic effects on
mechanosensitivity in mice." Bone 31(5): 562-569.

Rubin, C. T., S. D. Bain and K. J. McLeod (1992). "Suppression of the osteogenic response in the
aging skeleton." Calcif Tissue Int 50(4): 306-313.

Rubin, C. T. and L. E. Lanyon (1985). "Regulation of Bone Mass by Mechanical Strain Magnitude."
Calcified Tissue International 37(4): 411-417.

Rubin, C. T. and K. J. McLeod (1994). "Promotion of bony ingrowth by frequency-specific, low-
amplitude mechanical strain." Clin Orthop Relat Res(298): 165-174.

San Cheong, V., A. C. Marin, D. Lacroix and E. Dall'Ara (2020). "A novel algorithm to predict bone
changes in the mouse tibia properties under physiological conditions." Biomechanics and Modeling
in Mechanobiology 19(3): 985-1001.

San Cheong, V., B. C. Roberts, V. Kadirkamanathan and E. Dall'Ara (2020). "Bone remodelling in
the mouse tibia is spatio-temporally modulated by oestrogen deficiency and external mechanical
loading: A combined in vivo/in silico study." Acta Biomaterialia 116: 302-317.

Schabenberger, O. and F. J. Pierce (2001). Contemporary Statistical Models for the Plant and Soil
Sciences. Boca Raton, CRC Press.

Scheuren, A. C., P. Vallaster, G. A. Kuhn, G. R. Paul, A. Malhotra, Y. Kameo and R. Muller (2020).
"Mechano-Regulation of Trabecular Bone Adaptation Is Controlled by the Local in vivo

Environment and Logarithmically Dependent on Loading Frequency." Frontiers in Bioengineering
and Biotechnology 8.

Schulte, F. A., D. Ruffoni, F. M. Lambers, D. Christen, D. J. Webster, G. Kuhn and R. Muller
(2013). "Local Mechanical Stimuli Regulate Bone Formation and Resorption in Mice at the Tissue
Level." Plos One 8(4).

Skerry, T. M. (2006). "One mechanostat or many? Modifications of the site-specific response of bone
to mechanical loading by nature and nurture." J Musculoskelet Neuronal Interact 6(2): 122-127.

Song, F., D. Jiang, T. Wang, Y. Wang, Y. Lou, Y. Zhang, H. Ma and Y. Kang (2017). "Mechanical
Stress Regulates Osteogenesis and Adipogenesis of Rat Mesenchymal Stem Cells through
PI3K/Akt/GSK-3beta/beta-Catenin Signaling Pathway." Biomed Res Int 2017: 6027402.

Sugiyama, T., L. B. Meakin, W. J. Browne, G. L. Galea, J. S. Price and L. E. Lanyon (2012). "Bones'
adaptive response to mechanical loading is essentially linear between the low strains associated with
disuse and the high strains associated with the lamellar/woven bone transition." Journal of Bone and
Mineral Research 27(8): 1784-1793.

Terpilowski, M. (2019). "scikit-posthocs: Pairwise multiple comparison tests in Python." Journal of
Open Source Software 4(36).

Tourolle, D. (2019). A micro-scale multiphysics framework for fracture healing and bone
remodelling. D-HEST, ETH Zurich. Doctoral Degree.

Tourolle né Betts, D. C., E. Wehrle, G. R. Paul, G. A. Kuhn, P. Christen, S. Hofmann and R. Müller
(2020). "The association between mineralised tissue formation and the mechanical local in vivo
environment: Time-lapsed quantification of a mouse defect healing model." Sci Rep 10(1100).

Turner, C. H. (1998). "Three rules for bone adaptation to mechanical stimuli." Bone 23(5): 399-407.

Turner, C. H., M. R. Forwood, J. Y. Rho and T. Yoshikawa (1994). "Mechanical Loading Thresholds
for Lamellar and Woven Bone-Formation." Journal of Bone and Mineral Research 9(1): 87-97.

Turner, C. H., I. Owan and Y. Takano (1995). "Mechanotransduction in Bone - Role of Strain-Rate."
American Journal of Physiology-Endocrinology and Metabolism 269(3): E438-E442.

Vandamme, T. (2014). "Use of rodents as models of human diseases." Journal of Pharmacy And
Bioallied Sciences 6(1): 2-9.

Virtanen, P., R. Gommers, T. E. Oliphant, M. Haberland, T. Reddy, D. Cournapeau, E. Burovski, P.
Peterson, W. Weckesser, J. Bright, S. J. van der Walt, M. Brett, J. Wilson, K. J. Millman, N.
Mayorov, A. R. J. Nelson, E. Jones, R. Kern, E. Larson, C. J. Carey, I. Polat, Y. Feng, E. W. Moore,
J. VanderPlas, D. Laxalde, J. Perktold, R. Cimrman, I. Henriksen, E. A. Quintero, C. R. Harris, A. M.
Archibald, A. H. Ribeiro, F. Pedregosa, P. van Mulbregt and C. SciPy (2020). "SciPy 1.0:
fundamental algorithms for scientific computing in Python." Nat Methods 17(3): 261-272.

Walle, M., F. C. Marques, N. Ohs, M. Blauth, R. Muller and C. J. Collins (2021). "Bone
Mechanoregulation Allows Subject-Specific Load Estimation Based on Time-Lapsed Micro-CT and
HR-pQCT in Vivo." Frontiers in Bioengineering and Biotechnology 9.

Webster, D. J., P. L. Morley, G. H. van Lenthe and R. Muller (2008). "A novel in vivo mouse model
for mechanically stimulated bone adaptation--a combined experimental and computational validation
study." Comput Methods Biomech Biomed Engin 11(5): 435-441.

Weinbaum, S., Y. Duan, M. M. Thi and L. You (2011). "An Integrative Review of
Mechanotransduction in Endothelial, Epithelial (Renal) and Dendritic Cells (Osteocytes)." Cell Mol
Bioeng 4(4): 510-537.

Wolff, J. (1986). The law of bone remodeling. Maqet P., Furlong R., (Translation), Berlin, Germany:
Springer Verlag.

Figure captions

Figure 1

Overview of the computational pipeline for high-throughput analysis of time-lapsed *in vivo* micro-CT
mouse caudal vertebra samples. A) Qualitative visualization of a representative sample highlighting
the original bone structure, the identification of regional compartments (trabecular compartment in
blue and cortical compartment in orange), the local mechanical signal computed as strain energy
density (SED) from micro-FE analysis, the (re)modeling map obtained from time-lapsed micro-CT
images and the (re)modeling distance associated with surface voxels (Scale bar: 500 µm). B)
Diagram of the workflow included in the computational pipeline, from pre-processing micro-CT
images to post-processing steps, featuring mechanoregulation analysis. C) Illustration of the
workflow for mechanoregulation analysis and estimation of mechanostat parameters: the baseline,
follow-up, and inverted follow-up images are considered; for each surface voxel, (re)modeling events
are identified by overlapping consecutive time-points, the mechanical signal in the structure is
computed with micro-FE and the (re)modeling distance is determined with a distance transform
operation (see Materials and Methods). The data is used to compute conditional probability curves
for each (re)modeling event (dashed line represents a random probability of occurrence) and a
(re)modeling velocity curve (dashed line represents zero (re)modeling velocity), which can be fitted
with a piecewise linear function or a continuous hyperbola function to retrieve biologically
meaningful parameters. Parameter legend (see Materials and Methods for an extended description):
A- Resorption saturation level (RSL), B- Resorption velocity modulus (RVM), C- Resorption
threshold (RT), D- Formation threshold (FT), E- Formation velocity modulus (FVM), F- Formation
saturation level (FSL), G- (Re)modeling threshold (RmT), H- (Re)modeling velocity modulus
(RmVM).

Figure 2

Quantification of mechanoregulation information from time-lapsed *in vivo* micro-CT image data. A) Conditional probability curves connecting the mechanical environment with (re)modeling events, computed for all groups and mechanical signal descriptors considered (SED, effective strain, and ∇SED), using homogeneous material properties. The plots show the mean probability line per group after applying a LOWESS operation for the interval 0-4 weeks and its corresponding 95% confidence interval. The dashed line at 0.33 identifies the probability of a random event for a ternary classification case. B) Comparison of correct classification rate (CCR) values obtained by SED, effective strain, and ∇SED as local mechanical signal descriptors computed from micro-FE with homogeneous or heterogeneous material properties. Higher CCR values indicate higher sensitivity to retrieve mechanoregulation information. Similar to A), the analysis also considers the interval of 0-4 weeks. Statistical significance was determined by the Conover-Iman test, corrected for multiple

comparisons by the Holm-Bonferroni method. Statistical significance legend: *p < 0.05, **p < 0.01,
***p < 0.001, ****p < 0.0001.

Figure 3

Estimation of the mechanostat (re)modeling velocity (RmV) curve from time-lapsed *in vivo* micro-
CT imaging data, illustrated with the average raw net response (top row) per group, the fitted
piecewise linear functions (middle row), as described in the mechanostat theory and continuous
hyperbola functions (bottom row). Data points are filtered such that at least three mice are averaged
for each mechanical signal value. Mechanical signal values obtained from micro-FE analysis using
homogeneous material properties.

Figure 4

A) Root mean squared errors (RMSE) associated with the piecewise linear (top row) and hyperbola (bottom row) fitted functions for the analysis of weeks 1-2 are shown, highlighting that the hyperbola function consistently achieved lower errors than the piecewise linear function. B) Logarithmic relationships fitted to the bootstrapped distributions of mechanostat parameters estimated from the piecewise linear (top row) and hyperbola (bottom row) functions fitted to the (re)modeling velocity curves for the weeks 1-2. Formation saturation levels (FSL), formation, and (re)modeling thresholds (FT and RmT) were among the parameters that followed a logarithmic trend throughout the four weeks of the study. C) Qualitative visualization linking (re)modeling distance measurements with the mechanical environments *in vivo* as effective strain.

Tables

Table 1

Mechanostat parameters derived from the piecewise linear and hyperbola functions fitted to the (re)modeling velocity curves.

Function	Parameter	Abbreviation	Unit	Description
Piecewise linear	Resorption Saturation Level	RSL	µm/day	Minimum (re)modeling velocity observed.
	Resorption Velocity Modulus	RVM	(µm/day) / mech. signal units	Change in (re)modeling velocity resulting from a change in mechanical signal, defined between RSL and RT.

	Resorption Threshold	RT	Mech. signal units	Maximum mechanical signal value from which resorption events are observed.
	Formation Threshold	FT	Mech. signal units	Minimum mechanical signal value from which formation events are observed.
	Formation Modulus	FVM	(µm/day) / mech. signal units	Change in (re)modeling velocity resulting from a change in mechanical signal, defined between FSL and FT.
	Formation Saturation Level	FSL	µm/day	Maximum (re)modeling velocity observed.
Hyperbola	Resorption Saturation Level	RSL	µm/day	Minimum resorption velocity observed.
	(Re)modeling Threshold	RmT	Mech. signal units	Mechanical signal value at which the curve intercepts the zero-(re)modeling velocity.
	(Re)modeling Velocity Modulus	RmVM	(µm/day) x mech. signal units	Scale factor determining the rate of change in (re)modeling velocity resulting from a change in mechanical signal.
	Formation Saturation Level	FSL	µm/day	Maximum formation velocity observed.
(Re)modeling velocity (vertical axis)		RV	µm/day	Average velocity of the surface per day, leading to formation and resorption (re)modeling events.
Mechanical signal (horizontal axis)		ms	Mech. signal units	Quantity selected for mechanical signal such as Strain Energy Density (SED), effective strain or ∇SED.

Table 2

Correct classification rate (CCR) for all groups, mechanical signal descriptors, and material
properties analyzed for weeks 0-4. Data presented as "median (IQR)". Statistical significance legend:
a – "SED – Effective strain", b – "Effective strain – ∇SED", c – "SED – ∇SED"; ns: not significant,
*p < 0.05, **p < 0.01, ***p < 0.001, ****p < 0.0001. Statistical significance was determined with
Conover's test corrected for multiple comparisons with a step-down method using Bonferroni-Holm
adjustments.

Material properties	Group	Mechanical signal			p-value
		SED	Effective strain	∇SED	

Homogeneous	Sham	0.378 (0.374 - 0.391)	0.400 (0.392 - 0.404)	0.421 (0.413 - 0.440)	*a, **b, ****c
	Static	0.389 (0.375 - 0.395)	0.405 (0.403 - 0.410)	0.434 (0.427 - 0.448)	*b, ***c
	2 Hz	0.402 (0.387 - 0.404)	0.411 (0.407 - 0.417)	0.450 (0.430 - 0.451)	*b, ***c
	5 Hz	0.396 (0.387 - 0.397)	0.404 (0.399 - 0.422)	0.446 (0.439 - 0.454)	*a, *b, ***c
	10 Hz	0.417 (0.382 - 0.443)	0.418 (0.395 - 0.428)	0.461 (0.431 - 0.489)	ns
Heterogeneous	Sham	0.381 (0.373 - 0.387)	0.423 (0.410 - 0.432)	0.371 (0.366 - 0.374)	*b, **c
	Static	0.386 (0.379 - 0.392)	0.423 (0.416 - 0.434)	0.377 (0.364 - 0.381)	*b, **c
	2 Hz	0.387 (0.387 - 0.397)	0.430 (0.399 - 0.434)	0.382 (0.375 - 0.391)	*b, **c
	5 Hz	0.394 (0.387 - 0.398)	0.420 (0.412 - 0.431)	0.380 (0.372 - 0.391)	ns
	10 Hz	0.397 (0.387 - 0.435)	0.427 (0.414 - 0.447)	0.395 (0.365 - 0.408)	ns

Table 3

Parameters of the mathematical functions fitted to the estimated mechanostat group average
(re)modeling velocity curves for the interval weeks 0-4. Data presented as "parameter (IQR)", where
the IQR was estimated using the balanced bootstrapping approach described in the methods (see
section "Mechanostat (re)modeling velocity curve and parameter derivation") to provide an estimate
for the variability of each parameter. Root mean squared error (RMSE) was used to characterize the
quality of the fit. The row "Effective strain range" indicates the range of mechanical signal values
from which the fit of the mathematical functions was derived. Mechanical signal values obtained
from micro-FE analysis using homogeneous material properties. Parameter legend (see Materials and
Methods and Table 1 for an extended description): Resorption saturation level (RSL), Resorption
velocity modulus (RVM), Resorption threshold (RT), Formation threshold (FT), Formation velocity
modulus (FVM), Formation saturation level (FSL), (Re)modeling threshold (RmT), (Re)modeling
velocity modulus (RmVM). Statistical significance legend: a – "Sham – Static", b – "Sham – 2 Hz",
c – "Sham – 5 Hz", d – "Sham – 10 Hz", e – "Static – 2 Hz", f – "Static – 5 Hz", g – "Static – 10
Hz", h – "2 Hz – 5 Hz", i – "2 Hz – 10 Hz", j – "5 Hz – 10 Hz"; ns: not significant, *p < 0.05, **p <
0.01, ***p < 0.001, ****p < 0.0001. Statistical significance was determined with Conover's test
corrected for multiple comparisons with a step-down method using Bonferroni-Holm adjustments.

Function	Parameter	Unit	Group					p-value
			Sham	Static	2 Hz	5 Hz	10 Hz	

Piecewise linear	RSL	μm/day	-4.305 (-4.928 - -3.439)	-3.062 (-3.602 - -3.028)	-1.729 (-2.394 - -1.578)	-2.570 (-3.040 - -2.003)	-4.112 (-5.029 - -3.239)	****a, b, c, d, e, f, g, h, i, j
	RVM (x10³)	(μm/day) / με	29.748 (19.169 - 39.118)	5.737 (5.546 - 8.235)	8.802 (8.520 - 12.628)	16.245 (15.509 - 20.288)	45.003 (44.090 - 78.179)	****a, b, c, d, e, f, g, h, i, j
	RT	με	145 (125 - 184)	544 (430 - 565)	246 (202 - 265)	187 (160 - 197)	101 (74 - 102)	****a, b, c, d, e, f, g, h, i, j
	FT	με	440 (400 - 470)	1511 (840 - 1661)	270 (230 - 300)	190 (190 - 240)	110 (100 - 170)	****a, b, c, d, e, f, g, h, i, j
	FVM (x10³)	(μm/day) / με	1.676 (1.114 - 1.912)	1.919 (0.584 - 2.895)	2.435 (1.747 - 2.286)	2.330 (2.147 - 3.923)	2.481 (2.560 - 3.235)	****a, b, c, d, e, f, g, h, i; ns: j
	FSL	μm/day	0.180 (0.156 - 0.304)	0.891 (0.450 - 0.931)	1.274 (1.266 - 1.380)	1.640 (1.347 - 1.737)	1.954 (1.719 - 1.964)	****a, b, c, d, e, f, g, h, i, j
	RMSE	μm/day	0.381 (0.346 - 0.474)	0.382 (0.364 - 0.424)	0.227 (0.183 - 0.222)	0.407 (0.229 - 0.289)	0.388 (0.301 - 0.366)	
Hyperbola	RSL	μm/day	-5.776 (-6.540 - -4.761)	-4.115 (-5.301 - -4.423)	-2.390 (-2.822 - -1.917)	-3.208 (-3.676 - -1.154)	-4.180 (-4.549 - -1.457)	****a, b, c, d, e, f, g, h, j; ***i
	RmVM (x10⁻³)	(μm/day) x με	-0.236 (-0.276 - -0.216)	-1.037 (-0.921 - -0.626)	-0.843 (-1.212 - -0.791)	-0.769 (-174.467 - -0.646)	-0.507 (-2036.714 - -0.538)	****a, b, c, d, e, f, g, h, i, j
	RmT	με	482 (390 - 520)	899 (778 - 1212)	268 (247 - 315)	228 (-5.49e6 - 255)	158 (-1.56e7 - 148)	****a, b, c, d, e, f, g, h, i, j
	FSL	μm/day	0.274 (0.192 - 0.360)	0.522 (0.186 - 0.530)	1.468 (1.421 - 1.580)	1.836 (1.390 - 1.711)	2.051 (1.375 - 1.708)	****a, b, c, d, e, f, g, h, i; *j
	RMSE	μm/day	0.259 (0.192 - 0.308)	0.347 (0.261 - 0.345)	0.226 (0.171 - 0.215)	0.372 (0.209 - 0.763)	0.350 (0.383 - 0.962)	
Effective strain range		με	10–1280	10–2240	10–2060	10–2520	10–2650	

1003