Protein language model embedded geometric graphs power inter-protein contact prediction

Yunda Si, Chengfei Yan*

School of Physics, Huazhong University of Science and Technology, China

Correspondence: chengfeiyan@hust.edu.cn

Abstract

Accurate prediction of contacting residue pairs between interacting proteins is very useful for structural characterization of protein-protein interactions (PPIs). Although significant improvement has been made in inter-protein contact prediction recently, there is still large room for improving the prediction accuracy. Here we present a new deep learning method referred to as PLMGraph-Inter for inter-protein contact prediction. Specifically, we employ rotationally and translationally invariant geometric graphs obtained from structures of interacting proteins to integrate multiple protein language models, which are successively transformed by graph encoders formed by geometric vector perceptrons and residual networks formed by dimensional hybrid residual blocks to predict inter-protein contacts. Extensive evaluation on multiple test sets illustrates that PLMGraph-Inter outperforms five top inter-protein contact prediction methods, including DeepHomo, GLINTER, CDPred, DeepHomo2 and DRN-1D2D_Inter by large margins. In addition, we also show that the prediction of PLMGraph-Inter can complement the result of AlphaFold-Multimer. Finally, we show leveraging the contacts predicted by PLMGraph-Inter as constraints for protein-protein docking can dramatically improve its performance for protein complex structure prediction.

Introduction

Protein-protein interactions(PPIs) are essential activities of most cellular processes(Alberts, 1998; Spirin & Mirny, 2003). Structure characterization of PPIs is important for mechanistic investigation of these cellular processes and therapeutic development(Goodsell & Olson, 2000). However, currently experimental structures of many important PPIs are still missing as experimental methods to resolve complex structures such as X-ray crystallography, nuclear magnetic resonance, cryo-electron microscopy are costly and time-consuming(Berman et al., 2000). Therefore, it is necessary to develop computational methods to predict protein complex structures(Bonvin, 2006). Predicting contacting residue pairs between interacting proteins can be considered as an intermediate step for protein complex structure prediction(Hopf et al., 2014; Ovchinnikov et al., 2014), as the predicted contacts can be integrated into protein-protein docking algorithms to assist protein complex structure prediction(Dominguez et al., 2003; H. Li & Huang, 2021; Sun et al., 2020). Besides, the predicted contacts can also be very useful to guide protein interfacial design(Martino et al., 2021) and the inter-protein contact prediction methods can be further extended to predict novel PPIs (Cong et al., 2019; Green et al., 2021).

Based on the fact that contacting residue pairs often vary co-operatively during evolution, coevolutionary analysis methods(Weigt et al., 2009) have been used in previous studies to predict inter-protein contacts(Hopf et al., 2014; Ovchinnikov et al., 2014). However, coevolutionary analysis methods do have certain limitations. For examples, effective coevolutionary analysis requires a large number of interolog sequences, which are often difficult to obtain, especially for heteromeric PPIs(R. M. Rao et al., 2021a); and it is difficult to distinguish inter-protein and intra-protein coevolutionary signals for homomeric PPIs(Uguzzoni et al., 2017). Inspired by its great success in intra-protein contact prediction(Hanson et al., 2018; Ju et al., 2021; Y. Li et al., 2019; Si & Yan, 2021; Wang et al., 2017), deep learning has also been applied to predict inter-protein contacts(Guo et al., 2022; Roy et al., 2022; Xie & Xu, 2022; Yan & Huang, 2021; Zeng et al., 2018). ComplexContact(Zeng et al., 2018) , to the best of our knowledge, the first deep learning method for inter-protein contact prediction, has significantly improved the prediction accuracy over coevolutionary analysis methods. However, its performance on eukaryotic PPIs is still quite limited, partly due to the difficulty to accurately infer interologs for eukaryotic PPIs. In a later study, coming from the same group as ComplexContact, Xie et al. developed GLINTER(Xie & Xu, 2022), another deep learning method for inter-protein contact prediction. Comparing

with ComplexContact, GLINTER leverages structures of interacting

monomers, from which their rotational invariant graph representations are

used as additional input features. GLINTER outperforms ComplexContact in

the prediction accuracy, although there is still large room for improvement,

especially for heteromeric PPIs. It is worth mentioning that CDPred(Guo et

al., 2022), a recently developed method, further surpasses GLINTER in

prediction accuracy with 2D attention-based neural networks. Apart from

these methods developed to predict inter-protein contacts for both homomeric

and heteromeric PPIs, inter-protein contact prediction methods specifically

for homomeric PPIs were also developed(Roy et al., 2022; T. Wu et al., 2022;

Yan & Huang, 2021), as predicting the inter-protein contacts for homomeric

PPIs is generally much easier due to the symmetric restriction, relatively

larger interfaces and the trivialness of interologs identification. For example,

Yan et al. developed DeepHomo(Yan & Huang, 2021), a deep learning

method specifically to predict inter-protein contacts of homomeric PPIs,

which also significantly outperforms coevolutionary analysis-based methods.

However, DeepHomo requires docking maps calculated from structures of

interacting monomers, which is computationally expensive and is also

sensitive to the quality of monomeric structures. Besides, coming from the

same group, Lin et al. further developed DeepHomo2(Lin et al., 2023) for

inter-protein contact prediction for homomeric PPIs by including the MSA (multiple sequence alignment) embeddings and attentions from an MSA-based protein language model (MSA transformer)(R. M. Rao et al., 2021b) in their prediction model, which further improved the prediction performance. In almost the same time with DeepHomo2, we proved that embeddings from protein language models(R. Rao et al., 2021; Rives et al., 2021) (PLMs) are very effective features to predict inter-protein contacts for both homomeric and heteromeric PPIs, and we further show the sequence embeddings (ESM-1b(Rives et al., 2021)), MSA embeddings (ESM-MSA-1b(R. M. Rao et al., 2021b) & Position-Specific Scoring Matrix (PSSM)) and the inter-protein coevolutionary information complement each other in the prediction, with which we developed DRN-1D2D_Inter(Si & Yan, 2023). Extensive benchmark results show that DRN-1D2D_Inter significantly outperforms DeepHomo and GLINTER in inter-protein contact prediction, although DRN-1D2D_Inter makes the prediction purely from sequences.

In this study, we developed a structure-informed method to predict inter-protein contacts. Given the structures of two interacting proteins, we first build rotationally and translationally (SE(3)) invariant geometric graphs from the two monomeric structures, which encode both the inter-residue distance and orientation information of the monomeric structures. We further

embedded the single sequence embeddings (ESM-1b), MSA embeddings (ESM-MSA-1b & PSSM) and structure embeddings (ESM-IF(Hsu et al., 2022a)) from PLMs in the graph nodes of the corresponding residues to build the PLM embedded geometric graphs, which are then transformed by graph encoders formed by geometric vector perceptrons to generate graph embeddings for interacting monomers. The graph embeddings are further combined with inter-protein pairwise features and transformed by residual networks formed by dimensional hybrid residual blocks (residual block hybridizing 1D and 2D convolutions) to predict inter-protein contacts. The developed method referred to as PLMGraph-Inter was extensive benchmarked on multiple tests with application of either experimental or predicted structures of interacting monomers as the input. The result shows that in both cases, PLMGraph-Inter outperforms other top prediction methods including DeepHomo, GLINTER, CDPred, DeepHomo2 and DRN-1D2D_Inter by large margins. In addition, we also compared the prediction results of PLMGraph-Inter with the protein complex structures generated by AlphaFold-Multimer(Evans et al., 2022a). The result shows that for many targets which AlphaFold-Multimer made poor predictions, PLMGraph-Inter yielded better results. Finally, we show leveraging the contacts predicted by

118 PLMGraph-Inter as constraints for protein-protein docking can dramatically

119 improve its performance for protein complex structure prediction.

Results

Overview of PLMGraph-Inter

The method of PLMGraph-Inter is summarized in Figure 1a.

PLMGraph-Inter consists of three modules: the graph representation module

(Figure 1b), the graph encoder module (Figure 1c) and the residual network

module (Figure 1d). Each interacting monomer is first transformed into a

PLM-embedded graph by the graph representation module, then the graph is

passed through the graph encoder module to obtain a 1D representation of

each protein. The two protein representations are transformed into 2D

pairwise features through outer concatenation (horizontal & vertical tiling

followed by concatenation) and further concatenated with other 2D pairwise

features including the inter-protein attention maps and the inter-protein co-

evolution matrices, which are then transformed by the residual network

module to obtain the predicted inter-protein contact map.

The graph representation module. The first step of the graph

representation module is to represent the protein 3D structure as a geometric

graph, where each residue is represented as a node, and an edge is defined if

the C_α atom distance between two residues is less than 18Å. For each node
and edge, we use scalars and vectors extracted from the 3D structures as their
geometric features. To make the geometric graph SE(3) invariant, we use a
set of local coordinate systems to extract the geometric vectors. The SE(3)
invariance of representation of each interacting monomer is important, as in
principle, the inter-protein contact prediction result should not depend on the
initial positions and orientations of protein structures. A detailed description
can be found in the Methods section. The second step is to integrate the single
sequence embedding from ESM-1b(Rives et al., 2021), the MSA embedding
from ESM-MSA-1b(R. Rao et al., 2021), the Position-Specific Scoring Matrix
(PSSM) calculated from the MSA and structure embedding from ESM-IF(Hsu
et al., 2022b) for each interacting monomer using its corresponding geometric
graph. Where ESM-1b and ESM-MSA-1b are pretrained PLMs learned from
large datasets of sequences and MSAs respectively with masked language
modeling tasks, and ESM-IF is a supervised PLM trained from 12 million
protein structures predicted by AlphaFold2(Jumper et al., 2021) for fixed
backbone design. The embeddings from these models contain high
dimensional representations of each residue in the protein, which are
concatenated and further combined with the PSSM to form additional features
of each node in the geometric graph. Since the sequence embeddings, the

MSA embeddings, the PSSM and the structure embeddings are all SE(3)

invariant, the PLM-embedded geometric graph of each protein is also SE(3)

invariant.

The graph encoder module. The graph encoder module is formed by

geometric vector perceptron (GVP) and GVP convolutional layer

(GVPConv)(Jing, Eismann, Soni, et al., 2021; Jing, Eismann, Suriana, et al.,

2021). Where GVP is a graph neural network module consisting of a scalar

track and a vector track, which can perform rotationally invariant

transformations on scalar features and rotationally equivariant on vector

features of nodes and edges; GVPConv follows the message passing paradigm

of graph neural network and mainly consists of GVP, which updates the

embedding of each node by passing information from its neighboring nodes

and edges. A detailed description of GVP and GVPConv can be found in the

Methods section and also in the work of GVP(Jing, Eismann, Soni, et al., 2021;

Jing, Eismann, Suriana, et al., 2021). For each protein graph, we first use a

GVP module to reduce the dimension of the scalar features of each node from

2586 to 256, which is then transformed successively by three GVPConv layers.

Finally, we stitch the scalar features and the vector features of each node to

form the 1D representation of the protein. Since the input protein graph is

SE(3) invariant and the GVP and GVPConv transformations are rotationally

equivariant, the 1D representation of each interacting monomer is also SE(3)

invariant.

The residual network module. The residual network module is mainly

formed by 9 dimensional hybrid residual blocks to transform the 2D feature

maps to obtain the predicted inter-protein contact map. Our previous study

illustrated the effective receptive field can be enlarged with the application of

the dimensional hybrid residual block, thus helps improve the model

performance(Si & Yan, 2021). A more detailed description of the

transforming procedure can be found in the Methods section.

Evaluation of PLMGraph-Inter on HomoPDB and HeteroPDB test sets

We first evaluated PLMGraph-Inter on two self-built test sets which are

non-redundant to the training dataset of PLMGraph-Inter: HomoPDB and

HeteroPDB. Where HomoPDB is the test set for homomeric PPIs containing

400 homodimers and HeteroPDB is the test set for heteromeric PPIs

containing 200 heterodimers. For comparison, we also evaluated DeepHomo,

GLINTER, DeepHomo2, CDPred and DRN-1D2D_Inter on the same datasets.

Since DeepHomo and DeepHomo2 was developed to predict inter-protein

contacts only for homomeric PPIs, its evaluation was only performed on

HomoPDB. It should be noted that since HomoPDB and HeteroPDB are not

de-redundant with the training sets of DeepHomo, DeepHomo2, CDPred and

GLINTER, the performances of the four methods may be overestimated.

In all the evaluations, the structural related features were drawn from

experimental structures of interacting monomers separated from complex

structures of PPIs after randomizing their initial positions and orientations

(DRN-1D2D_Inter does not use structural information). Besides, we also used

the AlphaFold2 predicted monomeric structures as the input, considering

experimental structures of interacting monomers often do not exist. Since the

interacting monomers in HomoPDB and HeteroPDB are not de-redundant

with the training set of AlphaFold2, using default settings of AlphaFold2 may

overestimate its performance. To mimic the performance of AlphaFold2 in

real practice and produce predicted monomeric structures with more diverse

qualities, we only used the MSA searched from Uniref100(Suzek et al., 2015)

protein sequence database as the input of AlphaFold2 and set to not use the

template. The predicted structures yielded a mean TM-score 0.88, which is

close to the performance of AlphaFold2 for CASP14 targets (mean TM-score

0.85)(Z. Lin et al., 2023).

Table 1 shows the mean precision of each method on the HomoPDB and

HeteroPDB when top (5, 10, 50, L/10, L/5) predicted inter-protein contacts

are considered, where L denotes the sequence length of the shorter protein in

the PPI and (Note: GLINTER encountered errors for 81 (5 when using the

predicted monomeric structures) targets in HomoPDB and 15 (3 when using

the predicted monomeric structures) targets in HeteroPDB at run time and did

not produce predictions, thus we removed these targets in the evaluation of

the performance of GLINTER. The performances on HomoPDB and

HeteroPDB for these methods after the removal of these targets which

GLINTER failed in any case are shown in Table S1). As can be seen from the

table, whenever the experimental or the predicted monomeric structures were

used as the input, the mean precision of PLMGraph-Inter far exceeds those of

other algorithms in each metric for both datasets. Particularly, the mean

precision of PLMGraph-Inter is substantially improved in each metric on each

dataset compared to our previous method DRN-1D2D_Inter which used most

features of PLMGraph-Inter except these drawn from structures of the

interacting monomers, illustrating the importance of the inclusion of structural

information. Besides, GLINTER, CDPred and DeepHomo2 also use structural

information and PLMs, but have much lower performance than PLMGraph-

Inter, illustrating the efficacy of our deep learning framework.

It can also be seen from the result that all the methods tend to have better

performances on HomoPDB than those on HeteroPDB. One possible reason

is that the complex structures of homodimers are generally C2 symmetric,

which largely restricts the configurational spaces of PPIs, making the inter-

protein contact prediction a relatively easier task (e.g., the inter-protein

contact maps for homodimers are also symmetric). Besides, comparing with

heteromeric PPIs, we may more likely to successfully infer the inter-protein

coevolutionary information for homomeric PPIs to assist the contact

prediction for two reasons: First, it is straightforward to pair sequences in the

MSAs for homomeric PPIs, thus the paired MSA for homomeric PPIs may

have higher qualities; second, homomeric PPIs may undergo stronger

evolutionary constraints, as homomeric PPIs are generally permanent

interactions, but many heteromeric PPIs are transient interactions.

In addition to using the mean precision on each test set to evaluate the

performance of each method, the performance comparisons between

PLMGraph-Inter and other models on the top 50 predicted contacts for each

individual target in HomoPDB and HeteroPDB are shown in Figure 2

(Separate comparisons are shown in Figure S1 and S2). Specifically, when the

experimental (predicted) structures were used as the input, PLMGraph-Inter

achieved the best performance for 60% (53%) of the targets in HomoPDB and

58% (51%) of the targets in HeteroPDB. We further group targets in each

dataset according to their inter-protein contact densities defined as

$\frac{\text{\# of contacts}}{L_A * L_B}$ and the normalized number of the effective sequences (N_{eff}^{norm})

of paired MSAs. We found that all the methods tend to have lowers

performances for targets with lower contact densities (Figure S3), which is

reasonable, since obviously it is more challenging to identify the true contacts

when their ratio is lower. We also found when the N_{eff}^{norm} is low

($\log(N_{eff}^{norm})$<3), the prediction performances of all methods tend to improve

with N_{eff}^{norm}, but when N_{eff}^{norm} reaches to certain thresholds ($\log(N_{eff}^{norm})$>4),

the performances of all the methods tends to fluctuate with N_{eff}^{norm} (Figure S4).

However, PLMGraph-Inter consistently achieved the best performances in

most categories.

Impact of the monomeric structure quality on contact prediction

We further analyzed performance difference of PLMGraph-Inter when

using the AlphaFold2 predicted structures and using the experimental

structures as the inputs. As it can be seen from Figures 3a-b, when the

predicted structures were used by PLMGraph-Inter for inter-protein contact

prediction, mean precisions of the predicted inter-protein contacts in each

metric on both HomoPDB and HeteroPDB test sets decrease by about 5%

(also see Table 1), indicating qualities of the input structures do have certain

impact on the prediction performance.

We further explored the impact of the monomeric structure quality on

the inter-protein contact prediction performance of PLMGraph-Inter.

Specifically, for a given PPI, the TM-score(Zhang & Skolnick, 2004) was

used to evaluate the quality of the predicted structure for each interacting

monomer, and the TM-score of the predicted structure with lower quality was

used to evaluate the overall monomeric structure prediction quality for the PPI,

denoted as "DTM-score". In Figure 3c, we show the performance gaps (using

the mean precisions of the top 50 predicted contacts as the metric) between

applying the predicted structures and applying the experimental structures in

the inter-protein contact prediction, in which we grouped targets according to

DTM-scores of their monomeric structure prediction, and in Figure 3d, we

show the performance comparison for each specific target. From Figure 3c-

d, we can clearly see that when the DTM-score is lower, the prediction using

the prediction structure tends to have lower accuracy. However, when the

DTM-score is greater than or equal to 0.8, there is almost no difference

between the applying the predicted structures and applying the experimental

structure, which shows the robustness of PLMGraph-Inter to the structure

quality.

Ablation study

To explore the contribution of each input component to the performance of PLMGraph-Inter, we conducted ablation study on PLMGraph-Inter. The graph representation from the structure of each interacting proteins is the base feature of PLMGraph-Inter, so we first trained the baseline model using only the geometric graphs as the input feature, denoted as model a. Our previous study in DRN-1D2D_Inter has shown that the single sequence embeddings, the MSA 1D features (including the MSA embeddings and PSSMs) and the 2D pairwise features from the paired MSA play important roles in the model performance. To further explore the importance of these features when integrated with the geometric graphs, we trained model b-d separately (model b: geometric graphs + sequence embeddings, model c: geometric graphs + sequence embeddings + MSA 1D features, model d: geometric graphs + sequence embeddings + MSA 1D features + 2D features). Finally, we included the structure embeddings as additional features to train the model e (model e uses all the input features of PLMGraph-Inter). All the five models were trained using the same protocol as PLMGraph-Inter on the same training and validation partition without cross validation. We further evaluated performances of models a-e models together with PLMGraph-Inter (i.e.,

model f: model e + cross validation) on HomoPDB and HeteroPDB using

experimental structures of interacting monomers respective.

In Figure 4a, we show the mean precisions of the top 50 predicted contacts

by model a-f on HomoPDB and HeteroPDB respectively. It can be seen from

Figure 4a that including the sequence embeddings in the geometric graphs has

a very good boost to the model performance (model b versus model a), while

the additional introduction of MSA 1D features and 2D pairwise features can

further improve the model performance (model d versus model c versus model

b). DRN-1D2D_Inter also uses the same set of sequence embeddings, MSA

1D features and 2D pairwise features as the input, and our model d shows a

significant performance improvement over DRN-1D2D_Inter (single model)

(the model trained on the same training and validation partition without cross

validation) on both HomoPDB and HeteroPDB (the mean precision

improvement: HomoPDB:14%, HeteroPDB:5.6%), indicating that the

introduced graph representation is important for the model performance. The

head-to-head comparison of model d and DRN-1D2D_Inter (single model) on

each specific target in Figure 4b further demonstrates the value of the graph

representation. Besides, the additional introduced structure embeddings from

ESM-IF can further improve the mean precisions of the predicted contacts by

3~4% on both HomoPDB and HeteroPDB (model e versus model d) and the

application of the cross validation can also improve the precisions by 1.0 %

on HomoPDB and 2.7% on HeteroPDB (model f versus model d) (see Table

S3).

To demonstrate the efficacy of our proposed graph representation of

protein structures, we also trained a model using the structural representation

proposed in the work of GVP(Jing, Eismann, Soni, et al., 2021; Jing, Eismann,

Suriana, et al., 2021) (denoted as "GVP Graph"), as a control. Our structural

representation differs significantly from GVP Graph. For example, we

extracted inter-residue distances and orientations between five atoms

(C,O,Cα,N and a virtual Cβ) from the structure as the geometric scalar and

vector features, in which the vector features are calculated in a local

coordinate system. However, GVP Graph only uses the distances and

orientations between Cα atoms as the geometric scalar and vector features and

the vector features are calculated in a global coordinate system. In addition,

after the geometric graph is transformed by the graph encoder module, GVP

Graph only uses the scalar features of each node as the node representation,

while we concatenate the scalar and vector features of the node as the node

representation. In Figure 4c, we show the performance comparison between

this model and our base model (model a). From Figure 4c, we can clear see

that our base model significantly outperforms the GVP Graph-based model

on both HomoPDB and HeteroPDB, illustrating the high efficacy of our proposed graph representation.

We also explored the performance of PLMGraph-Inter on the HomoPDB and HeteroPDB test sets when using different protocols to further remove potential redundancies between the training and the test sets. Specifically, although the "40% sequence identity" used in our study is a widely used threshold to remove redundancy when evaluating deep learning-based protein-protein interaction and protein complex structure prediction methods(Evans et al., 2022b; Sledzieski et al., 2021), it is worth testing whether PLMGraph-Inter can keep its performance when more stringent threshold is applied. Besides, it is also worth evaluating whether PLMGraph-Inter can keep its performance on targets for which the folds of their interacting monomers are different from the targets in the training set (i.e. non-redundant in main chain structures of interacting monomers). To the best of our knowledge, all the previous studies failed to remove potential redundancies in folds of the interacting monomers when evaluating their methods.

In Table2, we show mean precisions of the contacts (top 50) predicted by PLMGraph-Inter on the HomoPDB and HeteroPDB when various sequence identity thresholds (with MMseq2(Steinegger & Söding, 2018)) and fold

similarity thresholds (with TMalign(Zhang & Skolnick, 2005)) were further used in the de-redundancy (see "Further potential redundancies removal between the training and the test" in the Methods section). It can be seen from that table that when using more stringent sequence identity thresholds for de-redundancy, the performance of PLMGraph-Inter on both the HomoPDB and HeteroPDB datasets decreases very little. For example, even when using "10% sequence identity" for de-redundancy, mean precisions of the predicted contacts only decreases by 2~4%. Whereas when using fold similarities of the interacting monomers for de-redundancy, although the performance of PLMGraph-Inter on HeteroPDB decreases very little (only 3%~4% when TM-Score 0.5 is used as the threshold), the performance of PLMGraph-Inter on HomoPDB decreases significantly (17%~19% when TM-Score 0.5 is used as the threshold). One possible reason for the performance decrease on HomoPDB is that the binding mode of the homomeric PPI is largely determined by the fold of its monomer, thus the model does not generalize well on targets whose folds have never been seen during the training.

Evaluation of PLMGraph-Inter on DHTest and DB5.5 test sets

We further evaluated PLMGraph-Inter on DHTest and DB5.5. The DHTest test set was formed by removing PPIs redundant to our training set from the original test set of DeepHomo, which contains 130 homomeric PPIs.

The DB5.5 test set was formed by removing PPIs redundant to our training

dataset from the heterodimers in Protein-protein Docking Benchmark 5.5,

which contains 59 heteromeric PPIs. Still, both the experimental structures

and the predicted structures (generated using the same protocol as in

HomoPDB and HeteroPDB) of the interacting monomers were used

respectively in the inter-protein contact prediction. It should be noted that

since DHTest and DB5.5 are not de-redundant with the training sets of

CDPred and GLINTER, particularly, all PPIs in the DHTest test set are

included in the training set of CDPred, thus the performances of the two

methods may be overestimated.

As shown in Figure 5a-b, when using the experimental structures in the

prediction, the mean precisions of the top 50 contacts predicted by

PLMGraph-Inter are 71.9% on DHTest and 29.5% on DB5.5 (also see Table

S3), which are dramatically higher than DeepHomo, GLINTER, DeepHomo2

and DRN-1D2D_Inter (Note: GLINTER encountered errors for 47 targets in

DHTest and 3 targets in DB5.5 at run time and did not produce predictions,

thus we removed these targets in the evaluation of the performance of

GLINTER. The performances of other methods on DHTest and DB5.5 after

the removal of these targets are shown in Table S4). We can also see that

although PLMGraph-Inter achieved significantly better performance than

CDPred on DB5.5, its performance on DHTest is quite close to CDPred. However, it should be noted that the performance of CDPred on DHTest might be grossly overestimated since PPIs in DHTest are fully included in the training set of CDPred. The distributions of the precisions of top 50 predicted contacts by different methods on DHTest and DB5.5 are shown in Figure 5d-e, from which we can clearly see that PLMGraph-Inter can make high-quality predictions for more targets on both DHTest and DB5.5.

When using the predicted structures in the prediction, the mean precisions of top 50 contacts predicted by PLMGraph-Inter show reasonable decrease to 61.1% on DHTest and 23.8% on DB5.5 respectively (see Figure 5a-b and Table S3). We also analyzed the impact of the monomeric structure quality on the inter-protein contact prediction performance of PLMGraph-Inter. As shown in Figure 5c, when the DTM-score is greater than or equal to 0.8, there is almost no difference between applying the predicted structures and the experimental structures, which is consistent with our analysis in HomoPDB and HeteroPDB.

We noticed that the performance of PLMGraph-Inter on the DB5.5 is significantly lower than that on HeteroPDB, and so are the performances of other methods. That the targets in DB5.5 have relatively lower mean contact densities (1.01% versus 1.29%) may partly explain this phenomenon. In

Figure 5f, we show the variations of the precisions of predicted contacts with

the variation of contact density. As can be seen from Figure 5f, as the contact

density increases, precisions of predicted contacts tend to increase regardless

of whether the experimental structures or predicted structures are used in the

prediction. 37.29% targets in DB5.5 are with inter-protein contact densities

lower than 0.5%, for which precisions of predicted contacts are generally very

low, making the overall inter-protein contact prediction performance on

DB5.5 relatively low.

Comparison of PLMGraph-Inter with AlphaFold-Multimer

After the development of AlphaFold2, DeepMind also released

AlphaFold-Multimer, as an extension of AlphaFold2 for protein complex

structure prediction. The inter-protein contacts can also be extracted from the

complex structures generated by AlphaFold-Multimer. It is worth making a

comparison between the performances of AlphaFold-Multimer and

PLMGraph-Inter on inter-protein contact prediction. Therefore, we also

employed AlphaFold-Multimer (version 2.2) with its default settings to

generate complex structures for all the PPIs in the four datasets which we used

to evaluate PLMGraph-Inter. We then selected the 50 inter-protein residue

pairs with the shortest heavy atom distances in each generated protein

complex structures as the predicted inter-protein contacts. It should be noted

that AlphaFold-Multimer used all protein complex structures in Protein Data

Bank deposited before 2018-04-30 in the model training, thus these PPIs

may have a large overlap with the training set of AlphaFold-Multimer.

Therefore, there is no doubt that the performance of AlphaFold-Multimer

would be overestimated here. It should also be noted that although AlphaFold-

Multimer makes the prediction from sequences, it automatically searches

templates of the interacting monomers. When we checked our AlphaFold-

Multimer runs, we noticed for 99% of the targets (including all the targets in

the four datasets: HomoPDB, HeteroPDB, DHTest and DB5.5), at least 20

templates were identified (AlphaFold-Multimer only employed the top 20

templates), and AlphaFold-Multimer employed the native template (i.e. the

template which has the same PDB id with the target) for 87.8% of the targets.

Besides, AlphaFold-Multimer employs multiple sequence databases

including huge metagenomics database(Jumper et al., 2021), but PLMGraph-

Inter only employs the UniRef100, thus the comparison is not on the same

footing.

In Figure 6a, we show the relationship between the quality of the

generated protein complex structure (evaluated with DockQ) and the precision

of the top 50 inter-protein contacts extracted from the protein complex

structure predicted by AlphaFold-Multimer for each PPI in the homomeric

PPI (DHTest + HomoPDB) and heteromeric PPI (DB5.5 + HeteroPDB)

datasets. As it can be seen from the figure that the precision of the predicted

contacts is highly correlated with the quality of the generated structure.

Especially when the precision of the contacts is higher than 50%, most of the

generated complex structures have at least acceptable qualities (DockQ $\geqslant$

0.23), in contrast, almost all the generated complex structures are incorrect

(DockQ<0.23) when the precision of the contacts is below 50%. Therefore,

50% can be considered as a critical precision threshold for inter-protein

contact prediction (the top 50 contacts).

In Figure 6b, we show the comparison of the precisions of top 50 contacts

predicted by AlphaFold-Multimer and PLMGraph-Inter for each target when

using the experimental monomeric structures as the input for PLMGraph-Inter

respectively (also see Table S5, and the comparison when using the

AlphaFold2 predicted structures is shown in Figure S5b-d). It can be seen

from the figure that although for most of the targets, AlphaFold-Multimer

yielded better results, but for a significant number of the targets that

AlphaFold-Multimer made poor predictions (precision<50%), the results of

PLMGraph-Inter can have certain improvement over the AlphaFold-Multimer

predictions.

We further explored the performance of PLMGraph-Inter on the PPIs which AlphaFold-Multimer failed to make correct predictions. Specifically, we denoted a PPI for which the precision of top 50 inter-protein contacts predicted by AlphaFold-Multimer is lower than 50% or the DockQ of protein complex structure predicted by AlphaFold-Multimer is less than 0.23 as "precision-Failed", "DockQ-Failed". The "iptm+ptm" metrics output by AlphaFold-Multimer for each target also has certain ability to characterize the quality of the predicted complexes. Our DockQ versus "iptm+ptm" analysis shows that 0.5 can be reasonably chosen as the cutoff of "iptm+ptm" to evaluate whether the prediction of AlphaFold-Multimer is successful or not (see Figure S5a), so we denoted a prediction for which the "iptm + ptm" of the prediction is lower than 0.5 as "pTM-Failed". Then the mean precisions of top 50 contacts predicted by PLMGraph-Inter and AlphaFold-Multimer on the "precision-Failed", "pTM-Failed" and "DockQ-Failed" sub-test sets from "DHTest+HomoPDB" and "DB5.5+HeteroPDB" are shown in Figure 6c-d. From Figure 6c-d we can see that the mean precisions of contacts predicted by PLMGraph-Inter are higher than the mean precisions of contacts predicted by AlphaFold-Multimer, further demonstrating that PLMGraph-Inter can complement AlphaFold-Multimer in certain cases.

PLMGraph-Inter can significantly improve protein-protein docking performance

Prior to AlphaFold-Multimer, protein-protein docking is generally used for protein complex structure prediction. HADDOCK(Honorato et al., 2021; van Zundert et al., 2016) is a widely used information-driven protein-protein docking approach to model complex structures of PPIs, which allows us to encode predicted inter-protein contacts as constraints to drive the docking. In this study, we used HADDOCK (version 2.4) to explore the contribution of PLMGraph-Inter to protein complex structure prediction.

We prepared the test set of homomeric PPIs by merging HomoPDB and DHTest and the test set of heteromeric PPIs by merging HeteroPDB and DB5.5, where the monomeric structures generated previously by AlphaFold2 were used as the input to HADDOCK for protein-protein docking, in which the top 50 contacts predicted by PLMGraph-Inter with the application of the predicted monomeric structures were used as the constraints. Since HADDOCK generally cannot model large conformational changes in protein-protein docking, we filtered PPIs in which either of the AlphaFold2 generated interacting monomeric structure has a TM-score lower than 0.8. Finally, the homomeric PPI test set contains 462 targets, denoted as Homodimer, and the heteromeric PPI test set contains 174 targets, denoted as Heterodimer.

For each PPI, we used the top 50 contacts predicted by PLMGraph-Inter

and other methods as ambiguous distance restraints between the alpha carbons

(CAs) of residues (distance=8Å, lower bound correction=8Å, upper-bound

correction=4Å) to drive the protein-protein docking. All other parameters of

HADDOCK were set as the default parameters. In each protein-protein

docking, HADDOCK output 200 predicted complex structures ranked by the

HADDOCK scores. As a control, we also performed protein-protein docking

with HADDOCK in ab initio docking mode (center of mass restraints and

random ambiguous interaction restraints definition). Besides, for homomeric

PPIs, we additionally added the C2 symmetry constraint in both cases.

As shown in Figure 7a-c, the success rate of docking on Homodimer and

Heterodimer test sets can be significantly improved when using the

PLMGraph-Inter predicted inter-protein contacts as restraints. Where on the

Homodimer test set, the success rate (DockQ $\geq$ 0.23) of the top 1 (top 10)

prediction of HADDOCK in ab initio docking mode are 15.37% (39.18%),

and when predicted by HADDOCK with PLMGraph-Inter predicted contacts,

the success rate of the top 1 (top 10) prediction 57.58% (61.04%). On the

Heterodimer test set, the success rate of top 1 (top 10) predictions of

HADDOCK in ab initio docking mode is only 1.72% (6.32%), and when

predicted by HADDOCK with PLMGraph-Inter predicted contacts, the

success rate of top 1 (top 10) prediction is 29.89% (37.93%). From Figure 7a-

7b we can also see that integrating PLMGraph-Inter predicted contacts with

HADDOCK not only allows for a higher success rate, but also more high-

quality models in the docking results.

We further explored the relationship between the precision of top 50

contacts predicted by PLMGraph-Inter and the success rate of the top

prediction of HADDOCK with PLMGraph-Inter predicted contacts. It can be

clearly seen from Figure 7d that the success rate of protein-protein docking

increases with the precision of contact prediction. Especially, when the

precision of the predicted contacts reaches 50%, the docking success rate of

both homologous and heterologous complexes can reach 80%, which is

consistent with our finding in AlphaFold-Multimer. Therefore, we think this

threshold can be used as a critical criterion for inter-protein contact prediction.

It is important to emphasize that for some targets, although precisions of

predicted contacts are very high, HADDOCK still failed to produce

acceptable models. We manually checked these targets and found many of

these targets have at least one chain totally entangled by another chain (e.g.,

PDB 3DFU in Figure S6). We think large structural rearrangements may exist

in forming the complex structures, which is difficult to model by traditional

protein-protein docking approach.

Finally, we compared the qualities of the complex structures predicted by

HADDOCK (with PLMGraph-Inter predicted contacts) and AlphaFold-

Multimer. Although for some targets (e.g., PDB 5HPS in Figure S7a), the

qualities of the structures predicted by HADDOCK were higher than those by

AlphaFold-Multimer, for most targets, AlphaFold-Multimer generated higher

quality structures (Figure S7). Several reasons can account for the

performance gap. First, precisions of the PLMGraph-Inter predicted contacts

are still not enough, especially for heteromeric PPIs; second, HADDOCK

cannot model large structural rearrangements in protein-protein docking, as

we can see that for some targets, HADDOCK made poor predictions with high

precisions of contact constraints (Figure 7d); third, it is difficult to provide an

objective evaluation of the true performance of AlphaFold-Multimer, since

many targets have already been included in the training set of AlphaFold-

Multimer.

Discussion

584   In this study, we proposed a new method to predict inter-protein contacts,

585   denoted as PLMGraph-Inter. PLMGraph-Inter is based on the SE(3) invariant

586   geometric graphs obtained from structures of interacting proteins which are

587   embedded with multiple PLMs. The predicted inter-protein contacts are

obtained by successively transforming the PLM embedded geometric graphs with graph encoders and residual networks. Benchmarking results on four test datasets show that PLMGraph-Inter outperforms five state-of-the-art inter-protein contact prediction methods including GLINTER, DeepHomo, CDPred, DeepHomo2 and DRN-1D2D_Inter by large margins, regardless of whether the experimental or predicted monomeric structures are used in building the geometric graphs. The ablation study further shows that the integration of the PLMs with the protein geometric graphs can dramatically improve the model performance, illustrating the efficacy of the PLM embedded geometric graphs in protein representations. The protein representation framework proposed in this work can also be used to develop models for other tasks like protein function prediction, PPI prediction, etc. Very recently, Fang et al. have also shown in their work that the incorporation of protein language models in geometric networks can significantly improve the model performances on a variety of protein-related tasks including protein-protein interface prediction, model quality assessment, protein-protein rigid docking and binding affinity prediction (F. Wu et al., 2023), which further supports this claim. We further show PLMGraph-Inter can complement the result of AlphaFold-Multimer and leveraging the inter-protein contacts predicted by PLMGraph-Inter as constraints in protein-

protein docking implemented with HADDOCK can dramatically improve its

performance for protein complex structure prediction.

We noticed that although PLMGraph-Inter has achieved remarkable

progress in inter-protein contact prediction, there is still room for further

improvement, especially for heteromeric PPIs. Using more advanced PLMs,

larger training datasets and explicitly integrating physicochemical features of

interacting proteins are directions worthy of exploration. Besides, since

protein-protein docking approach generally have difficulties in modelling

large conformational changes in PPIs, developing new approaches to

integrate the predicted inter-protein contacts in the more advanced folding-

and-docking framework like AlphaFold-Multimer or directly incorporating an

additional structural module for protein complex structure generation in the

network architecture can also be the future research directions.

Methods

Training and test datasets

We used the training set and test sets prepared in our previous work

DRN-1D2D_Inter(Si & Yan, 2023) to train and evaluate PLMGraph-Inter.

More details for the dataset generation can be found in the previous work.

Specifically, we first prepared a non-redundant PPI dataset containing 4828

homomeric PPIs and 3134 heteromeric PPIs (with sequence identity 40% as

the threshold), and after randomly selecting 400 homomeric PPIs (denoted as

HomoPDB) and 200 heteromeric PPIs (denoted as HeteroPDB) as

independent test sets, the remaining 7362 homomeric and heteromeric PPIs

were used for training and validation.

DHTest and DB5.5 were also prepared in the work of DRN-1D2D_Inter by

removing PPIs which are redundant (with sequence identity 40% as the

threshold) to our training and validation set from the test set of DeepHomo

and Docking Benchmark 5.5. DHTest contains 130 homomeric PPIs, and

DB5.5 contains 59 heteromeric PPIs. Therefore, all the test sets used in this

study are non-redundant (with sequence identity 40% as the threshold) to the

dataset for the model development.

Inter-protein contact definition

For a given PPI, two residues from the two interacting proteins are defined

to be in contact if the distance of any two heavy atoms belonging the two

residues is smaller than 8 Å.

Preparing the Input features

Geometric graphs from structures of interacting monomers

We first represent the protein as a graph, where each residue is represented as a node, and an edge is defined if the Cα atom distance between two residues is less than 18Å (In our small-scale tests, increasing the cutoff used for defining edges can slightly increase the performance of the model. However, due to GPU memory limitations, we set the cutoff as 18Å). For each node and edge, we use scalars and vectors extracted from the 3D structures as their geometric features.

For each residue, we use its C,O,Cα,N and a virtual Cβ atom coordinates to extract information, the virtual Cβ coordinates are calculated using the following formula(Dauparas et al., 2022): b = Cα - N, c = C -Cα, a = cross(b, c), Cβ = -0.58273431*a + 0.56802827*b - 0.54067466*c + Cα.

To achieve a SE(3) invariant graph representation, as shown in Figure S3b, we define a local coordinate system on each residue(Jumper et al., 2021; Pagès et al., 2019). Specifically, for each residue, the unit vector in the Cα − C direction is set as the $\vec{x}$ axis, the unit vector in the Cα-C-N plane and perpendicular $\vec{x}$ to is used as $\vec{y}$, and the z-direction is obtained through the cross product of $\vec{x}$ and $\vec{y}$.

For the ith node, we use the three dihedral angles (ϕ, ψ, ω) of the

corresponding residue as the scalar features of the node (Figure S8a), and the

unit vectors between the C_i, N_i, O_i, $C\alpha_i$, and $C\beta_i$ atoms of the corresponding

residue and the C_{i-1}, N_{i-1}, O_{i-1}, $C\alpha_{i-1}$, and $C\beta_{i-1}$ atoms of the forward

residue and the C_{i+1}, N_{i+1}, O_{i+1}, $C\alpha_{i+1}$, and $C\beta_{i+1}$ atoms of backward

residue as the vector features of the node. In total, for each node, the

dimension of the scalar features is 6 (each dihedral angle is encoded with its

sine and cosine) and the dimension of the vector features is 50*3.

For the edge between ith node and jth node, we use the distances and

directions between the atoms of the two residues as the scalar features and

vector features(See Figure S8b). The distances between the C_i, N_i, O_i, $C\alpha_i$,

and $C\beta_i$ atoms of ith residue and the C_j, N_j, O_j, $C\alpha_j$, and $C\beta_j$ atoms of the jth

residue are used as scalar features after encoded with the 16 Gaussian radial

basis functions(Jing, Eismann, Suriana, et al., 2021). The position difference

between i and j (j-i) is also used as a scalar feature after sinusoidal

encoding(Vaswani et al., 2017). The unit vectors between the C_i, N_i, O_i, $C\alpha_i$,

and $C\beta_i$ atoms of ith residue and the C_j, N_j, O_j, $C\alpha_j$, and $C\beta_j$ atoms of the jth

residue are used as vector features. In total, for each edge, the dimension of

the scalar features is 432 and the dimension of the vector features is 25*3.

Embeddings of single sequence, MSA and structure

The single sequence embedding is obtained by feeding the sequence into

ESM-1b, and the structure embedding is obtained by feeding the structure into

ESM-IF. To obtain the MSA embedding, we first search the Uniref100 protein

sequence database for the sequence using JACKHMMER(Potter et al., 2018)

with the parameter (--incT L/2) to obtain the MSA, which is then inputted to

hhmake(Steinegger et al., 2019) to get the HMM file, and to the LoadHMM.py

script from RaptorX_Contact(Wang et al., 2017) to obtain the PSSM. The

number of sequences of MSA is limited to 256 by hhfilter(Steinegger et al.,

2019) and then input to ESM-MSA-1b to get the MSA embedding. The

dimensions of the sequence embedding, PSSM, MSA embedding and

structural embeddings are 1280, 20, 768 and 512 respectively. After adding

embeddings to the scalar features of the nodes, the dimension of the scalar

features of each node is 2586.

2D feature from paired MSA

For homomeric PPIs, the paired MSA is formed by concatenating two

copies of the MSA. For heteromeric PPIs, the paired MSA is formed by

pairing the MSAs through the phylogeny-based approach described in

(https://github.com/ChengfeiYan/PPI_MSA-taxonomy_rank)(Si   &   Yan,

2022). We input the paired MSA into CCMpred(Seemayer et al., 2014) to get

the evolutionary coupling matrix, and into alnstats(Jones et al., 2015) to get

mutual information matrix, APC-corrected mutual information matrix and

contact potential matrix. The number of sequences of paired MSA is limited

to 256 by hhfilter(Steinegger et al., 2019) and then input to ESM-MSA-1b to

get the attention maps. In total, the channel of 2D features is 148.

GVP and GVPConv

GVP is a two-track neural network module consisting of a scalar track

and a vector track, which can perform SE(3) invariant transformations on

scalar features and SE(3) equivariant transformations on vector features. A

detailed description can be found in the work of GVP(Jing, Eismann, Soni, et

al., 2021; Jing, Eismann, Suriana, et al., 2021).

GVPConv is a message passing based graph neural network, which

mainly consists of a message function and a feedforward function. Where the

message function contains a sequence of three GVP modules and the

feedforward function contains a sequence of two GVP modules. GVPConv

is used to transform the node features. Specifically, the input node features

are first processed by the message function. We denote the features of node i

by $\boldsymbol{h}^i$, the feature of edge (j→i) by $\boldsymbol{h}^{j \to i}$, the set of nodes connected to node

i by $\boldsymbol{\varepsilon}_i$, and the three GVP modules of the message function by *gm*, then the

node features processed by the message function can be represented as:

721
$$h_m^i = \frac{1}{len(\varepsilon_i)}\left(\sum_{j\in\varepsilon_i} gm(concat(\boldsymbol{h}^i, \boldsymbol{h}^{j\rightarrow i}, \boldsymbol{h}^j))\right) \tag{1}$$

722   Where $len(\boldsymbol{\varepsilon}_i)$ denotes the number of nodes connected to node i. After

723   sequential normalization (Equation 2) and feedforward function (Equation 3),

724   the features of node i updated by GVPConv Layer are obtained:

725
$$h_m^i = \text{LayerNorm}(h_m^i + \text{Dropout}(h_m^i)) \tag{2}$$

726
$$h_{out}^i = \text{LayerNorm}(h_m^i + \text{Dropout}(\text{gs}(h_m^i))) \tag{3}$$

727   Where *gs* denotes the two GVP modules of the feedforward function,

728    $\boldsymbol{h}_{out}^i$ denotes the outputs of GVPConv Layer.

The transforming procedure in the residual network module

We first use a convolution layer with kernel size of 1*1 to reduce the

number of channels of the input 2D feature maps from 1044 to 96, which are

then transformed successively by 9 dimensional hybrid residual blocks and

another convolution layer with kernel size of 1*1 for the channel reduction

(from 96 to 1). Finally, we use the sigmoid function to transform the feature

map to obtain the predicted inter-protein contact map.

Training protocol

Our training set contains 7362 PPIs, and we used seven-fold cross-validation to train PLMGraph-Inter. Specifically, we randomly divided the training set into seven subsets, and each time, we selected six subsets as the training set and the remaining subset as the validation set. Seven models were trained in total, and the final prediction was the average of the predictions from the seven models. Each model was trained using AdamW optimizer with 0.001 as the initial learning rate, in which the singularity enhanced loss function proposed by in our previous study(Si & Yan, 2021) was used calculate the training and validation loss. During training, if the validation loss did not decrease within 2 epochs, we would decay the learning rate by 0.1. The training stopped after the learning rate decayed twice and the model with the highest top-50 mean precision on the validation dataset was saved as the prediction model.

PLMGraph-Inter was implemented with pytorch (v.1.11) and trained on one NVIDIA TESLA A100 GPU with batch size equaling to 1. Due to memory limitation of GPU, the length of each protein sequence was limited to 400. When a sequence was longer than 400, a fragment with sequence length equaling to 400 was randomly selected in the model training.

Quality assessment of the predicted protein complex structures

We evaluated the models generated by AlphaFold-Multimer and HADDOCK using DockQ(Basu & Wallner, 2016), a score ranging between 0 and 1. Specifically, a model with DockQ<0.23 means that the prediction is incorrect; 0.23≤DockQ<0.49 means the model is an acceptable prediction; 0.49≤DockQ<0.8 corresponds to a medium quality prediction; and 0.8≤DockQ corresponds to a high quality prediction.

Further potential redundancies removal between the training and the test

Removing potential redundancies using different sequence similarity thresholds

CD-HIT(W. Li et al., 2001) was originally used in removing redundancies between the training and test sets used in this study. Since the lowest sequence identity threshold accepted by CD-HIT is 40%, to use more stringent threshold in the redundancy removal. We further clustered all the monomer sequences from the training set and the test sets (HomoPDB, HeteroPDB) using MMSeq2(Steinegger & Söding, 2018) with different sequence identity thresholds (40%, 30%, 20%, 10%). Under a certain threshold, each sequence is uniquely labeled by the cluster (e.g. cluster 0,

cluster 1, …) to which it belongs, from which each PPI can be marked with a

pair of clusters (e.g. cluster 0-cluster 1). The PPIs belonging to the same

cluster pair (note: cluster n - cluster m and cluster n-cluster m were considered

as the same pair) were considered as redundant with this sequence identity

threshold. For each PPI in the test set, if the pair cluster it belonging to

contains any PPI belonging to the training set, we remove that PPI from the

test set.

Removing potential redundancies using different fold similarity thresholds of

interacting monomers

We used TM-align(Zhang & Skolnick, 2005) to evaluate the fold

similarities (in TM-scores) between the experimental structures of the

interacting monomers in the training set and the test sets (HomoPDB,

HeteroPDB). Specifically, for any two targets A-B and A'-B' in the training

set and test sets respectively, where A, B, A' and B' represent the interacting

monomers. We calculated the MTM-score defined as

789
$$\text{MTM} - \text{score} = \max \begin{cases} min(TM - score_{AA'}, TM - score_{BB'}) \\ min(TM - score_{AB'}, \ TM - score_{BA'}) \end{cases} \quad (4)$$

between the two targets. The MTM-score higher than a certain value means

that both the two interacting monomers in the two targets have fold similarity

scores (TM-scores) higher than this value. When a threshold is chosen, we

remove targets in the test tests if they have MTM-scores higher than this

threshold when comparing with any target in the training set. In this study,

different thresholds including 0.9, 0.8, 0.7, 0.6, 0.5 were used in the study. 0.5

was chosen as the lowest threshold for protein pairs with TM-score<0.5 are

mainly not in the same fold.

Calculating the normalized number of the effective sequences of paired

MSA

We define the normalized number of the effective sequences (N_{eff}^{norm})

as follows:

$$N_{eff}^{norm} = \frac{1}{\sqrt{L}}\sum_{n=1}^{N}\frac{1}{\sum_{m=1}^{N}I[S_{m,n}\geq 0.8]} \tag{5}$$

Where L is the length of the paired MSA, N is the number of sequences

in the paired MSA, $S_{m,n}$ is the sequence identity between the m-th and n-th

sequences, and I[ ] represents the Iverson bracket, which means $I[S_{m,n} \geq$

$0.8] = 1$ if $S_{m,n} \geq 0.8$ or 0 otherwise.

Data Availability

808 The PDB accession codes for the all the training and test sets are provided in

809 https://github.com/ChengfeiYan/PLMGraph-Inter/tree/main/data. Other data

for supporting the finds of this study are available from the corresponding author upon request.

Code Availability

The code for implementing PLMGraph-Inter is provided in https://github.com/ChengfeiYan/PLMGraph-Inter.

Acknowledgements

The work was supported by the National Natural Science Foundation of China (32101001) and new faculty startup grant (3004012167) of Huazhong University of Science and Technology. The computation is completed in the HPC Platform of Huazhong University of Science and Technology.

Author Contributions

Y.S. and C.Y. designed and performed the experiments. Y.S. and C.Y. wrote the manuscript. C.Y. supervised the work.

Ethics declarations

Competing interests

The authors declare no competing interests.

References

Alberts, B. (1998). The Cell as a Collection of Protein Machines: Preparing the Next Generation of Molecular Biologists. *Cell*, *92*(3), 291–294. https://doi.org/10.1016/S0092-8674(00)80922-8

Basu, S., & Wallner, B. (2016). DockQ: A Quality Measure for Protein-Protein Docking Models. *PLOS ONE*, *11*(8), e0161879. https://doi.org/10.1371/journal.pone.0161879

Berman, H. M., Westbrook, J., Feng, Z., Gilliland, G., Bhat, T. N., Weissig, H., Shindyalov, I. N., & Bourne, P. E. (2000). The Protein Data Bank. *Nucleic Acids Research*, *28*(1), 235–242. https://doi.org/10.1093/nar/28.1.235

Bonvin, A. M. (2006). Flexible protein–protein docking. *Current Opinion in Structural Biology*, *16*(2), 194–200. https://doi.org/10.1016/j.sbi.2006.02.002

Cong, Q., Anishchenko, I., Ovchinnikov, S., & Baker, D. (2019). Protein interaction networks revealed by proteome coevolution. *Science*, *365*(6449), 185–189. https://doi.org/10.1126/science.aaw6718

Dauparas, J., Anishchenko, I., Bennett, N., Bai, H., Ragotte, R. J., Milles, L. F., Wicky, B. I. M., Courbet, A., de Haas, R. J., Bethel, N., Leung, P. J. Y., Huddy, T. F., Pellock, S., Tischer, D., Chan, F., Koepnick, B., Nguyen, H., Kang, A., Sankaran, B., … Baker, D. (2022). Robust deep learning–based protein sequence design using ProteinMPNN. *Science*, *0*(0), eadd2187. https://doi.org/10.1126/science.add2187

Dominguez, C., Boelens, R., & Bonvin, A. M. J. J. (2003). HADDOCK: A Protein−Protein Docking Approach Based on Biochemical or Biophysical Information. *Journal of the American Chemical Society*, *125*(7), 1731–1737. https://doi.org/10.1021/ja026939x

Evans, R., O'Neill, M., Pritzel, A., Antropova, N., Senior, A., Green, T., Žídek, A., Bates, R., Blackwell, S., Yim, J., Ronneberger, O., Bodenstein, S., Zielinski, M., Bridgland, A.,

Potapenko, A., Cowie, A., Tunyasuvunakool, K., Jain, R., Clancy, E., … Hassabis, D.

(2022a). *Protein complex prediction with AlphaFold-Multimer* (p. 2021.10.04.463034).

bioRxiv. https://doi.org/10.1101/2021.10.04.463034

Evans, R., O'Neill, M., Pritzel, A., Antropova, N., Senior, A., Green, T., Žídek, A., Bates, R.,

Blackwell, S., Yim, J., Ronneberger, O., Bodenstein, S., Zielinski, M., Bridgland, A.,

Potapenko, A., Cowie, A., Tunyasuvunakool, K., Jain, R., Clancy, E., … Hassabis, D.

(2022b). *Protein complex prediction with AlphaFold-Multimer* (p. 2021.10.04.463034).

bioRxiv. https://doi.org/10.1101/2021.10.04.463034

Goodsell, D. S., & Olson, A. J. (2000). Structural Symmetry and Protein Function. *Annual Review*

of Biophysics and Biomolecular Structure, *29*(1), 105–153.

https://doi.org/10.1146/annurev.biophys.29.1.105

Green, A. G., Elhabashy, H., Brock, K. P., Maddamsetti, R., Kohlbacher, O., & Marks, D. S. (2021).

Large-scale discovery of protein interactions at residue resolution using co-evolution

calculated from genomic sequences. *Nature Communications*, *12*(1), Article 1.

https://doi.org/10.1038/s41467-021-21636-z

Guo, Z., Liu, J., Skolnick, J., & Cheng, J. (2022). Prediction of inter-chain distance maps of protein

complexes with 2D attention-based deep neural networks. *Nature Communications*,

13(1), Article 1. https://doi.org/10.1038/s41467-022-34600-2

Hanson, J., Paliwal, K., Litfin, T., Yang, Y., & Zhou, Y. (2018). Accurate prediction of protein

contact maps by coupling residual two-dimensional bidirectional long short-term

memory with convolutional neural networks. *Bioinformatics*, *34*(23), 4039–4045.

https://doi.org/10.1093/bioinformatics/bty481

Honorato, R. V., Koukos, P. I., Jiménez-García, B., Tsaregorodtsev, A., Verlato, M., Giachetti, A.,

Rosato, A., & Bonvin, A. M. J. J. (2021). Structural Biology in the Clouds: The WeNMR-

EOSC Ecosystem. *Frontiers in Molecular Biosciences*, *8*.

https://doi.org/10.3389/fmolb.2021.729513

Hopf, T. A., Schärfe, C. P. I., Rodrigues, J. P. G. L. M., Green, A. G., Kohlbacher, O., Sander, C.,

Bonvin, A. M. J. J., & Marks, D. S. (2014). Sequence co-evolution gives 3D contacts and

structures of protein complexes. *eLife*, *3*, e03430. https://doi.org/10.7554/eLife.03430

Hsu, C., Verkuil, R., Liu, J., Lin, Z., Hie, B., Sercu, T., Lerer, A., & Rives, A. (2022a). *Learning inverse*

folding from millions of predicted structures (p. 2022.04.10.487779). bioRxiv.

https://doi.org/10.1101/2022.04.10.487779

Hsu, C., Verkuil, R., Liu, J., Lin, Z., Hie, B., Sercu, T., Lerer, A., & Rives, A. (2022b). *Learning inverse*

folding from millions of predicted structures (p. 2022.04.10.487779). bioRxiv.

https://doi.org/10.1101/2022.04.10.487779

Jing, B., Eismann, S., Soni, P. N., & Dror, R. O. (2021). *Equivariant Graph Neural Networks for 3D*

Macromolecular Structure (arXiv:2106.03843). arXiv. http://arxiv.org/abs/2106.03843

Jing, B., Eismann, S., Suriana, P., Townshend, R. J. L., & Dror, R. O. (2021). *LEARNING FROM*

PROTEIN STRUCTURE WITH GEOMETRIC VECTOR PERCEPTRONS. 18.

Jones, D. T., Singh, T., Kosciolek, T., & Tetchner, S. (2015). MetaPSICOV: Combining coevolution

methods for accurate prediction of contacts and long range hydrogen bonding in

proteins. *Bioinformatics (Oxford, England)*, *31*(7), 999–1006.

https://doi.org/10.1093/bioinformatics/btu791

Ju, F., Zhu, J., Shao, B., Kong, L., Liu, T. Y., Zheng, W. M., & Bu, D. (2021). CopulaNet: Learning

residue co-evolution directly from multiple sequence alignment for protein structure

prediction. *Nature Communications*, *12*(1), 2535. https://doi.org/10.1038/S41467-021-

22869-8

Jumper, J., Evans, R., Pritzel, A., Green, T., Figurnov, M., Ronneberger, O., Tunyasuvunakool, K.,

898   Bates, R., Žídek, A., Potapenko, A., Bridgland, A., Meyer, C., Kohl, S. A. A., Ballard, A. J.,

899   Cowie, A., Romera-Paredes, B., Nikolov, S., Jain, R., Adler, J., … Hassabis, D. (2021).

900   Highly accurate protein structure prediction with AlphaFold. *Nature*, *596*(7873), Article

901   7873. https://doi.org/10.1038/s41586-021-03819-2

902   Li, H., & Huang, S.-Y. (2021). Protein–protein docking with interface residue restraints\ast.

903   *Chinese Physics B*, *30*(1), 018703. https://doi.org/10.1088/1674-1056/abc14e

904   Li, W., Jaroszewski, L., & Godzik, A. (2001). Clustering of highly homologous sequences to reduce

905   the size of large protein databases. *Bioinformatics*, *17*(3), 282–283.

906   https://doi.org/10.1093/bioinformatics/17.3.282

907   Li, Y., Hu, J., Zhang, C., & Yu, D. J. (2019). ResPRE: High-accuracy protein contact prediction by

908   coupling precision matrix with deep residual neural networks. *Bioinformatics*, *35*(22),

909   4647–4655. https://doi.org/10.1093/bioinformatics/btz291

910   Lin, P., Yan, Y., & Huang, S.-Y. (2023). DeepHomo2.0: Improved protein–protein contact

911   prediction of homodimers by transformer-enhanced deep learning. *Briefings in*

912   *Bioinformatics*, *24*(1), bbac499. https://doi.org/10.1093/bib/bbac499

913   Martino, E., Chiarugi, S., Margheriti, F., & Garau, G. (2021). Mapping, Structure and Modulation

914   of PPI. *Frontiers in Chemistry*, *9*, 718405. https://doi.org/10.3389/fchem.2021.718405

915   Ovchinnikov, S., Kamisetty, H., & Baker, D. (2014). Robust and accurate prediction of residue–

916   residue interactions across protein interfaces using evolutionary information. *eLife*, *3*,

917   e02030. https://doi.org/10.7554/eLife.02030

918   Pagès, G., Charmettant, B., & Grudinin, S. (2019). Protein model quality assessment using 3D

919   oriented convolutional neural networks. *Bioinformatics*, *35*(18), 3313–3319.

920   https://doi.org/10.1093/bioinformatics/btz122

Potter, S. C., Luciani, A., Eddy, S. R., Park, Y., Lopez, R., & Finn, R. D. (2018). HMMER web server:

2018 update. *Nucleic Acids Research*, *46*(W1), W200–W204.

https://doi.org/10.1093/nar/gky448

Rao, R., Liu, J., Verkuil, R., Meier, J., Canny, J. F., Abbeel, P., Sercu, T., & Rives, A. (2021). MSA

Transformer. *bioRxiv*, 2021.02.12.430858.

Rao, R. M., Liu, J., Verkuil, R., Meier, J., Canny, J., Abbeel, P., Sercu, T., & Rives, A. (2021a). MSA

Transformer. *Proceedings of the 38th International Conference on Machine Learning*,

8844–8856. https://proceedings.mlr.press/v139/rao21a.html

Rao, R. M., Liu, J., Verkuil, R., Meier, J., Canny, J., Abbeel, P., Sercu, T., & Rives, A. (2021b). MSA

Transformer. *Proceedings of the 38th International Conference on Machine Learning*,

8844–8856. https://proceedings.mlr.press/v139/rao21a.html

Rives, A., Meier, J., Sercu, T., Goyal, S., Lin, Z., Liu, J., Guo, D., Ott, M., Zitnick, C. L., Ma, J., &

Fergus, R. (2021). Biological structure and function emerge from scaling unsupervised

learning to 250 million protein sequences. *Proceedings of the National Academy of*

Sciences of the United States of America, *118*(15), 1–46.

https://doi.org/10.1073/pnas.2016239118

Roy, R. S., Quadir, F., Soltanikazemi, E., & Cheng, J. (2022). A deep dilated convolutional residual

network for predicting interchain contacts of protein homodimers. *Bioinformatics*,

38(7), 1904–1910. https://doi.org/10.1093/bioinformatics/btac063

Seemayer, S., Gruber, M., & Söding, J. (2014). CCMpred—Fast and precise prediction of protein

residue-residue contacts from correlated mutations. *Bioinformatics (Oxford, England)*,

30(21), 3128–3130. https://doi.org/10.1093/bioinformatics/btu500

Si, Y., & Yan, C. (2021). Improved protein contact prediction using dimensional hybrid residual

networks and singularity enhanced loss function. *Briefings in Bioinformatics*, *22*(6),

bbab341. https://doi.org/10.1093/bib/bbab341

Si, Y., & Yan, C. (2022). Protein complex structure prediction powered by multiple sequence

alignments of interologs from multiple taxonomic ranks and AlphaFold2. *Briefings in*

Bioinformatics, *23*(4), bbac208. https://doi.org/10.1093/bib/bbac208

Si, Y., & Yan, C. (2023). Improved inter-protein contact prediction using dimensional hybrid

residual networks and protein language models. *Briefings in Bioinformatics*, bbad039.

https://doi.org/10.1093/bib/bbad039

Sledzieski, S., Singh, R., Cowen, L., & Berger, B. (2021). D-SCRIPT translates genome to phenome

with sequence-based, structure-aware, genome-scale predictions of protein-protein

interactions. *Cell Systems*, *12*(10), 969–982. https://doi.org/10.1016/j.cels.2021.08.010

Spirin, V., & Mirny, L. A. (2003). Protein complexes and functional modules in molecular

networks. *Proceedings of the National Academy of Sciences*, *100*(21), 12123–12128.

https://doi.org/10.1073/pnas.2032324100

Steinegger, M., Meier, M., Mirdita, M., Vöhringer, H., Haunsberger, S. J., & Söding, J. (2019). HH-

suite3 for fast remote homology detection and deep protein annotation. *BMC*

Bioinformatics, *20*(1), Article 1. https://doi.org/10.1186/s12859-019-3019-7

Steinegger, M., & Söding, J. (2018). Clustering huge protein sequence sets in linear time. *Nature*

Communications, *9*(1), Article 1. https://doi.org/10.1038/s41467-018-04964-5

Sun, D., Liu, S., & Gong, X. (2020). Review of multimer protein–protein interaction complex

topology and structure prediction\ast. *Chinese Physics B*, *29*(10), 108707.

https://doi.org/10.1088/1674-1056/abb659

Uguzzoni, G., John Lovis, S., Oteri, F., Schug, A., Szurmant, H., & Weigt, M. (2017). Large-scale

identification of coevolution signals across homo-oligomeric protein interfaces by direct

coupling analysis. *Proceedings of the National Academy of Sciences*, *114*(13), E2662–

E2671. https://doi.org/10.1073/pnas.1615068114

van Zundert, G. C. P., Rodrigues, J. P. G. L. M., Trellet, M., Schmitz, C., Kastritis, P. L., Karaca, E.,

Melquiond, A. S. J., van Dijk, M., de Vries, S. J., & Bonvin, A. M. J. J. (2016). The

HADDOCK2.2 Web Server: User-Friendly Integrative Modeling of Biomolecular

Complexes. *Journal of Molecular Biology*, *428*(4), 720–725.

https://doi.org/10.1016/j.jmb.2015.09.014

Vaswani, A., Shazeer, N., Parmar, N., Uszkoreit, J., Jones, L., Gomez, A. N., Kaiser, Ł., &

Polosukhin, I. (2017). Attention is All you Need. *Advances in Neural Information*

Processing Systems, *30*.

https://papers.nips.cc/paper/2017/hash/3f5ee243547dee91fbd053c1c4a845aa-

Abstract.html

Wang, S., Sun, S., Li, Z., Zhang, R., & Xu, J. (2017). Accurate De Novo Prediction of Protein

Contact Map by Ultra-Deep Learning Model. *PLOS Computational Biology*, *13*(1),

1005324. https://doi.org/10.1371/journal.pcbi.1005324

Weigt, M., White, R. A., Szurmant, H., Hoch, J. A., & Hwa, T. (2009). Identification of direct

residue contacts in protein–protein interaction by message passing. *Proceedings of the*

National Academy of Sciences, *106*(1), 67–72.

https://doi.org/10.1073/pnas.0805923106

Wu, F., Wu, L., Radev, D., Xu, J., & Li, S. Z. (2023). Integration of pre-trained protein language

models into geometric deep learning networks. *Communications Biology*, *6*(1), Article 1.

https://doi.org/10.1038/s42003-023-05133-1

Wu, T., Huang, H., Li, J., Wang, W., & Gong, X. (2022). Inter-chain contact map prediction for

protein complex based on graph attention network and triangular multiplication update.

2022 IEEE International Conference on Bioinformatics and Biomedicine (BIBM), 2143–

2148. https://doi.org/10.1109/BIBM55620.2022.9995360

Xie, Z., & Xu, J. (2022). Deep graph learning of inter-protein contacts. *Bioinformatics*, *38*(4), 947–

953. https://doi.org/10.1093/bioinformatics/btab761

Yan, Y., & Huang, S. Y. (2021). Accurate prediction of inter-protein residue-residue contacts for

homo-oligomeric protein complexes. *Briefings in Bioinformatics*, *22*(5), 1–13.

https://doi.org/10.1093/bib/bbab038

Zeng, H., Wang, S., Zhou, T., Zhao, F., Li, X., Wu, Q., & Xu, J. (2018). ComplexContact: A web

server for inter-protein contact prediction using deep learning. *Nucleic Acids Research*,

46(W1), W432–W437. https://doi.org/10.1093/nar/gky420

Zhang, Y., & Skolnick, J. (2004). Scoring function for automated assessment of protein structure

template quality. *Proteins: Structure, Function, and Bioinformatics*, *57*(4), 702–710.

https://doi.org/10.1002/prot.20264

Zhang, Y., & Skolnick, J. (2005). TM-align: A protein structure alignment algorithm based on the

TM-score. *Nucleic Acids Research*, *33*(7), 2302–2309.

https://doi.org/10.1093/nar/gki524

1008

1009

1010

1011

1012

Figures and Tables

1014

1015

Figure 1. Overview of PLMGraph-Inter. (a) The network architecture of PLMGraph-Inter. (b) The graph representation module. (c) The graph encoder module, s denotes scalar features, v denotes vector features. (d) The dimensional hybrid residual block ("IN" denotes Instance Normalization).

1020

1021

Figure 2. The performances of PLMGraph-Inter and other methods on the HomoPDB and HeteroPDB test sets. (a)~(b): The head-to-head comparison of the precisions (%) of the top 50 contacts predicted by PLMGraph-Inter and other methods for each target in (a) HomoPDB and (b) HeteroPDB using experimental structures. (c)~(d): The head-to-head comparison of the precisions (%) of the top 50 contacts predicted by PLMGraph-Inter and other methods for each target in (c) HomoPDB and (d) HeteroPDB using AlphaFold2 predicted structures.

1029

Figure 3. The performances of PLMGraph-Inter when using experimental and AlphaFold2 predicted structures as the input. (a)~(b): The performance comparison of PLMGraph-Inter when using experimental structures and AlphaFold2 predicted structures as the input on (a) HomoPDB and (b) HeteroPDB. (c) The performance gaps (measured as the difference of the mean precision of the top 50 predicted contacts) of PLMGraph-Inter with the application of AlphaFold2 predicted structures and experimental structures as the input when the PPIs are within different intervals of DTM-score. The upper panel shows the percentage of the total number of PPI's in each interval. (d) The comparison of the precision of top 50 contacts predicted by PLMGraph-Inter for each target when using experimental structures and AlphaFold2 predicted structures as the input.

1041

Figure 4. The ablation study of PLMGraph-Inter on the HomoPDB and HeteroPDB test sets. (a) The mean precisions of the top 50 contacts predicted by different ablation models on the HomoPDB and HeteroPDB test sets. (b) The head-to-head comparisons of mean precisions of the top 50 contacts predicted by model d and DRN-1D2D_Inter (single model) for each target in HomoPDB and HeteroPDB. (c) The head-to-head comparison of mean precisions of the top 50 contacts predicted by the model using our geometric graphs and the GVP geometric graphs.

1049

1050

1051

Figure 5. The performances of PLMGraph-Inter and other methods on the DHTest and DB5.5 test sets. (a)~(b): The mean precisions of top 50 contacts predicted by PLMGraph-Inter, GLINTER, DeepHomo2, CDPred and DeepHomo on (a) DHTest and (b) DB5.5 when using experimental structures and AlphaFold2 predicted structures as the input, where the green lines indicate the performance of DRN-1D2D_Inter. (c) The performance gaps (measured as the difference of the mean precision of the top 50 predicted contacts) of PLMGraph-Inter with the application of AlphaFold2 predicted structures and experimental structures as the input when the PPIs are within different intervals of DTM-score. The upper panel shows the percentage of the total number of PPI's in each interval. (d)~(e): The distributions of precisions of the top 50 contacts predicted by PLMGraph-Inter and other methods for PPIs in (d) DHTest and (e) DB5.5. (f) The mean precisions of the top 50 contacts predicted by PLMGraph-Inter on PPIs within different intervals of contact densities in DB5.5. The upper panel shows the percentage of the total number of PPI's in each interval.

1066

Figure 6. The comparison of PLMGraph-Inter with AlphaFold-Multimer. (a) The head-to-head comparison between the qualities of the protein complex structures generated by AlphaFold-Multimer (evaluated with DockQ) and the precision of the top 50 inter-protein contacts extracted from the generated protein complex structures. The red horizontal lines represent the threshold (DockQ=0.23) to determine whether the complex

structure prediction is successful or not. (b) The head-to-head comparisons of precisions

of the top 50 inter-protein contacts predicted by PLMGraph-Inter and AlphaFold-Multimer

for each target in the homomeric PPI and heteromeric PPI datasets. (c)~(d): The mean

precisions of top 50 inter-protein contacts predicted by PLMGraph-Inter and AlphaFold-

Multimer on the PPI subsets from (c)"DHTest+HomoPDB" and (d) "DB5.5+HeteroPDB"

in which the precision of the top 50 inter-protein contacts predicted by AlphaFold-

Multimer is lower than 50% or the DockQ of the complex structure predicted by

AlphaFold-Multimer is lower than 0.23 or the "iptm + ptm" of the complex structure

predicted by AlphaFold-Multimer is lower than 0.5.

1083

1084

1085

1086

1087

Figure 7. Protein-protein docking performances on the Homodimer and Heterodimer test sets. (a)~(b) The protein-protein docking performance comparison between HADDOCK with and without (ab-initio) using PLMGraph-Inter predicted contacts as restraints on (a) Homodimer and (b) Heterodimer. The left side of each column shows the performance when the top 1 predicted model for each PPI is considered, and the right side shows the performance when the top 10 predicted models for each PPI are considered. (c) The head-to-head comparison of qualities of the top 1 model predicted by HADDOCK with and without using PLMGraph-Inter predicted contacts as restraints for each target PPI. The red lines represent the threshold (DockQ=0.23) to determine whether the complex structure

1097   prediction is successful or not. (d) The success rates (the top 1 model) for protein complex

1098   structure prediction when only including targets for which precisions of the predicted

1099   contacts are higher than certain thresholds.

1100

1101

1102

1103

1104

1105

1106

1107

1108

1109

1110

1111

1112

1113

1114

1115

 Table 1. The performances of DeepHomo, GLINTER, DRN-1D2D_Inter, CDPred,

 DeepHomo2 and PLMGraph-Inter on the HomoPDB and HeteroPDB test sets using

 experimental structures (AlphaFold2 predicted structures)

Methods	HomoPDB (precision %)					HeteroPDB (precision %)				
	L/5	L/10	50	10	5	L/5	L/10	50	10	5
DeepHomo	43.2 (39.3)	46.7 (42.7)	42.4 (38.8)	48.5 (44.8)	49.9 (46.2)					
GLINTER	42.9 (47.3)	45.0 (50.1)	42.2 (52.1)	46.4 (51.9)	48.5 (53.6)	23.9 (25.1)	24.7 (27.0)	20.9 (21.9)	25.5 (25.8)	26.7 (26.2)
DRN-1D2D_Inter	52.5	55.2	51.3	56.6	57.6	34.9	37.1	32.6	38.1	38.5
DeepHomo2	55.6 (52.4)	58.1 (53.9)	55.0 (51.7)	59.4 (55.7)	61.3 (56.7)					
CDPred	59.4 (54.7)	61.3 (56.2)	58.4 (54.1)	62.4 (57.1)	62.9 (57.7)	30.0 (30.2)	31.0 (31.7)	27.6 (27.3)	32.0 (32.2)	32.1 (32.7)
PLMGraph-Inter	**68.6 (61.8)**	**70.4 (63.6)**	**67.3 (60.9)**	**71.6 (65.0)**	**72.1 (65.25)**	**45.9 (41.9)**	**48.6 (43.6)**	**41.4 (37.8)**	**49.1 (44.1)**	**51.6 (45.0)**

 Note: The highest mean precision (%) in each column is highlighted in bold.

1129 **Table 2.** The performance of PLMGraph-Inter when using different sequence identity and

1130 fold similarity thresholds to further remove potential redundancies in HomoPDB and

1131 HeteroPDB.

		HomoPDB		HeteroPDB	
		Count	Precision (Top 50 (%))	Count	Precision (Top 50 (%))
Sequence identity (MMSeqs2)	Original	400	67.3 (60.9)	200	41.4 (37.8)
	40%	341	68.7 (62.5)	160	38.6 (35.6)
	30%	257	64.7 (58.7)	144	38.1 (35.1)
	20%	211	63.2 (56.3)	138	38.5 (35.3)
	10%	211	63.2 (56.3)	138	38.5 (35.3)
Fold similarity (TM-align)	0.9	370	65.2 (58.3)	185	39.7 (35.7)
	0.8	281	61.8 (53.4)	153	38.1 (34.1)
	0.7	179	56.5 (45.8)	126	38.8 (34.6)
	0.6	124	50.4 (39.9)	102	37.4 (34.1)
	0.5	70	49.6 (41.3)	83	36.5 (34.5)

1132 *The results using experimental structures are shown outside the parentheses, and the
1133 results using the AlphaFold2 predicted structures are shown in the parentheses.

1134

1135

1136

1137

1138

1139

1140

1141

1142

1143 # **Supplementary**

1144

1145

1146 **Figure S1.** The head-to-head comparison of the precisions (%) of the top 50 contacts
1147 predicted by PLMGraph-Inter and other methods for each target in HomoPDB and
1148 HeteroPDB using experimental structures.

1149

Figure S2. The head-to-head comparison of the precisions (%) of the top 50 contacts predicted by PLMGraph-Inter and other methods for each target in HomoPDB and HeteroPDB using AlphaFold2 predicted structures.

Figure S3. The mean precision versus contact density for the top 50 contacts predicted by PLMGraph-Inter, GLINTER, DeepHomo, DeepHomo2, CDPred, DRN-1D2D_Inter on the HomoPDB test set (a, c) and HeteroPDB test set (b, d) using experimental structures (first row) and AlphaFold2 predicted structures (second row).

1166

Figure S4. The mean precision versus $\log(N_{eff}^{norm})$ for the top 50 contacts predicted by PLMGraph-Inter, GLINTER, DeepHomo, DeepHomo2, CDPred, DRN-1D2D_Inter on the HomoPDB test set (a, c) and HeteroPDB test set (b, d) using experimental structures (first row) and AlphaFold2 predicted structures (second row).

1167

1168

1169

1170

1171

1172

1173

1174

Figure S5. The comparison of PLMGraph-Inter with AlphaFold-Multimer. (b) The head-to-head comparisons of precisions of the top 50 inter-protein contacts predicted by PLMGraph-Inter(using AlphaFold2 predicted structures) and AlphaFold-Multimer for each target in the homomeric PPI and heteromeric PPI datasets. (c)~(d): The mean precisions of top 50 inter-protein contacts predicted by PLMGraph-Inter(using AlphaFold2 predicted structures as input) and AlphaFold-Multimer on the PPI subsets from (c) "DHTest+HomoPDB" and (d) "DB5.5+HeteroPDB" in which the precision of the top 50

1183   inter-protein contacts predicted by AlphaFold-Multimer is lower than 50% or the DockQ

1184   of the complex structure predicted by AlphaFold-Multimer is lower than 0.23 or the "iptm

1185   + ptm" of the complex structure predicted by AlphaFold-Multimer is lower than 0.5.

1186

1187

1188

1189

1190

1191

1192

1193

1194

1195

1196

1197

1198

1199 **Figure S6.** 3D structure of the homodimer (PDB: 3DFU).

1200

1201

1202

1203

1204

Figure S7. The comparison of HADDOCK (with PLMGraph-Inter contact constraints)

with AlphaFold-Multimer in protein complex structure prediction. (a) The binding

configurations predicted by HADDOCK (colored orange，DockQ 0.375), predicted by

AlphaFold-Multimer (colored pink, DockQ 0) and the native binding configuration

(colored blue) for the chain B of the protein complex structure in PDB 5HPS. The chain A

is shown in the protein surface mode (colored green). (b)~(c): The head-to-head

comparison of qualities of the (a) top 1 or (b) top 10 model predicted by HADDOCK with

using PLMGraph-Inter predicted contacts as restraints and AlphaFold-Multimer for each

target PPI.

1222

Figure S8. The graph representation of protein structures. (a) Dihedral angles of the protein backbone. (b) The local coordinate system of each amino acid. (c) The scalar (distances) and vector (directions) of the edge i->j.

1223

1224

1225

1226

1227

1228

1229

1230

1231 **Table S1.** The performances of DeepHomo, GLINTER, DRN-1D2D_Inter, DeepHomo2,

1232 CDPred and PLMGraph-Inter on HomoPDB and HeteroPDB after the removal of targets

1233 which GLINTER failed to make the prediction using experimental structures (AlphaFold2

1234 predicted structures)

Methods	HomoPDB (precision %)					HeteroPDB (precision %)				
	L/5	L/10	50	10	5	L/5	L/10	50	10	5
DeepHomo	40.8 (36.8)	44.0 (39.5)	40.2 (36.1)	45.7 (41.6)	46.6 (42.6)					
GLINTER	42.6 (45.5)	44.7 (48.2)	41.8 (44.2)	46.1 (50.1)	48.2 (51.5)	24.3 (24.6)	25.2 (26.6)	21.3 (21.8)	25.9 (25.3)	27.1 (25.8)
DRN-1D2D_Inter	50.2	52.8	49.1	53.9	54.8	33.9	36.0	31.7	36.5	37.3
DeepHomo2	53.5 (49.8)	56.0 (51.3)	52.9 (49.2)	57.3 (53.4)	59.2 (54.1)					
CDPred	56.3 (51.5)	58.4 (52.9)	55.4 (50.9)	59.7 (53.9)	60.3 (54.2)	30.6 (30.7)	31.5 (32.3)	28.1 (27.7)	32.6 (32.8)	32.4 (33.2)
PLMGraph-Inter	**66.3 (59.1)**	**68.4 (61.0)**	**65.2 (58.4)**	**69.7 (62.4)**	**70.1 (62.5)**	**45.8 (41.9)**	**48.7 (43.5)**	**41.2 (37.7)**	**49.2 (44.3)**	**52.0 (45.2)**

1235 Note: The highest mean precision (%) in each column is highlighted in bold.

1236

1237

1238

1239

1240

1241

1242

1243

1244 **Table S2.** The performances of different ablation study models on the HomoPDB and

1245 HeteroPDB test sets

Methods	HomoPDB (precision %)					HeteroPDB (precision %)				
	L/5	L/10	50	10	5	L/5	L/10	50	10	5
Model a	31.7	34.2	30.9	35.8	37.4	18.2	19.1	16.5	19.3	19.7
Model b	52.1	54.9	50.7	57.3	58.3	32.7	32.8	28.8	32.9	34.3
Model c	54.5	57.4	52.8	58.9	60.6	32.9	34.1	29.3	34.0	34.3
Model d	64.0	65.7	62.6	67.3	68.1	37.8	39.7	35.4	40.1	41.0
Model e	67.1	69.2	66.3	70.5	71.3	42.2	43.3	38.7	43.9	44.6
Model f	68.6	70.4	67.3	71.6	72.1	45.9	48.6	41.4	49.1	51.6

1246

1247

1248

1249

1250

1251

1252

1253

1254

1255

1256

1257

1258 **Table S3.** The performances of DeepHomo, GLINTER, DRN-1D2D_Inter, DeepHomo2,

1259 CDPred and PLMGraph-Inter on the DHTest and DB5.5 test sets using experimental

1260 structures (AlphaFold2 predicted structures)

Methods	DHTest (precision %)					DB5.5 (precision %)				
	L/5	L/10	50	10	5	L/5	L/10	50	10	5
DeepHomo	45.0 (36.5)	47.4 (38.2)	44.2 (36.1)	50.2 (40.4)	50.9 (42.9)					
GLINTER	48.5 (46.7)	50.8 (48.8)	47.4 (45.1)	51.2 (51.0)	52.3 (51.5)	18.8 (16.1)	20.5 (15.0)	15.2 (12.6)	21.9 (15.6)	20.7 (16.9)
DRN-1D2D_Inter	52.1	53.3	52.3	54.9	56.0	24.4	26.9	20.7	25.4	27.5
DeepHomo2	59.5 (50.7)	60.0 (51.7)	58.7 (50.5)	61.3 (52.5)	62.0 (52.6)					
CDPred	69.2 (61.4)	72.2 (62.4)	69.1 (61.0)	73.7 (63.3)	74.8 **(64.1)**	27.7 (24.7)	29.3 (26.6)	24.7 (22.8)	30.6 (27.4)	30.2 (28.1)
PLMGraph-Inter	**72.0 (61.7)**	**73.3 (62.6)**	**71.9 (61.1)**	**74.7 (63.4)**	**75.4** (63.5)	**33.6 (28.6)**	**36.4 (31.4)**	**29.5 (23.8)**	**36.9 (30.3)**	**40.0 (31.5)**

1261 Note: The highest mean precision (%) in each column is highlighted in bold.

1262

1263

1264

1265

1266

1267

1268

1269

1270

1271 **Table S4.** The performances of DeepHomo, GLINTER, DRN-1D2D_Inter, DeepHomo2,

1272 CDPred and PLMGraph-Inter on DHTest and DB5.5 after the removal of targets which

1273 GLINTER failed to make the prediction using experimental structures (AlphaFold2

1274 predicted structures)

Methods	DHTest (precision %)					DB5.5 (precision %)				
	L/5	L/10	50	10	5	L/5	L/10	50	10	5
DeepHomo	41.6 (32.6)	43.9 (33.7)	41.3 (32.9)	47.6 (35.8)	48.6 (37.8)					
GLINTER	48.5 (41.6)	50.8 (43.4)	47.4 (40.4)	51.2 (46.1)	52.3 (46.3)	18.8 (15.5)	20.5 (14.0)	15.2 (12.6)	21.9 (15.4)	20.7 (16.4)
DRN-1D2D_Inter	45.5	46.9	45.5	48.9	49.9	23.4	25.3	19.9	24.6	25.7
DeepHomo2	56.3 (48.2)	57.1 (49.7)	56.0 (48.4)	58.9 (50.1)	59.2 (49.4)					
CDPred	**65.4** **(56.9)**	**67.9** **(58.1)**	**65.4** **(56.9)**	**69.7** **(59.3)**	**70.8** **(59.7)**	27.8 (24.3)	29.2 (25.9)	24.4 (22.6)	30.7 (27.1)	30.3 (27.9)
PLMGraph-Inter	64.7 (55.8)	66.2 (57.0)	65.3 (55.8)	68.3 (57.5)	69.2 (57.3)	**32.4** **(27.9)**	**34.4** **(30.4)**	**28.5** **(23.4)**	**35.5** **(30.0)**	**38.6** **(30.7)**

1275 Note: The highest mean precision (%) in each column is highlighted in bold.

1276

1277

1278

1279

1280

1281

1282

1283

1284 **Table S5.** The performances of AlphaFold-Multimer and PLMGraph-Inter on the

1285 homodimer and heterodimer test sets

Methods	Precision@Top 50 (%)	
	Homodimer	Heterodimer
AlphaFold-Multimer	76.5	67.8
PLMGraph-Inter (experimental structure as inputs)	68.7	38.6
PLMGraph-Inter (AlphaFold2 predicted structure as inputs)	61.2	34.6

1286

1287

1288