Reliance on Episodic vs. Procedural Systems in Decision-Making Depends on

Individual Differences in Their Relative Neural Efficiency

Yuxue Yang[1], Catherine L. Sibert[2], Andrea Stocco[1*]

[1]Department of Psychology, University of Washington; Seattle, WA, USA 98105

[2]Science and Engineering, University of Groningen, Groningen, Netherlands

*Corresponding author: A. Stocco.

Email: stocco@uw.edu

Statements and Declarations

Funding

Data were provided in part by the Human Connectome Project, WU-Minn
Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil;
1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH
Blueprint for Neuroscience Research; and by the McDonnell Center for Systems
Neuroscience at Washington University.

Competing Interests

The authors declare that the research was conducted in the absence of any
commercial or financial relationships that could be construed as a conflict of interest.

Author Contributions

Conceptualization: AS, CS, YY. Methodology: AS,YY. Formal analysis: AS,YY.
Visualization: AS,YY. Funding acquisition: AS. Project administration. AS; Supervision:
AS. Writing – original draft: AS, YY, CS. Writing – review & editing: N/A

Ethics approval

This study used data from the Human Connectome Project. The use of this data
was approved by the University of Washington's Institutional Review Board.

Consent to participate

Consent to participate was acquired at the time the data was collected by the
Human Connectome Project. The use of this data was approved by the University of
Washington's Institutional Review Board.

Consent to publish

Participants consented to the publication of follow-up data analysis and results at
the time their data was collected by the Human Connectome Project. The use of this data
was approved by the University of Washington's Institutional Review Board.

Abstract

Experiential decision-making can be explained as a result of either memory-based or reinforcement-based processes. Here, for the first time, we show that individual preferences between a memory-based and a reinforcement-based strategy, even when the two are functionally equivalent in terms of expected payoff, are adaptively shaped by individual differences in resting-state brain connectivity between the corresponding brain regions. Using computational cognitive models to identify which mechanism was most likely used by each participant, we found that individuals with comparatively stronger connectivity between memory regions prefer a memory-based strategy, while individuals with comparatively stronger connectivity between sensorimotor and habit-formation regions preferentially rely on a reinforcement-based strategy. These results suggest that human decision-making is adaptive and sensitive to the neural costs associated with different strategies.

Introduction

Two distinct frameworks have been proposed to explain how experience influences human behavior. According to one class of theories, previous decisions and their outcomes are stored as traces in episodic long-term memory, and decision-making is controlled by which memory is easier to retrieve (Gonzalez & Dutt, 2011; Stewart et al., 2006): we will refer to this as the declarative framework. The other class of theories suggests that decision-making based on experience is governed by the basic principles of reinforcement learning, in which the value of the outcome of each previous decision incrementally modifies an internal cached value associated with each option (Lee et al., 2012; Niv, 2009); when making a decision, the option with the highest expected value is chosen. We will refer to this as the procedural framework.

Despite making similar predictions about the outcome of decision-making processes (Chelian et al., 2015), these two mechanisms depend on different neural resources. In the *declarative* framework, decisions from experience depend on the brain circuits involved in the storage and retrieval of episodes in long-term memory, such as the medial temporal lobe (Knowlton et al., 1994) the lateral prefrontal cortex (Badre & Wagner, 2007), and the medial frontal and parietal regions associated with the default mode network (Raichle & Snyder, 2007; Sestieri et al., 2011). In the *procedural* framework, decisions from experience rely on brain circuits for implicit reward learning and habit formation, such as the basal ganglia (Foerde et al., 2006), the supplementary motor area (Nieuwenhuis et al., 2004), the cerebellum (Taylor & Ivry, 2014), and the specific sensorimotor regions involved in the task itself (Hill & Schneider, 2006).

Both systems are concurrently active at any given time (Foerde et al., 2006; Poldrack et al., 2001), so, why should individuals choose to rely on one system over the other? One likely explanation is that optimal behavior in humans is inherently limited by

processing capacity (Simon, 1957), therefore individuals must adopt different procedures to maximize the outcome of a decision while consuming the minimum amount of cognitive resources (Gigerenzer, 2008; Payne et al., 1988, 1993). Because the cost of a decision also depends on the neural resources it consumes, individuals with different neural characteristics would make decisions in different ways. This paper puts forward the hypothesis that individuals rely on *declarative* or *procedural* processes based on the relative neural efficiency of their corresponding brain circuits.

A common indicator of neural efficiency within a circuit is their functional resting-state connectivity, that is, the degree of correlation between the spontaneous neural activities of different regions in that circuit (Shen et al., 2017). Higher correlations at rest reflect tighter coupling of neural dynamics and greater exchange and integration of communication between regions (van den Heuvel & Hulshoff Pol, 2010). Thus, relatively higher functional connectivity within the *declarative* or *procedural* circuit should predict greater reliance on the corresponding system when making decisions.

An important obstacle in testing our hypothesis is that the choice between the two systems does not depend solely on their mental and neural costs but also on their relative effectiveness in a given task. For example, it has been argued that the *procedural* system would be preferred when decisions are probabilistic and the stimuli are difficult to verbalize (Frank et al., 2004; Knowlton et al., 1994; Poldrack et al., 2001). If, for some reason, one system is better suited for a given task than the other, an individual preference based on neural efficiency would be overridden by the effectiveness of the alternate system. Investigating the relationship between brain connectivity and preferred decision-making processes requires a task where the *procedural* system is equally as effective as the *declarative* system strategy. One such task is the Incentive Processing Task (IPT: Delgado et al., 2000), which guarantees that either system yields the same

expected payoff. In this task, participants repeatedly guess whether a hidden number is greater or smaller than five by pressing one of two buttons, and receive monetary feedback for correct guesses. Once the choice is made, the number is revealed, and feedback is provided (Figure 1A). Unbeknownst to participants, the number is chosen after their decision is made and follows a predefined feedback schedule. Under these conditions, preferences for either the *declarative* or *procedural* decision-making systems should depend only on the neural costs for each individual participant. Because the number of wins and losses is fixed and predefined, behavioral data from the IPT cannot be analyzed using accuracy measures. Instead, individual behavioral differences can be measured by computing the probability of choosing a different option (i.e., from "win" to "lose" or vice versa) after receiving feedback from the previous trial, referred to as the shift probability. Shift probabilities were computed for the different types of feedback ("win," "lose" or "neutral" when the number is exactly five) and the two different types of experimental blocks that were used in the task ("Mostly Lose," in which 6 loss trials were pseudo-randomly interleaved with either 1 neutral and 1 reward trial, 2 neutral trials, or 2 reward trials, and "Mostly Win", in which 6 reward trials were pseudo-randomly interleaved with either 1 neutral and 1 loss trial, 2 neutral trials, or 2 loss trials). Under these conditions, individual preferences for *declarative* vs. *procedural*-based decision-making should maximally reflect the underlying efficiency of the corresponding circuit.

To test this hypothesis, we analyzed a subset of 200 participants from the Human Connectome Project (Van Essen et al., 2013) for whom neural and behavioral measures from the IPT as well as resting-state fMRI data were available. Figure 1B illustrates the methodology of this study. To determine whether a participant relied on *procedural* or *declarative* mechanisms, each participant's behavior was fitted to two parametrized

computational models, one implementing *declarative* decision-making and one using the

procedural system.

Fig 1. (A) Incentive processing task paradigm. (B) The pipeline of the present study.

First, each subject's behavioral data are fit by two distinct cognitive models, *declarative*

vs. *procedural* model through maximum log-likelihood. Second, each subject's

neuroimaging data are processed to construct resting-state functional connectivity

matrices. Lastly, machine learning models are trained to predict an unseen subject's

decision-making process from the neuroimaging data.

The episodic control model is based on the memory model of Anderson and Schooler (Anderson & Schooler, 1991) and follows the multiple trace theory (Nadel et al., 2000). In this model, the outcome of every decision is stored as an episodic memory. After encoding a memory, without any intervention, that memory starts to be forgotten, and the availability of each memory trace decays according to a power law (Newell & Rosenbloom, 1981). Multiple experiences of the same decision-outcome pair, however, result in the accumulation of traces of the same memory, increasing the *activation* of that memory. Formally, the activation of a memory *m* at time *t* reflects the balance between these two effects, and is given by below equation:

$$A_t(m) = \sum_n \log (t - t_n)^{-d} \tag{1}$$

In this equation, t_n is the time at which the same decision/outcome pair has been experienced for the *n*-th time and *d* is an individual-specific forgetting rate (Sense et al., 2016; Zhou et al., 2021). A decision is guided by the most active memory of past interactions. If the retrieved memory is of a "win" outcome, the model repeats its associated decision, (e.g., choosing "more" if the "win" was associated with a "more" choice). If the memory is of an associated loss, the model executes the *opposite* action (e.g., choosing "less" if the loss was associated with a "more" choice). The probability that a given memory *m* will be retrieved is controlled by a Boltzmann function with noise temperature *v*:

$$P(m) = e^{A(m)/v} / \sum_i e^{A(i)/v} \tag{2}$$

The *procedural* model is based on the reinforcement learning framework (Niv, 2009). In this model, the two possible decisions ("more" or "less") are represented as two actions associated with the cue (in this paradigm, this is the presentation of the two cards). Each action a has an associated value $V(a)$ that is updated over time based on the difference between the expected and the actual outcome (Rescorla et al., 1972) For example, receiving a "win" feedback after making a "more" choice will increase the value of the "more" action, $V(more)$, making it more likely to be selected in future choices, while receiving "loss" feedback will decrease the value of the "more" action, making it less likely to be selected in future choices. Formally, after the n-th decision, the value $V_n(a)$ of an action is updated using the temporal difference method (Sutton, 1988):

$$V_n(a) = V_{n-1}(a) + \alpha[R - V_{n-1}(a)] \tag{3}$$

In Equation 3, R is the reward associated with an outcome, (1 for "win", -0.5 for "lose", corresponding to the dollar amount won by participants), and α is the learning rate. The probability that an action a will be selected is controlled by a Boltzmann function with noise temperature τ:

$$P(a) = e^{V(a)/\tau} / \sum_i e^{V(i)/\tau} \tag{4}$$

Thus, each model depends on one learning parameter (d or α) and one noise parameter (v or τ).

Both models were fit to each participant using maximum likelihood estimation (Myung, 2003), i.e., by fitting their parameters to maximize the probability of generating the specific series of decisions made by that participant (see Methods). Each participant

was then assigned to either the *declarative* or *procedural* group based on which version of the model had the greatest likelihood of producing their observed behavioral data.

Although indistinguishable in most cases, the two models behave differently in the IPT. Because, in the *declarative* model, the availability of a memory grows with the number of times it has been experienced as the task continues, feedback from the most recent decision has less influence on future choices, which are instead affected by the longer history of previous decisions. The *procedural* model, on the other hand, does not maintain a memory of previous choices and adjusts the value of an action after every feedback; thus, it is more sensitive to the most recent outcome. Because of this, we expect that individuals best fitted by the *declarative* model would be less prone to changing their choice preferences immediately after feedback, and thus would exhibit smaller shift probabilities. And because the two mechanisms rely on different neural substrates, we expect that regional differences in BOLD activation would reflect the neural cost associated with each. Therefore, we expect individuals best fitted by *declarative* models to show greater activity in regions associated with episodic encoding, such as the hippocampus, and retrieval, such as the ventral prefrontal cortex and default mode network. Correspondingly, we expect individuals best fit by the *procedural* model to display greater activity in the circuits associated with habit formation, such as the basal ganglia, the cerebellum, and the visuo-motor regions involved in interacting with a computer task. Finally, we expect the type of decision-making processes used to depend on the patterns of functional connectivity at rest. To test this latter prediction, a classifier was trained to predict whether a participant would be best fit by a *declarative* or *procedural* model from the same individual's functional connectivity data. We expect that functional connections that successfully predictict the reliance on the *declarative* mechanism for decision-making would be found between memory encoding and retrieval

regions. Conversely, we expected that functional connections predictive of reliance on the *procedural* mechanism reward-based learning would be found in sensorimotor cortices and the basal ganglia circuit.

Methods

Materials

This study analyzed both behavioral and neuroimaging data obtained from a subset of the Human Connectome Project (HCP) dataset (Van Essen et al., 2013). Data were provided by the Human Connectome Project, WU-Minn Consortium (Principal Investigators: David Van Essen and Kamil Ugurbil; 1U54MH091657) funded by the 16 NIH Institutes and Centers that support the NIH Blueprint for Neuroscience Research and by the McDonnell Center for Systems Neuroscience at Washington University. A total of 199 participants (111 females, 85 males, and 3 did not disclose) who completed both sessions of the task-based fMRI gambling game were included in this study and fit by the two ACT-R models. By excluding 23 participants who missed resting-state fMRI scanning, a total of 176 participants were fit by a predictive LASSO model. All participants were healthy adults with no neurodevelopmental or neuropsychiatric disorders. The experimental protocol, subject recruitment procedures, and consent to share de-identified information were approved by the Institutional Review Board at Washington University.

The Incentive Processing Task in the HCP

This incentive decision-making task was adapted from the gambling paradigm developed by Delgado and colleagues (Delgado et al., 2000). Participants were asked to guess if the number on a mystery card (represented by a "?", and ranging from 1 to 9) was more or less than 5. After making a guess, participants were given feedback, which could take one of three forms, "Win" (a green up arrow and $1), "Loss" (a red down arrow and

-$0.50), or "Neutral" (a gray double-headed arrow and the number 5). The feedback did

not depend on the subject's response, but was determined in advance; the sequence of

pre-defined feedback was identical for all participants. The task was presented in two

runs, each of which contains 32 trials divided into four blocks. Blocks could be "Mostly

Lose" (6 loss trials pseudo-randomly interleaved with either 1 neutral and 1 reward trial,

2 neutral trials, or 2 reward trials) or "Mostly Win" (6 win trials pseudo-randomly

interleaved with either 1 neutral and 1 loss trial, 2 neutral trials, or 2 loss trials). In each

of the two runs, there were two "Mostly Win" and two "Mostly Lose" blocks, interleaved

with 4 fixation blocks (15 seconds each). All participants received money as

compensation for completing the task, and the amount of reward is standard across

subjects.

fMRI Data Processing and Analysis

This study employed the "minimally preprocessed" version of resting-state fMRI

data and incentive processing task fMRI data, which has already undergone a minimal

number of standard preprocessing steps including artifact removal, motion correction,

normalization, and registration to the standard MNI ICBM152 template. Additional

preprocessing steps were performed using the AFNI software (Cox, 1996, 2012),

including despiking, spatial smoothing with an isotropic Gaussian 3D filter FWHM of 8

mm, and removal of linear components related to the six motion parameters and their

first-order derivatives.

Functional connectivity measures were constructed from the HCP resting-state

data using Power et al.'s whole-brain parcellation (Power et al., 2011). This parcellation

was used to construct a 264 Region of Interest (ROI) functional atlas, with each ROI

containing 81 voxels. This parcellation atlas is defined in the MNI space and was applied

to all participants in the HCP dataset. The extraction of the time series and calculation of

the connectivity matrices was performed using R (R Core Team, 2020) and Python. Pearson correlation coefficients and partial correlation coefficients between the time series of each brain region were calculated for each participant, resulting in a 264×264 symmetric connectivity matrix for each session for each subject. The average correlation coefficients across subjects were calculated by first transforming each r value into a Z-value, and then retransforming the average Z value back into an equivalent r value using the hyperbolic tangent transformation (Silver & Dunlap, 1987).

For task-based fMRI data analysis, we specified the first-level analysis model and estimated the parameters corresponding to the difference between "Mostly Win" and "Mostly Lose" blocks, as in (Barch et al., 2013). The resulting contrast maps for each subject were then used in a second-level weighted t-test between-declarative and procedural groups. The test was implemented using AFNI's 3dttest++ software, and its weights corresponded to the absolute difference in log-likelihood between the best-fitting declarative and best-fitting procedural model. This way, the contribution of each observation was proportionally scaled to the evidence favoring each participant's assignment to their groups. The statistical significance level was set at a significance level of $q < 0.01$ corrected for multiple comparisons using a False Discovery Rate (FDR (Benjamini & Hochberg, 1995)) procedure.

Computational Models

Episodic Memory Model

The episodic memory model relies on the declarative model of Anderson and Schooler (Anderson & Schooler, 1991), currently implemented as part of the influential ACT-R cognitive architecture (Anderson, 2009). When presented with a mystery card, the model retrieves a previous episodic memory in which the number was guessed successfully. After being presented with feedback, the model encodes a new memory

associating the action with its outcome. Memories are retrieved based on their activation, a noisy quantity that depends on the frequency and recency with which the decision-outcome episodes have been experienced (Eq. 1).

Procedural Model

By contrast, the procedural model represents the possible actions of the decision-making processes as competing stimulus-response rules, and reinforcement learning is used to increase the use of the rule that leads to the best outcomes. Instead of encoding each trial as a memory of action and associated feedback, the model has two competing actions that implement the "More" and "Less" decisions. When presented with the mystery card, the model chooses one of the rules to execute based on its expected value. Initially, both rules have equal value, and one will be chosen at random. After each decision, the model is presented with a "Win", "Lose", or "Neutral" response, and this feedback is encoded as the reward term in the reinforcement learning equation (Eq. 2) (+1 for a "Win" result, -0.5 for a "Lose" result, and 0 for a "Neutral" result). Positive rewards will encourage the model to repeat the associated action, while a sequence of losses will decrease the value of an action and encourage the selection of the alternate action.

Model Fitting

Model parameters were fit to maximize their likelihoods given the data. The likelihood of a model M with parameters θ given a vector of data $\mathbf{x}$, indicated as $L(M, \theta \mid \mathbf{x})$, is the probability of observing the data, given the model and its parameter, that is $L(M, \theta \mid \mathbf{x}) = P(\mathbf{x} \mid M, \theta)$. The data $\mathbf{x}$ consists of a vector of decisions $x_1, x_2, \ldots, x_N$:

$$L(M, \theta \mid \mathbf{x}) = P(x_1 \mid M, \theta) \cdot P(x_2 \mid M, \theta) \cdot \ldots \cdot P(x_N \mid M, \theta) = \prod_i P(x_i \mid M, \theta)$$

Since the product of conditional probabilities becomes vanishingly small, it is common to use *log*-likelihood:

$$\log L(M, \theta \mid \mathbf{x}) = \log \prod_i P(x_i \mid M, \theta) = \sum_i \log P(x_i \mid M, \theta)$$

Note that, because both models are *memory* models, the probability of decision x_i depends on the *history* of previous decisions $x_{i-1}, x_{i-2}, \ldots, x_1$ and their outcomes, i.e. $P(x_i \mid M, \theta) = P(x_i \mid M, \theta, x_{i-1}, x_{i-2}, \ldots, x_1)$. In both models, the history of previous decisions is implicitly represented in their respective memory representations, that is, the activations of episodic memories and the values of actions. Thus, the probabilities of generating a response x_i can be derived by Equations 2 and 4, provided that the history of previous decisions and outcomes is recorded in the corresponding activations and values.

To do so, each model is run forward, first calculating the probability of producing the participant's response in the current trials; next updating the cumulative log-likelihood; and finally adjusting the activation of episodic traces and the value of the decision based on Equations 1 and 3 before moving to the next trial. For each participant, the model simulates the exact series of 64 trials as they experienced them, in the exact order and with the same inter-trial and inter-block intervals.

In order to evaluate the goodness-of-fit for individual fitting, we estimated maximum Log-Likelihood across the parameter space, i.e. we selected the value of parameters θ^* such that $\theta^* = \text{argmax}_\theta \, L(M, \theta \mid \mathbf{x})$. Because no closed-form solutions exist to derive the maximum likelihood of Equations 1 and 3, the best-fitting parameter values were identified using Powell's optimization algorithm (Powell, 1964) as implemented in Python's SciPy package (Virtanen et al., 2020). This method was chosen because it does not require explicit derivatives and allows us to specify meaningful bounds for parameter

values. All parameters were constrained within the bounds [0, 2]; they are all meaningless

when negative and lead to instability and essentially random choices when > 2.

The starting parameter values for the algorithm were $\alpha = 0.1$, $\tau = 0.1$ for the

procedural model, and $d = 0.5$, $\nu = 0.1$ for the declarative model. The starting values of α

and d were chosen as the most common values found in their respective modeling

frameworks; they are also the default values of the corresponding parameters in ACT-R.

Supervised Classification Model

To explore if individuals' behavioral differences between declarative and

procedural strategies are indicated by an individual's underlying brain structure, we

trained three of the most commonly used supervised classification models (Logistic

regression model, Decision Tree model, and Random Forest model), using resting-state

functional connectivity as the input variable, and predicted the probability of a participant

being labeled as either preferring the declarative or procedural strategy. Considering the

equally high accuracy (> 0.8) among these classification models (Random Forest Model

(accuracy = 0.92) slightly outperformed the other two models), we are confident to say

that our Machine Learning models work very well in predicting the strategy selection

from an individual's resting state neuroimaging data.

In addition to the predictive power of machine learning models, another very

important dimension we need to carefully consider in Machine Learning related research

is the model's interpretability. While some ML models are excellent at predicting

outcome variables, as complexity grows exponentially (as in Deep neural networks), they

become a black box that is fundamentally difficult to interpret. Therefore, choosing an

appropriate ML model with reasonable predictability and interpretability is critical. We

chose the logistic regression model because it is a simple and powerful binary

classification model that has been widely used in many fields of research. It could be used

to predict the likelihood of an event happening or a choice being made. Rather than fitting data as a straight line, the logistic regression model uses the logistic function to constrain a value between 0 and 1. Specifically, the output value x of a linear model is transformed into a corresponding probability $P(x)$ by the function:

$$P(x) = 1/(1 + e^{-x})$$

In order to handle an imbalanced dataset with unequal target labels, upsampling was applied by randomly adding data from the minority class. We also applied individualized weights to each training sample, which is the absolute difference of maximum log-likelihood between two models. Specifically, for subjects who are better distinguished by either of the two models (declarative vs. procedural), we increased the weights of these data points in later ML model training, while for those who had a very close fit maximum log-likelihood between two models, the training procedure was less reliant on these samples. Having 69,696 (264 ROI $\times$ 264 ROI) connections, we want to select only the most important connections contributing to the prediction, therefore, LASSO regularization was applied to the Logistic Model. LASSO is a machine learning regression analysis technique that performs both variable selection and regularization in order to improve the prediction accuracy and interpretability of the computational model. It can reduce model complexity by penalizing large numbers of coefficients and also prevents overfitting which may result from a simple linear regression analysis. In LASSO, the best values associated with each regressor are chosen as to minimize a loss function that includes the ordinary squared errors as well as a penalty term for each regressor's β weight:

$$Loss = (y - \hat{y})^2 + \lambda \sum_{i}^{n} |\beta_i|$$

where the tuning parameter λ controls the degree of penalty: for greater values of λ, more coefficients are forced to become 0.

To account for the large disparity between the number of participants and the number of predictors, we performed a grid search cross-validation using the *glmnet* package in R (Friedman et al., 2010) to determine the best value for the fit hyper-parameter $\lambda_{regular}$. To alleviate the potential problems of small sample size in neuroimaging studies, Vabalas and colleagues (Vabalas et al., 2019) used Nested CV approaches to produce robust and unbiased model performance regardless of sample size. Following their suggestions, we fit the model with *n*-iteration nested cross-validation (*n* = 200) to determine the optimal hyperparameter λ. For each iteration, the dataset was randomly split into training and testing (the ratio of training to testing is 1:4). Instead of adopting a computationally expensive Leave-One-Out (LOO) method, we adopted the *k*-folds cross-validation (*k* = 20) method. The whole dataset was randomly split into 20 folds and trained on 19 folds of samples. The prediction was made on the remaining one fold of samples to obtain the best hyperparameter value λ_k, which gave the lowest classification error. With each best lambda λ_k, the model was restrained and made predictions on testing datasets. Then the process was repeated k times. To guarantee maximum generalizability, we chose the median of lambdas (λ_{nested}). This approach allowed us to obtain a reliable and unbiased assessment of the LASSO model's performance while accounting for the variability in the data and the selection of hyperparameters.

The mean accuracy score, true positive rate (TPR), true negative rate (TNR), false positive rate (FPR), and false negative rate (FNR) were calculated across all folds to

evaluate the overall performance of the model, taking sample weights into account. By definition, the receiver operating characteristic curve (ROC) demonstrates the performance of a classification model by plotting the relationship between TPR vs. FPR at different classification thresholds.As a measure of the model's overall accuracy, we calculated the AUC (Area under the curve), which is one of the most important metrics for evaluating a classification model's performance; as the AUC of a model approaches 1, the model approximates an ideal, perfect classifier.

Results

Reliability of Model Identification

Because our results depend on correctly identifying the model that best represents each participant, a model recovery procedure (Wilson & Collins, 2019) was run to ensure that our identification process was reliable. In this procedure, simulated participant data was generated by instantiating a model with random parameter values (uniformly drawn within their plausible boundaries; see Methods); the model-fitting procedure was then applied, treating the simulated data as participant data, and the accuracy to which the original model could be correctly identified was recorded (see Methods). Figure 2 provides the confusion matrix for the results of the procedure.

For both models, the recovery rate is approximately 85%. To account for errors in model assignment, in all of the following analyses, observations from a given participant are weighted by the difference in log-likelihood between the fit of the two models – that is, the stronger the evidence is in favor of one model, the greater the weight associated with the corresponding observation.

Fig 2. Confusion matrix showing the probability of correct model identification from 40,000 simulated runs. See Methods for details.

A second analysis was carried out to test whether each model's *parameters* (i.e., d and nu for the declarative model and alpha and tau for the procedural one) could also be correctly identified. This was done to make sure that any inferences about individual differences in the relative efficiency of the two systems could be grounded on reliable differences in parameters. Figure 3 illustrates the results of these simulations. All four parameters could be correctly identified from the simulated data, with correlations ranging from $r = 0.68$ (procedural temperature T, $p < 0.001$) to $r = 0.88$ (procedural learning rate alpha, $p < 0.001$).

Fig 3. Results of the parameter recovery analysis for the individual parameters of the procedural (blue, top row) and the declarative (red, bottom row) models from 40,000 simulated runs. See Methods for details.

Decision-Making Process Identification

Having examined the reliability of the models, we then proceeded with categorizing participants based on which model fit them best. A total of 199 participants were fit by the two models. Of these, 35 (17%) were best fit by the declarative model and thus were included in the declarative group.

The remaining 164 individuals were best fit by the procedural model and included in the procedural group. Figure 4 illustrates the distributions of the log-likelihood differences (Procedural - Declarative) across participants. Individuals for which the difference was < 0 were categorized as procedural, and those whose difference was > 0 were categorized as declarative.

In agreement with our hypothesis that individuals would preferentially perform the task using one of two mechanisms, the distribution of log-likelihoods is bimodal; that is, it has two peaks that likely correspond to the clusters of individuals best fit by the declarative and the procedural model. Note, however, that the leftmost peak is centered slightly to the right of the zero. This could be explained by the declarative model having inherently more difficulty fitting the data; this could happen, for example, if its equations do not capture the computations of human memory as well as the procedural model captures human reinforcement learning.

One possible solution to this problem would be to choose a decision criterion situated between the two peaks. In this study, we followed the alternative solution to keep the theoretically-motivated threshold point at zero, but to run all of the following analysis by weighting the contribution of each participant in proportion to the log-likelihood of their model identification. This second solution offers the advantage of maintaining a theoretically motivated criterion (that is, $\log L = 0$) while also automatically accounting for the uncertainty in identifying certain participants (those whose $\log L$ values hover around zero).

Fig 4. The distributions of the log-likelihood differences (Procedural - Declarative) across participants. As expected, the distribution is bimodal. Red bars represent the count of participants who are best fit by the procedural model, whereas blue bars represent the count of participants who are best fit by the declarative model.

Stability of Model Identification

Finally, we conducted a follow-up analysis to examine whether the process of model identification would be consistent over the course of the study. Of all 199 participants, 145 (72.9%) were best fit by the same model on both runs. These results suggest that the identification procedure is robust and that a participant's tendency to

make decisions in a procedural vs. declarative pattern is stable and does not flucuate over the duration of an experiment.

Group Differences In Behavioral Responses During The Task

Our prediction is that, because of the different dynamics in the two models, individuals best fitted by the procedural model would exhibit greater sensitivity to trial feedback and a greater probability of switching from their previous decision than individuals best fitted by the declarative model. To test this prediction, a dummy variable was created to code each trial after the very first as either a response switch (1) or not (0). The effect of the previous trial feedback on the probability of a response switch was then analyzed using a logistic mixed-effects model implemented in the lme4 package in R (Bates et al., 2015). In the model, Group (declarative vs. procedural) and Feedback (Win vs. Loss vs. Neutral) were treated as fixed effects, and individual subjects were treated as random effects, as shown in Figure 5.

Fig 5. Main behavioral differences between participants best fit by procedural (blue) or declarative models (red). Left: the procedural group shows a greater tendency to change responses after and neural and a "win" feedback. Right: the declarative group shows a greater tendency to repeat the same choice within a block.

As expected, we found a significant main effect of model ($\beta = 0.87$, $t = 2.21$, $p < 0.02$), a significant main effect of trial when the feedback was a loss ($\beta = 1.13$, $t = 2.92$, $p = 0.003$), and a significant interaction between the two factors ($\beta = -0.95$, $t = -2.44$, $p = 0.01$). In summary, participants in the procedural group showed a significantly greater probability of shifting their behavior than participants in the declarative group, and, although both groups were more likely to change their responses after a "loss" than a "win", this difference was magnified in the declarative group (Figure 5, left). This finding

was consistent with our understanding of the memory retrieval process, with the declarative system becoming less sensitive over time to individual items of feedback in relation to the accumulation of historical decision/outcome pairs.

We also reasoned that the declarative group would exhibit longer streaks of identical choices than the procedural group. Furthermore, since both models are more likely to change their responses after a "loss" than a "win", we expected that for both models the persistence would be larger in the "Mostly Win" blocks. To test these predictions, the maximum number of consecutive identical choices was computed for each block and individual, and the data were analyzed with a linear mixed model implemented in the *glmer* package in R. In the model, the persistence variable was modeled with a Poisson distribution, and both Block ("Mostly Lose" vs. "Mostly Win") and Model (declarative vs. procedural) were included as fixed-effects. Because, in this analysis, there is only one observation per participant, no random effect was included. The results showed a significant main effect of both block (blocks: $\beta = 0.25$, $t = 5.56$, $p < 0.0001$) and group ($\beta -0.70$, $t = -19.64$, $p < 0.0001$), as well as their interaction ($\beta = -0.13$, $t = -2.78$, $p = 0.005$). As expected, the declarative group had higher persistence than the procedural group and this effect was magnified in the "Mostly Win" block (Figure 5, right).

Group Differences in Brain Activity During the Task

In addition to finding significant behavioral differences between two groups of participants, we also found relevant and consistent differences in their task-based fMRI data. In line with previous studies using the same dataset (26), our investigation focused on the difference in brain activity between "Mostly Win" and "Mostly Lose" blocks. This contrast is particularly important in this analysis, since participants are more likely to

keep engaging their preferred decision-making system during "Mostly Win" blocks (as implied by Figure 5, right).

A *t*-test was performed to identify brain regions more active in one group over the other. The test was weighted using the relative log-likelihood of each participant's being fitted by either of the two models, so that participants who had a stronger preference for one process were weighted more heavily (See Materials and Methods). The False Discovery Rate (Benjamini & Hochberg, 1995) procedure was used to correct for multiple comparisons at a level of $q < 0.01$. The analysis identified several brain regions that show significant BOLD signal differences between the procedural and declarative groups (Figure 6; Table 1). Specifically, participants in the procedural group (Figure 6, blue) showed greater task activation in the primary (inferior and superior occipital cortex and lingual gyrus) and secondary (left and right inferior temporal cortex) visual regions, and in the primary (M1) and secondary (supplementary motor area) motor regions, together with greater task activation in the bilateral insula. This pattern of activation is consistent with the acquisition of habitual stimulus-response associations.

On the other hand, participants in the declarative group (Figure 6, red) showed greater brain activity in the canonical nodes of the default mode network (the bilateral medial frontal cortex, the bilateral precuneus, and the bilateral inferior parietal lobules) as well as regions involved in the encoding (right hippocampus, left anterior temporal lobe), and the retrieval (left and right lateral ventral prefrontal cortex) of declarative memories.

Fig 6. Differences between procedural and declarative participants during the incentive processing task. In the overlays, the color indicates the direction of the difference (blue: Procedural > Declarative; Red: Declarative > Procedural) and color intensity indicates the magnitude of the associated T statistics. Regions are thresholded at a significance level of at $q < 0.01$, corresponding to a voxel-wise threshold of $T >= 2.70$.

Table 1: Results from the task fMRI comparison. For clarity, only clusters spanning > 50 voxels and locations spanning > 1% of the cluster and > 10 voxels within the cluster are shown. L = Left, R = Right; the word "gyrus" is omitted from the location names.

Contrast	MNI (Peak)	Automated Anatomical Labeling (AAL) Locations	Size (voxels)	Peak T value
Procedural > Declarative	22, -82, -48	R Cerebellum (4.44%); L Cerebellum (5.22%); R Fusiform (3.15%); L Calcarine (2.99%); R Calcarine (2.94%); R Lingual (2.76%); L Middle Occipital (2.64%); R Middle Temporal (2.14%); Left Fusiform (2.12%); L Lingual (1.62%); R Inferior Frontal (1.35%); R Inferior Temporal (1.27%); R Middle Occipital (1.21%); R Hippocampus (1.13%); L Inferior Occipital (1.12%); L Inferior Temporal (1.01%)	30,662	14.09
	62, -26, 46	R Postcentral (34.73%); R Supramarginal (34.27%); R Inferior Parietal(17.60%); R Rolandic (11.89%)	858	7.48
	-14, -34, 58	L Paracentral (43.00%); L Postcentral (6.11%); L Precuneus (4.07%); L Precental (1.53%)	393	5.55
	-22, 4, 48	L Superior Frontal (36.72%); L Middle Frontal (35.94%); L Supplementary Motor Area (3.52%)	256	4.41
	-10, 36, 42	L Superior Frontal (90.04%); ; L Middle Frontal (2.90%)	241	5.23
	36, 14, 60	R Middle Frontal (96.94%);	196	6.75
	12, 24, 20	R Anterior Cingulate (57.05%);	149	5.49
	-6, 18, 26	L Anterior Cingulate (40.74%); L Median Cingulate (10.37%	135	4.9
	-40, 16, -4	L Insula (92.06%)	126	5.1
	10, -22, 66	R Paracentral (43.93%); R Supplementary Motor Area (29.91%); R Precental (26.17%)	107	4.73
	-24, 68, 16	L Middle Frontal (24.14%); L Superior Frontal (18.39%)	87	4.61
	-40, -8, 52	L Precental (91.89%)	74	4.15

	28, 62, 24	R Middle Frontal (56.16%); R Superior Frontal (39.73%)	73	5.47
	-32, 0, 2	L Putamen (56.72%)	67	4.33
Declarative > Procedural	-4, 66, -2	L Superior Frontal (7.26%); L Superior Temporal (3.29%); L Middle Temporal (3.25%); R Superior Frontal (5.56%); L Precuneus (2.12%); L Middle Frontal (2.12%); L Postcentral (2.00%); L Inferior Temporal gyrus (2.74%); L Inferior Frontal part (1.58%); L Angular (1.54%); L Rolandic (1.47%); L Anterior Cingulate (1.43%); L Supramarginal (1.35%); L Caudate (1.35%); R Median Cingulate (1.27%); R Superior Temporal (1.24%); L Precental (1.17%); L Medial Frontal Cortex (1.13%); R Insula (1.10%); L Insula (1.06%); R Anterior Cingulate (1.05%); R Supplementary Motor Area (1.04%); L Temporal Pole (1.03%); L Supplementary Motor Area (1.01%); R Precuneus (0.99%)	38,651	-15.92
	22, -44, -54	R Cerebellum (86.87%)	545	-15.02
	22, -24, -26	R Parahippocampal (26.42%); R Cerebellum (33.97%); R Fusiform (18.24%)	159	-12.17
	64, -4, 32	R Inferior Frontal (38.31%); R Postcentral (31.17%); R Precental (30.52%);	154	-9.32
	40, 0, -44	R Inferior Temporal (89.47%); R Temporal Pole (6.58%)	152	-7.13
	2, -88, -16	L Calcarine (25.49%); L Lingual (17.65%); L Crus (7.84%);	102	-8.99
	6, -20, 76	R Paracentral Lobule (59.60%); R Supplementary Motor Area (12.12%);	99	-7.52
	52, -38, 56	R Postcentral (89.53%)	86	-8.25
	0, -4, 32	R Median Cingulate (52.56%); L Median Cingulate (39.74%)	78	-4.21
	-42, 20, 50	L Middle Frontal (98.68%)	76	-6
	14, -26, -8	R Lingual (15.71%); R Hippocampus (8.57%);	70	-4.72
	40, 24, -26	R Temporal Pole (98.33%);	60	-5.2

Predicting Individual Differences in Decision-Making Processes Through Functional Connectivity

Functional connectivity data consisted of pairwise partial correlation matrices between each pair of the 264 regions in the Power parcellation scheme (Power et al., 2011). To identify which functional connectivity features predict whether a participant would belong to the declarative or procedural group, we used a logistic Least Absolute Shrinkage and Selection Operator (LASSO: (Tibshirani, 1996)) regression model, which reduces a large number of potential predictors while retaining the most predictive features. The LASSO model was implemented using the *glmnet* package in R (Friedman et al., 2010). To ensure generalization, we chose the optimal LASSO hyperparameter λ_{nested} (0.0059) using a nested cross-validation method (See Supplementary Materials). Having the optimal λ_{nested}, we refit the LASSO model using the Leave-One-Out (LOO) cross-validation approach and obtained the correlation coefficient betas (β) for subsequent brain connectivity analysis.

The prediction performance was evaluated by regular LOO cross-validation and nested cross-validation approaches. The training and testing accuracy with regular cross-validation and nested cross-validation approaches are shown in Table 2. These results indicate that the LASSO model was successful at predicting an individual's preferred decision-making process (declarative or procedural) from resting-state brain functional connectivity.

Table 2. Summary of the LASSO Model Performance

	Best λ	Testing AUC	Number of Non-Zero β parameters
Regular CV	0.0027	1.000	92
Nested CV	0.0059	0.911	91

Finally, we examined which functional connectivity features were predictive of individual preferences in decision making. After LASSO regularization, 92 functional connections (approximately 0.11% of the total) had non-zero β parameters, suggesting a very sparse neurofunctional connectivity. Fig 7 shows the non-zero β weights of connection between networks and within networks as extracted from the fit LASSO model. Since the ultimate effect of a β parameter on the predicted group assignment depends on the polarity of the underlying functional connectivity, a positive β value has different implications if applied to a positive or negative partial correlation between two regions. Consider, for example, a connectivity value associated with a positive β value: if the underlying connectivity is positive ($r > 0$), then the degree of functional connectivity can be taken as a vote in favor of the declarative system. If, on the other hand, the underlying connectivity value is negative ($r < 0$), then it should be counted as a vote for the procedural system.

To make the interpretation of the values unambiguous, we examined the corrected weight matrix by multiplying the β matrix with the sign of the functional connectivity matrix, obtaining a corrected weight correlation matrix W. The weight matrix W can now be interpreted unambiguously, since $W > 0$ predicts reliance on a declarative process and $W < 0$ predicts reliance on a procedural process. Fig 7A shows these different functional connections.

Connections predictive of declarative processes involve clearly different networks than connections predictive of procedural processes, as shown in Fig 7(B) and Fig 7(C).

As expected, reliance on declarative processes in decision-making was predicted by greater connectivity in the networks of regions associated with task control (task control networks and subcortical networks) as well as episodic memory (memory retrieval networks). Reliance on procedural learning processes, however, was predicted by greater connectivity in sensorimotor and salience regions. As Figures 7(B) and 7(C) show, the predictive functional connectivity also largely overlaps with the task-fMRI results, indicating that greater functional connectivity between two regions at rest predicts a greater likelihood that these two regions would be used to support the decision-making processes during the task.

Fig 7. The distribution of predictive connections in declarative and procedural functional networks. (A) Predictive Connectom across the Power parcellation networks. Red connections denote positive weight values ($W > 0$), predicting the procedural Group, and Blue connections denote negative weights values ($W < 0$), predicting the procedural Group. (B) The anatomical location of the function connection is predictive of declarative group assignment; nodes represent regions, node colors indicate the network they belong to; node size indicates the degree of connectivity (the number of adjacent edges), , and line width indicates the strength of connectivity between two nodes. (C) Anatomical location of the functional connections predictive of procedural group assignment.

Discussion

This study shows that individuals rely on different mechanisms when deciding from experience, and that this preference is adaptive and reflects individual differences in the functional connectivity between each process' corresponding circuitry. Specifically, individuals exhibiting stronger connectivity between and within frontoparietal and memory retrieval regions tend to use declarative strategies that are more reliant on episodic encoding and retrieval, while individuals with stronger connectivity in cingulate, sensory, and basal ganglia regions tend to rely on habitual actions and reinforcement learning. An individual's preference can, in fact, successfully be predicted from their underlying functional connectivity.

Although our results shed new light on the neural bases of experiential decision-making, a number of limitations must be acknowledged. First, participants were assigned to the declarative or procedural group based on the log-likelihood of a corresponding cognitive model. Because no other ground-truth labels were available, these classifications should be interpreted with caution. Another limitation is that the incentive processing task differs from most decision-making paradigms, as there is no winning rule for participants to learn from the feedback. Thus, although this task was particularly well suited for the current study, more work is needed to determine whether these findings would translate to more realistic situations.

In addition, our study assumes that greater functional connectivity reflects greater efficiency. While much experimental evidence points to this, the mechanisms by which connectivity translates to computational efficiency are not clear. One proposed solution is that connectivity reflects communication efficiency across regions. If so, connectivity should correspond to decision-making noise in our models. In fact, a follow-up analysis of individual model parameters shows that individual preferences for one process over the

other largely follow differences in the estimated noise parameter. That is, individuals whose estimated procedural noise was larger than the estimated declarative noise were significantly more likely to be fit by the declarative model, and vice-versa (Welch Two Sample *T*-test: $t(50.04) = 3.37$, $p = 0.001$, see Figure 8).

Fig 8. Differences in the estimated procedural and declarative temperature parameters τ and ν between the two groups. Individuals best fit by the procedural model had higher declarative temperature than individuals best fit by the declarative model, and vice-versa.

Although we have found evidence that individuals prefer to implement decision-making processes using the circuits that show the greatest connectivity, our analysis does not directly support a causal direction. To conclusively show a direct causal

effect, it would be necessary to experimentally alter functional connectivity within the declarative and procedural circuits and measure subsequent changes in behavior in the same task. Such an experimental intervention is difficult to carry out in humans, although it is in principle conceivable to use pharmacological interventions that directly target one circuit or intracranial direct stimulation of these circuits in patients with implanted electrodes or ECoG grids.

Finally, our study still does not directly address the source of differences in functional connectivity. Two hypotheses are possible. In principle, these differences could reflect underlying genetic or structural differences in brain function. Alternatively, it is possible that differences in functional connectivity simply reflect one's past history of relying on one particular process (and its underlying circuit) over the other. In this case, individuals might have a preference (let's say, for the declarative system), and repeated use leads to corresponding increases in functional connectivity (let's say, in the memory retrieval network). The two explanations might be intertwined, i.e., small initial differences in the efficiency of these circuits might lead to greater use of one process over the other, and practice over time might result in additional gains in efficiency.

Further investigation is needed to fully untangle these questions, but these results nevertheless represent a promising step forward in directly connecting the mechanical underpinnings of brain circuitry with observed human behavior in decision-making.

Data Availability Statement

All of the data and code are available in the OSF repository: https://osf.io/wf4my/

References

Anderson, J. R. (2009). *How Can the Human Mind Occur in the Physical Universe?*
Oxford University Press.

Anderson, J. R., & Schooler, L. J. (1991). Reflections of the Environment in Memory.
Psychological Science, *2*(6), 396–408.

Badre, D., & Wagner, A. D. (2007). Left ventrolateral prefrontal cortex and the cognitive
control of memory. *Neuropsychologia*, *45*(13), 2883–2901.

Barch, D. M., Burgess, G. C., Harms, M. P., Petersen, S. E., Schlaggar, B. L., Corbetta,
M., Glasser, M. F., Curtiss, S., Dixit, S., Feldt, C., Nolan, D., Bryant, E., Hartley, T.,
Footer, O., Bjork, J. M., Poldrack, R., Smith, S., Johansen-Berg, H., Snyder, A. Z., …
WU-Minn HCP Consortium. (2013). Function in the human connectome: task-fMRI
and individual differences in behavior. *NeuroImage*, *80*, 169–189.

Bates, D., Mächler, M., Bolker, B., & Walker, S. (2015). Fitting Linear Mixed-Effects
Models Using lme4. *Journal of Statistical Software*, *67*, 1–48.

Benjamini, Y., & Hochberg, Y. (1995). Controlling the False Discovery Rate: A Practical
and Powerful Approach to Multiple Testing. *Journal of the Royal Statistical Society.
Series B, Statistical Methodology*, *57*(1), 289–300.

Chelian, S. E., Paik, J., Pirolli, P., Lebiere, C., & Bhattacharyya, R. (2015).
Reinforcement learning and instance-based learning approaches to modeling human
decision making in a prognostic foraging task. *2015 Joint IEEE International
Conference on Development and Learning and Epigenetic Robotics (ICDL-EpiRob)*,
116–122.

Cox, R. W. (1996). AFNI: software for analysis and visualization of functional magnetic
resonance neuroimages. *Computers and Biomedical Research, an International
Journal*, *29*(3), 162–173.

Cox, R. W. (2012). AFNI: what a long strange trip it's been. *NeuroImage*, *62*(2), 743–747.

Delgado, M. R., Nystrom, L. E., Fissell, C., Noll, D. C., & Fiez, J. A. (2000). Tracking the hemodynamic responses to reward and punishment in the striatum. *Journal of Neurophysiology*, *84*(6), 3072–3077.

Foerde, K., Knowlton, B. J., & Poldrack, R. A. (2006). Modulation of competing memory systems by distraction. *Proceedings of the National Academy of Sciences*, *103*(31), 11778–11783.

Frank, M. J., Seeberger, L. C., & O'reilly, R. C. (2004). By carrot or by stick: cognitive reinforcement learning in parkinsonism. *Science*, *306*(5703), 1940–1943.

Friedman, J., Hastie, T., & Tibshirani, R. (2010). Regularization Paths for Generalized Linear Models via Coordinate Descent. *Journal of Statistical Software*, *33*(1), 1–22.

Gigerenzer, G. (2008). Why Heuristics Work. *Perspectives on Psychological Science: A Journal of the Association for Psychological Science*, *3*(1), 20–29.

Gonzalez, C., & Dutt, V. (2011). Instance-based learning: integrating sampling and repeated decisions from experience. *Psychological Review*, *118*(4), 523–551.

Hill, N. M., & Schneider, W. (2006). Brain changes in the development of expertise: Neuroanatomical and neurophysiological evidence about skill-based adaptations. *The Cambridge Handbook of Expertise and Expert Performance*, 653–682.

Knowlton, B. J., Squire, L. R., & Gluck, M. A. (1994). Probabilistic classification learning in amnesia. *Learning & Memory* , *1*(2), 106–120.

Lee, D., Seo, H., & Jung, M. W. (2012). Neural basis of reinforcement learning and decision making. *Annual Review of Neuroscience*, *35*, 287–308.

Myung, I. J. (2003). Tutorial on maximum likelihood estimation. *Journal of Mathematical Psychology*, *47*(1), 90–100.

Nadel, L., Samsonovich, A., Ryan, L., & Moscovitch, M. (2000). Multiple trace theory of human memory: computational, neuroimaging, and neuropsychological results. *Hippocampus*, *10*(4), 352–368.

Newell, & Rosenbloom. (1981). Mechanisms of skill acquisition. *Cognitive Skills and Their Acquisition*. https://books.google.com/books?hl=en&lr=&id=7oEtr1KvMbgC&oi=fnd&pg=PA1 &dq=+practice++newell+rosenbloom+1981&ots=1Nb-lfK7Zn&sig=gQdE9Ifcd1i0J Be6E8MABdrZmTU

Nieuwenhuis, S., Holroyd, C. B., Mol, N., & Coles, M. G. H. (2004). Reinforcement-related brain potentials from medial frontal cortex: origins and functional significance. *Neuroscience and Biobehavioral Reviews*, *28*(4), 441–448.

Niv, Y. (2009). Reinforcement learning in the brain. *Journal of Mathematical Psychology*, *53*(3), 139–154.

Payne, J. W., Bettman, J. R., & Johnson, E. J. (1988). Adaptive strategy selection in decision making. *Journal of Experimental Psychology. Learning, Memory, and Cognition*, *14*(3), 534–552.

Payne, J. W., Payne, J. W., Bettman, J. R., & Johnson, E. J. (1993). *The Adaptive Decision Maker*. Cambridge University Press.

Poldrack, R. A., Clark, J., Paré-Blagoev, E. J., Shohamy, D., Creso Moyano, J., Myers, C., & Gluck, M. A. (2001). Interactive memory systems in the human brain. *Nature*, *414*(6863), 546–550.

Powell, M. J. D. (1964). An efficient method for finding the minimum of a function of several variables without calculating derivatives. *Computer Journal*, *7*(2), 155–162.

Power, J. D., Cohen, A. L., Nelson, S. M., Wig, G. S., Barnes, K. A., Church, J. A., Vogel, A. C., Laumann, T. O., Miezin, F. M., Schlaggar, B. L., & Petersen, S. E.

(2011). Functional network organization of the human brain. *Neuron*, *72*(4), 665–678.

Raichle, M. E., & Snyder, A. Z. (2007). A default mode of brain function: a brief history of an evolving idea. *NeuroImage*, *37*(4), 1083–1090; discussion 1097–1099.

R Core Team. (2020). *R: A Language and Environment for Statistical Computing*. R Foundation for Statistical Computing. https://www.R-project.org/

Rescorla, R. A., Wagner, A. R., & Others. (1972). A theory of Pavlovian conditioning: Variations in the effectiveness of reinforcement and nonreinforcement. *Classical Conditioning II: Current Research and Theory*, *2*, 64–99.

Sense, F., Behrens, F., Meijer, R. R., & van Rijn, H. (2016). An individual's rate of forgetting is stable over time but differs across materials. *Topics in Cognitive Science*, *8*(1), 305–321.

Sestieri, C., Corbetta, M., Romani, G. L., & Shulman, G. L. (2011). Episodic memory retrieval, parietal cortex, and the default mode network: functional and topographic analyses. *The Journal of Neuroscience: The Official Journal of the Society for Neuroscience*, *31*(12), 4407–4420.

Shen, X., Finn, E. S., Scheinost, D., Rosenberg, M. D., Chun, M. M., Papademetris, X., & Constable, R. T. (2017). Using connectome-based predictive modeling to predict individual behavior from brain connectivity. *Nature Protocols*, *12*(3), 506–518.

Silver, N. C., & Dunlap, W. P. (1987). Averaging correlation coefficients: Should Fisher's z transformation be used? *The Journal of Applied Psychology*, *72*(1), 146–148.

Simon, H. A. (1957). A behavioral model of rational choice. *Models of Man, Social and Rational: Mathematical Essays on Rational Human Behavior in a Social Setting*, 241–260.

Stewart, N., Chater, N., & Brown, G. D. A. (2006). Decision by sampling. *Cognitive*

Psychology, *53*(1), 1–26.

Sutton, R. S. (1988). Learning to predict by the methods of temporal differences. *Machine Learning*, *3*(1), 9–44.

Taylor, J. A., & Ivry, R. B. (2014). Cerebellar and prefrontal cortex contributions to adaptation, strategies, and reinforcement learning. *Progress in Brain Research*, *210*, 217–253.

Tibshirani, R. (1996). Regression shrinkage and selection via the lasso. *Journal of the Royal Statistical Society*, *58*(1), 267–288.

Vabalas, A., Gowen, E., Poliakoff, E., & Casson, A. J. (2019). Machine learning algorithm validation with a limited sample size. *PloS One*, *14*(11), e0224365.

van den Heuvel, M. P., & Hulshoff Pol, H. E. (2010). Exploring the brain network: a review on resting-state fMRI functional connectivity. *European Neuropsychopharmacology: The Journal of the European College of Neuropsychopharmacology*, *20*(8), 519–534.

Van Essen, D. C., Smith, S. M., Barch, D. M., Behrens, T. E. J., Yacoub, E., Ugurbil, K., & WU-Minn HCP Consortium. (2013). The WU-Minn Human Connectome Project: an overview. *NeuroImage*, *80*, 62–79.

Virtanen, P., Gommers, R., Oliphant, T. E., & Haberland, M. (2020). SciPy 1.0: fundamental algorithms for scientific computing in Python. *Nature*.

Wilson, R. C., & Collins, A. G. (2019). Ten simple rules for the computational modeling of behavioral data. *eLife*, *8*. https://doi.org/10.7554/eLife.49547

Zhou, P., Sense, F., van Rijn, H., & Stocco, A. (2021). Reflections of idiographic long-term memory characteristics in resting-state neuroimaging data. *Cognition*, *212*, 104660.