What humans learn from corrective feedback for perceptual decision-making

Hyang-Jung Lee[1], Heeseung Lee[1], Chae Young Lim[2], Issac Rhim[3], and Sang-Hun Lee[1*]

[1]Department of Brain and Cognitive Sciences, Seoul National University, Seoul, South Korea
[2]Department of Statistics, Seoul National University, Seoul, South Korea
[3]Institute of Neuroscience, University of Oregon, Eugene, OR, U.S.A

*To whom correspondence should be addressed (visionsl@snu.ac.kr)

January 11st, 2023

Abstract

Corrective feedback is vital to learning about the environment, exerting its influence on subsequent episodes of perceptual decision-making (PDM) on a trial-to-trial basis. However, its intricate interplay with other history factors in PDM challenges a principled account of the history effects of feedback. One popular account, grounded in animal behavior and extended to human behavior, grafted the principle proven successful in reward-based decision-making— reinforcement-learning—onto the PDM processes. It assumes that decision-makers, although engaged in PDM, treat feedback as *rewards* from which they learn *choice values*. Here we report that human decision-makers do not conform to this assumption. Instead, humans acted like treating feedback as *evidence* for a specific world state and combining it with sensory evidence to learn the *statistical structure* crucial to perform a PDM task. A Bayesian implementation of our account reproduces human history effects, both retrospectively and prospectively, with an unprecedented level of correspondence and finesse.

Keywords

Feedback, History effects, Reinforcement learning, Perceptual decision-making, Bayesian inference, Binary classification

Introduction

PDM means committing to a proposition about an objective world state (e.g., 'this tree is tall'). Decision-makers adjust future commitments based on what they experienced from past commitments, including what they perceived, what they chose, and what the environment gave them as a return. Among these *history factors*, *trial-to-trial corrective feedback*—feedback about the correctness of a decision maker's choices on a trial-to-trial basis—is widely used by experimenters to train subjects on PDM tasks. Despite this clear utility of feedback and a pile of evidence for its impact on subsequent PDM behavior across species and across sensory modalities[1–10], much remains elusive about how corrective feedback, in conjunction with other history factors, exerts its trial-to-trial effects on subsequent decisions.

Unlike PDM, value-based decision-making (VDM) involves making choices based on decision makers' subjective preferences (e.g., 'choosing between two drinks based on their tastes'). The reinforcement learning (RL) algorithm has been offering successful accounts of how past rewards affect subsequent VDM based on error-driven incremental mechanisms[11–15]. Intriguingly, there have been attempts to explain the impacts of feedback on PDM by grafting the RL algorithm onto the PDM processes[3,4,8–10]. This grafting premises that decision-makers treat corrective feedback in PDM as reward feedback in VDM. On this premise, decision-makers would update the choice *values* based on reward prediction errors (red dashed arrows in Fig. 1a). Suppose a decision-maker committed to a proposition, 'this mountain is large.' Then, *correct* and *incorrect* feedback to that commitment increases and decreases, respectively, the value of the 'large' choice. This RL-grafting account, which will be referred to as *value-updating scenario* hereinafter, appears natural given that corrective feedback was typically provided as physical rewards such as juice or water in animal PDM experiments[4,5,8–10,16–18]. The value-updating scenario seems plausible from the perspective that PDM and VDM might share common mechanisms[19], as suggested by some empirical studies[20,21].

Nevertheless, value-updating might not be the only route through which feedback effects transpire in PDM, especially for humans receiving corrective feedback without any physical rewards. Alternatively, decision-makers may treat feedback, not as rewards, but as a logical indicator of whether the proposition to which they committed is true or false in the world. For example, *correct* and *incorrect* feedback to 'this tree is tall' indicate that its height is greater and smaller, respectively, than the average tree height of the wood of interest. Thus, in this

alternative scenario, feedback allows decision-makers to learn the world statistics pertinent to a given PDM task (green dashed arrows in Fig. 1a). We will call this *world-updating scenario*. This scenario is conceptually parsimonious in that it does not require any components outside the PDM processes, such as the RL algorithm developed in the VDM. Especially in Bayesian Decision Theory (BDT)[22,23], which has been providing compelling accounts for PDM behavior, the world statistics is a crucial knowledge that is required to infer a world state in PDM[24–27].

Fig. 1 | Two possible scenarios for what humans learn from feedback for PDM and their distinct predictions of feedback effects. a, Decision platform for perceptual binary classification. The gray arrows depict how a sensory measurement m and feedback F are generated from a stimulus S, which is sampled from the $world$, and a decision d. The black arrows depict the computational process, where, for a given choice $option$, a decision-maker computes its expected value Q_{option} by multiplying the probability that the choice is correct P_{option} given m and the class boundary B with the value of that choice V_{option} and make a choice d based on Q_{option}. In principle, the decision-maker may update either V_{option} (red dashed arrows; value-updating) or $world$ (green dashed arrows; world-updating) from m, d, and F. **b**, Distinct sensory-evidence-dependent feedback effects predicted by the two scenarios. According to the value-updating scenario (left), as the sensory evidence grows, P_{option}, and accordingly Q_{option} too, grows. As a result, reward prediction errors become smaller but remains in the direction congruent with feedback, which predicts that feedback effects on subsequent trials diminish asymptotically as a function of sensory evidence. According to the world-updating scenario (right), as sensory evidence grows, the stimulus distribution, and accordingly B too, becomes shifted farther towards the stimulus in the direction counteracting the influence of feedback. As a result, the direction of feedback effects is like that predicted by the value-updating scenario for weak sensory evidence but becomes eventually reversed to the direction incongruent with feedback as sensory evidence grows.

Here we test which of the two scenarios better explains the effects of corrective feedback—without any physical reward—on humans' PDM. To do so, we implemented the value-updating and world-updating scenarios into a variant of RL model[9] and a Bayesian model, respectively, and directly compared the two models' accountability for the feedback effects on humans' PDM behavior. As a PDM task, we opted for a binary classification task, one most widely used PDM task in which decision-makers sort items into two discrete classes by setting a boundary since the two scenarios make distinct predictions about the stimulus-dependent feedback effects in this task. As will be described in detail later, the value-updating scenario predicts that feedback, which acts like rewards, "unidirectionally" fosters and suppresses the rewarded ($correct$) and unrewarded ($incorrect$) choices, respectively, in subsequent trials while diminishing its impact asymptotically as sensory evidence becomes stronger, due to the reduction in reward prediction error (the red curve in Fig. 1b). By contrast, the world-updating scenario predicts that the feedback effects not just diminish but eventually become reversed to the opposite side as sensory evidence grows, as the shift of the class boundary toward the previous stimulus counteracts the boundary shift due to feedback (the green curve in Fig. 1b).

We found the world-updating model superior to the value-updating model. Critically, the value-updating model fails to account for the observed stimulus-dependent feedback effects. Our findings suggest that humans are likely to treat corrective feedback in PDM as logical indicators of the trueness of the proposition to which they committed, rather than as rewards, and update their knowledge of world statistics, rather than the values of choices, based on feedback in conjunction with the other history factors—previous stimuli and choices.

Results

Quantifying the retrospective and prospective history effects of feedback on binary classification. To study the stimulus-dependent feedback effects in PDM, we acquired long sequences (170 trials/sequence) of binary choices ($C \in \{small, large\}$) many times (30 sequences/participant) from each of 30 human participants while varying the ring size ($S \in \{-2, -1, 0, 1, 2\}$) and providing corrective feedback ($F \in \{correct, incorrect\}$) (Fig. 2a). On each trial, participants viewed a ring and judged whether its size is $small$ or $large$ as accurately as possible, while receiving feedback, indicated by color whether the choice was correct or

incorrect (Fig. 2b). We ensured the ring size to vary sufficiently—including the ones very easy and difficult for classification—so that the two scenarios' distinct predictions on the stimulus-dependent feedback effects can be readily compared. Also, we used stochastic feedback, where *correct* and *incorrect* feedback was very occasionally given to incorrect and correct choices, respectively, to cover the entire 3D space of decision-making episodes defined orthogonally over 'stimulus', 'choice', and 'feedback' ($5 \times 2 \times 2 = 20\ episodes$; Fig. 2c; Methods).

Fig. 2 | Experimental design and definition of retrospective and prospective history effects. a, A chain of PDM episodes over a single sequence of trials. Each trial sequence consists of 170 column vectors of PDM episode [stimulus; choice; feedback]. In this example, the trial of interest (*toi*) is defined as [0; *large; correct*] and demarcated by thick outlines. Accordingly, the trials that precede and follow *toi* can be labeled as *toi-1* and *toi+1*, respectively. **b**, Trial structure. Participants viewed a randomly sampled ring with their eyes fixed, classified its size, and then received feedback, which indicated by the color around the fixation whether the classification was correct or incorrect. **c**, 3D state space of the PDM episodes in the current experiment. The example episode of *toi* in (**a**) is marked by the black cube. **d**,

definition of retrospective and prospective history effects. As illustrated in (**a**) and (**c**), for any given episode of *toi*, all the trials labeled with *toi-1* and *toi+1* are stacked and used to derive the psychometric curves, respectively. The PSEs estimated for the *toi-1* and *toi+1* psychometric curves quantify the retrospective and prospective history effects, respectively. In this example, the black and gray curves were defined for *toi* = $[0;\ large;\ correct]$ and *toi* = $[0;\ small;\ correct]$, respectively, with circles and bars representing the mean and s.t.e. across 30 participants, respectively.

To evaluate rigorously the correspondence between model prediction and human behavior, we quantified the history effects in both—retrospective and prospective—directions of time, as follows (Fig. 2d). First, we localized the trials in which a PDM episode of interest occurred (the trials of interest, *toi*) and stacked the trials that preceded (the retrospective block of trials, *toi-1*) and those that followed (the prospective block of trials, *toi+1*) *toi*. Second, we derived the two psychometric curves based on the retrospective and prospective blocks of trials, respectively, and fit the cumulative normal distribution function to these curves to estimate the point-of-subjective-inequality (PSE) measures, which have previously been used[16–18] and known[28] to reliably estimate the history-dependent choice biases in PDM. Thus, the PSEs of the retrospective and prospective trials quantify the choice biases that exist *before* and *after* the PDM episode of interest occurs, respectively, with negative and positive values signifying that choices are biased to $large$ and $small$, respectively.

Decision-making processes for binary classification. As a first step of evaluating the value-updating and world-updating scenarios, we constructed a common platform of decision-making for binary classification where both scenarios play out. This platform consists of three processing stages (Fig. 3a). At the stage of 'perception', the decision-maker infers the class probabilities, i.e., the probabilities that the ring size (S) is larger and smaller, respectively, than the class boundary (B) given a noisy sensory measurement (m), as follows:

$$p(CL = large) = p(S > B|m) = \int_B^\infty p(S|m)dS;$$

$$p(CL = small) = 1 - p(CL = large),$$

where CL stands for the class variable with the two ($small$ and $large$) states.

At the stage of 'valuation', the decision-maker forms the expected values for the two choices (Q_{large} and Q_{small}) by multiplying the class probabilities by the learned values of the corresponding choices (V_{large} and V_{small}) as follows:

$$Q_{large} = p(CL = large) \times V_{large};$$

$$Q_{small} = p(CL = small) \times V_{small}.$$

Lastly, at the stage of 'decision', the decision-maker commits to the choice whose expected value is greater than the other. In this platform, choice bias may originate from the

perception or valuation stage. Suppose the decision-maker's internal model of size distribution at the perception stage is not fixed but changes depending previous PDM episodes (Fig. 3b, top). Such changes lead to the changes in PSE of the psychometric curve because the class probabilities change as the class boundary changes (Fig. 3b, bottom). Alternatively, suppose the decision-maker's learned values of the choices are not fixed but change similarly (Fig. 3c, top). These changes also lead to the changes in PSE of the psychometric curve because the expected values change as the choice values change (Fig. 3c, bottom).

Fig. 3 | Implementation of the value-updating and world-updating scenarios into computational models. a, Computational elements along the three stages of PDM for binary classification. At '*perception*' stage, the probabilities that the class variable takes its binary states $small$ and $large$— $p(CL = large)$ and $p(CL = small)$—are computed by comparing the belief on the stimulus size $p(S|m)$ against the belief on the class boundary B—the mean of the belief on stimulus distribution in the world $p(S)$. At '*valuation*' stage, the outcomes of the perception stage are multiplied by the learned values Vs to produce the expected values Qs. At '*decision*' stage, the choice with the greater expected value is selected. **b,c**, Illustration of two potential origins of choice biases, one at '*perception*' stage (**b**) and the other at '*valuation*' stage (**c**). The color indicates the direction of choice bias (yellow for bias to $large$; balck for no bias; blue for bias to $small$). **d,e**, Illustration of the architectures (left panels) and predictions on the stimulus-dependent feedback effects (right panels) of BMBU (**d**) and the belief-based RL model

(**e**). In the left panels, the dashed arrows represent the ways the history factors (feedback and stimulus) exerts their contribution to choice bias. In the right panels, PSE_{toi+1}, which quantifies the choice bias in the trials following a certain PDM episode *toi*, is plotted as a function of the stimulus size at *toi*. The color indicates the direction of choice bias, as in **b** and **c**.

The belief-based RL model. To implement the value-updating scenario, we adapted the belief-based RL model[9] to the current experimental setup. Here, feedback acts like a reward by positively or negatively reinforcing the value of the choice ($V_{large(small)}$) with the deviation of the reward outcome (r) from the expected value of that choice ($Q_{large(small)}$) as follows:

$$V_{large(small)} \leftarrow V_{large(small)} + \alpha\delta;$$

$$\delta = r - Q_{large(small)} = r - p(CL = large(small)) \times V_{large(small)},$$

where α, δ, and r are the learning rate, the reward prediction error, and the reward, respectively. The state of feedback determines the value of r: $r = 1$ for $correct$; $r = 0$ for $incorrect$. Note that δ has the statistical decision confidence at the perception stage, i.e., $p(CL = large(small))$, as one of its three arguments. This feature, as stressed by the authors who developed this algorithm[9], makes the strength of sensory evidence—i.e., statistical decision confidence—modulate the degree to which the decision-maker updates the chosen value based on feedback (Fig. 3e, left). Hence, this belief-based modulation of value-updating underlies the stimulus-dependent feedback effects: the amount of feedback effects decreases as the sensory evidence becomes stronger since the reward prediction error decreases as a function of $p(CL = large(small))$, which is proportional to sensory evidence (Fig. 3e, right).

The Bayesian model of boundary-updating (BMBU). To implement the world-updating scenario, we developed BMBU, which updates the class boundary based on the previous PDM episode in the framework of BDT. Specifically, given 'a state of the class variable that is indicated jointly by feedback and choice', CL, and 'a sensory measurement in memory', m', BMBU infers the mean of size distribution (i.e., class boundary), B, by updating its prior belief about B, $p(B)$, with the likelihood of B, $p(m', CL|B)$, by inverting its internal model of how m' and CL are generated (Fig. 3d, left) as follows:

$$p(B|m', CL) \propto p(m', CL|B)p(B) \equiv p(m', C, F|B)p(B).$$

This algorithm maps the specific ensembles of 'stimulus (evidence)', 'choice', and 'feedback' (since C and F jointly determine CL) in the previous trial onto the choice biases with

the specific directions and magnitudes in the following trial. Thus, with this algorithm, we can predict how feedback effects depend on stimuli under the world-updating scenario. Suppose a decision-maker currently believes that the size distribution is centered at 0, views a ring of size 0, classifies it as $large$—due to stochastic processes, and receives $correct$ feedback. Following this episode (i.e., $\{S = 0, C = large, F = correct\}$), the choice will be biased to the $small$ side because $correct$ feedback to the $large$ choice, which means that the true state of CL is $large$, will shift the class boundary to the $small$ side whereas the size of 0 will hardly move the class boundary. Next, let us vary only the stimulus variable gradually in the above episode to appreciate the stimulus-dependent feedback effects in the world-updating scenario. As the size grows (e.g., $S = 0 \rightarrow 1 \rightarrow 2$), the contribution of the size variable to class boundary shift increases, shifting the boundary farther and farther to the $large$ side, in the direction counteracting that of the feedback contribution (Fig. 3d, right). Hence, because the bias of the class boundary is inversely correlated with the choice bias, the choice is initially biased to the $large$ side but increasingly biased to the $small$ side as the size grows.

We stress that this 'bias direction reversal as a function of sensory evidence' (we will refer to this as 'bias reversal' in short hereafter) is a hallmark of the world-updating scenario's prediction of the history effects in PDM. Specifically, the direction of 'bias reversal' is always from $small$ to $large$ as long as the feedback in conjunction with the choice indicates $CL = small$ (e.g., $\{S = 0 \rightarrow -1 \rightarrow -2, C = small, F = correct\}$ or $\{S = 0 \rightarrow -1 \rightarrow -2, C = large, F = incorrect\}$) and always from $large$ to $small$ as long as the feedback in conjunction with the choice indicates $CL = large$ (e.g., $\{S = 0 \rightarrow 1 \rightarrow 2, C = large, F = correct\}$ or $\{S = 0 \rightarrow 1 \rightarrow 2, C = small, F = incorrect\}$). Critically, the value-updating scenario does not predict the bias reversal (Fig. 3e, right). It predicts that the feedback effects only asymptotically decrease as a function of sensory evidence but never switch to the other direction. This is because the decision confidence, $p(CL = large(small))$, only modulates the amount of value-updating but never changes the direction of value-updating.

***Ex ante* simulation of the feedback effects under the two scenarios.** Above, we have rather conceptually explained why and how the two scenarios imply the distinct patterns of stimulus-dependent feedback effects. Though this implication seems intuitively apparent, it must be confirmed under the experimental setting of the current study. Moreover, there are good reasons to expect any history effect to exhibit complex dynamics over trials. First, sensory evidence is subject to stochastic noises, which propagates through decision-making and value/boundary-updating processes to subsequent trials (e.g., a sensory measurement that

happens to fall on a relatively $small$ side is likely to lead to a $small$ choice, which affects the value/boundary-updating process, and so on). Second, provided that any deterministic value/boundary-updating processes are presumed to be at work, the PDM episode on a given trial must, in principle, be probabilistically conditioned on the episodes in past trials (e.g., the current $small$ choice on the ring of $S = 0$ is likely to have followed the previous episodes leading to 'boundary-updating in the $large$ direction' or 'positive value-updating of the $small$ choice'). Third, two steps of deterministic value/boundary-updating occur between what can be observed at $toi - 1$ and at $toi + 1$ (as indicated by the psychometric curves in Fig. 4a), once following the episode at $toi - 1$ (U_{toi-1} in Fig. 4a) and next following the episode at toi (U_{toi} in Fig. 4a). Thus, the differences between the retrospective and prospective history effects should be construed as reflecting not only U_{toi} but also U_{toi-1}. The nuanced impacts of this hidden updating on the history effects must be complicated and thus be inspected with realistic simulation. Further, considering that these multiple stochastic and deterministic events together interplay with one another to create diverse temporal contexts, history effects are supposed to reveal themselves in multiplexed dynamics.

Hence, we simulated *ex ante* the two models over a reasonable range of parameters by making the model agents perform the binary classification task on the sequences of stimuli that will be used in the actual experiment (Supplementary Table 1, Supplementary Fig. 1, and Methods). The simulation results confirmed our intuition, as summarized in Figure 4, which shows the retrospective and prospective history effects for the PDM episodes with $correct$ feedback. Notably, the retrospective history effects indicate that both value-updating and world-updating agents were already slightly biased to the choice that they are about to make in the— following—*toi* (Fig. 4b,e). One readily intuits that such retrospective biases are more pronounced when conditioned on the *toi* with weak sensory evidence because the stochastic bias consistent with the choice that would be made in the *toi* is required more in those trials. This testifies the presence of the complex dynamics of history effects discussed above and is also consistent with what has been previously observed (e.g., see Figure 2 of the previous study[9]). Importantly, in line with our conceptual conjecture (Fig. 3d,e), the two agents evidently disagree on the prospective history effects. While the value-adapting agent always exhibits the feedback-congruent bias but never reverses the direction of bias, the world-adapting agent shows the feedback-congruent bias after viewing the ambiguous stimulus but progressively reversed the direction of bias as the stimulus evidence supporting the decision becomes stronger (Fig. 4c,d,f,g,h).

Fig. 4 | *Ex ante* simulation results for the PDM episodes with *correct* feedback. a, Illustration of how the retrospective (left) and prospective (right) history effects are related to the value/boundary-updatings (bottom) occurring over the trials overarching the trial of interest. While the updating occurs latently at every trial (U_{toi-1}, U_{toi}, U_{toi+1}), one can access its behavioral consequences only at the pre-updating phase at *toi-1* and *toi+1*. **b,c,d**, The observable retrospective (**b**) and prospective (**d**) history effects and latent value-updating processes (**c**) displayed by the value-updating model agent (v-shaped symbol). Here, only the chosen value is updated positively with the amount dependent on the stimulus size, as indicated by the arrows. **e,f,g**, The same history effects (**e,g**) and latent boundary-updating processes (**f**) displayed by the world-updating model agent (square-shaped symbol). Here, the class boundary is shifted as a joint function of feedback and stimulus size, where the boundary shifts due to stimulus size counteract those due to feedback, as indicated by the arrows. All PSE values were taken from the mean across parameter sets used in *ex ante* simulations (see Methods; error bars show s.e.m.). **h**, Juxtaposition of the difference between the retrospective and prospective history effects displayed by the two model agents.

Next, Figure 5 summarizes the history effects for the PDM episodes with *incorrect* feedback. The retrospective history effects show that both agents exhibit the choice bias consistent with the choice they will make next trial, as in the case for *correct* feedback, but the amounts of bias are much greater compared to those in the *correct*-feedback condition (Fig. 5b,e). These pronounced retrospective effects conditioned on the *incorrect*-feedback episodes are intuitively understood as follows: the value-updating agent's value ratio or the world-

updating agent's class boundary was likely to be somehow "unusually and strongly" biased before the *toi,* given that they make an *incorrect*—thus "unusual"—choice in the *toi.* Supporting this intuition, the retrospective bias increases as the sensory evidence increases, since the prior value ratio or class boundary must be strongly biased to result in that particular *incorrect* choice despite such strong sensory evidence. Importantly, despite these large retrospective biases, the prospective history effects indicate that both agents adjust their value and class boundary, respectively, in their own manners identical to those for the *correct*-feedback episodes (Fig. 5c,d,f,g). Thus, as in the case for the *correct*-feedback episodes, the direction reversal is displayed only by the world-updating agent, but not by the value-updating agent (Fig. 5h).

Fig. 5 | *Ex ante* simulation results for the PDM episodes with *incorrect* feedback. The format is identical to that in Fig. 4.

In sum, the *ex ante* simulation confirmed that the bias reversal of the stimulus-dependent feedback effects occurs only under the world-updating scenario but not under the value-updating scenario, regardless of the (*correct* or *incorrect*) states of feedback. The

simulation results also confirmed that, with the current experimental setting, we can empirically determine which of the two scenarios provides a better account of feedback effects.

Evaluating the two scenarios for the goodness of fit to human decision-making data.
Having confirmed the distinct predictions of the two scenarios via *ex ante* simulation, we evaluated their goodness of fit to human data. As points of reference for evaluation, we created three more models in the model space. The 'Base' model sets the class boundary at the unbiased value ($B = 0$) and does not update any choice values, thus incorporating neither arbitrary choice preference nor adaptive updating. The 'Fixed' model is identical to the Base model except that it incorporates arbitrary choice preference by fitting the constant class boundary to the data. The 'Hybrid' model incorporated both value-updating and world-updating algorithms. In the model space consisting of five models (Fig. 6a), we quantified the models' ability to predict human classification choices using log likelihood (LL; Fig. 6b) and compared their abilities using two model-comparison criteria, the Akaike information criterion corrected for sample size (AICc[29]; Fig. 6c) and the Bayesian information criterion (BIC[30]; Fig. 6d).

In each comparison, the performance of the Fixed model relative to that of the Base model (gray dashed lines in Fig. 6b,c,d) captures the fraction of choice variability due to arbitrary choice preference. The performance of the Hybrid model relative to that of the Fixed model (the space between the gray and purple dashed lines in Fig. 6b,c,d) captures the (hypothetically) maximal fraction of choice variability that (i) cannot be ascribed to arbitrary choice preference but (ii) can be explained either by the value-updating model or by the world-updating model or by both. We found that the world-updating model was indistinguishable from the Hybrid model for AICc (paired *t*-test, *P=0.291*) and even superior to the Hybrid model for BIC (paired *t*-test, *P=1.49x10^-7*). By contrast, the value-updating model was only slightly better than the Fixed model for AICc (paired *t*-test, *P=0.008*) and indistinguishable from the Fixed model for BIC (paired *t*-test, *P=0.28*). These results, especially the BIC results, suggest that the value-updating algorithm only increased model complexity but hardly helped to explain human choice variability other than their arbitrary choice preferences.

Fig. 6 | Model goodness of fit to human choice behavior. a, Specification of the models constituting the model space. The color labels also apply to the rest of the panels (**b-f**). **b,c,d,** Model comparisons in goodness of fit in terms of log likelihood (**b**), AICc (**c**), and BIC (**d**). The height of bars represents the across-participant average differences from the goodness-of-fit measures of the Base model (N=30, mean±s.e.m). The purple and gray dashed lines provide the reference points (see Main text for their meanings). Pair-wise model comparisons were performed using paired two-tailed t-tests (asterisks indicate significance: *, $P < 0.05$; **, $P < 0.01$; ***, $P < 10^{-6}$) **e,f,** Model comparisons in the hierarchical Bayesian Model Selection measures in terms of AICc (**e**) and BIC (**f**) values. Height of bars, the across-participant average expected posterior probabilities (N=30, mean±s.e.m). Dots marked with short dashes, protected exceedance probability. Dashed lines, chance level (p=0.2) probability that a model is more likely than the others in describing data due to chance.

To complement the above pair-wise comparisons, we took the hierarchical Bayesian Model Selection (hBMS) approach[31–33], to assess how probable it is that each of the five models prevails in the population (expected posterior probability; vertical bars in Fig. 6e,f) and how likely it is that any given model is more frequent than the other models (protected exceedance probability; dots with horizontal bars in Fig. 6e,f). Both hBMS measures corroborated the outcomes of the pair-wise comparisons: the world-updating model predominated in expected posterior probability (*P=0.5992* for AICc; *P=0.9141* for BIC) and protected exceedance probability (*P=0.8938* for AICc; *P=0.9999* for BIC).

In sum, the world-updating scenario was superior to the value-updating scenario in predicting the choice behavior of human participants performing the binary classification task.

Ex post simulation of the feedback effects under the two scenarios. The _ex post_ simulations were identical to the _ex ante_ simulation except that the best-fit model parameters were used for each decision-maker (Supplementary Table 2-1; Methods). We assessed how well the models reproduce the human history effects of feedback in two different ways. First, we compared the models and the humans in the same way as the _ex ante_ simulation (Fig. 7a-c). We included the PDM episodes with non-veridical feedback (symbols with dotted lines in Fig. 7a-c) though those episodes rarely occurred (12.09±0.02% (mean±SEM) out of total _toi_ episode trials; bars with dotted outlines in Fig. 7d). As a result, we inspected the retrospective and prospective history effects, and their differences, for all the possible combinations of 'stimulus,' 'choice,' and 'feedback' (20 PDM episodes in total), which resulted in a total of 60 PSE pairs to compare. The PSEs simulated by the world-update model closely matched human PSEs, in both pattern and magnitude (Fig. 7a,c), whereas those by the value-update model substantively deviated from human PSEs (Fig. 7a,b). The statistical comparison (paired _t_-tests with Bonferroni correction) indicates that the value-updating model's PSEs significantly deviated from the corresponding human PSEs for almost half of the entire pairs (29 out of 60 pairs) whereas none of the world-updating model's PSEs significantly differed from the human PSEs (0 out of 60 pairs). Notably, most of the mismatches occurred because the value-updating model does not reverse the direction of feedback effects as sensory evidence grows while humans do so (compare the third columns of Fig. 7a and 7b).

Second, we compared the models and the humans in the probability distribution of retrospective and prospective episodes conditioned on each episode of _toi_ (Fig. 7d-f). This comparison allows us to assess the models' reproducibility not just for feedback effects but also for the history effects in general and to explore the origin of the value-based model's failure. By collapsing all the preceding and following trials onto each of the 20 _toi_ episodes (the columns of Fig. 7e,f) and computing their probability distributions across—again—the 20 _toi-1_ and 20 _toi+1_ episodes (the rows of Fig. 7e,f), respectively, we could create 400 joint-probability cells.

Fig. 7 | *Ex post* simulation results. a-c, Retrospective (left columns), prospective (middle columns), and subtractive (right columns) history effects in PSE for the human (**a**), value-updating (**b**), and world-updating (**c**) decision-makers. Top and bottom rows in each panel show the PSEs associated with the *toi* episodes involving *correct* and *incorrect* feedback. Symbols with error bars, mean±s.e.m across 30 decision-makers. **d**, Frequency of PDM episodes in the human data (mean and SD across participants). **e**,**f**, Maps of significant deviations of the value-updating (**e**) and world-updating (**f**) model agents from the human decision-makers in the retrospective (left) and prospective (right) history effects. Gray and black cells of the maps mark the insignificant and significant deviations (Bonferroni corrected P< 0.05 when paired two-tailed *t*-tests performed). Empty cells, data points with NaN values due to insufficient observations.

We carried out repeated *t*-tests with Bonferroni correction to see where the model-human mismatches occur (data were missing for a few cells—mostly those including non-veridical-feedback episodes, as indicated by the empty cells in Fig. 7e,f, because those episodes were too rare (Fig. 7d) to occur for all participants). For the remaining cells, the world-updating model showed a remarkable level of correspondence with the humans, deviating from the humans at only two cells (out of 790 cells, 0.25%; Fig. 7f). By contrast, the value-updating model failed to

match the humans for a total of 94 cells (out of 792 cells, 11.87%; Fig. 7e). Here, the mismatches occurred systematically: they were frequent when the preceding episode defining any given cell (i.e., episodes at *toi-1* for the retrospective cells or episodes at *toi* for the prospective cells) was featured with strong sensory evidence (as indicated by the arrows in Fig. 7e). This systematic deviation precisely reflects the incapability of the value-updating model to reverse the direction of feedback effects as sensory evidence grows in strength.

In sum, the stimulus-dependent history effects of feedback observed in humans could be reproduced by the world-updating scenario but not by the value-based scenario.

Discussion

Here, we explored the two possible scenarios for what humans learn from corrective feedback in a PDM task. We implemented the value-updating scenario with the belief-based RL model[9,10], which had originally been developed to account for the stimulus-dependent effects of reward feedback on animals' PDM. As an alternative, we implemented the world-updating scenario with BMBU, where decision-makers continuously update their internal knowledge about stimulus distribution based on sensory measurements and corrective feedback. The latter excels over the former in predicting the choice behavior and in reproducing the stimulus-dependent feedback effects in human PDM, suggesting that humans update their knowledge about world statistics, rather than their subjective choice values, upon corrective feedback for PDM.

Given the RL model's success in VDM and the presence of physical rewards, it is not surprising for the belief-based RL model to be considered as an account of the feedback effects in animals' PDM. The original work[9] supported this model using the six different datasets including one human dataset[34]. However, the current work indicates that the way humans learn from corrective feedback—without any physical or monetary reward—in PDM deviates from the value-updating scenario. The critical deviation occurred for the PDM episodes with strong sensory evidence: past *correct* feedback should, albeit weakly, reinforce the choice made in the past according to the value-updating scenario whereas humans tended to switch choices following *correct* feedback. In fact, the human dataset previously analyzed in the study[9] exhibits the same deviations (see their Figure 8c,d). When this dataset was analyzed in our way, it displayed the patterns almost identical to those of our dataset (Supplementary Fig. 4a). For that

matter, another published human dataset[28] also substantially deviated from the value-updating scenario (Supplementary Fig. 4b). We remain cautious about the possibility that even animals may also show such deviations. However, this possibility seems worth exploring though, given that the main dataset from the 16 rats engaged in an olfactory PDM task also exhibits the patterns like those found in humans when corrected for the bias present in previous trials (see Figure 2i in the study[9]). The bias reversal of feedback effects should not be ignored as a nuisance factor because any variant of the RL algorithm cannot reverse the direction of reinforcement in principle, as demonstrated in our work and in the modeling results by the same study[9] (shown in their Figure 3). By contrast, BMBU offers a normative account of these effects by treating *correct* and *incorrect* feedback as they supposedly mean, a teaching signal indicating the true state of the class variable.

To be sure, the idea of shifting the decision or class boundary toward past stimuli *per se* is not new and has been previously hypothesized[35,36] or implemented into various models[37–41]. However, BMBU goes beyond these efforts by offering a normative formalism of incorporating *correct* and *incorrect* feedback as the evidence for the class boundary such that it has an equal footing as sensory evidence in PDM tasks. This integration of feedback and sensory evidence within the framework of BDT advances the current computational account of the history effects because it addresses the history factors in the complete dimensions of PDM ('stimulus', 'choice', and 'feedback'), which is important given the multiplexed nature of history effects. For that matter, our modeling work joins recent computational and empirical efforts of incorporating feedback in the normative model of evidence accumulation for a random-dot motion task, another classic PDM task[6,42]. Together with these efforts, our work supports a general view that human decision-makers use corrective feedback as the evidence for updating their world knowledge pertinent to the PDM task engaging them. Having mentioned the general view on the role of feedback in human PDM, future efforts are needed to further verify the stimulus-dependent feedback effects under various sensory modalities and PDM tasks.

Previously, the so-called "Anna Karenina" account was presented to describe the seemingly idiosyncratic *incorrect* feedback effects[9]. The Anna-Karenina account leaves the crucial aspect of feedback effects—the different consequences of *correct* vs *incorrect* feedback—unexplained. Since the belief-based RL model clearly predicts the specific pattern of feedback effects for incorrect trials as we shown via *ex ante* simulation, endorsing the Anna-Karenina account admits that the belief-based RL model fails to account for the effects of *incorrect* feedback observed in animals. For that matter, past studies on the history effects in PDM paid little attention to incorrect trials because they are, owing to their infrequency,

considered too noisy and unreliable to be properly analyzed. By contrast, BMBU offers a principled account of the effects of feedback regardless of whether feedback is *correct* or *incorrect*. Furthermore, BMBU explains why the feedback effects appear different between the correct and incorrect trials on the surface (compare the prospective history effects between Fig. 4 and Fig.5): the correct and incorrect trials share the same deterministic boundary-updating process but had different histories of their own stochastic events, which led to correct versus incorrect choices, respectively.

As mentioned earlier, the history effects are highly dynamic and multiplexed in nature. This calls for an effort of establishing a rigorous framework to probe behavioral data for the history effects. A few recent studies made such efforts. First, a group of researchers[6,9] raised a concern about the conventional practice of inspecting only the prospective history effects because it is possible that the observed effects are caused by non-systematic slow fluctuations in the decision-making strategy. This group dealt with this concern by subtracting the retrospective history effects from the prospective ones. Another group[43] shared this concern but disagreed about its remedy by showing that the subtraction method cannot fairly recover diverse systematic updating strategies. Alternatively, they took a model-based approach to separate any given updating strategy from random drifts in decision criteria. Although we also share the two groups' concerns and welcome their efforts, we emphasize that BMBU successfully reproduced human history effects in both directions of time without incorporating any non-systematic components arising from random drifts. BMBU's concurrent reproduction of the retrospective and prospective history effects was confirmed not just for the summary statistics (the PSEs in Fig. 7c) but also for the individual data points spanning the almost entire space of PDM episode pairs (Fig. 7f). This suggests that it is an empirical matter whether the decision criterion slowly drifts or not, raising another concern that one might explain away systematic history effects with the slow drifts if the slow drifts do not exist at all or are negligible in magnitude. In this sense, we propose that researchers should treat the retrospective history effects not as a baseline or control condition but as what must be explained, the phenomenon equally important as the prospective history effects, before resorting to any non-systematic sources. We believe that such a treatment is the way historians treat historical events[44], and that our approach showcases its one rigorous example.

Methods

Participants

All participants (13 females and 17 males, aged 18-30 years) were recruited from the Seoul National University (SNU) community, gave prior written informed consent following the guidelines and approval of the Institutional Review Board at Seoul National University, and were compensated approximately $10/h.

Procedure

Stimuli. The stimulus was a thin (.07 deg in visual angle), Gaussian-noise filtered, black-and-white ring flickering at 20 Hz on a gray luminance background. On each trial, a fixation first appeared for 0.5 s on average (fixation duration uniformly jittered from 0.3 s to 0.7 s on a trial-to-trial basis) before the onset of a ring stimulus. Five different ring sizes (radii of 3.84, 3.92, 4.00, 4.08, 4.16 deg in visual angle (d.v.a.), denoted by -2, -1, 0, +1, +2, respectively, in the main text) were randomized within every block of 5 trials.

Task. Participants performed a binary classification task on ring size with trial-to-trial corrective feedback. Each individual participated in 5 daily sessions, each consisting of 6 runs, each consisting of 170 trials, ended up performing a total of 5,100 trials. In any given trial, participants viewed one of the five rings and indicated its class ($small$ or $large$) within 1.2 s after stimulus onset by pressing one of the two keys using their index and middle fingers. The assignment of computer keys for $small$ and $large$ choices alternated between successive sessions to prevent any unwanted choice bias possibly associated with finger preference. The response period was followed by a feedback period of 0.5 s, during which the color of the fixation mark informed the participants of whether their response was correct (green) or not (red). In case no response had been made within the response period, the fixation mark turned yellow, reminding participants that a response must be made in time. These late-response trials comprised 0.5418% of the entire trials across participants and were included in data analysis. Meanwhile, the trials on which a response was not made at all comprised 0.0948% of the entire trials. These trials were excluded from analysis and model fitting. As a result, the number of valid trials per participant ranged from 5,073 to 5,100 with an average of 5,095.2 trials. Before each run, we showed participants the ring stimulus of the median size (4.00 d.v.a. in radius) on the screen for 15 s while instructing them to use that ring as a reference for future trials, i.e., to judge whether a test ring is smaller or larger than this reference ring. This procedure was introduced for the purpose

of minimizing any possible carryovers from the belief they formed about the class boundary in the previous session. Participants were encouraged to maximize the fraction of correct trials.

Feedback Manipulation. We provided participants with stochastic feedback using a 'virtual' criterion sampled from a normal distribution $\mathcal{N}(\mu_{True}, \sigma_{True})$. σ_{True} was always fixed at 1.28 throughout the entire runs. In each run, μ_{True} was initially (up to 40-50 trials) set to 0 and then to one of the three values ($\mu_{True} = \{-0.4, 0, +0.4\}$) with the equal proportion (10 runs for each value) for the rest of trials. The stochastic feedback was introduced this particular way to create PDM episodes with (occasional) non-veridical feedback while mimicking a real-world situation where references are slightly noisy and biased in an unnoticeable manner.

Data analysis

For any given PDM episode at the trial of interest (*toi*), we quantified the retrospective and prospective history effects by probing the psychometric curves at the trials before and after *toi*, respectively. The psychometric function ($\psi(x)$) was estimated by fitting the cumulative Gaussian distribution (F) to the curves using *Psignifit* package[45–47] (https://github.com/wichmann-lab/psignifit), as follows:

$$\psi(x) = F(x; \mu, \sigma),$$

where μ and σ are the mean and standard deviation of F. By finding the best-fitting value of μ, we defined the point of subjective equality (PSE; the stimulus level with equal probability for a $small$ or $large$ choice), which was used as the summary statistics that quantifies the history effects associated with a given PDM episode. We note that no guess (lapse) rate was applied in the above equation to prevent any possible overfitting problems from occurring, rather unfairly, in infrequent—thus small numbers of trials available for fitting—episode types.

Value-updating model

As a model of the value-updating scenario, we used the belief-based RL model proposed in the previous work[9,10]. This model incorporates RL algorithm into the conventional Bayesian formalism of decision confidence—also known as statistical decision confidence (Fig.1a, Fig.3e) using a partially observable Markov decision process. In this model, the decision-maker, given sensory evidence m, computes the probability that the stimulus belongs to '$large$' (p_L) or class '$small$' ($p_S = 1 - p_L$) (hereinafter the p-computation), where $p_L = \int_0^\infty p(S|m)dS$. This probability will be referred to as a 'belief-state', following the original work. Next, the expected values of the

two choices Q_S and Q_L can be obtained by multiplying p_S and p_L with the learned values of the options of $small$ and $large$, V_S and V_L, respectively.

Accordingly, the expected value Q_C is also defined separately for the choice made between $small$ and $large$: Q_S and Q_L.

In the original work, the argmax rule was applied to determine the choice (i.e., the higher Q determines the choice C). Instead, here we applied the softmax rule, which selects $large$ with probability $\frac{\exp{(\beta Q_L + b)}}{\exp(\beta Q_S) + \exp{(\beta Q_L + b)}}$ (the higher Q preferentially selects C) where β is an inverse temperature and b represents an agent's inherent action bias. This feature was introduced to allow the belief-based RL model to deal with the idiosyncratic choice bias and noise at the decision stage with similar components as those carried by BMBU (see World-updating model).

Upon receiving feedback to the decision, the decision-maker updates the value of the selected choice by the reward prediction error δ with learning rate α:

$$V_C \leftarrow V_C + \alpha\delta.$$

No temporal discounting is assumed for simplicity. Since the decision-maker treats corrective feedback as rewards (*correct*: r =+1, *incorrect*: r =0), the reward prediction error δ is computed as follows:

$$\delta = r - Q_C = r - p_C V_C.$$

Note that the belief state p_C (statistical decision confidence) modulates δ such that δ increases as p_C decreases, which is the crucial relationship constraining the belief-based RL model' key prediction on the stimulus-dependent feedback effects. Specifically, upon $correct$ feedback, δ will take a positive value and reinforce the choice value. However, as p_C increases, the magnitude of such reinforcement will decrease. Critically, despite the decrease of reinforcement as a function of p_C, the sign of reinforcement will never be reversed until the learned value Q reaches the true value ($r = 1$). Based on the same ground, the sign of reinforcement will never be reversed either in the case of $incorrect$ feedback.

The model parameters are $\theta = \{b, \sigma_m, \alpha, \beta, V_{init}\}$. The initial values of $small$ and $large$ choices were set identically as a free parameter V_{init}.

World-updating model

As a model of the world-updating scenario, we developed the Bayesian model of boundary-updating (BMBU). BMBU shares the same platform for PDM with the belief-based RL model,

but its decision process is completely governed by p-computation because the choice values are never updated.

For p-computation, the Bayesian decision-maker does not fix the finite limit of the integral at zero but updates it with the inferred class boundary $\hat{B}$ on a trial-to-trial basis:

$$p_L = \int_{\hat{B}}^{\infty} p(S|m)dS.$$

The $large$ class is chosen if $p_L > 0.5$ (the higher p determines the choice). We will describe how the class boundary is inferred later, in the following paragraphs.

The class boundary is inferred as follows. Having experienced a PDM episode in any given trial t, the Bayesian decision-maker infers the class boundary based on the retrieved memory the sensory measurement m'_t, the choice C_t, and the corrective feedback F_t by computing the posterior probability distribution according to Bayes rule:

$$p(B_t|m'_t, C_t, F_t) \equiv p(B_t|m'_t, CL_t) \propto p(m'_t, CL_t|B_t)p(B_t),$$

where $p(B_t)$ is the prior belief about the class boundary and CL_t stands for the binary state of the class variable, which is deduced jointly by C_t and F_t in binary classification below:

$$\text{if } C_t = large \text{ and } F_t = correct \text{ or if } C_t = small \text{ and } F_t = incorrect, \ CL_t = large;$$
$$otherwise, \ CL_t = small.$$

The likelihood $p(m'_t, CL_t|B_t)$ can be computed by propagating the two pieces of evidence, m'_t and CL_t, inversely over the generative model of how m'_t and CL_t are generated (as depicted in Fig.1a, Fig.3d), as follows:

$$p(m'_t, CL_t|B_t) = \int p(m'_t, CL_t, S_t|B_t)dS_t$$

$$= \int \left[\int p\left(m'_t|m_t\right)p(m_t|S_t)dm_t \right] p(S_t|B_t)p(CL_t|S_t, B_t)dS_t$$

$$= \int N\left(m'_t, \sigma^2_{m'} + \sigma^2_m\right)N(S_t, \sigma^2_S)p(CL_t|S_t, B_t)dS_t$$

The integral above can be decomposed into the two components, which correspond to the two regimes of the inequality between S_t and B_t, as follows:

$$p(m'_t, CL_t|B_t) = \int_{S_t=-\infty}^{S_t<B_t} N\left(m'_t, \sigma^2_{m'} + \sigma^2_m\right)N(S_t, \sigma^2_S)p(CL_t|S_t, B_t)dS_t +$$

$$\int_{S_t>B_t}^{S_t=+\infty} N\left(m'_t, \sigma^2_{m'} + \sigma^2_m\right)N(S_t, \sigma^2_S)p(CL_t|S_t, B_t)dS_t$$

This decomposition allows the likelihood term to keep only the component relevant to the state of CL_t, which is indicated jointly by F_t and C_t. Specifically, for $CL_t = small$, the $p(CL_t|S_t, B_t)$ is

always 1 for the regime of $S_t < B_t$ and 0 for the regime of $S_t > B_t$ since $CL_t = small$ indicates $S_t < B_t$. Therefore, the likelihood is reduced as follows:

$$p(m_t', CL_t | B_t) = \int_{S_t=-\infty}^{S_t<B_t} N\left(m_t', \sigma_{m'}^2 + \sigma_m^2\right) N(S_t, \sigma_S^2) dS_t$$

$$\propto \int_{S_t=-\infty}^{S_t<B_t} e^{-\frac{(S_t - \frac{B_t\sigma_M^2 + m_t'\sigma_S^2}{\sigma_M^2+\sigma_S^2})^2}{\frac{\sigma_M^2\sigma_S^2}{2(\sigma_M^2+\sigma_S^2)}}} dS_t \times e^{-\frac{(B_t-m_t')^2}{2(\sigma_M^2+\sigma_S^2)}},$$

where $\sigma_{m'}^2 + \sigma_m^2$ is replaced by σ_M^2 for simplicity. Likewise, for $CL_t = large$, the $p(CL_t | S_t, B_t)$ is always 0 for the regime of $S_t < B_t$ and 1 for the regime of $S_t > B_t$ since $CL_t = large$ indicates $S_t > B_t$. Therefore, the likelihood is reduced as follows:

$$p(m_t', CL_t | B_t) = \int_{S_t>B_t}^{S_t=+\infty} N\left(m_t', \sigma_{m'}^2 + \sigma_m^2\right) N(S_t, \sigma_S^2) dS_t$$

$$\propto \int_{S_t>B_t}^{S_t=+\infty} e^{-\frac{(S_t - \frac{B_t\sigma_M^2 + m_t'\sigma_S^2}{\sigma_M^2+\sigma_S^2})^2}{\frac{\sigma_M^2\sigma_S^2}{2(\sigma_M^2+\sigma_S^2)}}} dS_t \times e^{-\frac{(B_t-m_t')^2}{2(\sigma_M^2+\sigma_S^2)}}.$$

To sum, the likelihood term boils down to a form of the product of a cumulative distribution function of $N\left(\frac{B_t\sigma_M^2 + m_t'\sigma_S^2}{\sigma_M^2+\sigma_S^2}, \frac{\sigma_M^2\sigma_S^2}{4(\sigma_M^2+\sigma_S^2)}\right)$ and a probability density function of $N(m_t', \sigma_M^2 + \sigma_S^2)$.

　　To recapture what have been described so far, based on the PDM episode $\{m_t', C_t, F_t\}$, the Bayesian decision-maker forms the belief about the class boundary $\hat{B}_t$ by combining the likelihood of B_t and its prior into the posterior of B_t. This posterior belief will be denoted by $\hat{B}_t^{post}$. Next, at the beginning of the following trial *t+1*, we assumed that the decision-maker has to recall $\hat{B}_t^{post}$ to the current working memory space and, while doing so, it is subject both to decay λ and diffusive noise $\sigma_{diffusion}$. As a result, the belief about the class boundary used on trial *t+1* $p(B_{t+1})$ is defined as the normal distribution $N(\hat{B}_{t+1}, \sigma_{B_{t+1}}^2)$, where

$$\hat{B}_{t+1} = \lambda \hat{B}_t^{post} + (1 - \lambda)\mu_0;$$

$$\sigma_{B_{t+1}}^2 = \lambda \sigma_t^{2\,post} + \sigma_{diffusion}^2.$$

Note that the decay parameter $\lambda = \frac{\sigma_0^2}{\sigma_0^2 + \sigma_t^{2\,post}}$ influences the width and location of the belief distribution, and that the diffusive noise of $\sigma_{diffusion} > 0$ helps to keep the width of the

distribution over multiple trials, thus avoiding sharpening and stopping the updating process. In this way, as the softmax rule served the belief-based RL model, λ and $\sigma_{diffusion}$ allows BMBU to address the idiosyncratic choice bias and noise. The model parameters are $\theta = \{\mu_0, \sigma_m, \sigma_s, \sigma_0, \sigma_{m'}, \sigma_{diffusion}\}$.

Reference models

As the references for evaluating the belief-based RL model and BMBU in predicting the variability of human choices, we created the three reference models. The 'Base' model captures the choice variability that can be explained by the p-computation with the class boundary fixed at 0 unanimously for all participants and without any value-updating process. Thus, it has only a single free parameter representing the variability of the sensory measurement ($\theta = \{\sigma_m\}$). The 'Fixed' model captures the choice variability that can be explained by the p-computation with the class boundary set free to a fixed constant μ_0 for each participant and without any value-updating process. Thus, it has two free parameters ($\theta = \{\mu_0, \sigma_m\}$). The 'Hybrid' model captures the choice variability that can be explained both by the p-computation with the inferred class boundary by BMBU and by the value-updating process implemented by the belief-based RL model. Thus, it has nine free parameters ($\theta = \{\sigma_m, \alpha, \beta, V_{init}, \sigma_s, \mu_0, \sigma_0, \sigma_{m'}, \sigma_{diffusion}\}$). In Figure 6b-d, the differential goodness-of-fit measures on the y-axis indicate the subtractions of the performance of the 'Base' model from those of the remaining models.

Model fitting

For each participant, we fitted the models to human choices over N valid trials (N≤170) of M(=10) experimental runs under K(=3) conditions, where invalid trials were the trials in which the participants did not make any response. For any given model, we denote the log likelihood of a set of parameters θ given the data as follows:

$$LL(\theta, model) = \log p(data | \theta, model) = \sum_{k=1}^{K_{cond}} \sum_{j=1}^{M_{runs}} \sum_{i=1}^{N_{trials}} \log p\left(C_{i,j,k} \middle| \theta, model\right),$$

where $C_{i,j,k}$ denotes the participant's choice ($large$ or $small$) on the i-th trial of the j-th run under the j-th condition. Computation of this LL is analytically intractable given the stochastic nature of choice determination. So, we used inverse binomial sampling (IBS[48]), an efficient way of generating unbiased estimates via numerical simulations. The maximum-likelihood estimate of the model parameters was obtained with Bayesian Adaptive Direct Search (BADS[49]), a hybrid

Bayesian optimization to find the parameter vector θ^* that maximizes the log likelihood, which works well with stochastic target functions. To reduce the risk of being stuck at local optima, we repeated 20 independent fittings by setting the starting positions randomly using Latin hypercube sampling (*lhsdesign_modifed.m* by Nassim Khlaled, https://www.mathworks.com/matlabcentral/fileexchange/45793-latin-hypercube), then picked the fitting with the highest log likelihood. To avoid infinite loops from using IBS, we did not impose individual lapse rates in an arbitrary manner. Instead, we calculated the average of the lapse rate and guess rate from the cumulative Gaussian fit to a given individual's grand mean (based on the entire trials) psychometric curve. With these individual lapse probabilities (mean rate of 0.05, which ranged from $[0.0051, 0.1714]$), trials were randomly designated as lapse trials, in which the choice was randomly determined to be either *small* or *large*.

Model comparison in goodness-of-fit

We compared the goodness-of-fit of the models using corrected Akaike information criterion (AICc) and Bayesian Information Criteria (BIC) based on maximum-likelihood estimation fitting, as follows:

$$AICc = -2 \cdot \text{LL}(\theta^*) + 2p + \frac{2p(p+1)}{(N \times M \times K) - p - 1})$$

$$BIC = -2 \cdot \text{LL}(\theta^*) + p \cdot log(N \times M \times K),$$

where p is the number of parameters of the model and the total number of trials in the dataset is $N \times M \times K$. Log model evidence[33] was obtained for each participant by multiplying AICc or BIC by -1/2. Furthermore, we took a hierarchical Bayesian Model Selection approach (BMS; *spm_BMS.m* in SPM12, http://www.fil.ion.ucl.ac.uk/spm/) that infers the posterior over model frequencies in the population based on log model evidence values in each subject. To conclude whether a given model is the most likely model above and beyond chance, we also reported protected exceedance probabilities for each model (see Fig. 6e,f).

Ex ante and *Ex post* model simulations

We conducted *ex ante* model simulations to confirm and preview the value-updating and world-updating models' distinct predictions on the stimulus-dependent feedback effects under the current experimental setting. Model simulations were conducted using trial sequences (i.e., stimulus order and correct answers) identical to those administered to human participants. The model parameters used in the *ex ante* simulation are summarized in the Supplementary Table

1. Note that the 25 levels (uniformly-spaced [0.15, 3.27]) of σ_m, the only parameter common to the two models, were used. As for the other parameters specific to each model, we selected the values that generated human-level task performances (see Supplementary Fig.1 for details and statistical results). Simulations were repeated 100 times, resulting in the 100 x N x M x K = 507,300~510,000 trials per participant. For simplicity, we assumed neither lapse trials nor any arbitrary choice bias.

The procedure of *ex post* model simulations was identical to that of *ex ante* model simulations except that the best-fitting model parameters and lapse trials were used.

Statistical tests

Unless otherwise mentioned, the statistical comparisons were performed using paired *t*-tests (two-tailed, N=30). To test the reversed feedback effects at extreme stimuli conditions, we applied one-sample *t*-tests (one-tailed, N=27 for Supplementary Fig.4a, N=8 for Supplementary Fig.4b). Repeated *t*-tests on PSEs between data and model (Fig.7) were performed and p-values (Supplementary Table 3) were reported after Bonferroni correction (two-tailed, N=30; *: P<0.00083, **: P<0.000167, ***: P<0.0000167). Same tests using Wilcoxon signed rank tests were also provided after correction. Repeated *t*-tests on each cell of episode frequency maps between the data and the models were performed and p-values (Fig.7e,f) were reported after Bonferroni correction (two-tailed, N=30; value-updating, P < 0.0000631; world-updating, P< 0.0000633). Task performances between human agents (N=30) and model agents with different sets of parameters (N=25) were compared based on unpaired *t*-tests (two-tailed, Supplementary Fig.1).

Data availability

Raw and processed data will be available after publication.

Code availability

The analysis code supporting the reported findings will be available after publication.

References

1. Gold, J. I., Law, C.-T., Connolly, P. & Bennur, S. The relative influences of priors and sensory evidence on an oculomotor decision variable during perceptual learning. *J Neurophysiol* 100, 2653–2668 (2008).

2. Hwang, E. J., Dahlen, J. E., Mukundan, M. & Komiyama, T. History-based action selection bias in posterior parietal cortex. *Nat Commun* 8, 1242 (2017).

3. Abrahamyan, A., Silva, L. L., Dakin, S. C., Carandini, M. & Gardner, J. L. Adaptable history biases in human perceptual decisions. *Proc National Acad Sci* 113, E3548–E3557 (2016).

4. Busse, L. *et al.* The detection of visual contrast in the behaving mouse. *J Neurosci* 31, 11351–11361 (2011).

5. Scott, B. B., Constantinople, C. M., Erlich, J. C., Tank, D. W. & Brody, C. D. Sources of noise during accumulation of evidence in unrestrained and voluntarily head-restrained rats. *eLife* 4, e11308 (2015).

6. Mendonça, A. G. *et al.* The impact of learning on perceptual decisions and its implication for speed-accuracy tradeoffs. *Nat Commun* 11, 2757 (2020).

7. Fernberger, S. W. Interdependence of judgments within the series for the method of constant stimuli. *J Exp Psychol* 3, 126–150 (1920).

8. Lak, A., Nomoto, K., Keramati, M., Sakagami, M. & Kepecs, A. Midbrain dopamine neurons signal belief in choice accuracy during a perceptual decision. *Curr Biol* 27, 821–832 (2017).

9. Lak, A. *et al.* Reinforcement biases subsequent perceptual decisions when confidence is low, a widespread behavioral phenomenon. *eLife* 9, e49834 (2020).

10. Lak, A. *et al.* Dopaminergic and prefrontal basis of learning from sensory confidence and reward value. *Neuron* 105, 700-711.e6 (2020).

11. Lee, D., Seo, H. & Jung, M. W. Neural basis of reinforcement learning and decision making. *Annu Rev Neurosci* 35, 287–308 (2012).

12. Daw, N. D. & Doya, K. The computational neurobiology of learning and reward. *Curr Opin Neurobiol* 16, 199–204 (2006).

13. Sutton, R. & Barto, A. *Reinforcement Learning: An Introduction.* (MIT Press, 1998).

14. Corrado, G. S., Sugrue, L. P., Seung, H. S. & Newsome, W. T. Linear-nonlinear-poisson models of primate choice dynamics. *J Exp Anal Behav* 84, 581–617 (2005).

15. Lau, B. & Glimcher, P. W. Dynamic response-by-response models of matching behavior in rhesus monkeys. *J Exp Anal Behav* 84, 555–579 (2005).

16. Odoemene, O., Pisupati, S., Nguyen, H. & Churchland, A. K. Visual evidence accumulation guides decision-making in unrestrained mice. *J Neurosci* 38, 10143–10155 (2018).

17. Hermoso-Mendizabal, A. *et al.* Response outcomes gate the impact of expectations on perceptual decisions. *Nat Commun* 11, 1057 (2020).

18. Akrami, A., Kopec, C. D., Diamond, M. E. & Brody, C. D. Posterior parietal cortex represents sensory history and mediates its effects on behaviour. *Nature* 554, 368–372 (2018).

19. Summerfield, C. & Tsetsos, K. Building bridges between perceptual and economic decision-making: neural and computational mechanisms. *Front Neurosci* 6, 70 (2012).

20. Kahnt, T., Grueschow, M., Speck, O. & Haynes, J.-D. Perceptual learning and decision-making in human medial frontal cortex. *Neuron* 70, 549–559 (2011).

21. Polanía, R., Krajbich, I., Grueschow, M. & Ruff, C. C. Neural oscillations and synchronization differentially support evidence accumulation in perceptual and value-based decision making. *Neuron* 82, 709–720 (2014).

22. Körding, K. P. & Wolpert, D. M. Bayesian decision theory in sensorimotor control. *Trends Cogn Sci* 10, 319–326 (2006).

23. Trommershäuser, J., Maloney, L. T. & Landy, M. S. Decision making, movement planning and statistical decision theory. *Trends Cogn Sci* 12, 291–297 (2008).

24. Griffiths, T. L. & Tenenbaum, J. B. Optimal predictions in everyday cognition. *Psychol Sci* 17, 767–73 (2006).

25. Tenenbaum, J. B., Kemp, C., Griffiths, T. L. & Goodman, N. D. How to grow a mind: statistics, structure, and abstraction. *Science* 331, 1279–1285 (2011).

26. Glaze, C. M., Filipowicz, A. L. S., Kable, J. W., Balasubramanian, V. & Gold, J. I. A bias–variance trade-off governs individual differences in on-line learning in an unpredictable environment. *Nat Hum Behav* 2, 213–224 (2018).

27. Ma, W. J. Bayesian decision models: A primer. *Neuron* 104, 164–175 (2019).

28. Hachen, I., Reinartz, S., Brasselet, R., Stroligo, A. & Diamond, M. E. Dynamics of history-dependent perceptual judgment. *Nat Commun* 12, 6036 (2021).

29. Burnham & Anderson. *Model selection and inference, A practical information-heuristic approach*. (Springer-Verlag, 2002).

30. Schwarz, G. Estimating the dimension of a model. *Ann Statistics* 6(2), 461–464 (1978).

31. Stephan, K. E., Penny, W. D., Daunizeau, J., Moran, R. J. & Friston, K. J. Bayesian model selection for group studies. *Neuroimage* 46, 1004–1017 (2009).

32. Rigoux, L., Stephan, K. E., Friston, K. J. & Daunizeau, J. Bayesian model selection for group studies — Revisited. *Neuroimage* 84, 971–985 (2014).

33. Cao, Y., Summerfield, C., Park, H., Giordano, B. L. & Kayser, C. Causal inference in the multisensory brain. *Neuron* 102, 1076-1087.e8 (2019).

34. Urai, A. E., Braun, A. & Donner, T. H. Pupil-linked arousal is driven by decision uncertainty and alters serial choice bias. *Nat Commun* 8, 14637 (2017).

35. Zariwala, H. A., Kepecs, A., Uchida, N., Hirokawa, J. & Mainen, Z. F. The limits of deliberation in a perceptual decision task. *Neuron* 78, 339–351 (2013).

36. Renart, A. & Machens, C. K. Variability in neural activity and behavior. *Curr Opin Neurobiol* 25, 211–220 (2014).

37. Qamar, A. T. *et al.* Trial-to-trial, uncertainty-based adjustment of decision boundaries in visual categorization. *Proc National Acad Sci* 110, 20332–20337 (2013).

38. Summerfield, C., Behrens, T. E. & Koechlin, E. Perceptual classification in a rapidly changing environment. *Neuron* 71, 725–736 (2011).

39. Norton, E. H., Fleming, S. M., Daw, N. D. & Landy, M. S. Suboptimal criterion learning in static and dynamic environments. *Plos Comput Biol* 13, e1005304 (2017).

40. Treisman, M. & Williams, T. C. A theory of criterion setting with an application to sequential dependencies. *Psychol Rev* 91, 68–111 (1984).

41. Lages, M. & Treisman, M. A criterion setting theory of discrimination learning that accounts for anisotropies and context effects. *Seeing Perceiving* 23, 401–434 (2010).

42. Drugowitsch, J., Mendonça, A. G., Mainen, Z. F. & Pouget, A. Learning optimal decisions with confidence. *Proc National Acad Sci* 116, 24872–24880 (2019).

43. Gupta, D. & Brody, C. D. Limitations of a proposed correction for slow drifts in decision criterion. *Arxiv* (2022) doi:10.48550/arxiv.2205.10912.

44. Carr, E. H. *What is History?* (University of Cambridge & Penguin Books, 1961).

45. Wichmann, F. A. & Hill, N. J. The psychometric function: I. Fitting, sampling, and goodness of fit. *Percept Psychophys* 63, 1293–1313 (2001).

46. Wichmann, F. A. & Hill, N. J. The psychometric function: II. Bootstrap-based confidence intervals and sampling. *Percept Psychophys* 63, 1314–1329 (2001).

47. Schütt, H. H., Harmeling, S., Macke, J. H. & Wichmann, F. A. Painfree and accurate Bayesian estimation of psychometric functions for (potentially) overdispersed data. *Vision Res* 122, 105–123 (2016).

48. Opheusden, B. van, Acerbi, L. & Ma, W. J. Unbiased and efficient log-likelihood estimation with inverse binomial sampling. *Plos Comput Biol* 16, e1008483 (2020).

49. Acerbi, L. & Ma, W. J. Practical Bayesian optimization for model fitting with Bayesian adaptive direct search. *Advances in Neural Information Processing Systems.* 1836–1846 (2017).

Acknowledgements

This research was supported by the Brain Research Program through the National Research Foundation of Korea (NRF) funded by the Ministry of Science and ICT (No. NRF-2021R1F1A1052020), and SNU R&DB Foundation (339-20220013).

Competing interests

The authors declare no competing interests.

- Supplementary Information -

What humans learn from corrective feedback for

perceptual decision-making

Hyang-Jung Lee[1], Heeseung Lee[1], Chae Young Lim[2], Issac Rhim[3],

and Sang-Hun Lee[1*]

[1]Department of Brain and Cognitive Sciences, Seoul National University, Seoul, South Korea

[2]Department of Statistics, Seoul National University, Seoul, South Korea

[3]Institute of Neuroscience, University of Oregon, Eugene, OR, U.S.A.

*To whom correspondence should be addressed;

Sang-Hun Lee

Rm 647 Bldg 220 Seoul National University,

1 Gwanak-ro, Gwanak-gu, Seoul 08826, South Korea

E-mail: visionsl@snu.ac.kr

Supplementary Fig. 1. Histograms of classification accuracies of the human participants and their model partners in the *ex ante* simulations. a,b, Across-individual distributions of the classification accuracy of the belief-based RL model (**a**) and BMBU (**b**) overlaid on those of the human participants. The models' choices were generated via *ex ante* simulations with a specific set of model parameters (**Supplementary Table 1**), the results of which are depicted in Fig.4 and Fig.5. The classification accuracy is measured by calculating the percentage of the trials in which the choice matched the feedback used in the actual experiment. The empty bars correspond to the histogram of human performances, the range of which is demarcated by the dashed vertical lines ([min, max]=[60.65%, 73.94%]). The average human classification accuracy was 67.85%. **a,** Comparison of classification accuracy between the belief-based RL model's simulation (red color) and the human choices. The model's *ex ante* simulation accuracy was not different from the human accuracy (P=0.1549; Null hypothesis: model's performance vector and humans' performance vector come from populations with equal means, unpaired two-tailed *t*-test). **b,** Comparison of classification accuracy between BMBU's simulation (green color) and the human choices. The model's *ex ante* simulation accuracy was not different from the human accuracy (P=0.3361, unpaired two-tailed *t*-test). There was no significant difference in classification accuracy between the value-updating model and BMBU (P=0.5691, unpaired two-tailed *t*-test).

Supplementary Fig. 2. Retrospective (left columns), prospective (middle columns), and subtractive (right columns) history effects in PSE for the 'Hybrid' model's ex post model simulations. Top and bottom rows in each panel show the PSEs associated with the *toi* episodes involving *correct* and *incorrect* feedback at *toi*. Symbols with error bars, mean±s.e.m across the 30 model agents, which correspond to their 30 human partners. The colors of the symbols and lines label choices (blue: *small* and yellow: *large*).

Supplementary Fig. 3. Maps of frequency deviations of the value-updating (a) and world-updating (b) model agents' classifications in the *ex post* simulations from the human decision-makers in the retrospective (left) and prospective (right) history effects. Each cell represents a pair of PDM episodes, as specified by the column and row labels. At each cell, the color represents how much the episode frequency observed in the model agents deviates from that observed in the corresponding human decision-makers. The results of statistical tests on these deviations are summarized in Fig.7e,f.

Supplementary Fig.4. Retrospective (left columns), prospective (middle columns), and subtractive (right columns) history effects in PSE for the human classification performances of Urai et al. (2017)'s work[1] (a) and Hachen et al. (2021)'s work[3] (b). a,b, We downloaded the datasets from the data-sharing platforms, analyzed them in the same way that we analyzed human observers in our work, plotted the results in the same format used for Fig.7a. Top and bottom rows in each panel show the PSEs associated with the *toi* episodes involving *correct* and *incorrect* feedback. Symbols with error bars, mean±s.e.m across human observers. The colors of the symbols and lines label choices (blue: *small* and yellow: *large*). The overall patterns of the PSEs plotted here appear similar to those plotted in Fig.7a, displaying the reversals in direction of stimulus-dependent feedback effects. When the same statistical tests used in our work were carried out, some of the data points at the stimuli with strong sensory evidence at *toi* significantly deviated from zero in the direction opposite to the feedback effect predicted by the value-updating scenario, as indicated by the asterisks. **a,** Sequential features of human observers (N=27) analyzed in our way from human dataset that once had been published[1], then analyzed in the previous study[2]. In this study, the participants performed a binary classification task on the difference in motion coherence by sorting the pairs of random-dot-kinematogram stimuli shown in two intervals (s1 and s2) into one of the two classes ('s1<s2' vs. 's1>s2') over consecutive trials. The presented stimuli were taken from 3 sets of difficulty levels (the difference between motion coherence of the test and the reference stimulus; easy: [2.5, 5, 10, 20, 30], medium: [1.25, 2.5, 5, 10, 30], hard: [0.625, 1.25, 2.5, 5, 20]). As done in the original study[2], we binned the trials into 8 levels by merging the trials of two neighboring coherence levels (e.g., the coherence levels of [0.625, 1.25]) into a single bin. Note that the coherence bins of [20, 35, 45, 48.75, 51.25, 55, 65, 80] (%s1) on the x-axis (50% represents the equal coherence between s1 and s2) are matched to the x-axis in Figure 8 of the previous study in which the same dataset had been used. Asterisks mark the significance of one-sample *t*-tests (uncorrected P<0.05, one-tailed in the direction of feedback effects) on the panel *toi+1* (*P=0.0272* for stimulus 80%) and on the panel *subtracted* (*P=0.0018 and 0.000318* for stimulus 20% and 80%). **b,** Sequential features of human observers (N=8) published in another previous study[3]. In this study, the participants performed a binary classification task on the speed of vibrotactile stimuli by classifying the speed of the presented vibration as 'low-speed(weak)' or 'high-speed(strong)'. Note that the nine-level stimuli of [-4,-3,-2,-1,0,1,2,3,4] on the x-axis followed how data were

encoded by the original study[3]. Asterisks mark the significance of one-sample *t*-tests (uncorrected P<0.05, one-tailed in the direction of feedback effects) on the panel *toi+1* (*P=0.004, 0.0048, and 0.04* for stimulus -4, -3, and -2) and on the panel *subtracted* (*P=0.034* for stimulus -4).

Supplementary Table 1. Parameters used for *ex ante* simulations

World		Value	
σ_m	25 levels [0.15, 3.27]	σ_m	25 levels [0.15, 3.27]
μ_0	0	b	0
σ_0	5	α	0.35
σ_s	1.5811	β	5
$\sigma_{m'}$	2.5	V_{init}	0.5
$\sigma_{diffusion}$	0.8		

Supplementary Table 2-1. Parameters recovered from fitting of the main models, world-updating model and value-updating model, to human choices (N=30)

World	Mean (standard deviation)	Value	Mean (standard deviation)
σ_m	0.86 (0.46)	σ_m	1.20 (0.30)
μ_0	0.04 (0.62)	b	0.02 (0.43)
σ_0	4.27 (1.22)	α	0.17 (0.20)
σ_s	0.84 (0.92)	β	7.43 (7.01)
$\sigma_{m'}$	3.70 (1.00)	V_{init}	0.92 (0.16)
$\sigma_{diffusion}$	3.20 (1.57)		

Supplementary Table 2-2. Parameters recovered from fitting of the rest of the models to human choices (N=30)

Hybrid	Mean (standard deviation)	Fixed	Mean (standard deviation)	Base	Mean (standard deviation)
σ_m	0.68 (0.33)	σ_m	1.52 (0.48)	σ_m	1.90 (0.50)
μ_0	0.01 (0.61)	μ_0	0.06 (0.40)		

σ_0	3.55 (1.28)				
σ_s	0.86 (1.03)				
$\sigma_{m'}$	3.84 (1.22)				
$\sigma_{diffusion}$	3.77 (1.87)				
α	0.15 (0.11)				
β	6.96 (2.83)				
V_{init}	0.882 (0.15)				

Supplementary Table 3. Statistical results on model behavior versus human behavior in terms of PSE measures

Model vs. Data	toi - 1 (20 conditions)			toi + 1 (20 conditions)			(toi+1) - (toi-1) (20 conditions)			ALL (60 conditions)	
	n.s.		signific-ance	n.s.		signific-ance	n.s.		signific-ance	n.s.	
Value	(13)	(13)	*(1) **(2) ***(4)	*(1) **(5) ***(1)	(10)	(9)	*(1) **(1) ***(8)	*(3) **(3) ***(5)	(8)	(9)	*(1) **(1) ***(10)	**(6) ***(5)	(31)	(31)
World	(20)	(20)	·	·	(20)	(20)	·	·	(20)	(20)	·	·	(60)	(60)
Hybrid	(20)	(20)	·	·	(17)	(19)	*(3)	*(1)	(19)	(20)	*(1)	·	(56)	(59)

Paired *t*-test | Wilcoxon signed rank

* : p<0.05
** : p<0.01 , Bonferroni corrected
*** : p<0.001 for 60 tests

References

1. Urai, A. E., Braun, A. & Donner, T. H. Pupil-linked arousal is driven by decision uncertainty and alters serial choice bias. *Nat Commun* 8, 14637 (2017).

2. Lak, A. *et al.* Reinforcement biases subsequent perceptual decisions when confidence is low, a widespread behavioral phenomenon. *eLife* 9, e49834 (2020).

3. Hachen, I., Reinartz, S., Brasselet, R., Stroligo, A. & Diamond, M. E. Dynamics of history-dependent perceptual judgment. *Nat Commun* 12, 6036 (2021).