Fast, accurate ranking of engineered proteins by receptor binding propensity using structure modeling

Xiaozhe Ding[1*], Xinhong Chen[1], Erin E. Sullivan[1], Timothy F. Shay[1] and Viviana Gradinaru[1*]

[1]Division of Biology and Biological Engineering, California Institute of Technology, 1200 E California Blvd, Pasadena, 91125, CA, USA.

*Corresponding authors. E-mails: xding@caltech.edu; viviana@caltech.edu;

Abstract

Deep learning-based methods for protein structure prediction have achieved unprecedented accuracy. However, the power of these tools to guide the engineering of protein-based therapeutics remains limited due to a gap between the ability to predict the structures of candidate proteins and the ability to assess which of those proteins are most likely to bind to a target receptor. Here we bridge this gap by introducing Automated Pairwise Peptide-Receptor AnalysIs for Screening Engineered proteins (APPRAISE), a method for predicting the receptor binding propensity of engineered proteins. After generating models of engineered proteins competing for binding to a target using an established structure-prediction tool such as AlphaFold-Multimer or ESM-Fold, APPRAISE performs a rapid (under 1 CPU second per model) scoring analysis that takes into account biophysical and geometrical constraints. As a proof-of-concept, we demonstrate that APPRAISE can accurately classify receptor-dependent vs. receptor-independent adeno-associated viral vectors and diverse classes of engineered proteins such as miniproteins targeting the SARS-CoV-2 spike, nanobodies targeting a G-protein-coupled receptor, and peptides that specifically bind to transferrin receptor or PD-L1. APPRAISE is accessible through a web-based notebook interface using Google Colaboratory (https://tiny.cc/APPRAISE). With its accuracy, interpretability, and generalizability, APPRAISE promises to expand the utility of protein structure prediction and accelerate protein engineering for biomedical applications.

Keywords: Protein engineering, AAV engineering, In silico screening, Receptor binding, Protein structure prediction

Introduction

Many protein-based biologics rely on precise targeting. As a result, protein engineers have devoted considerable effort to create specific binders, using methods such as directed evolution[1–4] and rational design[5–7]. Currently, the costly experimental evaluation of candidate binders using *in vitro* and *in vivo* assays presents a bottleneck, which can be eased using computational prioritization[8].

Two strategies are employed to predict protein functions: end-to-end sequence-function and two-step sequence-structure/structure-function. End-to-end, sequence-function models can predict complex functions such as enzyme activities or ion channel conductivity[9,10], which are challenging to calculate using physical principles[11]. However, such specialized models require domain-specific, high-quality training datasets for accurate prediction. In comparison, the two-step sequence-structure/structure-function strategy offers a more generalizable solution, particularly for functions with well-understood biophysical mechanisms such as protein-protein binding.

The rapid development of deep learning-based methods has brought unprecedented accuracy to the first step of the sequence-structure/structure-function strategy. Since AlphaFold2 (AF2)'s outstanding performance in CASP14 in 2020[12], several new deep learning-based structure-prediction tools have been released[13–24], providing a diverse tool set for generating protein models with atomic-level precision. While the original AlphaFold2 can predict peptide-protein complexes[25], there are enhanced versions such as AlphaFold-Multimer that can

model multi-chain complexes with greater accuracy[14,17]. Importantly, these structure-prediction tools allow the
generation of models in less than one GPU hour each, a level of throughput that experimental methods cannot
match.
The second step, ranking target binding propensities based on structure predictions, has been less attended
than the first. Structure-prediction tools generate confidence scores for predicted multimer models, such as
pLDDT and pTM scores (used by AF2)[12], and interface pTM scores (used by AF-Multimer)[14], which have
been used "off-label" as metrics to evaluate the probability of binding[17,26]. However, previous reports[27] and our
experience revealed that these scores alone are, in some cases, not reflective of binding propensities, particularly
when the interaction is weak or transient. Extracting additional information stored in the 3D coordinates using
biophysical principles may help improve the accuracy of binder ranking.
Ranking the binding probability of engineered proteins through modeled structures presents unique chal-
lenges. A frequent challenge is imposed by the high sequence similarity between candidate molecules. Engineered
protein variants are often constructed by modifying a short variable region in a common scaffold. Due to this
similarity, the energy difference between the candidate binders can be very small, sometimes buried in the error
of the energy function used for candidate ranking[28,29]. This problem is compounded by structure-prediction
methods that rely heavily on co-evolutionary information or homology, causing them to generate similar bind-
ing poses for the candidate proteins. Another major challenge is assessing a large number of predicted structure
models efficiently. Direct quantification of protein-protein interface energy using interpretable, physics-based
methods trades off between accuracy and speed[30]. For instance, molecular dynamics simulation methods can
cost more than 10^3 CPU hours per model. Faster, less rigorous methods with better-than-random ability to
predict the impact of interface mutations still require 1 CPU minute to 1 CPU hour per non-antibody-antigen
model[30]. In the post-AlphaFold era, an interpretable and efficient method of predicting the target binding of a
large number of models would greatly accelerate protein engineering efforts.
Recently, Chang and Perez utilized competitive modeling with AF-Multimer to demonstrate a correlation
between competition results and peptide binding affinities[27]. However, the study's method of assessing the
competition results necessitates a comparison of the modeled structures to an experimentally solved "native"
structure, which is not available for many engineered proteins.
To bridge the remaining gap between structure prediction and protein engineering, here we present
Automated Pairwise Peptide-Receptor AnalysIs for Screening Engineered proteins (APPRAISE), a readily inter-
pretable and generalizable method for ranking the receptor binding propensity of engineered proteins based on
competitive structure modeling and fast physics-informed structure analysis.

Results

The workflow of APPRAISE (Figure 1) comprises four main components. In the first step, pairs of peptides from
N candidate protein molecules (N^2 pairs total) are modeled in complex with a target receptor using a state-
of-the-art structure method such as AF-Multimer[14]. In the second stage, a simplified energetic binding score is
calculated for each peptide (i.e., the peptide of interest (POI) and its competitor). In the third optional step,
geometrical constraints for effective binding are applied to these scores. Finally, the result of each competition
is decided using the score difference between the POI and the competitor, and the peptides are ranked based
on the matrix of competition results.

Fig. 1 Workflow of Automated Pairwise Peptide-Receptor AnalysIs for Screening Engineered proteins (APPRAISE). First, peptides from the engineered protein candidates' receptor-binding region are modeled in competing pairs with the target receptor using tools like AF-Multimer or ESMFold. Second, a non-negative energetic binding score based on atom counting is calculated for each peptide. Third, in APPRAISE 1.1+, additional geometrical constraints critical for peptide binding, including the binding angle and pocket depth, are considered. Finally, a relative score for each match is calculated by taking the difference between the scores for the two peptides. The averaged relative scores form a matrix that determines the final ranking.

APPRAISE can accurately classify receptor-mediated brain transduction of viral vectors

We first developed APPRAISE to predict the binding propensities of engineered Adeno-Associated Viral (AAV) capsids for brain receptors. Recombinant AAVs are widely used as delivery vectors for gene therapy due to their relative safety as well as their broad and engineerable tropism. *In vivo* selections from libraries of randomized peptide-displaying AAV variants have yielded capsids that can transduce the animal brain [1,2,31–35], an organ tightly protected by the blood-brain barrier (BBB). Widely-known examples among these capsids are AAV-PHP.B[1] and AAV-PHP.eB[31], two AAV9-based[36] variants displaying short (7-9 amino acids) surface peptides. The two variants can efficiently deliver genetic cargo to the brains of a subset of rodent strains. Genetic and biophysical studies have revealed that the BBB receptor for PHP.B/PHP.eB in these strains is LY6A, a GPI-anchored membrane protein [37–39]. A dataset comprising peptide-displaying AAV capsids that were engineered in a similar way as PHP.B/eB was collected in order to train the APPRAISE method (Figure S1). Although binding between the AAV and the LY6A receptor is dynamic [40,41] and therefore challenging to quantitatively measure, we could infer the binary LY6A-binding profiles of AAV capsids from their differential brain transduction profiles in mouse strains with and without the receptor, producing a training set of peptide-displaying AAV capsids (Figure S1).

One challenge for modeling AAV capsids is that they are huge complexes made of 30,000+ amino acids (aa). In order to reduce computational costs for structure modeling and avoid complications arising from non-specific interactions, we modeled each AAV capsid variant using a single peptide spanning the engineered region (Figure 2a). This peptide (residues 587-594 in the VP1 sequence) includes 7 inserted residues and 8 contextual residues flanking the insertion. All of these residues are surface-exposed and may make direct contact with the receptor in the assembled capsid. Modeling this surface peptide (15 aa) is far less computationally intensive than modeling the entire capsid or even an asymmetric capsid subunit (500+ aa). In addition, compared to the latter, it may improve accuracy by eliminating competing interactions of residues normally buried in inter-subunit interfaces.

To discriminate relatively small differences in receptor binding propensities of candidate peptides, we modeled the peptides pairwise in competition for the target receptor [27,42]. To evaluate the competition results efficiently, we designed a score based on simple atom counting as a rough estimate of the interface free energy between the peptide of interest (POI) and the receptor in a structure model (Figure 2b). This score, which we term the energetic binding score ($B^{POI}_{energetic}$, simplified as B^{POI}_0), is a non-negative value calculated from the numbers of contacting and clashing atoms at the interface (Eq. 1). We describe the detailed rationale behind this score in the Methods.

$$B^{POI}_0 = B^{POI}_{energetic} = \max(N^{POI}_{contact} - 10^3 \cdot N^{POI}_{clash}, 0) \tag{1}$$

To take full advantage of the information encoded in the competitive models, we further derived a "relative binding score", inspired by the "specificity strategy" for protein-protein interface design[43]. The relative score takes the difference between the absolute scores for the POI and competitor peptide (Eq. 2), rewarding POIs destabilizing competing peptides' binding.

$$\Delta B_0^{POI,competitor} = B_0^{POI} - B_0^{competitor} \tag{2}$$

An engineered protein must meet certain geometrical constraints to effectively bind to a membrane receptor (Figure 2c). To utilize this geometrical information, which is likely unused by structure-prediction tools, we incorporated two essential constraints for effective binding: the binding angle and the binding depth (Figure 2c-e).

The first constraint comes from the angle a binding protein can make (Figure 2c,d). In modeling a peptide-receptor complex using the extracellular domain of the membrane receptor (e.g., LY6A), most structure predictors (e.g., AF-Multimer) would consider the whole surface of the domain to be accessible by the peptide. However, in biological conditions, the membrane-facing side of the receptor is inaccessible to the engineered peptide. This polarity of accessibility is a general property of any receptor that is closely anchored to a larger complex. To account for the potentially huge energy cost of an engineered peptide binding these inaccessible locations, we used a steep polynomial term to penalize peptides that bind to the anchor-facing part of the receptor (Figure 2d, defined in the Methods by Eq. 5). B_0^{POI} is adjusted by this geometrical constraint term, rectified to be non-negative, and $\Delta B_0^{POI,competitor}$ is also re-calculated accordingly, yielding new scores B_1^{POI} and $\Delta B_1^{POI,competitor}$ (Eq. 3).

$$\begin{aligned} \Delta B_1^{POI,competitor} &= B_1^{POI} - B_1^{competitor} \\ &= \max(B_{energetic}^{POI} + B_{angle}^{POI}, 0) \\ &\quad - \max(B_{energetic}^{competitor} + B_{angle}^{competitor}, 0) \end{aligned} \tag{3}$$

The second constraint concerns the binding pocket depth (Figure 2c,e). We hypothesized that peptides binding to a deeper pocket on the receptor surface might benefit from longer receptor residence time, which is vital for the efficacy of many therapeutics[44]. Based on this hypothesis, we included a pocket depth consideration in APPRAISE's scoring function. We used a relative pocket depth measurement instead of an absolute peptide-receptor distance measurement to avoid possible bias caused by the sizes of different receptors. We then used an odd polynomial term to reward peptides that insert into deep pockets on the receptor while penalizing peptides that attach to surface humps (Figure 2e, defined in the Methods by Eq. 6). The addition of the depth term gives us an adjusted score $\Delta B_2^{POI,competitor}$ (Eq. 4).

$$\begin{aligned} \Delta B_2^{POI,competitor} &= B_2^{POI} - B_2^{competitor} \\ &= \max(B_{energetic}^{POI} + B_{angle}^{POI} + B_{depth}^{POI}, 0) \\ &\quad - \max(B_{energetic}^{competitor} + B_{angle}^{competitor} + \\ &\quad\quad B_{depth}^{competitor}, 0) \end{aligned} \tag{4}$$

We compared different versions of scoring methods based on competitive modeling results using AF-Multimer modeling (Figure 2f-i). Individual matching scores with statistical significance were used to determine wins and losses, and the total matching points in a tournament were used to rank all candidate proteins (Methods). We found that simple atom-counting-based B_0^{POI} can already differentiate LY6A-binding peptides from non-binders (Figure 2g, j). Compared to B_0^{POI} alone, the relative score $\Delta B_0^{POI,competitor}$ showed improved prediction power, a ROC AUC of 0.800 and an AUPRC of 0.756 for the training dataset (Figure 2h, j, k). Adding both geometrical terms, B_{angle} and B_{depth}, into consideration indeed improved the prediction accuracy of the binding

Fig. 2 Binary classification of receptor-binding AAV capsids using physical and geometrical principles. See the next page for the caption.

score (Figure 2f, i-k), yielding a ROC AUC of 0.838 and an AUPRC of 0.845 (Figure 2j, k). Importantly, the improvement in ROC AUC mainly came from the low-false-positive-rate segment of the ROC curve, which is

Fig. 2 Binary classification of receptor-binding AAV capsids using physical and geometrical principles. a, a structure model of AAV-PHP.eB, highlighting the site for inserting the displayed peptide (orange) and the peptide used for APPRAISE modeling (yellow or orange). The left image shows the AAV capsid of 60 structurally identical subunits. The two images on the top right show a top view and a side view around the 3-fold axis, respectively. The three subunits that make the trimer are colored blue, cyan, and white. The sequence corresponding to the peptides is shown in the bottom right. **b**, An example showing the calculation process of a relative energetic binding score. The number of contacting atoms (< 5 Å) and the number of clashing atoms (< 1 Å) for each peptide in the competition are counted, and an absolute energetic binding score is calculated based on the counts according to Eq. 1. A difference between the two numbers, or the relative energetic binding score, is then calculated. The competition result between two peptides is determined using the average of relative binding scores across 10 replicates. The matrix of the mean scores is then used to rank the peptides of interest (POIs). **c**, A simplified geometrical representation of a peptide-receptor model, where the hull of the receptor is represented by an ellipsoid (blue). Point O: the center of mass of the receptor. Point A: the receptor's terminus attached to an anchor. Segment OB: the minor axis of the ellipsoid receptor hull. Point C: the deepest point on the candidate peptide (orange). θ: the binding angle of the peptide. d: the binding pocket depth of the peptide. **d**, The angle constraint function. Three representative scenarios with different binding angles are highlighted. **e**, The depth constraint function. Three representative scenarios with different binding depths are highlighted. **f**, Comparison of the averaged relative binding energy scores before geometry-based adjustments vs. after adjustments. **g-i** Heatmaps representing the matrix of mean scores of 22 AAV9-based capsid variants, including **g** mean absolute binding scores, **h** mean relative binding scores, and **i** mean relative binding scores that have considered both angle and depth constraints. All heatmap matrices were sorted by point-based round-robin tournaments (Methods). Bracketed numbers in the row labels are LY6A-binding profiles of the capsids inferred from experimental evidence (Figure S1). Each block in the heatmap represents the mean score measured from 10 independent models. **j-k**, comparison of different ranking methods used as binary classifiers to predict the LY6A-binding profile of 22 AAV9-based capsid variants. **j**, comparison between rankings given by different versions of APPRAISE scores using AF-Multimer as the structure prediction tool. **k**, comparison between rankings given by confidence scores of AF-Multimer versus rankings given by APPRAISE 1.2 using either AF-Multimer or ESMFold as prediction engines. The sequence and shape parameters of LY6A used for the modeling and analyses are included in Table S1.

crucial for *in silico* screening of engineered proteins. For clarity, we name the version that considers only the angle constraint (through score ΔB_1) APPRAISE 1.1 (Figure S2a) and the version that considers both angle and depth constraints (through score ΔB_2) APPRAISE 1.2 (Figure 2i).

We then compared AF-Multimer-based APPRAISE 1.2 with other structure-based peptide affinity ranking methods on the AAV dataset (Figure 2k). With this particular dataset, the model confidence scores pLDDT, pTM, and interface pTM failed to differentiate whether an AAV variant is an LY6A binder, producing worse-than-random prediction (ROC AUC < 0.5). This is possibly due to the dynamic nature of the interaction between LY6A-binding AAV variants and the receptor[40,41], which causes the confidence scores of the complex models to be generally low. APPRAISE 1.2 utilizing ESMFold as the structure prediction engine, however, performed at a comparable level to AF-Multimer-APPRAISE 1.2 (Figure S2b), with a ROC AUC of 0.895 and AUPRC of 0.818 (Figure 2k).

AF-Multimer-APPRAISE 1.2 ranking outperformed all other ranking methods at the low-false-positive-rate end of the ROC curve, with a true positive rate of 0.714 and no false positive predictions. The performance with stringent cut-off values is particularly relevant for protein engineering applications, where the goal is typically to identify a few positive binders from many negative, non-binding candidates. The superiority of AF-Multimer-APPRAISE 1.2 in dealing with this kind of imbalanced library is also evidenced by its highest AUPRC. Because of this, we chose to characterize AF-Multimer-APPRAISE 1.2 further. In the following text, 'APPRAISE' will be used to refer to AF-Multimer-APPRAISE 1.2 unless otherwise specified.

APPRAISE is generally applicable to diverse classes of engineered proteins

To determine the applicability of APPRAISE to different classes of engineered proteins, we applied the method to four classes of engineered protein binders targeting four representative receptors for therapeutics.

We first applied APPRAISE 1.2 to other short peptide binders (Figure 3a-d). In the first trial, the method successfully ranked a peptide selected by phage display to bind human transferrin receptor[4], a well-characterized BBB receptor, over non-binding counterparts from the same selection[4] (Figure 3a). In the second trial we evaluated two 47-aa-long, rationally-designed PD-L1 binding peptides[7] against the scaffold and length-matched AAV variable region fragments. Both designed PD-L1 binding peptides were clear winners, with the higher-affinity MOPD-1 peptide topping the list despite a high degree of sequence similarity (Figure 3c, Figure S3a).

We next tested whether APPRAISE 1.2 can be used to evaluate larger proteins, for example, computationally designed miniproteins (50-90 aa) that bind to the receptor-binding domain (RBD) of SARS-CoV-2 spike protein[5] (Figure 3e-g). Among the designed miniproteins, 5 can neutralize live SARS-CoV-2 virus *in vitro* with IC50 from 20 pM to 40 nM[5]. The APPRAISE 1.2 rankings of the 5 neutralizing miniproteins matched well with their IC50 rankings (Spearman's $\rho = 0.90$, $p = 0.037$, Figure 3g). The predictive accuracy of APPRAISE decreased when non-neutralizing miniproteins[5] and control AAV fragments were included (Spearman's $\rho = 0.88$, $p < 0.001$, Figure 3g); nevertheless, the top 4 binders still remained on the top. In contrast, the ranking given by the iPTM score of AF-Multimer only achieved a Spearman's ρ of 0.67 ($p = 0.035$).

Fig. 3 AF-Multimer-APPRAISE 1.2 accurately ranks binding propensities of different classes of engineered proteins. See the next page for the caption.

Fig. 3 AF-Multimer-APPRAISE 1.2 accurately ranks binding propensities of different classes of engineered proteins. a-b, APPRAISE 1.2 ranking of transferrin receptor-binding peptides and non-binding control peptides[4]. **a,** Pairwise score matrix and ranking of a panel of 12-aa peptides given by APPRAISE 1.2. Bracketed numbers in the row labels are experimentally determined transferrin receptor-binding profiles of each peptide[4]. **b,** A representative AF-Multimer model result of a binding peptide (blue) competing against a non-binding peptide (red) for binding to transferrin receptor. **c-d,** APPRAISE 1.2 ranking of PD-L1-binding peptides and non-binding control peptides[7]. **c,** Pairwise score matrix and ranking of a panel of 47-aa peptides given by APPRAISE 1.2. Bracketed numbers in the row labels show the PD-L1-binding profile of each peptide determined either experimentally (for MOPD-1, MNPD-1, and scaffold protein) or by expectation (for AAV9 and PHP.eB)[7]. **d,** A representative AF-Multimer model result of MOPD-1 (blue), a designed binding peptide, competing against a non-binding scaffold peptide (red) for binding to PD-L1. **e-g,** APPRAISE 1.2 ranking of SARS-CoV-2-S RBD-binding miniproteins[5]. **e,** Pairwise score matrix and ranking given by APPRAISE 1.2. Bracketed rankings in the row labels are determined based on experimentally-measured IC50 of each miniprotein to neutralize live SARS-CoV-2[5]. **f,** A representative AF-Multimer model result of LCB1 (blue), a SARS-CoV-2-S RBD-binding miniprotein, competing against an influenza virus-binding miniprotein[6] (red). **g,** A scatter plot showing the correlation between APPRAISE-predicted ranking and experimentally-measured IC50 ranking of all miniproteins tested. Blue points highlight binders that showed the capability of complete neutralization of the SARS-CoV-2 virus in the tested range of concentration *in vitro*. **h-j,** APPRAISE 1.2 ranking of β_2 adrenergic receptor-binding nanobodies[3]. **h,** Pairwise score matrix and ranking given by APPRAISE 1.2. Bracketed numbers in the row labels are rankings of experimentally-measured binding of each nanobody[3]. **i,** A representative AF-Multimer model result of Nb6B9 (blue), the strongest evolved binder to active β_2AR, competing against Nb80 (red), the nanobody used for the evolution. **j,** A scatter plot showing the correlation between APPRAISE-predicted ranking and experimentally-measured ranking by β_2AR binding of all nanobodies tested. Each block in the heatmap represents the mean score measured from 10 independent models. For comparison, rankings given by AF-Multimer-APPRAISE 1.0, ESMFold-APPRAISE 1.2, and interface pTM of SARS-Cov2-S RBD-binding miniproteins and β_2 adrenergic receptor-binding nanobodies are shown in Figure S4. **k,** A summary of APPRAISE rankings of eight miniproteins[45] designed to bind to eight different target receptors. Figure S5 displays the score matrices utilized for rankings with individual receptors. Tables S1 and S2 include sequences and shape parameters of all receptors.

We also used APPRAISE to rank 6 nanobodies (120 aa) that were evolved experimentally[3] with highly similar scaffolds (Figure S3b) to bind to an activated conformation of β_2 adrenergic receptor (β_2AR), a G-protein-coupled receptor (GPCR) (Figure 3h-j). APPRAISE 1.2 correctly found the strongest evolved binder and placed the parent (the weakest binder among all candidates) at the bottom (Figure 3h). The overall predicted ranking correlated well with the ranking from experimentally determined binding readouts[3] (Spearman's $\rho = 0.89$, $p = 0.02$, Figure 3j), surpassing the prediction given by the iPTM score of AF-Multimer (Spearman's $\rho = 0.49$, $p = 0.329$, Figure S4f). The ability of APPRAISE to rank the binding affinity of nanobodies, a widely-used therapeutic modality, has the potential to expand its value in drug design and development. However, predicting the structure of larger adaptive immune complexes like IgG-antigen complexes is still considered a difficult task in general, and further improvements in the underlying structure prediction methods that APPRAISE relies on are required to generalize the ranking capability to these targets.

To evaluate the cross-receptor capabilities of APPRAISE, we used the method to rank eight recently developed miniproteins binding eight different therapeutically significant receptors[45]. This ranking included all receptors with a ligand binding domain that is smaller than 250 aa in the Cao et al. study. APPRAISE accurately identified the correct binder within the top 3 in every instance, and 6 out of 8 times, the correct binder was ranked as the top 1 (Figure 3k, Figure S5).

We next compared the performance of AF-Multimer-APPRAISE 1.2 to alternative methods on both the miniprotein dataset and the nanobody datasets. AF-Multimer-APPRAISE 1.2 again yielded the most accurate predictions when compared to AF-Multimer-APPRAISE 1.0, ESMFold-APPRAISE 1.2, or interface pTM scores given by AF-Multimer (Figure S4), reflected by higher Spearman's correlation to experimental rankings. ESMFold-APPRAISE 1.2 failed completely with the miniprotein dataset (Figure S4b). Upon further inspection, we found that the unfolded SARS-Cov-2-S RBD structure in ESMFold-generated complex models can explain the failed ranking prediction.

Without any fine-tuning, AF-Multimer-APPRAISE 1.2 demonstrated consistent prediction ability for ranking all four classes of proteins, including experimentally-selected and rationally-designed peptides, computationally-designed miniproteins, and nanobodies. Realizing the potential general applicability of the APPRAISE method, we have created a web-based notebook interface to make it readily accessible to the protein engineering community (Figure S6).

HT-APPRAISE screening can identify novel receptor-dependent capsid variants

We next adapted APPRAISE 1.2 for *in silico* screening. The computational cost in the pairwise competition mode grows quadratically with the number of input variants, which is unsuitable for high-throughput screening. To address this scalability issue, we designed a two-stage screening strategy named high-throughput (HT)-APPRAISE (Figure 4a). The first stage aims to shrink the size of the variant library using a less accurate yet more scalable strategy. Variants are randomly pooled into groups and compete for receptor binding. The

variants are then ranked by their absolute score $\overline{B}_2^{POI}$. The number of pooled competitions grows linearly with the number of variants in the starting library, making the first stage of HT-APPRAISE suitable for larger libraries. In the second stage, the top variants selected from the first stage compete pairwise, yielding a matrix of $\overline{\Delta B}_2^{POI,competitor}$ and a more accurate ranking.

We used our HT-APPRAISE *in silico* screening to find LY6A binders in a library of 100 capsid variants (Figure 4b-c). This library is composed of 97 capsid variants randomly chosen from a list of 9,000 variants showing superior brain enrichment in C57BL/6J mice compared to the wild-type AAV9 capsid[2] as well as three spiked-in capsids: the variants PHP.B and PHP.D, and the wild-type AAV9 (Table S4). PHP.D is a brain-transducing capsid identified in a recent directed evolution campaign in our lab, the relevant receptor for which was unknown.

The HT-APPRAISE screening took 24 hours using 3 parallel Google Colaboratory GPU sessions and a laptop computer. In both stages of the HT-APPRAISE, the most time-consuming step was the structural prediction, which took approximately 0.1-1 GPU minute per peptide-LY6A model (a complex made of 114 aa total). In comparison, the time cost for structural analysis was negligible, taking less than 1 second per model on a CPU.

After the first stage of screening, both PHP.D and PHP.B appeared in the top 15% of the library (ranked by $\overline{B}_2^{POI}$) (Figure 4b).). In the second stage, the top 18 capsids were ranked using pairwise APPRAISE 1.2 (Figure 4c). PHP.D and PHP.B were the 1^{st} and the 4^{th} in the final ranking.

The most intriguing aspect of PHP.D's result is that its variable region bears little sequence similarity to any of the LY6A-dependent variants used to develop the APPRAISE method (Figure 4d-e). To confirm this prediction result, we experimentally tested PHP.D's LY6A dependency. An *in vitro* viral infection assay showed that PHP.D indeed exhibits LY6A-enhanced transduction of HEK293T cells (Figure 4f). In addition, *in vivo* systemic delivery of PHP.D packaging a ubiquitously-expressed fluorescent protein revealed that the brain transduction capability of this capsid variant is restricted to LY6A-expressing mouse strains (Figure 4g). The ability of HT-APPRAISE to identify binders with distinct sequences highlights the generalizability of the physics-informed, sequence-structure/structure-function strategy.

Fig. 4 An *in silico* **HT-APPRAISE screening of a medium-sized AAV library identifies a LY6A-dependent variant with a distinct sequence.** See the next page for the caption.

Fig. 4 An *in silico* HT-APPRAISE screening of a medium-sized AAV library identifies a LY6A-dependent variant with a distinct sequence. a, A schematic showing the two-stage strategy for *in silico* screening of a variant library. In the first stage, M variants of interest are randomly pooled into groups of 4 and compete for receptor binding. At least two parallel groupings are used to reduce bias. Each peptide's mean absolute binding score in the pool competitions is used for selecting the top N variants. In the second stage, the top N variants compete pairwise using standard APPRAISE for a more accurate ranking. **b-c,** Results from a proof-principle screening with 100 AAV9-based variants, including the wild-type control and variants with 7 aa insertions. Using a standard random algorithm, a total of 97 variants were picked from a list of 9000 variants [2] that demonstrated higher brain enrichment than the wild-type AAV9 after one round of screening in C57BL/6J mice ("Round 2 library" in [2]). PHP.B and PHP.D, two known brain-transducing capsids, and wild-type AAV9, are spiked into the library. Table S4 shows the peptide sequences used in the screening. **b,** Stage 1 result. Dots indicate absolute binding scores measured from individual structure models. Horizontal bars indicate the mean scores of each variant. Scores of PHP.D (ranked 3^{rd}), PHP.B (ranked 13^{th}), and AAV9 (ranked 100^{th}) are highlighted. **c,** Stage 2 result. Rows corresponding to scores of PHP.D (ranked 1^{st}) and PHP.B (ranked 4^{th}) are highlighted. Each block in the heatmap represents the mean score measured from 10 independent models. **d-g,** Characterization of PHP.D, a variant that tops the *in silico* screening. **d,** Sequence alignment and phylogenetic tree of known LY6A-dependent brain transducing variants. The sequence of PHP.D is very different from all other variants. The alignment and sequence distances were generated with Clustal Omega [46]. The colored alignment is plotted with Snapgene software. Blue: conserved hydrophobic residues; green: conserved hydrophilic residues; orange or yellow: conserved unique residues (glycine or proline). **e,** Sequence identity matrix of the LY6A-dependent variants. **f,** *In vitro* infectivity assay in HEK293T cells. PHP.D and PHP.eB showed LY6A-enhanced transduction, while the negative control PHP.C2 did not show LY6A-enhanced transduction. AAV capsids carrying a fluorescent protein expression cassette were applied to HEK293T cells either transfected with LY6A or not at 5×10^8 vg per well in a 96-well plate. Images were taken 24hr after transduction. n=3 per condition. Scale bar, 250 μm **g,** *In vivo* brain transduction of PHP.D vs. AAV9 in two mice strains. PHP.D showed transduction only in the LY6A+ strain, C57BL/6J. AAVs carrying CAG-mNeonGreen transgene were injected intravenously at 3×10^{11} vg per animal, and the tissues were harvested and imaged 3 weeks after injection. n=3 per condition. Scale bar, 2 mm.

Discussion

Here we describe APPRAISE, a structure-based, physics-informed method that accurately ranks receptor binding propensities of engineered proteins. APPRAISE uses a competitive, pairwise modeling strategy to capture affinity differences between even proteins with similar sequences and takes into account biophysical and geometrical principles.

The competition-based structure modeling strategy addresses the challenge of assessing small differences in binding affinity with high accuracy. This challenge was highlighted by a recent benchmarking study using AF2 models for molecular docking of small-molecule antibiotic candidates. The authors reported that the prediction power of the direct physics-based scoring is no better than a random model [47]. By contrast, a competition-based modeling strategy might have helped cancel the shared noise and amplify the signal arising from the small affinity differences. The competition setup, in many cases, forces the structure-prediction neural network to put only the more probable binder close to the receptor (Figure 3 d, i), converting a small probabilistic difference into a binary output.

The generalizability of AF-Multimer-APPRAISE is shown by its accurate ranking of five different classes of engineered proteins and twelve different receptors. This generalizability may be grounded in the physical principles learned by AlphaFold [27,48]. For example, consistent with the report of [27], we also observed a recurring trend in our tests with AF-Multimer where binders ranked at the top are frequently predicted with secondary structures, which may indicate a stable binding interface. While we were revising this manuscript, APPRAISE has been applied in various scenarios, extending beyond the examples presented in this manuscript. For instance, in a recent study uncovering previously unknown blood-brain barrier receptors used by engineered AAVs, APPRAISE helped classify the AAVs based on their receptor specificity [49].

A key feature of APPRAISE is that its analysis module uses only information stored in the 3D coordinates, making the modular pipeline compatible with other computational tools for protein engineering. For example, the structure-prediction tool used in APPRAISE can be replaced by any current or future structure-prediction tool. Moreover, APPRAISE can be an orthogonal validation tool for structure-based protein design methods [50–52], particularly those that rely on optimization of predicted confidence scores [53].

The scalable, two-stage HT-APPRAISE strategy we designed allows *in silico* screening of protein candidates for receptor binding (Figure 4). Such screening can help prioritize leading candidates during drug discovery, reducing the huge time, financial, and environmental costs of experimental validation. For example, the computational tasks needed to screen 100 AAV variants that we presented here (Figure 4) could be completed within 24hr with research-grade computational resources. *In vivo* characterization of the capsids at a comparable scale would have taken several months.

As a competition-based ranking method, APPRAISE faces several intrinsic limitations. One such limitation is that APPRAISE only outputs the relative, not the absolute, probability of binding. Therefore, unless there are positive controls with known binding to compare against, a variant's position at the top of the ranking does not indicate that the variant has an experimentally detectable binding affinity. Another limitation lies in APPRAISE's assumption that the binding of competing proteins is mutually exclusive. Counterexamples arise if the competing proteins exhibit cooperative binding or attach to epitopes situated at a considerable distance. Furthermore, certain candidate proteins may exhibit a tendency to interact with one another rather than with the designated receptor. Additionally, the geometrical scores utilized in APPRAISE 1.1+ were computed assuming the receptor has a predominantly convex structure. Thus, these scores are most effective when applied to single protein domains with convex shapes.

Other limitations of APPRAISE may arise from the protein structure prediction engine that it relies on. For example, ESMFold-APPRAISE fails when the language-model-based structure prediction tool cannot properly fold the protein in a complex (Figure S4b). At the same time, AF-Multimer-APPRAISE results can be biased by the specific selection of multiple-sequence alignments due to the dependence on co-evolutionary information by AF-Multimer. So far, the APPRAISE pipeline's ability to accurately rank IgG antibodies is limited due to the complexity of predicting antibody-antigen complex structures. Moreover, the accuracy and speed of APPRAISE may be compromised when the modeled proteins contain long disordered regions or large domains that are unnecessary for binding. As a result, pre-screening of several truncated protein constructs for minimal folding domains with the particular structure prediction tool (analogous to the common practice in structural biology) is always helpful. Additionally, the APPRAISE method is ineffective in ranking weak binders in a pool (e.g., Figure 3g), perhaps because the predicted structures do not offer many opportunities for meaningful interaction, resulting in near-zero competition scores. Fortunately, this should not be a practical concern for most protein engineering applications since the most valuable candidates usually bind with higher affinities. Considering these limitations, it is essential to conduct spot checks on model results to confirm their physical soundness.

While APPRAISE has succeeded in ranking the binding propensities of different protein variants, its accuracy and speed could be further improved. For example, the parameters of APPRAISE 1.2's scoring function have only been minimally tuned to proper orders of magnitude to decrease the risk of over-fitting (Methods). With further fine-tuning of parameters and the ever-growing power of protein structure prediction, the APPRAISE method promises to streamline the process of engineering protein-based therapeutics.

Methods

Structure Modeling

Modeling of peptide-receptor complexes using AF-Multimer

Peptide-receptor models are modeled using Colabfold (Python package index: alphafold-colabfold 2.1.14), an implementation of integrated multiple-sequence alignment generation with MMseqs2 and structure modeling with AF-Multimer-v2[14,15,54–57]. First, batches of *.fasta files containing combined receptor sequences (Tables S1 and S2) and peptide sequences for the pairwise competition or pooled competition, where the ":" symbol separates the protein chains, are prepared using the function (appraise.input_fasta_prep.get_complex_fasta()). Second, the *.fasta files are used as input files for the "batch" Jupyter notebook in the Colabfold package, and the notebook is run on Google Colaboratory using a V100 SXM2 16GB GPU or an A100 SXM4 40GB GPU. The settings used for the modeling are listed below:

```
msa_mode = "MMseqs2 (UniRef+Environmental)"
num_models = 5
num_recycles = 3
stop_at_score = 100
use_custom_msa = False
use_amber = False
use_templates = True
model_type = "auto" #or "alphafold2_multimer_v2"
```

Modeling of peptide-receptor complexes using ESMFold

To model the peptide-receptor complexes using ESMFold, a process analogous to the one employed for AF-Multimer modeling is implemented. First, batches of *.fasta files containing combined receptor sequences (Tables S1 and S2) and peptide sequences for the pairwise competition or pooled competition, where the protein chains are separated by a poly-glycine linker (30 glycine residues), are prepared using the same Python function(get_complex_fasta()) mentioned above. Second, the *.fasta files are used as input files for a custom Jupyter notebook with codes adapted from the Colabfold package for batch modeling using ESMFold, and the notebook is run on Google Colaboratory using an A100 SXM4 40GB GPU. The custom Colab notebook is included in the APPRAISE package:

```
appraise/misc_utilities/ColabFold_ESMFold_batch_run.ipynb.
```

Physics-informed analysis of individual structure models

The output folder containing *.pdb files generated by alphafold-colabfold is downloaded to a local computer for processing. Key parameters in a predicted structure model are measured, and the measurements are used to generate binding scores for each peptide in a model.

Automated quantification of the peptide-receptor models

The structure models are analyzed using PyMOL 2.3.3 using a custom PyMOL script. Briefly, the script loads all *.pdb models in a directory, extracts metadata from the file names, and measures the relevant contact atom numbers, angles, and distances. The measurements are saved as a *.csv file. The custom PyMOL script is included in the APPRAISE package:

```
appraise/pymol_quantify_peptide_binding.py.
```

Measurement of the R_{minor} of the receptor hull

The receptor shape parameter R_{minor}, which is necessary for APPRAISE 1.2, is obtained by measuring the shape parameters of an AlphaFold-modeled receptor structure. Briefly, the monomeric receptor (Table S1) is modeled using Colabfold (Python package index: alphafold-colabfold 2.1.14). The top model is then analyzed using HullRad v8.1[58] to obtain its major axis diameter D_{max} and aspect ratio P. R_{minor} is then calculated using the formula $R_{minor} = D_{max}/P/2$. Before the analysis, R_{minor} measurement is manually added as a column to the pandas dataframe storing PyMOL measurements with the column "R_minor".

Construction and calculation of $B_{energetic}$

We defined a contact atom as a non-hydrogen atom of either the receptor or the peptide within 5Å of the binding partner in the peptide-receptor model since atoms within this distance cutoff are responsible for most protein-protein interactions[59]. We defined a clashing term as the number of non-hydrogen atoms in the peptide that are within 1Å of the receptor since this distance is smaller than the typical diameter of an atom and can cause a huge Van der Waals strain. To find the suitable weight for the clashing term, we estimated the relative

energy scales using Lennard-Jones' potential. We concluded that an order of magnitude of 10^3 should be proper (Eq. 1). Since most interfaces between the engineered peptide and the receptor have up to a few hundred non-hydrogen atoms (tens of residues) in the interface, this heavy weight for the clashing atom practically sets the B_0^{POI} of any peptide with steric clashing against the receptor to 0. Thus, Eq. 1 is practically equivalent to:

$$B_{energetic}^{peptide} = \begin{cases} N_{contact}^{peptide}, & \text{if } N_{clash}^{peptide} = 0 \\ 0, & \text{if } N_{clash}^{peptide} >= 1 \end{cases}$$

Construction and calculation of geometrical scores

The binding angle θ is defined as the angle between the vector from receptor center of mass to receptor anchor $\overrightarrow{OA}$ and the vector from receptor center of mass to peptide center of mass $\overrightarrow{OC'}$ (Figure 2c. Note that the peptide center of mass C' is usually very close to the deepest point C, and therefore point C and point C' are undifferentiated in this schematic). A steep function is used to penalize inaccessible binding angles that are close to the anchor point:

$$B_{angle}^{peptide} = \begin{cases} -10^3 \cdot (1 - \frac{\theta}{\frac{\pi}{2}})^{10}, & \text{if } \theta < \frac{\pi}{2} \\ 0, & \text{if } \frac{\pi}{2} <= \theta <= \pi \end{cases} \tag{5}$$

The definition of binding depth d is a simplification of previously defined travel depth[60]: we first calculate the hydrodynamic radius of the hull of the receptor at the minor axis (R_{minor}) using HullRad[58], and then take the difference of the distance between the "closest point on the peptide" to the receptor center and R_{minor}. The ratio between the difference and R_{minor} is defined as the depth. In other words, binding depth $d = \frac{\|OB\| - \|OC\|}{\|OB\|}$ where $\|OB\|$ is the minor axis radius (in Å) of the receptor hull when considering it as an ellipsoid (Figure 2c), and $\|OC\|$ is the distance (in Å) between the center of mass of the receptor and the closest point on the peptide (Figure 2c). An odd polynomial function is used to construct the score to reflect both the positive effect of a deep binding pocket and the negative effect of a convex binding site:

$$B_{depth}^{peptide} = 10^2 \cdot d^3 \tag{6}$$

Calculation of scores for each peptide in a model

The total binding scores for each peptide in a model are calculated using Eqs. 1-4 in the main text.

Generation of the score matrix and a ranking

The total binding scores of a POI vs. a competitor across 10 replicate models are averaged to get $\overline{\Delta B}^{POI,competitor}$ ($\overline{\Delta B_0}^{POI,competitor}$ for APPRAISE 1.0, $\overline{\Delta B_1}^{POI,competitor}$ for APPRAISE 1.1, or $\overline{\Delta B_2}^{POI,competitor}$ for APPRAISE 1.2). These averaged competition scores are then used to create a matrix and are plotted as a heatmap.

In the final score matrix, the POIs are ranked using a point-based round-robin tournament system[61] to avoid the bias caused by individual competitions with unusually high scores. Briefly, each $\overline{\Delta B}^{POI,competitor}$ in the matrix is considered as the match result between a POI and a competitor. A POI gains 1 point for winning over each match and loses 1 point for losing each match. (In the cases when $|\overline{\Delta B}^{POI,competitor}|$ does not reach the threshold of $p < 0.05$ using a one-sample, two-sided, Student's t test (degree of freedom=9), the match is called a tie, and the POI gets 0 points from the match.)

Code Availability

All code is available in a GitHub repository:
   github.com/GradinaruLab/APPRAISE

In addition, APPRAISE is made accessible through a web-based notebook interface using Google Colaboratory. The notebook can be found in the GitHub repository above or be directly accessed through the link:
   tiny.cc/APPRAISE

The Colab-APPRAISE notebook includes pre-filled templates that can be used to demonstrate the workflow of APPRAISE. More demos can be found under the `demo` folder in the GitHub repository.

Experimental Validations

In vitro infectivity assay

HEK293T (ATCC, CRL-3216) cells were seeded in 6-well plates at 80% confluency and maintained in Dulbecco's Modified Eagle Medium (DMEM) supplemented with 5% fetal bovine serum (FBS), 1% non-essential amino acids (NEAA), and 100 U/mL penicillin-streptomycin at 37°C in 5% CO2. Cells were transiently transfected with 2.53 µg plasmid DNA encoding an expression cassette for the LY6A receptor. The following day, receptor-expressing cells were transferred to black, clear-bottom 96-well plates at 20% confluency and maintained in FluoroBrite™ DMEM supplemented with 0.5% FBS, 1% NEAA, 100 U/mL penicillin-streptomycin, 1x GlutaMAX, and 15 µM HEPES at 37°C in 5% CO2. Engineered AAV variants packaging a CAG-mNeonGreen transgene were dosed in triplicate at 5E8 vg per well once the cells were attached. Plates were imaged 24 hours after AAV was introduced to cells with a Keyence BZ-X700 using a 4x objective and NucBlue™ Live ReadyProbes™ Reagent (Hoechst 33342) to autofocus each well.

In vivo mouse experiment

For all the experiments performed in this study, the animals were randomly assigned, and the experimenters were not blinded while performing the experiments unless mentioned otherwise. All animal procedures in mice were approved by the California Institute of Technology Institutional Animal Care and Use Committee (IACUC), Caltech Office of Laboratory Animal Resources (OLAR), and were carried out in accordance with guidelines and regulations.

For the profiling of the novel AAVs in C57BL/6J mice (The Jackson Laboratory, 000664) and BALB/cJ mice (The Jackson Laboratory, 000651), the AAV vectors were injected intravenously via the retro-orbital route to 6-8 week-old adult mice at a dose of 3×10^{11} vg per mouse. Retro-orbital injections were performed as described previously[62]. To harvest the tissues of interest after 3 weeks of expression, the mice were anesthetized with Euthasol (pentobarbital sodium and phenytoin sodium solution, Virbac AH) and transcardially perfused using 50 mL of 0.1 M phosphate-buffered saline (PBS) (pH 7.4), followed by 50 mL of 4% paraformaldehyde (PFA) in 0.1 M PBS. The organs were collected and post-fixed 24 h in 4% PFA at 4°C. Following this, the tissues were washed with 0.1 M PBS and stored in fresh PBS-azide (0.1 M PBS containing 0.05% sodium azide) at 4°C. Before imaging, the 100 µm tissue slices were cut using a Leica VT1000S. Brain images were acquired with a Zeiss LSM 880 confocal microscope using a Plan-Apochromat 10× 0.45 M27 (working distance 2.0 mm) objective. Zen Black 2.3 SP1 was used to process the images.

Ethical approval

All animal procedures in mice were approved by the California Institute of Technology Institutional Animal Care and Use Committee (IACUC), Caltech Office of Laboratory Animal Resources (OLAR) and were carried out in accordance with guidelines and regulations.

Materials Availability

The plasmid expressing the AAV-PHP.D capsid reported in this manuscript is deposited in Addgene (ID: 197055).

Supplementary Information

Supplementary Figures

Variant name	Ref.	Modeled peptide sequence	C57BL/6J brain?	BALB/c brain?	Inferred LY6A dependency
PHP.B	Deverman et al.	AQTLAVPFKAQAQTG	✓	✗	True[*]
PHP.eB	Chan et al.	DGTLAVPFKAQAQTG	✓	✗	True[**]
PHP.B2	Deverman et al.	AQSVSKPFLAQAQTG	✓	✗	True[*]
PHP.B3	Deverman et al.	AQFTLTTPKAQAQTG	✓	✗	True[*]
PHP.N	Kumar et al.	AQTLAVPFSNPAQTG	✓	✗	True
PHP.V1	Kumar et al.	AQTALKPFLAQAQTG	✓[†]	✗	True
PHP.V2	Kumar et al.	AQTTLKPFLAQAQTG	✓[†]	✗	True
PHP.C1	Kumar et al.	AQRYQGDSVAQAQTG	✓	✓	False
PHP.C2	Kumar et al.	AQWSTNAGYAQAQTG	✓	✓	False
PHP.C3	Kumar et al.	AQERVGFAQAQAQTG	✓	✓	False
AAV9	Gao et al.	AQ-------AQAQTG	✗	✗	False[**]
MaCPNS1	Chen et al.	AQPHEGSSRAQAQTG	✗	-	False
MaCPNS2	Chen et al.	AQPNASVNSAQAQTG	✗	-	False
NB-1	Kumar et al.	AQSLDTTKGAQAQTG	✗	-	False
NB-2	Kumar et al.	AQESRGLSLAQAQTG	✗	-	False
NB-3	Kumar et al.	AQMIRGLDTAQAQTG	✗	-	False
NB-4	Kumar et al.	AQNGDLTRSAQAQTG	✗	-	False
NB-5	Kumar et al.	AQTKREIDYAQAQTG	✗	-	False
NB-6	Kumar et al.	AQMHHGMEIAQAQTG	✗	-	False
NB-7	Kumar et al.	AQTPRMDTFAQAQTG	✗	-	False
NB-8	Kumar et al.	AQVHRDLNFAQAQTG	✗	-	False
NB-9	Kumar et al.	AQTARKEEFAQAQTG	✗	-	False

* LY6A binding confirmed by cell binding assay
** LY6A dependency confirmed by biochemical and genetic assays
† Endothelial-restricted transduction

Fig. S1 Prior experimental studies revealing the receptor dependency of some brain-transducing AAV variants. **a,** A schematic showing an AAV capsid binding to a blood-brain barrier (BBB) receptor that is only expressed at a high level on the endothelial cells of certain mouse strains[37–39]. **b,** A schematic showing how we can infer whether an AAV capsid can use LY6A, a mouse BBB receptor, by characterizing its brain transduction across different strains. A capsid with strain-restricted brain transduction in C57BL/6J mice is likely LY6A-dependent, while a capsid with cross-strain brain transduction or which does not transduce the brain is not LY6A-dependent. **c,** A table summarizing all 22 capsids used in Figure 2 with their source literature, sequence, brain transduction profile, and inferred LY6A dependency.

Fig. S2 Heatmaps representing score matrices of AF-Multimer-APPRAISE 1.1 and ESMFold-APPRAISE 1.2.

Fig. S3 Sequence identity between some engineered proteins. Sequence identity matrix generated with Clustal Omega[46] for **a)** PD-L1-binding peptides and **b)** β_2 adrenergic receptor-binding nanobodies, demonstrating that these proteins share similar sequences.

Fig. S4 Ranking protein binders using alternative methods. Rankings of two groups of peptides analyzed in Figure 3g, j based on **a, d)** AF-Multimer-APPRAISE 1.0, **b, e)** ESMFold-APPRAISE 1.2, and **c, f)** interface pTM given by AlphaFold-Multimer.

Fig. S5 Score matrices for APPRAISE rankings of miniprotein binders with individual receptors. Detailed rankings of miniproteins with individual receptors summarized in Figure 3k using AF-Multimer-APPRAISE 1.2. The miniprotein sequences were from [45].

Fig. S6 A screenshot of the interface of Colab-APPRAISE. APPRAISE can be easily accessed by running a web-based notebook on Google Colaboratory (https://tiny.cc/APPRAISE).

1198 **Table S1** Receptor sequences and parameters used for APPRAISE analysis (part 1 of 2)

Receptor name	Organism	Uniprot accession ID	Domain used for modeling	Residue indices (start-end)	D_{max} (Å)	Axial ratio	R_{minor} (Å)	Anchor site	Sequence used for modeling
LY6A	Mus musculus (Mouse)	P05533	Mature protein	27-110	46.68	1.74	13.4	C-term	LECYQCYGVPFETSCPSITCPYPDGVCVTQEAAVIVDSQ TRKVKNNLCLPICPPNIESMEILGTKVNVKTSCCQEDLC NVAVP
PD-L1	Homo sapiens (Human)	Q9NZQ7	V domain	18-132	46.50	1.51	15.4	C-term	AFTVTVPKDLYVVEYGSNMTIECKFPVEKQLDLAALIVY WEMEDKNIIQFVHGEEDLKVQHSSYRQRARLLKDQLSLG NAALQITDVKLQDAGVYRCMISYGGADYKRITVKVNA
Beta-2 adrenergic receptor	Homo sapiens (Human)	P07550	TM1-TM7	29-342	93.8	2.23	21.0	N-term	DEVWVVGMGIVMSLIVLAIVFGNVLVITAIAKFERLQTV TNYFITSLACADLVMGLAVVPFGAAHILMKMWTFGNFWC EFWTSIDVLCVTASIETLCVIAVDRYFAITSPFKYQSLL TKNKARVIILMVWIVSGLTSFLPIQMHWYRATHQEAINC YANETCCDFFTNQAYAIASSIVSFYVPLVIMVFVYSRVF QEAKRQLQKIDKSEGRFHVQNLSQVEQDGRTGHGLRRSS KFCLKEHKALKTLGIIMGTFTLCWLPFFIVNIVHVIQDN LIRKEVYILLNWIGYVNSGFNPLIYCRSPDFRIAFQELL CL
Transferrin receptor 1	Homo sapiens (Human)	P02786	Ectodomain	122-760	86.50	1.47	29.4	N-term	LYWDDLKRKLSEKLDSTDFTGTIKLLNENSYVPREAGSQ KDENLALYVENQFREFKLSKVWRDQHFVKIQVKDSAQNS VIIVDKNGRLVYLVENPGGYVAYSKAATVTGKLVHANFG TKKDFEDLYTPVNGSIVIVRAGKITFAEKVANAESLNAI GVLIYMDQTKFPIVNAELSFFGHAHLGTGDPYTPGFPSF NHTQFPPSRSSGLPNIPVQTISRAAAEKLFGNMEGDCPS DWKTDSTCRMVTSESKNVKLTVSNVLKEIKILNIFGVIK GFVEPDHYVVVGAQRDAWGPGAAKSGVGTALLLKLAQMF SDMVLKDGFQPSRSIIFASWSAGDFGSVGATEWLEGYLS SLHLKAFTYINLDKAVLGTSNFKVSASPLLYTLIEKTMQ NVKHPVTGQFLYQDSNWASKVEKLTLDNAAFPFLAYSGI PAVSFCFCEDTDYPYLGTTMDTYKELIERIPELNKVARA AAEVAGQFVIKLTHDVELNLDYERYNSQLLSFVRDLNQY RADIKEMGLSLQWLYSARGDFFRATSRLTTDFGNAEKTD RFVMKKLNDRVMRVEYHFLSPYVSPKESPFRHVFWGSGS HTLPALLENLKLRKQNNGAFNETLFRNQLALATWTIQGA ANALSGDVWDIDNEF
Spike	SARS-CoV-2	P0DTC2	RBD	331-529	67.93	1.87	18.2	C-term	NITNLCPFGEVFNATRFASVYAWNRKRISNCVADYSVLY NSASFSTFKCYGVSPTKLNDLCFTNVYADSFVIRGDEVR QIAPGQTGKIADYNYKLPDDFTGCVIAWNSNNLDSKVGG NYNYLYRLFRKSNLKPFERDISTEIYQAGSTPCNGVEGF NCYFPLQSYGFQPTNGVGYQPYRVVVLSFELLHAPATVC GPKK

1224 **Table S2** Receptor sequences and parameters used for APPRAISE analysis (part 2 of 2)

Receptor name	PDB ID	Chain ID	Regions used for modeling	Construct length	D_{max} (Å)	Axial ratio	R_{minor} (Å)	Anchor site	Sequence used for modeling
FGFR2	1DJS	A	Structured region	216	105.22	3.06	17.19	C-term	TLEPEGAPYWTNTEKMEKRLHAVPAANTVKFRCPAGGNP MPTMRWLKNGKEFKQEHRIGGYKVRNQHWSLIMESVVPS DKGNYTCVVENEYGSINHTYHLDVVERSPHRPILQAGLP ANASTVVGGDVEFVCKVYSDAQPHIQWIKHVEKNGSKYG PDGLPYLKVLKAAGVNTTDKEIEVLYIRNVTFEDAGEYT CLAGNSIGISFHSAWLTVLPA
TGF-β1	3KFD	A	Structured region	112	65.88	2.4	13.73	C-term	ALDTNYCFSSTEKNCCVRQLYIDFRKDLGWKWIHEPKGY HANFCLGPCPYIWSLDTQYSKVLALYNQHNPGASAAPCC VPQALEPLPIVYYVGRKPKVEQLSNMIVRSCKCS
CD3δ	1XIW	B	Structured region	74	48.7	2.06	11.82	C-term	MKIPIEELEDRVFVNCNTSITWVEGTVGTLLSDITRLDL GKRILDPRGIYRCNGTDIYKDKESTVQVHYRMCQS
VirB8	4O3V	A	Cytoplasmic domain	143	56.27	1.62	17.37	C-term	ANPYISVANIMLQNYVKQREKYNYDTLKEQFTFIKNAST SIVYMQFANFMNIDNSLSPVIRYQKLYRRSINIISINNI NNNEATVTFESLAQNNTGEILENMLWEAKIGFIMDSIST STLHNMPFHFIVTSYKLKLLRNKNQQ
PDGFR	3MJG	C	Ig-like C2-type domains 2&3	202	86.04	2.33	18.46	C-term	DERKRLYIFVPDPTVGFLPNDAEELFIFLTEITEITIPC RVTDPQLVVTLHEKKGDVALPVPYDHQRGFSGIFEDRSY ICKTTIGDREVDSDAYYVYRLQVSSINVSVNAVQTVVRQ GENITLMCIVIGNEVVNFEWTYPRKESGRLVEPVTDFLL DMPYHIRSILHIPSAELEDSGTYTCNVTESVNDHQDEKA INITVVE
TrkA	2IFG	A	Ig-like C2-type domain 2	100	50.52	1.8	14.03	C-term	SFPASVQLHTAVEMHHWCIPFSVDGQPAPSLRWLFNGSV LNETSFIFTEFLEPAANETVRHGCLRLNQPTHVNNGNYT LLAANPFGQASASIMAAFMDNP
IL-7Rα	3DI3	B	Structured region	193	70.65	2.07	17.07	C-term	DYSFSCYSQLEVNGSQHSLTCAFEDPDVNTTNLEFEICG ALVEVKCLNFRKLQEIYFIETKKFLLIGKSNICVKVGEK SLTCKKIDLTTIVKPEAPFDLSVVYREGANDFVVTFNTS HLQKKYVKVLMHDVAYRQEKDENKWTHVNLSSTKLTLLQ RKLQPAAMYEIKVRSIPDHYFKGFWSEWSPSYYFRTP

Table S3 Sequences of engineered proteins used in APPRAISE tests in Figure 3

Protein Name	Description	Source	Protein sequence
12aa-B	Peptide from a phage display selection for Transferrin binding (positive)	Lee et al. 2001	THRPPMWSPVWP
12aa-B-scramble	Scrambled sequence of 12aa-B	Lee et al. 2001	PWRPSHPVWMPT
12aa-NB1	Peptide from a phage display selection for Transferrin binding (negative)	Lee et al. 2001	SSHMENTPDTLR
12aa-NB2	Peptide from a phage display selection for Transferrin binding (negative)	Lee et al. 2001	SNIRLSNSPMNT
12aa-NB3	Peptide from a phage display selection for Transferrin binding (negative)	Lee et al. 2001	YSYTPHATSMYS
12aa-NB4	Peptide from a phage display selection for Transferrin binding (negative)	Lee et al. 2001	SDMYPSTTLPVI
MNPD-1	Peptide rationally designed to bind to PD-L1	Yin et al. 2021	AQIREYKRCGQDEERVRRECKERGERQNCVYNIYKEGNCYVCGIICL
MOPD-1	Peptide rationally designed to bind to PD-L1	Yin et al. 2021	AQIREYKRCGQDEERVRRECKERGERQNCVYNIYKEGNCYVCGIICL
Scaffold	Scaffold of the designed peptides	Yin et al. 2021	GSEERRYKRCGQDEERVRRECKERGERQNCQYQIRKEGNCYVCEIRC
AAV9_560-606	Negative control sequence for PD-L1 binding (from AAV capsid)	negative control	ITNEEEIKTTNPVATESYGQVATNHQSAQAQAQTGWVQNQGILPGMV
PHP.eB_560-606	Negative control sequence for PD-L1 binding (from AAV capsid)	negative control	ITNEEEIKTTNPVATESYGQVATNHQSDGTLAVPFKAQAQTGWVQNQGILPGMV
AHB1	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	DEDLEELERLYRKAEEVAKEAKDASRRGDDERAKEQMERAMRLFDQVFELAQELQEKQTDGNRQKA THLDKAVKEAADELYQRVR
AHB2	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	ELEEQVMHVLDQVSELAHELLHKLTGEELERAAYFNWWATEMMLELIKSDDEREIREIEEEARRIL EHLEELARK
Influenza	Miniproteins designed to bind to Influenza virus	Chevalier et al., 2017	CIEQSFTTLFACQTAAEIWRAFGYTVKIMVDNGNCRLHVC
LCB1	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	DKEWILQKIYEIMRLLDELGHAEASMRVSDLIYEFMKKGDERLLEEAERLLEEVER
LCB2	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	SDDEDSVRYLLYMAELRYEQGNPEKAKKILEMAEFIAKRNNNEELERLVREVKKRL
LCB3	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	NDDELHMLMTDLVYEALHFAKDEEIKKRVFQLFELADKAYKNNDRQKLEKVVEELKELLERLLS
LCB4	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	QREKRLKQLEMLLEYAIERNDPYLMFDVAVEMLRLAEENNDERIIERAKRILEEYE
LCB5	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	SLEELKEQVKELKKELSPEMRRLIEEALRFLEEGNPAMAMMVLSDLVYQLGDPRVIDLYMLVTKT
AAV9_560-606	Negative control sequence for SARS-Cov-2-S binding (from AAV capsid)	Cao et al. 2020	ITNEEEIKTTNPVATESYGQVATNHQSAQAQAQTGWVQNQGILPGMV
PHP.eB_560-606	Negative control sequence for SARS-Cov-2-S binding (from AAV capsid)	Cao et al. 2020	ITNEEEIKTTNPVATESYGQVATNHQSDGTLAVPFKAQAQTGWVQNQGILPGMV
Nb80	Nanobody that binds to beta2 adrenergic receptor (parent)	Ring et al. 2013	QVQLQESGGGLVQAGGSLRLSCAASGSIFSINTMGWYRQAPGKQRELVAAIHSGGSTNYANSVKGR FTISRDNAANTVYLQMNSLKPEDTAVYYCNVKDYGAVLYEYDYWGQGTQVTVSS
Nb6A10	Nanobody selected to bind to beta2 adrenergic receptor using yeast display	Ring et al. 2013	QVQLQESGGGLVQAGGSLRLSCAASGGIFGFNTMGWYRQAPGKQRELVAAILSGGTTYYANSVKGR FTISRDNAANTVYLQMNSLKPEDTAVYYCNVKDHGSIIYDYDYWGQGTQVTVSS
Nb6B11	Nanobody selected to bind to beta2 adrenergic receptor using yeast display	Ring et al. 2013	QVQLQESGGGLVQAGGSLRLSCAASGTIFSINTMGWYRQAPGKQRELVAAIHSGGSTYYANSVKGR FTISRDNAANTVYLQMNSLKPEDTAVYYCNVKDYGAVLYDYDYWGQGTQVTVSS
Nb6A5	Nanobody selected to bind to beta2 adrenergic receptor using yeast display	Ring et al. 2013	QVQLQESGGGLVQAGGSLRLSCAASGSIFTFNTMGWYRQAPGKQRELVAAIHSGGNTDYANSVKGR FTISRDNAANTVYLQMNSLKPEDTAVYYCNVKDYGAIIYEYDYWGQGTQVTVSS
Nb6A9	Nanobody selected to bind to beta2 adrenergic receptor using yeast display	Ring et al. 2013	QVQLQESGGGLVQAGGSLRLSCAASGSIFAINTMGWYRQAPGKQRELVAAIHSGGSTNYANSVKGR FTISRDNAANTVYLQMNSLKPEDTAVYYCNVKDYGAIVYEYDYWGQGTQVTVSS
Nb6B9	Nanobody selected to bind to beta2 adrenergic receptor using yeast display	Ring et al. 2013	QVQLQESGGGLVQAGGSLRLSCAASGSIFALNIMGWYRQAPGKQRELVAAIHSGGTTNYANSVKGR FTISRDNAANTVYLQMNSLKPEDTAVYYCNVKDFGAIIYDYDYWGQGTQVTVSS
FGFR2_mb	Miniprotein designed to bind to FGFR2	Cao et al. 2022	DRRKEMDKVYRTAFKRITSTPDKEKRKEVVKEATEQLRRIAKDEEEKKKAAYMILFLKTLG
TGF-β1_mb	Miniprotein designed to bind to TGF-β1	Cao et al. 2022	HCTIEVVGVDPEKVEAIAAAYGAEVCEKDGKFEIHLDDPHSAESAAVAISVLTNRPVRLQC
CD3δ_mb	Miniprotein designed to bind to CD3δ	Cao et al. 2022	NHIACEIHNPEAAKEIAKVANVRRVYFIKQPGNRYFVLLKNADPEGVKKVRSKYNVRCVIRE
VirB8_mb	Miniprotein designed to bind to VirB8	Cao et al. 2022	NAEEITEKATLVGIEAWLLAKDEEQKKKVRTLNRQVKKLLQQNDLDQAKRVLDQLKSVLEDLKS
PDGFR_mb	Miniprotein designed to bind to PDGFR	Cao et al. 2022	DDERLATLAFRALIKRAGVKNLDVKVTNGKVRVTITGRDQASFKALQLVFALARLGLQVQIDTR
TrkA_mb	Miniprotein designed to bind to TrkA	Cao et al. 2022	RDEIKERIFKAVVRAIVTGNPEQLKEAKKLLEKLKKLGRLDQDAKKFEKAIRQVEKRLRS
IL-7Rα_mb	Miniprotein designed to bind to IL-7Rα	Cao et al. 2022	SVIEKLRKLEKQARKQGDEVLVMLARMVLEYLEKGWVSEEDADESADRIEEVLKK
LCB1	Miniproteins designed to bind to SARS-Cov-2-S	Cao et al. 2020	DKEWILQKIYEIMRLLDELGHAEASMRVSDLIYEFMKKGDERLLEEAERLLEEVER

Table S4 Peptides used for *in silico* screening

Peptide name	Peptide sequence (residues 587-594 in VP1)	Original source
AAV9	AQ-------AQAQTG	Gao et al., 2002
PHP.B	AQTLAVPFKAQAQTG	Deverman et al. 2016
PHP.D	AQWKNMGLQAQAQTG	Unpublished in vivo selection
SRK-1	AQLYHGGSTAQAQTG	Kumar et al. 2020
SRK-2	AQNNSVRQLAQAQTG	Kumar et al. 2020
SRK-3	AQVNSTRNVAQAQTG	Kumar et al. 2020
SRK-4	AQGNMTKFTAQAQTG	Kumar et al. 2020
SRK-5	AQTAIQPPKAQAQTG	Kumar et al. 2020
SRK-6	AQITTDQPFAQAQTG	Kumar et al. 2020
SRK-7	AQDTANTARAQAQTG	Kumar et al. 2020
SRK-8	AQTHDAQAWAQAQTG	Kumar et al. 2020
SRK-9	AQQPLAEEAAQAQTG	Kumar et al. 2020
SRK-10	AQTALANQKAQAQTG	Kumar et al. 2020
SRK-11	AQTGTERLSAQAQTG	Kumar et al. 2020
SRK-12	AQNGVTQSKAQAQTG	Kumar et al. 2020
SRK-13	AQWTEQRLVAQAQTG	Kumar et al. 2020
SRK-14	AQDTGLNNRAQAQTG	Kumar et al. 2020
SRK-15	AQPLPPTSIAQAQTG	Kumar et al. 2020
SRK-16	AQSDPGKFMAQAQTG	Kumar et al. 2020
SRK-17	AQTTMGTMLAQAQTG	Kumar et al. 2020
SRK-18	AQKQTQDSSAQAQTG	Kumar et al. 2020
SRK-19	AQLAHNSALAQAQTG	Kumar et al. 2020
SRK-20	AQVVPSTYRAQAQTG	Kumar et al. 2020
SRK-21	AQFRHLTGAAQAQTG	Kumar et al. 2020
SRK-22	AQSANLLSSAQAQTG	Kumar et al. 2020
SRK-23	AQFSNTHALAQAQTG	Kumar et al. 2020
SRK-24	AQFNSKLQLAQAQTG	Kumar et al. 2020
SRK-25	AQFKTNISAAQAQTG	Kumar et al. 2020
SRK-26	AQYPVPLKQAQAQTG	Kumar et al. 2020
SRK-27	AQHVNHMAPAQAQTG	Kumar et al. 2020
SRK-28	AQIVSNQMSAQAQTG	Kumar et al. 2020
SRK-29	AQPRPERMYAQAQTG	Kumar et al. 2020
SRK-30	AQNMKIQHVAQAQTG	Kumar et al. 2020
SRK-31	AQNTNVPAMAQAQTG	Kumar et al. 2020
SRK-32	AQSAQLRSSAQAQTG	Kumar et al. 2020
SRK-33	AQSHHEQVSAQAQTG	Kumar et al. 2020
SRK-34	AQGATGHLTAQAQTG	Kumar et al. 2020
SRK-35	AQHNLRDSIAQAQTG	Kumar et al. 2020
SRK-36	AQGPGTSFKAQAQTG	Kumar et al. 2020
SRK-37	AQSPPVQGLAQAQTG	Kumar et al. 2020
SRK-38	AQTLYNAIHAQAQTG	Kumar et al. 2020
SRK-39	AQLGDITGFAQAQTG	Kumar et al. 2020
SRK-40	AQGFNSMKPAQAQTG	Kumar et al. 2020
SRK-41	AQSNGLNGLAQAQTG	Kumar et al. 2020
SRK-42	AQVRIPGALAQAQTG	Kumar et al. 2020
SRK-43	AQDMGTDNLAQAQTG	Kumar et al. 2020
SRK-44	AQNYATKSQAQAQTG	Kumar et al. 2020
SRK-45	AQSVTTSHVAQAQTG	Kumar et al. 2020
SRK-46	AQTSGTDGIAQAQTG	Kumar et al. 2020
SRK-47	AQARTAHGYAQAQTG	Kumar et al. 2020
SRK-48	AQHSANMSKAQAQTG	Kumar et al. 2020
SRK-49	AQHDERANMAQAQTG	Kumar et al. 2020
SRK-50	AQNNFNASLAQAQTG	Kumar et al. 2020
SRK-51	AQSASLVSHAQAQTG	Kumar et al. 2020
SRK-52	AQAPRIDNAAQAQTG	Kumar et al. 2020
SRK-53	AQLTSSNALAQAQTG	Kumar et al. 2020
SRK-54	AQTLNSIRAAQAQTG	Kumar et al. 2020
SRK-55	AQSGTGRQQAQAQTG	Kumar et al. 2020
SRK-56	AQKTTLASGAQAQTG	Kumar et al. 2020
SRK-57	AQMRVNTEEAQAQTG	Kumar et al. 2020
SRK-58	AQFETLHKTAQAQTG	Kumar et al. 2020
SRK-59	AQTQHRFEMAQAQTG	Kumar et al. 2020
SRK-60	AQHTAEKAPAQAQTG	Kumar et al. 2020
SRK-61	AQNHMVRELAQAQTG	Kumar et al. 2020
SRK-62	AQRFQPSSAAQAQTG	Kumar et al. 2020
SRK-63	AQRSVANVPAQAQTG	Kumar et al. 2020
SRK-64	AQVFQATRTAQAQTG	Kumar et al. 2020
SRK-65	AQEQRTPSPAQAQTG	Kumar et al. 2020
SRK-66	AQGSSTASLAQAQTG	Kumar et al. 2020
SRK-67	AQQVPHLHSAQAQTG	Kumar et al. 2020
SRK-68	AQPSQPYTKAQAQTG	Kumar et al. 2020
SRK-69	AQTHTRDQGAQAQTG	Kumar et al. 2020
SRK-70	AQINPGITLAQAQTG	Kumar et al. 2020
SRK-71	AQLQPTKSSAQAQTG	Kumar et al. 2020
SRK-72	AQQDAKVTTAQAQTG	Kumar et al. 2020
SRK-73	AQGASTHNAAQAQTG	Kumar et al. 2020
SRK-74	AQIPVSIQAAQAQTG	Kumar et al. 2020
SRK-75	AQVTSAHPVAQAQTG	Kumar et al. 2020
SRK-76	AQTASLIASAQAQTG	Kumar et al. 2020
SRK-77	AQDRGTRTVAQAQTG	Kumar et al. 2020
SRK-78	AQTAYLEVKAQAQTG	Kumar et al. 2020
SRK-79	AQATTQMSSAQAQTG	Kumar et al. 2020
SRK-80	AQKYDASQSAQAQTG	Kumar et al. 2020
SRK-81	AQTGTSHLHAQAQTG	Kumar et al. 2020
SRK-82	AQTMTPSGIAQAQTG	Kumar et al. 2020
SRK-83	AQTPSSSGNAQAQTG	Kumar et al. 2020
SRK-84	AQKDVVNSNAQAQTG	Kumar et al. 2020
SRK-85	AQRSPATMLAQAQTG	Kumar et al. 2020
SRK-86	AQYDQKSLAAQAQTG	Kumar et al. 2020
SRK-87	AQMGARNLPAQAQTG	Kumar et al. 2020
SRK-88	AQLPISATEAQAQTG	Kumar et al. 2020
SRK-89	AQTRHTSLTAQAQTG	Kumar et al. 2020
SRK-90	AQNKLTANGAQAQTG	Kumar et al. 2020
SRK-91	AQNGDSHSHAQAQTG	Kumar et al. 2020
SRK-92	AQVRTDMDMAQAQTG	Kumar et al. 2020
SRK-93	AQSVSTPRGAQAQTG	Kumar et al. 2020
SRK-94	AQVSRQFEPAQAQTG	Kumar et al. 2020
SRK-95	AQSANNVRGAQAQTG	Kumar et al. 2020
SRK-96	AQIGTKSTNAQAQTG	Kumar et al. 2020
SRK-97	AQGSELRTGAQAQTG	Kumar et al. 2020

Acknowledgments. The authors thank Elisha Mackey, Zhe Qu, and Pat Anguiano for administrative assistance, Catherine Oikonomou for help with manuscript editing, and Sripriya R. Kumar, Seongmin Jang, Jimin Park, and Changfan Lin for helpful discussions. Schematics in this manuscript were created with BioRender.com. The study was funded by an NIH Director's Pioneer Award DP1OD025535 (to V.G.).

Declarations

- **Declaration of Generative AI and AI-assisted technologies in the writing process** During the preparation of this work, the authors used Stork Writing Assistant in order to improve grammar and writing clarity. After using this tool/service, the authors reviewed and edited the content as needed and take full responsibility for the content of the publication.
- **Conflict of interest/Competing interests** V.G. is a scientific co-founder and BoD member of Capsida Biotherapeutics. The terms of the arrangements have been reviewed and approved by the California Institute of Technology in accordance with its conflict of interest policies.
- **Ethics approval** All animal procedures in mice were approved by the California Institute of Technology Institutional Animal Care and Use Committee (IACUC), Caltech Office of Laboratory Animal Resources (OLAR), and were carried out in accordance with guidelines and regulations.
- **Authors' contributions** X.D. and V.G. conceived the project. X.D. developed the APPRAISE method and applied APPRAISE to predict the receptor binders. X.C. identified PHP.D through directed evolution and characterized PHP.D *in vivo*. E.E.S. and T.F.S. designed and performed *in vitro* infectivity assays.

References

[1] Deverman, B. E. *et al.* Cre-dependent selection yields AAV variants for widespread gene transfer to the adult brain. *Nature biotechnology* **34** (2), 204–209 (2016). URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC5088052/. https://doi.org/10.1038/nbt.3440 .

[2] Ravindra Kumar, S. *et al.* Multiplexed Cre-dependent selection yields systemic AAVs for targeting distinct brain cell types. *Nature Methods* **17** (5), 541–550 (2020). https://doi.org/10.1038/s41592-020-0799-7 .

[3] Ring, A. M. *et al.* Adrenaline-activated structure of the 2-adrenoceptor stabilized by an engineered nanobody. *Nature* **502** (7472), 575–579 (2013). URL https://www.ncbi.nlm.nih.gov/pmc/articles/PMC3822040/. https://doi.org/10.1038/nature12572 .

[4] Lee, J. H., Engler, J. A., Collawn, J. F. & Moore, B. A. Receptor mediated uptake of peptides that bind the human transferrin receptor. *European Journal of Biochemistry* **268** (7), 2004–2012 (2001). https://doi.org/10.1046/j.1432-1327.2001.02073.x .

[5] Cao, L. *et al.* De novo design of picomolar SARS-CoV-2 miniprotein inhibitors. *Science* **370** (6515), 426–431 (2020). URL https://www.science.org/doi/10.1126/science.abd9909. https://doi.org/10.1126/science.abd9909, publisher: American Association for the Advancement of Science .

[6] Chevalier, A. *et al.* Massively parallel de novo protein design for targeted therapeutics. *Nature* **550** (7674), 74–79 (2017). URL https://www.nature.com/articles/nature23912. https://doi.org/10.1038/nature23912, number: 7674 Publisher: Nature Publishing Group .

[7] Yin, H. *et al.* Rational Design of Potent Peptide Inhibitors of the PD-1:PD-L1 Interaction for Cancer Immunotherapy. *Journal of the American Chemical Society* **143** (44), 18536–18547 (2021). URL https://doi.org/10.1021/jacs.1c08132. https://doi.org/10.1021/jacs.1c08132, publisher: American Chemical Society .

[8] Sliwoski, G., Kothiwale, S., Meiler, J. & Lowe, E. W. Computational Methods in Drug Discovery. *Pharmacological Reviews* **66** (1), 334–395 (2014). URL https://pharmrev.aspetjournals.org/content/66/1/334. https://doi.org/10.1124/pr.112.007336, publisher: American Society for Pharmacology and Experimental Therapeutics Section: Review Article .

[9] Yang, K. K., Wu, Z. & Arnold, F. H. Machine-learning-guided directed evolution for protein engineering. *Nature Methods* 1 (2019). URL https://www.nature.com/articles/s41592-019-0496-6. https://doi.org/10.

1038/s41592-019-0496-6 .

[10] Bedbrook, C. N., Yang, K. K., Rice, A. J., Gradinaru, V. & Arnold, F. H. Machine learning to design
integral membrane channelrhodopsins for efficient eukaryotic expression and plasma membrane localization.
PLOS Computational Biology 1–21 (2017). URL http://journals.plos.org/ploscompbiol/article/file?id=10.
1371/journal.pcbi.1005786&type=printable. https://doi.org/10.1371/journal.pcbi.1005786 .

[11] Bolon, D. N., Voigt, C. A. & Mayo, S. L. De novo design of biocatalysts. *Current Opinion in Chemical Biol-*
ogy **6** (2), 125–129 (2002). URL https://www.sciencedirect.com/science/article/pii/S1367593102003034.
https://doi.org/10.1016/S1367-5931(02)00303-4 .

[12] Jumper, J. *et al.* Highly accurate protein structure prediction with AlphaFold. *Nature* (2021). https:
//doi.org/10.1038/s41586-021-03819-2 .

[13] Baek, M. *et al.* Accurate prediction of protein structures and interactions using a three-track neural
network. *Science* **373** (6557), 871–876 (2021). URL https://www.science.org/doi/10.1126/science.abj8754.
https://doi.org/10.1126/science.abj8754, publisher: American Association for the Advancement of Science .

[14] Evans, R. *et al.* Protein complex prediction with AlphaFold-Multimer. *bioRxiv* (2021). https://doi.org/
10.1101/2021.10.04.463034v1 .

[15] Mirdita, M. *et al.* ColabFold: Making Protein folding accessible to all. *Nature Methods* (2022). https:
//doi.org/10.1038/s41592-022-01488-1 .

[16] Aderinwale, T., Christoffer, C. & Kihara, D. RL-MLZerD: Multimeric protein docking using reinforcement
learning (2022). URL https://www.frontiersin.org/articles/10.3389/fmolb.2022.969394.

[17] Motmaen, A. *et al.* Peptide binding specificity prediction using fine-tuned protein structure pre-
diction networks (2022). URL https://www.biorxiv.org/content/10.1101/2022.07.12.499365v1. Pages:
2022.07.12.499365 Section: New Results.

[18] Ruffolo, J. A., Chu, L.-S., Mahajan, S. P. & Gray, J. J. Fast, accurate antibody structure prediction from
deep learning on massive set of natural antibodies (2022). URL https://www.biorxiv.org/content/10.1101/
2022.04.20.488972v1. Pages: 2022.04.20.488972 Section: New Results.

[19] Lin, Z. *et al.* Language models of protein sequences at the scale of evolution enable accurate structure
prediction. *bioRxiv* 2022.07.20.500902 (2022). URL http://biorxiv.org/content/early/2022/07/21/2022.07.
20.500902.abstract. https://doi.org/10.1101/2022.07.20.500902 .

[20] Li, Z. *et al.* Uni-Fold: An Open-Source Platform for Developing Protein Folding Models beyond AlphaFold.
bioRxiv 2022.08.04.502811 (2022). URL http://biorxiv.org/content/early/2022/08/30/2022.08.04.502811.
abstract. https://doi.org/10.1101/2022.08.04.502811 .

[21] Wu, R. *et al.* High-resolution ¡em¿de novo¡/em¿ structure prediction from primary sequence. *bioRxiv*
2022.07.21.500999 (2022). URL http://biorxiv.org/content/early/2022/07/22/2022.07.21.500999.abstract.
https://doi.org/10.1101/2022.07.21.500999 .

[22] Wang, G. *et al.* HelixFold: An Efficient Implementation of AlphaFold2 using PaddlePaddle (2022). URL
https://arxiv.org/abs/2207.05477.

[23] Cheng, S. *et al.* FastFold: Reducing AlphaFold Training Time from 11 Days to 67 Hours (2022). URL
https://arxiv.org/abs/2203.00854.

[24] Liu, S. *et al.* PSP: Million-level Protein Sequence Dataset for Protein Structure Prediction (2022). URL
https://arxiv.org/abs/2206.12240.

[25] Tsaban, T. *et al.* Harnessing protein folding neural networks for peptide–protein docking. *Nature*
Communications **13** (1), 176 (2022). URL https://www.nature.com/articles/s41467-021-27838-9. https:
//doi.org/10.1038/s41467-021-27838-9, number: 1 Publisher: Nature Publishing Group .

[26] Bennett, N. *et al.* Improving ¡em¿de novo¡/em¿ Protein Binder Design with Deep Learning. *bioRxiv* 2022.06.15.495993 (2022). URL http://biorxiv.org/content/early/2022/06/17/2022.06.15.495993.abstract. https://doi.org/10.1101/2022.06.15.495993 .

[27] Chang, L. & Perez, A. Ranking Peptide Binders by Affinity with AlphaFold. *Angewandte Chemie* (2022). URL https://onlinelibrary.wiley.com/doi/full/10.1002/ange.202213362https://onlinelibrary.wiley.com/doi/abs/10.1002/ange.202213362https://onlinelibrary.wiley.com/doi/10.1002/ange.202213362. https://doi.org/10.1002/ANGE.202213362 .

[28] Baker, D. What has de novo protein design taught us about protein folding and biophysics? *Protein Science* **28** (4), 678–683 (2019). URL https://doi.org/10.1002/pro.3588. https://doi.org/https://doi.org/10.1002/pro.3588 .

[29] Alford, R. F. *et al.* The Rosetta All-Atom Energy Function for Macromolecular Modeling and Design. *Journal of Chemical Theory and Computation* **13** (6), 3031–3048 (2017). URL https://doi.org/10.1021/acs.jctc.7b00125. https://doi.org/10.1021/acs.jctc.7b00125 .

[30] Gonzalez, T. R., Martin, K. P., Barnes, J. E., Patel, J. S. & Ytreberg, F. M. Assessment of software methods for estimating protein-protein relative binding affinities. *PLOS ONE* **15** (12), e0240573 (2020). URL https://doi.org/10.1371/journal.pone.0240573 .

[31] Chan, K. Y. *et al.* Engineered AAVs for efficient noninvasive gene delivery to the central and peripheral nervous systems. *Nature Neuroscience* **20** (8), 1172–1179 (2017). URL http://dx.doi.org/10.1038/nn.4593. https://doi.org/10.1038/nn.4593 .

[32] Nonnenmacher, M. *et al.* Rapid evolution of blood-brain-barrier-penetrating AAV capsids by RNA-driven biopanning. *Molecular Therapy - Methods Clinical Development* **20**, 366–378 (2021). URL https://doi.org/10.1016/j.omtm.2020.12.006. https://doi.org/10.1016/j.omtm.2020.12.006 .

[33] Goertsen, D. *et al.* AAV capsid variants with brain-wide transgene expression and decreased liver targeting after intravenous delivery in mouse and marmoset. *Nature Neuroscience* **25** (1), 106–115 (2022). URL https://doi.org/10.1038/s41593-021-00969-4. https://doi.org/10.1038/s41593-021-00969-4 .

[34] Chuapoco, M. R. *et al.* Intravenous gene transfer throughout the brain of infant Old World primates using AAV. *bioRxiv* 2022.01.08.475342 (2022). URL http://biorxiv.org/content/early/2022/01/09/2022.01.08.475342.abstract. https://doi.org/10.1101/2022.01.08.475342 .

[35] Chen, X. *et al.* Engineered AAVs for non-invasive gene delivery to rodent and non-human primate nervous systems. *Neuron* **110** (14), 2242–2257.e6 (2022). URL https://www.sciencedirect.com/science/article/pii/S0896627322004111. https://doi.org/https://doi.org/10.1016/j.neuron.2022.05.003 .

[36] Gao, G. *et al.* Clades of Adeno-Associated Viruses Are Widely Disseminated in Human Tissues. *Journal of Virology* **78** (12), 6381–6388 (2004). URL http://www.pubmedcentral.nih.gov/articlerender.fcgi?artid=416542&tool=pmcentrez&rendertype=abstract. https://doi.org/10.1128/JVI.78.12.6381-6388.2004 .

[37] Huang, Q. *et al.* Delivering genes across the blood-brain barrier: LY6A, a novel cellular receptor for AAV-PHP.B capsids. *PLOS ONE* **14** (11), e0225206 (2019). URL https://doi.org/10.1371/journal.pone.0225206 .

[38] Hordeaux, J. *et al.* The GPI-Linked Protein LY6A Drives AAV-PHP.B Transport across the Blood-Brain Barrier. *Molecular Therapy* **27** (5), 912–921 (2019). URL https://doi.org/10.1016/j.ymthe.2019.02.013. https://doi.org/10.1016/j.ymthe.2019.02.013 .

[39] Batista, A. R. *et al.* Ly6a Differential Expression in Blood–Brain Barrier Is Responsible for Strain Specific Central Nervous System Transduction Profile of AAV-PHP.B. *Human Gene Therapy* **31** (1-2), 90–102 (2019). URL https://doi.org/10.1089/hum.2019.186. https://doi.org/10.1089/hum.2019.186 .

[40] Xu, G. *et al.* Structural basis for the neurotropic AAV9 and the engineered AAVPHP.eB recognition with cellular receptors. *Molecular Therapy - Methods Clinical Development* **26**, 52–60 (2022). URL

1540   https://doi.org/10.1016/j.omtm.2022.05.009. https://doi.org/10.1016/j.omtm.2022.05.009 .
1541

1542 [41] Jang, S., Shen, H. K., Ding, X., Miles, T. F. & Gradinaru, V. Structural basis of receptor usage by the
1543   engineered capsid AAV-PHP.eB. *Molecular Therapy - Methods Clinical Development* **26**, 343–354 (2022).
1544   URL https://doi.org/10.1016/j.omtm.2022.07.011. https://doi.org/10.1016/j.omtm.2022.07.011 .

1545
1546 [42] Morrone, J. A., Perez, A., MacCallum, J. & Dill, K. A. Computed Binding of Peptides to Proteins with
1547   MELD-Accelerated Molecular Dynamics. *Journal of Chemical Theory and Computation* **13** (2), 870–876
1548   (2017). URL https://doi.org/10.1021/acs.jctc.6b00977. https://doi.org/10.1021/acs.jctc.6b00977 .

1549
[43] Bolon, D. N., Grant, R. A., Baker, T. A. & Sauer, R. T. Specificity versus stability in computational
protein design. *Proceedings of the National Academy of Sciences* **102** (36), 12724–12729 (2005). URL
https://doi.org/10.1073/pnas.0506124102. https://doi.org/10.1073/pnas.0506124102 .

[44] Copeland, R. A. The drug–target residence time model: a 10-year retrospective. *Nature Reviews Drug*
Discovery **15** (2), 87–95 (2016). URL https://doi.org/10.1038/nrd.2015.18. https://doi.org/10.1038/nrd.
2015.18 .
1556

1557 [45] Cao, L. *et al.* Design of protein-binding proteins from the target structure alone. *Nature* **605** (7910),
1558   551–560 (2022). URL https://www.nature.com/articles/s41586-022-04654-9. https://doi.org/10.1038/
1559   s41586-022-04654-9 .
1560

1561 [46] Sievers, F. *et al.* Fast, scalable generation of high-quality protein multiple sequence alignments using
1562   Clustal Omega. *Molecular Systems Biology* **7** (1), 539 (2011). URL https://doi.org/10.1038/msb.2011.75.
1563   https://doi.org/https://doi.org/10.1038/msb.2011.75 .

1564
1565 [47] Wong, F. *et al.* Benchmarking AlphaFold-enabled molecular docking predictions for antibiotic discovery.
1566   *Molecular Systems Biology* **18** (9), e11081 (2022). URL https://doi.org/10.15252/msb.202211081. https:
1567   //doi.org/https://doi.org/10.15252/msb.202211081 .

1568
1569 [48] Roney, J. P. & Ovchinnikov, S. State-of-the-art estimation of protein model accuracy using alphafold. *Phys.*
1570   *Rev. Lett.* **129**, 238101 (2022). URL https://link.aps.org/doi/10.1103/PhysRevLett.129.238101. https:
1571   //doi.org/10.1103/PhysRevLett.129.238101 .

1572
[49] Shay, T. F. *et al.* Primate-conserved carbonic anhydrase iv and murine-restricted ly6c1 are new tar-
gets for crossing the blood-brain barrier. *bioRxiv* (2023). URL https://www.biorxiv.org/content/early/
2023/01/13/2023.01.12.523632. https://doi.org/10.1101/2023.01.12.523632, https://arxiv.org/abs/https:
//www.biorxiv.org/content/early/2023/01/13/2023.01.12.523632.full.pdf .

[50] Ovchinnikov, S. & Huang, P.-S. Structure-based protein design with deep learning. *Mechanistic Biology* *
Machine Learning in Chemical Biology **65**, 136–144 (2021). URL https://www.sciencedirect.com/science/
article/pii/S1367593121001125. https://doi.org/10.1016/j.cbpa.2021.08.004 .
1580

1581 [51] Anand, N. *et al.* Protein sequence design with a learned potential. *Nature Communications* **13** (1), 746
1582   (2022). URL https://doi.org/10.1038/s41467-022-28313-9. https://doi.org/10.1038/s41467-022-28313-9 .
1583

1584 [52] Dauparas, J. *et al.* Robust deep learning based protein sequence design using ProteinMPNN. *bioRxiv*
1585   2022.06.03.494563 (2022). URL http://biorxiv.org/content/early/2022/06/04/2022.06.03.494563.abstract.
1586   https://doi.org/10.1101/2022.06.03.494563 .

1587
1588 [53] Wang, J. *et al.* Scaffolding protein functional sites using deep learning. *Science* **377** (6604), 387–394 (2022).
1589   URL https://doi.org/10.1126/science.abn2100. https://doi.org/10.1126/science.abn2100 .

1590
1591 [54] Steinegger, M. *et al.* HH-suite3 for fast remote homology detection and deep protein annotation. *BMC*
1592   *Bioinform.* **20** (1), 473 (2019). https://doi.org/10.1186/s12859-019-3019-7 .

1593 [55] Mitchell, A. L. *et al.* MGnify: the microbiome analysis resource in 2020. *Nucleic Acids Res.* (2019).
1594   https://doi.org/10.1093/nar/gkz1035 .
1595

1596

[56] Mirdita, M., Steinegger, M. & S"oding, J. MMseqs2 desktop and local web server app for fast, interactive sequence searches. *Bioinformatics* **35** (16), 2856–2858 (2019). https://doi.org/10.1093/bioinformatics/bty1057 .

[57] Mirdita, M. *et al.* Uniclust databases of clustered and deeply annotated protein sequences and alignments. *Nucleic Acids Res.* **45** (D1), D170–D176 (2017). https://doi.org/10.1093/nar/gkw1081 .

[58] Fleming, P. J. & Fleming, K. G. HullRad: Fast Calculations of Folded and Disordered Protein and Nucleic Acid Hydrodynamic Properties. *Biophysical Journal* **114** (4), 856–869 (2018). URL https://www.sciencedirect.com/science/article/pii/S0006349518300651. https://doi.org/10.1016/j.bpj.2018.01.002 .

[59] Salamanca Viloria, J., Allega, M. F., Lambrughi, M. & Papaleo, E. An optimal distance cutoff for contact-based Protein Structure Networks using side-chain centers of mass. *Scientific Reports* **7** (1), 2838 (2017). URL https://doi.org/10.1038/s41598-017-01498-6. https://doi.org/10.1038/s41598-017-01498-6 .

[60] Coleman, R. G. & Sharp, K. A. Travel Depth, a New Shape Descriptor for Macromolecules: Application to Ligand Binding. *Journal of Molecular Biology* **362** (3), 441–458 (2006). URL https://www.sciencedirect.com/science/article/pii/S0022283606008746. https://doi.org/https://doi.org/10.1016/j.jmb.2006.07.022 .

[61] McCarthy, C. A. & Benjamin, A. T. Determinants of the Tournaments. *Mathematics Magazine* **69** (2), 133–135 (1996). URL https://doi.org/10.1080/0025570X.1996.11996410. https://doi.org/10.1080/0025570X.1996.11996410 .

[62] Challis, R. C. *et al.* Systemic AAV vectors for widespread and targeted gene delivery in rodents. *Nature Protocols* **14** (February), 1–1 (2019). URL http://www.nature.com/articles/s41596-018-0097-3. https://doi.org/10.1038/s41596-018-0097-3 .