1 Imputation of label-free quantitative

2 mass spectrometry-based proteomics

3 data using self-supervised deep learning

4 Authors

5 Henry Webel[1], Lili Niu[1], Annelaura Bach Nielsen[1], Marie Locard-Paulet[1], Matthias Mann[1,3], Lars

6 Juhl Jensen[1], Simon Rasmussen[1,2]

7 Affiliations

[1] Novo Nordisk Foundation Center for Protein Research, Faculty of Health and Medical

Sciences, University of Copenhagen, Copenhagen N, Denmark

[2] The Novo Nordisk Foundation Center for Genomic Mechanisms of Disease, Broad Institute of

MIT and Harvard, Cambridge, MA 02142, USA

[3] Department of Proteomics and Signal Transduction, Max Planck Institute of Biochemistry,

Martinsried, Germany

14
15

16 Keywords

17 Imputation, self-supervised learning, deep learning, reproducibility, mass spectrometry,

18 proteomics

Abstract

Imputation techniques provide means to replace missing measurements with a value and are used in almost all downstream analysis of mass spectrometry (MS) based proteomics data using label-free quantification (LFQ). Here we demonstrate how collaborative filtering, denoising autoencoders, and variational autoencoders can impute missing values in the context of LFQ at different levels. We applied our method, proteomics imputation modeling mass spectrometry (PIMMS), to an alcohol-related liver disease (ALD) cohort with blood plasma proteomics data available for 358 individuals. Removing 20 percent of the intensities we were able to recover 15 out of 17 significant abundant protein groups using PIMMS-VAE imputations. When analyzing the full dataset we identified 30 additional proteins (+13.2%) that were significantly differentially abundant across disease stages compared to no imputation and found that some of these were predictive of ALD progression in machine learning models. We, therefore, suggest the use of deep learning approaches for imputing missing values in MS-based proteomics on larger datasets and provide workflows for these.

Introduction

Proteomics is a technology for the identification and quantification of proteins to answer a broad set of biological questions[1] and together with RNA and DNA sequencing offers a way to map the composition of biological systems. It is widely applied across many fields of research including identification of biomarkers and drug targets for diseases such as alcoholic liver disease (ALD)[2], ovarian cancer[3] and Alzheimer's disease[4]. Different workflows have been developed for analysis of body fluids, cells, frozen tissues and tissue slides, and are rapidly evolving. Recent technological advancements have enabled proteome analysis at the single cell or single cell-population level[5,6], allowing the selection of single cells using image recognition[7]. However, for most approaches, missing values are abundant due to the semi-stochastic nature of precursor selection for fragmentation and need to be replaced for at least some parts of the data analysis. Currently, imputation of missing values in proteomics data usually assumes that the protein abundance was below the instrument detection limit or the protein was absent. In general, the community differentiates between missing at random (MAR) which is assumed to affect all intensities across the dynamic range, whereas missing not at random (MNAR) becomes more prevalent the more the intensity of a peptide approaches the limit of detection of the instrument. However, not all missing values are due to this mechanism, and by assuming the limit of

detection as the reason for missingness will lead to potentially wrong imputations and

subsequently to biased statistical results that are limiting the conclusion from data. A strategy is

therefore to combine missing completely at random (MCAR) and simulated MNAR in

comparisons[8].

Various acquisition methods have been developed including data-independent acquisition (DIA),

BoxCar and PASEF to alleviate the "missing value" problem in data-dependent acquisition

(DDA) methods[9–11]. Advances in informatics solutions have also greatly improved data analysis

of mass spectra acquired by these acquisition methods and consequently proteome depth and

data completeness[12]. However, missing value imputation of search results for downstream

analysis remains a recurring task for most applications. The noise in data from the instrument as

well as peptide identification is most abundant for label-free quantification proteomics in DDA

with missingness ranging from 10-40%[13], but for instance, blood plasma measured using DIA in

a study of ALD still contained 37% missing values across all samples and protein groups before

any filtering. Independent of the proteomics setup, once data is to be analyzed, the remaining

missing values between samples have to be imputed for most methods. Therefore, how they

are handled will influence the downstream results.

Several methods have been evaluated for imputation of MS proteomics data with an overview

and a benchmark provided in work by Wang et al., using NAguideR[14]. Despite an abundance of

imputation methods, an often-used approach to impute data at the protein group level is by

using random draws from a down-shifted normal (RSN) distribution. The mass spectrometry

(MS) signal comes from ions and most people are interested in the summary of ions through

peptide spectrum matches to groups of proteins. The protein intensities, stemming from

aggregation of the precursor and/or fragment ion values in MS1 and MS2 scans, are assumed

to be log-normally distributed, i.e. the log transformed intensities are entirely determined by their

mean and variance. In RSN replacements are then drawn using a normal distribution with a

mean shifted towards the lower detection limit with a reduced variance. This is done on the

assumption that the data is left-censored, i.e. that proteins are missing due to absence or lower

abundance than the instrument detection limit. Following this line of thought, several studies

focus on determining what works best for different causes of missing values using some form of

simulation[8,13]. Other studies focus their analysis on post-translational modifications[15], the best

combination of software tools, datasets and imputation method[16], normalization and batch

effects correction[17] or downstream analysis[18,19]. Other methods have been developed to handle

specific missing mechanisms, for instance, random imputation, fixed value imputation such as

limit of detection or x-quantile of feature, model-based imputation using k-nearest neighbor

(KNN), linear models[13] or tree-based models[14]. These either impute using a global minimum, a

statistic calculated on a single feature or a few features, with the need to iteratively consider

each feature at a time. Finally, approaches such as DAPAR and Prostar offer several methods

for imputing left-censored data, e.g. the widely used drawing from a normal distribution around

the lower detection limit where the Gaussian mean and variance are estimated using quantile

regression, abbreviated QRILC[8,20,21]. Their latest development is Pirat exploiting correlations of

precursors from the same protein group[22]. MSStats offers end-to-end statistical analysis. It

requires MaxQuant running samples jointly and providing both precursor as well as protein

groups next to grouping information and does not impute all values.

Most previous work on developing methods for imputation of MS proteomics data focus on small

scale setups where they for instance evaluate two separate groups in three replicates[16,23]. Other

studies prefer to reduce the number of initial missing values by transferring identification from

one run to the next using e.g. Match Between Run implemented in MaxQuant or cross-

assignment by Proline[24,25]. Alternatively, an established laboratory method to tackle variability in

small-scale setups is to use replicates of samples to have complementary measurements, in

order to transfer identifications between runs[26]. The specific evaluation strategy varies between

the setup of the data and the missing values simulation approach, but to our knowledge, no

scalable workflows are provided to run the evaluation on a new single tabular dataset

generating a validation and test dataset, as well as a generic and flexible approach to

imputation.

We turn to machine learning for imputation of missing intensities as it offers the possibility to

learn from the data itself. Deep Learning (DL) has been used to improve over existing machine

learning models in a variety of biological data problems[27–29]. DL has been successfully applied

to predict peptide features such as retention times, collisional cross-sections and tandem mass

spectra, significantly boosting the peptide identifications and precision of searches of MS-based

proteomics[30–34]. We use intensities from search results generated from tools like e.g. MaxQuant

or Spectronaut and apply DL methods to impute these. We considered three types of models

that process the search results of precursors, peptides or protein groups slightly differently.

First, we considered a collaborative filtering (CF) approach, where each feature and each

sample is assigned a trainable embedding. Second, we considered an autoencoder with a

deterministic latent representation - a denoising autoencoder (DAE). Third, we considered a

variational autoencoder (VAE) as a generative model that encodes a stochastic latent

representation, i.e. a high-dimensional Gaussian distribution. Although the inputs to all models

are intensities for a feature and sample combination, the training objectives, complexity, and

therefore capabilities of the models are different. The CF and autoencoder objective only focus

on reconstruction, whereas the VAE adds a constraint on the latent representation.

Furthermore, the first two modeling approaches use a mean-squared error (MSE) reconstruction

loss, whereas the VAE uses a probabilistic loss to assess the reconstruction error.

Here we used large (N≈450) and smaller (N≈50) MS-based proteomics datasets of HeLa cell

line tryptic lysates acquired on a single machine (Q Executive HF-X Orbitrap) over a period of

roughly two years to evaluate the general performance on repeated measurements of an

homogenous biological sample on a medium to large-scale dataset. We applied the DL models

described above (CF, DAE, VAE) which create feature representation holistic for the entire

distribution in a given dataset prior to any normalization. For evaluation, we developed a

workflow that allowed comparison between the three DL models and 27 approaches (**Supp.**

Table 1). Finally, we applied the VAE to a study of ALD patients and found 30(+13.2%) more

significantly differential abundant protein groups in comparison to no imputation and showed

that additional protein groups could be leveraged for predicting disease. We termed our set of

models and workflows proteomics imputation modeling mass spectrometry (PIMMS) and made

the workflows, code, and example configs available at

https://github.com/RasmussenLab/pimms. To enable reproducibility and adaptation to new data

and strategies, we share our Python code along snakemake workflows.

Results

Evaluating self-supervised models for imputation of MS data

We assessed the capability of three unsupervised models for proteomics data imputation. First,

we considered modeling proteomics data using CF assigning each sample and each feature an

embedding vector and using their combination to predict intensity values. Second, we

considered a standard autoencoder, training it using a denoising strategy that has to learn to

reconstruct masked values making it a DAE. Third, we applied a VAE with a stochastic latent

space (**Fig. 1a**). The two autoencoder architectures used all features to represent a sample in a

low dimensional space, which was used to reconstruct the original data. In contrast, the CF

model had to learn both a latent embedding space for the samples and features. We compared

these to a heuristic-based approach of median imputation per feature across samples and 26

other approaches such as k-nearest neighbors (KNN) or random forest (RF) (**Supp. Table 1**).

While the DL methods, KNN and median imputation were able to also impute large datasets,

nine methods implemented in R failed to scale to high-dimensional data.

Our development dataset consisted of 564 HeLa runs of one Q Executive HF-X Orbitrap

generated during continuous quality control of the mass spectrometers[35]. We initially

investigated the structure of the dataset using the first two principal components (**Fig. 1b**),

which grouped the samples into two separate clusters. The median prevalence per protein

group, i.e. the median number of samples where a protein group was detected, was 526

samples [min: 45, max: 564], and samples had a median of 3,768 protein groups [min: 2,170,

max: 4,185]. We generated another smaller development dataset using the most recent 50

samples (**Fig. 1c**) to test dependence of performance on sample size. Whereas median

imputation per feature across samples did not condition their imputation on the value of other

features in a given sample, our and other machine learning approaches consider other feature

values. Validation and test data were drawn with 25, 50 or 75 percent MNAR using the

procedure laid out in Lazar et. al.[8] from all samples in a dataset. This ensures that lower

intensities are represented sufficiently, but also makes training harder due to additionally

removing values from low abundant features with fewer quantifications.

Figure 1: Overview of workflow for downstream analysis tasks and HeLa dataset. a) Single tabular results taken

from MS data analysis software (search and quantification) were used as input for downstream analysis. Here we

used MaxQuant for data dependent acquisition to analyze raw MS data. We compared three different self-supervised

DL approaches with 27 other methods: median imputation and KNN interpolation exemplified. **b)** Principal component

one versus two of 539 selected HeLa runs for protein groups recorded on one instrument. **c)** Same as b, based on

the 50 runs forming the small development dataset. We used a cutoff of 25% feature prevalence across samples to

be included into the workflow shown in (a). Samples were filtered in a second step by their completeness of the

selected features (**Fig. S1**).

Imputing precursors, aggregated peptides, and protein group data

We applied the imputation methods to the development dataset, e.g. consisting of 564 samples

for protein groups using our selection criteria (**Supp. Fig. S1**). We ran several configurations

using a grid search to find the best configurations using simulated missing values in a validation

and test split from all samples (see Methods, **Supp. Data 1, 2**). In absolute numbers these were

100,001 for the protein group, 616,561 aggregated peptides and 661,817 precursors intensities

in the test set for our development dataset of instrument 6070. When investigating the

performance of the imputation methods we used the mean absolute error (MAE) on the log2

scaled intensities between predicted and true measured intensity values on our simulated

missing values. Focusing on the best performing models from the grid search, we evaluated

these in a setup of 25 percent MNAR in the simulated missing data. We found that the DL

approaches had less than half MAE compared (0.55, 0.54 and 0.58 for CF, DAE and VAE,

respectively) to the median imputation with MAE of 1.24. KNN of samples across HeLa cell line

measurements had a MAE of 0.59 using the scikit learn implementation and of 0.68 using an R

based implementation using impute[36,37]. The R based random forest (RF) imputation[38] only

completed for the protein groups and had an MAE of 0.59 and a Bayesian principal component

analysis (BPCA) with 0.53. Thus, BPCA was slightly better (0.01 MAE) compared to the second-

best model on protein groups however it did not finish for the other two datasets within 24 hours.

Overall, when comparing the performance across levels of data aggregation for the best models

(**Fig. 2a,c, Supp. Data 3**) we found that the self-supervised models performed similarly to other

methods. Across all models, we found the overall performance to be the worst for the protein-

level data, better for aggregated peptides, and best for precursors. This is in line with previous

results of Lazar and co-workers that showed better performance for lower levels of aggregations

as it avoids implicit imputations by a neutral element[8]. A higher share (25, 50 and 75 percent) of

MNAR simulated missing values was associated with a decreased overall performance of most

methods (**Supp. Data 3**). One reason for this could be that features with fewer observations are

oversampled and the total number of available training data points drops as low as four

intensities in the training data split. To balance available data for low abundant features and

statistical power in evaluation, we set the share of MNAR to 25 percent in our evaluations.

Runtime for imputation of protein groups including data loading, manipulations and training were

between 14 seconds using the minimum and roughly 8h for IRM (for the best models in

h:min:sec: KNN-IMPUTE: 0:19, KNN: 0:41, VAE: 1:58, DAE: 2:24, CF: 2:28, RF: 1:05:02,

BPCA: 6:37:56) using 1 CPU and up to 192 GB of shared memory for the PIMMS models

(**Supp. Data. 4**). Runtimes of PIMMS models for the precursor dataset were higher (KNN: 4:17,

DAE: 33:08, VAE: 1:35:51 and CF: 18:23), but could run faster with special hardware (GPUs).

Among the models with good performance we found that BPCA, MICE-NORM, SEQKNN and

RF did not scale to the high dimensional datasets of peptides and precursors for the large

datasets. IMPSEQ ran into errors for all larger datasets. In general runtimes varied based on the

number of epochs, mini batch-size, model architecture, patience for early stopping and the initial

random weights. Additionally, the grid search results showed that the models could be trained

without prior normalization and were able to fit the data using many different hyperparameter

configurations (**Supp. Fig. S2**). Reducing the training sample by roughly a tenth, performance

on the smaller development dataset (N=50) was comparable to the performance on the larger

development dataset, while runtime reduced by 5 to 15 times for precursors (Median: 0:23,

KNN: 0:33, VAE: 1:04, DAE: 0:52, CF: 1:06). On the medium sized HeLa datasets all models

completed (**Supp. Data. 4**) for the protein groups and 26 out of 27 for the peptides and

precursors. We found that IMPSEQ and BPCA[39] performed best on the 50 homogenous HeLa

samples although some with longer runtimes compared to PIMMS models (e.g. on precursors:

IMPSEQ: 1:09, BPAC: 20:44, MICE-NORM: 4:42). For fewer than 50 samples the PIMMS

models can fit the data, but alternatives were better suited (**Supp. Data 3**). In summary, this

indicated that on an unnormalized, intensity varying dataset (**Supp. Fig. S3a**) from a single

machine the PIMMS models were able to capture patterns between detected features to impute

values for as few as 50 samples with competitive performance to other state-of-the-art methods.

Imputation was consistent across a wide range of intensities

We evaluated the performance across the dynamic range of intensities by binning test

intensities by their feature's training median and reporting the average error per bin for the best

five models. For protein groups on both development datasets the minimal median intensity was

23 for protein groups (**Fig. 2c-d**). The average error for intensities was roughly twice as large for

intensities from the minimum median intensity bin in comparison to the best performance (**Fig.

2e-f**). Interestingly, the worst performance on the large HeLa dataset was observed for protein

groups with the highest observed median intensity, which for intensities from one protein group

had a two to four times worse MAE than the overall MAE. The relative performance between the

models was consistent across the bins. If we compared this to the relative distribution of

imputed intensities (with errors) to the unmodified intensities in the test split, we found that low

intensity values were partly imputed towards the center of the intensity distribution (**Fig. 2g**).

Furthermore, we investigated whether there was a difference in the accuracy of the imputation

based on how often a protein group was observed. Here we found that the MAE varied between

0.6 and 0.8 for proteins observed in 25-80% of the samples, whereas for proteins observed in

more than 80% of the samples the MAE decreased to below 0.4 (**Fig. 2c, e**). We observed a

similar trend when analyzing the smaller dataset of only 50 samples (**Fig. 2d, f**). This indicated

that some protein groups were harder for all the methods to impute than others, but also that the

CF, DAE, and VAE predicted consistently across a wide range of protein groups intensities. We

found similar results for the two other levels of data, aggregated peptides and precursors

(**Supp. Fig. S4**). Finally, we investigated how stable the self-supervised models trained. In a

first step, we randomly permuted all protein groups of the large development dataset, which

leaves the median performance unchanged. Accordingly, training models on randomly

permuted data could not outperform the imputation by the median of the training data split with

an MAE of 1.25 (**Supp. Fig. S5a, Supp. Data 5,** CF: 1.24, VAE: 1.26, KNN_IMPUTE: 1,30

DAE: 1.32). Next, we trained the self-supervised models five times on the same data split as

well as repeated training five times on new splits. The performance between fitted models

varied in a narrow margin (protein groups: CF: 0.538-0.550, DAE: 0.535-0.545, VAE: 0.561-

0.587 [Min-Max]) (**Supp. Fig. S5b,c, Supp. Data 5**). We therefore conclude that the DL models

could be consistently fitted to data and that self-supervised models were able to fit the data

holistically for imputation purposes.

Competitive within-sample and feature-wise between-sample correlation

We evaluated performance without a specific distance measure by evaluating Pearson

correlations of simulated missing values to the truth (**Supp. Fig. S6, Supp. Data 6**). The mean

Pearson correlation between samples for protein groups was a bit higher for BPCA than the

others, including the self-supervised models for the imputations on the large development

dataset (BPCA, DAE: 0.86, CF: 0.85, VAE: 0.84, RF: 0.83, KNN: 0.82, KNN_IMPUTE: 0.77).

The correlation between features within a sample was higher in general, with a mean correlation

of around 0.95 for all models seen among the best along the sorting by the MAE (BPCA, DAE,

CF: 0.96, VAE, RF, KNN: 0.95, KNN_IMPUTE: 0.93). This showed that the ordering within a

sample was better than the correlation of protein groups between samples as the overall

abundance level of single protein groups vary across samples. For the smaller development

dataset we found similar trends of within-sample correlation (IMPSEQ: 0.80, BPCA: 0.80, CF:

0.79, SEQKNN, VAE: 0.78, DAE: 0.76) and between feature sample correlation (IMPSEQ,

BPCA, CF, SEQKNN, VAE: 0.95, MICE-NORM, DAE: 0.94). Both correlation comparisons,

therefore, indicated that the three self-supervised models were able to model the data well

without prior normalization of the data.

Figure 2: Different levels of MS-based proteomics data can be imputed using self-supervised DL models. a)
Performance of best imputation methods at the level of protein groups, aggregated peptides, and precursors for
MaxQuant outputs with 25 percent MNAR. Mean averaged error (MAE) is shown on the y-axis. Blue: KNN (scikit-
learn), green: CF, red: DAE, purple: VAE, olive: BPCA, brown: random forest (missForest), orange:
KNN_IMPUTE(impute), pink: IMPSEQ, dark-orange: MICE-NORM, sand: SEQKNN. The DL methods performed

better or equally good in comparison to other models. Performance was similar for all three models on each data
level and less aggregated data, i.e models on precursors and aggregated peptides performed better compared to
models on protein groups. BPCA and RF did not finish for aggregated peptides and precursors within 24 hours.
Models were ordered by overall performance on the three datasets combining the best five for each. N: number of
samples, M: number of features. **b)** As (a) but showing a decrease in performance for a subset of the data with a
maximum of 50 samples. The CF adapted better to smaller sample sizes. **c,d)** Protein groups medians were binned
by their integer median value and the boxplot of the proportion of missing values per protein group is shown for large
and small development. Number of protein groups in bin in parentheses. **e)** MAE 95% confidence interval for protein
groups intensities in the test split of the larger development dataset binned by the integer value of the protein group's
median intensity in the training data split (4,495 protein groups, 103,902 intensities, models ordered by overall
performance). Models on protein groups with a median intensity above 26 performed in the range of the overall
performance shown in a). **f)** MAE for protein groups in test split of smaller development dataset binned by integer
value of intensity (4,405 protein groups, 9,327 intensities, models ordered by overall performance). **g)** Imputed and
ground truth (observed) intensities for test data on large protein group development dataset for top four overall
models.

Performance of PIMMS on simulated missing values in real use case

To assess the impact of imputation on a large real-world DIA dataset, we applied PIMMS to 455

blood plasma proteomics samples from a cohort of ALD patients and healthy controls[2]. After

imputation we again compared how well PIMMS imputed simulated missing values with a share

of 25 percent MNAR in the ALD data and found that DAE, TRKNN, CF, RF and VAE achieved

similar results of MAE between 0.52-0.55 (**Fig. 3a, Fig. 4a-c, Supp. Data 3**). BPCA which

performed well on the development dataset, was worse with an MAE of 2.95 and took more

than 10 minutes to complete compared to 30 seconds up to just above one minute for the best

models (**Supp. Data 3, 4**). In the original study RSN was used for imputation on a per sample

basis, i.e. using the mean and standard deviation of all protein groups in a sample. This yielded

8 times worse results on the simulated data (**Supp. Data 7**). The correlation across samples for

each protein group was lower for the ALD data in comparison to the heterogeneous

measurements of HeLa cell line data for the self-supervised models (median; DAE: 0.60,

TRKNN: 0.58, CF: 0.54, VAE: 0.53, RF: 0.52) based on 377 protein groups with at least 3

intensities in test data split (**Supp. Data 7**). The median correlation within samples (**Supp. Data**

7) was around 0.98 for all models keeping the order by MAE. This, thus, matched the overall

results from the HeLa data analysis.

Recovering lost differentially abundant protein groups

Then we tested the ability of the self-supervised methods to recover differentially abundant

protein groups. To achieve this, we subset the dataset at a share of 25 percent MNAR and only

kept 80 percent and compared differentially abundant proteins to using the full dataset. We

found that the MAE performance on the simulated missing values with a share of 25 percent

MNAR data were nearly the same compared to the full dataset (**Fig. 3a, b, Supp. Data 3).** This

can be explained by the relatively stable measurements of the dataset (**Supp. Fig. S3b**) and

indicates that most protein groups were stable across patients. Comparing the results of the

differential abundance analysis using the complete dataset compared to the reduced dataset

using no imputations, we observed a decrease in the number of differentially abundant protein

groups from 226 to 212 (ANCOVA, Benjamini-Hochberg multiple testing correction, p-

value≤0.05). Interestingly, we found that besides 17 protein groups losing their differential

abundance, three became differentially abundant by randomly removing data. To assess the

effectiveness of various imputation methods, we used no imputation as a benchmark. We found

that VAE and TRKNN imputation techniques successfully recovered 15 out of the 17 protein

groups that lost their differential abundance (DAE, RF: 14, CF: 13, Median, QRILC: 2) (**Fig.**

3c,e, Supp. Data 8). Three protein groups became differentially abundant without imputation

when intensities were removed in the 80% dataset, which we labeled as false positives to follow

our approach (**Fig. 3d,f**). However, the three protein groups were nearly statistically significantly

abundant in the 100% dataset and therefore adding back patients through imputation to the

analysis can be seen as beneficial. This indicated that the PIMMS models could recover lost

signals with simulated missing data with a share of 25 MNAR.

345
Figure 3: Performance on simulated missing data with 25 percent MNAR in ALD dataset and effects of
imputation on differential analysis. a) Performance for protein groups of plasma proteome data using a share of 25
percent MNAR simulated missing values on the full dataset and **b)** on the 80% dataset using the same configurations
(LD: latent dimension, HL: hidden layer dimension). The performance of best five imputation methods for protein
groups of plasma proteome data using a share of 25 percent MNAR simulated missing values (red: DAE, dark-green:
truncated KNN (TRKNN), green: CF, brown: RF, purple: VAE) **c)** q-values, i.e. multiple testing adjusted p-values, for
17 protein groups which were differentially abundant using the full dataset without imputation, but not for the 80%
dataset without imputation. The gray line indicates the five percent FDR cutoff. No imputation (None) shows the result
without imputing values. **d)** q-values for three protein groups which were differentially abundant using the 80%
dataset without imputation, but not initially when using all data. **e)** Count of false negative (FN) and true positives (TP)
per method on the reduced dataset taking the 17 differentially abundant protein groups from c) on the full dataset as
ground truth. **f)** Same as in e) for three protein groups in d), labeling differentially abundant protein groups in the 80%
dataset as false positives (FP) since they did not show up as differentially abundant in the full dataset. The three
examples are around the FDR cutoff without imputation. True negatives (TN) are not differentially abundant here
(**Supp. Data. 5**). No imputation (None) is the reference defining the labels.

More differentially abundant proteins when using PIMMS

Then we investigated the number of differentially abundant protein groups as well as the ability

of the plasma proteome to predict the fibrosis status of 358 individuals for the top five models,

RSN, QRILC and median imputation (**Supp. Data 9**). The fibrosis status was based on a liver

biopsy, and individuals with all fibrosis scores ranging from zero to four were included. By using

these models for imputation of missing data, leaving the available data as it was, we were able
to perform the analysis for 377 protein groups (ANCOVA, Benjamini-Hochberg multiple testing
correction, p-value≤0.05) compared to only 313 protein groups when using the RSN imputation
approach as originally applied in Niu et. al (2022)[2]. Comparing RSN and VAE we observed that
both methods replaced missing values with a distribution shifted towards the lower abundance
region. However, the maximum intensity for missing values was higher for the VAE with a value
of 21 compared to the RSN with a value of 15 for protein groups (**Supp. Fig. S7**). Translating
the overall shift in distribution by the VAE to the RSN idea, the intensity distribution was shifted
by one standard deviation and the variance was shrunk by 0.7 in comparison to 1.6 standard
deviations and 0.3 shrinkage in the ALD-RSN setup. This difference underlies a fundamental
difference in the approaches and can be generalized for all other models (**Supp. Fig. S7**).
Whereas the RSN always assumes missing values due to low abundance, the VAE and other
approaches assign some missing values a higher intensity if other protein groups in the same
sample suggest that the missing value occurred rather due to a missed detection than low
abundance. QRILC is a more nuanced MNAR method that does not only assign low intensities
for missing values and we therefore added it to the comparison, although it shifts the distribution
more strongly than RSN (**Supp. Fig. S7**).
383
When performing differential analysis, we found that 209 of the 313 protein groups originally
included were significantly differentially expressed using the RSN approach. However, 212 were
significant without any imputation and up to 221 were significant using the other methods
(TRKNN: 221, VAE: 220, DAE, CF: 219, RF: 217, QRILC: 216, Median: 211). Adding the newly
included 64 protein groups, 258 of 377 in the PIMMS-VAE setup were differentially expressed,
an increase by 23% to the originally included and imputed protein groups with RSN (see
Methods and **Supp. Data 9**). We found that using the nine approaches, 287 decisions from the
differential expression analysis were the same for the 313 shared protein groups. We went on
analyzing the 26 differences in detail (**Supp. Data 10**). First, we found that nine of the 26 protein
groups were differentially abundant without imputation. For these nine protein groups RSN
imputation led to non-significant results, whereas the top five models found these nine to be
significant. For the four least significant protein groups without imputation of missing values
QRILC imputation made these significantly abundant. For three protein groups with multiple
testing adjusted p-values (q-values) just above the 0.05 threshold the self-supervised models
and TRKNN imputation led to differential abundance, whereas only Median imputation did not.
399

On one hand when using QRILC imputations six protein groups *IGLV9-49, TTN,*

DEFA1B/DEFA3, PRDX1, ACTA2/ACTG2, SSP2, F7) were significant which none of the other

non-MNAR methods found, with few having extremely diverging q-values. Few relatively non-

prevalent protein groups, i.e. here below 70% prevalence (250/358 and less) of quantified

samples, showed a strong difference in differential analysis testing between e.g. the VAE and

the RSN imputation. The relatively non-prevalent (222/358) protein group

F5H8B0/P08709/P08709-2 associated with the gene *F7* was clearly not significant using the

VAE or no imputation, but passed the statistical thresholds when using QRILC imputation and

leaned towards significance using RSN. On the other hand, a relatively rarely quantified protein

A0A0D9SG88 (gene *CFH*) was significant using VAE imputation, but not RSN or QRILC (**Table**

1, Supp. Data 10). Visualization using swarm plots indicated that the RSN and QRILC

imputation for these two protein groups were shifted downwards of the original center (**Fig. 4d-**

e). In combination with a slight imbalance of targets in the 142 imputed samples, this led to

different results. Similarly, for two newly included protein groups P06702 (gene *S100A9*) and

Q8WUD1/Q8WUD1-2 (gene *RAB2B*) imputation by a fixed median value or QRILC did not lead

to significant results (**Fig. 4f-g, Supp. Data 10**). It could, therefore, be good scientific practice to

check the effect of imputation on differential analysis before a single protein group is selected

for further analysis, especially for explicitly random methods such as RSN.

Finally, expanding the analysis to the 64 additional protein groups included here, we found 16 of

them to be significantly differentially abundant without any imputation and 38 using VAE

imputations (TRKNN: 44, VAE: 38, RF: 34, CF: 33, DAE: 32, QRILC: 19, Median: 14, see **Supp.**

Data 9). Therefore, apart from the difference from the shared protein groups, which yielded 11

more significant hits, imputation using e.g. the VAE allowed us to identify 38 additional protein

groups that were not considered for statistical analysis in the original study.

Protein Group	F5H8B0 P08709 P08709-2	A0A0D9S G88	A0A075B6 R2	P02741	I3L0A1 J3KPA1 P54108 P54108-2 P54108-3	P59665 P59666
Gene	F7	CFH	IGHV4-4	CRP	CRISP3	DEFA1B DEFA3
Q-value						

None (ref.)	0,954	0,117	0,000	0,030	0,018	0,365
DAE	0,916	0,022	0,000	0,038	0,001	0,025
TRKNN	0,470	0,059	0,000	0,029	0,000	0,082
VAE	0,918	0,038	0,000	0,039	0,000	0,023
RF	0,915	0,061	0,000	0,040	0,000	0,061
CF	0,841	0,079	0,000	0,031	0,001	0,022
Median	0,937	0,113	0,000	0,030	0,051	0,373
RSN	0,082	0,951	0,080	0,052	0,745	0,012
QRILC	0,002	0,727	0,003	0,062	0,626	0,029

426 **Table 1. Examples of diverging decisions between imputation methods.** Based on comparison of multiple testing
427 corrected decisions using previously included protein groups. Analysis without imputed values is denoted as None.
428 All see **Supp. Data 10,11**.
429

Robustness of differently abundant protein group identification

Next, we decided to analyze in more detail which protein groups were differentially abundant

using the different models and how reliable the differential outcome was per model. We

repeated the analysis on the ALD data ten times with 25 percent MNAR simulated missing

values, re-training the models on the same training data split. In this scenario median, TRKNN

and RSN imputations were guaranteed to yield the same result for all repetitions. Of the 313

originally included protein groups, 27 did not have the same differently abundant outcome for all

models on all ten repetitions. Especially for protein groups with few missing values, seeing the

same outcome is not unexpected. However, for nine protein groups with two to 29 percent

missing values, adding RSN imputations changed the result from being differentially abundant

without imputation to being not differentially abundant. The results did not change running DAE,

TRKNN, CF, RF and VAE ten times for these nine protein groups. A total of 46 out of the 64

newly included protein groups with a higher percentage of missing values were at least once

differentially abundant by using one of the methods. Of these 46 newly included ones, 16 were

differentially abundant without imputation, which except by median or QRILC imputation was not

changed using the top five model imputations. Additionally, 13 were at least identified seven

times as differentially abundant using DAE, TRKNN, CF, RF or VAE imputations (**Supp. Table**

2). Using CF imputation, we found 17 protein groups to be differentially abundant in all ten

repetitions. Deterministic TRKNN imputation in our setup found 28 protein groups to be

differential abundant ten times. However, ten of these were only found using TRKNN

imputations at least seven times (**Supp. Table 2**). We conclude that there is some variability in

the analysis due to imputations and that for certain imputed protein groups the choice of the

imputation method is crucial.

Novel proteins could be biological relevant

We then investigated if these protein groups could be associated with disease using the

DISEASES database[40] and found that 39 of the 64 novel proteins had an association entry to

fibrosis. Of the 38 at least once newly significant protein groups 30 had an association entry to

fibrosis, with four having a confidence score greater than two (**Supp. Data 11, 13**). For example,

the protein P05362 from gene *ICAM1* had the highest disease-association with a score of 3.3. It

was found to be significantly dysregulated in the liver data and missing in the plasma data in the

original study. Following this reasoning, the second highest scoring protein group was

composed of P01033 and Q5H9A7 (gene *TIMP1*). This indicated that the novel protein groups

using the PIMMS criteria for inclusion could be biologically relevant.

The additionally added protein groups were predictive of fibrosis

Finally, in the work by Niu et al., the authors trained machine learning models to predict clinical

endpoints such as fibrosis from the plasma protein groups. To assess the impact on the

machine learning model, a logistic regression, we used the data from the differential analysis

above. We replicated the workflow performed by Niu et al., and evaluated the model using the

ALD cohort for individuals with histology-based fibrosis staging data available (N=358). Using

minimum redundancy, maximum relevance (MRMR) approach we selected the most predictive

set of features of each subset of features on the assigned training samples[41]. Using median

imputation for all available protein groups yielded the best area under the receiver operating

curve (AUROC) of 0.90 compared to 0.86-0.90 for DAE, TRKNN, CF, RF, QRILC and VAE on

the test samples (**Supp. Fig. S8**). For models trained on only the newly included protein groups

the DAE and VAE model imputation led to the best AUROC using only one protein group

(*TIMP1*) previously mentioned, whereas the model using five median imputed protein groups

was worse (VAE: 0.80, DAE: 0.82, CF: 0.73, RF: 0.79, Median: 0.66, TRKNN: 0.76, QRILC:

0.74). Therefore, this suggests that the additional protein groups were retained with more

missing values when using the PIMMS approach compared to the original study's approach.

Figure 4: Underlying data distribution and performance in detail on an ALD dataset. a) Stacked histogram of

validation and test split using a share of 25 percent MNAR. Bins were created using the integer value of the log2

transformed intensities. N is the number of intensities in the split, each corresponds to 5 percent of all available

quantifications. **b)** Protein groups medians were binned by their integer median value and the boxplot of the

proportion of missing values is shown. The number of protein groups in a bin is in parentheses. **c)** MAE with 95%

confidence interval for protein groups intensities in the test split binned by the integer value of the protein group's

median intensity in the training data split. RF was replaced with QRILC to showcase a MNAR focused method. N:
number of intensities in a bin from test split. **d-g)** Comparison of q-values, i.e. multiple testing adjusted p-values,
based on no imputation (measured) and adding imputations using the models for four protein groups. orange: kleiner
score > 1, blue: kleiner score < 2, crosses in the first column indicate observed values, and dots in other imputation
by models.
492

Discussion

Imputation is an essential step for many analysis types in proteomics, which is often done

heuristically. Here we tested three models using a more holistic approach to imputation. We

showed that CF, DAE and VAE models reached a similar performance on simulated missing

values across the entire distribution of the data - including low abundant features. In comparison

to most other methods they scaled better to high dimensional data or outperformed fast

implementations as scikit-learn based KNN, which was especially beneficial when working with

peptides instead of protein groups to avoid implicit imputations[8]. Further, we investigated the

effect of the imputation method on a concrete analysis, using DIA data from 358 liver patients.

Here we found that missing values were imputed by the models towards the lower end of the

distribution but less pronounced as when using QRILC or RSN imputation which shifts all

replacements towards the limit of detection (LOD) in a sample. We believe that this is due to the

lowest abundant features limiting the learned data distributions (**Supp. Fig. S2**) and that some

features are not set towards the LOD by the model due to being missing at random. We

therefore argue that our holistic model-based imputations are more conservative than e.g. the

RSN imputations and that the three self-supervised DL models offer a sensible approach to

proteomics imputation while scaling well to high feature dimensions. We found that all methods

besides RSN were a better choice for the ALD dataset analyzed.

Simulating 20 percent missing values with a share of 25 percent MNAR we saw the ability to

recover signal by the three semi-supervised models. TRKNN and RF recovered lost signal in

this application, but median imputation and QRILC were too heuristic to recover most of the

signal (**Fig. 3**). However, the analysis also revealed that some protein groups will be false

positives or negatives as removing some observations can change the outcome. This suggests

that imputation using our or other data driven models can recover lost biological signals which is

in line with the observation that significant values were not made insignificant when using data

driven models (DAE, TRKNN, CF, RF, VAE) in comparison to RSN or QRILC on the ALD cohort

(**Fig. 4**). Finally, we offer a workflow to reproduce the comparison done here for all 30 general

imputation methods using any other single tabular data provided by the user.

A limitation of the model-based approach is that the models should only be used for imputation

if the samples are related. Therefore, the best imputation strategy will be dependent on the

experimental setup. We showed that the models can learn to perform imputation on plasma

samples from a diverse set of clinical phenotypes ranging from healthy to liver cirrhosis.

However, the data-driven models would not perform well when imputing for instance one liver

proteome together with ten plasma proteomes. In such a case the data-driven models would not

have any other liver proteomes to learn from. If replicas on a small number of samples are the

study design, KNN interpolation can be a good remedy or using a set of tests which among

others capture missingness[23]. DAE and VAE are not suited to be trained on too few samples,

however the exact cutoff will need to be evaluated on a per dataset basis. CF will by the training

design not be too dependent on the number of samples if trained sufficiently. We showed that

performance is at least competitive with at least 50 samples. In summary, for highly varying

features in a complex experimental setting with many differing samples, a holistic model trained

with all features and potentially additional related samples can capture dependencies between

features - such as the ones implemented in PIMMS.

In general, the modeling approaches here are restricted to the samples in a particular study and

all models are fitted for each new dataset. However, transfer of models between datasets can

be envisioned although a recent study suggested that this brings no benefits[42]. The potential to

fine-tune a model trained on one dataset to a new dataset for a fixed set of features is possible

without further efforts for autoencoders. For CF it would need to find the closest training

samples in the case where samples are separated strictly into train, validation and test set.

However, feature embeddings could be transferred and extended easily. Therefore, all models

could potentially be envisioned in a clinical setup, where models are re-trained with the latest

samples. This could be implemented using similar cohorts, e.g. for the same tissue and similar

patients, which is then the basis to build a database of tissue specific models - or by

incorporating tissue embeddings as an additional source of information. The difficulty in

achieving this will be a stable setup for comparable results without major batch effects due to

sample handling or different instruments. How to approach and the potential for data integration

from different setups is an unresolved issue.

To ensure reproducibility and further extension we offer an evaluation workflow for simulated

MCAR missing values of the entire data distribution and oversampling low abundant intensities

(MNAR) instead of only reporting results on our specific datasets. Everything is available on

GitHub, including the workflows, which allows for additional methods to be added to our

comparisons. This includes comparisons on simulated missing values with varying degrees of

MNAR which can be extended to further holistic models. The potential extensibility of the

workflow allows for comparison of different ideas on different datasets, including the

downstream analysis.

We evaluated imputation on different levels of proteomics features and found that lower-level

data was easier to learn due to being less aggregated[8]. Therefore, it would be great to assess

further if machine learning models can be trained on lower-level data as peptides are the most

sensible unit and imputation on protein groups level performs one form of implicit imputation at

the peptide level[8]. One could assess if imputed features on lower-level data can be

reaggregated to protein groups, e.g using ideas from Sticker and coworkers[43] or MSStats[44].

Additionally, the three self-supervised DL models could also be explored for denoising of

samples, especially the generative VAE, or by adding diffusion models as they are trained by

adding noise to the data[45].

Finally, an interesting application will be single cell proteomics with hundreds of MS runs. This

community in proteomics has not yet developed their own methods to our knowledge, but might

not want to fall back to the ones established for discrete count-based single cell RNA data[46,47]

for intensity based label-free quantified proteomics data without further testing. In conclusion we

suggest that holistic models such as the ones implemented in PIMMS can improve imputation

for proteomics and that our evaluation workflow allows further experimentation leading to more

robust imputation.

580   Methods

Description of the HeLa proteomics dataset

The HeLa cell lines were repeatedly measured as maintenance (MNT) and quality control (QC)

of the mass spectrometers at Novo Nordisk Foundation Center for Protein Research (NNF

CPR) and Max Planck Institute of Biochemistry. The samples were run as QC samples during

the measurement of cohorts or as MNT samples after instrument cleaning and calibration using

different column lengths and liquid chromatography methods. The cells were lysed by different

protocols, which are expected to include digestion using trypsin, but on a per sample basis the

exact protocol was not annotated[48]. The injection volume ranges from one to seven microliter.

Therefore, our dataset contains repeated measures of similar underlying biological samples

acquired using DDA label-free quantification and can be used to explore general questions of

applicability of self-supervised learning to proteomics data.

Description of raw file processing of HeLa proteomics dataset

We used 564 raw files of quality and maintenance runs of HeLa cell lines from a larger set of

7444 quality control and maintenance runs. We processed all of these in a Snakemake[49]

workflow as single runs in MaxQuant 1.6.12[24] yielding single abundances for precursor,

aggregated peptide and protein group intensities using LFQ. As FASTA file the UNIPROT

human reference proteome database 2019_05 release, containing 20,950 canonical and

75,468 additional sequences, was used for the DDA analysis. Contaminants were controlled

using the default contaminants fasta shipped with MaxQuant. From the MaxQuant summary

folder we then used the *evidence.txt* for precursor quantifications, *peptides.txt* for aggregated

peptides and *proteinGroups.txt* for protein groups. The full dataset and detailed pre-processing

steps are explained in a Data Descriptor[35].

Feature selection strategy for quantified runs in general comparison workflow

We applied a two-step procedure for feature and sample selection (**Supp. Fig. S1**). We used a

cutoff of 25% feature prevalence across samples to be included into the workflow. Samples

were then filtered in a second step by their completeness of the selected features. To be

included a sample had to have 50% of the selected features. In order to create train, validation

and test splits, a dataset was split in the long-data view, where a row consists of a sample

name, feature name and its quantification. We divided 90% of the data into training data, 5%

into validation and 5% into the test split, including per default 75% MCAR and 25% MNAR

simulated missing values. This ensured that the validation and test data were representative of

the entire data, while enough low abundant intensities were available for evaluation of features

from the lower range of intensities. The validation cohort was only used for early stopping and

the performance on the validation and test data was therefore expected to be similar. On a few

hundred sample datasets, the number of sampled quantifications for both validation and test

split is quickly in the order of hundred thousand for protein groups and several hundred

thousands for peptide-related measurements.

GALA-ALD dataset

The clinical data consisted of a cohort of patients with liver disease[2]. 457 plasma samples were

measured in data-independent acquisition (DIA) and processed using Spectronaut v.15.4[50] with

the libraries as described in detail by Liu and coworkers[2]. Peptide quantification was extracted

from "PEP.Quantity" - representing the stripped peptide sequence. Data for downstream

analysis was selected with the same two-step procedure as described for the HeLa data. 3,048

aggregated peptides were available in at least 25% of the samples of a total of 4,345

aggregated peptides being present at least once. Protein group quantifications were extracted

from "PG.Quantity", dropping filtered-out values. 377 protein groups were available in at least

25% of the samples of a total of 506 protein groups being present at least once. We used a

fibrosis marker (kleiner[51] score ranging from zero to four, N=358) to compare the effects of

different imputation methods. In the original ALD study the features were further selected based

on QC samples where a maximum coefficient of variation of 0.4 on the non log transformed

quantification per feature was used as cutoff for inclusion. This step was omitted in the

comparison with the original study results in **Fig. 4** as we wanted to have a standardized

workflow applicable also to approaches without interspersed QC samples. In numbers this

means that we retained 313 protein groups instead of 277 omitting the selection criteria on QC

samples. For the differential abundance analysis we had 348 complete clinical samples both

with kleiner score and clinical control measurements we used.

Self-supervised DL models

All models used self supervision as their setup, i.e. the data itself is used as a target in a

prediction task. CF builds on the idea to combine a sample representation with a feature

representation to a target value of interest[52–54]. The simplest implementation is to combine

embedding vectors of equal length using their scalar product to the desired outcome, here the

log intensity value assigned by a proteomics data analysis program. The approach is flexible to

the total number of samples and features, and the model was trained only on the non-missing

features. The loss function is the mean squared error.

A DAE is at inference time a plain autoencoder. During training its input values were partly

masked and needed to be reconstructed. For each mini-batch the error was used to update the

model so that the model learned better to reconstruct the data[55,56]. The loss was the squared

error:

$$L_{reconstruction} = \Sigma_i^{N_B} \quad \Sigma_f^{F_i} \quad \left(I_{f,i}^{pred} - I_{f,i}^{obs}\right)^2$$

where N_B is the number of samples in a batch B, F_i is the number of features not missing in a

sample i and $I_{f,i}$ is the predicted and observed label-free quantification intensity value I of

feature f in sample i. Missing features in a sample, which were not missing due to the training

procedure of masking intensity values, were not used to calculate the loss. VAE introduces a

different objective and models the latent space explicitly, here and as most often done as a

standard normal distribution[57,58]. The latent space of a VAE has two components that are used

for the first part of the loss function, the regularization loss:

$$L_{regularization} = \Sigma_i^{I_B} \quad \Sigma_l^{L} \quad max\left(0, 0.5 * \left\{\mu_{l,i}^z + e^{v_{l,i}^z} - 1 - v_{l,i}^z\right\}\right)$$

662 where $\mu_{l,i}^z$ is the mean and $v_{l,i}^z$ the log variance of dimension l and sample i of the isotropic

663 multivariate Gaussian with L dimensions of the encoder output, i.e. the latent representation z.

664 The reconstruction loss was based assuming a normal distribution for the decoder as output[58,59],

665 leading to

$$L_{reconstruction} = \sum_i^{N_B} \sum_f^{F_i} 0.5\left\{ln(2\pi) + \left[\left(I_{f,i}^{obs} - \mu_{f,i}^I\right)^2\right] + v_{f,i}^I\right\}$$

where N_B, F_i and $I_{f,i}^{obs}$ are as before and $\mu_{f,i}^I$ and log variance of $v_{f,i}^I$ are the parameters of the

isotropic multivariate Gaussian distribution of the decoder outputs, i.e. of the modeled feature

distribution. Training of the VAE was augmented by masking input values as in the denoising

autoencoder[60], although this is not strictly necessary due to the stochastic nature of the latent

space. For inference, missing values are predicted using both the mean of the encoder and

decoder output. The models were developed using a variety of software including numpy

(v.1.20)[61], pandas (v.1.4.)[62,63], pytorch (v.1.10)[64] and fastai (v.2.5)[53].

Other imputation approaches

We used other methods which were available either in scikit-learn or R[14,65]. R or bioconductor

packages were e1071, impute[36], SeqKnn[66], pcaMethods[67], norm, imputeLCMD[8], VIM[68],

rrconNA[69], mice[70], missForest[38], GSimp[71] and msImpute[65] (**Supp. Table 1**), which were

included in a previous comparison[14] except the last one. We did not include non-general

imputation methods as e.g. provided by MSstats[44] or without reusable software[72]. We used KNN

interpolation of replicates based on the HeLa cell line measurements being repeated over time.

The only parameter to set was how many neighboring samples should be used as replicates.

We used three replicates for the scikit-learn[73] based implementation as this was found to be the

best setting by Poulous and coauthors[26], which is also the most widely encountered replication

number used in the field and set as default of both packages we used. However, the R based

implementation of KNN (SEQKNN, TRKNN, KNNIMPUTE) used ten neighbors in NAguideR[14]

and we kept the default. We also used a simple median calculation for each feature across

samples. This requires estimating one parameter per feature. For features that did not vary a

lot, this strategy should yield robust estimates for missing values. We used a random forest

implementation using missForest[38]. The implementation works well for datasets on the protein

group level, but fails for datasets on the peptide and precursor level as these are roughly ten

times higher dimensional. We also included methods which assume MNAR missing values,

such as the random shifted normal (RSN) distribution for imputation or QRLIC[21]. RSN has as

parameters a global mean shift and scaling factor for standard deviation, as well as a mean and

standard deviation for each unit of interest, i.e. all quantified features of a sample or for a

feature all quantification of that feature across samples. Note, that RSN and other MNAR

focused methods assume that measurements are not present as they are below the limit of

detection (LOD). Therefore, in our default setup we sample 25 percent of the simulated missing

values as MNAR into the validation and test data splits to represent the lower range of intensity

values (**Supp. Fig. S9**), aiming to make the methods more comparable. All methods are

available through our workflow and at least one method per included R package is tested via a

GitHub action. Some methods and packages did however not work being called as in NAguideR

for some of our data.

Hyperparameter search using simulated missing values

In order to find good configurations for the self-supervised models a grid search was performed

on three data levels on the development dataset. We sampled simulated missing values

completely at random from the dataset, i.e. 5% for validation and 5% for testing. The training

procedure and architecture of models was refined using the validation data. The performance of

the best performing models on the validation data were then reported using the test data. We

found that test performance metrics matched validation metrics up to the second decimal and

that many model configurations yielded similar results. Performance was compared between the

three self-supervised models to improve performance during model development. In this work

all results were reported based on the simulated missing values in the test data split. Different

latent representation dimension, namely 10, 25, 50, 75 and 100 dimensions were connected to

a varying dimension and composition of hidden layers with a leaky rectified linear activation:

(256), (512), (1024), (2056), (128, 64), (256, 128), (512, 256), (512, 512), (512, 256, 128),

(1024, 512, 256), (128, 128, 128), (256, 256, 128, 128) - for the encoder and inverted for the

decoder. The total number of parameters using these combinations ranged from a couple of

ten-thousands in the case of the CF models to tens of millions for the autoencoder

architectures. We picked the smallest model in terms of parameters of the top 3 performing

ones as their performance was nearly equal on the validation data split. Then we retrained the

best models with a share of 25 percent MNAR simulated missing values. Besides the best

models on all simulated missing values, we reported results using other plots. The intensities in

a split were binned by the median of the feature, e.g. protein group, they originated from based

on the training data split. The MAE per bin was then reported (**Fig. 2e,f**), which allows for

selection of the best models in the intensity range of interest. This is accompanied by a plot

showing the proportion of missing values of a feature based on its median value over samples

(**Fig. 2c,d**). The correlation plots were based on Pearson correlation of predicted intensities and

their original values in the test split. The Pearson correlation was calculated for a feature across

all predictions of all samples, denoted "per feature correlation", or for all predictions within one

sample, denoted "per sample correlation" (**Supp. Fig. S6**).

Evaluation, imputation and differential expression in GALA-ALD dataset

We used the same splitting approach of the data as for the development dataset for evaluation

with a share of 25 percent MNAR. We evaluated using a dimension of ten for CF's sample and

feature embeddings, and the DAE and VAE latent spaces. The autoencoders were composed of

one hidden layer with 64 neurons both for the encoder and decoder, leading to a total number of

parameters between 9,174 and 74,462 for the three models. The RSN imputation for the

missing values in the original ALD study was done on a per sample basis, i.e. mean and

standard deviation for each sample. Using the two-step procedure with defaults as in the

original study, this yielded 313 protein groups for comparison (see ALD data description). Using

a filtering of 25% for feature prevalence prior to imputation with the VAE (**Supp. Fig. S1**) we

increased the share of missing values to 14% for the selected 377 protein groups in comparison

to roughly 5% for the 313 features using the selection approach as in the original study[2]. The

differential analysis was done using an analysis of covariance (ANCOVA) procedure using

statsmodels (v.0.12) and pingouin (v.0.5)[74,75]. We used a linear regression with the original

kleiner score[51] as the stratification variable of interest for the patient's cirrhosis disease stage to

predict protein quantifications, controlling for covariates. Therefore, effects for each protein

group were based on an ANCOVA controlling for age, BMI, gender, steatosis, and abstinence

from alcohol as well as correcting for multiple testing as done in the original study. The multiple

comparison corrections (q-values) were based on 313 protein groups in the original data

imputed using RSN, and on 377 protein groups retained here. Correction for multiple testing

correction was done using Benjamini-Hochberg's correction[76]. The q-values of each DA were

then compared for the overlapping 313 protein groups (**Supp. Data 9-11**).

Machine learning in GALA-ALD dataset

In order to assess the predictive performance of newly retained features, we evaluated a logistic

regression using different feature sets for the binary target of a fibrosis score greater than one

(F2 endpoint in the original study, False: kleiner < 2, True, kleiner ≥ 2). The feature sets were:

First, the features retained using the selection approach with settings as in the ALD study;

second, all features available when using PIMMS selection approach; third, and the difference

between both feature sets termed "new feat". We used maximum relevance, minimum

redundancy using the F-test based implementation, in detail the F-test correlation quotient

(FCQ)[41,77] to select a set of features to be used in the logistic regression. Using cross validation

we selected the best set of up to 15 features for each of the three sub datasets. Then, the

model was retrained on a final 80-20 percent training-testing data split of samples for each

subdataset. Areas under the curve (AUC) for the receiver operation (ROC) and precision recall

(PRC) curves were compared between these three sub datasets. The shown graphs and

reported metrics were calculated on the test split[73,74,78].

Acknowledgements

We would like to acknowledge Rebeca Quinones, Mario Oroshi and John Damm Sørensen for

their huge effort to retrieve all quality and maintenance HeLa raw files for the creation of our

development dataset. Furthermore, we would like to thank Jeppe Madsen and Martin Rykær for

their time and expertise. Lastly, we would like to thank the proteomics groups that have kindly

shared their maintenance and QC HeLa files, both at Novo Nordisk Foundation Center for

Protein Research and at the Proteomics and Signal Transduction department of the MaxPlanck

institute of biochemistry. H.W. was supported by the Novo Nordisk Foundation (grant

NNF19SA0035440). H.W., A.B.N., L.N., M.L-P., M.M, L.J.J. and S.R. were supported by the

Novo Nordisk Foundation grant NNF14CC0001 and S.R. from the Novo Nordisk Foundation

grant NNF21SA0072102.

780 Author contributions

781 S.R. and A.B.N. initiated the study and guided the analysis. M.M. and A.B.N. led the efforts in

782 collecting the data. H.W. assembled the data, performed the analyses and wrote the software

783 choosing the modeling approaches and refining the idea. M.L.P, L.N. and L.J.J. provided

784 guidance and input for the analysis. H.W. and S.R. wrote the manuscript with contributions from

785 all coauthors. All authors read and approved the final version of the manuscript.

786 Data availability

The mass spectrometry proteomics data have been deposited to the ProteomeXchange

Consortium via the PRIDE[79] partner repository with the dataset identifier PXD042233:

ebi.ac.uk/pride/archive/projects/PXD042233. A manuscript[48] describing these data has been

submitted to Scientific Data and is available as a pre-print at doi.org/10.21203/rs.3.rs-

3083547/v2.

The clinical data is not freely available, but can be requested as specified by Niu et. al.[2] : "The

full proteomics datasets and histologic scoring generated and/or analyzed (…) are available (...)

upon request, to Odense Patient Data Exploratory Network (open@rsyd.dk) with reference to

project ID OP_040. Permission to access and analyze data can be obtained following approval

from the Danish Data Protection Agency and the ethics committee for the Region of Southern

Denmark."

Code availability

The PIMMS package and all analysis scripts are available on PyPI and at github.com/RasmussenLab/pimms. The differential analysis and machine learning procedure used on the ALD data is available on PyPI and github at github.com/RasmussenLab/njab.

Competing interest

The authors declare no competing interests.

References

1. Aebersold, R. & Mann, M. Mass-spectrometric exploration of proteome structure and function. *Nature* **537**, 347–355 (2016).

2. Niu, L. *et al.* Noninvasive proteomic biomarkers for alcohol-related liver disease. *Nat. Med.* **28**, 1277–1287 (2022).

3. Francavilla, C. *et al.* Phosphoproteomics of Primary Cells Reveals Druggable Kinase Signatures in Ovarian Cancer. *Cell Rep.* **18**, 3242–3256 (2017).

4. Bader, J. M. *et al.* Proteome profiling in cerebrospinal fluid reveals novel biomarkers of Alzheimer's disease. *Mol. Syst. Biol.* **16**, e9356 (2020).

5. Schoof, E. M. *et al.* Quantitative single-cell proteomics as a tool to characterize cellular hierarchies. *Nat. Commun.* **12**, 3341 (2021).

6. Brunner, A.-D. *et al.* Ultra-high sensitivity mass spectrometry quantifies single-cell proteome changes upon perturbation. *Mol. Syst. Biol.* **18**, e10798 (2022).

7. Mund, A. *et al.* Deep Visual Proteomics defines single-cell identity and heterogeneity. *Nat. Biotechnol.* **40**, 1231–1240 (2022).

8. Lazar, C., Gatto, L., Ferro, M., Bruley, C. & Burger, T. Accounting for the Multiple Natures of Missing Values in Label-Free Quantitative Proteomics Data Sets to Compare Imputation

Strategies. *J. Proteome Res.* **15**, 1116–1125 (2016).

9.   Meier, F. *et al.* Parallel Accumulation-Serial Fragmentation (PASEF): Multiplying

Sequencing Speed and Sensitivity by Synchronized Scans in a Trapped Ion Mobility

Device. *J. Proteome Res.* **14**, 5378–5387 (2015).

10. Meier, F., Geyer, P. E., Virreira Winter, S., Cox, J. & Mann, M. BoxCar acquisition method

enables single-shot proteomics at a depth of 10,000 proteins in 100 minutes. *Nat. Methods*

15, 440–448 (2018).

11. Meier, F., Park, M. A. & Mann, M. Trapped Ion Mobility Spectrometry and Parallel

Accumulation-Serial Fragmentation in Proteomics. *Mol. Cell. Proteomics* **20**, 100138

(2021).

12. Demichev, V., Messner, C. B., Vernardis, S. I., Lilley, K. S. & Ralser, M. DIA-NN: neural

networks and interference correction enable deep proteome coverage in high throughput.

Nat. Methods **17**, 41–44 (2020).

13. Webb-Robertson, B.-J. M. *et al.* Review, evaluation, and discussion of the challenges of

missing value imputation for mass spectrometry-based label-free global proteomics. *J.*

Proteome Res. **14**, 1993–2001 (2015).

14. Wang, S. *et al.* NAguideR: performing and prioritizing missing value imputations for

consistent bottom-up proteomic analyses. *Nucleic Acids Res.* **48**, e83 (2020).

15. Berg, P., McConnell, E. W., Hicks, L. M., Popescu, S. C. & Popescu, G. V. Evaluation of

linear models and missing value imputation for the analysis of peptide-centric proteomics.

BMC Bioinformatics **20**, 102 (2019).

16. Välikangas, T., Suomi, T. & Elo, L. L. A comprehensive evaluation of popular proteomics

software workflows for label-free proteome quantification and imputation. *Brief. Bioinform.*

19, 1344–1355 (2017).

17. Čuklina, J. *et al.* Diagnostics and correction of batch effects in large-scale proteomic

studies: a tutorial. *Mol. Syst. Biol.* **17**, e10240 (2021).

18. Liu, M. & Dongre, A. Proper imputation of missing values in proteomics datasets for

differential expression analysis. *Brief. Bioinform.* **22**, (2021).

19. Harris, L., Fondrie, W. E., Oh, S. & Noble, W. S. Evaluating proteomics imputation methods

with improved criteria. *bioRxiv* 2023.04.07.535980 (2023) doi:10.1101/2023.04.07.535980.

20. Wieczorek, S. *et al.* DAPAR & ProStaR: software to perform statistical analyses in

quantitative discovery proteomics. *Bioinformatics* **33**, 135–136 (2017).

21. Lazar, C. imputeLCMD: a collection of methods for left-censored missing data imputation. *R*

package, version **2**, (2015).

22. Etourneau, L., Fancello, L., Wieczorek, S., Varoquaux, N. & Burger, T. A new take on

missing value imputation for bottom-up label-free LC-MS/MS proteomics. *bioRxiv*

2023.11.09.566355 (2023) doi:10.1101/2023.11.09.566355.

23. Schwämmle, V., Hagensen, C. E., Rogowska-Wrzesinska, A. & Jensen, O. N. PolySTest:

Robust Statistical Testing of Proteomics Data with Missing Values Improves Detection of

Biologically Relevant Features. *Mol. Cell. Proteomics* **19**, 1396–1408 (2020).

24. Tyanova, S., Temu, T. & Cox, J. The MaxQuant computational platform for mass

spectrometry-based shotgun proteomics. *Nat. Protoc.* **11**, 2301–2319 (2016).

25. Bouyssié, D. *et al.* Proline: an efficient and user-friendly software suite for large-scale

proteomics. *Bioinformatics* **36**, 3148–3155 (2020).

26. Poulos, R. C. *et al.* Strategies to enable large-scale proteomics for reproducible research.

Nat. Commun. **11**, 3793 (2020).

27. Nissen, J. N. *et al.* Improved metagenome binning and assembly using deep variational

autoencoders. *Nat. Biotechnol.* **39**, 555–560 (2021).

28. Frazer, J. *et al.* Disease variant prediction with deep generative models of evolutionary

data. *Nature* 1–5 (2021).

29. Buergel, T. *et al.* Metabolomic profiles predict individual multidisease outcomes. *Nat. Med.*

(2022) doi:10.1038/s41591-022-01980-3.

30. Mann, M., Kumar, C., Zeng, W.-F. & Strauss, M. T. Artificial intelligence for proteomics and

biomarker discovery. *Cell Syst* **12**, 759–770 (2021).

31. Bouwmeester, R., Gabriels, R., Van Den Bossche, T., Martens, L. & Degroeve, S. The Age

of Data-Driven Proteomics: How Machine Learning Enables Novel Workflows. *Proteomics*

20, e1900351 (2020).

32. Wen, B. *et al.* Deep Learning in Proteomics. *Proteomics* **20**, e1900335 (2020).

33. Bouwmeester, R., Gabriels, R., Hulstaert, N., Martens, L. & Degroeve, S. DeepLC can

predict retention times for peptides that carry as-yet unseen modifications. *Nat. Methods*

18, 1363–1369 (2021).

34. Wilhelm, M. *et al.* Deep learning boosts sensitivity of mass spectrometry-based

immunopeptidomics. *Nat. Commun.* **12**, 3346 (2021).

35. Webel, H., Perez-Riverol, Y., Nielson, A. B. & Rasmussen, S. Mass spectrometry-based

proteomics data from thousands of HeLa control samples. *Research Square* (2023)

doi:10.21203/rs.3.rs-3083547/v1.

36. Trevor Hastie, Robert Tibshirani, Balasubramanian Narasimhan, Gilbert Chu. *impute*.

(Bioconductor, 2017). doi:10.18129/B9.BIOC.IMPUTE.

37. Troyanskaya, O. *et al.* Missing value estimation methods for DNA microarrays.

Bioinformatics **17**, 520–525 (2001).

38. Stekhoven, D. J. & Bühlmann, P. MissForest--non-parametric missing value imputation for

mixed-type data. *Bioinformatics* **28**, 112–118 (2012).

39. Oba, S. *et al.* A Bayesian missing value estimation method for gene expression profile data.

Bioinformatics **19**, 2088–2096 (2003).

40. Pletscher-Frankild, S., Pallejà, A., Tsafou, K., Binder, J. X. & Jensen, L. J. DISEASES: text

mining and data integration of disease-gene associations. *Methods* **74**, 83–89 (2015).

41. Zhao, Z., Anand, R. & Wang, M. Maximum Relevance and Minimum Redundancy Feature

Selection Methods for a Marketing Machine Learning Platform. *arXiv [stat.ML]* (2019).

42. Rehfeldt, T. G. *et al.* Variability analysis of LC-MS experimental factors and their impact on

machine learning. *Gigascience* **12**, (2023).

43. Sticker, A., Goeminne, L., Martens, L. & Clement, L. Robust Summarization and Inference

in Proteome-wide Label-free Quantification. *Mol. Cell. Proteomics* **19**, 1209–1219 (2020).

44. Kohler, D. *et al.* MSstats Version 4.0: Statistical Analyses of Quantitative Mass

Spectrometry-Based Proteomic Experiments with Chromatography-Based Quantification at

Scale. *J. Proteome Res.* **22**, 1466–1482 (2023).

45. Rombach, R., Blattmann, A., Lorenz, D., Esser, P. & Ommer, B. High-Resolution Image

Synthesis with Latent Diffusion Models. *arXiv [cs.CV]* (2021).

46. van Dijk, D. *et al.* Recovering Gene Interactions from Single-Cell Data Using Data Diffusion.

Cell **174**, 716–729.e27 (2018).

47. Wolf, F. A., Angerer, P. & Theis, F. J. SCANPY: large-scale single-cell gene expression

data analysis. *Genome Biol.* **19**, 15 (2018).

48. Webel, H. HeLa quality control sample preparation for MS-based proteomics. *Protocol*

Exchange (2023) doi:10.21203/rs.3.pex-2155/v1.

49. Mölder, F. *et al.* Sustainable data analysis with Snakemake. *F1000Res.* **10**, 33 (2021).

50. Bruderer, R. *et al.* Extending the Limits of Quantitative Proteome Profiling with Data-

Independent Acquisition and Application to Acetaminophen-Treated Three-Dimensional

Liver Microtissues. *Mol. Cell. Proteomics* **14**, 1400–1410 (2015).

51. Kleiner, D. E. *et al.* Design and validation of a histological scoring system for nonalcoholic

fatty liver disease. *Hepatology* **41**, 1313–1321 (2005).

52. He, X. *et al.* Neural Collaborative Filtering. *arXiv [cs.IR]* (2017)

doi:10.1145/3038912.3052569.

53. Howard, J. & Gugger, S. fastai: A Layered API for Deep Learning. *Information* **11**, (2020).

54. Howard, J. & Gugger, S. *Deep Learning for Coders with fastai and PyTorch: AI Applications*

Without a PhD. 582 (O'Reilly, 2020).

55. Vincent, P., Larochelle, H., Bengio, Y. & Manzagol, P.-A. *Extracting and Composing Robust*

Features with Denoising Autoencoders. (2008).

56. Ca, P. V., Edu, L. T., Lajoie, I., Ca, Y. B. & Ca, P.-A. M. *Stacked Denoising Autoencoders:*

Learning Useful Representations in a Deep Network with a Local Denoising Criterion. vol.

11 3371–3408 http://jmlr.org/papers/v11/vincent10a.html (2010).

57. Kingma, D. P. & Welling, M. An Introduction to Variational Autoencoders. *Foundations and*

Trends® in Machine Learning **12**, 307–392 (2019).

58. Yu, R. A Tutorial on VAEs: From Bayes' Rule to Lossless Compression. *arXiv [cs.LG]*

(2020).

59. Kingma, D. P. & Welling, M. Auto-encoding variational bayes. in *2nd International*

Conference on Learning Representations, ICLR 2014 - Conference Track Proceedings

(International Conference on Learning Representations, ICLR, 2014).

60. Im, D. J., Ahn, S., Memisevic, R. & Bengio, Y. Denoising Criterion for Variational Auto-

Encoding Framework. *arXiv [cs.LG]* 2059–2065 (2015).

61. Harris, C. R. *et al.* Array programming with NumPy. *Nature* **585**, 357–362 (2020).

62. The pandas development team. *pandas-dev/pandas: Pandas*. (2022).

doi:10.5281/zenodo.7093122.

63. Mc Kinney, W. Data Structures for Statistical Computing in Python. in *Proceedings of the*

9th Python in Science Conference (eds. van der Walt, S. & Millman, J.) 56–61 (2010).

64. Paszke, A. *et al.* Pytorch: An imperative style, high-performance deep learning library. *Adv.*

Neural Inf. Process. Syst. **32**, (2019).

65. Hediyeh-Zadeh, S., Webb, A. I. & Davis, M. J. MsImpute: Estimation of Missing Peptide

Intensity Data in Label-Free Quantitative Mass Spectrometry. *Mol. Cell. Proteomics* **22**,

100558 (2023).

66. Kim, K.-Y., Kim, B.-J. & Yi, G.-S. Reuse of imputed data in microarray analysis increases

imputation efficiency. *BMC Bioinformatics* **5**, 160 (2004).

67. Stacklies, W., Redestig, H., Scholz, M., Walther, D. & Selbig, J. pcaMethods--a

bioconductor package providing PCA methods for incomplete data. *Bioinformatics* **23**,

1164–1167 (2007).

68. Kowarik, A. & Templ, M. Imputation with the R Package VIM. *J. Stat. Softw.* **74**, 1–16

(2016).

69. Todorov, V., Templ, M. & Filzmoser, P. Detection of multivariate outliers in business survey

data with incomplete information. *Adv. Data Anal. Classif.* **5**, 37–56 (2011).

70. van Buuren, S. & Groothuis-Oudshoorn, K. mice: Multivariate Imputation by Chained

Equations in R. *J. Stat. Softw.* **45**, 1–67 (2011).

71. Wei, R. *et al.* GSimp: A Gibbs sampler based left-censored missing value imputation

approach for metabolomics studies. *PLoS Comput. Biol.* **14**, e1005973 (2018).

72. Kong, W. *et al.* ProJect: a powerful mixed-model missing value imputation method. *Brief.*

Bioinform. (2023) doi:10.1093/bib/bbad233.

73. Pedregosa, F. *et al.* Scikit-learn: Machine Learning in Python. *J. Mach. Learn. Res.* **12**,

2825–2830 (2011).

74. Vallat, R. Pingouin: statistics in Python. *J. Open Source Softw.* **3**, 1026 (2018).

75. Seabold, S. & Perktold, J. Statsmodels: Econometric and statistical modeling with python.

in *Proceedings of the 9th Python in Science Conference* vol. 57 10–25080 (Austin, TX,

2010).

76. Benjamini, Y. & Hochberg, Y. Controlling the False Discovery Rate: A Practical and

Powerful Approach to Multiple Testing. *J. R. Stat. Soc. Series B Stat. Methodol.* **57**, 289–

300 (1995).

77. Mazzanti, S. *mrmr-selection*. (2022).

78. Seabold, S. & Perktold, J. Statsmodels: Econometric and Statistical Modeling with Python.

9th Python in Science Conference (2010).

79. Perez-Riverol, Y. *et al.* The PRIDE database resources in 2022: a hub for mass

spectrometry-based proteomics evidences. *Nucleic Acids Res.* **50**, D543–D552 (2022).

a)

b) by identified features

c) by identified features